Intertek

Valued Quality. Delivered.

Issuing Laboratory:
Intertek Testing Services Hong Kong Limited

HKAS has accredited this laboratory (HOKLAS 005 – TEST) under HOKLAS for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories.

# TEST REPORT

## Report No.: 14071200HKG-001

## Goldsound Electronic Limited

Application
For
Certification
(Original Grant)
**(FCC ID: RQU-BSS862)**

Transceiver

Prepared and Checked by:

Wong Cheuk Ho, Herbert
Lead Engineer

Approved by:

Chan Chi Hung, Terry
Supervisor
Date: September 01, 2014

- Intertek's standard Terms and Conditions can be obtained at our website http://www.intertek.com/terms/.
- This report shall not be reproduced, except in full.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

# GENERAL INFORMATION

| | |
|---|---|
| Grantee: | Goldsound Electronic Limited |
| Grantee Address: | Room 13, 3/F., Hewlett Centre,<br>54 Hoi Yuen Road, Kwun Tong,<br>Hong Kong. |
| Contact Person: | Raymond Tse |
| Tel: | (852) 2191 2681 |
| Fax: | (852) 2191 3781 |
| e-mail: | N/A |
| Manufacturer: | Goldsound Electronic Manufactory |
| Manufacturer Address: | Building B, C, Tanghuanling Industrial Park,<br>Chashan Town, Dongguan, China. |
| Brand Name: | Goldsound / Memorex / Sylvania / Pyle Vintage |
| Model: | BSS-862, BSS-863, MX5540, SP303,<br>PWPBT-250BK, PWPBT-250YL, PWPBT-250OR |
| Type of EUT: | Transceiver |
| Description of EUT: | Bluetooth Speaker with PLL Radio and USB/SD |
| Serial Number: | N/A |
| FCC ID: | RQU-BSS862 |
| Date of Sample Submitted: | July 29, 2014 |
| Date of Test: | July 29, 2014 to August 20, 2014 |
| Report No.: | 14071200HKG-001 |
| Report Date: | September 01, 2014 |
| Environmental Conditions: | Temperature: +10 to 40°C<br>Humidity: 10 to 90% |



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

Valued Quality. Delivered.

Issuing Laboratory:
Intertek Testing Services Hong Kong Limited
HKAS has accredited this laboratory (HOKLAS 005 – TEST) under HOKLAS for specific laboratory activities as listed in the HOKLAS directory of accredited laboratories.

HOKLAS 005 TEST

## SUMMARY OF TEST RESULT

| TEST SPECIFICATION | REFERENCE | RESULTS |
|---|---|---|
| Transmitter Power Line Conducted Emissions | 15.207 | Pass |
| Radiated Emission<br>Radiated Emission on the Bandedge | 15.249 | Pass |
| Radiated Emission in Restricted Bands | 15.205 | Pass |

The equipment under test is found to be complying with the following standards:
FCC Part 15, October 1, 2012 Edition

Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the pervisions of this section.
2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

## Table of Contents

1.0 **General Description** ..... 1
1.1 Product Description ..... 1
1.2 Related Submittal(s) Grants ..... 1
1.3 Test Methodology ..... 2
1.4 Test Facility ..... 2

2.0 **System Test Configuration** ..... 3
2.1 Justification ..... 3
2.2 EUT Exercising Software ..... 3
2.3 Special Accessories ..... 3
2.4 Measurement Uncertainty ..... 3
2.5 Support Equipment List and Description ..... 4

3.0 **Emission Results** ..... 5
3.1 Field Strength Calculation ..... 5
3.2 Radiated Emission Configuration Photograph ..... 6
3.3 Radiated Emission Data ..... 6
3.4 Conducted Emission Configuration Photograph ..... 6
3.5 Conducted Emission Data ..... 6

4.0 **Equipment Photographs** ..... 12

5.0 **Product Labelling** ..... 12

6.0 **Technical Specifications** ..... 12

7.0 **Instruction Manual** ..... 12

8.0 **Miscellaneous Information** ..... 13
8.1 Radiated Emission on the Bandedge ..... 13
8.2 Discussion of Pulse Desensitization ..... 16
8.3 Calculation of Average Factor ..... 16
8.4 Emissions Test Procedures ..... 17

9.0 **Equipment List** ..... 19



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

# 1.0 General Description

## 1.1 Product Description

The Equipment Under Test (EUT) is a Bluetooth Speaker with PLL Radio and USB/SD. The EUT is using adaptive frequency hopping for Bluetooth module. The Bluetooth portion is operating between 2402MHz and 2480MHz (79 channels with 1MHz channel spacing). When the EUT is switched ON in Bluetooth mode, the display will show “BT” and a LED flashing. The Bluetooth enabled device would be searched and connected the EUT before playing audio. After pairing, the “BT” LED will stay lit. The audio signal will be amplified and fed to internal stereo loudspeaker. The EUT also have FM radio and playback MP3 function. A LED display acts as the visual interface. The EUT is powered by 12V DC from an AC/DC adaptor and/or eight size C batteries (1.5VDC). The AC/DC adaptor can accept 100-240VAC. A USB port (5VDC) is for charging purpose and playback MP3 from USB drive only. A SD card slot is for playback MP3 from SD Card only. The Aux port is for playback MP3 from MP3 device only.

The Model: BSS-863, MX5540, SP303, PWPBT-250BK, PWPBT-250YL and PWPBT-250OR are the same as the Model: BSS-862 in hardware aspect. The difference in color, cosmetic details, model number and brand name serves as marketing strategy.

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

## 1.2 Related Submittal(s) Grants

This is a single application for certification of a transceiver.



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

## 1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009). All radiated measurements were performed in an Open Area Test Site. Preliminary scans were performed in the Open Area Test Site only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the **"Justification Section"** of this Application.

## 1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong. This test facility and site measurement data have been placed on file with the FCC.



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

## 2.0 System Test Configuration

### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2009).

The device was powered by 120VAC adaptor and/or eight Size C alkaline battery (1.5V).

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

### 2.2 EUT Exercising Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use.

### 2.3 Special Accessories

(1)AC/DC Adaptor with ferrite
(Model: AS360-120-AA200, Brand: KINGWALL, Input: 100-240VAC 50/60Hz, Output: 12.0VDC 2.0A)

### 2.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

## 2.5 Support Equipment List and Description

(1) Iphone 5, Model: MD297, FCC ID:BCG-E2599A(Supplied by Intertek)
(2) Ipod Nano, Model:A1446, FCC ID:BCG-A1446A(Supplied by Intertek)
(3) USB thumbdrive (Supplied by Intertek)
(4) SD card (Supplied by Intertek)
(5) Aux cable with 1meter long (Supplied by Intertek)
(6) 8xAlkaline battery (1.5V)



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

## 3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

### 3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CF - AG - AV

where FS = Field Strength in dBµV/m
RA = Receiver Amplitude (including preamplifier) in dBµV
CF = Cable Attenuation Factor in dB
AF = Antenna Factor in dB
AG = Amplifier Gain in dB
AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

FS = RR + LF

where FS = Field Strength in dBµV/m
RR = RA - AG - AV in dBµV
LF = CF + AF in dB

Assume a receiver reading of 52.0 dBµV is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 32 dBµV/m. This value in dBµV/m was converted to its corresponding level in µV/m.

RA = 52.0 dBµV/m
AF = 7.4 dB
CF = 1.6 dB
AG = 29.0 dB
AV = 5.0 dB
RR = 18.0 dBµV
LF = 9.0 dB
FS = RR + LF
FS = 18 + 9 = 27 dBµV/m

Level in µV/m = Common Antilogarithm [(27 dBµV/m)/20] = 22.4 µV/m



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 33.870 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 7.8 dB

3.4 Conducted Emission Configuration Photograph

The worst case in line-conducted emission was found at 0.456 MHz

For electronic filing, the worst case line-conducted configuration photographs are saved with filename: conducted photo.pdf.

3.5 Conducted Emission Data

For electronic filing, the graph and data table of conducted emission is saved with filename: conducted.pdf.

Judgment: Pass by 8.55 dB



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

## Worst-Case Operating Mode: Transmitting (Bluetooth)




| EDIT PEAK LIST (Final Measurement Results) | | | |
|---|---|---|---|
| Trace1: | CF15MQP | | |
| Trace2: | CF15MAV | | |
| Trace3: | --- | | |
| TRACE | FREQUENCY | LEVEL dBµV | DELTA LIMIT dB |
| 1 Quasi Peak | 150 kHz | 43.40 N | -22.59 |
| 1 Quasi Peak | 213 kHz | 38.34 N | -24.74 |
| 1 Quasi Peak | 379.5 kHz | 38.28 L1 | -20.00 |
| 2 CISPR Average | 393 kHz | 30.29 L1 | -17.70 |
| 1 Quasi Peak | 456 kHz | 48.20 L1 | -8.55 |
| 2 CISPR Average | 456 kHz | 36.10 L1 | -10.66 |
| 1 Quasi Peak | 748.5 kHz | 35.33 N | -20.67 |
| 1 Quasi Peak | 834 kHz | 36.16 L1 | -19.83 |
| 2 CISPR Average | 856.5 kHz | 26.19 L1 | -19.80 |
| 1 Quasi Peak | 1.221 MHz | 36.82 L1 | -19.17 |
| 2 CISPR Average | 1.2615 MHz | 25.94 L1 | -20.05 |
| 1 Quasi Peak | 1.842 MHz | 34.52 L1 | -21.47 |
| 1 Quasi Peak | 2.1885 MHz | 34.86 L1 | -21.13 |
| 1 Quasi Peak | 3.1065 MHz | 32.52 N | -23.47 |
| 1 Quasi Peak | 4.65 MHz | 29.78 N | -26.22 |



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

Applicant: Goldsound Electronic Limited Date of Test: August 20, 2014
Model: BSS-862
Worst-Case Operating Mode: Transmitting (Bluetooth)

Table 1

**Radiated Emissions**
**Pursuant to FCC Part 15 Section 15.249 Requirement**

Lowest Channel

| Polari-zation | Frequency (MHz) | Reading (dBµV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Peak (dBµV/m) | Average Factor (dB) | Calculated at 3m (dBµV/m) | Average Limit at 3m (dBµV/m) | Margin (dB) |
|---|---|---|---|---|---|---|---|---|---|
| V | 2402.000 | 89.1 | 33 | 29.4 | 85.5 | 24 | 61.5 | 94.0 | -32.5 |
| ***V*** | ***4804.000*** | ***47.6*** | ***33*** | ***34.9*** | ***49.5*** | ***24*** | ***25.5*** | ***54.0*** | ***-28.5*** |
| V | 7206.000 | 45.1 | 33 | 37.9 | 50.0 | 24 | 26.0 | 54.0 | -28.0 |
| V | 9608.000 | 46.1 | 33 | 40.4 | 53.5 | 24 | 29.5 | 54.0 | -24.5 |
| ***V*** | ***12010.000*** | ***49.4*** | ***33*** | ***40.5*** | ***56.9*** | ***24*** | ***32.9*** | ***54.0*** | ***-21.1*** |
| V | 14412.000 | 53.4 | 33 | 40.0 | 60.4 | 24 | 36.4 | 54.0 | -17.6 |

| Polari-zation | Frequency (MHz) | Reading (dBµV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Peak (dBµV/m) | Peak Limit at 3m (dBµV/m) | Margin (dB) |
|---|---|---|---|---|---|---|---|
| V | 2402.000 | 89.1 | 33 | 29.4 | 85.5 | 114.0 | -28.5 |
| ***V*** | ***4804.000*** | ***47.6*** | ***33*** | ***34.9*** | ***49.5*** | ***74.0*** | ***-24.5*** |
| V | 7206.000 | 45.1 | 33 | 37.9 | 50.0 | 74.0 | -24.0 |
| V | 9608.000 | 46.1 | 33 | 40.4 | 53.5 | 74.0 | -20.5 |
| ***V*** | ***12010.000*** | ***49.4*** | ***33*** | ***40.5*** | ***56.9*** | ***74.0*** | ***-17.1*** |
| V | 14412.000 | 53.4 | 33 | 40.0 | 60.4 | 74.0 | -13.6 |

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

5. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205.



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

Applicant: Goldsound Electronic Limited Date of Test: August 20, 2014
Model: BSS-862
Worst-Case Operating Mode: Transmitting (Bluetooth)

Table 2

**Radiated Emissions**
**Pursuant to FCC Part 15 Section 15.249 Requirement**

Middle Channel

| Polari-zation | Frequency (MHz) | Reading (dBµV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Peak (dBµV/m) | Average Factor (dB) | Calculated at 3m (dBµV/m) | Average Limit at 3m (dBµV/m) | Margin (dB) |
|---|---|---|---|---|---|---|---|---|---|
| V | 2440.000 | 88.9 | 33 | 29.4 | 85.3 | 24 | 61.3 | 94.0 | -32.7 |
| ***V*** | ***4880.000*** | ***48.4*** | ***33*** | ***34.9*** | ***50.3*** | ***24*** | ***26.3*** | ***54.0*** | ***-27.7*** |
| ***V*** | ***7320.000*** | ***45.5*** | ***33*** | ***37.9*** | ***50.4*** | ***24*** | ***26.4*** | ***54.0*** | ***-27.6*** |
| V | 9760.000 | 46.3 | 33 | 40.4 | 53.7 | 24 | 29.7 | 54.0 | -24.3 |
| ***V*** | ***12200.000*** | ***49.3*** | ***33*** | ***40.5*** | ***56.8*** | ***24*** | ***32.8*** | ***54.0*** | ***-21.2*** |
| V | 14640.000 | 55.3 | 33 | 38.4 | 60.7 | 24 | 36.7 | 54.0 | -17.3 |

| Polari-zation | Frequency (MHz) | Reading (dBµV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Peak (dBµV/m) | Peak Limit at 3m (dBµV/m) | Margin (dB) |
|---|---|---|---|---|---|---|---|
| V | 2440.000 | 88.9 | 33 | 29.4 | 85.3 | 114.0 | -28.7 |
| ***V*** | ***4880.000*** | ***48.4*** | ***33*** | ***34.9*** | ***50.3*** | ***74.0*** | ***-23.7*** |
| ***V*** | ***7320.000*** | ***45.5*** | ***33*** | ***37.9*** | ***50.4*** | ***74.0*** | ***-23.6*** |
| V | 9760.000 | 46.3 | 33 | 40.4 | 53.7 | 74.0 | -20.3 |
| ***V*** | ***12200.000*** | ***49.3*** | ***33*** | ***40.5*** | ***56.8*** | ***74.0*** | ***-17.2*** |
| V | 14640.000 | 55.3 | 33 | 38.4 | 60.7 | 74.0 | -13.3 |

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

5. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205.



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

Applicant: Goldsound Electronic Limited Date of Test: August 20, 2014
Model: BSS-862
Worst-Case Operating Mode: Transmitting (Bluetooth)

Table 3

**Radiated Emissions**
**Pursuant to FCC Part 15 Section 15.249 Requirement**

Highest Channel

| Polari-zation | Frequency (MHz) | Reading (dBµV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Peak (dBµV/m) | Average Factor (dB) | Calculated at 3m (dBµV/m) | Average Limit at 3m (dBµV/m) | Margin (dB) |
|---|---|---|---|---|---|---|---|---|---|
| V | 2480.000 | 89.3 | 33 | 29.4 | 85.7 | 24 | 61.7 | 94.0 | -32.3 |
| ***V*** | ***4960.000*** | ***47.7*** | ***33*** | ***34.9*** | ***49.6*** | ***24*** | ***25.6*** | ***54.0*** | ***-28.4*** |
| ***V*** | ***7440.000*** | ***45.7*** | ***33*** | ***37.9*** | ***50.6*** | ***24*** | ***26.6*** | ***54.0*** | ***-27.4*** |
| V | 9920.000 | 45.8 | 33 | 40.4 | 53.2 | 24 | 29.2 | 54.0 | -24.8 |
| ***V*** | ***12400.000*** | ***49.4*** | ***33*** | ***40.5*** | ***56.9*** | ***24*** | ***32.9*** | ***54.0*** | ***-21.1*** |
| V | 14880.000 | 46.4 | 33 | 38.4 | 51.8 | 24 | 27.8 | 54.0 | -26.2 |

| Polari-zation | Frequency (MHz) | Reading (dBµV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m - Peak (dBµV/m) | Peak Limit at 3m (dBµV/m) | Margin (dB) |
|---|---|---|---|---|---|---|---|
| V | 2480.000 | 89.3 | 33 | 29.4 | 85.7 | 114.0 | -28.3 |
| ***V*** | ***4960.000*** | ***47.7*** | ***33*** | ***34.9*** | ***49.6*** | ***74.0*** | ***-24.4*** |
| ***V*** | ***7440.000*** | ***45.7*** | ***33*** | ***37.9*** | ***50.6*** | ***74.0*** | ***-23.4*** |
| V | 9920.000 | 45.8 | 33 | 40.4 | 53.2 | 74.0 | -20.8 |
| ***V*** | ***12400.000*** | ***49.4*** | ***33*** | ***40.5*** | ***56.9*** | ***74.0*** | ***-17.1*** |
| V | 14880.000 | 46.4 | 33 | 38.4 | 51.8 | 74.0 | -22.2 |

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

5. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205.



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

Applicant: Goldsound Electronic Limited Date of Test: August 20, 2014
Model: BSS-862
Worst-Case Operating Mode: Transmitting (music play via Bluetooth)

Table 4

**Radiated Emissions**
**Pursuant to FCC Part 15 Section 15.209 Requirement**

| Polarization | Frequency (MHz) | Reading (dBµV) | Pre-amp (dB) | Antenna Factor (dB) | Net at 3m (dBµV/m) | Limit at 3m (dBµV/m) | Margin (dB) |
|---|---|---|---|---|---|---|---|
| V | 33.870 | 38.2 | 16 | 10.0 | 32.2 | 40.0 | -7.8 |
| V | 143.996 | 30.2 | 16 | 14.0 | 28.2 | 43.5 | -15.3 |
| H | 155.996 | 30.8 | 16 | 16.0 | 30.8 | 43.5 | -12.7 |
| H | 179.996 | 24.7 | 16 | 20.0 | 28.7 | 43.5 | -14.8 |
| H | 191.995 | 30.4 | 16 | 16.0 | 30.4 | 43.5 | -13.1 |
| H | 307.200 | 24.5 | 16 | 23.0 | 31.5 | 46.0 | -14.5 |
| H | 528.400 | 24.0 | 16 | 27.0 | 35.0 | 46.0 | -11.0 |
| H | 620.883 | 22.6 | 16 | 29.0 | 35.6 | 46.0 | -10.4 |

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205.



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

## 4.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

## 5.0 Product Labelling

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

## 6.0 Technical Specifications

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

## 7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

## 8.0 Miscellaneous Information

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor (calculation and timing diagram).

### 8.1 Radiated Emission on the Bandedge

From the following plots, they show that the fundamental emissions are confined in the specified band (2400MHz to 2483.5MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.4 (2009) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com









**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

Peak Measurement

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

Lower bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

=85.5 dBµV/m - 44.2 dB
=41.3 dBµV/m

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

=61.5 dBµV/m - 44.2 dB
=17.3 dBµV/m

Upper bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

=85.7 dBµV/m - 34.4 dB
=51.3 dBµV/m

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

=61.7 dBµV/m - 34.4 dB
=27.3 dBµV/m

The resultant field strength meets the general radiated emission limit in Section 15.209, which does not exceed 74 dBµV/m (Peak Limit) and 54 dBµV/m (Average Limit).



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

## 8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period (Teff) is approximately 0.625ms for a digital "1" bit which illustrated on technical specification, with a resolution bandwidth (3dB) of 1MHz, so the pulse desensitivity factor is 0dB.

## 8.3 Calculation of Average Factor

Based on the Bluetooth Specification Version 3.0 + EDR, the transmitter ON time for each timeslot of Bluetooth is 625μs. DH5 has the maximum duty cycle, which consists of 5 continuous Tx slots and 1 Rx slot. Therefore one hopset take (5+1) x 625μs = 3.75ms. For one period for a pseudo-random hopping through at least 20 RF channels in adaptive mode (worse case), it take: 20 x 3.75ms = 75ms.

The dwell time for DH5 is 5 x 625μs = 3.125ms.

For the worst case calculation, there are two transmissions might occur in 100ms. Therefore,

Duty Cycle (DC) = Maximum On time in 100ms/100ms
= 3.125ms x 2/100ms
= 0.0625

Average Factor (AF) of Bluetooth in dB = $20 \log_{10} (0.0625)$
= -24 dB



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

## 8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 150 kHz to 30 MHz.



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.4 (2009).

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

## 10.0 **Equipment List**

1) Radiated Emissions Test

| Equipment | EMI Test Receiver | Biconical Antenna | Log Periodic Antenna |
|---|---|---|---|
| Registration No. | EW-2666 | EW-0571 | EW-0572 |
| Manufacturer | R&S | EMCO | EMCO |
| Model No. | ESCI7 | 3104C | 3146 |
| Calibration Date | Jun. 20, 2013 | Nov. 01, 2013 | Jun. 26, 2013 |
| Calibration Due Date | Sep. 20, 2014 | May 01, 2015 | Dec. 26, 2014 |

| Equipment | Spectrum Analyzer | Pyramidal Horn Antenna | Double Ridged Guide Antenna |
|---|---|---|---|
| Registration No. | EW-2253 | EW-0905 | EW-1015 |
| Manufacturer | R&S | EMCO | EMCO |
| Model No. | FSP40 | 3160-09 | 3115 |
| Calibration Date | May 08, 2014 | Jan. 28, 2014 | Mar. 05, 2013 |
| Calibration Due Date | May 08, 2015 | Jul. 28, 2015 | Sep. 05, 2014 |

2) Conducted Emissions Test

| Equipment | EMI Test Receiver | LISN |
|---|---|---|
| Registration No. | EW-2251 | EW-2501 |
| Manufacturer | R&S | R&S |
| Model No. | ESCI | ENV-216 |
| Calibration Date | Nov. 20, 2013 | Dec. 25, 2013 |
| Calibration Due Date | Nov. 20, 2014 | Nov. 30, 2014 |

3) Bandedge Measurement

| Equipment | Spectrum Analyzer |
|---|---|
| Registration No. | EW-2329 |
| Manufacturer | R&S |
| Model No. | FSP3 |
| Calibration Date | Jun. 19, 2014 |
| Calibration Due Date | Jun. 19, 2015 |

END OF TEST REPORT



**Intertek Testing Services Hong Kong Ltd.**
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com