

FCC TEST REPORT

Report No: AB26080213FW02
FCC ID.....: **RSN-FULTRA5G**
Applicant.....: Cellphone-Mate Inc. dba SureCall
Address.....: 48346 Milmont Drive, Fremont, California 94538, United States
Manufacturer.....: Cellphone-Mate Inc. dba SureCall
Address.....: 48346 Milmont Drive, Fremont, California 94538, United States
Product Name.....: Broadband Consumer Signal Booster
Trade Mark.....: Surecall
Test Model: Fusion Ultra 5G
Additional Model(s).....: /
Standard.....: FCC Part 2 (Section 2.1091);KDB 447498 D01;IEEE C95.1
Date of Receipt.....: Jun. 10, 2026
Date of Test Date.....: Jun. 10, 2026 - Aug. 09, 2026
Date of Issue.....: Aug. 10, 2026
Test Result.....: Pass

Compiled by:
(Printed Name + Signature)

Huajie Li

Huajie Li

Supervised by:
(Printed Name + Signature)

David Huang

David Huang

Approved by:
(Printed Name + Signature)

Jay Liu

Jay Liu

Testing Laboratory Name.....: Aibo Standard Technology (Shenzhen) Co., Ltd.

Address : 101, Building B, Tuori New Energy Industrial Park, High-tech Park, Tianliao Community, Yutang Street, Guangming District, Shenzhen City, Guangdong Province, China

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by Aibo. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to Aibo within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit. The test report merely correspond to the test sample.

FCC TEST REPORT

EUT.....	: Broadband Consumer Signal Booster
Test Model.....	: Fusion Ultra 5G
Applicant.....	: Cellphone-Mate Inc. dba SureCall
Address.....	: 48346 Milmont Drive, Fremont, California 94538, United States
Manufacturer.....	: Cellphone-Mate Inc. dba SureCall
Address.....	: 48346 Milmont Drive, Fremont, California 94538, United States

Test Result	Positive
--------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

REPORT VERSION

Version No.	Issue Date	Description
01	2026.08.10	Initial Issue

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1. GENERAL DESCRIPTION OF EUT	4
1.2. DESCRIPTION OF TEST FACILITY	5
2. RF EXPOSURE EVALUATION	6
2.1 LIMIT	6
2.2 EVALUATION RESULT	7

1. GENERAL INFORMATION

1.1. GENERAL DESCRIPTION OF EUT

Product Name:	Broadband Consumer Signal Booster		
Trade Mark:	Surecall		
Test Model:	Fusion Ultra 5G		
Additional Model(s):	/		
Model Difference:	/		
Hardware Version:	Fusion Ultra 5G V1.1.0		
Software Version:	Fusion Ultra 5G V1.1.0		
Power Supply:	AC 100-240V, 50/60Hz, 1.2A		
Test Sample(s) Number:	ABA166260804-S006		
Radio Specification Subject to this Report			
Signal Booster Type:	Fixed Consumer Signal Booster		
Frequency Range:	PCS	Uplink:	1850MHz - 1915MHz
		Downlink:	1930MHz - 1995MHz
	AWS	Uplink:	1710MHz - 1755MHz
		Downlink:	2110MHz - 2155MHz
	Cellular	Uplink:	824MHz - 849MHz
		Downlink:	869MHz - 894MHz
	Lower700M Hz	Uplink:	698MHz - 716MHz
		Downlink:	728MHz - 746MHz
	Upper700M Hz	Uplink:	776MHz - 787MHz
		Downlink:	746MHz - 757MHz
Emission Designator:	F9W, G7D, G7W, GXW, W7D		
FCC Classification:	B2W/Wideband Consumer Booster (CMRS)		
Antenna information:	Refer to the Antenna kitting		

1.2. DESCRIPTION OF TEST FACILITY

Test Lab: Aibo Standard Technology (Shenzhen) Co., Ltd.

Address: 101, Building B, Tuori New Energy Industrial Park, High-tech Park, Tianliao Community, Yutang Street, Guangming District, Shenzhen City, Guangdong Province, China

Tel.: +(86) 0755 85250797

E-mail: aibo@aibonorm.com

Website: www.aibonorm.com

The test facility is recognized, certified, or accredited by the following organizations:

A2LA-Lab Certificate No.: 7514.01

Aibo Standard Technology (Shenzhen) Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC Accredited Lab.

Designation Number: CN1411

Test Firm Registration Number: 567066

ISED Wireless Device Testing Laboratories

CAB identifier: CN0185

2. RF EXPOSURE EVALUATION

2.1 Limit

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm², P_{out} = output power to antenna in mW;

G = gain of antenna in linear scale, $\pi = 3.1416$;

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

2.2 Evaluation Result

Operation Bands	Frequency (MHz)	Max. Output power(dBm)	Cable loss (dB)	Power to Antenna(mW)	Antenna gain	
					Isotropic	Numeric
UL1850-1915	1883.15	22.93	7.62	33.96	14.5	28.18
UL1710-1755	1723.16	22.78	7.25	35.73	14	25.12
UL824-849	834.00	25.81	5.62	104.47	7	5.01
UL698-716	709.48	23.19	5.42	59.84	7	5.01
UL776-787	779.50	24.89	5.42	88.51	7	5.01
DL1930-1995	1955.61	15.98	6.17	9.57	7	5.01
DL2110-2155	2139.26	16.51	6.54	9.93	7	5.01
DL869-894	875.65	15.17	4.41	11.91	6	3.98
DL728-746	742.36	15.87	4.22	14.62	5	3.16
DL746-757	749.04	16.11	4.22	15.45	5	3.16

Operation Bands	Power (mW)	Antenna gain(G)	Measure Distance(cm)	Power density (mW/cm ²)	MPE limit (mW/cm ²)
UL1850-1915	33.96	28.18	40	0.0476	1
UL1710-1755	35.73	25.12	40	0.0446	1
UL824-849	104.47	5.01	40	0.0260	0.56
UL698-716	59.84	5.01	40	0.0149	0.47
UL776-787	88.51	5.01	40	0.0221	0.52
DL1930-1995	9.57	5.01	40	0.0024	1
DL2110-2155	9.93	5.01	40	0.0025	1
DL869-894	11.91	3.98	40	0.0024	0.58
DL728-746	14.62	3.16	40	0.0023	0.49
DL746-757	15.45	3.16	40	0.0024	0.50

Simultaneous Transmission with BLE (FCC ID: 2ATPO-PB03), Simultaneous Transmission with IOT (FCC ID: 2AJYU-8VC0002), and the RF exposure evaluation is as follow:

Operation Bands	Frequency (MHz)	Max. Output power(dBm)	Cable loss (dB)	Power to Antenna(mW)	Antenna gain	
					Isotropic	Numeric
BLE	2402	7.59	0	5.74	1.5	1.41
IOT 1850-1910	1850	23.37	7.62	37.58	14.5	28.18
IOT 1710-1755	1710	21.92	7.25	29.31	14	25.12
IOT 824-849	824	23.41	5.62	60.12	7	5.01
IOT 699-716	699	23.31	5.42	61.52	7	5.01
IOT 777-787	777	20.76	5.42	34.20	7	5.01

Operation Bands	Power (mW)	Antenna gain(G)	Measure Distance(cm)	Power density (mW/cm ²)	MPE limit (mW/cm ²)
BLE	5.74	1.41	40	0.0004	1
IOT 1850-1910	37.58	28.18	40	0.0527	1
IOT 1710-1755	29.31	25.12	40	0.0366	1
IOT 824-849	60.12	5.01	40	0.0150	0.55
IOT 699-716	61.52	5.01	40	0.0153	0.47
IOT 777-787	34.20	5.01	40	0.0085	0.52

Operation Bands	Result	Limit
BLE + IOT + UL1850-1915	0.1007	1
BLE + IOT + UL1710-1755	0.0977	1
BLE + IOT + UL824-849	0.0995	1
BLE + IOT + UL698-716	0.0848	1
BLE + IOT + UL776-787	0.0956	1
BLE + IOT + DL1930-1995	0.0555	1
BLE + IOT + DL2110-2155	0.0556	1
BLE + IOT + DL869-894	0.0572	1
BLE + IOT + DL728-746	0.0578	1
BLE + IOT + DL746-757	0.0579	1

Results: PASS

So a SAR test is not required

*****THE END*****