

1. FCC § 1.1307 (b) (1)& § 2.1091–RF EXPOSURE

1.1 Applicable Standard

According to § 1.1310 and § 2.1091 (Mobile Devices) RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Power Density (mW/cm ²)
Limits for General Population/Uncontrolled Exposure	
0.3-1.34	*(100)
1.34-30	*(180/f ²)
30-300	0.2
300 – 1,500	f/1500
1,500 – 100,000	1

Note: f= frequency in MHz

*=Plane-wave equivalent power density

1.2 MPE Prediction

1.2.1 Calculation of MPE at 20 cm distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG / 4 \pi R^2$$

Where: S=power density

P=power input to antenna

G= maximum power gain of the antenna in the direction of interest relative to an isotropic radiator, subtract antenna's cable loss, (result is in numeric form)

R=distance to the center of radiation of the antenna (20cm in the following calculation)

1.2.2 Calculation formula of G (numeric)

$$G(\text{numeric}) = 10^{\frac{\{\text{Maximum Antenna Gain (dBi)} - \text{Cable Loss (dB)}\}}{10}}$$

Where: G (numeric) = Maximum power gain of the antenna in the direction of interest relative to an isotropic radiator, subtract antenna's cable loss, (result is converted from decibel into numeric form with above equation)

1.3 Test Result

For all antenna kits, the following tables find worst case value for each component :

1. Vehicle Kit

Vehicle Kit Component				
Outdoor Antenna KIT Antenna:SC-200W Cable:SC-174 -5FT 5Feet	Outdoor Antenna Gain		Outdoor Cable Loss	
	At 1900MHz(dBi)	At 800MHz(dBi)	At 1900MHz(dB)	At 800MHz(dB)
	5	3	4.6	2.4
Indoor Patch Antenna KIT Antenna:SC-110W Cable: SC-174 -5FT 5Feet	Indoor Antenna Gain		Indoor Cable Loss	
	At 1900MHz(dBi)	At 800MHz(dBi)	At 1900MHz(dB)	At 800MHz(dB)
	3	1.1	4.6	2.4

Cellular Band UL:	
Maximum peak output power at antenna input terminal(dBm):	19.90
Maximum peak output power at antenna input terminal(mW):	97.72
Prediction distance(cm):	20
Prediction frequency(MHz):	829.75
Maximum Antenna Gain (dBi):	3
Cable Loss(dB):	2.4
G (numeric) :	1.15
Power density at predication frequency and distance(mW/cm ²) :	0.0223
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²) :	0.5532

Cellular Band DL:	
Maximum peak output power at antenna input terminal(dBm):	-9.30
Maximum peak output power at antenna input terminal(mW):	0.12
Prediction distance(cm):	20
Prediction frequency(MHz):	887.50
Maximum Antenna Gain (dBi):	1.1
Cable Loss(dB):	2.4
G (numeric) :	0.74
Power density at predication frequency and distance(mW/cm ²) :	0.00002
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²) :	0.5917

PCS Band UL:	
Maximum peak output power at antenna input terminal(dBm):	19.40
Maximum peak output power at antenna input terminal(mW):	87.10
Prediction distance(cm):	20
Prediction frequency(MHz):	1881.80
Maximum Antenna Gain (dBi):	5
Cable Loss(dB):	4.6
G (numeric) :	1.10
Power density at predication frequency and distance(mW/cm ²) :	0.0190
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²) :	1.0000

PCS Band DL:	
Maximum peak output power at antenna input terminal(dBm):	-9.70
Maximum peak output power at antenna input terminal(mW):	0.11
Prediction distance(cm):	20
Prediction frequency(MHz):	1978.60
Maximum Antenna Gain (dBi):	3
Cable Loss(dB):	4.6
G (numeric) :	0.69
Power density at predication frequency and distance(mW/cm ²) :	0.00001
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²) :	1.0000

2. Marine Kit

Marine Kit Component				
Outdoor Antenna KIT Antenna:SC-288W or Galaxy 5412-P Cable:SC-240-40FN 40Feet	Outdoor Antenna Gain		Outdoor Cable Loss	
	At 1900MHz(dBi)	At 800MHz(dBi)	At 1900MHz(dB)	At 800MHz(dB)
	4	3	6.52	3.98
Indoor Patch Antenna KIT Antenna:SC-248W Cable: SC-240-20FN 20Feet	Indoor Antenna Gain		Indoor Cable Loss	
	At 1900MHz(dBi)	At 800MHz(dBi)	At 1900MHz(dB)	At 800MHz(dB)
	3	1.1	3.56	2.29

Cellular Band UL:	
Maximum peak output power at antenna input terminal(dBm):	19.90
Maximum peak output power at antenna input terminal(mW):	97.72
Prediction distance(cm):	20
Prediction frequency(MHz):	829.75
Maximum Antenna Gain (dBi):	3
Cable Loss(dB):	3.98
G (numeric) :	0.80
Power density at predication frequency and distance(mW/cm ²) :	0.0155
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²) :	0.5532

Cellular Band DL:	
Maximum peak output power at antenna input terminal(dBm):	-9.30
Maximum peak output power at antenna input terminal(mW):	0.12
Prediction distance(cm):	20
Prediction frequency(MHz):	887.50
Maximum Antenna Gain (dBi):	1.1
Cable Loss(dB):	2.29
G (numeric) :	0.76
Power density at predication frequency and distance(mW/cm ²) :	0.00002
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²) :	0.5917

PCS Band UL:	
Maximum peak output power at antenna input terminal(dBm):	19.40
Maximum peak output power at antenna input terminal(mW):	87.10
Prediction distance(cm):	20
Prediction frequency(MHz):	1881.80
Maximum Antenna Gain (dBi):	4
Cable Loss(dB):	6.52
G (numeric) :	0.56
Power density at predication frequency and distance(mW/cm ²) :	0.0097
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²) :	1.0000

PCS Band DL:	
Maximum peak output power at antenna input terminal(dBm):	-9.70
Maximum peak output power at antenna input terminal(mW):	0.11
Prediction distance(cm):	20
Prediction frequency(MHz):	1978.60
Maximum Antenna Gain (dBi):	3
Cable Loss(dB):	3.56
G (numeric) :	0.88
Power density at predication frequency and distance(mW/cm ²) :	0.00002
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²) :	1.0000

3. Desk top/RV Kit

Desk top/RV Component				
Outdoor Antenna KIT Antenna:SC-288W Cable:SC-240-40FN 40Feet	Outdoor Antenna Gain		Outdoor Cable Loss	
	At 1900MHz(dBi)	At 800MHz(dBi)	At 1900MHz(dB)	At 800MHz(dB)
	4	3	6.52	3.98
Indoor Patch Antenna KIT Antenna:SC-120W Cable: No	Indoor Antenna Gain		Indoor Cable Loss	
	At 1900MHz(dBi)	At 800MHz(dBi)	At 1900MHz(dB)	At 800MHz(dB)
	3	1.2	0.3	0.3

Cellular Band UL:	
Maximum peak output power at antenna input terminal(dBm):	19.90
Maximum peak output power at antenna input terminal(mW):	97.72
Prediction distance(cm):	20
Prediction frequency(MHz):	829.75
Maximum Antenna Gain (dBi):	3
Cable Loss(dB):	3.98
G (numeric) :	0.80
Power density at predication frequency and distance(mW/cm ²) :	0.0155
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²) :	0.5532

Cellular Band DL:	
Maximum peak output power at antenna input terminal(dBm):	-9.30
Maximum peak output power at antenna input terminal(mW):	0.12
Prediction distance(cm):	20
Prediction frequency(MHz):	887.50
Maximum Antenna Gain (dBi):	1.2
Cable Loss(dB):	0.3
G (numeric) :	1.23
Power density at predication frequency and distance(mW/cm ²) :	0.00003
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²) :	0.5917

PCS Band UL:	
Maximum peak output power at antenna input terminal(dBm):	19.40
Maximum peak output power at antenna input terminal(mW):	87.10
Prediction distance(cm):	20
Prediction frequency(MHz):	1881.80
Maximum Antenna Gain (dBi):	4
Cable Loss(dB):	6.52
G (numeric) :	0.56
Power density at predication frequency and distance(mW/cm ²):	0.0097
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	1.0000

PCS Band DL:	
Maximum peak output power at antenna input terminal(dBm):	-9.70
Maximum peak output power at antenna input terminal(mW):	0.11
Prediction distance(cm):	20
Prediction frequency(MHz):	1978.60
Maximum Antenna Gain (dBi):	3
Cable Loss(dB):	0.3
G (numeric) :	1.86
Power density at predication frequency and distance(mW/cm ²):	0.00004
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	1.0000