



Mobile Power Density Calculation for FCC ID: RUT1200BG

The Alcatel access point, Model 1200B and 1200B INT are IEEE802.11 B /G radios. The access points operate on the 2.4 GHz ISM band.

Operating Environment:

The operating environment for the radio in all cases is a fixed, uncontrolled environment, however, the devices are classified as being "Mobile", Therefore the exposure at 20 cm is calculated.

Fixed, Uncontrolled Environment:

The FCC limit for the power density for uncontrolled exposure to RF devices operation at 2.4GHz at a distance of 20 cm is:

$$1 \text{ mW/cm}^2$$

Power density is calculated from the following equation

$$\text{Exposure (mW/cm}^2\text{)} = \frac{\text{EIRP(mW)} * \text{Duty Cycle}}{4 * \text{PI} * \text{Radius}^2\text{(cm)}}$$

Where:

Radius = 20 cm

Duty Cycle = assumed to be 100% to yield a worst case result.

NOTE: Maximum allowable certified external antenna gain: 6.8 dBi

2.4GHz ISM Band MPE distance Calculation

Using the highest power measured on the 2.4 GHz ISM band.

MAX Pout: 20.4 dBm (109.65 mW) MAX Ant Gain 6.8 dBi (4.78x)

EIRP: 27.2 dBm (524.80 mW EIRP)

Calculating power density at a distance of 20 cm yields:

$$\text{Power Density} = \frac{524.127 * 1}{4 * \text{Pi} * 20^2} \Rightarrow \frac{524.127}{5026.54} \Rightarrow .1043 \text{ mw/cm}^2$$

$$\begin{aligned} \text{Delta} &= \text{specification} - \text{result} \\ &= 1 \text{ mW/cm}^2 - .1043 \text{ mw/cm}^2 = .8956 \text{ mw/cm}^2 \\ &= -9.817 \text{ dB below limit} \end{aligned}$$