

FCC Part 15 TEST REPORT

EUT : NCNA BLUETOOTH HEADSET

MODEL : NBT-01HS

FCC ID : RVINCN040220

APPLICANT : NCNA Co., Ltd.

ADDRESS : 8F Gongduck Building, 385-64

Gongduck-Dong, Mapo-gu ,Seoul,
Korea.

March 19, 2004

TUV Rheinland Korea Ltd.

TEST REPROT CERTIFICATION

Applicant : NCNA Co., Ltd.

Adderss : 8F Gongduck Building, 385-64 Gongduck-Dong, Mapo-gu ,Seoul,
Korea

EUT Name : NCNA Bluetooth Headset
Model no. : NBT-01HS
Serial No. : Engineering Sample
FCCID : RVINCN040220
Testing location : LG Innotek Co.,Ltd.
133, Gongdan-dong, Gumi-City , Gyeongbuk 730-703, R.O.K

Applied specification : FCC Part 15 , ANSI C63.4-1992 , CISPR 22:1997

Test result : The above mentioned test item passed.

Tested by : Gye-Woog Lee

Reviewed by : Uon-Chae Song

March 18,2004



Date

Signature

March 18,2004



Date

Signature

I HEREBY CERTIFY THAT the data shown in this report were made in accordance with the Procedures given in the applied specification and I assume full responsibility for accuracy and completeness of these data.

Note : This test report relates to the a. m. test item. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark on this or similar products.

Contents

1. General Information	5
1.1 Product Description	5
1.2 Project data	5
1.3 Applicant	5
1.4 Manufacturer	5
2. EUT Information	6
2.1 General EUT Information	6
2.2 Center Frequency of Tested Channel	6
2.3 Test Environment	6
2.4 Accessories and Ancillary Equipment	6
3. Testing Facilities	7
4. EUT Description and Operational Description	7
4.1 General Description	7
4.2 Product Function and Intended use	7
5. Test Set-up	8
5.1 Principle of configuration	8
5.2 Operational Modes	8
5.3 Applied Specification	8
6. Test Report Summary	9
7. Test Results	10
7.1 Antenna Connector Requirements	10
7.2 AC CONNECTED EMISSION	11
7.3 Carrier Frequency Separation	12
7.4 Time of Occupancy(Dwell time)	13
7.5 20dB Bandwidth	14
7.6 Number of Hopping Frequencies Requirements	15
7.7 Pseudorandom Frequency Hopping Sequence and Equal Hopping Frequency use Requirements	16



7.8 Receiver Input Bandwidth Requirements-----18
7.9 Peak Output Power -----19
7.10 Band-edge Compliance-----20
7.11 Spurious Conducted emissions -----21
7.12 Spurious Radiated emissions -----22
8. List of Test and Measurement Instruments -----24
9. complementary Materials-----25

1. General Information

1.1 Product Description

Product Name : NCNA Bluetooth Headset
Product ID : NBT-01HS
Serial No. : Engineering Sample
FCC ID : RVINCN040220

1.2 Project data

Receipt of EUT : December 20,2003
Date of Test : March 10, 2004
Data of report : March 19,2004

1.3 Applicant

Company Name : NCNA Co.,Ltd.
Address : 8F Gongduck Building, 385-64 Gongduck-Dong, Mapo-gu ,
Seoul, Korea.

Contact Person : Nam-IL Jang

1.4 Manufacturer

Company Name : NCNA Co.,Ltd.
Address : 8F Gongduck Building, 385-64 Gongduck-Dong, Mapo-gu ,
Seoul, Korea.

Contact Person : Nam-IL Jang

2. EUT Information

2.1 General EUT Information

Type	Transmitter	Receiver
FCC Classification	FHSS Sequence Spread Spectrum (FHSS)	FHSS Sequence Spread Spectrum (FHSS)
Frequency Range	2402 – 2480 MHz	2402 – 2480 MHz
Number of Channels	79	79
Channel Separation	1MHz	1MHz
Type of Antenna	Surface Mountable Dielectric Chip Antenna	Surface Mountable Dielectric Chip Antenna
Power Supply	DC 3.7V Lithium Battery	DC 3.7V Lithium Battery

2.2 Center Frequency of Tested Channel

Frequency	Tx (MHz)	Rx (MHz)
Lowest	2402	2402
Middle	2441	2441
Highest	2480	2480

2.3 Test Environment

Temperature	20°C
Relative Humidity	30 ~ 60%
Voltage	DC 3.7V

2.4 Accessories and Ancillary Equipment

Equipment	Model No.	Serial Number	Maker
AC/DC Adopter	DP412E	N.A.	Digital Power
Laptop PC	PS428L-OE142	30014068J	Toshiba

3. Testing Facilities

LG Innotek Co.,Ltd.

133, Gongdan-dong, Gumi-City , Gyeongbuk 730-703, R.O.K

4. EUT Description and Operational Description

4.1 General Description

Bluetooth is a short-range radio link intended to replace the cable(s) connecting portable and/or fixed electronic devices. Key features are robustness, low complexity, low power, and low cost.

Bluetooth operates in the unlicensed ISM band at 2.4 GHz. A frequency hop transceiver is applied to combat interference and fading. A shaped, binary FM modulation is applied to minimize transceiver complexity. The symbol rate is 1Ms/s. A slotted channel is applied with a nominal slot length of 625 μ s. For full duplex transmission, a Time-Division Duplex (TDD) scheme is used.

4.2 Product Function and Intended use

The submitted sample is a wireless headset based on the Bluetooth technology. Bluetooth is a short-range radio link intended to be a cable replacement between portable and/or fixed electronic devices.

Bluetooth operates in the unlicensed ISM Band at 2.4 GHz. In the US a band of 83.5 MHz width is available. In this band, 79 RF channels spaced 1MHz apart are defined.

The channel is represented by a pseudo-random hopping sequence through the 79 channels. The channel is divided into time slots, with a nominal slot length of 625 μ s, where each slot corresponds to different RF hop frequencies. The nominal hop rate is 1600 hops/s. The symbol rate on the channel is 1 Ms/s. the low, middle and high operating frequency is 2402Mhz, 2441Mhz and 2480Mhz respectively.

5. Test Set-up

5.1 Principle of configuration

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes and test settings were adapted accordingly in reference to the instructions for use.

For details, please refer to the Operation mode in chapter 7.

5.2 Operational Modes

Page Scan,

Inquiry Scan

Hopping Mode

Fixed mode (2402Mhz, 2441Mhz and 2480Mhz)

5.3 Applied Specification

FCC Part 15

ANSI C63.4-1992

CISPR 22:1997

6. Test Report Summary

Related Clause	Test case or Requirements	Subclause	Limit	Result (Note1)
7.1	Antenna Connector Requirements	15.203 15.204	15.203 15.204(c)	C
7.2	AC Connected Emission	15.207	15.207(a)	Pass
7.3	Carrier Frequency Separation	15.247	15.247(a)(1)	Pass
7.4	Time of Occupancy(Dwell time)	15.247	15.247(a)(1)(ii)	Pass
7.5	20dB Bandwidth	15.247	15.247(a)(1)(ii)	Pass
7.6	Number of Hopping Frequencies Requirements	15.247	15.247(a)(1)(ii)	C
7.7	Pseudorandom Frequency Hopping Sequence and Equal Hopping Frequency use Requirements	15.247	15.247(a)(1)	C
7.8	Receiver Input Bandwidth Requirements	15.247	15.247(a)(1)	C
7.9	Peak Output Power	15.247	15.247(b)(1)	Pass
7.10	Band-edge Compliance	15.247	15.247(c)	Pass
7.11	Spurious Conducted emissions	15.247	15.247(c)	Pass
7.12	Spurious Radiated emissions	15.247	15.247(c)	Pass

* Note1 : C: Complies, Pass: Passed, Fail : Failed and NA: Not Applicable

7. Test Results

7.1 Antenna Connector Requirements

RESULT:

Complies

The antenna is permanently attached on the PCB.

The EUT has a Surface Mountable Dielectric Chip Antenna soldered to the circuit board.

For more information on antenna follows;

Antenna gain : 0dBi.

Manufacturer : Mitsubishi Antenna

Model No. : AHD1403-244ST

Type : Surface Mountable Dielectric Chip Antenna

7.2 AC Connected Emission

Test Specification : CISPR 22: 1997
 Mode of operation : Charging only / Normal use during charging
 Port of testing : AC power port of the charger of the EUT
 Supply voltage : AC 220V
RESULT : Pass

Operation mode: Normal use during charging
 For Live measurement

Frequency	QP reading	QP limit	Av reading	Av limit
MHz	dB μ V	dB μ V	dB μ V	dB μ V
	No peak limit	66 – 56*	No peak limit	56 – 46*

For Neutral measurement

Frequency	QP reading	QP limit	Av reading	Av limit
MHz	dB μ V	dB μ V	dB μ V	dB μ V
	No peak limit	66 – 56*	No peak limit	56 – 46*

* Decreases with the logarithm of the frequency.

The radio frequency voltage conducted back onto the Live and the Neutral power lines complies with the limits.

For test results refer to Appendix 1(13002537), page 2

Limit

Subclause 15.207(a)

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

7.3 Carrier Frequency Separation

Test specification : FCC § 15
Mode of operation : Tx mode (hopping on), DH1 packet
Port of testing : Temporary antenna port
Detector : PK
Trace : Max hold
RBW/VBW : 100kHz/300kHz
RESULT : Pass

The centre frequencies of the hopping channels are separated by more than the 20dB bandwidth.

For test results refer to Appendix 1(13002537), page 5

Limit

Subclause 15.247(a)(1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

7.4 Time of Occupancy(Dwell time)

Test specification : FCC § 15
Mode of operation : Tx mode (2441MHz), DH5 packet
Port of testing : Temporary antenna port
Detector : PK
Trace : Max hold
RBW/VBW : 1MHz/3MHz
RESULT : Pass

The system makes 1600 hops per second or has a length of 625us.

Let take DH5 packet in worst case. A DH5 packet has 5 slots for transmitting and 1 slot for receiving. It means it can have maximum 266.67 ($=1600/6$) hops per second.

Therefore it has 3.38 hops($=266.67/79$) per second for each channel.

And it has 106.81hops appearance for 31.6 seconds ($= 0.4 \times 79$ channels).

Each TX length per appearance is 2.9 ms.

i.e. The dwell time for DH5 Packet (in worst case) :

$$106.81 \times 2.9 \text{ ms} = 309.75 \text{ ms}$$

For test results(Each TX length per appearance) please refer to Appendix 1(13002537), page 6.

Limit

Subclause 15.247(a)(1)(ii)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 75 hopping frequencies. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

7.5 20dB Bandwidth

Test specification : FCC § 15
Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), DH5 packet
Port of testing : Temporary antenna port
Detector : PK
Trace : Max hold
RBW/VBW : 30kHz/100kHz
RESULT : Pass

20dB bandwidth (MHz)		
2402	2441	2480
0.932	0.924	0.928

For test results refer to Appendix 1(13002537), page 7.

Limit

Subclause 15.247(a)(1)(ii)

The maximum 20dB bandwidth of the hopping channel is 1Mhz.

7.6 Number of Hopping Frequencies Requirements

Test specification : FCC § 15
Mode of operation : Hopping
Port of testing : Temporary antenna port
Detector : PK
Trace : Max hold
RBW/VBW : 100kHz/100kHz
RESULT : Complies

It uses exactly 79 hopping frequencies.

For test results refer to Appendix 1(13002537), page 10.

Limit

15.247(a)(1)(ii)

Frequency hopping systems operating in the 2400-2483.5 bands shall use at least 75 Hopping frequencies.

0x00000f0: 09 45 | 13 47 | 11 77 | 15 00 | 64 49 | 66 53 | 68 02 | 70 06 |
0x0000110: 01 51 | 03 55 | 05 04 | 07 08 | 72 57 | 74 61 | 76 10 | 78 14 |
0x0000130: 09 59 | 11 63 | 13 12 | 15 16 | 17 65 | 19 69 | 21 18 | 23 22 |
0x0000150: 33 67 | 35 71 | 37 20 | 39 24 | 25 73 | 27 77 | 29 26 | 31 30 |
0x0000170: 41 75 | 43 00 | 45 28 | 47 32 | 17 02 | 21 04 | 19 34 | 23 36 |
0x0000190: 33 06 | 37 08 | 35 38 | 39 40 | 25 10 | 29 12 | 27 42 | 31 44 |
0x00001b0: 41 14 | 45 16 | 43 46 | 47 48 | 49 18 | 53 20 | 51 50 | 55 52 |
0x00001d0: 65 22 | 69 24 | 67 54 | 71 56 | 57 26 | 61 28 | 59 58 | 63 60 |
0x00001f0: 73 30 | 77 32 | 75 62 | 00 64 | 49 34 | 51 42 | 57 66 | 59 74 |
0x0000210: 53 36 | 55 44 | 61 68 | 63 76 | 65 50 | 67 58 | 73 03 | 75 11 |
0x0000230: 69 52 | 71 60 | 77 05 | 00 13 | 02 38 | 04 46 | 10 70 | 12 78 |
0x0000250: 06 40 | 08 48 | 14 72 | 16 01 | 18 54 | 20 62 | 26 07 | 28 15 |
0x0000270: 22 56 | 24 64 | 30 09 | 32 17 | 02 66 | 06 74 | 10 19 | 14 27 |
0x0000290: 04 70 | 08 78 | 12 23 | 16 31 | 18 03 | 22 11 | 26 35 | 30 43 |
0x00002b0: 20 07 | 24 15 | 28 39 | 32 47 | 34 68 | 38 76 | 42 21 | 46 29 |
0x00002d0: 36 72 | 40 01 | 44 25 | 48 33 | 50 05 | 54 13 | 58 37 | 62 45 |
0x00002f0: 52 09 | 56 17 | 60 41 | 64 49 | 34 19 | 36 35 | 50 51 | 52 67 |
0x0000310: 38 21 | 40 37 | 54 53 | 56 69 | 42 27 | 44 43 | 58 59 | 60 75 |
0x0000330: 46 29 | 48 45 | 62 61 | 64 77 | 66 23 | 68 39 | 03 55 | 05 71 |
0x0000350: 70 25 | 72 41 | 07 57 | 09 73 | 74 31 | 76 47 | 11 63 | 13 00 |
0x0000370: 78 33 | 01 49 | 15 65 | 17 02 | 66 51 | 70 67 | 03 04 | 07 20 |
0x0000390: 68 55 | 72 71 | 05 08 | 09 24 | 74 59 | 78 75 | 11 12 | 15 28 |
0x00003b0: 76 63 | 01 00 | 13 16 | 17 32 | 19 53 | 23 69 | 35 06 | 39 22 |
0x00003d0: 21 57 | 25 73 | 37 10 | 41 26 | 27 61 | 31 77 | 43 14 | 47 30 |
0x00003f0: 29 65 | 33 02 | 45 18 | 49 34 | 19 04 | 21 08 | 23 20 | 25 24

7.8 Receiver Input Bandwidth Requirements

RESULT:

Complies

The receiver bandwidth is equal to the receiver bandwidth in the 79 hopping channel mode, which is 1 MHz. The receiver bandwidth is indirectly verified during Bluetooth RF conformance testing.

7.9 Peak Output Power

Test specification : FCC § 15
 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), DH1 packet
 Port of testing : Temporary antenna port
 Detector : PK
 Trace : Max hold
 RBW/VBW : 1MHz/3MHz
 RESULT : Pass

Frequency (MHz)	Maximum peak output power (dBm)	Cable attenuation (dB)	Actual value (dBm)
2402	-1.42	1.80	0.38
2441	-0.56	1.83	1.27
2480	-0.62	1.85	1.32

All three transmit frequency modes comply with the maximum peak output power limit.
 For test results refer to Appendix 1(13002537), page 11.

Limit

Subclause 15.247(b)(1)

Frequency range	RF output power
2.400-2.483,5MHz	0.125W (21.0dBm)

7.10 Band-edge Compliance

Test specification : FCC § 15
Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), DH1 packet
Port of testing : Temporary antenna port
Detector : PK
Trace : Max hold
RBW/VBW : 300kHz/1.0MHz
RESULT : Pass

There is no peak found outside any 100kHz bandwidth of the operating frequency band in the three transmit frequency. All three transmit frequency modes comply with the limit stated in subclause 15.247(c).

For test results refer to Appendix 1(13002537), page 14.

Limit

Subclause 15.247(c)

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

7.11 Spurious Conducted emissions

Test specification : FCC § 15
 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), DH1 packet
 Port of testing : Temporary antenna port
 Detector : PK
 Trace : Max hold
 RBW/VBW : 100kHz/300kHz
RESULT : Pass

Operating frequency : 2402MHz

Spurious Frequency (MHz)	Power level (dBm)	Reference value (dBm)	Delta to reference level (dB)
No Peak Found	-	-	-

Operating frequency : 2441MHz

Spurious Frequency (MHz)	Power level (dBm)	Reference value (dBm)	Delta to reference level (dB)
No Peak Found	-	-	-

Operating frequency : 2480MHz

Spurious Frequency (MHz)	Power level (dBm)	Reference value (dBm)	Delta to reference level (dB)
No Peak Found	-	-	-

All three transmit frequency modes comply with the 20dB limit stated in subclause 15.247(c).

For test results refer to Appendix 1(13002537), page 17.

Limit

Subclause 15.247(c)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

7.12 Spurious Radiated emissions

Test specification : ANSI C63.4 - 1992
 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), DH1 packet
 Detector : PK
 Trace : Max hold
 Port of testing : Enclosure
 Measurement Distance : 3m
 Measurement BW : 1 MHz
RESULT : Pass

Tx frequency (MHz)	Polarization	Spurious Frequency (MHz)	Power Level (dBuV/m)	Detector (Peak)
2402	Horizontal	-	No Peak above the limit	-

Tx frequency (MHz)	Polarization	Spurious Frequency (MHz)	Power Level (dBuV/m)	Detector (Peak)
2402	Vertical	-	No Peak above the limit	-

Tx frequency (MHz)	Polarization	Spurious Frequency (MHz)	Power Level (dBuV/m)	Detector (Peak)
2441	Horizontal	-	No Peak above the limit	-

Tx frequency (MHz)	Polarization	Spurious Frequency (MHz)	Power Level (dBuV/m)	Detector (Peak)
2441	Vertical	-	No Peak above the limit	-

Tx frequency (MHz)	Polarization	Spurious Frequency (MHz)	Power Level (dBuV/m)	Detector (Peak)
2480	Horizontal	-	No Peak above the limit	-

Tx frequency (MHz)	Polarization	Spurious Frequency (MHz)	Power Level (dBuV/m)	Detector (Peak)
2480	Vertical	-	No Peak above the limit	-

All three transmit frequency modes comply with the field strength within the restricted bands.

For test results refer to Appendix 1(13002537), page 27.

Limit

Subclause 15.247(c)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209 (a) (see Section 15.205(c)).

Field strength limits within the restricted bands using average detector:

Frequency (MHz)	Field strength (microvolts/meter)	Field strength (dB μ V/m)	Measurement distance (meters)
30-88	100	$20 \cdot \log(100) = 40.0$	3
88-216	150	$20 \cdot \log(150) = 43.5$	3
216-960	200	$20 \cdot \log(200) = 46.0$	3
960-2500	500	$20 \cdot \log(500) = 54.0$	3

According to section 15.35(b), on any frequency or frequencies above 1000 MHz the radiated limits shown are based upon the use of measurement instrumentation employing an average detector function. When average radiated emission measurements are specified in this part, including emission measurements below 1000 MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit for the frequency being investigated.

8. List of Test and Measurement Instruments

	Kind of Equipment	Type	Manufacturer	S/N
☒	EMI Test Receiver	ESMI	R/S	1032.5510.53
☒	Spectrum Analyzer	FSP30	R/S	1093.4495.30
☐	Tracking Generator	ESMI-B1	R/S	1033.3240.52
☐	Spectrum Analyzer	8566B	HP	3638A0857E
☐	Spectrum Analyzer	SA-930	LGIT	02040025
☐	Wave Dipole Antenna	HZ-12	R/S	842006/0012
☐	Wave Dipole Antenna	HZ-12	R/S	846556/0004
☒	Biconical Antenna	3104C	EMCO	9408-4667
☐	Biconical Antenna	3109	EMCO	9405-2812
☒	Log-Periodic Antenna	3146A	EMCO	1064
☐	Biconilog Antenna	3142	EMCO	9710-1220
☐	V-Network	ESH3-Z5	R/S	847265/030
☐	V-Network	ESH3-Z6	R/S	847250/016
☐	T-Network	E-Z10	R/S	84480/011
☐	LISN	6338-5-PJ-50-N	Solar	953938/953939
☒	Turn Table	2081	EMCO	
☒	Antenna Tower	2075	EMCO	
☒	Multi Device Controller	2090	EMCO	9708-1255
☐	Printer	C4569A	HP	SG78K1H1FS
☐	Absorbing Clamp	MDS 21	R/S	847905/005
☐	Signal Generator	2023	MARCONI	112246067
☐	Swept Signal Generator	83620B	HP	3722A00549
☐	10dB Attenuator	23-10-34	Weinschel co	BD4316
☐	10dB Attenuator	33-10-34	Weinschel co	BB9784
☒	Antenna	3142	EMCO	9710-1220
☒	Antenna	3115	EMCO	9511-4612

☒	Antenna	3160-08	EMCO	1168
☒	Antenna	3160-09	EMCO	1304
☒	Amplifier	HP8447F	HP	3113A06911
☒	Amplifier	HP83006	HP	3104A00611
☒	Amplifier	HP8449B	HP	3008A00859
☒	EMI test receiver	ESCS30	R&S	839809/003
☒	Artificial mains network	ESH2-Z5	R&S	829991/009
☒	Artificial hand	FCC-AH-1	Fischer custom communications Inc.	2008

9. Complementary Materials

Appendix 1 : Test Results

Appendix 2 : Test Setup

Appendix 3 : EUT Photos

Appendix 4 : FCC ID Label

Technical Documents :

- **Schematics**
- **Block Diagram**
- **PCB Layout**
- **User Manual**