



FCC Radio Test Report

FCC ID: RWO-RC21024501

This report concerns: Original Grant

Project No. : 2605C154
Equipment : Wireless Charging Dock
Brand Name : 
Model Name : RAZER,
Applicant : RC21-024501, RC21-024501XX-XXXX (X can be 0-9 or A-Z)
Address : Razer Inc.
Manufacturer : 9 Pasteur, Irvine, CA 92618, USA
Address : RAZER (ASIA-PACIFIC) PTE. LTD.
Factory : Razer SEA HQ, 1 One-north Crescent, #02-01, Singapore 138538
Address : RAZER TECHNOLOGY AND DEVELOPMENT (SHENZHEN) CO., LTD
Date of Receipt : East Wing, 3rd Floor, Block 2, Phase 1 of Vision Shenzhen Business
Date of Test : Park Keji South Road, Hi-Tech Industrial Park, Shenzhen 518057, China
Issued Date : May 26, 2026
Test Sample : May 27, 2026 ~ Jul. 21, 2026
Standard(s) : Jul. 29, 2026
Sample No.: DG920260713280 for Radiated Emissions-9KHz – 30MHz
and 1GHz- 18 GHz, DG92026052699 for conducted, DG92026052698
for others.
FCC CFR Title 47, Part 15, Subpart C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc. (Dongguan)

Prepared by : 
Jaden Kong

Approved by : 
Chay Cai

No.3, Jinshagang 1st Road, Dalang, Dongguan, Guangdong People's Republic of China.

Tel: +86-769-8318-3000 Web: www.newbtl.com Service mail: btl_qa@newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacturer's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** assumes no responsibility for the data provided by the customer, any statements, inferences or generalizations drawn by the customer or others from the reports issued by **BTL**.

The report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the ISO/IEC 17025: 2017 requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

Table of Contents	Page
REVISION HISTORY	6
1 . APPLICABLE STANDARDS	7
2 . SUMMARY OF TEST RESULTS	7
2.1 TEST FACILITY	8
2.2 MEASUREMENT UNCERTAINTY	8
2.3 TEST ENVIRONMENT CONDITIONS	9
3 . GENERAL INFORMATION	10
3.1 GENERAL DESCRIPTION OF EUT	10
3.2 DESCRIPTION OF TEST MODES	12
3.3 PARAMETERS OF TEST SOFTWARE	13
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	14
3.5 SUPPORT UNITS	15
3.6 CUSTOMER INFORMATION DESCRIPTION	15
4 . AC POWER LINE CONDUCTED EMISSIONS	16
4.1 LIMIT	16
4.2 TEST PROCEDURE	16
4.3 DEVIATION FROM TEST STANDARD	16
4.4 TEST SETUP	17
4.5 EUT OPERATING CONDITIONS	17
4.6 TEST RESULTS	17
5 . RADIATED EMISSIONS	18
5.1 LIMIT	18
5.2 TEST PROCEDURE	19
5.3 DEVIATION FROM TEST STANDARD	20
5.4 TEST SETUP	20
5.5 EUT OPERATING CONDITIONS	22
5.6 TEST RESULT - 9 KHZ TO 30 MHZ	22
5.7 TEST RESULT - 30 MHZ TO 1000 MHZ	22
5.8 TEST RESULT - ABOVE 1000 MHZ	22
6 . BANDWIDTH	23
6.1 LIMIT	23

Table of Contents	Page
6.2 TEST PROCEDURE	23
6.3 DEVIATION FROM STANDARD	23
6.4 TEST SETUP	23
6.5 EUT OPERATION CONDITIONS	23
6.6 TEST RESULTS	23
7 . MAXIMUM OUTPUT POWER	24
7.1 LIMIT	24
7.2 TEST PROCEDURE	24
7.3 DEVIATION FROM STANDARD	24
7.4 TEST SETUP	24
7.5 EUT OPERATION CONDITIONS	24
7.6 TEST RESULTS	24
8 . CONDUCTED SPURIOUS EMISSION	25
8.1 LIMIT	25
8.2 TEST PROCEDURE	25
8.3 DEVIATION FROM STANDARD	26
8.4 TEST SETUP	26
8.5 EUT OPERATION CONDITIONS	26
8.6 TEST RESULTS	26
9 . POWER SPECTRAL DENSITY	27
9.1 LIMIT	27
9.2 TEST PROCEDURE	27
9.3 DEVIATION FROM STANDARD	27
9.4 TEST SETUP	27
9.5 EUT OPERATION CONDITIONS	27
9.6 TEST RESULTS	27
10 . MEASUREMENT INSTRUMENTS LIST	28
APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS	30
APPENDIX B - RADIATED EMISSION - 9 KHZ TO 30 MHZ	33
APPENDIX C - RADIATED EMISSION - 30 MHZ TO 1000 MHZ	38
APPENDIX D - RADIATED EMISSION - ABOVE 1000 MHZ	41
APPENDIX E - BANDWIDTH	56

Table of Contents	Page
APPENDIX F - MAXIMUM OUTPUT POWER	59
APPENDIX G - CONDUCTED SPURIOUS EMISSION	61
APPENDIX H - POWER SPECTRAL DENSITY	64

REVISION HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-1-2605C154	R00	Original Report.	Jul. 29, 2026	Valid

1. APPLICABLE STANDARDS

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standard:

ANSI C63.10-2020

The following reference test guidance is not within the scope of accreditation of A2LA:

KDB 558074 D01 15.247 Meas Guidance v05r02

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC CFR Title 47, Part 15, Subpart C				
Standard(s) Section	Test Item	Test Result	Judgment	Remark
15.207	AC Power Line Conducted Emissions	APPENDIX A	PASS	-----
15.247(d) 15.205(a) 15.209(a)	Radiated Emissions	APPENDIX B APPENDIX C APPENDIX D	PASS	-----
15.247(a)(2)	Bandwidth	APPENDIX E	PASS	-----
15.247(b)(3)	Maximum Output Power	APPENDIX F	PASS	-----
15.247(d)	Conducted Spurious Emission	APPENDIX G	PASS	-----
15.247(e)	Power Spectral Density	APPENDIX H	PASS	-----
15.203	Antenna Requirement	-----	PASS	Note(2)

Note:

(1) "N/A" denotes test is not applicable to this device.

(2) The device what use a permanently attached antenna were considered sufficient to comply with the provisions of 15.203.

2.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No.3, Jinshagang 1st Road, Dalang, Dongguan, Guangdong People's Republic of China.

BTL's Registration Number for FCC: 747969

BTL's Designation Number for FCC: CN1377

2.2 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95.45% confidence level (based on a coverage factor ($k=2$))

The BTL measurement uncertainty as below table:

A. AC power line conducted emissions Measurement:

Test Site	Method	Measurement Frequency Range	U , (dB)
DGDLC02	CISPR	150kHz ~ 30MHz	2.66

B. Radiated emissions Measurement:

Test Site	Method	Measurement Frequency Range	U , (dB)
DGDLCB03	CISPR	9kHz ~ 30MHz	2.26

Test Site	Method	Measurement Frequency Range	Ant. H / V	U , (dB)
DGDLCB03 (3m)	CISPR	30MHz ~ 200MHz	V	4.40
		30MHz ~ 200MHz	H	3.62
		200MHz ~ 1,000MHz	V	4.58
		200MHz ~ 1,000MHz	H	3.98

Test Site	Method	Measurement Frequency Range	U , (dB)
DGDLCB03 (3m)	CISPR	1GHz ~ 6GHz	4.16
		6GHz ~ 18GHz	4.74

Test Site	Method	Measurement Frequency Range	U , (dB)
DGDLCB03 (1m)	CISPR	18 ~ 26.5 GHz	4.30

C. Other Measurement:

Test Item	Uncertainty
Bandwidth	0.75 %
Maximum Output Power	1.3 dB
Conducted Spurious Emission	2.1 dB
Conducted Bandedge Emission	1.7 dB
Power Spectral Density	1.8 dB
Temperature	0.7 °C
Humidity	1.7 %

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

2.3 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage	Tested By
AC Power Line Conducted Emissions	24°C	54%	AC 120V/60Hz	Hayden Chen
Radiated Emissions -9 kHz to 30 MHz	24°C	48%	DC 5V	Hayden Chen
Radiated Emissions -30 MHz to 1000 MHz	24°C	49%	DC 5V	AllenTong
Radiated Emissions -Above 1000 MHz	23°C	50%	DC 5V	Ilya Zhang
	23°C	48%	DC 5V	AllenTong
Bandwidth	25-28°C	49-51%	DC 5V	Jensen Zhou Jay Wei
Maximum Output Power	25-28°C	49-51%	DC 5V	Jensen Zhou Jay Wei
Conducted Spurious Emission	25-28°C	49-51%	DC 5V	Jensen Zhou Jay Wei
Power Spectral Density	25-28°C	49-51%	DC 5V	Jensen Zhou Jay Wei

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	Wireless Charging Dock
Brand Name	RAZER, 
Test Model	RC21-024501
Model Name	RC21-024501, RC21-024501XX-XXXX (X can be 0-9 or A-Z)
Model Difference(s)	Only differ in the model name.
Hardware Version	DVT
Software Version	1.00.02.00
Power Source	Supplied from Type-C port.
Power Rating	5V  1.5A
Operation Frequency	2Mbps: 2402 MHz ~ 2480 MHz 4Mbps: 2404 MHz ~ 2476 MHz
Modulation Type	GFSK
Bit Rate of Transmitter	2Mbps, 4Mbps
Max. Output Power	4Mbps: 7.79 dBm (0.0056 W)

Note:

1. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.
2. The system's model name is RZ81-0245XXXX-XXXX (X: Can be 0-9, A-Z), and the system contains a Charging Dock (Model name:RC21-024501) and Wireless Charging Puck(Model name: RC21-024502).

3. Channel List:

For 2Mbps:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2442
01	2404	21	2444
02	2406	22	2446
03	2408	23	2448
04	2410	24	2450
05	2412	25	2452
06	2414	26	2454
07	2416	27	2456
08	2418	28	2458
09	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

For 4Mbps:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2404	10	2444
01	2408	11	2448
02	2412	12	2452
03	2416	13	2456
04	2420	14	2460
05	2424	15	2464
06	2428	16	2468
07	2432	17	2472
08	2436	18	2476
09	2440		

4. Table for Filed Antenna:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1		Y4RRW0MB1AA	Metal	N/A	2.4

3.2 DESCRIPTION OF TEST MODES

The test system was pre-tested based on the consideration of all possible combinations of EUT operation mode.

Pretest Mode	Description
Mode 1	TX Mode_2Mbps Channel 00/19/39
Mode 2	TX Mode_4Mbps Channel 00/09/18
Mode 3	TX Mode_4Mbps Channel 18

Following mode(s) was (were) found to be the worst case(s) and selected for the final test.

AC power line conducted emissions test	
Final Test Mode	Description
Mode 3	TX Mode_4Mbps Channel 18

Radiated emissions test - Below 1GHz & Above 18 GHz	
Final Test Mode	Description
Mode 3	TX Mode_4Mbps Channel 18

Radiated emissions test - 1 GHz - 18 GHz	
Final Test Mode	Description
Mode 1	TX Mode_2Mbps Channel 00/19/39
Mode 2	TX Mode_4Mbps Channel 00/09/18

Conducted test	
Final Test Mode	Description
Mode 1	TX Mode_2Mbps Channel 00/19/39
Mode 2	TX Mode_4Mbps Channel 00/09/18

Note:

- (1) For radiated emission above 1 GHz test, the spurious points of 1GHz~26.5GHz have been pre-tested and in this report only recorded the worst case. The remaining spurious points are all below the limit value of 20dB.
- (2) For AC power line conducted emissions and radiated emissions below 1 GHz test, the 4Mbps Channel 18 is found to be the worst case and recorded.
- (3) For radiated emission Harmonic 18-26.5GHz test, only tested the worst case and recorded.
- (4) For radiated emission 1GHz to 18GHz test, both Vertical and Horizontal are evaluated, only the worst polarization is recorded.


3.3 PARAMETERS OF TEST SOFTWARE

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.


Test Software Version	FCCMTKTest_v1.05.05		
Frequency (MHz)	2402	2440	2480
2Mbps	8	8	8
Frequency (MHz)	2404	2440	2476
4Mbps	8	8	8

3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

For AC power line conducted emissions test



For Radiated emissions test



3.5 SUPPORT UNITS

AC power line conducted emissions test

Item	Equipment	Brand	Model No.	Series No.
A	Adapter	HUAWEI	P0018	N/A

Item	Cable Type	Shielded Type	Ferrite Core	Length
1	USB Cable	NO	NO	1.2m

Radiated emissions test

Item	Equipment	Brand	Model No.	Series No.
A	Notebook	HW	WFH9	N/A

Item	Cable Type	Shielded Type	Ferrite Core	Length
1	USB Cable	NO	NO	1.2m

3.6 CUSTOMER INFORMATION DESCRIPTION

- 1) The antenna gain is provided by the manufacturer.
- 2) Except for AC power line conducted emissions and radiated emissions, the results of all test items include cable losses. Part of the cable losses (0.5dB) are provided by the manufacturer, while the other parts of the cable losses are provided by the testing laboratory.

4. AC POWER LINE CONDUCTED EMISSIONS

4.1 LIMIT

Frequency of Emission (MHz)	Limit (dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56*	56 to 46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.
- (3) The test result calculated as following:
 Measurement Value = Reading Level + Correct Factor
 Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor (if use)
 Margin Level = Measurement Value - Limit Value

4.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.


The following table is the setting of the receiver:

Receiver Parameters	Setting
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.3 DEVIATION FROM TEST STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.6 TEST RESULTS

Please refer to the APPENDIX A.

Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of 『Note』 . If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform. In this case, a " * " marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150 kHz to 30 MHz.

5. RADIATED EMISSIONS

5.1 LIMIT

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (9 kHz-1000 MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000 MHz)

Frequency (MHz)	Band edge/ Harmonic at 3m (dBμV/m)		Harmonic at 1m (dBμV/m)	
	Peak	Average	Peak	Average
Above 1000	74	54	83.5 (Note 5)	63.5 (Note 5)

Note:

(1) The limit for radiated test was performed according to FCC CFR Title 47, Part 15, Subpart C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

(4) The test result calculated as following:

Measurement Value = Reading Level + Correct Factor

Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)

Margin Level = Measurement Value - Limit Value

(5)

$$FS_{\text{limit}} = FS_{\text{max}} - 20 \log \left(\frac{d_{\text{limit}}}{d_{\text{measure}}} \right)$$

20log (d_{limit}/d_{measure})=20log (3/1)=9.5 dB.

FS_{limit}: Harmonic at 3m Peak and Average limit.

FS_{max}: Harmonic at 1m Peak and Average Maximum value.

d_{limit}: Harmonic at 3m test distance.

d_{measure}: Harmonic Actual test distance.

5.2 TEST PROCEDURE

- The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1 GHz)
- The measuring distance of 3 m or 1m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
(below 1 GHz)
- All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1 GHz)
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

The following table is the setting of the receiver:

Spectrum Parameters	Setting
Start ~ Stop Frequency	9 kHz~150 kHz for RBW 200 Hz
Start ~ Stop Frequency	0.15 MHz~30 MHz for RBW 9 kHz
Start ~ Stop Frequency	30 MHz~1000 MHz for RBW 100 kHz

Spectrum Parameters	Setting
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1 MHz / 3 MHz for PK value 1 MHz / 1/T Hz for AVG value


Spectrum Parameters	Setting
Start ~ Stop Frequency	9 kHz~90 kHz for PK/AVG detector
Start ~ Stop Frequency	90 kHz~110 kHz for QP detector
Start ~ Stop Frequency	110 kHz~490 kHz for PK/AVG detector
Start ~ Stop Frequency	490 kHz~30 MHz for QP detector
Start ~ Stop Frequency	30 MHz~1000 MHz for QP detector
Start ~ Stop Frequency	1 GHz~26.5 GHz for PK/AVG detector

5.3 DEVIATION FROM TEST STANDARD


No deviation.

5.4 TEST SETUP


9 kHz to 30 MHz




30 MHz to 1 GHz



**Above 1 GHz
Band edge & Harmonic(1 GHz to 18 GHz)**



Harmonic(18 GHz to 26.5 GHz)



5.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

5.6 TEST RESULT - 9 kHz TO 30 MHz

Please refer to the APPENDIX B.

Remark:

- (1) Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB).
- (2) Limit line = specific limits (dBuV) + distance extrapolation factor.

5.7 TEST RESULT - 30 MHz TO 1000 MHz

Please refer to the APPENDIX C.

5.8 TEST RESULT - ABOVE 1000 MHz

Please refer to the APPENDIX D.

Remark:

- (1) No limit: This is fundamental signal, the judgment is not applicable.
For fundamental signal judgment was referred to Peak output test.

6. BANDWIDTH

6.1 LIMIT

Section	Test Item	Limit
FCC 15.247(a)(2)	6 dB Bandwidth	≥ 500 kHz
	99% Emission Bandwidth	-

6.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- The following table is the setting of the spectrum analyzer:

For 6 dB Bandwidth:

Spectrum Parameters	Setting
Span	$>$ Measurement Bandwidth
RBW	shall be in the range of 1% to 5% of the OBW but not less than 100 kHz
VBW	$\geq 3 \times$ RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

For 99% Emission Bandwidth:

Spectrum Parameters	Setting
Span	Between 1.5 times and 5.0 times the OBW
RBW	30 kHz
VBW	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

6.6 TEST RESULTS

Please refer to the APPENDIX E.

7. MAXIMUM OUTPUT POWER

7.1 LIMIT

Section	Test Item	Limit
FCC 15.247(b)(3)	Maximum Output Power	1.0000 watt or 30.00 dBm

7.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- The following table is the setting of the spectrum analyzer:

Spectrum Parameters	Setting
Span	$\geq 3 \times \text{RBW}$
RBW	3 MHz
VBW	10 MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

7.6 TEST RESULTS

Please refer to the APPENDIX F.

8. CONDUCTED SPURIOUS EMISSION

8.1 LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak Output Power limits. If the transmitter complies with the Output Power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required.

8.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- The following table is the setting of the spectrum analyzer:

For Reference Level:

Spectrum Parameters	Setting
Span	≥ 1.5 times the bandwidth.
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

For Emission Level - Band edge:


Spectrum Parameters	Setting
Start Frequency	2300 MHz
Stop Frequency	2690 MHz
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

For Emission Level - Harmonic:

Spectrum Parameters	Setting
Start Frequency	30 MHz
Stop Frequency	26.5 GHz
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP**8.5 EUT OPERATION CONDITIONS**

The EUT was programmed to be in continuously transmitting mode.

8.6 TEST RESULTS

Please refer to the APPENDIX G.

9. POWER SPECTRAL DENSITY

9.1 LIMIT

Section	Test Item	Limit
FCC 15.247(e)	Power Spectral Density	8 dBm (in any 3 kHz)

9.2 TEST PROCEDURE


- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- The following table is the setting of the spectrum analyzer:

Spectrum Parameters	Setting
Span	1.5 times the DTS bandwidth
RBW	3 kHz
VBW	10 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP



9.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

9.6 TEST RESULTS

Please refer to the APPENDIX H.

10. MEASUREMENT INSTRUMENTS LIST

AC Power Line Conducted Emissions (Test Date: Jun. 03, 2026)					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EMI TEST RECEIVER	R&S	ESCI	100382	Nov. 21, 2026
2	TWO-LINE V-NETWORK	R&S	ENV216	101447	Nov. 21, 2026
3	BTL_RE_System	BTL	BTL_RE_System	N/A	N/A
4	Cable	N/A	SFT205-NMNM-9M-001	9M	Jul. 08, 2026
5	643 Shield Room	ETS	6*4*3	N/A	N/A

Radiated Emissions - 9 kHz to 30 MHz (Test Date: Jul. 15, 2026)					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Active Loop Antenna	Schwarzbeck	FMZB 1513-60	00025	Mar. 14, 2027
2	Receiver	Agilent	N9038A	MY52130039	Apr. 25, 2027
3	Cable	RegalWay	LMR400-NMNM-6m	N/A	Apr. 22, 2027
4	Cable	RegalWay	LMR400-NMRANM-3.5m	N/A	Apr. 22, 2027
5	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
6	966 Chamber room	CM	9*6*6	N/A	May 14, 2027

Radiated Emissions - 30 MHz to 1 GHz (Test Date: Jul. 13, 2026)					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	01462	Dec. 07, 2026
2	Attenuator	EMC INSTRUMENT	EMCI-N-6-06	AT-06009	Dec. 07, 2026
3	Preamplifier	EMC INSTRUMENT	EMC001330	980998	Apr. 25, 2027
4	Cable	RegalWay	LMR400-NMNM-12.5m	N/A	May 17, 2027
5	Cable	RegalWay	LMR400-NMNM-3m	N/A	May 17, 2027
6	Cable	RegalWay	LMR400-NMNM-0.5m	N/A	May 17, 2027
7	Receiver	Agilent	N9038A	MY52130039	Apr. 25, 2027
8	Positioning Controller	MF	MF-7802	N/A	N/A
9	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
10	966 Chamber room	CM	9*6*6	N/A	May 14, 2027

Radiated Emissions - 1 GHz - 18 GHz
(Test Date: Jul. 15, 2026)

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Receiver	Agilent	N9038A	MY52130039	Apr. 25, 2027
2	Preamplifier	EMC INSTRUMENT	EMC118A45SE	980888	Oct. 17, 2026
3	Double Ridged Guide Antenna	ETS	3115	75846	Mar. 03, 2027
4	Cable	RegalWay	RWLP50-4.0A-SMS M-12.5M	N/A	Jul. 07, 2027
5	Cable	RegalWay	RWLP50-4.0A-NM RASM-2.5M	N/A	Jul. 07, 2027
6	Cable	RegalWay	RWLP50-4.0A-NM RASM-0.8M	N/A	Jul. 07, 2027
7	966 Chamber room	CM	9*6*6	N/A	May 14, 2027
8	Filter	STI	STI15-9912	N/A	May 16, 2027
9	Positioning Controller	MF	MF-7802	N/A	N/A
10	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
11	Attenuator	RegalWay	RWA-201-S-10	N/A	Apr. 25, 2027

Radiated Emissions - Above 18 GHz
(Test Date: Jun. 05, 2026)

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Cable	Tonscend	HF160-KMKM-0.5M	N/A	Oct. 21, 2026
2	Cable	Tonscend	HF160-KMKM-5M	N/A	Oct. 21, 2026
3	Pre-Amplifier	EMC INSTRUMENT	EMC184045SE	980409	Nov. 21, 2026
4	DRG Horn Antenna	ETS	3116C	218942	Feb. 03, 2027
5	Positioning Controller	MF	MF-7802	N/A	N/A
6	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
7	EXA Spectrum Analyze	Keysight	N9010A	MY55150209	Oct. 17, 2026
8	966 Chamber room	CM	9*6*6	N/A	May 14, 2027


**Bandwidth &
Maximum Output Power &
Power Spectral Density &
Conducted Spurious Emission**
(Test Date: Jun. 02, 2026 ~ Jul. 16, 2026)

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyze	R&S	FSP40	100185	Apr. 25, 2027
2	Isolation attenuator	Z-Link	ASMA-16-18-2W	N/A	May 16, 2027
3	CTA	BTL	CTA	N/A	N/A

Remark: "N/A" denotes no model name, serial no. or calibration specified.
All calibration period of equipment list is one year.

APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS

Test Mode	TX Mode_4Mbps Channel 18	Phase	Line
-----------	--------------------------	-------	------




Suspected Note List									
	NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBμV]	Limit [dBμV]	Margin [dB]	Detector	Content
	1	0.1735	21.95	10.38	32.33	64.77	-32.43	QP	
*	2	0.1735	16.22	10.38	26.6	54.77	-28.16	AVG	
	3	0.8784	8.07	10.56	18.62	56	-37.38	QP	
	4	0.8784	1.27	10.56	11.83	46	-34.17	AVG	
	5	1.8704	7.59	10.63	18.22	56	-37.78	QP	
	6	1.8704	2.16	10.63	12.79	46	-33.21	AVG	
	7	13.9663	11.97	12.82	24.79	60	-35.21	QP	
	8	13.9663	5.99	12.82	18.81	50	-31.19	AVG	
	9	18.7617	9.84	14.07	23.91	60	-36.09	QP	
	10	18.7617	4.46	14.07	18.52	50	-31.48	AVG	
	11	26.4139	5.96	15.33	21.3	60	-38.7	QP	
	12	26.4139	-0.12	15.33	15.22	50	-34.78	AVG	

REMARKS:

- (1) Level = Reading + Factor.
- (2) Margin = Level - Limit.

Test Mode	TX Mode_4Mbps Channel 18	Phase	Neutral
-----------	--------------------------	-------	---------



Suspected Note List									
	NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBμV]	Limit [dBμV]	Margin [dB]	Detector	Content
	1	0.1539	21.13	10.42	31.55	65.78	-34.24	QP	
*	2	0.1539	17.67	10.42	28.09	55.78	-27.69	AVG	
	3	0.1735	21.95	10.43	32.38	64.77	-32.38	QP	
	4	0.1735	16.07	10.43	26.5	54.77	-28.27	AVG	
	5	0.3463	11.08	10.49	21.57	59.06	-37.49	QP	
	6	0.3463	3.95	10.49	14.44	49.06	-34.62	AVG	
	7	14.4744	10.04	13.17	23.2	60	-36.8	QP	
	8	14.4744	3.73	13.17	16.9	50	-33.1	AVG	
	9	18.9976	7.75	14.34	22.08	60	-37.92	QP	
	10	18.9976	2.5	14.34	16.83	50	-33.17	AVG	
	11	26.7296	7.39	15.58	22.96	60	-37.04	QP	
	12	26.7296	0.44	15.58	16.02	50	-33.98	AVG	


REMARKS:

(1) Level = Reading + Factor.

(2) Margin = Level - Limit.

APPENDIX B - RADIATED EMISSION - 9 KHZ TO 30 MHZ

Test Mode	TX Mode_4Mbps Channel 18	Polarization	Ant 0°
-----------	--------------------------	--------------	--------




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	0.030	63.24	20.55	83.79	118.15	-34.36	AVG	
2		0.042	55.18	20.61	75.79	115.06	-39.27	AVG	
3		0.051	52.39	20.65	73.04	113.52	-40.48	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX Mode_4Mbps Channel 18	Polarization	Ant 0°
-----------	--------------------------	--------------	--------




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	3.314	16.34	20.34	36.68	69.54	-32.86	QP	
2	3.821	15.21	20.34	35.55	69.54	-33.99	QP	
3	8.120	14.86	20.48	35.34	69.54	-34.20	QP	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX Mode_4Mbps Channel 18	Polarization	Ant 90°
-----------	--------------------------	--------------	---------




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	0.039	58.94	20.59	79.53	115.87	-36.34	AVG	
2	0.052	51.35	20.64	71.99	113.27	-41.28	AVG	
3	0.066	47.62	20.60	68.22	111.25	-43.03	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX Mode_4Mbps Channel 18	Polarization	Ant 90°
-----------	--------------------------	--------------	---------



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	3.075	15.24	20.34	35.58	69.54	-33.96	QP	
2 *	6.150	15.39	20.39	35.78	69.54	-33.76	QP	
3	14.836	14.71	20.38	35.09	69.54	-34.45	QP	


REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

APPENDIX C - RADIATED EMISSION - 30 MHZ TO 1000 MHZ

Test Mode	TX Mode_4Mbps Channel 18	Polarization	Vertical
-----------	--------------------------	--------------	----------




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		30.000	39.08	-11.64	27.44	40.00	-12.56	peak	
2		157.070	38.30	-11.09	27.21	43.52	-16.31	peak	
3		431.580	42.71	-7.27	35.44	46.02	-10.58	peak	
4		575.140	40.82	-4.39	36.43	46.02	-9.59	peak	
5	*	795.330	38.84	-0.65	38.19	46.02	-7.83	peak	
6		879.720	38.30	-0.49	37.81	46.02	-8.21	peak	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX Mode_4Mbps Channel 18	Polarization	Horizontal
-----------	--------------------------	--------------	------------



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		241.460	42.11	-12.41	29.70	46.02	-16.32	peak	
2		311.300	40.63	-10.14	30.49	46.02	-15.53	peak	
3		383.080	42.77	-8.48	34.29	46.02	-11.73	peak	
4		407.330	42.25	-8.07	34.18	46.02	-11.84	peak	
5		431.580	44.14	-7.27	36.87	46.02	-9.15	peak	
6	*	857.410	39.37	-0.64	38.73	46.02	-7.29	peak	


REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

APPENDIX D - RADIATED EMISSION - ABOVE 1000 MHZ

Test Mode	TX 2402 MHz_CH00_2Mbps	Polarization	Horizontal
-----------	------------------------	--------------	------------




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		2389.900	37.96	7.21	45.17	74.00	-28.83	peak	
2		2389.900	27.17	7.21	34.38	54.00	-19.62	AVG	
3		2390.000	33.53	7.21	40.74	74.00	-33.26	peak	
4		2390.000	22.74	7.21	29.95	54.00	-24.05	AVG	
5	X	2402.000	98.19	7.21	105.40	74.00	31.40	peak	No Limit
6	*	2402.000	87.40	7.21	94.61	54.00	40.61	AVG	No Limit

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2402 MHz_CH00_2Mbps	Polarization	Vertical
-----------	------------------------	--------------	----------




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		12012.480	46.21	10.66	56.87	74.00	-17.13	peak	
2	*	12012.480	35.42	10.66	46.08	54.00	-7.92	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2440 MHz_CH19_2Mbps	Polarization	Vertical
-----------	------------------------	--------------	----------




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		12202.240	47.21	10.48	57.69	74.00	-16.31	peak	
2	*	12202.240	36.42	10.48	46.90	54.00	-7.10	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2480 MHz_CH39_2Mbps	Polarization	Horizontal
-----------	------------------------	--------------	------------




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	X	2480.000	98.15	7.17	105.32	74.00	31.32	peak	No Limit
2	*	2480.000	87.36	7.17	94.53	54.00	40.53	AVG	No Limit
3		2483.500	47.54	7.17	54.71	74.00	-19.29	peak	
4		2483.500	36.75	7.17	43.92	54.00	-10.08	AVG	
5		2488.000	51.33	7.16	58.49	74.00	-15.51	peak	
6		2488.000	40.54	7.16	47.70	54.00	-6.30	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2480 MHz_CH39_2Mbps	Polarization	Vertical
-----------	------------------------	--------------	----------




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		12402.340	46.41	10.30	56.71	74.00	-17.29	peak	
2	*	12402.340	35.62	10.30	45.92	54.00	-8.08	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2404 MHz_CH00_4Mbps	Polarization	Horizontal
-----------	------------------------	--------------	------------




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		2380.000	35.72	7.23	42.95	74.00	-31.05	peak	
2		2380.000	18.33	7.23	25.56	54.00	-28.44	AVG	
3		2390.000	31.94	7.21	39.15	74.00	-34.85	peak	
4		2390.000	14.55	7.21	21.76	54.00	-32.24	AVG	
5	X	2404.000	97.81	7.21	105.02	74.00	31.02	peak	No Limit
6	*	2404.000	80.42	7.21	87.63	54.00	33.63	AVG	No Limit

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2404 MHz_CH00_4Mbps	Polarization	Vertical
-----------	------------------------	--------------	----------




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		12024.800	46.22	10.65	56.87	74.00	-17.13	peak	
2	*	12024.800	28.83	10.65	39.48	54.00	-14.52	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2440 MHz_CH09_4Mbps	Polarization	Vertical
-----------	------------------------	--------------	----------




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		12199.720	47.04	10.48	57.52	74.00	-16.48	peak	
2	*	12199.720	29.65	10.48	40.13	54.00	-13.87	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2476 MHz_CH18_4Mbps	Polarization	Horizontal
-----------	------------------------	--------------	------------




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	X	2476.000	98.41	7.18	105.59	74.00	31.59	peak	No Limit
2	*	2476.000	81.02	7.18	88.20	54.00	34.20	AVG	No Limit
3		2483.500	39.53	7.17	46.70	74.00	-27.30	peak	
4		2483.500	22.14	7.17	29.31	54.00	-24.69	AVG	
5		2483.950	53.74	7.17	60.91	74.00	-13.09	peak	
6		2483.950	36.35	7.17	43.52	54.00	-10.48	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2476 MHz_CH18_4Mbps	Polarization	Vertical
-----------	------------------------	--------------	----------




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		12379.920	46.81	10.32	57.13	74.00	-16.87	peak	
2	*	12379.920	29.42	10.32	39.74	54.00	-14.26	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2404 MHz_CH00_4Mbps	Polarization	Vertical
-----------	------------------------	--------------	----------




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		19215.500	56.38	2.69	59.07	83.50	-24.43	peak	
2		19215.500	40.81	2.69	43.50	63.50	-20.00	AVG	
3		19402.500	58.88	2.83	61.71	83.50	-21.79	peak	
4	*	19410.100	46.58	2.84	49.42	63.50	-14.08	AVG	
5		19598.000	53.58	2.99	56.57	83.50	-26.93	peak	
6		19598.000	38.25	2.99	41.24	63.50	-22.26	AVG	
7		19836.000	55.62	3.16	58.78	83.50	-24.72	peak	
8		19836.000	38.70	3.16	41.86	63.50	-21.64	AVG	
9		24018.000	53.98	4.80	58.78	83.50	-24.72	peak	
10		24018.000	38.31	4.80	43.11	63.50	-20.39	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2404 MHz_CH00_4Mbps	Polarization	Horizontal
-----------	------------------------	--------------	------------



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		19411.000	56.80	2.84	59.64	83.50	-23.86	peak	
2	*	19411.000	44.73	2.84	47.57	63.50	-15.93	AVG	
3		19844.500	55.78	3.16	58.94	83.50	-24.56	peak	
4		19844.500	42.75	3.16	45.91	63.50	-17.59	AVG	
5		21833.500	53.73	4.00	57.73	83.50	-25.77	peak	
6		21833.500	39.91	4.00	43.91	63.50	-19.59	AVG	


REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

The Worst Case:

Test Mode	TX 2440 MHz_CH19_2Mbps	Polarization	Vertical
-----------	------------------------	--------------	----------




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		2800.000	43.98	8.70	52.68	74.00	-21.32	peak	
2		2800.000	34.28	8.70	42.98	54.00	-11.02	AVG	
3		2994.000	43.41	9.69	53.10	74.00	-20.90	peak	
4	*	2994.000	34.12	9.69	43.81	54.00	-10.19	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX 2440 MHz_CH00_2Mbps	Polarization	Vertical
-----------	------------------------	--------------	----------



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		4875.000	45.43	2.95	48.38	74.00	-25.62	peak	
2		4875.000	34.64	2.95	37.59	54.00	-16.41	AVG	
3		12202.240	47.21	10.48	57.69	74.00	-16.31	peak	
4	*	12202.240	36.42	10.48	46.90	54.00	-7.10	AVG	
5		17880.000	43.90	11.64	55.54	74.00	-18.46	peak	
6		17880.000	34.09	11.64	45.73	54.00	-8.27	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.


(2) Margin Level = Measurement Value - Limit Value.

APPENDIX E - BANDWIDTH

Test Mode	TX Mode_2Mbps
-----------	---------------


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	99 % Occupied Bandwidth (MHz)	6 dB Bandwidth Min. Limit (MHz)	Test Result
00	2402	1.144	2.112	0.5	Pass
19	2440	1.160	2.112	0.5	Pass
39	2480	1.176	2.112	0.5	Pass

CH00




Date: 2.JUN.2026 10:15:32

CH19
6 dB Bandwidth




Date: 2.JUN.2026 10:29:50

CH39




Date: 2.JUN.2026 10:31:24


99 % Occupied Bandwidth



Date: 2.JUN.2026 10:15:44



Date: 2.JUN.2026 10:30:02




Date: 2.JUN.2026 10:31:36


Test Mode	TX Mode_4Mbps
-----------	---------------

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	99 % Occupied Bandwidth (MHz)	6 dB Bandwidth Min. Limit (MHz)	Test Result
00	2404	0.848	4.288	0.5	Pass
09	2440	2.176	4.272	0.5	Pass
18	2476	1.072	4.096	0.5	Pass

CH00




Date: 11.JUN.2026 20:45:48

CH09
6 dB Bandwidth



Date: 10.JUN.2026 21:38:27

CH18




Date: 11.JUN.2026 20:53:41


99 % Occupied Bandwidth



Date: 11.JUN.2026 20:46:38



Date: 10.JUN.2026 21:39:18




Date: 11.JUN.2026 20:54:43

APPENDIX F - MAXIMUM OUTPUT POWER


Test Mode	TX Mode_2Mbps
-----------	---------------

Frequency (MHz)	Output Power (dBm)	Output Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	7.51	0.0056	30.00	1.0000	Pass
2440	7.58	0.0057	30.00	1.0000	Pass
2480	7.76	0.0060	30.00	1.0000	Pass


Note: Output power = Measure result + Cable loss



Date: 16.JUL.2026 09:48:12



Date: 16.JUL.2026 09:48:32




Date: 16.JUL.2026 09:49:49


Test Mode	TX Mode_4Mbps
-----------	---------------

Frequency (MHz)	Output Power (dBm)	Output Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2404	7.58	0.0057	30.00	1.0000	Pass
2440	7.64	0.0058	30.00	1.0000	Pass
2476	7.79	0.0060	30.00	1.0000	Pass


Note: Output power = Measure result + Cable loss



Date: 16.JUL.2026 09:55:58



Date: 16.JUL.2026 09:56:36




Date: 16.JUL.2026 09:56:55

APPENDIX G - CONDUCTED SPURIOUS EMISSION


Test Mode TX Mode_2Mbps

Reference Level-CH00




Date: 2.JUN.2026 10:16:08

Reference Level-CH19




Date: 2.JUN.2026 10:30:26

Reference Level-CH39




Date: 2.JUN.2026 10:31:59

Bandedge-CH00




Date: 2.JUN.2026 10:16:20

Bandedge-CH39




Date: 2.JUN.2026 10:32:12

Harmonic-CH00




Date: 2.JUN.2026 10:28:44

Harmonic-CH19



Date: 2.JUN.2026 10:30:51


Harmonic-CH39



Date: 2.JUN.2026 10:32:25


Test Mode TX Mode_ 4Mbps

Reference Level-CH00




Date: 11.JUN.2026 20:49:51

Reference Level-CH09




Date: 10.JUN.2026 21:40:16

Reference Level-CH18




Date: 11.JUN.2026 20:56:00

Bandedge-CH00




Date: 11.JUN.2026 20:50:06

Bandedge-CH18




Date: 11.JUN.2026 20:56:40

Harmonic-CH00




Date: 11.JUN.2026 20:50:51

Harmonic-CH09



Date: 10.JUN.2026 21:41:35

Harmonic-CH18




Date: 11.JUN.2026 20:57:53


APPENDIX H - POWER SPECTRAL DENSITY

Test Mode	TX Mode_2Mbps
-----------	---------------


Channel	Frequency (MHz)	Power Spectral Density (dBm/3 kHz)	Max. Limit (dBm/3 kHz)	Test Result
00	2402	-7.88	8.00	Pass
19	2440	-8.09	8.00	Pass
39	2480	-7.56	8.00	Pass



Date: 2.JUN.2026 10:15:56




Date: 2.JUN.2026 10:30:14




Date: 2.JUN.2026 10:31:48

Test Mode	TX Mode_4Mbps
-----------	---------------


Channel	Frequency (MHz)	Power Spectral Density (dBm/3 kHz)	Max. Limit (dBm/3 kHz)	Test Result
00	2404	-13.77	8.00	Pass
09	2440	-11.20	8.00	Pass
18	2476	-11.18	8.00	Pass



Date: 11.JUN.2026 20:49:05



Date: 10.JUN.2026 21:40:04



Date: 11.JUN.2026 20:55:25

End of Test Report