

FCC Radio Test Report

FCC ID: RWO-RC30012301

This report concerns (check one): ☒Original Grant ☐Class II Change

Project No. : 1407C253
Equipment : LASER GAMING MOUSE
Model Name : RC30-012301
Applicant : Razer Inc.
Address : 2035 Corte Del Nogal, Suite 101. Carlsbad California
92011. USA

Date of Receipt : Jul. 31, 2014
Date of Test : Jul. 31, 2014~ Aug. 19, 2014
Issued Date : Aug. 20, 2014
Tested by : BTL Inc.

Testing Engineer : David Mao
(David Mao)

Technical Manager : Leo Hung
(Leo Hung)

Authorized Signatory : Steven Lu
(Steven Lu)

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (NML) of **R.O.C.**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

BTL's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL's** authorized written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Table of Contents	Page
1 . CERTIFICATION	6
2 . SUMMARY OF TEST RESULTS	7
2.1 TEST FACILITY	8
2.2 MEASUREMENT UNCERTAINTY	8
3 . GENERAL INFORMATION	9
3.1 GENERAL DESCRIPTION OF EUT	9
3.2 DESCRIPTION OF TEST MODES	11
3.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	12
3.4 DESCRIPTION OF SUPPORT UNITS	13
4 . EMC EMISSION TEST	14
4.1 CONDUCTED EMISSION MEASUREMENT	14
4.1.1 POWER LINE CONDUCTED EMISSION	14
4.1.2 TEST PROCEDURE	14
4.1.3 DEVIATION FROM TEST STANDARD	14
4.1.4 TEST SETUP	15
4.1.5 EUT OPERATING CONDITIONS	15
4.1.6 EUT TEST CONDITIONS	15
4.1.7 TEST RESULTS	15
4.2 RADIATED EMISSION MEASUREMENT	16
4.2.1 RADIATED EMISSION LIMITS	16
4.2.2 TEST PROCEDURE	17
4.2.3 DEVIATION FROM TEST STANDARD	17
4.2.4 TEST SETUP	18
4.2.5 EUT OPERATING CONDITIONS	19
4.2.6 EUT TEST CONDITIONS	19
4.2.7 TEST RESULTS (BELOW 30MHz)	19
4.2.8 TEST RESULTS (BETWEEN 30 – 1000 MHz)	19
4.2.9 TEST RESULTS (ABOVE 1000 MHz)	20
5 . BANDWIDTH TEST	21
5.1 TEST PROCEDURE	21
5.2 DEVIATION FROM STANDARD	21
5.3 TEST SETUP	21
5.4 EUT OPERATION CONDITIONS	21
5.5 EUT TEST CONDITIONS	21
5.6 TEST RESULTS	21
6 . MEASUREMENT INSTRUMENTS LIST AND SETTING	22
ATTACHMENT A - CONDUCTED EMISSION	23

Table of Contents	Page
ATTACHMENT B - RADIATED EMISSION (9KHZ to 30MHZ)	26
ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)	28
ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)	35
ATTACHMENT E - BANDWIDTH	48

REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
BTL-FCCP-1-1407C253	Original Issue.	Aug. 20, 2014

1. CERTIFICATION

Equipment : LASER GAMING MOUSE
Brand Name : RAZER
Model Name : RC30-012301
Applicant : Razer Inc.
Manufacturer : Razer (Asia-Pacific) Pte Ltd
Address : 514 Chai Chee Lane #07-01 ~ 06 Singapore 469029
Factory : RAZER TECHNOLOGY AND DEVELOPMENT (SHENZHEN) CO., LTD
Address : East Wing, 3rd Floor, Block 2, Phase 1 of Vision Shenzhen Business Park
Keji South Road, Hi-Tech Industrial Park, Shenzhen 518057, China
Date of Test : Jul. 31, 2014~ Aug. 19, 2014
Test Sample : Engineering Sample
Standard(s) : FCC Part15, Subpart C(15.249)/ ANSI C63.4-2009
RSS-GEN Issue 3, Dec 2010

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-1-1407C253) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC Part15, Subpart C (15.249)			
StandardSection	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.209 15.249	Radiated Spurious Emission	PASS	

NOTE:

(1)"N/A" denotes test is not applicable in this test report.

2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-C02/DG-CB03** at the location of No.3,Jinshagang 1st Road, ShiXia, Dalang Town,Dong Guan, China.523792

BTL's test firm number for FCC: 319330

2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U , (dB)	NOTE
DG-C02	CISPR	150 KHz ~ 30MHz	3.4	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U,(dB)	NOTE
DG-CB03	CISPR	9KHz~30MHz	V	3.79	
		9KHz~30MHz	H	3.57	
		30MHz ~ 200MHz	V	3.82	
		30MHz ~ 200MHz	H	3.60	
		200MHz ~ 1,000MHz	V	3.86	
		200MHz ~ 1,000MHz	H	3.94	
		1GHz~18GHz	V	3.12	
		1GHz~18GHz	H	3.68	
		18GHz~40GHz	V	4.15	
		18GHz~40GHz	H	4.14	

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	LASER GAMING MOUSE	
Brand Name	RAZER	
Model Name	RC30-012301	
Model Difference	N/A	
Product Description	Operation Frequency	2402~2480 MHz
	Modulation Technology	GFSK(1Mbps)
	Data rate	
	Field Strength	66.78dBuV/m(AV Max)
Power Source	1# Supplier from in-built battery 2# Supplier from USB Port	
Power Rating	1# DC 3.7V 1500mAh 2# DC 5V 500mA	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2402	28	2429	55	2456
02	2403	29	2430	56	2457
03	2404	30	2431	57	2458
04	2405	31	2432	58	2459
05	2406	32	2433	59	2460
06	2407	33	2434	60	2461
07	2408	34	2435	61	2462
08	2409	35	2436	62	2463
09	2410	36	2437	63	2464
10	2411	37	2438	64	2465
11	2412	38	2439	65	2466
12	2413	39	2440	66	2467
13	2414	40	2441	67	2468
14	2415	41	2442	68	2469
15	2416	42	2443	69	2470
16	2417	43	2444	70	2471
17	2418	44	2445	71	2472
18	2419	45	2446	72	2473
19	2420	46	2447	73	2474
20	2421	47	2448	74	2475
21	2422	48	2449	75	2476
22	2423	49	2450	76	2477
23	2424	50	2451	77	2478
24	2425	51	2452	78	2479
25	2426	52	2453	79	2480
26	2427	53	2454		
27	2428	54	2455		

3. Table for Filed Antenna

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain (dBi)
1	GainForce Technology Co.,Ltd	AT3216	Internal	N/A	0.5

3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Low Channel
Mode 2	TX Middle Channel
Mode 3	TX High Channel


For Radiated Test	
Final Test Mode	Description
Mode 1	TX Low Channel
Mode 2	TX Middle Channel
Mode 3	TX High Channel

Note:


(1) The measurements are performed at the high, middle, low available channels.

3.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted TX Mode:



RadiatedTX Mode:



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	Notebook	DELL	INSPIRON 1420	NA	NA	-

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	1.5M	USB Cable

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION (FREQUENCY RANGE 150KHZ-30MHZ)

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 -0.5	66 to 56*	56 to 46*
0.50 -5.0	56	46
5.0 -30.0	60	50

Note:

(1) The limit of " * " decreases with the logarithm of the frequency

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


4.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

The EUT was programmed to be in continuously transmitting mode.

4.1.6 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

4.1.7 TEST RESULTS

Please refer to the Attachment A.

Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of "Note". If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform in this case, a "*" marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS (FCC 15.209)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Harmonic emissions limits comply with below 54 dBuV/m at 3m. Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed.

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RADIATED EMISSION MEASUREMENT (FCC 15.209)

FREQUENCY (MHz)	(dBuV/m) (at 3m)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RADIATED EMISSION MEASUREMENT (FCC Part 15.249)

FCC Part15 (15.249) , Subpart C	
Limit	Frequency Range (MHz)
Field strength of fundamental 50000 μ V/m (94 dB μ V/m) @ 3 m	2400-2483.5
Field strength of harmonics 500 μ V/m (54 dB μ V/m) @ 3 m	Above 2483.5

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz for PK/AVG detector
Start ~ Stop Frequency	90kHz~110kHz for QP detector
Start ~ Stop Frequency	110kHz~490kHz for PK/AVG detector
Start ~ Stop Frequency	490kHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

4.2.2 TEST PROCEDURE


- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then AV detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) For radiated emissions below 30MHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: DC 3.7V

4.2.7 TEST RESULTS (BELOW 30MHz)

Please refer to the Attachment B.

Remark

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);.
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor..

4.2.8 TEST RESULTS (BETWEEN 30 – 1000 MHz)

Please refer to the Attachment C

Remark :

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.
- (3) Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Peak detector mode or QP detector mode of the emission .

4.2.9 TEST RESULTS (ABOVE 1000 MHz)

Please refer to the Attachment D

Remark :

- (1) All readings are Peak unless otherwise stated QP in column of 『Note 』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (2) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (3) Data of measurement within this frequency range shown “ * ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (4) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (5) EUT Orthogonal Axis :
“X” - denotes Laid on Table ; “Y” - denotes Vertical Stand ; “Z” - denotes Side Stand
- (6) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (7) The average value of fundamental frequency is:
Average = Peak value + 20log(Duty cycle) ,Final AV=PK-19.49

5. BANDWIDTH TEST

5.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

5.2 DEVIATION FROM STANDARD

No deviation.

5.3 TEST SETUP



5.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

5.5 EUT TEST CONDITIONS

Temperature: 25°C
Relative Humidity: 55%
Test Voltage: DC 3.7V

5.6 TEST RESULTS

Please refer to the Attachment E

6. MEASUREMENT INSTRUMENTS LIST AND SETTING

Conducted Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	EMCO	3816/2	00052765	Mar. 29, 2015
2	LISN	R&S	ENV216	101447	Mar. 29, 2015
3	Test Cable	N/A	C_17	N/A	Mar. 14, 2015
4	EMI TEST RECEIVER	R&S	ESCS30	833364/017	Mar. 29, 2015
5	50Ω Terminator	SHX	TF2-3G-A	08122902	Mar. 29, 2015

Radiated Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarbeck	VULB9160	9160-3232	Mar. 29, 2015
2	Amplifier	HP	8447D	2944A09673	Mar. 29, 2015
3	Test Receiver	R&S	ESCI	100382	Mar. 29, 2015
4	Test Cable	N/A	C-01_CB03	N/A	Jul. 01, 2015
5	Antenna	ETS	3115	00075789	Mar. 29, 2015
6	Amplifier	Agilent	8449B	3008A02274	Mar. 29, 2015
7	Spectrum	Agilent	E4408B	US39240143	Nov. 09, 2014
8	Test Cable	HUBER+SUHNER	C-45	N/A	Jan. 14, 2015
9	Controller	CT	SC100	N/A	N/A
10	Horn Antenna	EMCO	3115	9605-4803	Mar. 29, 2015
11	Active Loop Antenna	R&S	HFH2-Z2	830749/020	Mar. 29, 2015
12	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Oct. 22, 2014

Bandwidth					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 11, 2014


Antenna Conducted Spurious Emission					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 11, 2014

Remark: "N/A" denotes no model name, serial no. or calibration specified.
All calibration period of equipment list is one year.

ATTACHMENT A - CONDUCTED EMISSION

Test Mode: TX Mode


Line



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
		MHz	Level	Factor	ment			Detector	Comment
			dBuV	dB	dBuV	dBuV	dB		
1		0.2477	10.93	9.56	20.49	61.83	-41.34	peak	
2		0.6813	11.95	9.63	21.58	56.00	-34.42	peak	
3		2.4312	13.78	9.73	23.51	56.00	-32.49	peak	
4		3.8711	13.82	9.81	23.63	56.00	-32.37	peak	
5		7.5040	15.21	10.00	25.21	60.00	-34.79	peak	
6	*	28.5703	18.21	10.85	29.06	60.00	-30.94	peak	

Test Mode: TX Mode

Neutral



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
		MHz	Level	Factor	ment			Detector	Comment
			dBuV	dB	dBuV	dBuV	dB		
1		0.3220	9.99	9.62	19.61	59.66	-40.05	peak	
2		0.4470	11.24	9.63	20.87	56.93	-36.06	peak	
3		1.0836	11.33	9.68	21.01	56.00	-34.99	peak	
4		1.5523	12.05	9.71	21.76	56.00	-34.24	peak	
5		7.8360	15.05	9.99	25.04	60.00	-34.96	peak	
6	*	21.6328	15.42	10.56	25.98	60.00	-34.02	peak	

ATTACHMENT B - RADIATED EMISSION (9KHZ to 30MHZ)

Test Mode: TX Mode

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
0.0146	0°	14.16	24.64	38.80	104.32	-65.52	AVG
0.0146	0°	15.03	24.64	39.67	124.32	-84.65	PEAK
0.0293	0°	8.50	23.71	32.21	98.27	-66.06	AVG
0.0293	0°	9.41	23.71	33.12	118.27	-85.15	PEAK
0.0353	0°	4.85	23.33	28.18	96.65	-68.47	AVG
0.0353	0°	5.65	23.33	28.98	116.65	-87.67	PEAK
0.0382	0°	2.54	23.15	25.69	95.96	-70.28	AVG
0.0382	0°	3.81	23.15	26.96	115.96	-89.01	PEAK
2.0471	0°	27.64	19.47	47.11	69.54	-22.43	QP
3.3056	0°	22.38	18.93	41.31	69.54	-28.23	QP


Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
0.0132	90°	13.54	24.30	37.84	125.19	-87.35	AVG
0.0132	90°	14.68	24.30	38.98	145.19	-106.21	PEAK
0.0284	90°	7.58	23.77	31.35	118.54	-87.19	AVG
0.0284	90°	8.98	23.77	32.75	138.54	-105.79	PEAK
0.0337	90°	4.41	23.43	27.84	117.05	-89.21	AVG
0.0337	90°	5.74	23.43	29.17	137.05	-107.88	PEAK
0.0476	90°	2.28	22.55	24.83	114.05	-89.22	AVG
0.0476	90°	4.16	22.55	26.71	134.05	-107.34	PEAK
2.0380	90°	28.17	19.48	47.65	69.54	-21.89	QP
3.1068	90°	20.85	18.91	39.76	69.54	-29.78	QP

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)


Test Mode:	TX Low Channel
------------	----------------



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		81.4100	36.81	-17.23	19.58	40.00	-20.42	peak	
2		138.6400	30.06	-13.15	16.91	43.50	-26.59	peak	
3		165.8000	29.92	-13.22	16.70	43.50	-26.80	peak	
4		564.4700	27.96	-7.93	20.03	46.00	-25.97	peak	
5		670.2000	27.91	-5.06	22.85	46.00	-23.15	peak	
6	*	948.5900	27.41	-0.25	27.16	46.00	-18.84	peak	

Test Mode: TX Low Channel


Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	X	37.7600	32.37	-14.38	17.99	40.00	-22.01	peak	
2	X	71.7100	31.13	-16.38	14.75	40.00	-25.25	peak	
3	X	243.4000	36.76	-14.03	22.73	46.00	-23.27	peak	
4	X	414.1200	27.77	-9.27	18.50	46.00	-27.50	peak	
5	X	672.1400	28.47	-5.06	23.41	46.00	-22.59	peak	
6	X	938.8900	27.29	-0.50	26.79	46.00	-19.21	peak	

Test Mode: TX Middle Channel


Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		81.4100	36.11	-17.23	18.88	40.00	-21.12	peak	
2		138.6400	29.77	-13.15	16.62	43.50	-26.88	peak	
3		289.9600	26.62	-11.18	15.44	46.00	-30.56	peak	
4		669.2300	28.55	-5.06	23.49	46.00	-22.51	peak	
5		777.8700	27.58	-3.66	23.92	46.00	-22.08	peak	
6	*	935.9800	27.79	-0.58	27.21	46.00	-18.79	peak	

Test Mode: TX Middle Channel


Horizontal



No	Mk	Freq MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	37.7600	32.16	-14.38	17.78	10.00	-22.22	peak	
2		77.5300	31.95	-16.87	15.08	40.00	-24.92	peak	
3		243.4000	36.38	-14.03	22.35	40.00	-23.65	peak	
4		402.4800	27.30	-9.48	17.82	46.00	-28.18	peak	
5		473.2900	28.02	-9.50	18.52	46.00	-27.48	peak	
6		980.6000	27.08	0.33	26.75	54.00	27.25	peak	

Test Mode: TX High Channel


Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		34.8500	33.50	-14.75	18.75	40.00	-21.25	peak	
2		81.4100	36.36	-17.23	19.13	40.00	-20.87	peak	
3		132.8200	30.03	-13.09	16.94	43.50	-26.56	peak	
4		215.2700	37.58	-15.13	22.45	43.50	-21.05	peak	
5		648.8600	27.86	-5.21	22.65	46.00	-23.35	peak	
6	*	953.4400	26.86	-0.23	26.63	46.00	-19.37	peak	

Test Mode: TX High Channel

Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		37.7600	32.16	-14.38	17.78	40.00	-22.22	peak	
2		77.5300	31.45	-16.87	14.58	40.00	-25.42	peak	
3		243.4000	38.49	-14.03	24.46	46.00	-21.54	peak	
4		548.9500	28.41	-7.99	20.42	46.00	-25.58	peak	
5		797.2700	27.52	-2.99	24.53	46.00	-21.47	peak	
6	*	949.5600	27.17	-0.22	26.95	46.00	-19.05	peak	

ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)

Orthogonal Axis :	X
Test Mode :	TX Low Channel


Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2400.000	24.34	31.89	56.23	74.00	-17.77	peak	
2	*	2400.000	13.68	31.89	45.57	54.00	-8.43	AVG	
3		2401.900	38.33	31.89	70.22	114.0	-43.78	peak	
4		2402.250	30.52	31.89	62.41	94.00	-31.59	AVG	


Orthogonal Axis :	X
Test Mode :	TX Low Channel

Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4803.940	44.22	3.58	47.80	74.00	-26.20	peak	
2	*	4803.960	33.74	3.58	37.32	54.00	-16.68	AVG	
3		1600.820	41.22	-5.18	36.04	54.00	-17.96	AVG	
4		1600.880	47.92	-5.18	42.74	74.00	-31.26	peak	

Orthogonal Axis :	X
Test Mode :	TX Low Channel



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2400.000	24.95	31.89	56.84	74.00	-17.16	peak	
2	*	2400.000	13.75	31.89	45.64	54.00	-8.36	AVG	
3		2401.900	42.34	31.89	74.23	114.0	-39.77	peak	
4		2402.200	31.89	31.89	66.78	94.00	-27.22	AVG	


Orthogonal Axis :	X
Test Mode :	TX Low Channel



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	4803.940	31.99	3.58	35.57	54.00	-18.43	AVG	
2		4803.970	41.54	3.58	45.12	74.00	-28.88	peak	
3		1600.800	40.16	-5.18	34.98	54.00	-19.02	AVG	
4		1600.850	46.68	-5.18	41.50	74.00	-32.50	peak	


Orthogonal Axis :	X
Test Mode :	TX Middle Channel

Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2440.800	38.51	31.95	70.46	114.0	-43.54	peak	
2	*	2441.200	30.84	31.95	62.79	94.00	-31.21	AVG	


Orthogonal Axis :	X
Test Mode :	TX Middle Channel



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4881.600	40.98	3.73	44.71	74.00	-29.29	peak	
2		4881.950	29.71	3.73	33.44	54.00	-20.56	AVG	
3	*	1626.820	41.32	-5.03	36.29	54.00	-17.71	AVG	
4		1626.790	47.81	-5.03	42.78	74.00	-31.22	peak	


Orthogonal Axis :	X
Test Mode :	TX Middle Channel

Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2440.800	38.51	31.95	70.46	114.0	-43.54	peak	
2	*	2441.200	30.84	31.95	62.79	94.00	-31.21	AVG	

Orthogonal Axis :	X
Test Mode :	TX Middle Channel



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4881.890	42.78	3.73	46.51	74.00	-27.49	peak	
2		4881.970	32.26	3.73	35.99	54.00	-18.01	AVG	
3	*	1626.815	42.08	-5.03	37.05	54.00	-16.95	AVG	
4		1626.715	47.51	-5.03	42.48	74.00	-31.52	peak	


Orthogonal Axis :	X
Test Mode :	TX High Channel



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2479.950	38.31	32.00	70.31	114.0	-43.69	peak	
2		2480.200	30.55	32.00	62.55	94.00	-31.45	AVG	
3		2483.500	24.00	32.01	56.01	74.00	-17.99	peak	
4	*	2483.500	13.53	32.01	45.54	54.00	-8.46	AVG	

Orthogonal Axis :	X
Test Mode :	TX High Channel


Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4960.010	31.02	3.83	34.90	54.00	-19.10	AVG	
2		4960.170	42.23	3.83	46.11	74.00	-27.89	peak	
3	*	1652.815	41.55	-4.83	36.67	54.00	-17.33	AVG	
4		1652.960	47.79	-4.83	42.91	74.00	-31.09	peak	


Orthogonal Axis :	X
Test Mode :	TX High Channel

Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2479.950	37.99	32.00	69.99	114.0	-44.01	peak	
2		2480.250	30.25	32.00	62.25	94.00	-31.75	AVG	
3		2483.500	22.97	32.01	54.98	74.00	-19.02	peak	
4	*	2483.500	13.51	32.01	45.52	54.00	-8.48	AVG	


Orthogonal Axis :	X
Test Mode :	TX High Channel



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4959.870	29.55	3.88	33.43	54.00	-20.57	AVG	
2		4959.960	40.28	3.88	44.16	74.00	-29.84	peak	
3	*	1652.820	41.11	-4.88	36.23	54.00	-17.77	AVG	
4		1652.750	47.16	-4.88	42.28	74.00	-31.72	peak	


ATTACHMENT E - BANDWIDTH

TX Low Channel




Date: 11.AUG.2014 19:36:03

TX Middle Channel



Date: 11.AUG.2014 19:40:25

TX High Channel



Date: 11.AUG.2014 19:43:50