6. 6dB&26dB&99% Bandwidth Test

6.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	N9030A	MY51380221	Oct. 29, 14	1Year
2.	Attenuator (20dB)	Agilent	8491B	MY39262165	Apr. 28,15	1 Year
3.	RF Cable	Hubersuhner	SUCOFLEX102	28620/2	Apr. 28,15	1 Year

6.2. Limit

6dB Bandwidth should be not less than 500kHz

6.3. Test Procedure

6dB Bandwidth:
The transmitter output was connected to a spectrum analyzer, The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 300 KHz VBW for signal width below 20MHz and 300KHz RBW ,1MHz VBW for Above 20MHz signal Bandwidth.

26dB Bandwidth:
The transmitter output was connected to a spectrum analyzer, The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 300 KHz VBW The 26dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 26dB.

6.4. Test Results

5180-5240MHz Band:
6dB bandwidth

EUT: Notebook		
M/N: RZ09-0168		
Test date: 2015-08-20	Pressure: 101.3±1.0 kpa	Humidity: 49.6±3.0%
Tested by: Alice_Yang	Test site: RF site	Temperature:22.5±0.6 ℃

Test Mode	CH	6dB bandwidth (MHz)		Limit (KHz)
		ANT0	ANT1	
11a	CH36	15.16	15.16	> 500
	CH40	15.30	14.48	> 500
	CH48	15.55	14.67	> 500
11n HT20	CH36	12.69	14.74	> 500
	CH40	14.71	16.57	> 500
	CH48	15.01	14.98	> 500
11n HT40	CH38	35.19	35.55	> 500
	CH46	35.41	35.59	> 500
11ac VHT20	CH36	16.56	15.12	> 500
	CH40	12.79	15.10	> 500
	CH48	12.18	15.10	> 500
11ac VHT40	CH38	35.29	35.54	> 500
	CH46	35.69	35.39	> 500
11ac VHT80	CH42	74.09	74.70	> 500
Conclusion：PASS				

26dB bandwidth

EUT: Notebook		
M/N: RZ09-0168		
Test date: 2015-08-20	Pressure: 101.3±1.0 kpa	Humidity: 49.6±3.0%
Tested by: Alice_Yang	Test site: RF site	Temperature:22.5±0.6 ℃

Test Mode	CH	26dB bandwidth (MHz)		Limit (KHz)
		ANT0	ANT1	
11a	CH36	18.43	18.24	N/A
	CH40	18.36	18.96	N/A
	CH48	18.43	18.41	N/A
11n HT20	CH36	18.85	19.53	N/A
	CH40	18.83	18.81	N/A
	CH48	18.88	19.22	N/A
11n HT40	CH38	40.42	40.01	N/A
	CH46	39.97	39.58	N/A
11ac VHT20	CH36	18.87	19.51	N/A
	CH40	19.58	19.49	N/A
	CH48	19.94	19.87	N/A
11ac VHT40	CH38	39.59	39.62	N/A
	CH46	39.78	40.18	N/A
11ac VHT80	CH42	80.43	80.28	N/A
Conclusion：PASS				

99% bandwidth

Test Mode	Frequency (MHz)	99% bandwidth (MHz)		Limit (KHz)
		ANT0	ANT1	
11a	5180	16.233	16.247	N/A
	5200	16.250	16.245	N/A
	5240	16.271	16.270	N/A
11n HT20	5180	17.450	17.458	N/A
	5200	17.429	17.456	N/A
	5240	17.459	17.459	N/A
11n HT40	5190	35.723	35.773	N/A
	5230	35.775	35.856	N/A
11ac VHT20	5180	17.467	17.456	N/A
	5200	17.427	17.449	N/A
	5240	17.455	17.468	N/A
11ac VHT40	5190	35.740	35.726	N/A
	5290	35.792	35.828	N/A
11ac VHT80	5210	74.892	74.941	N/A
Conclusion：PASS				

5260-5320MHz Band:
6dB bandwidth

EUT: Notebook		
M/N: RZ09-0168		
Test date: 2015-08-20	Pressure: 101.3±1.0 kpa	Humidity: 49.6±3.0%
Tested by: Alice_Yang	Test site: RF site	Temperature:22.5±0.6 ℃

Test Mode	CH	6dB bandwidth (MHz)		Limit (KHz)
		ANT0	ANT1	
11a	CH52	15.77	16.30	> 500
	CH60	14.70	14.38	> 500
	CH64	15.12	14.06	> 500
11n HT20	CH52	14.03	13.86	> 500
	CH60	15.70	16.41	> 500
	CH64	15.09	14.52	> 500
11n HT40	CH54	35.39	34.91	> 500
	CH62	35.49	35.59	> 500
11ac VHT20	CH52	14.23	15.03	> 500
	CH60	15.12	13.94	> 500
	CH64	14.43	15.92	> 500
11ac VHT40	CH54	35.27	35.41	> 500
	CH62	34.91	35.33	> 500
11ac VHT80	CH58	74.42	73.94	> 500
Conclusion：PASS				

26dB bandwidth

EUT: Notebook		
M/N: RZ09-0168		
Test date: 2015-08-20	Pressure: 101.3±1.0 kpa	Humidity: 49.6±3.0%
Tested by: Alice_Yang	Test site: RF site	Temperature:22.5±0.6 ℃

Test Mode	CH	26dB bandwidth (MHz)		Limit (KHz)
		ANT0	ANT1	
11a	CH52	18.32	18.48	N/A
	CH60	18.25	18.13	N/A
	CH64	18.53	18.43	N/A
11n HT20	CH52	18.84	19.11	N/A
	CH60	19.43	18.77	N/A
	CH64	19.28	19.05	N/A
11n HT40	CH54	39.90	40.66	N/A
	CH62	40.11	39.65	N/A
11ac VHT20	CH52	19.27	19.36	N/A
	CH60	18.79	18.76	N/A
	CH64	18.88	18.81	N/A
11ac VHT40	CH54	39.23	40.51	N/A
	CH62	39.59	40.11	N/A
11ac VHT80	CH58	79.08	81.00	N/A
Conclusion：PASS				

99% bandwidth

Test Mode	Frequency (MHz)	99% bandwidth (MHz)		Limit (KHz)
		ANT0	ANT1	
11a	5260	16.268	16.282	N/A
	5300	16.252	16.257	N/A
	5320	16.244	16.284	N/A
11n HT20	5260	17.456	17.473	N/A
	5300	17.444	17.473	N/A
	5320	17.455	17.463	N/A
11n HT40	5270	35.737	35.767	N/A
	5310	35.724	35.783	N/A
11ac VHT20	5260	17.429	17.449	N/A
	5300	17.425	17.465	N/A
	5320	17.457	17.455	N/A
11ac VHT40	5270	35.713	35.777	N/A
	5310	35.733	35.765	N/A
11ac VHT80	5290	74.526	74.810	N/A
Conclusion：PASS				

5500-5700MHz Band:
6dB bandwidth

EUT: Notebook		
M/N: RZ09-0168		
Test date: 2015-08-20	Pressure: 101.3±1.0 kpa	Humidity: 49.6±3.0%
Tested by: Alice_Yang	Test site: RF site	Temperature:22.5±0.6 ℃

Test Mode	CH	6dB bandwidth (MHz)		Limit (KHz)
		ANT0	ANT1	
11a	CH100	14.95	14.66	> 500
	CH120	15.28	15.59	> 500
	CH140	14.48	15.35	> 500
11n HT20	CH100	15.45	15.04	> 500
	CH120	15.44	15.42	> 500
	CH140	14.14	15.01	> 500
11n HT40	CH102	35.59	35.54	> 500
	CH134	34.31	35.44	> 500
11ac VHT20	CH100	15.97	14.72	> 500
	CH120	14.64	14.20	> 500
	CH140	13.45	16.54	> 500
11ac VHT40	CH102	34.50	35.58	> 500
	CH134	35.55	35.49	> 500
11ac VHT80	CH106	75.79	76.01	> 500
Conclusion：PASS				

26dB bandwidth

EUT: Notebook		
M/N: RZ09-0168		
Test date: 2015-08-20	Pressure: 101.3±1.0 kpa	Humidity: 49.6±3.0%
Tested by: Alice_Yang	Test site: RF site	Temperature:22.5±0.6 ℃

Test Mode	CH	26dB bandwidth (MHz)		Limit (KHz)
		ANT0	ANT1	
11a	CH100	20.58	20.82	N/A
	CH120	18.30	18.30	N/A
	CH140	18.47	20.02	N/A
11n HT20	CH100	19.89	19.50	N/A
	CH120	19.02	19.34	N/A
	CH140	18.82	19.03	N/A
11n HT40	CH102	41.50	40.27	N/A
	CH134	39.66	39.74	N/A
11ac VHT20	CH100	20.64	19.29	N/A
	CH120	18.81	18.75	N/A
	CH140	18.84	18.81	N/A
11ac VHT40	CH102	42.40	41.34	N/A
	CH134	40.12	39.43	N/A
11ac VHT80	CH106	81.00	83.04	N/A
Conclusion：PASS				

99% bandwidth

Test Mode	Frequency (MHz)	99% bandwidth (MHz)		Limit (KHz)
		ANT0	ANT1	
11a	5500	16.302	16.302	N/A
	5600	16.261	16.279	N/A
	5700	16.275	16.235	N/A
11n HT20	5500	17.470	17.505	N/A
	5600	17.447	17.457	N/A
	5700	17.429	17.459	N/A
11n HT40	5510	35.857	35.789	N/A
	5670	35.843	35.779	N/A
11ac VHT20	5500	17.475	17.481	N/A
	5600	17.479	17.459	N/A
	5700	17.460	17.460	N/A
11ac VHT40	5510	35.829	35.863	N/A
	5670	35.803	35.752	N/A
11ac VHT80	5530	75.334	75.311	N/A
Conclusion：PASS				

5745-5825MHz Band:
6dB bandwidth

EUT: Notebook		
M/N: RZ09-0168		
Test date: 2015-08-20	Pressure: 101.3±1.0 kpa	Humidity: 49.6±3.0%
Tested by: Alice_Yang	Test site: RF site	Temperature:22.5±0.6 ℃

Test Mode	CH	6dB bandwidth (MHz)		Limit (KHz)
		ANT0	ANT1	
11a	CH149	15.34	16.06	> 500
	CH157	14.42	15.53	> 500
	CH165	13.82	14.36	> 500
11n HT20	CH149	15.11	15.29	> 500
	CH157	15.07	14.01	> 500
	CH165	15.05	15.43	> 500
11n HT40	CH151	35.17	35.35	> 500
	CH159	35.29	35.33	> 500
11ac VHT20	CH149	12.58	15.10	> 500
	CH157	13.88	16.84	> 500
	CH165	14.72	15.31	> 500
11ac VHT40	CH151	35.59	35.56	> 500
	CH159	35.47	35.23	> 500
11ac VHT80	CH155	75.47	75.23	> 500
Conclusion：PASS				

26dB bandwidth

EUT: Notebook		
M/N: RZ09-0168		
Test date: 2015-08-20	Pressure: 101.3±1.0 kpa	Humidity: 49.6±3.0%
Tested by: Alice_Yang	Test site: RF site	Temperature:22.5±0.6 ℃

Test Mode	CH	26dB bandwidth (MHz)		Limit (KHz)
		ANT0	ANT1	
11a	CH149	20.95	18.19	N/A
	CH157	19.16	17.81	N/A
	CH165	21.10	18.21	N/A
11n HT20	CH149	19.10	18.81	N/A
	CH157	20.39	18.76	N/A
	CH165	19.49	19.04	N/A
11n HT40	CH151	41.19	40.07	N/A
	CH159	43.52	39.80	N/A
11ac VHT20	CH149	19.07	18.86	N/A
	CH157	19.44	18.69	N/A
	CH165	19.29	19.50	N/A
11ac VHT40	CH151	41.08	39.99	N/A
	CH159	42.07	39.52	N/A
11ac VHT80	CH155	81.37	80.71	N/A
Conclusion：PASS				

99% bandwidth

Test Mode	Frequency (MHz)	99% bandwidth (MHz)		Limit (KHz)
		ANT0	ANT1	
11a	5745	16.259	16.288	N/A
	5785	16.298	16.252	N/A
	5825	16.319	16.299	N/A
11n HT20	5745	17.467	17.455	N/A
	5785	17.490	17.451	N/A
	5825	17.490	17.476	N/A
11n HT40	5755	35.829	35.789	N/A
	5795	35.836	35.736	N/A
11ac VHT20	5745	17.454	17.475	N/A
	5785	17.488	17.436	N/A
	5825	17.507	17.462	N/A
11ac VHT40	5755	35.851	35.767	N/A
	5795	35.817	35.762	N/A
11ac VHT80	5775	75.048	74.918	N/A
Conclusion：PASS				

5180-5240MHz Band:

6dB bandwidth

ANT 0

11a	**11n HT20**
5180MHz	5180MHz
	
5200MHz	5200MHz
	
5240MHz	5240MHz
	

11n HT40

5190MHz

5200MHz



5230MHz

5240MHz



11ac VHT20

5180MHz



11ac VHT40

5190MHz

	11ac VHT80
5230MHz	5210MHz
	

5180-5240MHz Band:

6dB bandwidth

ANT 1

11a	**11n HT20**
5180MHz	5180MHz
	
5200MHz	5200MHz
	
5240MHz	5240MHz

11n HT40

5190MHz

5200MHz



5230MHz



5240MHz



11ac VHT20

5180MHz

11ac VHT40

5190MHz

	11ac VHT80
5230MHz	5210MHz

5180-5240MHz Band:

26dB bandwidth

ANT 0

11a	**11n HT20**
5180MHz	5180MHz
5200MHz	5200MHz
	
5240MHz	5240MHz
	

11n HT40

5190MHz

5200MHz



5230MHz

5240MHz



11ac VHT20

5180MHz

11ac VHT40

5190MHz

	11ac VHT80
5230MHz	5210MHz
	

5180-5240MHz Band:

26dB bandwidth

ANT 1

11a	**11n HT20**
5180MHz	5180MHz
	
5200MHz	5200MHz
5240MHz	5240MHz

11n HT40

5190MHz

5200MHz

5230MHz



5240MHz

11ac VHT20

5180MHz



11ac VHT40

5190MHz



	11ac VHT80
5230MHz	5210MHz

5260-5320MHz Band:

6dB bandwidth

ANT 0

11a	**11n HT20**
5260MHz	5260MHz
	
5300MHz	5300MHz
	
5320MHz	5320MHz
	

11n HT40

5270MHz

5300MHz

5310MHz

5320MHz



11ac VHT20

5260MHz

11ac VHT40

5270MHz

	11ac VHT80
5310MHz	5290MHz
	

5260-5320MHz Band:

6dB bandwidth

ANT 1

11a	**11n HT20**
5260MHz	5260MHz
	
5300MHz	5300MHz
	
5320MHz	5320MHz

11n HT40

5270MHz

5300MHz



5310MHz

5320MHz

11ac VHT20

5260MHz



11ac VHT40

5270MHz

	11ac VHT80
5310MHz	5290MHz

5260-5320MHz Band:

26dB bandwidth

ANT 0

11a	**11n HT20**
5260MHz	5260MHz
	
5300MHz	5300MHz
5320MHz	5320MHz

11n HT40

5270MHz

5300MHz



5310MHz



5320MHz



11ac VHT20

5260MHz

11ac VHT40

5270MHz

	11ac VHT80
5310MHz	5290MHz
	

5260-5320MHz Band:

26dB bandwidth

ANT 1

11a	**11n HT20**
5260MHz	5260MHz
	
5300MHz	5300MHz
	
5320MHz	5320MHz

11n HT40

5270MHz

5300MHz

5310MHz

5320MHz



11ac VHT20

5260MHz



11ac VHT40

5270MHz

	11ac VHT80
5310MHz	5290MHz
	

5500-5700MHz Band:

6dB bandwidth

ANT 0

11a	**11n HT20**
5500MHz	5500MHz
	
5600MHz	5600MHz
	
5700MHz	5700MHz

11n HT40

5510MHz

5600MHz



5670MHz



5700MHz



11ac VHT20

5500MHz



11ac VHT40

5510MHz

	11ac VHT80
5670MHz	5530MHz
	

5500-5700MHz Band:

6dB bandwidth

ANT 1

11a	**11n HT20**
5500MHz	5500MHz
	
5600MHz	5600MHz
	
5700MHz	5700MHz

11n HT40

5510MHz



5600MHz

5670MHz

5700MHz



11ac VHT20

5500MHz



11ac VHT40

5510MHz

	11ac VHT80
5670MHz	5530MHz
	

5500-5700MHz Band:

26dB bandwidth

ANT 0

11a	**11n HT20**
5500MHz	5500MHz
	
5600MHz	5600MHz
	
5700MHz	5700MHz

11n HT40

5510MHz

5600MHz

5670MHz

5700MHz

11ac VHT20

5500MHz



11ac VHT40

5510MHz

	11ac VHT80
5670MHz	5530MHz

5500-5700MHz Band:

26dB bandwidth

ANT 1

11a	**11n HT20**
5500MHz	5500MHz
	
5600MHz	5600MHz
	
5700MHz	5700MHz

11n HT40

5510MHz

5600MHz

5670MHz



5700MHz

11ac VHT20

5500MHz



11ac VHT40

5510MHz

	11ac VHT80
5670MHz	5530MHz

5745-5825MHz Band:

6dB bandwidth

ANT 0

11a	**11n HT20**
5745MHz	5745MHz
	
5785MHz	5785MHz
	
5825MHz	5825MHz

11n HT40

5755MHz



5785MHz

5795MHz



5825MHz

11ac VHT20

5745MHz



11ac VHT40

5755MHz

	11ac VHT80
5795MHz	5775MHz
	

5745-5825MHz Band:

6dB bandwidth

ANT 1

11a	**11n HT20**
5745MHz	5745MHz
	
5785MHz	5785MHz
	
5825MHz	5825MHz

11n HT40

5755MHz

5785MHz



5795MHz

5825MHz



11ac VHT20

5745MHz

11ac VHT40

5755MHz

	11ac VHT80
5795MHz	5775MHz

5745-5825MHz Band:

26dB bandwidth

ANT 0

11a	**11n HT20**
5745MHz	5745MHz
	
5785MHz	5785MHz
	
5825MHz	5825MHz
	

11n HT40	
5755MHz	5785MHz

5795MHz

5825MHz

11ac VHT20

11ac VHT40

5745MHz

5755MHz

	11ac VHT80
5795MHz	5775MHz

5745-5825MHz Band:

26dB bandwidth

ANT 1

11a	**11n HT20**
5745MHz	5745MHz
	
5785MHz	5785MHz
	
5825MHz	5825MHz

11n HT40

5755MHz



5785MHz

5795MHz

5825MHz

11ac VHT20

5745MHz



11ac VHT40

5755MHz

	11ac VHT80
5795MHz	5775MHz

7. OUTPUT POWER TEST

7.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	N9030A	MY51380221	Oct.29, 14	1Year
2.	Power meter	Anritsu	ML2487A	6K00002472	Apr.28, 15	1Year
3.	Power sensor	Anritsu	MA2491A	0033005	Apr.28, 15	1Year
4.	Attenuator (20dB)	Agilent	8491B	MY39262165	Apr.28, 15	1 Year
5.	RF Cable	Hubersuhner	SUCOFLEX102	28620/2	Apr.28, 15	1 Year

7.2. Limit

For the band 5.15–5.25 GHz.
For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the max-imum antenna gain does not exceed 6 dBi.
For the 5.25–5.35 GHz and 5.47–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz.
For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

7.3. Test Procedure

1. Connected the EUT's antenna port to measure device by 26dB attenuator.
2. For IEEE 802.11a and IEEE802.11n HT20 and 802.11ac VHT20 mode, use a PK power meter which's bandwidth is 20MHz and above 26dB bandwidth of signal to measure out each test modes' PK output power.
3. For IEEE802.11n HT40 mode, because the signal's bandwidth is about 40MHz and above 20MHz bandwidth of power sensor ML2491A. So use the test method described in KBD789033 clause E Method SA-1
   1) Connect the antenna port to the spectrum analyzer and Set span of the spectrum to encompass the entire emission bandwidth (EBW) of the signal.
   2) Set the RBW=1MHz and VBW =3MHz
   3) Number of points in sweep ≥ 2 Span / RBW
   4) Detector = RMS
   5) Sweep time = auto couple
   6) Allow the sweep to "free run" and set the Trace average at least 100 traces in power averaging (i.e., RMS) mode.
   7) Compute power by integrating the spectrum across the 26 dB EBW of the signal using the instrument's band power measurement function with band limits set equal to the EBW band edges.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

7.4.Test Results

5180-5240MHz Band:

EUT: Notebook		
M/N: RZ09-0168		
Test date: 2015-08-21	Pressure: 101.6±1.0 kpa	Humidity:53.0±3.0%
Tested by: Alice_Yang	Test site: RF site	Temperature:22.1±0.6 ℃

Test Mode	Frequency (MHz)	Maximum Conducted output power (dBm)			Limit (dBm)
		ANT0	ANT1	Total	
11a	5180	14.82	15.42	N/A	23
	5200	14.71	15.07	N/A	23
	5240	13.53	13.88	N/A	23
11n HT20	5180	14.56	15.35	17.98	23
	5200	14.48	15.00	17.76	23
	5240	13.25	14.01	16.66	23
11n HT40	5190	14.39	14.98	17.71	23
	5230	12.57	13.86	16.27	23
11ac VHT20	5180	14.75	15.15	17.96	23
	5200	14.46	14.90	17.70	23
	5240	13.45	13.67	16.57	23
11ac VHT40	5190	13.91	15.03	17.52	23
	5230	12.55	13.84	16.25	23
11ac VHT80	5210	12.14	12.42	15.29	23

Conclusion: PASS

5260-5320MHz Band:

EUT: Notebook		
M/N: RZ09-0168		
Test date: 2015-08-21	Pressure: 101.6±1.0 kpa	Humidity:53.0±3.0%
Tested by: Alice_Yang	Test site: RF site	Temperature:22.1±0.6 ℃

Test Mode	Frequency (MHz)	Maximum Conducted output power (dBm)			Limit (dBm)
		ANT0	ANT1	Total	
11a	5260	13.73	14.32	N/A	24
	5300	14.61	14.33	N/A	24
	5320	13.52	13.01	N/A	24
11n HT20	5260	13.49	14.28	16.91	24
	5300	14.28	14.35	17.33	24
	5320	13.30	13.07	16.20	24
11n HT40	5270	12.89	14.46	16.76	24
	5310	12.87	13.49	16.20	24
11ac VHT20	5260	13.40	14.11	16.78	24
	5300	14.36	14.06	17.22	24
	5320	13.30	12.78	16.06	24
11ac VHT40	5270	12.66	14.38	16.61	24
	5310	13.38	13.49	16.45	24
11ac VHT80	5290	11.80	11.87	14.85	24

Conclusion: PASS

5500-5700MHz Band:

EUT: Notebook		
M/N: RZ09-0168		
Test date: 2015-08-21	Pressure: 101.6±1.0 kpa	Humidity:53.0±3.0%
Tested by: Alice_Yang	Test site: RF site	Temperature:22.1±0.6 ℃

Test Mode	Frequency (MHz)	Maximum Conducted output power (dBm)			Limit (dBm)
		ANT0	ANT1	Total	
11a	5500	14.81	13.64	N/A	23.7
	5600	14.97	14.38	N/A	23.7
	5700	15.48	14.94	N/A	23.7
11n HT20	5500	14.53	13.69	17.14	23.7
	5600	14.69	14.36	17.54	23.7
	5700	15.21	15.00	18.12	23.7
11n HT40	5510	14.17	12.89	16.59	23.7
	5670	14.54	14.62	17.59	23.7
11ac VHT20	5500	14.58	13.41	17.04	23.7
	5600	14.73	14.14	17.46	23.7
	5700	15.22	14.66	17.96	23.7
11ac VHT40	5510	13.73	12.95	16.37	23.7
	5670	14.11	14.73	17.44	23.7
11ac VHT80	5530	12.87	11.13	15.10	23.7
Conclusion: PASS					

Note: 11ac/n Mode

Directional Gain= $10 \log[(10^{3.52/20}+10^{3.07/20})^2/2]$dBi

=6.3dBi>6dBi

5745-5825MHz Band:

EUT: Notebook		
M/N: RZ09-0168		
Test date: 2015-08-21	Pressure: 101.6±1.0 kpa	Humidity:53.0±3.0%
Tested by: Alice_Yang	Test site: RF site	Temperature:22.1±0.6 ℃

Test Mode	Frequency (MHz)	Maximum Conducted output power (dBm)			Limit (dBm)
		ANT0	ANT1	Total	
11a	5745	14.48	13.54	N/A	29.7
	5785	14.89	14.38	N/A	29.7
	5825	14.88	13.96	N/A	29.7
11n HT20	5745	14.40	13.17	16.84	29.7
	5785	14.52	14.11	17.33	29.7
	5825	14.47	13.67	17.10	29.7
11n HT40	5755	14.09	13.20	16.68	29.7
	5790	14.61	14.15	17.40	29.7
11ac VHT20	5745	14.14	13.14	16.68	29.7
	5785	14.55	14.07	17.33	29.7
	5825	14.30	13.75	17.04	29.7
11ac VHT40	5755	13.96	13.17	16.59	29.7
	5790	14.88	14.15	17.54	29.7
11ac VHT80	5775	13.27	12.45	15.89	29.7
Conclusion: PASS					

Note: 11ac/n Mode

Directional Gain= $10 \log[(10^{3.48/20}+10^{3.18/20})^2/2]$dBi

=6.3dBi>6dBi

5180-5240MHz Band:

ANT 0

11n HT40

5190MHz

5230MHz



11ac VHT80

5230MHz

5210MHz

11acVHT40

5190MHz



5180-5240MHz Band:

ANT 1

11n HT40

5190MHz

5230MHz



11ac VHT80

5230MHz



5210MHz

11acVHT40

5190MHz



5260-5320MHz Band:

ANT 0

11n HT40

5270MHz



5310MHz



11ac VHT80

5310MHz

5290MHz

11acVHT40

5270MHz



5260-5320MHz Band:

ANT 1

11n HT40

5270MHz



5310MHz



11ac VHT80

5310MHz

5290MHz

11acVHT40

5270MHz



5500-5700MHz Band:

ANT 0

11n HT40

5510MHz



5670MHz



11ac VHT80

5670MHz



5530MHz

11acVHT40

5510MHz



5500-5700MHz Band:

ANT 1

11n HT40

5510MHz

5670MHz



11ac VHT80

5670MHz

5530MHz

11acVHT40

5510MHz



5745-5825MHz Band:

ANT 0

11n HT40

5755MHz



5795MHz



11ac VHT80

5795MHz

5775MHz

11acVHT40

5755MHz



5745-5825MHz Band:

ANT 1

11n HT40

5755MHz

5795MHz



11ac VHT80

5795MHz

5775MHz

11acVHT40

5755MHz