Product Specification

WBU058-BGA-V11

WBU058-BGA-V13

WBU058-BGA-V15

WLAN and BT Wireless Module

CHAPTER 1. MODULE OVERVIEW

Foxconn WBU058-BGA-VXX (XX=11, 13, 15) module is a highly integrated module which features a high performance 2x2 dual-band WLAN subsystem, a Bluetooth v5.3 subsystem and merged buttom swtich/IR receiver/LED indicator/light sensor/thermal sensor (V13 only)/far field mic (V15 only). The WLAN subsystem contains the 802.11a/b/g/n/ac/ax radio, baseband that are designed to meet feature-rich wireless connectivity at high standards, and delivering reliable, cost-effective throughput from an extended distance.

Optimized RF architecture and baseband algorithms provide superb performance and low power consumption. Intelligent MAC design deploys a high efficient offload engine and hardware data processing accelerators which fully offloads Wi-Fi task of the host processor.

1-1 Key Characteristic

- Integrate high efficiency power management unit with single 3.3V and 5V power supply input.
- 32-bit RISC MCU for Wi-Fi/Bluetooth protocols and Wi-Fi offload
- Embedded SRAM/ROM
- IEEE 802.11 a/b/g/n/ac/ax compliant
- Support 20MHz, 40MHz, 80MHz bandwidth in 2.4GHz, 5GHz, 6GHz band
- Support Bluetooth 5.3
- Dual band 2T2R mode
- Support MU-MIMO RX
- Support STBC, LDPC
- Greenfield, mixed mode, legacy modes support
- IEEE 802.11 d/e/h/i/j/k/mc/r/v/w support
- Security support for WFA WPA/WPA2/WPA3 personal, WPS2.0, WAPI
- QoS support of WFA WMM, WMM PS
- Bluetooth v5.3 with BLE (BT low energy)
- Supports BT/BLE dual mode.
- Supports BT/Wi-Fi coexistence.
- Supports 7 BT links and 16 BLE link.
- Bottom switch
- IR receiver
- White / RED LED indicator
- Ambient light sensor
- Thermal sensor (V13 only)
- Far field mic (V15 only)

1-2 Feature Difference

Feature	WBU058-BGA-VXX		
	WBU058-BGA-V11	WBU058-BGA-V13	WBU058-BGA-V15
Wi-Fi 6E + BT5.3	V	V	V
IR receiver	V	V	V
Key	V	V	V
LED indicator	V	V	V
Light Sensor	V	V	V
Thermal Sensor	-	V	-
Far Filed Mic (MIC/Tally & RGB/MIC SWITCH)	-	-	V

1-3 Pin Definition

Connector: P-TWO 1311019-45CD1N001

Pin#	Pin Name	Pin Type	Supply Domain	Description	Remark
1	5V_STBY	Power	5V	5V input for White and RGB LED	
2	GND	Ground	-	Ground	
3	GND	Ground	-	Ground	
4	GND	Ground	-	Ground	
5	GND	Ground	-	Ground	
6	3.3V_MAIN	Power	3.3V	3.3V for light sensor and thermal sensor	
7	ERR_LED	I	-	error indicator control	
8	W_LED	I	-	white light control	
9	POWER_KEY	O	-	power button switch	
10	MIC_DET	O	-	Microphone enable detect	V15 only
11	MIC_DATA_R	O	-	Microphone R side data	V15 only
12	MIC_CLK	O	-	Microphone clock	V15 only
13	GND	Ground	-	Ground	
14	MIC_DATA_L	O	-	Microphone L side data	V15 only
15	MIC_TALLY	I	-	Tally light control	V15 only
16	SENSE_OPT	O	-	Light sensor output signal	
17	GND	Ground	-	Ground	
18	IR_OUT	O	-	Signal from IR receiver	
19	MIC_B	I	-	Blue light control	V15 only
20	MIC_G	I	-	Green light control	V15 only
21	MIC_R	I	-	Red light control	V15 only
22	3.3V_STBY	Power	3.3V	3.3V power supply to IR receiver/Red LED/MIC	
23	I2C0_SCL	I/O	-	I2C for Light sensor	V13 only
24	I2C0_SDA	I/O	-	I2C for Light sensor	V13 only
25	GND	Ground	-	Ground	
26	GND	Ground	-	Ground	
27	BT_WOBT#	O	-	Wake up on BT	
28	WIFI_BT_RST#	I	-	Reset BT	
29	WIFI_WOWL#	O	-	Wake up on LAN	
30	WIFI_RST#	I	-	Reset Wi-Fi	
31	BT_RST#	I	-	Full reset	
32	WIFI_VBUS	Power	3.3V	3.3V power supply to MT7921AUN	
33	WIFI_VBUS	Power	3.3V	3.3V power supply to MT7921AUN	
34	WIFI_VBUS	Power	3.3V	3.3V power supply to MT7921AUN	
35	WIFI_VBUS	Power	3.3V	3.3V power supply to MT7921AUN	
36	WIFI_VBUS	Power	3.3V	3.3V power supply to MT7921AUN	
37	WIFI_VBUS	Power	3.3V	3.3V power supply to MT7921AUN	
38	WIFI_VBUS	Power	3.3V	3.3V power supply to MT7921AUN	
39	WIFI_VBUS	Power	3.3V	3.3V power supply to MT7921AUN	
40	GND	Ground	-	Ground	
41	GND	Ground	-	Ground	
42	WIFI_DP	I/O	-	USB differential Signal	
43	WIFI_DM	I/O	-	USB differential Signal	
44	GND	Ground	-	Ground	
45	GND	Ground	-	Ground	

Chapter 2. Electrical and RF Specifications

2-1 Recommended Operation Rating

Power domain	Condition	Min	Typ.	Max.	Unit
3.3V	3.3V	3	3.3	3.6	V
5V	5V	4.5	5	5.5	V
RF Interface	Zo		50		Ohm

2-2 RF Operation Frequency

	Min	Max.	Unit
2.4GHz WLAN	2412	2462	MHz
2.4GHz BT	2402	2480	MHz
5GHz	5180	5825	MHz
6GHz	5955	7115	MHz

2-3 WLAN RF Specification – TX

B-mode (Total Conducted AVG Power Max.)

Data Rate (Mbps)	Modulation	Typical Power (dBm)	Data Rate (Mbps)	Modulation	Typical Power (dBm)
1	DBPSK	15	5.5	CCK	15
2	DQPSK	15	11	CCK	15

*If some channels cannot reach the maximum, use the reported power as reference.

G-mode (Total Conducted AVG Power Max.)

Data Rate (Mbps)	Modulation	Typical Power (dBm)	Data Rate (Mbps)	Modulation	Typical Power (dBm)
6	OFDM	15	24	OFDM	15
9	OFDM	15	36	OFDM	15
12	OFDM	15	48	OFDM	15
18	OFDM	15	54	OFDM	15

*If some channels cannot reach the maximum, use the reported power as reference.

2.4G BW20/40 n/ax-mode (Total Conducted AVG Power Max.)

Data Rate (Mbps)	Typical Power (dBm)	Data Rate (Mbps)	Typical Power (dBm)
HT20/HE20-MCS0	14.5	HT40/HE40-MCS0	14
HT20/HE20-MCS1	14.5	HT40/HE40-MCS1	14
HT20/HE20-MCS2	14.5	HT40/HE40-MCS2	14
HT20/HE20-MCS3	14.5	HT40/HE40-MCS3	14
HT20/HE20-MCS4	14.5	HT40/HE40-MCS4	14
HT20/HE20-MCS5	14.5	HT40/HE40-MCS5	14
HT20/HE20-MCS6	14.5	HT40/HE40-MCS6	14
HT20/HE20-MCS7	14.5	HT40/HE40-MCS7	14
HE20-MCS8	14.5	HE40-MCS8	14
HE20-MCS9	14.5	HE40-MCS9	14
HE20-MCS10	14.5	HE40-MCS10	14
HE20-MCS11	14.5	HE40-MCS11	14

*If some channels cannot reach the maximum, use the reported power as reference.

5G A-mode UNII-1/UNII-2a/UNII-2c (Total Conducted AVG Power Max.)

Data Rate (Mbps)	Modulation	Typical Power (dBm)	Data Rate (Mbps)	Modulation	Typical Power (dBm)
6	OFDM	11.5	24	OFDM	11.5
9	OFDM	11.5	36	OFDM	11.5
12	OFDM	11.5	48	OFDM	11.5
18	OFDM	11.5	54	OFDM	11.5

*If some channels cannot reach the maximum, use the reported power as reference.

5G A-mode UNII-3 (Total Conducted AVG Power Max.)

Data Rate (Mbps)	Modulation	Typical Power (dBm)	Data Rate (Mbps)	Modulation	Typical Power (dBm)
6	OFDM	9	24	OFDM	9
9	OFDM	9	36	OFDM	9
12	OFDM	9	48	OFDM	9
18	OFDM	9	54	OFDM	9

*If some channels cannot reach the maximum, use the reported power as reference.

5G BW20/40/80 n/ac/ax mode UNII-1/UNII-2a/UNII-2c
(Total Conducted Power Max.)

Data Rate (Mbps)	Typical Power (dBm)	Data Rate (Mbps)	Typical Power (dBm)
VHT/HT20/HE20-MCS0	11	VHT/HT40/HE40-MCS6	11
VHT/HT20/HE20-MCS1	11	VHT/HT40/HE40-MCS7	11

VHT/HT20/HE20-MCS2	11	VHT/HE40-MCS8	11
VHT/HT20/HE20-MCS3	11	VHT/HE40-MCS9	11
VHT/HT20/HE20-MCS4	11	VHT/HT80/HE80-MCS0	11
VHT/HT20/HE20-MCS5	11	VHT/HT80/HE80 -MCS1	11
VHT/HT20/HE20-MCS6	11	VHT/HT80/HE80-MCS2	11
VHT/HT20/HE20-MCS7	11	VHT/HT80/HE80-MCS3	11
VHT/HE20-MCS8	11	VHT/HT80/HE80-MCS4	11
VHT/HE20-MCS9	11	VHT/HT80/HE80-MCS5	11
VHT/HT40/HE40-MCS0	11	VHT/HT80/HE80-MCS6	11
VHT/HT40/HE40-MCS1	11	VHT/HT80/HE80-MCS7	11
VHT/HT40/HE40-MCS2	11	VHT/HE80-MCS8	11
VHT/HT40/HE40-MCS3	11	VHT/HE80-MCS9	11
VHT/HT40/HE40-MCS4	11		
VHT/HT40/HE40-MCS5	11		

*If some channels cannot reach the maximum, use the reported power as reference.

5G BW20/40/80 n/ac/ax mode UNII-3 (Total Conducted Power Max.)

Data Rate (Mbps)	Typical Power (dBm)	Data Rate (Mbps)	Typical Power (dBm)
VHT/HT20/HE20-MCS0	9	VHT/HT40/HE40-MCS6	9
VHT/HT20/HE20-MCS1	9	VHT/HT40/HE40-MCS7	9
VHT/HT20/HE20-MCS2	9	VHT/HE40-MCS8	9
VHT/HT20/HE20-MCS3	9	VHT/HE40-MCS9	9
VHT/HT20/HE20-MCS4	9	VHT/HT80/HE80-MCS0	9
VHT/HT20/HE20-MCS5	9	VHT/HT80/HE80 -MCS1	9
VHT/HT20/HE20-MCS6	9	VHT/HT80/HE80-MCS2	9
VHT/HT20/HE20-MCS7	9	VHT/HT80/HE80-MCS3	9
VHT/HE20-MCS8	9	VHT/HT80/HE80-MCS4	9
VHT/HE20-MCS9	9	VHT/HT80/HE80-MCS5	9
VHT/HT40/HE40-MCS0	9	VHT/HT80/HE80-MCS6	9
VHT/HT40/HE40-MCS1	9	VHT/HT80/HE80-MCS7	9
VHT/HT40/HE40-MCS2	9	VHT/HE80-MCS8	9
VHT/HT40/HE40-MCS3	9	VHT/HE80-MCS9	9
VHT/HT40/HE40-MCS4	9		
VHT/HT40/HE40-MCS5	9		

*If some channels cannot reach the maximum, use the reported power as reference.

6G BW20/40/80 ax mode (Total Conducted Power Max.)

Data Rate (Mbps)	Typical Power (dBm)	Data Rate (Mbps)	Typical Power (dBm)
HE20-MCS0	7	HE40-MCS6	9
HE20-MCS1	7	HE40-MCS7	9
HE20-MCS2	7	HE40-MCS8	9
HE20-MCS3	7	HE40-MCS9	9
HE20-MCS4	7	HE80-MCS0	9
HE20-MCS5	7	HE80-MCS1	9
HE20-MCS6	7	HE80-MCS2	9
HE20-MCS7	7	HE80-MCS3	9
HE20-MCS8	7	HE80-MCS4	9
HE20-MCS9	7	HE80-MCS5	9
HE40-MCS0	9	HE80 -MCS6	9
HE40-MCS1	9	HE80-MCS7	9
HE40-MCS2	9	HE80-MCS8	9
HE40-MCS3	9	HE80-MCS9	9
HE40-MCS4	9		
HE40-MCS5	9		

*If some channels cannot reach the maximum, use the reported power as reference.

2-4 Bluetooth RF Specification(draft)

Parameter	Condition	Min.	Typ.	Max.	Unit
Basic Data Rate- Transmit Performance					
RF Transmit Power (TRM-LE01,02)		0	4	8	dBm
In-Band Emission (TRM-LE03,04)	$\lvert f-f_0 \rvert$ = 2MHz	≤ -20			dBm
	$\lvert f-f_0 \rvert$ ≥ 3MHz	≤ -30			
TX Output Spectrum – Out of Band Spurious Emission	30MHz – 1GHz	≤ -36			dBm
	1GHz -12.75GHz	≤ -30			
	5.15GHz -5.35GHz	≤ -47			
	5.725GHz-5.825GHz	≤ -47			
Modulation Characteristic (TRM-LE05)	Delta f1 avg	225 ≤ $\Delta f1_{avg}$ ≤ 275			kHz
	Delta f2 max	≥ 185 at 99.9%			
	Delta f2 avg/Delta f1 avg	≥ 0.8			
Carrier Frequency Drift (TRM-LE06,07)	Center frequency	≤± 150			kHz
	During any packet	≤± 50			
Maximum Drift Rate (TRM-LE06,07)		20 Hz/50 us			
Basic Data Rate- Receiver Performance					
Sensitivity at 30.8% PER(0.1%BER) (RCV-LE01,02)		≤ -81			dBm
C/I Co-Channel interference (RCV-LE03)	Co-channel	≤ 21			dB
C/I Adjacent CH interference (RCV-LE03)	$\lvert f-f_0 \rvert$ = 1MHz	≤ 15			
	$\lvert f-f_0 \rvert$ = 2MHz	≤ -17			
	$\lvert f-f_0 \rvert$ ≥ 3MHz	≤ -27			
C/I Image CH interference (RCV-LE03)	C/I_{image}	≤ -9			
	$C/I_{image\pm1MHz}$	≤ -15			
Out of band Blocking (RCV-LE04)	30MHz – 2000 MHz	-30			dBm
	2003MHz – 2399MHz	-35			
	2484MHz – 2997MHz	-35			
	3000MHz – 12750MHz	-30			
Intermodulation Performance at ≤30.8% (≤ 0.1% BER) (RCV-LE05)		-64			dBm
Maximum input power level (RCV-LE06)		≥ -10			dBm
PER Report Integrity 50% ≤ PER ≤ 65.4% (RCV-LE07)		-30			dBm
Spurious Emission	30MHz – 12.75GHz	≤ -57			dBm

*If some channels cannot reach the maximum, use the reported power as reference.

2-5 Environment Specifications

Operating Conditions

Operation Temperature : -10 ~ 50℃

Relevant Humidity: 5 ~ 95% (non-condensing)

Storage Conditions

Non-Operation Temperature : -20 ~ 85℃ (Typ. 25℃)

Relevant Humidity: 5 ~ 95% (non-condensing)

Federal Communication Commission Interference Statement:
This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

—Reorient or relocate the receiving antenna.
—Increase the separation between the equipment and receiver.
—Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
—Consult the dealer or an experienced radio/TV technician for help.

Any changes or modifications not expressly approved by the party responsible for compliance could void your authority to operate the equipment.

RF exposure statements
This Transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.
This equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20 centimeters between the radiator and your body or nearby persons.

CFR 47 FCC PART 15 SUBPART C (15.247) and SUBPART E (15.407) have been investigated. It is applicable to the modular transmitter.

The devices must be installed and used in strict accordance with the manufacturer's instructions as described in the user documentation that comes with the product.

This radio transmitter FCC ID: RX3-WBU058BGA has been approved by Federal Communications Commission to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that

have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

The Part 15 authorized transmitters used in the host product must use a unique antenna connector. The EUT antennas are printed antennas without a connector, which fully complies with the requirements.

If the FCC identification number is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: “Contains Transmitter Module FCC ID: RX3-WBU058BGA” Or “Contains FCC ID: RX3-WBU058BGA”

The modular transmitter is only FCC authorized for the specific rule parts (i.e., FCC transmitter rules) listed on the grant, and the host product manufacturer is responsible for compliance to any other FCC rules that apply to the host not covered by the modular transmitter grant of certification. The final host product still requires Part 15 Subpart B compliance testing with the modular transmitter installed.

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

OEM Integrator must refer to FCC KDB “996369 D04 Module Integration Guide v02” for modular transmitter integration guidance.

The module is for indoor applications only.

The module may not be used for the purposes of remote control of drones

The antenna must be installed into the host device so that the end user does not have access to the antenna or its connector.

Label Indoor Only Info & restrictions.

FCC regulations restrict the operation of this device to indoor use only. Operation prohibited on oil platforms, cars, trains, boats, and aircraft, except that operation of this device is permitted in large aircraft while flying above 10,000 feet.

Industry Canada statement:
This device complies with Industry Canada license-exempt RSSs. Operation is subject to the following two conditions:
1) This device may not cause interference, and
2) This device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes :
1) l'appareil ne doit pas produire de brouillage;
2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, meme si le brouillage est susceptible d'en compromettre le fonctionnement.

Radiation Exposure Statement:
This equipment complies with IC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

Déclaration d'exposition aux radiations:
Cet équipement est conforme aux limites d'exposition aux rayonnements IC établies pour un environnement non contrôlé. Cet équipement doit être installé et utilisé avec un minimum de 20 cm de distance entre la source de rayonnement et votre corps.

This radio transmitter (IC: 2878F-WBU058BGA has been approved by Industry Canada to operate with the antenna types listed below with the maximum permissible gain indicated. Antenna types not included in this list, having a gain greater than the maximum gain indicated for that type, are strictly prohibited for use with this device.
Le présent émetteur radio (IC: 2878F-WBU058BGA a été approuvé par Industrie Canada pour fonctionner avec les types d'antenne énumérés cidessous et ayant un gain admissible maximal. Les types d'antenne non inclus dans cette liste, et dont le gain est supérieur au gain maximal indiqué, sont strictement interdits pour l'exploitation de l'émetteur.

Ant. No.	Transmitter Circuit	Frequency Range	Brand Name	Model Name	Maximum Gain (dBi)	Ant. Type	Connector Type

WLAN ANT1	Chain0	2.412~2.472GHz 5.15~5.25GHz 5.25~5.35GHz 5.47~5.725GHz 5.725~5.85GHz 5.925~6.425GHz 6.425~6.525GHz 6.525~6.875GHz 6.875~7.125GHz	FOXCONN	WBU058-BGA	2.412~2.472GHz: 3.91 5.15~5.25GHz: 4.11 5.25~5.35GHz: 5.18 5.47~5.725GHz: 4.62 5.725~5.85GHz: 4.28 5.925~6.425GHz: 3.34 6.425~6.525GHz: 3.35 6.525~6.875GHz: 4.88 6.875~7.125GHz: 4.72	Printing	N/A
WLAN ANT2	Chain1	2.412~2.472GHz 5.15~5.25GHz 5.25~5.35GHz 5.47~5.725GHz 5.725~5.85GHz 5.925~6.425GHz 6.425~6.525GHz 6.525~6.875GHz 6.875~7.125GHz	FOXCONN	WBU058-BGA	2.412~2.472GHz: 4.94 5.15~5.25GHz: 3.8 5.25~5.35GHz: 3.76 5.47~5.725GHz: 3.36 5.725~5.85GHz: 3.34 5.925~6.425GHz: 3.07 6.425~6.525GHz: 3.39 6.525~6.875GHz: 4.01 6.875~7.125GHz: 2.97	Printing	N/A
BT ANT1	Chain0	2.4~2.4835GHz	FOXCONN	WBU058-BGA	2.81	Printing	N/A
BT ANT2	Chain1	2.4~2.4835GHz	FOXCONN	WBU058-BGA	1.53	Printing	N/A

If the ISED certification number is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: “Contains IC: 2878F-WBU058BGA”.

Si le numéro de certification ISDE n'est pas visible lorsque le module est installé à l'intérieur d'un autre appareil, alors l'extérieur de l'appareil dans lequel le module est installé doit également afficher une étiquette faisant référence au module inclus. Cette étiquette extérieure peut utiliser un libellé comme celui-ci: “ Contient IC: 2878F-WBU058BGA“.

Plaque signalétique du produit final:
Le produit final doit être étiqueté dans un endroit visible avec l'inscription suivante: "Contient des IC: 2878F-WBU058BGA ".

Manual Information To the End User:
The OEM integrator has to be aware not to provide information to the end user regarding how to install or remove this RF module in the user’s manual of the end product which integrates this module.
The end user manual shall include all required regulatory information/warning as show in this manual.

Manuel d'information à l'utilisateur final
L'intégrateur OEM doit être conscient de ne pas fournir des informations à l'utilisateur final quant à la façon d'installer ou de supprimer ce module RF dans le manuel de l'utilisateur du produit final qui intègre ce module. Le manuel de l'utilisateur final doit inclure toutes les informations réglementaires requises et avertissements comme indiqué dans ce manue

Must use the device only in host devices that meet the FCC/ISED RF exposure category of mobile, which means the device is installed and used at distances of at least 20cm from persons.
The end user manual shall include FCC Part 15 /ISED RSS GEN compliance statements related to the transmitter as show in this manual.
Host manufacturer is responsible for compliance of the host system with module installed with all other applicable requirements for the system such as Part 15 B, ICES 003.
Host manufacturer is strongly recommended to confirm compliance with FCC/ISED requirements for the transmitter when the module is installed in the host.
Must have on the host device a label showing Contains FCC ID: RX3-WBU058BGA, Contains IC: 2878F-WBU058BGA
The use condition limitations extend to professional users, then instructions must state that this information also extends to the host manufacturer’s instruction manual.

If the end product will involve the Multiple simultaneously transmitting condition or different operational conditions for a stand-alone modular transmitter in a host, host manufacturer have to consult with module manufacturer for the installation method in end system.

l'hôte doit utiliser l'instrument uniquement dans des dispositifs qui répondent à la fcc / (catégorie d'exposition rf mobile, ce qui signifie le dispositif est installé et utilisé à une distance d'au moins 20 cm de personnes.
le manuel de l'utilisateur final doit inclure la partie 15 / (fac rss gen déclarations de conformité relatives à l'émetteur que de montrer dans ce manuel.
le fabricant est responsable de la conformité de l'hôte, le système d'accueil avec le module installé avec toutes les autres exigences applicables du système comme la partie 15 b, ices - 003. accueillir le fabricant est fortement recommandé de confirmer la conformité avec les exigences de la fcc / (émetteur lorsque le module est installé dans l'hôte.
le dispositif d'accueil doivent avoir une étiquette indiquant contient FCC ID: RX3-

WBU058BGA, contient IC : 2878F-WBU058BGA

Operation shall be limited to indoor use only.
Operation on oil platforms, cars, trains, boats and aircraft shall be prohibited except for on large aircraft flying above 10,000 ft.
Le fonctionnement doit être limité à une utilisation en intérieur uniquement.
L'exploitation sur les plates-formes pétrolières, les voitures, les trains, les bateaux et les aéronefs est interdite, sauf pour les gros aéronefs volant au-dessus de 10 000 pieds.

Model: WBU058-BGA-V11 only sale for Canada
Model: WBU058-BGA-V11, WBU058-BGA-V13, WBU058-BGA-V15 sales for FCC