Appendix B

RF Test Data for 2.4GWIFI (Conducted Measurement)

Product Name: SUUNTO RACE S

Test Model: OW233

Environmental Conditions

Temperature:	23.1° C
Relative Humidity:	52.3%
ATM Pressure:	100.0 kPa
Test Engineer:	Paddi Chen
Supervised by:	Nick Peng

B.1 -6dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	b	2412	Ant1	9.038	>=0.5	Pass
NVNT	b	2437	Ant1	9.574	>=0.5	Pass
NVNT	b	2462	Ant1	8.041	>=0.5	Pass
NVNT	g	2412	Ant1	15.325	>=0.5	Pass
NVNT	g	2437	Ant1	15.123	>=0.5	Pass
NVNT	g	2462	Ant1	15.095	>=0.5	Pass
NVNT	n20	2412	Ant1	15.109	>=0.5	Pass
NVNT	n20	2437	Ant1	16.279	>=0.5	Pass
NVNT	n20	2462	Ant1	15.045	>=0.5	Pass

Test Graphs

-6dB Bandwidth NVNT b 2412MHz Ant1



-6dB Bandwidth NVNT b 2437MHz Ant1



-6dB Bandwidth NVNT b 2462MHz Ant1



-6dB Bandwidth NVNT g 2412MHz Ant1



-6dB Bandwidth NVNT g 2437MHz Ant1



-6dB Bandwidth NVNT g 2462MHz Ant1



-6dB Bandwidth NVNT n20 2412MHz Ant1



-6dB Bandwidth NVNT n20 2437MHz Ant1



-6dB Bandwidth NVNT n20 2462MHz Ant1



B.2 Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	b	2412	Ant1	7.97	30	Pass
NVNT	b	2437	Ant1	7.23	30	Pass
NVNT	b	2462	Ant1	7.67	30	Pass
NVNT	g	2412	Ant1	8.86	30	Pass
NVNT	g	2437	Ant1	8.38	30	Pass
NVNT	g	2462	Ant1	8.64	30	Pass
NVNT	n20	2412	Ant1	8.64	30	Pass
NVNT	n20	2437	Ant1	8.09	30	Pass
NVNT	n20	2462	Ant1	8.61	30	Pass

B.3 Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	b	2412	Ant1	-16.75	8	Pass
NVNT	b	2437	Ant1	-12.97	8	Pass
NVNT	b	2462	Ant1	-16.73	8	Pass
NVNT	g	2412	Ant1	-20.14	8	Pass
NVNT	g	2437	Ant1	-21.79	8	Pass
NVNT	g	2462	Ant1	-20.32	8	Pass
NVNT	n20	2412	Ant1	-21.05	8	Pass
NVNT	n20	2437	Ant1	-20.06	8	Pass
NVNT	n20	2462	Ant1	-20.01	8	Pass

Test Graphs

PSD NVNT b 2412MHz Ant1



PSD NVNT b 2437MHz Ant1



PSD NVNT b 2462MHz Ant1



PSD NVNT g 2412MHz Ant1



PSD NVNT g 2437MHz Ant1



PSD NVNT g 2462MHz Ant1



PSD NVNT n20 2412MHz Ant1



PSD NVNT n20 2437MHz Ant1



PSD NVNT n20 2462MHz Ant1



B.4 Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant1	-51.73	-20	Pass
NVNT	b	2462	Ant1	-53.93	-20	Pass
NVNT	g	2412	Ant1	-36.6	-20	Pass
NVNT	g	2462	Ant1	-47.97	-20	Pass
NVNT	n20	2412	Ant1	-36.72	-20	Pass
NVNT	n20	2462	Ant1	-48.63	-20	Pass

Test Graphs

Band Edge NVNT b 2412MHz Ant1 Ref



Band Edge NVNT b 2412MHz Ant1 Emission



Band Edge NVNT b 2462MHz Ant1 Ref



Band Edge NVNT b 2462MHz Ant1 Emission



Band Edge NVNT g 2412MHz Ant1 Ref



Band Edge NVNT g 2412MHz Ant1 Emission



Band Edge NVNT g 2462MHz Ant1 Ref



Band Edge NVNT g 2462MHz Ant1 Emission



Band Edge NVNT n20 2412MHz Ant1 Ref



Band Edge NVNT n20 2412MHz Ant1 Emission



Band Edge NVNT n20 2462MHz Ant1 Ref



Band Edge NVNT n20 2462MHz Ant1 Emission



B.5 Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant1	-43.04	-20	Pass
NVNT	b	2437	Ant1	-41.5	-20	Pass
NVNT	b	2462	Ant1	-43.53	-20	Pass
NVNT	g	2412	Ant1	-41.95	-20	Pass
NVNT	g	2437	Ant1	-38.88	-20	Pass
NVNT	g	2462	Ant1	-39.98	-20	Pass
NVNT	n20	2412	Ant1	-40.37	-20	Pass
NVNT	n20	2437	Ant1	-39.7	-20	Pass
NVNT	n20	2462	Ant1	-40	-20	Pass