

STATEMENT OF EXPOSURE TO ELECTROMAGNETIC FIELDS

No. 311783

EQUIPMENT

Type of equipment	Mesurement unit
Type / Model	52198-003
Manufacturer	Tour & Andersson AB
By request of:	PartnerTech Åtvidaberg

DIRECTIVE / STANDARD

OET Bulletin 65, supplement C

CALCULATIONS

According to the manufacturer the product has an EIRP of less 1 mW and the operator shall not be any closer than (R) 5 cm to the transmitter's antenna.

A worst case calculation is as follows:


$$S = \frac{4 \times EIRP}{4 \times \pi \times r^2} \quad (\text{Power density with 100 \% reflection})$$

$$S = 4 \times 1 / (4 \times \pi \times 5^2) = 0,013 \text{ mW/ cm}^2$$

Limit according to OET Bulletin 65, supplement C for power density is 1 mW/ cm².
In considering the calculations above it is determined that the requirements according to the referred standard is fulfilled without testing.

Date of issue: 6 October 2004

Intertek Semko AB
EMC & Radio


Björn Rosenquist
Technical Manager



Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
Registered in Sweden: No SE556024059901, Registered office: As address