Prüfbericht-Nr.: *Test report no.:*	CN22EXN3 (FCC-RFEXP) 001	**Auftrags-Nr.:** *Order no.:*	238542230	
Kunden-Referenz-Nr.: *Client reference no.:*	N/A	**Auftragsdatum:** *Order date:*	2022-04-13	
Auftraggeber: *Client:*	TAIYO YUDEN CO., LTD. 43-1, Yawatabara-machi, Takasaki-shi, Gunma, 370-0024, Japan			
Prüfgegenstand: *Test item:*	Bluetooth low energy/ANT/802.15.4 Module			
Bezeichnung / Typ-Nr.: *Identification / Type no.:*	EYSPDN			
Auftrags-Inhalt: *Order content:*	FCC Certification			
Prüfgrundlage: *Test specification:*	IEEE Std C95.1 47 CFR §2.1093 47 CFR §1.1310			
Wareneingangsdatum: *Date of sample receipt:*	2022-03-14			
Prüfmuster-Nr.: *Test sample no:*	A003226724-002 A003226724-003			
Prüfzeitraum: *Testing period:*	2022-04-28 - 2022-06-01			
Ort der Prüfung: *Place of testing:*	EMC/RF Taipei Testing Site			
Prüflaboratorium: *Testing laboratory:*	Taipei Testing Laboratories			
Prüfergebnis*: *Test result*:*	Pass			

überprüft von: *compiled by:*	Jack Wang	**genehmigt von:** authorized by:	Brenda Chen
Datum: *Date:* 2022-06-07		**Ausstellungsdatum:** *Issue date:* 2022-06-07	
Stellung / *Position:*	Jack Wang Project Manager	**Stellung** / *Position:*	Brenda Chen Senior Project Manager

Sonstiges / *Other:*

Zustand des Prüfgegenstandes bei Anlieferung: Prüfmuster vollständig und unbeschädigt
Condition of the test item at delivery: *Test item complete and undamaged*

* Legende:	1 = sehr gut	2 = gut	3 = befriedigend	4 = ausreichend	5 = mangelhaft
	P(ass) = entspricht o.g. Prüfgrundlage(n)		F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
** Legend:*	*1 = very good*	*2 = good*	*3 = satisfactory*	*4 = sufficient*	*5 = poor*
	P(ass) = passed a.m. test specification(s)		*F(ail) = failed a.m. test specification(s)*	*N/A = not applicable*	*N/T = not tested*

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.
This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.
V05

Contents

HISTORY OF THIS TEST REPORT 3

1 GENERAL REMARKS 4
1.1 COMPLEMENTARY MATERIALS 4
1.2 DECISION RULE OF CONFORMITY 4

2 TEST SITES 5
2.1 TEST FACILITIES 5
2.2 TEST FACILITY 5

3 GENERAL PRODUCT INFORMATION 6
3.1 PRODUCT FUNCTION AND INTENDED USE 6
3.2 RATINGS AND SYSTEM DETAILS 6

4 RF EXPOSURE EVALUATION 7
4.1 SAR TEST EXCLUSION 7

5 TEST RESULTS 8
5.1 SAR TEST EXCLUSION THRESHOLD 8

APPENDIX EP - PHOTOGRAPHS OF EUT

HISTORY OF THIS TEST REPORT

Report No.	Description	Date Issued
CN22EXN3 (FCC-RFEXP) 001	Original Release	2022-06-07

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:
Appendix EP - Photographs of EUT

1.2 Decision Rule of Conformity

The decision rule of conformity of this test report is following the requirements of the requested standard in the quotation, and agreed among testing laboratory and manufacturer (applicant) to exclude the consideration of Measurement Uncertainty, unless it is required by the specific standard.

2 Test Sites

2.1 Test Facilities

Taipei Testing Laboratories

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)

2.2 Test Facility

Taipei Testing Laboratories

No.458-18, Sec. 2, Fenliao Rd., Linkou Dist.,
New Taipei City 244
Taiwan (R.O.C.)

3 General Product Information

3.1 Product Function and Intended Use

The EUT is Bluetooth low energy/ANT/802.15.4 Module. It contains Bluetooth & IEEE802.15.4 compatible module enabling the user to communicate data through Wireless interface.
For details refer to the User Guide, Data Sheet and Circuit Diagram.

3.2 Ratings and System Details

Basic Information of EUT

Item	EUT Information
Kind of Equipment/Test Item	Bluetooth low energy/ANT/802.15.4 Module
Type Identification	EYSPDN
FCC ID	RYYEYSPDN

Technical Specification of EUT

Item	EUT Information
Operating Frequency	Bluetooth: 2402 MHz ~ 2480 MHz IEEE802.15.4: 2405 MHz ~ 2475 MHz
Modulation	Bluetooth: GFSK IEEE802.15.4: O-QPSK
Operation Voltage	1.7 ~ 5.5 Vdc (Tested at 3 Vdc)
Antenna Type	PCB
Antenna Gain	2.5 dBi

4 RF Exposure Evaluation

4.1 SAR test exclusion

Following FCC KDB 447498 D01 "General SAR test exclusion guidance v06"

The corresponding SAR Test Exclusion Threshold condition(s), listed below:

a) For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:
[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] · [$\sqrt{f_{(GHz)}}$)] ≤ 3.0 for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where
- $f_{(GHz)}$ is the RF channel transmit frequency in GHz.
- Power and distance are rounded to the nearest mW and mm before calculation.
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

b) For 100 MHz to 6 GHz and test separation distances > 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:
   1) {[Power allowed at numeric threshold for 50 mm in step a)] + [(test separation distance – 50 mm)·($f_{(MHz)}$/150)]} mW, for 100 MHz to 1500 MHz
   2) {[Power allowed at numeric threshold for 50 mm in step a)] + [(test separation distance – 50 mm)·10]} mW, for > 1500 MHz and ≤ 6 GHz

c) For frequencies below 100 MHz, the following may be considered for SAR test exclusion.
   1) For test separation distances > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by [1 + log(100/$f_{(MHz)}$)]
   2) For test separation distances ≤ 50 mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by ½
   3) SAR measurement procedures are not established below 100 MHz.

When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any SAR test results below 100 MHz to be acceptable.

5 Test Results

5.1 SAR Test Exclusion Threshold

Mode	Frequency (MHz)	Max. Power (mW)	Min. test separation distance (mm)	SAR test exclusion calculation value	1-g head or body SAR test exclusion thresholds	Result
BLE	2402	6.46	5	2.002	3	Pass
ANT	2402	6.47	5	2.005	3	Pass
Nordic Original	2402	6.46	5	2.002	3	Pass
IEEE802.15.4	2405	6.44	5	1.997	3	Pass