

# RF EXPOSURE EVALUATION

## 1. PRODUCT INFORMATION

|                                   |                                                                                                                                                                                                                                                           |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>FCC ID</b>                     | S34-DFD848                                                                                                                                                                                                                                                |
| <b>Product Description</b>        | REMOTE CONTROL PRODUCTS                                                                                                                                                                                                                                   |
| <b>Model Name</b>                 | F08, F05, F06, 1886, 1888, 1889, K101, K102, K103, K104, K105, K106, K107, K108, K109, K181, K182, K183, K185, K186                                                                                                                                       |
| <b>Frequency band (Operating)</b> | <input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz<br><input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz<br><input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz<br><input checked="" type="checkbox"/> Others (SRD: 2.402GHz ~ 2.479GHz) |
| <b>Device category</b>            | <input checked="" type="checkbox"/> Portable (<20cm separation)<br><input type="checkbox"/> Mobile (>20cm separation)<br><input type="checkbox"/> Others:                                                                                                 |
| <b>Antenna diversity</b>          | <input checked="" type="checkbox"/> Single antenna<br><input type="checkbox"/> Multiple antennas                                                                                                                                                          |
| <b>Maximum field strength</b>     | 84.74dBμV/m(Peak)@3m<br>74.56dBμV/m(Average)@3m                                                                                                                                                                                                           |
| <b>Antenna gain</b>               | 2.20dBi                                                                                                                                                                                                                                                   |
| <b>Evaluation applied</b>         | <input type="checkbox"/> MPE Evaluation<br><input checked="" type="checkbox"/> SAR Evaluation                                                                                                                                                             |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

## 2. PORTABLE DEVICE EVALUATION METHOD AND LIMIT

According to §15.247(i) and §1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See KDB 447498 D01 General RF Exposure Guidance v05, section 4.3.1.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
 for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: [agc@agccert.com](mailto:agc@agccert.com) Web: <http://www.agccert.com/>

### 3. MOBILE DEVICE EVALUATION METHOD AND LIMIT

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

#### LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE

| Frequency Range (MHz) | E-field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (Minutes) |
|-----------------------|----------------------------|-----------------------------------|-----------------------------------------|-------------------------------------------------------------------|
| 0.3 -- 1.34           | 614                        | 1.63                              | (100)*                                  | 30                                                                |
| 1.34 -- 30            | 824/f                      | 2.19/f                            | (180/f <sup>2</sup> )*                  | 30                                                                |
| 30 -- 300             | 27.5                       | 0.073                             | 0.2                                     | 30                                                                |
| 300 -- 1500           | --                         | --                                | f/1500                                  | 30                                                                |
| 1500 -- 100,000       | --                         | --                                | 1.0                                     | 30                                                                |

\*Note:

1. f= Frequency in MHz \* Plane-wave Equivalent Power Density
2. The averaging time for General Population/Uncontrolled exposure to fixed transmitters is not applicable for mobile and portable transmitters. See 47 CFR §§2.1091 and 2.1093 on source-based time-averaging requirement for mobile and portable transmitters.

$$S = PG / 4\pi R^2$$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator R=distance to the center of radiation of the antenna

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

#### 4. MEASUREMENT RESULT

| Test Mode     | Channel Frequency (MHz) | Field Strength (dBμV/m) | Max Output power (mW) | Calculation Value (Note 1) | Threshold Value |
|---------------|-------------------------|-------------------------|-----------------------|----------------------------|-----------------|
| GFSK          |                         |                         |                       |                            |                 |
| 2.4G(Peak)    | 2479                    | 84.74                   | 0.089                 | 0.028                      | 3.0             |
| 2.4G(Average) | 2402                    | 74.56                   | 0.009                 | 0.003                      | 3.0             |

Note 1: Calculation Value = [(max. power of channel, mW)/(min. test separation distance, mm)] · [√f(GHz)].

For example:  $0.089/5 \cdot \sqrt{2.479} = 0.028 \leq 3.0$

Note 2: Max Power (dBm) = Field Strength of Fundamental (dBμV/m@3m) - 95.23

Note 3: Max Power (mW) =  $10^{(\text{Max power (dBm)}/10)}$

**According to KDB447498 D01 V06, threshold at which no SAR required is ≤3.0 for 1-g SAR, separation distance is 5mm, and no simultaneous SAR measurement is required.**

#### 5. CONCLUSION

Since Source-base time average power is below SAR test exclusion power thresholds, the SAR evaluation is not required.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: [agc@agccert.com](mailto:agc@agccert.com) Web: <http://www.agccert.com/>