

FCC TEST REPORT

Product : 8" Tablet PC
Trade mark :  ,  , 
Model/Type reference : M8, M8X, M8 PLUS, M8X PLUS, T8, T8X, K8, K8X
Serial number : N/A
Ratings : Input: 5V  2A
(Class III, IPX0)
FCC ID : S5V-D07M80
Report number : EED32H000332-2
Date : Apr. 20, 2015
Regulations : See below

Test Standards	Results
☒ 47 CFR FCC Part 15 Subpart C 15.247: 2014	PASS


Prepared for:

Proexpress Distributor LLC
11011 GREENWOOD AVE.N APT 5, SEATTLE, WA 98103, United States

Prepared by:

Centre Testing International (Shenzhen) Corporation
Hongwei Industrial Zone, 70 Area, Bao'an District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Tested by: Kevin Yang

Reviewed by: 

Approved by: 

Date: Apr. 20, 2015

Jimmy Li

Lab manager

Check No.: 1727836113



TABLE OF CONTENTS

Description	Page
1. CERTIFICATION INFORMATION	4
2. TEST SUMMARY	4
3. MEASUREMENT UNCERTAINTY	5
4. PRODUCT INFORMATION	5
5. SYSTEM TEST CONFIGURATION	6
6. TEST EQUIPMENT LIST	6
7. SUPPORT EQUIPMENT LIST	6
8. 6DB BANDWIDTH MEASUREMENT	7
8.1. LIMITS	7
8.2. BLOCK DIAGRAM OF TEST SETUP	7
8.3. TEST PROCEDURE	7
8.4. TEST RESULT	7
9. POWER SPECTRAL DENSITY	13
9.1. LIMITS	13
9.2. BLOCK DIAGRAM OF TEST SETUP	13
9.3. TEST PROCEDURE	13
9.4. TEST RESULT	13
10. MAXIMUM PEAK CONDUCTED OUTPUT POWER MEASUREMENT	19
10.1. LIMITS	19
10.2. BLOCK DIAGRAM OF TEST SETUP	19
10.3. TEST PROCEDURE	19
10.4. TEST RESULT	19
11. BAND EDGE EMISSION MEASUREMENT	24
11.1. LIMITS	24
11.2. BLOCK DIAGRAM OF TEST SETUP	24
11.3. TEST PROCEDURE	24
11.4. TEST RESULT	24

12.	SPURIOUS RF CONDUCTED EMISSIONS MEASUREMENT	28
12.1.	LIMITS	28
12.2.	BLOCK DIAGRAM OF TEST SETUP	28
12.3.	TEST PROCEDURE	28
12.4.	TEST RESULT	28
13.	RADIATED EMISSIONS MEASUREMENT	34
13.1.	LIMITS	34
13.2.	BLOCK DIAGRAM OF TEST SETUP	34
13.3.	TEST PROCEDURE	35
13.4.	TEST RESULT	36
14.	AC CONDUCTED EMISSION TEST.....	41
14.1.	LIMITS	41
14.2.	BLOCK DIAGRAM OF TEST SETUP	41
14.3.	PROCEDURE OF CONDUCTED EMISSION TEST	41
14.4.	GRAPHS AND DATA	42
	APPENDIX 1 PHOTOGRAPHS OF TEST SETUP.....	44
	APPENDIX 2 EXTERNAL PHOTOGRAPHS OF PRODUCT.....	46
	APPENDIX 3 INTERNAL PHOTOGRAPHS OF PRODUCT.....	50

N/A means not applicable.

1. CERTIFICATION INFORMATION

Applicant: Proexpress Distributor LLC
11011 GREENWOOD AVE.N APT 5, SEATTLE, WA 98103,
United States

Manufacturer: SHENZHEN KAIDA TECHNOLOGY DIGITAL CO., LTD
5F, A Block, Tongsheng Technology Building, Huahui Road,
Dalang Street, Longhua Town, Bao'an District, Shenzhen

FCC ID: S5V-D07M80

Product: 8" Tablet PC

Model/Type reference: M8, M8X, M8 PLUS, M8X PLUS, T8, T8X, K8, K8X

Trade Name:



Serial Number: N/A

Report Number: EED32H000332-2

Sample Received Date: Mar. 20, 2015

Sample tested Date: Mar. 20, 2015 to Apr. 20, 2015

The above equipment was tested by Centre Testing International (Shenzhen) Corporation for compliance with the requirements set forth in the FCC Rules and Regulations Part 15, Subpart C and the measurement procedure according to ANSI C63.4:2009 and ANSI C63.10:2013.

2. TEST SUMMARY

No.	Test Item	Rule	Result
1	6dB Bandwidth	15.247(a)(2)	PASS
2	Peak Output Power	15.247(b)(3)	PASS
3	Power Spectral Density	15.247(e)	PASS
4	Bandedge Emission	15.247(d)	PASS
5	Spurious RF Conducted Emission	15.247(d)	PASS
6	Radiated Emission	15.247(d)	PASS
7	Conducted Emission	15.207	PASS
8	Antenna requirements	15.203	PASS (See Notes)

Notes: The product uses an internal integral antenna which in accordance with Section 15.203 is considered sufficient to comply with the provisions of this section.

3. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Value (dB)
Conducted disturbance	3.0
Radiated disturbance	4.9

4. PRODUCT INFORMATION

Items	Description
Rating	Input: 5V $\overline{=}$ 2A (Class III, IPX0)
Modulation	DSSS/ OFDM
Transmit Data Rate	802.11b: 1Mbps, 2Mbps, 5.5Mbps, 11Mbps 802.11g: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps 802.11n: MCS0, MCS1, MCS2, MCS3, MCS4, MCS5, MCS6, MCS7
Type	Integral antenna
Connector	fixed on board
Gain	0dBi

Technical Specification of WiFi module (802.11b/g/n)

Item	Description		
	IEEE 802.11b	IEEE 802.11g	IEEE 802.11n
Operating Frequency band	2412MHz-2462MHz		
Channel Number	11	11	11

Technical Specification of Carrier Frequency

Frequency Band	Channel No.	Frequency	Channel No.	Frequency	Channel No.	Frequency
2412MHz -2462MHz	1	2412 MHz	6	2437 MHz	11	2462 MHz
	2	2417 MHz	7	2442 MHz	--	--
	3	2422 MHz	8	2447 MHz	--	--
	4	2427 MHz	9	2452 MHz	--	--
	5	2432 MHz	10	2457 MHz	--	--

All models are same except model name and brand name. Model M8 was selected for test.

Test mode : Keeping TX with dutycycle >98%

Remark: Input voltage have been adjusted from 85% to 115% , no influence was found .

5. SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. It was powered by AC 100-240V. Only the worst case data were recorded in this test report.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

6. TEST EQUIPMENT LIST

Equipment	Manufacturer	Model	Serial No.	Due Date
3M Chamber & Accessory Equipment	TDK	SAC-3	---	06/01/2016
Receiver	R&S	ESCI	100435	07/08/2015
TRILOG Broadband Antenna	schwarzbeck	VULB 9163	618	06/17/2015
Multi device Controller	maturo	NCD/070/10711112	---	N/A
Horn Antenna	ETS-LINGREN	3117	00057407	07/07/2015
Microwave Preamplifier	Agilent	8449B	3008A02425	03/19/2016
Spectrum Analyzer	R&S	FSP40	100416	07/06/2015
Receiver	R&S	ESCI	100009	07/19/2015
LISN	R&S	ENV216	100098	07/19/2015

7. SUPPORT EQUIPMENT LIST


No.	Device Type	Brand	Model	Series No.	Certification Type
1.	---	---	---	---	---
2.	---	---	---	---	---

8. 6DB BANDWIDTH MEASUREMENT

8.1. LIMITS

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.2. BLOCK DIAGRAM OF TEST SETUP



8.3. TEST PROCEDURE

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set spectrum analyzer's RBW and VBW to applicable value with Peak in Max Hold.
3. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level.
4. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

8.4. TEST RESULT

The test data of worst case are below:

802.11b, 1Mbps

Frequency (MHz)	Measured Value (MHz)	Result
2412	10	PASS
2437	10	PASS
2462	10	PASS


802.11g, 6Mbps

Frequency (MHz)	Measured Value (MHz)	Result
2412	16.64	PASS
2437	16.64	PASS
2462	16.64	PASS

802.11n, MCS0


Frequency (MHz)	Measured Value (MHz)	Result
2412	17.54	PASS
2437	17.54	PASS
2462	17.52	PASS

Please see the following plots (worst case):
802.11b, 1Mbps:




Date: 31.MAR.2015 12:26:40

Low channel



Date: 31.MAR.2015 12:16:08


Middle channel



Date: 31.MAR.2015 12:01:27


High channel

802.11g, 6Mbps:




Date: 1.APR.2015 12:29:01

Low channel



Date: 1.APR.2015 12:41:35


Middle channel



Date: 1.APR.2015 14:24:04


High channel

802.11n, MCS0:




Date: 2.APR.2015 13:31:36

Low channel



Date: 2.APR.2015 13:36:53

Middle channel




High channel

9. POWER SPECTRAL DENSITY

9.1. LIMITS

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

9.2. BLOCK DIAGRAM OF TEST SETUP



9.3. TEST PROCEDURE

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set spectrum analyzer's RBW and VBW to applicable and set span wide enough to capture the whole plot, record the frequency of the max emission in the plot.
3. Set the frequency as center frequency, and set RBW = 3 kHz, VBW > RBW, sweep = (SPAN/3 kHz) with Peak detector in Max Hold mode.
4. Read the output peak data from the spectrum analyzer directly.

9.4. TEST RESULT

The test data of worst case are below:

802.11b, 1Mbps

Frequency (MHz)	Measured Value (dBm)	Result
2412	-26.28	PASS
2437	-25.84	PASS
2462	-25.34	PASS


802.11g, 6Mbps

Frequency (MHz)	Measured Value (dBm)	Result
2412	-30.07	PASS
2437	-31.01	PASS
2462	-31.59	PASS


802.11n, MCS0

Frequency (MHz)	Measured Value (dBm)	Result
2412	-27.61	PASS
2437	-28.98	PASS
2462	-28.65	PASS


Please see the following plots (worst case):
802.11b, 1Mbps:



Low channel




Middle channel



Date: 31.MAR.2015 16:41:47


High channel

802.11g, 6Mbps:




Date: 2.APR.2015 16:00:34

Low channel



Date: 2.APR.2015 15:59:46


Middle channel



Date: 2.APR.2015 15:56:28


High channel

802.11n, MCS0:




Date: 3.APR.2015 11:23:02

Low channel



Date: 3.APR.2015 11:20:41

Middle channel



High channel


10. MAXIMUM PEAK CONDUCTED OUTPUT POWER MEASUREMENT

10.1. LIMITS

The maximum peak conducted output power of the intentional radiator shall not exceed the following:

For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt (30dBm).

10.2. BLOCK DIAGRAM OF TEST SETUP



10.3. TEST PROCEDURE

1. The transmitter output is connected to the Spectrum analyzer. The Spectrum analyzer is set to the peak power detection.
2. Set spectrum analyzer's RBW and VBW to applicable and set span wide enough to capture the whole plot, record the frequency of the max emission in the plot.
3. Set the frequency as center frequency, and set RBW = 1 MHz, VBW >RBW, sweep= auto with Peak detector in Max Hold mode.

10.4. TEST RESULT

802.11B:

Frequency (MHz)	Data rate (Mbps)	Result (dBm)	Limit (dBm)
Low Channel: 2412	1	4.55	30
	11	4.34	30
Middle Channel: 2437	1	4.65	30
	11	4.43	30
High Channel: 2462	1	4.52	30
	11	4.34	30


802.11g:

Frequency (MHz)	Data rate (Mbps)	Result (dBm)	Limit (dBm)
Low Channel: 2412	6	3.66	30
	18	3.56	30
	54	3.45	30
Middle Channel: 2437	6	3.98	30
	18	3.87	30
	54	3.91	30
High Channel: 2462	6	3.54	30
	18	3.53	30
	54	3.50	30


802.11g:

Frequency (MHz)	Data rate (Mbps)	Result (dBm)	Limit (dBm)
Low Channel: 2412	MCS0	4.87	30
	MCS3	4.46	30
	MCS7	4.67	30
Middle Channel: 2437	MCS0	4.74	30
	MCS3	4.78	30
	MCS7	4.76	30
High Channel: 2462	MCS0	4.65	30
	MCS3	4.64	30
	MCS7	4.39	30


Please see the following plots (Typical case):
802.11b, 1Mbps:



Low channel




Middle channel




High channel


802.11g, 6Mbps:



Low channel




Middle channel




High channel


802.11n, MCS0:



Low channel



Middle channel




High channel

11. BAND EDGE EMISSION MEASUREMENT

11.1. LIMITS

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

11.2. BLOCK DIAGRAM OF TEST SETUP




11.3. TEST PROCEDURE

- Set to the maximum power setting and enable the EUT transmit continuously.
- Set RBW = 100 kHz, VBW = 300 kHz ($\geq$ RBW). Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
- Enable hopping function of the EUT and then repeat step a and b.
- Measure and record the results in the test report.


11.4. TEST RESULT

Typical case data attached.---please see the following plots.


802.11b, 1Mbps:
2412MHz:




2462MHz:



802.11g, 6Mbps:
2412MHz:




2462MHz:




802.11n, MCS0:

2412MHz:



Date: 2.APR.2015 17:36:29

2462MHz:




Date: 2.APR.2015 17:32:45

12. SPURIOUS RF CONDUCTED EMISSIONS MEASUREMENT

12.1. LIMITS

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

12.2. BLOCK DIAGRAM OF TEST SETUP




12.3. TEST PROCEDURE

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set spectrum analyzer's RBW and VBW to applicable value with Peak in Max Hold.
3. Record the peak level of the in-band emission and all spurious emissions from the lowest frequency generated in the product up through the 10th harmonic.


12.4. TEST RESULT

Worst case data---Please see the following plots.


802.11b, 1Mbps:



Low channel




Middle channel



Date: 31.MAR.2015 15:59:36


High channel

802.11g, 6Mbps:




Date: 2.APR.2015 15:29:46

Low channel



Date: 2.APR.2015 15:31:46


Middle channel




Date: 2.APR.2015 15:53:49

High channel


802.11n, MCS0:



Low channel



Middle channel



High channel

13. RADIATED EMISSIONS MEASUREMENT

13.1. LIMITS


The field strength of any emissions, which appear outside of operating frequency band and restricted band specified on 15.205(a), shall not exceed the general radiated emission limits as below.

Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Distance (m)
0.009-0.490	$2400/F(\text{kHz})$	300
0.490-1.705	$24000/F(\text{kHz})$	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


Note: the tighter limit applies at the band edges.

13.2. BLOCK DIAGRAM OF TEST SETUP


For radiated emissions from 9kHz to 30MHz



For radiated emissions from 30 - 1000MHz



For radiated emissions from 1GHz to 25GHz



13.3. TEST PROCEDURE

Below 30MHz:

- The product is placed on a turntable 0.8 meters above the ground in the chamber, 1 meter away from the antenna (loop antenna). The maximum values of the field strength are recorded by adjusting the polarizations of the test antenna and rotating the turntable.
- For each suspected emission, the product was arranged to its worst case and then turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test frequency analyzer system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

30MHz ~ 1GHz:

- The Product was placed on the non-conductive turntable 0.8m above the ground at a chamber.
- Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 100 kHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied between 1~4 m in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
- For each frequency whose maximum record was higher or close to limit, measure its QP value (120 kHz RBW): vary the antenna's height and rotate the turntable from 0 to 360 degrees to find the height and degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to QP Detector and specified bandwidth with Maximum Hold Mode, and record the maximum value.

Above 1GHz:

- The EUT was placed on the non-conductive turntable 1.5 m above the ground at a chamber.
- Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 1MHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the

antenna is varied in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.

13.4. TEST RESULT


Below 30MHz:

No emissions were found higher than the background below 30MHz and background is lower than the limit, so it deems to compliance with the limit without recorded.

30MHz ~ 1GHz:


The test data of low channel, middle channel and high channel in IEEE 802.11b/g/n are almost same in frequency bands 30MHz to 1GHz and the data of low channel in IEEE 802.11b of 1Mbps are chosen as representative in below:

H:



Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
51.340000	23.90	15.9	40.0	16.1	QP	200.0	342.00	HORIZONTAL
59.100000	22.50	14.9	40.0	17.5	QP	200.0	332.00	HORIZONTAL
99.840000	18.80	13.4	43.5	24.7	QP	100.0	92.00	HORIZONTAL
214.300000	24.20	14.6	43.5	19.3	QP	100.0	320.00	HORIZONTAL
538.280000	27.70	21.5	46.0	18.3	QP	200.0	238.00	HORIZONTAL
920.460000	33.80	27.1	46.0	12.2	QP	200.0	138.00	HORIZONTAL

V:



Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
33.880000	36.80	13.5	40.0	3.2	QP	100.0	287.00	VERTICAL
55.220000	32.80	15.4	40.0	7.2	QP	100.0	277.00	VERTICAL
142.520000	20.70	10.6	43.5	22.8	QP	100.0	162.00	VERTICAL
177.440000	22.70	12.6	43.5	20.8	QP	100.0	235.00	VERTICAL
549.920000	28.30	21.7	46.0	17.7	QP	100.0	121.00	VERTICAL
910.760000	33.20	27.1	46.0	12.8	QP	200.0	70.00	VERTICAL

Above 1GHz:

The test data of worst case are below:

IEEE 802.11b, 1Mbps:

Frequency (MHz)	Measurement (dBuV/m)	Limit (dBuV/m)	Detector Type	Antenna (H/V)	Result (P/F)
Low channel (2412MHz)					
2390.0	33.12	74	PK	H	P
2400.0	40.12	74	PK	H	P
4824.0	33.14	74	PK	H	P
2390.0	30.98	74	PK	V	P
2400.0	40.67	74	PK	V	P
4824.0	35.77	74	PK	V	P
Middle channel (2437MHz)					
4874.0	33.22	74	PK	H	P
4874.0	32.09	74	PK	V	P
High channel (2462MHz)					
2483.5	32.78	74	PK	H	P
4924.0	33.56	74	PK	H	P
2483.5	33.23	74	PK	V	P
4924.0	34.45	74	PK	V	P

Remark:

1. The above tables show that the frequencies peak data are all below the average limit, so the average data of these frequencies are deemed to fulfill the average limits and not reported.
2. No emission found from 18GHz to 25GHz.
3. All outside of operating frequency band and restricted band specified are below 15.209.

IEEE 802.11g, 6Mbps:

Frequency (MHz)	Measurement (dBuV/m)	Limit (dBuV/m)	Detector Type	Antenna (H/V)	Result (P/F)
Low channel (2412MHz)					
2390.0	32.23	74	PK	H	P
2400.0	40.34	74	PK	H	P
4824.0	32.98	74	PK	H	P
2390.0	31.67	74	PK	V	P
2400.0	41.43	74	PK	V	P
4824.0	33.43	74	PK	V	P
Middle channel (2437MHz)					
4874.0	34.23	74	PK	H	P
4874.0	33.12	74	PK	V	P
High channel (2462MHz)					
2483.5	32.56	74	PK	H	P
4924.0	33.34	74	PK	H	P
2483.5	31.98	74	PK	V	P
4924.0	34.12	74	PK	V	P

Remark:

1. The above tables show that the frequencies peak data are all below the average limit, so the average data of these frequencies are deemed to fulfill the average limits and not reported.
2. No emission found from 18GHz to 25GHz.
3. All outside of operating frequency band and restricted band specified are below 15.209.

IEEE 802.11n, MCS0:

Frequency (MHz)	Measurement (dBuV/m)	Limit (dBuV/m)	Detector Type	Antenna (H/V)	Result (P/F)
Low channel (2412MHz)					
2390.0	33.23	74	PK	H	P
2400.0	40.34	74	PK	H	P
4824.0	32.56	74	PK	H	P
2390.0	32.12	74	PK	V	P
2400.0	40.23	74	PK	V	P
4824.0	33.66	74	PK	V	P
Middle channel (2437MHz)					
4874.0	32.56	74	PK	H	P
4874.0	34.23	74	PK	V	P
High channel (2462MHz)					
2483.5	32.10	74	PK	H	P
4924.0	34.23	74	PK	H	P
2483.5	31.45	74	PK	V	P
4924.0	34.23	74	PK	V	P

Remark:

1. The above tables show that the frequencies peak data are all below the average limit, so the average data of these frequencies are deemed to fulfill the average limits and not reported.
2. No emission found from 18GHz to 25GHz.
3. All outside of operating frequency band and restricted band specified are below 15.209.

14. AC CONDUCTED EMISSION TEST


14.1. LIMITS

Limits for Class B digital devices

Frequency range (MHz)	Limits dB(μV)	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

14.2. BLOCK DIAGRAM OF TEST SETUP



14.3. PROCEDURE OF CONDUCTED EMISSION TEST


- The Product was placed on a nonconductive table above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
- The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

14.4. GRAPHS AND DATA

Product : 8" Tablet PC
Power : AC 120V/60Hz
Mode : Keeping TX (WIFI)


Model/Type reference : M8
Temperature : 22℃
Humidity : 52%

L:




No.	Freq. MHz	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1539	53.51	47.41	18.36	9.90	63.41	57.31	28.26	65.78	55.78	-8.47	-27.52	P	
2	0.2540	31.15		15.02	9.90	41.05		24.92	61.62	51.62	-20.57	-26.70	P	
3	0.3339	28.10		15.18	9.90	38.00		25.08	59.35	49.35	-21.35	-24.27	P	
4	0.7300	27.08		7.73	9.90	36.98		17.63	56.00	46.00	-19.02	-28.37	P	
5	6.8140	34.05		24.39	9.90	43.95		34.29	60.00	50.00	-16.05	-15.71	P	

N:




No.	Freq. MHz	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1500	53.82	47.43	20.60	9.90	63.72	57.33	30.50	65.99	55.99	-8.66	-25.49	P	
2	0.3220	31.08		14.60	9.90	40.98		24.50	59.65	49.65	-18.67	-25.15	P	
3	0.5220	27.10		10.94	9.90	37.00		20.84	56.00	46.00	-19.00	-25.16	P	
4	0.7380	28.66		10.25	9.90	38.56		20.15	56.00	46.00	-17.44	-25.85	P	
5	7.0020	33.89		25.32	9.90	43.79		35.22	60.00	50.00	-16.21	-14.78	P	

APPENDIX 1 PHOTOGRAPHS OF TEST SETUP



TEST SETUP OF RADIATED EMISSION (30MHz-1GHz)



TEST SETUP OF RADIATED EMISSION (above 1GHz)



TEST SETUP OF CONDUCTED EMISSION

APPENDIX 2 EXTERNAL PHOTOGRAPHS OF PRODUCT



External View of product-1



External View of product-2



External View of product-3



External View of product-4



External View of product-5



External View of product-6



External View of product-7

APPENDIX 3 INTERNAL PHOTOGRAPHS OF PRODUCT




Internal View of product-1




Internal View of product-2




Internal View of product-3




Internal View of product-4



Internal View of product-5



Internal View of product-6



Internal View of product-7



Internal View of product-8

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.