

SPECIFICATION

Chip Antenna

Manufacturer: Sena Technologies, Inc.

Part Number: SENA_009

WRITTEN	CHECKED	APPROVED
Seunghyun Kim	Seunghyun Kim	

September 2, 2020

Sena Technologies, Inc.

19, Heolleung-ro 569-gil, Gangnam-gu,
Seoul, 06376, South Korea
Tel: +82-2-576-7362
Fax: +82-2-573-7710
Website: <http://www.sena.com>

1. SPECIFICATIONS

1.1. Electrical Specifications


ITEM	SPEC.	Unit
Frequency	2400-2485	MHz
Bandwidth @ VSWR 2.5:1	100	MHz
Gain Max.	0.5	dBi
Polarization	Linear	
Azimuth Beam Pattern	Omni-directional	
Impedance	50	Ω

※ These values are measured on the matched reference test board.

1.2. Mechanical Specifications

Electrode	Silver	
Dimensions (L x W x H)	9.0 x 3.0 x 1.2	mm
Operating Temperature	-35 ~ +85	°C

1.3. Appearance and Dimensions



L	9.0
W	3.0
H	1.2




- Laminate: FR-4, 1.20mm

- Plating Thickness: 1.5oz (54um)


- Board Thickness: 1.30mm (typ.)

3. Radiation Data

Frequency	Efficiency	Average Gain			Max Gain			Max Position	Directivity
		Ver	Hor	Total	Ver	Hor	Total		
2400 MHz	37.4 %	-6.6 dBi	-8.0 dBi	-4.3 dBi	-1.1 dBi	-0.9 dBi	0.1 dBi	Theta135/Pie255	4.34 dB
2442 MHz	43.0 %	-6.0 dBi	-7.5 dBi	-3.7 dBi	-0.3 dBi	-0.1 dBi	0.5 dBi	Theta15/Pie240	4.60 dB
2485 MHz	37.2 %	-6.6 dBi	-8.1 dBi	-4.3 dBi	-0.1 dBi	-0.2 dBi	0.2 dBi	Theta135/Pie255	4.91 dB




4. RELIABILITY TEST

No	Item	Test condition	Test Requirements
1	Adhesion strength	. Applied force on SMD chip till detached point from PCB  PCB →  ← F  SMD PAD	1. No mechanical damage by forces applied on the right 2. Strength (F) > 5 kgf
2	Thermal Shock (Temperature Cycle)	1. 1 cycle / step 1 : $-40 \pm 3^{\circ}\text{C}$, 30 min step 2 : $+85 \pm 3^{\circ}\text{C}$, 30 min 2. Number of cycle : 10 3. Measure after left for 48 hrs min. at room temperature	1. No visual damage 2. VSWR satisfy
3	High Temperature Resistance	1. Temperature: $+85 \pm 5^{\circ}\text{C}$ 2. Time : 96 hrs 3. Measure VSWR_C after left for 24 hrs min. at room temperature	1. No visual damage 2. VSWR satisfy
4	Low Temperature Resistance	1. Temperature: $-40 \pm 5^{\circ}\text{C}$ 2. Time : 96 hrs 3. Measure VSWR_C after left for 48 hrs min. at room temperature	1. No visual damage 2. VSWR satisfy
5	Humidity (Steady Condition)	1. Humidity : 85 % RH 1. Temperature: $+85 \pm 3^{\circ}\text{C}$ 2. Time : 96 hrs 3. Measure VSWR_C after left for 48 hrs min. at room temperature	1. No visual damage 2. VSWR satisfy
6	ESD	1. ESD Level : 8KV 2. Mode : Contact discharge 3. Number of cycle : 100 ※ Used Ref test PCB.	1. No visual damage 2. VSWR satisfy

5. SOLDERING RECOMMENDATIONS

5.1. Reflow Soldering Profile



Note: All the through hole devices can withstand 260°C soldering by terminals only (ie wave solder or hand soldering process)