



TEST REPORT



Report No. : KES-RF260084
Page 1 / 45

KES Co., Ltd.

#3002, #3503, #3701, 40, Simin-daero365beon-gil, Dongan-gu,
Anyang-si, Gyeonggi-do, 14057, Republic of Korea
Tel : +82-31-425-6200, Fax : +82-31-341-3838

■ FCC & IC TEST REPORT

1. Client

- Name : Sena Technologies Co., Ltd.
- Address : 19, Heolleung-ro 569-gil, Gangnam-gu, Seoul, South Korea

2. Sample Description

- Product item : Wireless Communication Systems
- Model name : WiFiLink
- Manufacturer etc. : Sena Technologies Co., Ltd.

3. Date of test : 2026.01.19 ~ 2026.02.05

4. Location of Test : ☒ Permanent Testing Lab ☐ On Site Testing

- Address : 473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, 12658, Rep. of Korea

5. Test method used : Part 15 Subpart C 15.247, RSS-247 (Issue 4) & RSS-Gen (Issue 5)

6. Test result : PASS

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test report cannot be reproduced and copied without permission without the written consent of KES Co., Ltd.

This laboratory is not accredited for the test results marked *.

This test report is not related to KOLAS accreditation.

Affirmation	Tested by	Technical Manager
	Name : Gu-Bong, Kang (Signature)	Name : Young-Jin, Lee (Signature)

[김구봉]2026/02/20

[이영진]2026/02/20

2026. 02. 20.

KES Co., Ltd.



REPORT REVISION HISTORY

Date	Test Report No.	Revision History
2026.02.20	KES-RF260084	Initial

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.





TABLE OF CONTENTS

1.	General information	4
1.1.	EUT description	4
1.2.	Test configuration.....	5
1.3.	Information about derivative model	5
1.4.	Accessory information	5
1.5.	Device modifications.....	5
1.6.	Sample calculation	6
1.7.	Measurement Uncertainty	6
1.8.	Worst case data rate.....	6
1.9.	Frequency/channel operations	7
2.	Summary of tests	8
3.	Test results	9
3.1.	Radiated restricted band and emissions	9
3.2.	AC conducted emissions	41
3.3.	Antenna Requirement.....	44
Appendix A.	Measurement equipment.....	45



1. General information

Applicant: Sena Technologies Co., Ltd.
Applicant address: 19, Heolleung-ro 569-gil, Gangnam-gu, Seoul, South Korea
Test site: KES Co., Ltd.
Test site address: ☐ #3002, #3503, #3701, 40, Simin-daero365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Rep. of Korea
☒ 473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, 12658, Rep. of Korea
Test Facility FCC Accreditation Designation No.: KR0100, Registration No.: 444148
ISED Registration No.: 23298
FCC rule part(s): 15.247
FCC ID: S7A-SP194
IC rule part(s): RSS-247 (Issue 4), RSS-Gen (Issue 5)
IC Number: 8154A-SP194
Module FCC ID: VPYLBEE59B1LV
Module IC Number: 772C-LBEE59B1LV
Test device serial No.: ☒ Production ☐ Pre-production ☐ Engineering

1.1. EUT description

Equipment under test Wireless Communication Systems
Frequency range & Number of channels 2 402 MHz ~ 2 480 MHz (BDR/EDR) : 79 ch
2 402 MHz ~ 2 480 MHz (LE 1 Mbps) : 40 ch
2 412 MHz ~ 2 462 MHz (802.11b/g/n_HT20) : 11 ch
UNII-1 (FCC only) 5 180 MHz ~ 5 240 MHz (802.11a/n_HT20) : 4 ch
UNII-2A (FCC only) 5 260 MHz ~ 5 320 MHz (802.11a/n_HT20) : 4 ch
UNII-2C (FCC & IC) 5 500 MHz ~ 5 720 MHz (802.11a/n_HT20) : 12 ch
UNII-3 (FCC & IC) 5 745 MHz ~ 5 825 MHz (802.11a/n_HT20) : 5 ch
Model WiFiLink
Modulation technique GFSK, $\pi/4$ DQPSK, 8DPSK, DSSS, OFDM
Antenna specification Bluetooth
2.4 GHz band Chip Antenna // Peak gain: 0.5 dBi
WLAN
2.4 GHz band PCB Antenna // Peak gain: 0.9 dBi
5.15 ~ 5.35 GHz PCB Antenna // Peak gain: 2.0 dBi
5.47 ~ 5.85 GHz PCB Antenna // Peak gain: 2.0 dBi
Power source DC 3.8 V (Battery)
H/W version 1.0
S/W version 1.0
Serial Number M060211

**1.2. Test configuration**

The **Sena Technologies Co., Ltd. // Wireless Communication Systems // WiFiLink**
// FCC ID: S7A-SP194 // IC Number: 8154A-SP194 was tested according to the specification of EUT, the EUT must comply with following standards and KDB documents.

IC RSS-247 Issue 4 and RSS-Gen Issue 5
KDB 789033 D02 v02r01
FCC - ANSI C63.10-2020
IC - ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

1.3. Information about derivative model

N/A

1.4. Accessory information

Equipment	Manufacturer	Model	Serial No.	Power source
Main Unit	Sena Technologies Co., Ltd.	WiFiLink	-	DC 3.8 V (Battery)
Belt Clip Mount	-	-	-	-
USB-C Charging Cable	-	-	-	-

1.5. Device modifications

N/A



1.6. Sample calculation

Where relevant, the following sample calculation is provided
For all conducted test items :

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

For Radiation test :

Field strength level (dB μ V/m) = Measured level (dB μ V) + Antenna factor (dB) + Cable loss (dB) – Amplifier gain (dB)

1.7. Measurement Uncertainty

Test Item		Uncertainty
Uncertainty for Conduction emission test		2.22 dB (SHIELD ROOM #6)
Uncertainty for Radiation emission test (include Fundamental emission)	Below 1 GHz	4.04 dB (SAC #6)
	Above 1 GHz	5.32 dB (SAC #5)
Note. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.		

1.8. Worst case data rate

1. Worst-case data rates were:

Mode	Data rate
LE 1 Mbps	1 Mbps
802.11b	1 Mbps
802.11g	6 Mbps
802.11n_HT20	MCS0

**1.9. Frequency/channel operations**

Ch.	Frequency (MHz)	Rate(Mbps)
00	2 402	BDR 1 Mbps, EDR 2 Mbps, EDR 3 Mbps
.	.	.
39	2 441	BDR 1 Mbps, EDR 2 Mbps, EDR 3 Mbps
.	.	.
78	2 480	BDR 1 Mbps, EDR 2 Mbps, EDR 3 Mbps

Ch.	Frequency (MHz)	Rate(Mbps)
00	2 402	LE 1 Mbps
.	.	.
20	2 442	LE 1 Mbps
.	.	.
39	2 480	LE 1 Mbps

Ch.	Frequency (MHz)	Mode
1	2 412	802.11b/g/n_HT20
.	.	.
6	2 437	802.11b/g/n_HT20
.	.	.
11	2 462	802.11b/g/n_HT20

UNII-1 (FCC only)

Ch.	Frequency (MHz)
36	5 180
44	5 220
48	5 240

UNII-2A (FCC only)

Ch.	Frequency (MHz)
52	5 260
56	5 280
64	5 320

UNII-2C (FCC & IC)

Ch.	Frequency (MHz)
100	5 500
120	5 600
144	5 720

UNII-3 (FCC & IC)

Ch.	Frequency (MHz)
149	5 745
157	5 785
165	5 825

802.11a/n_HT20 mode



2. Summary of tests

Section in FCC Part 15	Section in RSS-247 & Gen	Test description	Test results
-	RSS-Gen 6.7	99% Occupied Bandwidth	N/T ^{Note.1}
15.247(a)(2)	RSS-247 6.3.1 (a)	6 dB bandwidth	N/T ^{Note.1}
15.247(b)(3)	RSS-247 6.3.2	Output power	N/T ^{Note.1}
15.247(e)	RSS-247 6.3.1 (b)	Power spectral density	N/T ^{Note.1}
15.205, 15.209	RSS-247 6.6 RSS-Gen 8.9,8,10	Radiated restricted band and emission	Pass
15.247(d)	RSS-247 6.6	Conducted spurious emission and band edge	N/T ^{Note.1}
15.207(a)	RSS-Gen 8.8	AC Conducted emissions	Pass
15.203	-	Antenna Requirement	Pass

*N/T: Not Tested

Note.

1. This product is equipped with an approved module, please refer to Module Report below for details.
Report No. 1901WSU002-U5, 1901WSU002-U1
2. By the request of applicant, test is performed with power setting value below :

Mode	Frequency (MHz)	Setting value
LE 1 Mbps	2 402 ~ 2 480	Default
802.11b (1 Mbps)	2 412	77
	2 437	77
	2 462	77
802.11g (6 Mbps)	2 412	80
	2 437	80
	2 462	80
802.11n_HT20 (MCS0)	2 412	80
	2 437	79
	2 462	80




3. Test results


3.1. Radiated restricted band and emissions

Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions.




The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.





The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



Test procedure

Radiated emissions from the EUT were measured according to the dictates in section 11.11 & 11.12 of ANSI C63.10-2020 (FCC) & ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 (IC).

Test procedure below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel, ground parallel and perpendicular of the antenna are set to make the measurement. It was determined that parallel was worst-case orientation; therefore, all final radiated testing was performed with the EUT in parallel.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum hold mode.

Test procedure above 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground for 30 MHz-1 GHz and 1.5 meters for above 1 GHz at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The antenna is a bi-log antenna, a horn antenna, and its height are varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

5. Spectrum analyzer settings for $f < 1$ GHz:

- ① Span = wide enough to fully capture the emission being measured
- ② RBW = 120 kHz
- ③ VBW $\geq$ RBW
- ④ Detector = quasi peak
- ⑤ Sweep time = auto
- ⑥ Trace = max hold

6. Spectrum analyzer settings for $f \geq 1$ GHz: Peak

- ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- ② RBW = 1 MHz
- ③ VBW ≥ 3 MHz
- ④ Detector = peak
- ⑤ Sweep time = auto
- ⑥ Trace = max hold
- ⑦ Trace was allowed to stabilize

7. Spectrum analyzer settings for $f \geq 1$ GHz: Average

- ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- ② RBW = 1 MHz
- ③ VBW $\geq 3 \times$ RBW
- ④ Detector = RMS, if $\text{span}/(\# \text{ of points in sweep}) \leq (\text{RBW}/2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- ⑤ Averaging type = power(i.e., RMS)
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- ⑥ Sweep = auto
- ⑦ Trace = max hold
- ⑧ Perform a trace average of at least 100 traces.
- ⑨ A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step ⑤, then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step ⑤, then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

**Note.**

1. $f < 30$ MHz, extrapolation factor of 40 dB/decade of distance. $F_d = 40\log(D_m/D_s)$
 $f \geq 30$ MHz, extrapolation factor of 20 dB/decade of distance. $F_d = 20\log(D_m/D_s)$
 Where:
 F_d = Distance factor in dB
 D_m = Measurement distance in meters
 D_s = Specification distance in meters
2. Field strength(dB μ V/m) = Level(dB μ V) + CF (dB) + or DCF(dB)
3. Margin(dB) = Limit(dB μ V/m) - Field strength(dB μ V/m)
4. Emissions below 18 GHz were measured at a 3 meter test distance while emissions above 18 GHz were measured at a 1 meter test distance with the application of a distance correction factor.
5. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z, it was determined that **X orientation** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **X orientation**.
6. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
7. According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

FCC Limit

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

Frequency (MHz)	Distance (Meters)	Radiated (μ V/m)
0.009 ~ 0.490	300	$2400/F(\text{kHz})$
0.490 ~ 1.705	30	$24000/F(\text{kHz})$
1.705 ~ 30.0	30	30
30 ~ 88	3	100**
88 ~ 216	3	150**
216 ~ 960	3	200**
Above 960	3	500

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 MHz, 76 ~ 88 MHz, 174 ~ 216 MHz or 470 ~ 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

**IC Limit**

According to RSS-Gen, Except when the requirements applicable to a given device state otherwise, emissions from licence-exempt transmitters shall comply with the field strength limits :

Frequency (MHz)	Distance (Meters)	Radiated ($\mu\text{V/m}$)
0.009 ~ 0.490	300	$2\,400 / F(\text{kHz})$
0.490 ~ 1.705	30	$24\,000 / F(\text{kHz})$
1.705 ~ 30.0	30	30
30 ~ 88	3	100
88 ~ 216	3	150
216 ~ 960	3	200
Above 960*	3	500

* Unless otherwise specified, for all frequencies greater than 1 GHz, the radiated emission limits for licence-exempt radio apparatus stated in applicable RSSs (including RSS-Gen) are based on measurements using a linear average detector function having a minimum resolution bandwidth of 1 MHz. If an average limit is specified for the EUT, then the peak emission shall also be measured with instrumentation properly adjusted for such factors as pulse desensitization to ensure the peak emission is less than 20 dB above the average limit.

Note: Transmitting devices are not permitted in restricted frequency bands unless stated otherwise in the specific RSS.

**Duty cycle**


Regarding to KDB 558074 D01_v05 r02, 6. Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

- A diode detector and an oscilloscope that together have sufficiently short response time to permit accurate measurements of the on- and off-times of the transmitted signal.
- The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on- and off-times of the transmitted signal.

Mode	T _{on} time (ms)	Period (ms)	Duty cycle (Linear)	Duty cycle (%)	Duty cycle correction factor (dB)
LE 1 Mbps	0.391	0.625	0.63	62.56	2.01
802.11b (1 Mbps)	12.429	12.436	0.99	99.94	-
802.11g (6 Mbps)	2.067	2.094	0.99	98.71	-
802.11n_HT20 (MCS0)	1.930	1.953	0.99	98.82	-

Duty cycle (Linear) = T_{on} time/Period

DCF(Duty cycle correction factor (dB)) = 10log(1/duty cycle)




Note.

- Tested with the maximum duty that can be set on the EUT.



Test results (Below 30 MHz)

Mode:	LE 1 Mbps
Distance of measurement:	3 meter
Channel:	39 (Worst case)




Note.

1. No spurious emission were detected under 30 MHz.



Mode: 802.11n_HT20 (MCS0) (Worst case)
Distance of measurement: 3 meter
Channel: 1 (Worst case)




Note.

1. No spurious emission were detected under 30 MHz.

**Test results (Below 1 000 MHz)**

Mode: LE 1 Mbps
Distance of measurement: 3 meter
Channel: 39 (Worst case)






Mode: 802.11n_HT20 (MCS0) (Worst case)

Distance of measurement: 3 meter

Channel: 1 (Worst case)

Horizontal // Vertical



Final Result

No.	Frequency [MHz]	Pol	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	78.743	H	48.7	-18.7	30.0	40.0	10.0	400.0	170.8	
2	78.743	V	45.1	-18.7	26.4	40.0	13.6	387.0	35.9	
3	208.601	H	44.3	-13.2	31.1	43.5	12.4	100.0	330.2	
4	208.601	V	41.8	-13.2	28.6	43.5	14.9	110.0	209.8	
5	214.543	V	42.1	-13.0	29.1	43.5	14.4	107.0	231.9	
6	217.453	H	45.0	-12.9	32.1	46.0	13.9	109.0	330.2	
7	307.784	H	47.8	-10.3	37.5	46.0	8.5	101.0	0.0	
8	312.270	V	49.7	-10.1	39.6	46.0	6.4	157.0	36.6	
9	313.725	H	51.7	-10.1	41.6	46.0	4.4	101.0	173.0	
10	313.725	V	50.1	-10.1	40.0	46.0	6.0	105.0	308.8	
11	321.000	H	46.1	-9.7	36.4	46.0	9.6	107.0	173.0	
12	329.730	V	40.9	-9.4	31.5	46.0	14.5	142.0	308.8	



Report No. : KES-RF260084

Test results (Above 1 000 MHz)


Mode: LE 1 Mbps
Distance of measurement: 3 meter
Channel: 00


- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 000.90	43.90	Peak	V	-7.57	-	36.33	74.00	37.67
1 129.69	44.54	Peak	H	-6.86	-	37.68	74.00	36.32

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 324.27	42.39	Peak	H	0.75	-	43.14	74.00	30.86
2 338.51	42.87	Peak	V	0.83	-	43.70	74.00	30.30





Note.


1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Mode: LE 1 Mbps
Distance of measurement: 3 meter
Channel: 20

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 000.10	43.97	Peak	V	-7.58	-	36.39	74.00	37.61
1 061.89	44.91	Peak	H	-7.23	-	37.68	74.00	36.32

**Note.**

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.




Mode: LE 1 Mbps
Distance of measurement: 3 meter
Channel: 39


- Spurious

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 131.09	44.28	Peak	H	-6.85	-	37.43	74.00	36.57
1 298.87	44.15	Peak	V	-5.94	-	38.21	74.00	35.79

- Band edge

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 493.93	43.25	Peak	V	1.32	-	44.57	74.00	29.43
2 497.10	43.46	Peak	H	1.32	-	44.78	74.00	29.22





Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.




Mode: 802.11b (1 Mbps)
Distance of measurement: 3 meter
Channel: 1


- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 062.69	48.18	Peak	H	-7.23	-	40.95	74.00	33.05
2 125.99	49.93	Peak	V	-0.18	-	49.75	74.00	24.25

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 384.47	59.74	Peak	V	1.08	-	60.82	74.00	13.18
2 384.47	39.45	Average	V	1.08	-	40.53	54.00	13.47
2 384.96	59.52	Peak	H	1.08	-	60.60	74.00	13.40
2 384.96	32.92	Average	H	1.08	-	34.00	54.00	20.00
2 389.53	60.14	Peak	V	1.11	-	61.25	74.00	12.75
2 389.53	38.77	Average	V	1.11	-	39.88	54.00	14.12
2 389.73	60.22	Peak	H	1.11	-	61.33	74.00	12.67
2 389.73	33.15	Average	H	1.11	-	34.26	54.00	19.74





Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.