

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C AND CANADIAN RSS 210 ISSUE 8
REQUIREMENTS**

OF

nextbook

MODEL No.: NXW10QC32G

FCC ID: S7JNXW10QC32G

IC ID: 8082A-NXW10QC32G

Trademark: N/A

REPORT NO: ES140828400E2

ISSUE DATE: September 09, 2014

Prepared for

SHENZHEN YIFANG DIGITAL TECHNOLOGY CO., LTD.

**Building NO.22,23, Fifth Region, Baiwangxin Industrial Park, Songbai Rd.,
Nanshan, Shenzhen 518108, China**

Prepared by

SHENZHEN EMTEK CO., LTD.

**Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen,
Guangdong, China**

TEL: 86-755-26954280

FAX: 86-755-26954282

VERIFICATION OF COMPLIANCE


Applicant:	SHENZHEN YIFANG DIGITAL TECHNOLOGY CO., LTD. Building NO.22,23, Fifth Region, Baiwangxin Industrial Park, Songbai Rd., Nanshan, Shenzhen 518108, China
Manufacturer:	SHENZHEN YIFANG DIGITAL TECHNOLOGY CO., LTD. Building NO.22,23, Fifth Region, Baiwangxin Industrial Park, Songbai Rd., Nanshan, Shenzhen 518108, China
Product Description:	nextbook
Model Number:	NXW10QC32G
File Number:	ES140828400E2
Date of Test:	August 29, 2014 to September 09, 2014

We hereby certify that:

The above equipment was tested by SHENZHEN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2009) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247 and Canadian RSS 210 ISSUE 8 REQUIREMENTS

The test results of this report relate only to the tested sample identified in this report.

Date of Test : August 29, 2014 to September 09, 2014

Prepared by : 
Yaping Shen/Editor

Reviewer : 
Jack Li/Supervisor

Approve & Authorized Signer : 
Lisa Wang/Manager

Table of Contents

1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION	5
1.2 RELATED SUBMITTAL(S) / GRANT(S)	6
1.3 TEST METHODOLOGY	6
1.4 SPECIAL ACCESSORIES	6
1.5 EQUIPMENT MODIFICATIONS	6
1.6 TEST FACILITY	6
2. SYSTEM TEST CONFIGURATION	7
2.1 EUT CONFIGURATION	7
2.2 EUT EXERCISE	7
2.3 TEST PROCEDURE	7
2.4 CONFIGURATION OF TESTED SYSTEM	7
3. DESCRIPTION OF TEST MODES	9
4. SUMMARY OF TEST RESULTS	10
5. CONDUCTED EMISSIONS TEST	11
5.1 MEASUREMENT PROCEDURE	11
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	11
5.3 MEASUREMENT EQUIPMENT USED	11
5.4 CONDUCTED EMISSION LIMIT	11
5.5 MEASUREMENT RESULT	11
6. RADIATED EMISSION TEST	16
6.1 MEASUREMENT PROCEDURE	16
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	17
6.3 MEASUREMENT EQUIPMENT USED	18
6.4 RADIATED EMISSION LIMIT	18
6.5 MEASUREMENT RESULT	20
7. 6DB BANDWIDTH TEST AND 99% BANDWIDTH TEST	30
7.1 MEASUREMENT PROCEDURE	30
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	30
7.3 MEASUREMENT EQUIPMENT USED	30
7.4 MEASUREMENT RESULTS	30
8. MAXIMUM PEAK OUTPUT POWER TEST	35
8.1 MEASUREMENT PROCEDURE	35
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	35
8.3 MEASUREMENT EQUIPMENT USED	35
8.4 PEAK POWER OUTPUT LIMIT	35
8.5 MEASUREMENT RESULTS	35
9. BAND EDGE TEST	36
9.1 MEASUREMENT PROCEDURE	36
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	36
9.3 MEASUREMENT EQUIPMENT USED	36
9.4 MEASUREMENT RESULTS	36
10. POWER DENSITY	38
10.1 TEST EQUIPMENT	38
10.2 MEASURING INSTRUMENTS AND SETTING	38
10.3 TEST PROCEDURES	38
10.4 BLOCK DIAGRAM OF TEST SETUP	38
10.5 LIMIT	38

10.6	TEST RESULT	39
11	ANTENNA PORT EMISSION.....	41
11.1	TEST EQUIPMENT	41
11.2	MEASURING INSTRUMENTS AND SETTING	41
11.3	TEST PROCEDURES	41
11.4	BLOCK DIAGRAM OF TEST SETUP	41
11.5	TEST RESULT	41
12.	ANTENNA APPLICATION.....	45
12.1	ANTENNA REQUIREMENT	45
12.2	RESULT.....	45

1. General Information

1.1 Product Description

A major technical descriptions of EUT is described as following:

- A). Operation Frequency: Bluetooth: 2402-2480MHz,
WIFI 802.11b/g/n HT20: 2412-2462MHz;
WIFI 802.11n HT40: 2422-2452MHz
- B). Modulation: BT: GFSK
WIFI: OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n,
DSSS with DBPSK/DQPSK/CCK for 802.11b
- C). Number of Channel: 802.11b/g/ n HT20: 11Channels;
802.11n HT40: 9 Channels;
BT: 40 Channels;
- D).Conducted Power:3.75dBm
- E) Antenna Gain: 2dBi
- F). Antenna Type: Integral Antenna
- G). Bluetooth Verison: Bluetooth V4.0 BLE
- H). Power Supply: DC 5V with AC Adapter and DC 3.7V from Li-ion Battery.
- I). Adapter 1: Model: PS18C050K2500UD
Input: 100-240V~50/60Hz 0.5A
Output: DC 5V 2500mA
- J). Adapter 2: Model: TEKA018-0502500UK
Input: 100-240V~50/60Hz 0.5A MAX
Output: DC 5V 2.5A

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2402	15	2430	29	2458
2	2404	16	2432	30	2460
3	2406	17	2434	31	2462
4	2408	18	2436	32	2464
5	2410	19	2438	33	2466
6	2412	20	2440	34	2468
7	2414	21	2442	35	2470
8	2416	22	2444	36	2472
9	2418	23	2446	37	2474
10	2420	24	2448	38	2476
11	2422	25	2450	39	2478
12	2424	26	2452	40	2480
13	2426	27	2454		
14	2428	28	2456		

Note:

1. This device is Nextbook included BT4.0 transceiver function.
2. Test of channel was included the lowest middle and highest frequency in lowest data rate and to perform the test, then record on this report.

1.2 Related Submittal(s) / Grant(s)

This submittal(s) (test report) is intended for FCC ID: S7JNXW10QC32G filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules and also intended for IC ID: 8082A-NXW10QC32G filing to comply with Canadian RSS 210 Issue 8.0.
The composite system is compliance with Subpart B is authorized under a DOC procedure.

1.3 Test Methodology

All the test program has follow FCC new test procedure KDB558074 D01 v03r02, Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2009). Radiated testing was performed at an antenna to EUT distance 3 meters.

1.4 Special Accessories

Not available for this EUT intended for grant.

1.5 Equipment Modifications

Not available for this EUT intended for grant.

1.6 Test Facility

Site Description

EMC Lab. : Accredited by CNAS, 2013.10.29
The certificate is valid until 2016.10.28
The Laboratory has been assessed and proved to be in compliance with CNAS/CL01: 2006(identical to ISO/IEC17025: 2005)
The Certificate Registration Number is L2291

Accredited by TUV Rheinland Shenzhen 2010.5.25
The Laboratory has been assessed according to the requirements ISO/IEC 17025

Accredited by FCC, April 17, 2013
The Certificate Registration Number is 406365.

Accredited by Industry Canada, March 05, 2010
The Certificate Registration Number is 46405-4480.

Name of Firm : SHENZHEN EMTEK CO., LTD.
Site Location : Bldg 69, Majialong Industry Zone,
Nanshan District, Shenzhen, Guangdong, China

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements of ANSI C63.4-2009 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. Emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4-2009.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	IC ID	Series No.	Note
1.	nextbook	N/A	NXW10QC32G	S7JNXW10QC 32G	8082A-NXW10QC3 2G	N/A	EUT

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column, device(s) used in tested system is a support equipment.

3. Description of Test Modes

The Transmitter of EUT is an Internet Tablet and powered by host equipment; these is Digital Transmission system (DTS) and with modulation GFSK.

The mode is used: **Transmitting mode**

1. For lowest channel : 2402MHz (Channel 01)
2. For middle channel : 2440MHz (Channel 20)
3. For highest channel: 2480MHz (Channel 40)

4. Summary of Test Results


FCC Rules	IC Rule	Description Of Test	Result
§15.247(a)(2)	RSS-210, A8.2(a)	6dB bandwidth	Pass
§15.247(b)(3)	RSS-210, A8.4(2)	Max Peak output Power test	Pass
§15.247(e)	RSS-210, A8.2(b)	Power density	Pass
§15.247(d)	RSS-210, A2.9, A8.5	Band edge test	Pass
§15.207	RSS-GEN, Section 7.2.2	AC Power Conducted Emission	Pass
§15.247(d), §15.209	RSS-210, A2.9, A8.5	Radiated Emission	Pass
§15.247(d)	RSS-210, A8.5 RSS-GEN, Section 7.2.3	Antenna Port Emission	Pass
§15.247(b)&§15.203	N/A	Antenna Application	Pass
N/A	RSS-210, A1.1.3	99%dB Bandwidth	Pass

5. Conducted Emissions Test

5.1 Measurement Procedure

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

5.2 Test SET-UP (Block Diagram of Configuration)



5.3 Measurement Equipment Used

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/17/2014	05/16/2015
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	05/17/2014	05/16/2015
50Ω Coaxial Switch	Anritsu	MP59B	M20531	N/A	N/A
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	05/17/2014	05/16/2015
Voltage Probe	Rohde & Schwarz	TK9416	N/A	05/17/2014	05/16/2015
I.S.N	Rohde & Schwarz	ENY22	1109.9508.02	05/17/2014	05/16/2015

5.4 Conducted Emission Limit

Conducted Emission

Frequency(MHz)

Quasi-peak

Average

0.15-0.5

66-56

56-46

0.5-5.0

56

46

5.0-30.0


60

50

Note: 1. The lower limit shall apply at the transition frequencies


2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.5 Measurement Result



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1550	59.87	0.00	59.87	65.73	-5.86	QP	
2		0.1550	27.55	0.00	27.55	55.73	-28.18	AVG	
3		0.1900	57.61	0.00	57.61	64.04	-6.43	QP	
4		0.1900	36.71	0.00	36.71	54.04	-17.33	AVG	
5		0.2650	51.90	0.00	51.90	61.27	-9.37	QP	
6		0.2650	30.67	0.00	30.67	51.27	-20.60	AVG	
7		5.3900	45.49	0.00	45.49	60.00	-14.51	QP	
8		5.3900	32.09	0.00	32.09	50.00	-17.91	AVG	
9		13.1000	47.33	0.00	47.33	60.00	-12.67	QP	
10		13.1000	36.40	0.00	36.40	50.00	-13.60	AVG	
11		21.5250	48.22	0.00	48.22	60.00	-11.78	QP	
12		21.5250	38.57	0.00	38.57	50.00	-11.43	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Cai



Site Conduction #1

Phase: **N**

Temperature: 26

Limit: (CE)FCC PART 15 C

Power: AC 120V/60Hz


Humidity: 60 %

Mode: BT ON

Note: Adapter 1

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1500	61.02	0.00	61.02	66.00	-4.98	QP	
2		0.1500	32.15	0.00	32.15	56.00	-23.85	AVG	
3		0.2100	56.41	0.00	56.41	63.21	-6.80	QP	
4		0.2100	37.61	0.00	37.61	53.21	-15.60	AVG	
5		0.2600	52.06	0.00	52.06	61.43	-9.37	QP	
6		0.2600	33.85	0.00	33.85	51.43	-17.58	AVG	
7		5.6000	45.62	0.00	45.62	60.00	-14.38	QP	
8		5.6000	33.15	0.00	33.15	50.00	-16.85	AVG	
9		12.9750	44.36	0.00	44.36	60.00	-15.64	QP	
10		12.9750	32.92	0.00	32.92	50.00	-17.08	AVG	
11		22.6000	43.70	0.00	43.70	60.00	-16.30	QP	
12		22.6000	33.80	0.00	33.80	50.00	-16.20	AVG	

*:Maximum data x:Over limit l:over margin Comment: Factor build in receiver. Operator: Cai



Site Conduction #1

Phase: **L1**

Temperature: 26

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz


Humidity: 60 %

Mode: BT ON

Note: Adapter 2

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1582	53.65	0.00	53.65	65.56	-11.91	QP	
2		0.1582	32.90	0.00	32.90	55.56	-22.66	AVG	
3		0.2454	50.48	0.00	50.48	61.91	-11.43	QP	
4		0.2454	17.42	0.00	17.42	51.91	-34.49	AVG	
5	*	0.4150	47.79	0.00	47.79	57.55	-9.76	QP	
6		0.4150	23.49	0.00	23.49	47.55	-24.06	AVG	
7		0.7122	45.98	0.00	45.98	56.00	-10.02	QP	
8		0.7122	32.79	0.00	32.79	46.00	-13.21	AVG	
9		6.3700	44.92	0.00	44.92	60.00	-15.08	QP	
10		6.3700	28.93	0.00	28.93	50.00	-21.07	AVG	
11		15.7500	42.80	0.00	42.80	60.00	-17.20	QP	
12		15.7500	28.87	0.00	28.87	50.00	-21.13	AVG	

*:Maximum data x:Over limit l:over margin Comment: Factor build in receiver. Operator: Cai



Site Conduction #1

Phase: **N**

Temperature: 26

Limit: (CE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 60 %

Mode: BT ON

Note: Adapter 2

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
		MHz	Level	Factor	ment			Detector	Comment
			dBuV	dB	dBuV	dBuV	dB		
1	*	0.1955	52.17	0.00	52.17	63.80	-11.63	QP	
2		0.1955	37.89	0.00	37.89	53.80	-15.91	AVG	
3		0.2454	49.98	0.00	49.98	61.91	-11.93	QP	
4		0.2454	40.00	0.00	40.00	51.91	-11.91	AVG	
5		0.3150	47.61	0.00	47.61	59.84	-12.23	QP	
6		0.3150	34.64	0.00	34.64	49.84	-15.20	AVG	
7		0.7160	43.98	0.00	43.98	56.00	-12.02	QP	
8		0.7160	28.89	0.00	28.89	46.00	-17.11	AVG	
9		6.3700	46.92	0.00	46.92	60.00	-13.08	QP	
10		6.3700	31.50	0.00	31.50	50.00	-18.50	AVG	
11		21.5500	43.78	0.00	43.78	60.00	-16.22	QP	
12		21.5500	31.01	0.00	31.01	50.00	-18.99	AVG	

*:Maximum data x:Over limit l:over margin Comment: Factor build in receiver. Operator: Cai

6. Radiated Emission Test

6.1 Measurement Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured was complete.

When spectrum scanned from 30 MHz to 1GHz setting resolution bandwidth 120 kHz and video bandwidth 300kHz.

EMI Test Receiver	Setting
Attenuation	Auto
RB	120kHz
VB	300kHz
Detector	QP
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz.


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz.


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	AVG
Trace	Max hold

6.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



6.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/17/2014	05/16/2015
Pre-Amplifier	HP	8447D	2944A07999	05/17/2014	05/16/2015
Bilog Antenna	Schwarzbeck	VULB9163	142	05/17/2014	05/16/2015
Loop Antenna	ARA	PLA-1030/B	1029	05/17/2014	05/16/2015
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/17/2014	05/16/2015
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/17/2014	05/16/2015
Cable	Schwarzbeck	AK9513	ACRX1	05/17/2014	05/16/2015
Cable	Rosenberger	N/A	FP2RX2	05/17/2014	05/16/2015
Cable	Schwarzbeck	AK9513	CRPX1	05/17/2014	05/16/2015
Cable	Schwarzbeck	AK9513	CRRX2	05/17/2014	05/16/2015

6.4 Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

- Remark: 1. Emission level in dBuV/m=20 log (uV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of § 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

6.5 Measurement Result

Operation Mode: TX Mode Test Date : September 03, 2014
 Frequency Range: 0.009~30MHz Temperature : 26℃
 Test Result: PASS Humidity : 55%
 Measured Distance: 3m Test By: SYP

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40 \log(\text{Specific distance} / \text{test distance})$ (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor.

Operation Mode: TX Channel 01 Test Date : September 03, 2014
Frequency Range: 30~1000MHz Temperature : 26°C
Test Result: PASS Humidity : 55%
Measured Distance: 3m Test By: SYP
Note:




Site site #1 Polarization: **Horizontal** Temperature: 24 C
Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 53 %
Mode:TX 2402
Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	103.0608	16.00	12.87	28.87	43.50	-14.63	QP		
2		218.0930	12.17	10.90	23.07	46.00	-22.93	QP		
3		323.7980	14.80	14.60	29.40	46.00	-16.60	QP		
4		395.3042	11.34	18.52	29.86	46.00	-16.14	QP		
5		508.7820	6.48	20.99	27.47	46.00	-18.53	QP		
6		827.4520	4.11	24.76	28.87	46.00	-17.13	QP		

*:Maximum data x:Over limit !:over margin

Operator: ZHL




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	82.8525	20.40	8.04	28.44	40.00	-11.56	QP		
2		110.8332	15.71	12.53	28.24	43.50	-15.26	QP		
3		131.0415	15.60	9.72	25.32	43.50	-18.18	QP		
4		508.7820	11.12	20.99	32.11	46.00	-13.89	QP		
5		625.3685	5.54	22.48	28.02	46.00	-17.98	QP		
6		748.1730	3.11	24.08	27.19	46.00	-18.81	QP		

*:Maximum data x:Over limit !:over margin

Operator: ZHL

Operation Mode: TX Channel 20 Test Date : September 03, 2014
Frequency Range: 30~1000MHz Temperature : 26°C
Test Result: PASS Humidity : 55%
Measured Distance: 3m Test By: SYP
Note:




Site site #1 Polarization: **Horizontal** Temperature: 24 C
Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 53 %
Mode: TX 2440
Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		115.4967	11.95	11.36	23.31	43.50	-20.19	QP		
2		218.0930	14.67	10.90	25.57	46.00	-20.43	QP		
3	*	280.2724	16.85	14.97	31.82	46.00	-14.18	QP		
4		323.7980	16.30	14.60	30.90	46.00	-15.10	QP		
5		395.3042	10.84	18.52	29.36	46.00	-16.64	QP		
6		508.7820	6.98	20.99	27.97	46.00	-18.03	QP		

*:Maximum data x:Over limit l:over margin

Operator: ZHL




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		110.8332	17.71	12.53	30.24	43.50	-13.26	QP		
2	*	131.0415	20.60	9.72	30.32	43.50	-13.18	QP		
3		159.0224	19.78	8.27	28.05	43.50	-15.45	QP		
4		196.3300	14.27	10.61	24.88	43.50	-18.62	QP		
5		339.3430	8.85	15.46	24.31	46.00	-21.69	QP		
6		413.9583	6.29	18.80	25.09	46.00	-20.91	QP		

*:Maximum data x:Over limit !:over margin

Operator: ZHL

Operation Mode: TX Channel 40 Test Date : September 03, 2014
Frequency Range: 30~1000MHz Temperature : 26°C
Test Result: PASS Humidity : 55%
Measured Distance: 3m Test By: SYP
Note:




Site site #1 Polarization: **Horizontal** Temperature: 24 C
Limit: (RE)FCC PART 15 C Power: AC 120V/60Hz Humidity: 53 %
Mode:TX 2480
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		110.8332	14.67	12.53	27.20	43.50	-16.30	QP		
2		214.9840	15.06	10.82	25.88	43.50	-17.62	QP		
3		275.6090	15.58	15.14	30.72	46.00	-15.28	QP		
4	*	323.7980	17.80	14.60	32.40	46.00	-13.60	QP		
5		395.3042	10.34	18.52	28.86	46.00	-17.14	QP		
6		622.2595	2.99	22.41	25.40	46.00	-20.60	QP		

*:Maximum data x:Over limit !:over margin

Operator: ZHL



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		95.2883	18.35	12.10	30.45	43.50	-13.05	QP		
2	*	110.8332	20.21	12.53	32.74	43.50	-10.76	QP		
3		131.0415	22.60	9.72	32.32	43.50	-11.18	QP		
4		191.6665	14.27	10.29	24.56	43.50	-18.94	QP		
5		413.9583	10.29	18.80	29.09	46.00	-16.91	QP		
6		508.7820	5.12	20.99	26.11	46.00	-19.89	QP		

*:Maximum data x:Over limit !:over margin

Operator: ZHL

Operation Mode: TX Channel 01 Test Date : September 03, 2014
Frequency Range: 1GHz~25GHz Temperature : 26℃
Test Result: PASS Humidity : 55%
Measured Distance: 3m Test By: SYP

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4804.00	V	60.36	43.93	74.00	54.00	-13.64	-10.07
8605.29	V	52.88	33.04	74.00	54.00	-21.12	-20.96
10646.11	V	53.73	32.90	74.00	54.00	-20.27	-21.10
14271.92	V	54.53	34.98	74.00	54.00	-19.47	-19.02
16151.74	V	54.11	33.79	74.00	54.00	-19.89	-20.21
17702.23	V	54.94	34.94	74.00	54.00	-19.06	-19.06
4804.00	H	60.80	43.70	74.00	54.00	-13.20	-10.30
10128.50	H	54.04	33.26	74.00	54.00	-19.96	-20.74
12689.37	H	54.12	34.04	74.00	54.00	-19.88	-19.96
14244.71	H	55.47	35.02	74.00	54.00	-18.53	-18.98
16260.76	H	53.88	33.99	74.00	54.00	-20.12	-20.01
17702.14	H	54.03	34.79	74.00	54.00	-19.97	-19.21

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: TX Channel 20 Test Date : September 03, 2014
Frequency Range: 1GHz~25GHz Temperature : 26℃
Test Result: PASS Humidity : 55%
Measured Distance: 3m Test By: SYP

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4880.00	V	58.78	43.45	74.00	54.00	-15.22	-10.55
8850.97	V	51.30	32.56	74.00	54.00	-22.70	-21.44
10891.79	V	52.15	32.42	74.00	54.00	-21.85	-21.58
14517.60	V	52.95	34.50	74.00	54.00	-21.05	-19.50
16397.42	V	52.53	33.31	74.00	54.00	-21.47	-20.69
17947.91	V	53.36	34.46	74.00	54.00	-20.64	-19.54
4880.00	H	59.22	43.22	74.00	54.00	-14.78	-10.78
10374.18	H	52.46	32.78	74.00	54.00	-21.54	-21.22
12935.05	H	52.54	33.56	74.00	54.00	-21.46	-20.44
14490.39	H	53.89	34.54	74.00	54.00	-20.11	-19.46
16506.44	H	52.30	33.51	74.00	54.00	-21.70	-20.49
17947.82	H	52.45	34.31	74.00	54.00	-21.55	-19.69

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:** (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: TX Channel 40 Test Date : September 03, 2014
 Frequency Range: 1GHz~25GHz Temperature : 26℃
 Test Result: PASS Humidity : 55%
 Measured Distance: 3m Test By: SYP

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
7346.42	V	52.09	32.79	74.00	54.00	-21.91	-21.21
7975.42	V	52.56	33.09	74.00	54.00	-21.44	-20.91
11187.75	V	52.03	33.55	74.00	54.00	-21.97	-20.45
12822.33	V	53.09	33.95	74.00	54.00	-20.91	-20.05
14868.05	V	53.58	34.69	74.00	54.00	-20.42	-19.31
17265.52	V	52.76	33.64	74.00	54.00	-21.24	-20.36
4867.16	H	50.58	31.52	74.00	54.00	-23.42	-22.48
7893.61	H	52.22	32.85	74.00	54.00	-21.78	-21.15
9852.73	H	53.05	33.70	74.00	74.00	-20.95	-40.30
12985.65	H	53.02	34.29	74.00	54.00	-20.98	-19.71
14595.56	H	53.40	33.84	74.00	54.00	-20.60	-20.16
16554.58	H	52.39	33.36	74.00	54.00	-21.61	-20.64

All emissions not reported were more than 20dB below the specified limit or in the noise floor.


Note: (1) All Readings are Peak Value and AV.
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

7. 6dB Bandwidth Test and 99% Bandwidth Test

7.1 Measurement Procedure

1. The testing follows FCC KDB Publication No. 558074 DTS 001 Meas. Guidance v03r02
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously
4. Make the measurement with the spectrum analyzer 's resolution bandwidth (RBW) = 100 kHz.Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement The 6dB bandwidth must be greater than 500 kHz
5. Measure and record the results in the test report.

7.2 Test SET-UP (Block Diagram of Configuration)



7.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Signal Analyzer	Agilent	N9010A	My53470879	05/17/2014	05/16/2015


7.4 Measurement Results



6db Bandwidth Test Data Chart and 99% Bandwidth Test Data Chart:
Refer to attached data chart.

6db Bandwidth Test

Spectrum Detector: PK Test Date : September 03, 2014
Test By: SYP Temperature : 26°C
Test Result: PASS Humidity : 55 %

Channel number	Channel frequency (MHz)	Measurement level (KHz)	Mode	Limit (KHz)
01	2402	742.006	6db Bandwidth	>500
20	2440	744.587	6db Bandwidth	>500
40	2480	743.073	6db Bandwidth	>500








99% Bandwidth Test

Spectrum Detector:	PK	Test Date :	September 03, 2014
Test By:	SYP	Temperature :	26°C
Test Result:	PASS	Humidity :	55 %
Operation Mode: GFSK			

Channel number	Channel frequency (MHz)	Measurement level (MHz)	Mode
01	2402	3.2583	99% Bandwidth Test
20	2440	3.2643	99% Bandwidth Test
40	2480	3.2736	99% Bandwidth Test






8. Maximum Peak Output Power Test

8.1 Measurement Procedure

The maximum peak conducted output power can be measured using a broadband peak RF power meter. The power meter must have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast, average-responding diode type sensor.

- The Transmitter output (antenna port) was connected to the power meter.
- Turn on the EUT and power meter and then record the peak power value.
- Repeat above procedures on all channels needed to be tested.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used

EQUIPMENT TYPE	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Power meter	ML2495A	0824006	05/17/2014	05/16/2015
Power sensor	MA2411B	0738172	05/17/2014	05/16/2015

8.4 Peak Power output limit

The maximum peak power shall be less 1Watt.

8.5 Measurement Results

Spectrum Detector:	PK	Test Date :	September 03, 2014
Test By:	SYP	Temperature :	26°C
Test Result:	PASS	Humidity :	55 %
Modulation:	GFSK		

Channel number	Channel Frequency(MHz)	Peak Power output(dBm)	Peak Power Limit(W)	Pass/Fail
01	2402	3.51	1W(30dBm)	PASS
20	2440	3.75	1W(30dBm)	PASS
40	2480	3.24	1W(30dBm)	PASS

9. Band Edge Test

9.1 Measurement Procedure

1. The EUT was Operating in hopping mode or could be controlled its channel. Printed out test result from the spectrum by hard copy function.
2. The EUT was placed on a turn table which is 0.8m above ground plane.
3. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
4. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
5. Repeat above procedures until all frequency measured were complete.

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz.

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz.

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	AVG
Trace	Max hold

9.2 Test SET-UP (Block Diagram of Configuration)

As 6.2 Test set up (B) and (C)

9.3 Measurement Equipment Used

Same as 6.3 Radiated Emission Measurement.

9.4 Measurement Results

Spectrum Detector: PK/AV Test Date : September 03, 2014
 Test By: SYP Temperature : 26°C
 Test channel: 01 Humidity : 55 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2322.57	H	54.69	40.25	74	54
2368.95	V	58.74	40.33	74	54

Spectrum Detector: PK/AV Test Date : September 03, 2014
 Test By: SYP Temperature : 26°C
 Test channel: 40 Humidity : 55 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2485.68	H	56.48	44.27	74	54
2492.74	V	52.57	43.47	74	54

10. Power Density

10.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Signal Analyzer	Agilent	N9010A	My53470879	05/17/2014	05/16/2015

10.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS bandwidth.
RB	$3\text{KHz} \leq \text{RBW} \leq 100\text{KHz}$
VB	$3 \times \text{RBW}$
Detector	Peak
Trace	Max hold
Sweep Time	Automatic

10.3 Test Procedures

- a. The transmitter output (antenna port) was connected to the spectrum analyzer.
- b. Set analyzer center frequency to DTS channel center frequency.
- c. Set the analyzer span to a minimum of 1.5 times the DTS bandwidth.
- d. Set the $\text{RBW} \geq 3 \text{ kHz}$. Set the $\text{VBW} \geq 3 \times \text{RBW}$.
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level.

10.4 Block Diagram of Test Setup




10.5 Limit



The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3 kHz bandwidth.

10.6 Test Result

Spectrum Detector: PK Test Date : September 03, 2014
 Test By: SYP Temperature : 26°C
 Test Result: PASS Humidity : 55 %
 Operation Mode: BLE

Channel	Measurement Level (dBm)	Required Limit (dBm)	Result
01	-16.30	<8dBm	PASS
20	-15.93	<8dBm	PASS
40	-16.46	<8dBm	PASS





11 Antenna Port Emission

11.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Signal Analyzer	Agilent	N9010A	My53470879	05/17/2014	05/16/2015

11.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
RB	100kHz
VB	300kHz
Detector	Peak
Trace	Max hold

11.3 Test Procedures

The conducted spurious emissions were measured conducted using a spectrum analyzer at low, Middle, and high channels, the limit was determined by attenuation 20dB of the RF peak power output.



11.4 Block Diagram of Test setup





11.5 Test Result

PASS.



Low Channel 01



Mid Channel 20



High Channel 40



12. Antenna Application

12.1 Antenna Requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

12.2 Result

The EUT'S antenna is integral antenna. The antenna's gain is 2dBi and meets the requirement.