TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: **47 CFR FCC Part 15, Subpart C (Section 15.247)**

Report No.: RFBICM-WTW-P25020305-3

FCC ID: S9E-135100

Product: Rugged Controller

Brand: Trimble or Trimble

Model No.: 135100

Received Date: 2025/2/12

Test Date: 2025/3/14 ~ 2025/4/10

Issued Date: 2025/5/16

Applicant: Trimble Inc.

Address: 5475 Kellenburger Road, Dayton, Ohio 45424

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

FCC Registration / Designation Number: 198487 / TW2021

Approved by: Jeremy Lin , **Date:** 2025/5/16

Jeremy Lin / Project Engineer

This test report consists of 48 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Annie Chang / Senior Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/ and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record **4**

1 Certificate **5**

2 Summary of Test Results **6**

2.1 Measurement Uncertainty 6
2.2 Supplementary Information 6

3 General Information **7**

3.1 General Description 7
3.2 Antenna Description of EUT 8
3.3 Channel List 8
3.4 Test Mode Applicability and Tested Channel Detail 9
3.5 Duty Cycle of Test Signal 10
3.6 Test Program Used and Operation Descriptions 11
3.7 Connection Diagram of EUT and Peripheral Devices 11
3.8 Configuration of Peripheral Devices and Cable Connections 11

4 Test Instruments **12**

4.1 RF Output Power 12
4.2 Number of Hopping Frequency Used 12
4.3 Dwell Time on Each Channel 12
4.4 Hopping Channel Separation 12
4.5 20 dB Bandwidth 12
4.6 Conducted Out of Band Emissions 12
4.7 AC Power Conducted Emissions 13
4.8 Unwanted Emissions below 1 GHz 14
4.9 Unwanted Emissions above 1 GHz 15

5 Limits of Test Items **16**

5.1 RF Output Power 16
5.2 Number of Hopping Frequency Used 16
5.3 Dwell Time on Each Channel 16
5.4 Hopping Channel Separation 16
5.5 20 dB Bandwidth 16
5.6 Conducted Out of Band Emissions 16
5.7 AC Power Conducted Emissions 16
5.8 Unwanted Emissions below 1 GHz 17
5.9 Unwanted Emissions above 1 GHz 17

6 Test Arrangements **18**

6.1 RF Output Power 18
6.1.1 Test Setup 18
6.1.2 Test Procedure 18
6.2 Number of Hopping Frequency Used 18
6.2.1 Test Setup 18
6.2.2 Test Procedure 18
6.3 Dwell Time on Each Channel 19
6.3.1 Test Setup 19
6.3.2 Test Procedure 19
6.4 Hopping Channel Separation 19
6.4.1 Test Setup 19
6.4.2 Test Procedure 19
6.5 20 dB Bandwidth 20
6.5.1 Test Setup 20
6.5.2 Test Procedure 20
6.6 Conducted Out of Band Emissions 20
6.6.1 Test Setup 20
6.6.2 Test Procedure 20
6.7 AC Power Conducted Emissions 21

6.7.1 Test Setup 21
6.7.2 Test Procedure 21
6.8 Unwanted Emissions below 1 GHz 22
6.8.1 Test Setup 22
6.8.2 Test Procedure 23
6.9 Unwanted Emissions above 1 GHz 24
6.9.1 Test Setup 24
6.9.2 Test Procedure 24

7 Test Results of Test Item 25

7.1 RF Output Power 25
7.2 Number of Hopping Frequency Used 26
7.3 Dwell Time on Each Channel 27
7.4 Hopping Channel Separation 29
7.5 20 dB Bandwidth 30
7.6 Conducted Out of Band Emissions 31
7.7 AC Power Conducted Emissions 33
7.8 Unwanted Emissions below 1 GHz 37
7.9 Unwanted Emissions above 1 GHz 39

8 Pictures of Test Arrangements 47

9 Information of the Testing Laboratories 48

Release Control Record

Issue No.	Description	Date Issued
RFBICM-WTW-P25020305-3	Original release.	2025/5/16

1 Certificate

Product:	Rugged Controller
Brand:	Trimble or
Test Model:	135100
Sample Status:	Engineering sample
Applicant:	Trimble Inc.
Test Date:	2025/3/14 ~ 2025/4/10
Standard:	47 CFR FCC Part 15, Subpart C (Section 15.247)
Measurement procedure:	ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
Standard / Clause	Test Item	Result	Remark
15.247 (a)(1)	RF Output Power	Pass	Meet the requirement of limit.
15.247(a)(1) (iii)	Number of Hopping Frequency Used	Pass	Meet the requirement of limit.
15.247(a)(1) (iii)	Dwell Time on Each Channel	Pass	Meet the requirement of limit.
15.247(a)(1)	Hopping Channel Separation	Pass	Meet the requirement of limit.
15.247(a)(1)	20 dB Bandwidth	-	Refer to Note 1
15.247(d)	Conducted Out of Band Emissions	Pass	Meet the requirement of limit.
15.207	AC Power Conducted Emissions	Pass	Minimum passing margin is -14.75 dB at 0.15391 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions below 1 GHz	Pass	Minimum passing margin is -6.5 dB at 212.36 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions above 1 GHz	Pass	Minimum passing margin is -11.5 dB at 2483.50 MHz
15.203	Antenna Requirement	Pass	Antenna connector is ipex 4 not a standard connector.

Notes:

1. If the Frequency Hopping System operating in 2400-2483.5 MHz band and the output power less than 125 mW. The hopping channel carrier frequencies separated by a minimum of 25 kHz or two-thirds of the 20 dB bandwidth of hopping channel whichever is greater.
2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Specification	Uncertainty (±)
RF Output Power	-	1.1 dB
Dwell Time on Each Channel	-	2.18 %
Hopping Channel Separation	-	390 Hz
20 dB Bandwidth	-	960 Hz
Conducted Out of Band Emissions	9 kHz ~ 40 GHz	2.7 dB
AC Power Conducted Emissions	9 kHz ~ 30 MHz	2.9 dB
Unwanted Emissions below 1 GHz	9 kHz ~ 30 MHz	2.55 dB
	30 MHz ~ 1 GHz	5.77 dB
Unwanted Emissions above 1 GHz	1 GHz ~ 6 GHz	4.71 dB
	6 GHz ~ 18 GHz	5.3 dB
	18 GHz ~ 40 GHz	4.98 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description

Product	Rugged Controller
Brand	Trimble or Trimble
Test Model	135100
Host Marketing Name (HMN)	Rugged Controller
Status of EUT	Engineering sample
Power Supply Rating	7.26Vdc from battery 5.0Vdc from adapter or host equipment
Modulation Type	GFSK, π/4-DQPSK, 8DPSK
Modulation Technology	FHSS
Transfer Rate	Up to 3 Mbps
Operating Frequency	2.402 GHz ~ 2.48 GHz
Number of Channel	79
Output Power	38.019 mW (15.8 dBm)

Note:

1. The EUT uses following accessories.

Item	Brand	Model	Specification
USB-C Cable	Trimble	140100-00	1.95m, type C to type C, shielded
Touch Pen	Trimble	122338	-
Adapter(Optional)	FULLPOWER	TYPE-C45IC	Input Power: 100-240Vac, 50/60Hz, 1.3A Output Power: 5.0V⎓3.0A/9.0V⎓3.0A/12.0V⎓3.0A, 15.0V⎓3.0A/20.0V⎓2.25A 45.0W

2. The EUT consumes power from the following battery:

Item	Brand	Model No.	Specification
Battery	ETICA Battery Inc.	SGB-02	7.26V, 32.67Wh, 4500mAh

3. There are WWAN, WLAN, Bluetooth & NFC technology used for the EUT.
4. Contain FCC ID: S9E-N7NEM75T.
5. Simultaneously transmission combination.

Combination	Technology			
1	WWAN	WLAN 2.4GHz (MIMO)	-	NFC
2	WWAN	WLAN 2.4GHz (Main)	BT (Aux)	NFC
3	WWAN	WLAN 5GHz (MIMO)	BT (Aux)	NFC
Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.				

6. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 Antenna Description of EUT

The antenna information is listed as below.

RF Chain NO.	Brand	Model	Gain (dBi)	Frequency range	Antenna Type	Connector Type
Aux	Pulse	TZ29770	2.47	2.4~2.4835GHz	PIFA	ipex 4

* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

3.3 Channel List

79 channels are provided for BT-EDR:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	1. EUT can be used in the following ways: X-axis/ Y-axis/ Z-axis. Pre-scan these ways and find the worst case as a representative test condition. 2. For Unwanted Emission below/ above 1 GHz has Battery/ EUT with USB cable(Adapter)/ EUT with USB cable(Laptop) mode of power supply. Pre-scan these modes and find the worst case as a representative test condition.
Worst Case:	1. X-axis/ Y-axis/ Z-axis Worst Condition: X-axis. 2. For Unwanted Emission below/ above 1 GHz Worst Condition: EUT with USB cable(Adapter).

Following channel(s) was (were) selected for the final test as listed below:

Test Item	EUT Configure Mode	Tested Channel	Modulation	Data Rate Parameter
RF Output Power	A	0, 39, 78	GFSK	DH5
			8DPSK	3DH5
Number of Hopping Frequency Used	A	Hopping	GFSK	DH5
			8DPSK	3DH5
Dwell Time on Each Channel	A	Hopping	GFSK	DH1/DH3/DH5
			8DPSK	3DH1/3DH3/3DH5
Hopping Channel Separation / 20 dB Bandwidth	A	0, 39, 78	GFSK	DH5
			8DPSK	3DH5
Conducted Out of Band Emissions	A	Hopping 0, 78	GFSK	DH5
			8DPSK	3DH5
AC Power Conducted Emissions	A	39	GFSK	DH5
	B	39	GFSK	DH5
Unwanted Emissions below 1 GHz	A	39	GFSK	DH5
Unwanted Emissions above 1 GHz	A	0, 39, 78	GFSK	DH5
			8DPSK	3DH5
EUT Configure Mode:	A	EUT with USB cable(Adapter)		
	B	EUT with USB cable(Laptop)		

3.5 Duty Cycle of Test Signal

GFSK: Duty cycle = 2.887 ms / 100 ms x 100% = 2.9%
8DPSK: Duty cycle = 2.893 ms / 100 ms x 100% = 2.9%



GFSK



8DPSK

3.6 Test Program Used and Operation Descriptions

Controlling software (QRCT v4.0.211) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

3.7 Connection Diagram of EUT and Peripheral Devices

Mode A



Mode B



3.8 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Adapter	FULLPOWER	TYPE-C45IC	N/A	N/A	Supplied by applicant
B	NB	Lenovo	IdeaPad 5 15ITL05	N/A	N/A	Provided by Lab
C	NB Adapter	Lenovo	ADLX65CLGC2A	N/A	N/A	Provided by Lab

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	USB-C Cable	1	1.95	Y	0	Supplied by applicant
2	DC cable	1	1.9	N	0	Provided by Lab

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 RF Output Power

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Pulse Power Sensor Anritsu	MA2411B	0738404	2024/5/13	2025/5/12
RF Power Meter Anritsu	ML2495A	0842014	2024/5/13	2025/5/12
USB Wideband Power Sensor Keysight	U2021XA	U2021XA_001	2024/6/7	2025/6/6
Fixed Attenuator Solvang Technology	STI02-3310-10	STI02-3310-10_013	2024/6/19	2025/6/18

Notes:

1. The test was performed in LK - Oven
2. Tested Date: 2025/4/2

4.2 Number of Hopping Frequency Used

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
PXA Signal Analyzer Keysight	N9030A	MY54490260	2024/7/17	2025/7/16
Signal Analyzer R&S	FSV40	101042	2024/9/12	2025/9/11
Software	ADT_RF Test Software V6.6.5.4	N/A	N/A	N/A
Fixed Attenuator Solvang Technology	STI02-3310-10	STI02-3310-10_013	2024/6/19	2025/6/18

Notes:

1. The test was performed in LK - Oven
2. Tested Date: 2025/4/2

4.3 Dwell Time on Each Channel

Refer to section 4.2 to get the tested date and information of the instruments.

4.4 Hopping Channel Separation

Refer to section 4.2 to get the tested date and information of the instruments.

4.5 20 dB Bandwidth

Refer to section 4.2 to get the tested date and information of the instruments.

4.6 Conducted Out of Band Emissions

Refer to section 4.2 to get the tested date and information of the instruments.

4.7 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohm terminal resistance LYNICS	0900510	E1-011284	2024/9/16	2025/9/15
		E1-011285	2024/9/25	2025/9/24
EMI Test Receiver R&S	ESR3	102412	2024/12/26	2025/12/25
		102414	2024/12/11	2025/12/10
Fixed Attenuator STI	STI02-2200-10	NO.4	2024/8/30	2025/8/29
High Voltage Probe Schwarzbeck	TK9420	00982	2024/12/6	2025/12/5
Isolation Transformer Erika Fiedler	D-65396	017	2024/9/18	2025/9/17
LISN R&S	ENV216	101196	2024/5/22	2025/5/21
LISN Schwarzbeck	NNLK 8121	8121-731	2024/6/12	2025/6/11
		8121-808	2024/4/26	2025/4/25
	NNLK 8129	8129229	2024/10/14	2025/10/13
	NSLK 8128	8128-244	2024/11/11	2025/11/10
Passive Voltage Probe R&S	ESH2-Z3	100073	2024/5/16	2025/5/15
RF Coaxial Cable PEWC	5D-FB	Cable-CO5-01	2025/1/17	2026/1/16
Software BVADT	Cond_V7.4.1.0	N/A	N/A	N/A

Notes:

1. The test was performed in Linkou Conduction 5.
2. Tested Date: 2025/3/20 ~ 2025/4/10

4.8 Unwanted Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Bi_Log Antenna Schwarzbeck	VULB 9168	137	2024/10/9	2025/10/8
Coupling / Decoupling Network Schwarzbeck	CDNE-M2	00097	2024/5/28	2025/5/27
	CDNE-M3	00091	2024/5/28	2025/5/27
MXE EMI Receiver Keysight	N9038A	MY55420137	2024/5/8	2025/5/7
Preamplifier Agilent	8447D	2944A11064	2025/2/14	2026/2/13
Preamplifier EMCI	EMC001340	980269	2024/6/25	2025/6/24
Radiating Loop Antenna TESEQ	RLA 6120-20	80002	2024/7/30	2025/7/29
RF Coaxial Cable Pacific	8D-FB	Cable-CH6-02	2024/6/25	2025/6/24
Signal Analyzer R&S	FSV40	101544	2024/6/20	2025/6/19
Software BVADT	Radiated_V8.7.08	N/A	N/A	N/A
Tower ADT	AT100	0306	N/A	N/A
Turn Table ADT	TT100	0306	N/A	N/A

Notes:

1. The test was performed in Linkou 966 Chamber 6 (CH 6).
2. Tested Date: 2025/3/14

4.9 Unwanted Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Boresight antenna tower fixture BV	BAF-02	6	N/A	N/A
High Pass Filter Wainwright	WHK 3.1/18G-10SS	SN 8	2024/5/24	2025/5/23
Horn Antenna EMCO	3115	00028257	2024/11/10	2025/11/9
Horn Antenna ETS-Lindgren	3117-PA	00215857	2024/11/10	2025/11/9
Horn Antenna Schwarzbeck	BBHA 9170	212	2024/10/18	2025/10/17
		BBHA9170190	2024/11/10	2025/11/9
MXE EMI Receiver Keysight	N9038A	MY55420137	2024/5/8	2025/5/7
Notch Filter Micro-Tronics	BRC50703-01	010	2024/5/24	2025/5/23
	BRM17690	005	2024/5/24	2025/5/23
Preamplifier EMCI	EMC0126545	980076	2025/2/14	2026/2/13
	EMC184045B	980175	2024/8/25	2025/8/24
		980235	2025/2/14	2026/2/13
Preamplifier HP	8449B	3008A01201	2025/2/14	2026/2/13
RF Coaxial Cable EMCI	EMC104	190801	2024/7/5	2025/7/4
		190804	2024/7/5	2025/7/4
RF Coaxial Cable EMEC	EM102-KMKM-100	02	2024/7/5	2025/7/4
RF Coaxial Cable HUBER+SUHNER	SF-104	Cable-CH6-01	2024/7/5	2025/7/4
Signal Analyzer R&S	FSV40	101042	2024/9/12	2025/9/11
		101544	2024/6/20	2025/6/19
Software BVADT	Radiated_V7.7.1.1.1	N/A	N/A	N/A
Tower ADT	AT100	0306	N/A	N/A
Turn Table ADT	TT100	0306	N/A	N/A

Notes:

1. The test was performed in Linkou 966 Chamber 6 (CH 6).
2. Tested Date: 2025/3/26

5 Limits of Test Items

5.1 RF Output Power

The Maximum Output Power Measurement is 125 mW (21 dBm).

5.2 Number of Hopping Frequency Used

At least 15 channels frequencies, and should be equally spaced.

5.3 Dwell Time on Each Channel

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

5.4 Hopping Channel Separation

At least 25 kHz or two-third of 20 dB hopping channel bandwidth (whichever is greater).

5.5 20 dB Bandwidth

Maximum bandwidth is not specified.

5.6 Conducted Out of Band Emissions

Below 20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

5.7 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.8 Unwanted Emissions below 1 GHz

Radiated emissions up to 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

5.9 Unwanted Emissions above 1 GHz

Radiated emissions above 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

6 Test Arrangements

6.1 RF Output Power

6.1.1 Test Setup



6.1.2 Test Procedure

Peak Power:
A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average Power:
Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

6.2 Number of Hopping Frequency Used

6.2.1 Test Setup



6.2.2 Test Procedure

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
c. Set the SA Sweep time = Auto, Detector function = Peak.
d. Set the SA trace on Max hold mode and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
e. Set the SA on View mode and then plot the result on SA screen.
f. Repeat above procedures until all frequencies measured were complete.

6.3 Dwell Time on Each Channel

6.3.1 Test Setup



6.3.2 Test Procedure

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
e. Repeat above procedures until all different time-slot modes have been completed.

6.4 Hopping Channel Separation

6.4.1 Test Setup



6.4.2 Test Procedure

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
c. Set the SA Sweep time = Auto, Detector function = Peak.
d. Set the SA trace on Max hold mode and record the separation of two adjacent channels.
e. Measure the frequency difference of these two adjacent channels by SA marker-delta function. And then plot the result on SA screen.
f. Repeat above procedures until all frequencies measured were complete.

6.5 20 dB Bandwidth

6.5.1 Test Setup



6.5.2 Test Procedure

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
c. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
d. Repeat above procedures until all frequencies measured were complete.

6.6 Conducted Out of Band Emissions

6.6.1 Test Setup



6.6.2 Test Procedure

MEASUREMENT PROCEDURE REF

a. Set the RBW = 100 kHz.
b. Set the VBW ≥ 300 kHz.
c. Detector = peak.
d. Sweep time = auto couple.
e. Trace mode = max hold.
f. Allow trace to fully stabilize.
g. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOBE

a. Set RBW = 100 kHz.
b. Set VBW ≥ 300 kHz.
c. Detector = peak.
d. Sweep = auto couple.
e. Trace Mode = max hold.
f. Allow trace to fully stabilize.
g. Use the peak marker function to determine the maximum amplitude level.

6.7 AC Power Conducted Emissions

6.7.1 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.2 Test Procedure

a. The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.

6.8 Unwanted Emissions below 1 GHz

6.8.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.8.2 Test Procedure

For Radiated emission below 30 MHz

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
3. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated emission above 30 MHz

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

6.9 Unwanted Emissions above 1 GHz

6.9.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.9.2 Test Procedure

a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Notes:

1. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
2. According to ANSI C63.10 section 6.6.4 and 4.1.4.2.2. For fundamental and harmonic signal measurement, according to ANSI C63.10 section 7.5, the average value = peak value + duty cycle correction factor. For duty cycle correction factor values, see the Test Signal Duty Cycle section in this report.
3. All modes of operation were investigated and the worst-case emissions are reported.

7 Test Results of Test Item

7.1 RF Output Power

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 76% RH	Tested By:	Jed Wu

For Peak Power

GFSK

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
0	2402	34.356	15.36	21	Pass
39	2441	38.019	15.80	21	Pass
78	2480	28.576	14.56	21	Pass

Note: The antenna gain is 2.47 dBi < 6 dBi, so the output power limit shall not be reduced.

8DPSK

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
0	2402	24.322	13.86	21	Pass
39	2441	29.992	14.77	21	Pass
78	2480	20.749	13.17	21	Pass

Note: The antenna gain is 2.47 dBi < 6 dBi, so the output power limit shall not be reduced.

For Average Power

GFSK

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	32.359	15.10
39	2441	35.81	15.54
78	2480	26.915	14.30

8DPSK

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	22.909	13.60
39	2441	28.249	14.51
78	2480	19.543	12.91

7.2 Number of Hopping Frequency Used

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 76% RH	Tested By:	Jed Wu

GFSK



(Left side)



(Right side)

Note: There are 79 hopping frequencies in the hopping mode. On the plots, it shows that the hopping frequencies are equally spaced.

8DPSK



(Left side)



(Right side)

Note: There are 79 hopping frequencies in the hopping mode. On the plots, it shows that the hopping frequencies are equally spaced.

7.3 Dwell Time on Each Channel

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 76% RH	Tested By:	Jed Wu

GFSK

Mode	Number of transmission in 31.6 sec	Length of transmission time (msec)	Dwell Time (msec)	Limit (msec)	Test Result
DH1	50 (times / 5 sec) * 6.32 = 316 times	0.426	134.62	400	Pass
DH3	27 (times / 5 sec) * 6.32 = 171 times	1.72	294.12	400	Pass
DH5	17 (times / 5 sec) * 6.32 = 108 times	3.008	324.86	400	Pass

Spectrum plots of Dwell Time



GFSK DH1



GFSK DH1



GFSK DH3



GFSK DH3



GFSK DH5



GFSK DH5

8DPSK

Mode	Number of transmission in 31.6 sec	Length of transmission time (msec)	Dwell Time (msec)	Limit (msec)	Test Result
3DH1	50 (times / 5 sec) * 6.32 = 316 times	0.444	140.3	400	Pass
3DH3	26 (times / 5 sec) * 6.32 = 165 times	1.725	284.63	400	Pass
3DH5	17 (times / 5 sec) * 6.32 = 108 times	2.957	319.36	400	Pass

Spectrum plots of Dwell Time



8DPSK 3DH1



8DPSK 3DH1



8DPSK 3DH3



8DPSK 3DH3



8DPSK 3DH5



8DPSK 3DH5

7.4 Hopping Channel Separation

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 76% RH	Tested By:	Jed Wu

GFSK

Channel	Frequency (MHz)	Hopping Channel Separation (MHz)	Minimum Limit (MHz)	Test Result
0	2402	1.00	0.64	Pass
39	2441	1.00	0.64	Pass
78	2480	1.01	0.64	Pass

Note: The minimum limit is two-third 20dB bandwidth.

8DPSK

Channel	Frequency (MHz)	Hopping Channel Separation (MHz)	Minimum Limit (MHz)	Test Result
0	2402	1.00	0.87	Pass
39	2441	1.00	0.87	Pass
78	2480	1.00	0.87	Pass

Note: The minimum limit is two-third 20dB bandwidth.

Spectrum Plot of Minimum Value



GFSK : CH 0



8DPSK : CH 0

7.5 20 dB Bandwidth

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 76% RH	Tested By:	Jed Wu

GFSK

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
0	2402	0.95
39	2441	0.95
78	2480	0.95

8DPSK

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
0	2402	1.3
39	2441	1.3
78	2480	1.3

Spectrum Plot of Minimum Value



GFSK : CH 0



8DPSK : CH 0

7.6 Conducted Out of Band Emissions

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 76% RH	Tested By:	Jed Wu

GFSK



Hopping disabled (Low Channel)



Hopping disabled (Low Channel)



Hopping disabled (High Channel)



Hopping disabled (High Channel)



Hopping enabled (Low Channel)



Hopping enabled (Low Channel)



Hopping enabled (High Channel)



Hopping enabled (High Channel)

8DPSK



Hopping disabled (Low Channel)



Hopping disabled (Low Channel)



Hopping disabled (High Channel)



Hopping disabled (High Channel)



Hopping enabled (Low Channel)



Hopping enabled (Low Channel)



Hopping enabled (High Channel)



Hopping enabled (High Channel)

7.7 AC Power Conducted Emissions

Mode A

RF Mode	BT GFSK	Channel	CH 39：2441 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75 % RH
Tested By	Dalen Dei		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15678	10.03	25.87	8.32	35.90	18.35	65.63	55.63	-29.73	-37.28
2	0.36902	10.12	22.45	15.18	32.57	25.30	58.52	48.52	-25.95	-23.22
3	0.84808	10.19	13.30	5.46	23.49	15.65	56.00	46.00	-32.51	-30.35
4	1.50122	10.24	13.15	5.48	23.39	15.72	56.00	46.00	-32.61	-30.28
5	3.59960	10.35	13.60	4.83	23.95	15.18	56.00	46.00	-32.05	-30.82
6	15.71614	10.68	7.97	2.30	18.65	12.98	60.00	50.00	-41.35	-37.02

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



RF Mode	BT GFSK	**Channel**	CH 39：2441 MHz
Frequency Range	150 kHz ~ 30 MHz	**Detector Function & Resolution Bandwidth**	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	**Environmental Conditions**	25 °C, 75 % RH
Tested By	Dalen Dei		

Phase Of Power : Neutral (N)										
No	**Frequency (MHz)**	**Correction Factor (dB)**	**Reading Value (dBuV)**		**Emission Level (dBuV)**		**Limit (dBuV)**		**Margin (dB)**	
			Q.P.	**AV.**	**Q.P.**	**AV.**	**Q.P.**	**AV.**	**Q.P.**	**AV.**
1	0.15000	10.04	27.29	10.15	37.33	20.19	66.00	56.00	-28.67	-35.81
2	0.36902	10.05	24.09	16.69	34.14	26.74	58.52	48.52	-24.38	-21.78
3	0.86763	10.08	14.18	5.12	24.26	15.20	56.00	46.00	-31.74	-30.80
4	1.54781	10.12	13.18	2.85	23.30	12.97	56.00	46.00	-32.70	-33.03
5	3.47836	10.21	13.79	4.78	24.00	14.99	56.00	46.00	-32.00	-31.01
6	15.13731	10.55	7.86	2.17	18.41	12.72	60.00	50.00	-41.59	-37.28

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



Mode B

RF Mode	BT GFSK	Channel	CH 39：2441 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75 % RH
Tested By	Dalen Dei		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15595	10.03	40.57	21.27	50.60	31.30	65.68	55.68	-15.08	-24.38
2	0.55475	10.15	28.78	18.69	38.93	28.84	56.00	46.00	-17.07	-17.16
3	1.24700	10.22	23.15	14.97	33.37	25.19	56.00	46.00	-22.63	-20.81
4	3.70702	10.36	25.33	14.01	35.69	24.37	56.00	46.00	-20.31	-21.63
5	5.91517	10.44	11.76	5.93	22.20	16.37	60.00	50.00	-37.80	-33.63
6	26.69432	10.71	7.31	1.05	18.02	11.76	60.00	50.00	-41.98	-38.24

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



RF Mode	BT GFSK	**Channel**	CH 39：2441 MHz
Frequency Range	150 kHz ~ 30 MHz	**Detector Function & Resolution Bandwidth**	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	**Environmental Conditions**	25 °C, 75 % RH
Tested By	Dalen Dei		

Phase Of Power : Neutral (N)										
No	**Frequency (MHz)**	**Correction Factor (dB)**	**Reading Value (dBuV)**		**Emission Level (dBuV)**		**Limit (dBuV)**		**Margin (dB)**	
			Q.P.	**AV.**	**Q.P.**	**AV.**	**Q.P.**	**AV.**	**Q.P.**	**AV.**
1	**0.15391**	**10.04**	**41.00**	**20.37**	**51.04**	**30.41**	**65.79**	**55.79**	**-14.75**	**-25.38**
2	0.51858	10.06	29.88	19.45	39.94	29.51	56.00	46.00	-16.06	-16.49
3	1.43864	10.11	18.28	11.51	28.39	21.62	56.00	46.00	-27.61	-24.38
4	3.15557	10.20	19.65	7.92	29.85	18.12	56.00	46.00	-26.15	-27.88
5	10.92516	10.52	14.65	8.82	25.17	19.34	60.00	50.00	-34.83	-30.66
6	17.27272	10.57	8.48	3.84	19.05	14.41	60.00	50.00	-40.95	-35.59

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



7.8 Unwanted Emissions below 1 GHz

RF Mode	BT GFSK	**Channel**	CH 39：2441 MHz
Frequency Range	30 MHz ~ 1 GHz	**Detector Function & Bandwidth**	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	**Environmental Conditions**	20 °C, 72 % RH
Tested By	Dalen Dai		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	39.70	25.4 QP	40.0	-14.6	1.37 H	350	34.9	-9.5
2	66.86	28.1 QP	40.0	-11.9	1.75 H	42	37.7	-9.6
3	**212.36**	**37.0 QP**	**43.5**	**-6.5**	**1.63 H**	**284**	**46.9**	**-9.9**
4	396.66	34.8 QP	46.0	-11.2	1.88 H	64	38.2	-3.4
5	658.56	30.8 QP	46.0	-15.2	2.11 H	266	28.6	2.2
6	842.86	34.4 QP	46.0	-11.6	1.79 H	229	28.3	6.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



RF Mode	BT GFSK	Channel	CH 39：2441 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	20 °C, 72 % RH
Tested By	Dalen Dai		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	43.58	29.3 QP	40.0	-10.7	1.73 V	0	38.3	-9.0
2	66.86	28.7 QP	40.0	-11.3	1.54 V	345	38.3	-9.6
3	225.94	34.9 QP	46.0	-11.1	1.66 V	0	44.8	-9.9
4	373.38	33.3 QP	46.0	-12.7	1.81 V	114	37.2	-3.9
5	660.50	30.4 QP	46.0	-15.6	1.42 V	267	28.1	2.3
6	854.50	34.6 QP	46.0	-11.4	1.70 V	186	28.3	6.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



7.9 Unwanted Emissions above 1 GHz

RF Mode	BT GFSK	Channel	CH 0：2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 MHz, DET=RMS
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 74 % RH
Tested By	Dalen Dai		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	52.7 PK	74.0	-21.3	1.51 H	281	53.9	-1.2
2	2390.00	41.3 AV	54.0	-12.7	1.51 H	281	42.5	-1.2
3	*2402.00	111.4 PK			1.51 H	281	112.5	-1.1
4	*2402.00	80.6 AV			1.51 H	281	81.7	-1.1
5	4804.00	47.6 PK	74.0	-26.4	1.27 H	14	40.4	7.2
6	4804.00	16.8 AV	54.0	-37.2	1.27 H	14	9.6	7.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	51.9 PK	74.0	-22.1	3.73 V	327	53.1	-1.2
2	2390.00	40.6 AV	54.0	-13.4	3.73 V	327	41.8	-1.2
3	*2402.00	104.1 PK			3.73 V	327	105.2	-1.1
4	*2402.00	73.3 AV			3.73 V	327	74.4	-1.1
5	4804.00	46.3 PK	74.0	-27.7	1.69 V	335	39.1	7.2
6	4804.00	15.5 AV	54.0	-38.5	1.69 V	335	8.3	7.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(2.887 ms / 100 ms) = -30.8 dB

RF Mode	BT GFSK	Channel	CH 39：2441 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 MHz, DET=RMS
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 74 % RH
Tested By	Dalen Dai		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	111.9 PK			1.48 H	265	112.8	-0.9
2	*2441.00	81.1 AV			1.48 H	265	82.0	-0.9
3	4882.00	48.0 PK	74.0	-26.0	1.31 H	17	40.3	7.7
4	4882.00	17.2 AV	54.0	-36.8	1.31 H	17	9.5	7.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	104.6 PK			3.81 V	322	105.5	-0.9
2	*2441.00	73.8 AV			3.81 V	322	74.7	-0.9
3	4882.00	46.6 PK	74.0	-27.4	1.65 V	341	38.9	7.7
4	4882.00	15.8 AV	54.0	-38.2	1.65 V	341	8.1	7.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(2.887 ms / 100 ms) = -30.8 dB

RF Mode	BT GFSK	**Channel**	CH 78：2480 MHz
Frequency Range	1 GHz ~ 25 GHz	**Detector Function & Bandwidth**	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 MHz, DET=RMS
Input Power	120 Vac, 60 Hz	**Environmental Conditions**	25 °C, 74 % RH
Tested By	Dalen Dai		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	*2480.00	110.6 PK			1.44 H	288	111.1	-0.5
2	*2480.00	79.8 AV			1.44 H	288	80.3	-0.5
3	2483.50	55.6 PK	74.0	-18.4	1.44 H	288	56.1	-0.5
4	2483.50	42.3 AV	54.0	-11.7	1.44 H	288	42.8	-0.5
5	4960.00	47.2 PK	74.0	-26.8	1.23 H	11	39.4	7.8
6	4960.00	16.4 AV	54.0	-37.6	1.23 H	11	8.6	7.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	*2480.00	103.8 PK			3.70 V	317	104.3	-0.5
2	*2480.00	73.0 AV			3.70 V	317	73.5	-0.5
3	2483.50	53.9 PK	74.0	-20.1	3.70 V	317	54.4	-0.5
4	2483.50	41.1 AV	54.0	-12.9	3.70 V	317	41.6	-0.5
5	4960.00	46.0 PK	74.0	-28.0	1.77 V	352	38.2	7.8
6	4960.00	15.2 AV	54.0	-38.8	1.77 V	352	7.4	7.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(2.887 ms / 100 ms) = -30.8 dB

RF Mode	BT 8DPSK	**Channel**	CH 0：2402 MHz
Frequency Range	1 GHz ~ 25 GHz	**Detector Function & Bandwidth**	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 MHz, DET=RMS
Input Power	120 Vac, 60 Hz	**Environmental Conditions**	25 °C, 74 % RH
Tested By	Dalen Dai		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	2390.00	52.3 PK	74.0	-21.7	1.50 H	280	53.5	-1.2
2	2390.00	41.1 AV	54.0	-12.9	1.50 H	280	42.3	-1.2
3	*2402.00	109.2 PK			1.50 H	280	110.3	-1.1
4	*2402.00	78.4 AV			1.50 H	280	79.5	-1.1
5	4804.00	47.1 PK	74.0	-26.9	1.29 H	16	39.9	7.2
6	4804.00	16.3 AV	54.0	-37.7	1.29 H	16	9.1	7.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	2390.00	51.6 PK	74.0	-22.4	3.75 V	326	52.8	-1.2
2	2390.00	40.5 AV	54.0	-13.5	3.75 V	326	41.7	-1.2
3	*2402.00	101.1 PK			3.75 V	326	102.2	-1.1
4	*2402.00	70.3 AV			3.75 V	326	71.4	-1.1
5	4804.00	45.9 PK	74.0	-28.1	1.66 V	345	38.7	7.2
6	4804.00	15.1 AV	54.0	-38.9	1.66 V	345	7.9	7.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(2.893 ms / 100 ms) = -30.8 dB

RF Mode	BT 8DPSK	**Channel**	CH 39：2441 MHz
Frequency Range	1 GHz ~ 25 GHz	**Detector Function & Bandwidth**	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 MHz, DET=RMS
Input Power	120 Vac, 60 Hz	**Environmental Conditions**	25 °C, 74 % RH
Tested By	Dalen Dai		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	*2441.00	110.0 PK			1.47 H	277	110.9	-0.9
2	*2441.00	79.2 AV			1.47 H	277	80.1	-0.9
3	4882.00	47.7 PK	74.0	-26.3	1.25 H	12	40.0	7.7
4	4882.00	16.9 AV	54.0	-37.1	1.25 H	12	9.2	7.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	*2441.00	101.9 PK			3.77 V	323	102.8	-0.9
2	*2441.00	71.1 AV			3.77 V	323	72.0	-0.9
3	4882.00	46.2 PK	74.0	-27.8	1.71 V	349	38.5	7.7
4	4882.00	15.4 AV	54.0	-38.6	1.71 V	349	7.7	7.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(2.893 ms / 100 ms) = -30.8 dB

RF Mode	BT 8DPSK	**Channel**	CH 78：2480 MHz
Frequency Range	1 GHz ~ 25 GHz	**Detector Function & Bandwidth**	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 MHz, DET=RMS
Input Power	120 Vac, 60 Hz	**Environmental Conditions**	25 °C, 74 % RH
Tested By	Dalen Dai		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	*2480.00	108.7 PK			1.44 H	295	109.2	-0.5
2	*2480.00	77.9 AV			1.44 H	295	78.4	-0.5
3	2483.50	55.7 PK	74.0	-18.3	1.44 H	295	56.2	-0.5
4	**2483.50**	**42.5 AV**	**54.0**	**-11.5**	**1.44 H**	**295**	**43.0**	**-0.5**
5	4960.00	46.8 PK	74.0	-27.2	1.28 H	14	39.0	7.8
6	4960.00	16.0 AV	54.0	-38.0	1.28 H	14	8.2	7.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	*2480.00	100.6 PK			3.77 V	319	101.1	-0.5
2	*2480.00	69.8 AV			3.77 V	319	70.3	-0.5
3	2483.50	53.8 PK	74.0	-20.2	3.77 V	319	54.3	-0.5
4	2483.50	41.2 AV	54.0	-12.8	3.77 V	319	41.7	-0.5
5	4960.00	45.7 PK	74.0	-28.3	1.69 V	352	37.9	7.8
6	4960.00	14.9 AV	54.0	-39.1	1.69 V	352	7.1	7.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(2.893 ms / 100 ms) = -30.8 dB

Plot of Band Edge

Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak

BT GFSK Channel 0



Horizontal (Peak)



Vertical (Peak)

BT GFSK Channel 78



Horizontal (Peak)



Vertical (Peak)

Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak

BT 8DPSK Channel 0



Horizontal (Peak)



Vertical (Peak)

BT 8DPSK Channel 78



Horizontal (Peak)



Vertical (Peak)

8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab
Tel: 886-3-6668565
Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@bureauveritas.com
Web Site: http://ee.bureauveritas.com.tw

The address and road map of all our labs can be found in our web site also.

--- END ---