

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: 47 CFR FCC Part 15, Subpart C (Section 15.247)
Report No.: RFBEDV-WTW-P25060594-1
FCC ID: S9E-136500
Product: Rugged Controller
Brand: Trimble
Model No.: 136500
Received Date: 2025/6/27
Test Date: 2025/9/1 ~ 2025/9/12
Issued Date: 2025/12/9
Applicant: Trimble Inc.
Address: 5475 Kellenburger Road, Dayton, Ohio, 45424
Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories
Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan
FCC Registration / 788550 / TW0003
Designation Number:

Approved by: _____

Jeremy Lin

Jeremy Lin / Project Engineer

, Date: _____

2025/12/9

This test report consists of 60 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



Prepared by : Gina Liu / Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	4
1 Certificate.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Supplementary Information	6
3 General Information	7
3.1 General Description	7
3.2 Antenna Description of EUT	8
3.3 Channel List	8
3.4 Test Mode Applicability and Tested Channel Detail	9
3.5 Duty Cycle of Test Signal	10
3.6 Test Program Used and Operation Descriptions	12
3.7 Connection Diagram of EUT and Peripheral Devices	12
3.8 Configuration of Peripheral Devices and Cable Connections	12
4 Test Instruments	13
4.1 RF Output Power	13
4.2 Power Spectral Density	13
4.3 6 dB Bandwidth	13
4.4 Conducted Out of Band Emissions	13
4.5 AC Power Conducted Emissions	14
4.6 Unwanted Emissions below 1 GHz	14
4.7 Unwanted Emissions above 1 GHz	15
5 Limits of Test Items.....	16
5.1 RF Output Power	16
5.2 Power Spectral Density	16
5.3 6 dB Bandwidth	16
5.4 Conducted Out of Band Emissions	16
5.5 AC Power Conducted Emissions	16
5.6 Unwanted Emissions below 1 GHz	16
5.7 Unwanted Emissions above 1 GHz	17
6 Test Arrangements	18
6.1 RF Output Power	18
6.1.1 Test Setup	18
6.1.2 Test Procedure	18
6.2 Power Spectral Density	18
6.2.1 Test Setup	18
6.2.2 Test Procedure	18
6.3 6 dB Bandwidth	19
6.3.1 Test Setup	19
6.3.2 Test Procedure	19
6.4 Conducted Out of Band Emissions	20
6.4.1 Test Setup	20
6.4.2 Test Procedure	20
6.5 AC Power Conducted Emissions	21
6.5.1 Test Setup	21
6.5.2 Test Procedure	21
6.6 Unwanted Emissions below 1 GHz	22
6.6.1 Test Setup	22
6.6.2 Test Procedure	23
6.7 Unwanted Emissions above 1 GHz	24
6.7.1 Test Setup	24
6.7.2 Test Procedure	24
7 Test Results of Test Item	25

7.1	RF Output Power.....	25
7.2	Power Spectral Density	27
7.3	6 dB Bandwidth	29
7.4	Conducted Out of Band Emissions	31
7.5	AC Power Conducted Emissions	35
7.6	Unwanted Emissions below 1 GHz	37
7.7	Unwanted Emissions above 1 GHz.....	39
8	Pictures of Test Arrangements	59
9	Information of the Testing Laboratories	60

Release Control Record

Issue No.	Description	Date Issued
RFBEDV-WTW-P25060594-1	Original release.	2025/12/9

1 Certificate

Product: Rugged Controller
Brand: Trimble
Test Model: 136500
Sample Status: Engineering sample
Applicant: Trimble Inc.
Test Date: 2025/9/1 ~ 2025/9/12
Standard: 47 CFR FCC Part 15, Subpart C (Section 15.247)
Measurement procedure: ANSI C63.10-2020
KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
Standard / Clause	Test Item	Result	Remark
15.247(b)	RF Output Power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.247(a)(2)	6 dB Bandwidth	Pass	Meet the requirement of limit.
15.247(d)	Conducted Out of Band Emissions	Pass	Meet the requirement of limit.
15.207	AC Power Conducted Emissions	Pass	Minimum passing margin is -25.76 dB at 0.44600 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions below 1 GHz	Pass	Minimum passing margin is -8.4 dB at 65.89 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions above 1 GHz	Pass	Minimum passing margin is -1.0 dB at 2312.47 MHz
15.203	Antenna Requirement	Pass	Antenna connector is ipex(MHF) not a standard connector.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Specification	Expanded Uncertainty (k=2) (±)
RF Output Power	-	1.371 dB
Power Spectral Density	-	1.017 dB
6 dB Bandwidth	-	206.5 Hz
Conducted Out of Band Emissions	9 kHz ~ 40 MHz	2.79 dB
AC Power Conducted Emissions	9 kHz ~ 30 MHz	2.90 dB
Unwanted Emissions below 1 GHz	9 kHz ~ 30 MHz	3.59 dB
	30 MHz ~ 1 GHz	3.6 dB
Unwanted Emissions above 1 GHz	1 GHz ~ 18 GHz	2.29 dB
	18 GHz ~ 40 GHz	2.29 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description

Product	Rugged Controller
Brand	Trimble
Test Model	136500
Status of EUT	Engineering sample
Power Supply Rating	5V – 3A, 9V – 3A for adapter 3.635 Vdc for battery
Modulation Type	GFSK
Modulation Technology	DTS
Transfer Rate	1MBaud with 1Mbps transfer rate 1MBaud with Coded 125kbps transfer rate 1MBaud with Coded 500kbps transfer rate 2MBaud with 2Mbps transfer rate
Operating Frequency	2.402 GHz ~ 2.48 GHz
Number of Channel	40
Output Power	5.572 mW (7.46 dBm)

Note:

1. The EUT uses following accessories.

Item	Brand	Model	Specification
USB Type C Cable	SINBON Electronics Co., Ltd.	A9866672-02	-
Battery	Trimble	136510	Power Rating: 3.635Vdc, 12400mAh, 46Wh
Stylus & Tether Pen 1	DAKING COMPONENTS LIMITED	CUSTTRIM112	-
Stylus & Tether Pen 2	TAXXTRON INTERNATIONAL CORPORATION	CHSA175-00	-

2. There are WWAN, NFC, Bluetooth and WLAN (2.4 GHz & 5 GHz) technology used for the EUT.

3. Simultaneously transmission combination.

Combination	Technology			
1	WWAN	BT	WLAN (2.4 GHz)	NFC
2	WWAN	BT	WLAN (5 GHz)	NFC

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

4. The BT support 1TX diversity function.

5. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 Antenna Description of EUT

1. The antenna information is listed as below.

Antenna NO.		Brand	Model	Frequency range	Antenna Net Gain (dBi)	Antenna Type	Connector Type
1	Aux	Pulse	TZ31844	2.4~2.4835GHz	0.3	PIFA	ipex(MHF)
				5.15~5.25GHz	1.79	PIFA	ipex(MHF)
				5.25~5.35GHz	1.79	PIFA	ipex(MHF)
				5.47~5.725GHz	0.94	PIFA	ipex(MHF)
				5.725~5.85GHz	2.21	PIFA	ipex(MHF)
2	Main	Pulse	TZ31840	2.4~2.4835GHz	1.07	PIFA	ipex(MHF)
				5.15~5.25GHz	2.08	PIFA	ipex(MHF)
				5.25~5.35GHz	2.08	PIFA	ipex(MHF)
				5.47~5.725GHz	3.66	PIFA	ipex(MHF)
				5.725~5.85GHz	3.5	PIFA	ipex(MHF)

* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

3.3 Channel List

40 channels are provided for BT-LE:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	1. EUT can be used in the following ways: X-axis/ Y-axis/ Z-axis. Pre-scan these ways and find the worst case as a representative test condition.
Worst Case:	X-axis/ Y-axis/ Z-axis Worst Condition: X-axis

Following channel(s) was (were) selected for the final test as listed below:

Test Item	Mode	Tested Channel	Modulation	Data Rate Parameter
RF Output Power	BT-LE 1M	0, 19, 39	GFSK	1Mb/s
	BT-LE 2M	0, 19, 39	GFSK	2Mb/s
	BT-LE 125k	0, 19, 39	GFSK	125kbps
	BT-LE 500k	0, 19, 39	GFSK	500kbps
Power Spectral Density	BT-LE 1M	0, 19, 39	GFSK	1Mb/s
	BT-LE 2M	0, 19, 39	GFSK	2Mb/s
	BT-LE 125k	0, 19, 39	GFSK	125kbps
	BT-LE 500k	0, 19, 39	GFSK	500kbps
6 dB Bandwidth / Conducted Out of Band Emissions	BT-LE 1M	0, 19, 39	GFSK	1Mb/s
	BT-LE 2M	0, 19, 39	GFSK	2Mb/s
AC Power Conducted Emissions	BT-LE 2M	19	GFSK	2Mb/s
Unwanted Emissions below 1 GHz	BT-LE 2M	39	GFSK	2Mb/s
Unwanted Emissions above 1 GHz	BT-LE 1M	0, 19, 39	GFSK	1Mb/s
	BT-LE 2M	0, 19, 39	GFSK	2Mb/s
	BT-LE 125k	0, 19, 39	GFSK	125kbps
	BT-LE 500k	0, 19, 39	GFSK	500kbps


3.5 Duty Cycle of Test Signal

BT-LE 1M: Duty cycle = $2.15 \text{ ms} / 2.49 \text{ ms} \times 100\% = 86.3\%$, duty factor = $10 * \log (1/\text{Duty cycle}) = 0.64 \text{ dB}$


BT-LE 2M: Duty cycle = $1.092 \text{ ms} / 1.876 \text{ ms} \times 100\% = 58.2\%$, duty factor = $10 * \log (1/\text{Duty cycle}) = 2.35 \text{ dB}$

BT-LE 125k: Duty cycle = $17.16 \text{ ms} / 17.46 \text{ ms} \times 100\% = 98.3\%$

BT-LE 500k: Duty cycle = $4.6 \text{ ms} / 5 \text{ ms} \times 100\% = 92.0\%$, duty factor = $10 * \log (1/\text{Duty cycle}) = 0.36 \text{ dB}$




BT-LE 1M




BT-LE 2M

Duty Cycle Analysis



BT-LE 125k

Duty Cycle Analysis




BT-LE 500k

3.6 Test Program Used and Operation Descriptions

Controlling software QRCT4 Version 4.0.163.1 has been activated to set the EUT under transmission condition continuously at specific channel frequency.

3.7 Connection Diagram of EUT and Peripheral Devices



3.8 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Adapter	ADAPTER TECH	ATN65A3-W200V	N/A	N/A	Supplied by applicant

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	Type-C	1	1.5	Y	0	Accessory of EUT

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 RF Output Power

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Fixed Attenuator Woken	00800A1K01A-10	00800A1K01A-10-01	2025/5/23	2026/5/22
Peak Power Analyzer Keysight	8990B	MY51000485	2025/1/20	2026/1/19
USB Power Sensor Anritsu	MA24408A	12994	2024/12/4	2025/12/3
Wideband Power Sensor Keysight	N1923A	MY58020002	2025/1/21	2026/1/20
		MY58140009	2025/1/21	2026/1/20

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2025/9/12

4.2 Power Spectral Density

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Fixed Attenuator Woken	00800A1K01A-10	00800A1K01A-10-01	2025/5/23	2026/5/22
Signal & Spectrum Analyzer R&S	FSV3044	101504	2025/6/18	2026/6/17
Software BV	ADT_RF Test Software V7.6.5.4	N/A	N/A	N/A

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2025/9/12

4.3 6 dB Bandwidth

Refer to section 4.2 to get the tested date and information of the instruments.

4.4 Conducted Out of Band Emissions

Refer to section 4.2 to get the tested date and information of the instruments.

4.5 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohm terminal resistance	E1-011279	04	2024/11/28	2025/11/27
	E1-011280	05	2024/11/28	2025/11/27
	E1-011311	09	2024/11/28	2025/11/27
DC LISN Schwarzbeck	NNBM 8126G	8126G-069	2024/11/5	2025/11/4
Diode Pulse Limiter Schwarzbeck	VTSD 9561 F-N	01617	2025/8/23	2026/8/22
EMI Test Receiver R&S	ESR3	102783	2024/12/17	2025/12/16
LISN R&S	ESH2-Z5	100100	2025/3/5	2026/3/4
	ESH3-Z5	100312	2025/8/29	2026/8/28
RF Coaxial Cable Woken	5D-FB	Cable-cond2-01	2025/8/23	2026/8/22
Software BVADT	BVADT_Conf_ V7.4.1.0	N/A	N/A	N/A
V-LISN Schwarzbeck	NNBL 8226-2	8226-142	2025/8/27	2026/8/26

Notes:

1. The test was performed in HY - Conduction 2.
2. Tested Date: 2025/9/5

4.6 Unwanted Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn BV ADT	AT100	AT93021705	N/A	N/A
Bi_Log Antenna Schwarzbeck	VULB 9168	9168-160	2024/10/9	2025/10/8
Loop Antenna TESEQ	HLA 6121	64095	2024/10/17	2025/10/16
MXE EMI Receiver Agilent	N9038A	MY51210203	2025/8/27	2026/8/26
Preamplifier Agilent	8447D	2944A10638	2025/4/27	2026/4/26
RF Coaxial Cable Woken	8D-FB	Cable-CH9-01	2025/4/27	2026/4/26
Signal & Spectrum Analyzer R&S	FSW43	101866	2025/3/25	2026/3/24
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table BV ADT	TT100	TT93021705	N/A	N/A
Turn Table Controller BV ADT	SC100	SC93021705	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 4.
2. Tested Date: 2025/9/1

4.7 Unwanted Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn BV ADT	AT100	AT93021705	N/A	N/A
Boresight antenna tower fixture BV	BAF-02	5	N/A	N/A
Horn Antenna Schwarzbeck	BBHA 9120D	9120D-1169	2024/11/10	2025/11/9
	BBHA 9170	9170-480	2024/11/10	2025/11/9
		BBHA9170243	2024/11/10	2025/11/9
MXE EMI Receiver Agilent	N9038A	MY51210203	2025/8/27	2026/8/26
Preamplifier Agilent	8449B	3008A02367	2025/1/5	2026/1/4
Preamplifier EMCI	EMC 184045	980116	2024/9/24	2025/9/23
RF Coaxial Cable EMCI	EMC102-KM-KM-600	150928	2025/6/30	2026/6/29
	EMC102-KM-KM-3000	150929	2025/6/30	2026/6/29
RF Coaxial Cable HUBER+SUHNER	SUCOFLEX 104	CABLE-CH9-(250795/4)	2025/1/5	2026/1/4
RF Coaxial Cable HUBER+SUHNER&EMCI	SUCOFLEX 104& EMC104-SM-SM8000	CABLE-CH9-02 (248780+171006)	2025/1/5	2026/1/4
Signal & Spectrum Analyzer R&S	FSW43	101866	2025/3/25	2026/3/24
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table BV ADT	TT100	TT93021705	N/A	N/A
Turn Table Controller BV ADT	SC100	SC93021705	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 4.
2. Tested Date: 2025/9/12

5 Limits of Test Items

5.1 RF Output Power

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30 dBm)

5.2 Power Spectral Density

The Maximum of Power Spectral Density Measurement is 8 dBm in any 3 kHz.

5.3 6 dB Bandwidth

The minimum of 6 dB Bandwidth Measurement is 0.5 MHz.

5.4 Conducted Out of Band Emissions

Below 20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

5.5 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.6 Unwanted Emissions below 1 GHz

Radiated emissions up to 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

5.7 Unwanted Emissions above 1 GHz

Radiated emissions above 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
Above 960	500	3


Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

6 Test Arrangements

6.1 RF Output Power

6.1.1 Test Setup



6.1.2 Test Procedure

Peak Power:

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.


The power meter video bandwidth is greater than or equal to the DTS bandwidth and use a fast responding diode detector.

Average Power:

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

6.2 Power Spectral Density

6.2.1 Test Setup




6.2.2 Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span > 1.5 times the DTS bandwidth.
- Set the RBW to: 3 kHz.
- Set the VBW $\geq 3 \times$ RBW.
- Detector = peak.
- Sweep time = No faster than coupled (auto) time.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

6.3 6 dB Bandwidth

6.3.1 Test Setup




6.3.2 Test Procedure

- a. Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- b. Set the VBW $\geq [3 \times \text{RBW}]$.
- c. Detector = peak.
- d. Trace mode = max-hold.
- e. Sweep = No faster than coupled (auto) time.
- f. Allow the trace to stabilize.
- g. Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value.

6.4 Conducted Out of Band Emissions

6.4.1 Test Setup



6.4.2 Test Procedure

MEASUREMENT PROCEDURE REF


- Set instrument center frequency to DTS channel center frequency.
- Set the span to ≥ 1.5 times the DTS bandwidth.
- Set the RBW = 100 kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Sweep time = No faster than coupled (auto) time.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum PSD level.

MEASUREMENT PROCEDURE OOB

- Set the center frequency and span to encompass frequency range to be measured. Note that the frequency range might need to be divided into multiple frequency ranges to retain frequency resolution.
- Set RBW = 100 kHz.
- Set VBW ≥ 300 kHz.
- Detector = peak.
- Sweep = No faster than coupled (auto) time.
- Trace Mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

6.5 AC Power Conducted Emissions

6.5.1 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.5.2 Test Procedure


- Exploratory ac power-line conducted emission measurements: The EUT shall be operated on the mid channel and in the mode with highest output power unless the fundamental operates in the AC power-line emission test range then the EUT shall be operated in the range of typical modes of operation.
- The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.


6.6 Unwanted Emissions below 1 GHz

6.6.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.6.2 Test Procedure

For Radiated emission below 30 MHz

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

Notes:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
- All modes of operation were investigated and the worst-case emissions are reported.

For Radiated emission above 30 MHz


- The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-peak(QP) detect function, Average(AV) detect function, Peak(PK) detect function and specified bandwidth with maximum hold mode when the test frequencies less than or equal to 1 GHz.

Notes:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

6.7 Unwanted Emissions above 1 GHz

6.7.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.2 Test Procedure

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver/spectrum analyzer was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Notes:

- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
- For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

7 Test Results of Test Item

7.1 RF Output Power

Input Power:	3.64 Vdc	Environmental Conditions:	25°C, 60% RH	Tested By:	Ivan Tseng
--------------	----------	---------------------------	--------------	------------	------------

For Peak Power

BT-LE 1M

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
0	2402	4.92	6.92	30	Pass
19	2440	5.26	7.21	30	Pass
39	2480	5.284	7.23	30	Pass

Note: The antenna gain is 1.07 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

BT-LE 2M

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
0	2402	5.164	7.13	30	Pass
19	2440	5.559	7.45	30	Pass
39	2480	5.572	7.46	30	Pass

Note: The antenna gain is 1.07 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

BT-LE 125k

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
0	2402	4.932	6.93	30	Pass
19	2440	5.297	7.24	30	Pass
39	2480	5.272	7.22	30	Pass

Note: The antenna gain is 1.07 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

BT-LE 500k

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
0	2402	4.932	6.93	30	Pass
19	2440	5.37	7.30	30	Pass
39	2480	5.309	7.25	30	Pass

Note: The antenna gain is 1.07 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

For Average Power

BT-LE 1M

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	4.325	6.36
19	2440	4.634	6.66
39	2480	4.645	6.67

BT-LE 2M

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	4.315	6.35
19	2440	4.613	6.64
39	2480	4.624	6.65

BT-LE 125k

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	4.305	6.34
19	2440	4.624	6.65
39	2480	4.613	6.64

BT-LE 500k

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	4.159	6.19
19	2440	4.457	6.49
39	2480	4.446	6.48

7.2 Power Spectral Density

Input Power:	3.64 Vdc	Environmental Conditions:	25°C, 60% RH	Tested By:	Ivan Tseng
--------------	----------	---------------------------	--------------	------------	------------

BT-LE 1M

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
0	2402	-8.81	8	Pass
19	2440	-8.55	8	Pass
39	2480	-8.50	8	Pass

Note: The antenna gain is 1.07 dBi $\leq$ 6 dBi, so the power density limit shall not be reduced.

BT-LE 2M

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
0	2402	-11.37	8	Pass
19	2440	-11.13	8	Pass
39	2480	-11.18	8	Pass

Note: The antenna gain is 1.07 dBi $\leq$ 6 dBi, so the power density limit shall not be reduced.

BT-LE 125k

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
0	2402	0.05	8	Pass
19	2440	0.30	8	Pass
39	2480	0.24	8	Pass


Note: The antenna gain is 1.07 dBi $\leq$ 6 dBi, so the power density limit shall not be reduced.

BT-LE 500k

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
0	2402	-0.06	8	Pass
19	2440	0.18	8	Pass
39	2480	0.10	8	Pass

Note: The antenna gain is 1.07 dBi $\leq$ 6 dBi, so the power density limit shall not be reduced.

Spectrum Plot of Maximum Value



7.3 6 dB Bandwidth

Input Power:	3.64 Vdc	Environmental Conditions:	25°C, 60% RH	Tested By:	Ivan Tseng
--------------	----------	---------------------------	--------------	------------	------------

BT-LE 1M

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
0	2402	0.68	0.5	Pass
19	2440	0.68	0.5	Pass
39	2480	0.67	0.5	Pass

BT-LE 2M

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
0	2402	1.15	0.5	Pass
19	2440	1.15	0.5	Pass
39	2480	1.14	0.5	Pass





BT-LE 125k

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
0	2402	0.63	0.5	Pass
19	2440	0.63	0.5	Pass
39	2480	0.63	0.5	Pass

BT-LE 500k

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
0	2402	0.66	0.5	Pass
19	2440	0.66	0.5	Pass
39	2480	0.67	0.5	Pass

Spectrum Plot of Minimum Value




7.4 Conducted Out of Band Emissions

Input Power:	3.64 Vdc	Environmental Conditions:	25°C, 60% RH	Tested By:	Ivan Tseng
--------------	----------	---------------------------	--------------	------------	------------

BT-LE 1M



BT-LE 2M



BT-LE 125k



BT-LE 500k




7.5 AC Power Conducted Emissions

RF Mode	BT-LE 2M	Channel	CH 19 : 2440 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75% RH
Tested By	Rex Wang		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17755	10.26	16.12	1.91	26.38	12.17	64.60	54.60	-38.22	-42.43
2	0.23351	10.30	4.52	1.34	14.82	11.64	62.32	52.32	-47.50	-40.68
3	0.32600	10.36	6.58	4.52	16.94	14.88	59.55	49.55	-42.61	-34.67
4	0.41362	10.40	3.45	0.54	13.85	10.94	57.58	47.58	-43.73	-36.64
5	0.64600	10.45	3.03	1.52	13.48	11.97	56.00	46.00	-42.52	-34.03
6	17.27800	11.02	5.65	1.38	16.67	12.40	60.00	50.00	-43.33	-37.60

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	BT-LE 2M	Channel	CH 19 : 2440 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75% RH
Tested By	Rex Wang		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15800	10.29	2.22	1.24	12.51	11.53	65.57	55.57	-53.06	-44.04
2	0.17800	10.30	7.84	5.78	18.14	16.08	64.58	54.58	-46.44	-38.50
3	0.20600	10.31	15.26	0.45	25.57	10.76	63.37	53.37	-37.80	-42.61
4	0.29400	10.37	12.12	1.22	22.49	11.59	60.41	50.41	-37.92	-38.82
5	0.44600	10.45	17.34	10.74	27.79	21.19	56.95	46.95	-29.16	-25.76
6	16.60200	11.18	5.02	2.65	16.20	13.83	60.00	50.00	-43.80	-36.17

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




7.6 Unwanted Emissions below 1 GHz

RF Mode	BT-LE 2M	Channel	CH 39 : 2480 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120 kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	65.89	31.6 QP	40.0	-8.4	1.50 H	206	41.8	-10.2
2	79.47	31.2 QP	40.0	-8.8	2.00 H	222	44.2	-13.0
3	167.74	34.0 QP	43.5	-9.5	1.50 H	126	42.3	-8.3
4	428.67	27.7 QP	46.0	-18.3	2.00 H	354	31.4	-3.7
5	540.22	28.8 QP	46.0	-17.2	1.00 H	288	30.8	-2.0
6	629.46	32.0 QP	46.0	-14.0	2.00 H	213	31.9	0.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	BT-LE 2M	Channel	CH 39 : 2480 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120 kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	65.89	31.5 QP	40.0	-8.5	1.50 V	327	41.7	-10.2
2	79.47	29.1 QP	40.0	-10.9	2.00 V	178	42.1	-13.0
3	167.74	31.5 QP	43.5	-12.0	1.50 V	270	39.8	-8.3
4	299.66	25.1 QP	46.0	-20.9	2.00 V	19	31.5	-6.4
5	485.90	27.6 QP	46.0	-18.4	1.00 V	303	30.4	-2.8
6	624.61	29.5 QP	46.0	-16.5	2.00 V	136	29.5	0.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



7.7 Unwanted Emissions above 1 GHz

RF Mode	BT-LE 125K	Channel	CH 0 : 2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Owen Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2325.58	57.4 PK	74.0	-16.6	2.14 H	126	25.5	31.9
2	2325.58	49.2 AV	54.0	-4.8	2.14 H	126	17.3	31.9
3	2337.74	56.3 PK	74.0	-17.7	2.14 H	126	24.3	32.0
4	2337.74	47.5 AV	54.0	-6.5	2.14 H	126	15.5	32.0
5	*2402.00	97.1 PK			2.14 H	126	65.3	31.8
6	*2402.00	95.9 AV			2.14 H	126	64.1	31.8
7	4804.00	48.2 PK	74.0	-25.8	1.27 H	259	45.3	2.9
8	4804.00	34.6 AV	54.0	-19.4	1.27 H	259	31.7	2.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2325.20	57.4 PK	74.0	-16.6	1.87 V	182	25.5	31.9
2	2325.20	49.3 AV	54.0	-4.7	1.87 V	182	17.4	31.9
3	2337.74	57.6 PK	74.0	-16.4	1.87 V	182	25.6	32.0
4	2337.74	47.6 AV	54.0	-6.4	1.87 V	182	15.6	32.0
5	*2402.00	99.8 PK			1.87 V	182	68.0	31.8
6	*2402.00	98.6 AV			1.87 V	182	66.8	31.8
7	4804.00	48.8 PK	74.0	-25.2	2.06 V	154	45.9	2.9
8	4804.00	34.9 AV	54.0	-19.1	2.06 V	154	32.0	2.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 125K	Channel	CH 19 : 2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Owen Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2311.90	58.8 PK	74.0	-15.2	1.37 H	228	26.9	31.9
2	2311.90	52.7 AV	54.0	-1.3	1.37 H	228	20.8	31.9
3	2363.39	57.0 PK	74.0	-17.0	1.37 H	228	25.0	32.0
4	2363.39	48.3 AV	54.0	-5.7	1.37 H	228	16.3	32.0
5	2376.31	57.1 PK	74.0	-16.9	1.37 H	228	25.2	31.9
6	2376.31	47.1 AV	54.0	-6.9	1.37 H	228	15.2	31.9
7	*2440.00	98.4 PK			1.37 H	228	66.6	31.8
8	*2440.00	97.1 AV			1.37 H	228	65.3	31.8
9	4880.00	48.4 PK	74.0	-25.6	1.77 H	162	45.4	3.0
10	4880.00	34.7 AV	54.0	-19.3	1.77 H	162	31.7	3.0

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2312.47	59.2 PK	74.0	-14.8	1.11 V	214	27.3	31.9
2	2312.47	53.0 AV	54.0	-1.0	1.11 V	214	21.1	31.9
3	2363.20	58.0 PK	74.0	-16.0	1.11 V	214	26.0	32.0
4	2363.20	49.1 AV	54.0	-4.9	1.11 V	214	17.1	32.0
5	2376.50	57.3 PK	74.0	-16.7	1.11 V	214	25.4	31.9
6	2376.50	48.1 AV	54.0	-5.9	1.11 V	214	16.2	31.9
7	*2440.00	100.8 PK			1.11 V	214	69.0	31.8
8	*2440.00	99.7 AV			1.11 V	214	67.9	31.8
9	4880.00	48.9 PK	74.0	-25.1	2.17 V	184	45.9	3.0
10	4880.00	35.1 AV	54.0	-18.9	2.17 V	184	32.1	3.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 125K	Channel	CH 39 : 2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Owen Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2326.34	56.8 PK	74.0	-17.2	2.31 H	185	24.9	31.9
2	2326.34	46.9 AV	54.0	-7.1	2.31 H	185	15.0	31.9
3	2352.37	58.4 PK	74.0	-15.6	2.31 H	185	26.4	32.0
4	2352.37	50.5 AV	54.0	-3.5	2.31 H	185	18.5	32.0
5	*2480.00	98.2 PK			2.31 H	185	66.3	31.9
6	*2480.00	96.9 AV			2.31 H	185	65.0	31.9
7	2483.50	56.3 PK	74.0	-17.7	2.31 H	185	24.4	31.9
8	2483.50	44.4 AV	54.0	-9.6	2.31 H	185	12.5	31.9
9	4960.00	48.3 PK	74.0	-25.7	1.45 H	163	45.1	3.2
10	4960.00	34.7 AV	54.0	-19.3	1.45 H	163	31.5	3.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2326.15	56.9 PK	74.0	-17.1	1.48 V	136	25.0	31.9
2	2326.15	47.2 AV	54.0	-6.8	1.48 V	136	15.3	31.9
3	2351.80	58.9 PK	74.0	-15.1	1.48 V	136	26.9	32.0
4	2351.80	51.4 AV	54.0	-2.6	1.48 V	136	19.4	32.0
5	*2480.00	101.7 PK			1.48 V	136	69.8	31.9
6	*2480.00	100.4 AV			1.48 V	136	68.5	31.9
7	2483.50	56.4 PK	74.0	-17.6	1.48 V	136	24.5	31.9
8	2483.50	44.3 AV	54.0	-9.7	1.48 V	136	12.4	31.9
9	4960.00	48.8 PK	74.0	-25.2	2.26 V	114	45.6	3.2
10	4960.00	35.0 AV	54.0	-19.0	2.26 V	114	31.8	3.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 500K	Channel	CH 0 : 2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Owen Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2325.50	56.7 PK	74.0	-17.3	2.14 H	126	24.8	31.9
2	2325.50	47.8 AV	54.0	-6.2	2.14 H	126	15.9	31.9
3	2338.10	56.2 PK	74.0	-17.8	2.14 H	126	24.2	32.0
4	2338.10	50.3 AV	54.0	-3.7	2.14 H	126	18.3	32.0
5	*2402.00	97.4 PK			2.14 H	126	65.6	31.8
6	*2402.00	96.4 AV			2.14 H	126	64.6	31.8
7	4804.00	47.9 PK	74.0	-26.1	1.27 H	259	45.0	2.9
8	4804.00	34.7 AV	54.0	-19.3	1.27 H	259	31.8	2.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2325.20	57.0 PK	74.0	-17.0	1.87 V	182	25.1	31.9
2	2325.20	48.8 AV	54.0	-5.2	1.87 V	182	16.9	31.9
3	2338.50	56.2 PK	74.0	-17.8	1.87 V	182	24.2	32.0
4	2338.50	47.5 AV	54.0	-6.5	1.87 V	182	15.5	32.0
5	*2402.00	99.8 PK			1.87 V	182	68.0	31.8
6	*2402.00	98.8 AV			1.87 V	182	67.0	31.8
7	4804.00	48.7 PK	74.0	-25.3	2.06 V	154	45.8	2.9
8	4804.00	35.2 AV	54.0	-18.8	2.06 V	154	32.3	2.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 500K	Channel	CH 19 : 2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Owen Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2311.52	58.1 PK	74.0	-15.9	1.37 H	228	26.2	31.9
2	2311.52	52.0 AV	54.0	-2.0	1.37 H	228	20.1	31.9
3	2362.82	56.3 PK	74.0	-17.7	1.37 H	228	24.3	32.0
4	2362.82	49.5 AV	54.0	-4.5	1.37 H	228	17.5	32.0
5	2376.12	56.9 PK	74.0	-17.1	1.37 H	228	25.0	31.9
6	2376.12	47.7 AV	54.0	-6.3	1.37 H	228	15.8	31.9
7	*2440.00	98.0 PK			1.37 H	228	66.2	31.8
8	*2440.00	96.9 AV			1.37 H	228	65.1	31.8
9	4880.00	48.2 PK	74.0	-25.8	1.77 H	162	45.2	3.0
10	4880.00	34.8 AV	54.0	-19.2	1.77 H	162	31.8	3.0

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2311.52	58.5 PK	74.0	-15.5	1.11 V	214	26.6	31.9
2	2311.52	52.5 AV	54.0	-1.5	1.11 V	214	20.6	31.9
3	2363.01	56.9 PK	74.0	-17.1	1.11 V	214	24.9	32.0
4	2363.01	48.7 AV	54.0	-5.3	1.11 V	214	16.7	32.0
5	2376.12	56.5 PK	74.0	-17.5	1.11 V	214	24.6	31.9
6	2376.12	47.6 AV	54.0	-6.4	1.11 V	214	15.7	31.9
7	*2440.00	100.3 PK			1.11 V	214	68.5	31.8
8	*2440.00	99.4 AV			1.11 V	214	67.6	31.8
9	4880.00	48.9 PK	74.0	-25.1	2.17 V	184	45.9	3.0
10	4880.00	35.0 AV	54.0	-19.0	2.17 V	184	32.0	3.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 500K	Channel	CH 39 : 2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Owen Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2326.53	56.7 PK	74.0	-17.3	2.31 H	185	24.8	31.9
2	2326.53	46.7 AV	54.0	-7.3	2.31 H	185	14.8	31.9
3	2351.80	58.1 PK	74.0	-15.9	2.31 H	185	26.1	32.0
4	2351.80	50.7 AV	54.0	-3.3	2.31 H	185	18.7	32.0
5	*2480.00	98.6 PK			2.31 H	185	66.7	31.9
6	*2480.00	97.5 AV			2.31 H	185	65.6	31.9
7	2483.50	50.6 PK	74.0	-23.4	2.31 H	185	18.7	31.9
8	2483.50	44.3 AV	54.0	-9.7	2.31 H	185	12.4	31.9
9	4960.00	48.4 PK	74.0	-25.6	1.45 H	163	45.2	3.2
10	4960.00	35.1 AV	54.0	-18.9	1.45 H	163	31.9	3.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2326.34	56.5 PK	74.0	-17.5	1.48 V	136	24.6	31.9
2	2326.34	47.8 AV	54.0	-6.2	1.48 V	136	15.9	31.9
3	2351.97	60.2 PK	74.0	-13.8	1.48 V	136	28.2	32.0
4	2351.97	52.4 AV	54.0	-1.6	1.48 V	136	20.4	32.0
5	*2480.00	101.1 PK			1.48 V	136	69.2	31.9
6	*2480.00	100.2 AV			1.48 V	136	68.3	31.9
7	2483.50	55.0 PK	74.0	-19.0	1.48 V	136	23.1	31.9
8	2483.50	44.4 AV	54.0	-9.6	1.48 V	136	12.5	31.9
9	4960.00	49.2 PK	74.0	-24.8	2.26 V	114	46.0	3.2
10	4960.00	35.5 AV	54.0	-18.5	2.26 V	114	32.3	3.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 1M	Channel	CH 0 : 2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Owen Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2325.01	55.9 PK	74.0	-18.1	2.14 H	126	24.0	31.9
2	2325.01	45.3 AV	54.0	-8.7	2.14 H	126	13.4	31.9
3	2337.74	55.5 PK	74.0	-18.5	2.14 H	126	23.5	32.0
4	2337.74	45.9 AV	54.0	-8.1	2.14 H	126	13.9	32.0
5	*2402.00	98.3 PK			2.14 H	126	66.5	31.8
6	*2402.00	97.2 AV			2.14 H	126	65.4	31.8
7	4804.00	48.2 PK	74.0	-25.8	1.27 H	259	45.3	2.9
8	4804.00	34.6 AV	54.0	-19.4	1.27 H	259	31.7	2.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2325.01	58.7 PK	74.0	-15.3	1.87 V	182	26.8	31.9
2	2325.01	49.4 AV	54.0	-4.6	1.87 V	182	17.5	31.9
3	2338.31	58.7 PK	74.0	-15.3	1.87 V	182	26.7	32.0
4	2338.31	49.0 AV	54.0	-5.0	1.87 V	182	17.0	32.0
5	*2402.00	99.8 PK			1.87 V	182	68.0	31.8
6	*2402.00	99.5 AV			1.87 V	182	67.7	31.8
7	4804.00	48.4 PK	74.0	-25.6	2.06 V	154	45.5	2.9
8	4804.00	34.6 AV	54.0	-19.4	2.06 V	154	31.7	2.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 1M	Channel	CH 19 : 2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Owen Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2311.90	55.3 PK	74.0	-18.7	1.37 H	228	23.4	31.9
2	2311.90	43.9 AV	54.0	-10.1	1.37 H	228	12.0	31.9
3	2363.20	56.6 PK	74.0	-17.4	1.37 H	228	24.6	32.0
4	2363.20	48.1 AV	54.0	-5.9	1.37 H	228	16.1	32.0
5	2376.31	56.7 PK	74.0	-17.3	1.37 H	228	24.8	31.9
6	2376.31	46.8 AV	54.0	-7.2	1.37 H	228	14.9	31.9
7	*2440.00	97.8 PK			1.37 H	228	66.0	31.8
8	*2440.00	96.7 AV			1.37 H	228	64.9	31.8
9	4880.00	48.7 PK	74.0	-25.3	1.77 H	162	45.7	3.0
10	4880.00	35.1 AV	54.0	-18.9	1.77 H	162	32.1	3.0

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2312.09	57.1 PK	74.0	-16.9	1.11 V	214	25.2	31.9
2	2312.09	47.7 AV	54.0	-6.3	1.11 V	214	15.8	31.9
3	2363.20	57.7 PK	74.0	-16.3	1.11 V	214	25.7	32.0
4	2363.20	51.1 AV	54.0	-2.9	1.11 V	214	19.1	32.0
5	2375.74	56.9 PK	74.0	-17.1	1.11 V	214	25.0	31.9
6	2375.74	49.3 AV	54.0	-4.7	1.11 V	214	17.4	31.9
7	*2440.00	100.0 PK			1.11 V	214	68.2	31.8
8	*2440.00	98.9 AV			1.11 V	214	67.1	31.8
9	4880.00	48.1 PK	74.0	-25.9	2.17 V	184	45.1	3.0
10	4880.00	34.8 AV	54.0	-19.2	2.17 V	184	31.8	3.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 1M	Channel	CH 39 : 2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Owen Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2351.80	60.3 PK	74.0	-13.7	2.31 H	185	28.3	32.0
2	2351.80	50.5 AV	54.0	-3.5	2.31 H	185	18.5	32.0
3	*2480.00	98.4 PK			2.31 H	185	66.5	31.9
4	*2480.00	97.2 AV			2.31 H	185	65.3	31.9
5	2483.50	55.3 PK	74.0	-18.7	2.31 H	185	23.4	31.9
6	2483.50	44.3 AV	54.0	-9.7	2.31 H	185	12.4	31.9
7	4960.00	48.4 PK	74.0	-25.6	1.45 H	163	45.2	3.2
8	4960.00	34.9 AV	54.0	-19.1	1.45 H	163	31.7	3.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2352.37	58.8 PK	74.0	-15.2	1.48 V	136	26.8	32.0
2	2352.37	48.4 AV	54.0	-5.6	1.48 V	136	16.4	32.0
3	*2480.00	100.5 PK			1.48 V	136	68.6	31.9
4	*2480.00	99.3 AV			1.48 V	136	67.4	31.9
5	2483.50	56.7 PK	74.0	-17.3	1.48 V	136	24.8	31.9
6	2483.50	45.3 AV	54.0	-8.7	1.48 V	136	13.4	31.9
7	4960.00	48.9 PK	74.0	-25.1	2.26 V	114	45.7	3.2
8	4960.00	35.3 AV	54.0	-18.7	2.26 V	114	32.1	3.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 2M	Channel	CH 0 : 2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Owen Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2325.20	57.8 PK	74.0	-16.2	2.14 H	126	25.9	31.9
2	2325.20	47.7 AV	54.0	-6.3	2.14 H	126	15.8	31.9
3	2338.12	57.0 PK	74.0	-17.0	2.14 H	126	25.0	32.0
4	2338.12	46.9 AV	54.0	-7.1	2.14 H	126	14.9	32.0
5	*2402.00	97.1 PK			2.14 H	126	65.3	31.8
6	*2402.00	94.0 AV			2.14 H	126	62.2	31.8
7	4804.00	48.2 PK	74.0	-25.8	1.27 H	259	45.3	2.9
8	4804.00	34.6 AV	54.0	-19.4	1.27 H	259	31.7	2.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2324.80	57.8 PK	74.0	-16.2	1.87 V	182	25.9	31.9
2	2324.80	48.3 AV	54.0	-5.7	1.87 V	182	16.4	31.9
3	2337.74	58.0 PK	74.0	-16.0	1.87 V	182	26.0	32.0
4	2337.74	47.3 AV	54.0	-6.7	1.87 V	182	15.3	32.0
5	*2402.00	100.7 PK			1.87 V	182	68.9	31.8
6	*2402.00	97.7 AV			1.87 V	182	65.9	31.8
7	4804.00	48.7 PK	74.0	-25.3	2.06 V	154	45.8	2.9
8	4804.00	35.0 AV	54.0	-19.0	2.06 V	154	32.1	2.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 2M	Channel	CH 19 : 2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Owen Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2311.52	58.7 PK	74.0	-15.3	1.37 H	228	26.8	31.9
2	2311.52	50.8 AV	54.0	-3.2	1.37 H	228	18.9	31.9
3	2363.01	56.3 PK	74.0	-17.7	1.37 H	228	24.3	32.0
4	2363.01	47.0 AV	54.0	-7.0	1.37 H	228	15.0	32.0
5	2375.36	56.9 PK	74.0	-17.1	1.37 H	228	25.0	31.9
6	2375.36	46.6 AV	54.0	-7.4	1.37 H	228	14.7	31.9
7	*2440.00	98.3 PK			1.37 H	228	66.5	31.8
8	*2440.00	95.3 AV			1.37 H	228	63.5	31.8
9	4880.00	48.3 PK	74.0	-25.7	1.77 H	162	45.3	3.0
10	4880.00	34.8 AV	54.0	-19.2	1.77 H	162	31.8	3.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2312.00	59.3 PK	74.0	-14.7	1.11 V	214	27.4	31.9
2	2312.00	50.9 AV	54.0	-3.1	1.11 V	214	19.0	31.9
3	2363.58	58.5 PK	74.0	-15.5	1.11 V	214	26.5	32.0
4	2363.58	49.1 AV	54.0	-4.9	1.11 V	214	17.1	32.0
5	2376.50	57.8 PK	74.0	-16.2	1.11 V	214	25.9	31.9
6	2376.50	48.6 AV	54.0	-5.4	1.11 V	214	16.7	31.9
7	*2440.00	101.1 PK			1.11 V	214	69.3	31.8
8	*2440.00	98.0 AV			1.11 V	214	66.2	31.8
9	4880.00	48.6 PK	74.0	-25.4	2.17 V	184	45.6	3.0
10	4880.00	35.1 AV	54.0	-18.9	2.17 V	184	32.1	3.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT-LE 2M	Channel	CH 39 : 2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Owen Lee		


Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2326.53	56.3 PK	74.0	-17.7	2.31 H	185	24.4	31.9
2	2326.53	45.9 AV	54.0	-8.1	2.31 H	185	14.0	31.9
3	2351.80	58.5 PK	74.0	-15.5	2.31 H	185	26.5	32.0
4	2351.80	49.5 AV	54.0	-4.5	2.31 H	185	17.5	32.0
5	*2480.00	99.7 PK			2.31 H	185	67.8	31.9
6	*2480.00	96.3 AV			2.31 H	185	64.4	31.9
7	2483.50	55.7 PK	74.0	-18.3	2.31 H	185	23.8	31.9
8	2483.50	44.3 AV	54.0	-9.7	2.31 H	185	12.4	31.9
9	4960.00	48.7 PK	74.0	-25.3	1.45 H	163	45.5	3.2
10	4960.00	35.2 AV	54.0	-18.8	1.45 H	163	32.0	3.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2325.58	56.5 PK	74.0	-17.5	1.48 V	136	24.6	31.9
2	2325.58	45.7 AV	54.0	-8.3	1.48 V	136	13.8	31.9
3	2352.40	58.7 PK	74.0	-15.3	1.48 V	136	26.7	32.0
4	2352.40	50.2 AV	54.0	-3.8	1.48 V	136	18.2	32.0
5	*2480.00	101.9 PK			1.48 V	136	70.0	31.9
6	*2480.00	98.8 AV			1.48 V	136	66.9	31.9
7	2483.50	55.7 PK	74.0	-18.3	1.48 V	136	23.8	31.9
8	2483.50	44.6 AV	54.0	-9.4	1.48 V	136	12.7	31.9
9	4960.00	49.1 PK	74.0	-24.9	2.26 V	114	45.9	3.2
10	4960.00	35.5 AV	54.0	-18.5	2.26 V	114	32.3	3.2


Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.


Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	--------------------	-------------------------------	--

BT-LE 125K Channel 0




BT-LE 125K Channel 39


Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
-----------------	--------------------	-------------------------------	--

BT-LE 500K Channel 0




BT-LE 500K Channel 39


Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
-----------------	--------------------	-------------------------------	--

BT-LE 1M Channel 0




BT-LE 1M Channel 39


Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
-----------------	--------------------	-------------------------------	--

BT-LE 2M Channel 0




BT-LE 2M Channel 39


Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)

8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---