



Radio Test Report

FCC ID: S9E-73355046

Report No.	:	TBR-C-202506-0272-83	
Applicant	:	Trimble Inc.	
Equipment Under Test (EUT)			
EUT Name	:	HCB2	
Model No.	:	73355046	
Series Model No.	:	N/A	
Brand Name	:	Trimble	
Sample ID	:	HC-C-202506-0272-01-01&HC-C-202506-0272-02-01	
Receipt Date	:	2025-07-23	
Test Date	:	2025-07-23 to 2026-07-22	
Issue Date	:	2026-07-22	
Standards	:	FCC Part 15 Subpart E 15.407	
Test Method	:	ANSI C63.10: 2020+Cor.1:2023+C63.10a: 2024+Errata to C63.10a: 2024 KDB 789033 D02 General UNII Test Procedures New Rules v02r01 KDB 662911 D01 Multiple Transmitter Output v02r01	
Conclusions	:	PASS	
		In the configuration tested, the EUT complied with the standards specified above.	
Test By	:	Gold. zhang	
Reviewed By	:	Henry huang	
Approved By	:	IVAN SU	
This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.			

Contents

CONTENTS	2
1. GENERAL INFORMATION ABOUT EUT	5
1.1 Client Information	5
1.2 General Description of EUT (Equipment Under Test)	5
1.3 Block Diagram Showing the Configuration of System Tested.....	7
1.4 Description of Support Units	7
1.5 Description of Test Mode	8
1.6 Description of Test Software Setting	10
1.7 Measurement Uncertainty	12
1.8 Test Facility.....	13
2. TEST SUMMARY.....	14
3. TEST SOFTWARE	14
4. TEST EQUIPMENT AND TEST SITE	15
5. CONDUCTED EMISSION TEST	17
5.1 Test Standard and Limit	17
5.2 Test Setup.....	17
5.3 Test Procedure	17
5.4 Deviation From Test Standard.....	17
5.5 EUT Operating Mode	18
5.6 Test Data.....	18
6. RADIATED AND CONDUCTED UNWANTED EMISSIONS.....	19
6.1 Test Standard and Limit	19
6.2 Test Setup.....	21
6.3 Test Procedure	22
6.4 Deviation From Test Standard.....	23
6.5 EUT Operating Mode	23
6.6 Test Data.....	23
7. RESTRICTED BANDS REQUIREMENT	24
7.1 Test Standard and Limit	24
7.2 Test Setup.....	26
7.3 Test Procedure	26
7.4 Deviation From Test Standard.....	27
7.5 EUT Operating Mode	27
7.6 Test Data.....	27
8. BANDWIDTH TEST.....	28
8.1 Test Standard and Limit	28
8.2 Test Setup.....	28
8.3 Test Procedure	28
8.4 Deviation From Test Standard.....	29
8.5 EUT Operating Mode	30
8.6 Test Data.....	30



9.	MAXIMUM CONDUCTED OUTPUT POWER.....	31
9.1	Test Standard and Limit	31
9.2	Test Setup.....	31
9.3	Test Procedure	31
9.4	Deviation From Test Standard.....	32
9.5	EUT Operating Mode	32
9.6	Test Data.....	32
10.	POWER SPECTRAL DENSITY TEST	33
10.1	Test Standard and Limit	33
10.2	Test Setup	33
10.3	Test Procedure	33
10.4	Deviation From Test Standard	34
10.5	Antenna Connected Construction.....	34
10.6	Test Data	34
11.	FREQUENCY STABILITY.....	35
11.1	Test Standard and Limit	35
11.2	Test Setup	35
11.3	Test Procedure	35
11.4	Deviation From Test Standard	36
11.5	Antenna Connected Construction.....	36
11.6	Test Data	36
12.	DUTY CYCLE.....	37
12.1	Test Standard and Limit	37
12.2	Test Setup	37
12.3	Test Procedure	37
12.4	Deviation From Test Standard	37
12.5	Antenna Connected Construction.....	37
12.6	Test Data	37
13.	ANTENNA REQUIREMENT	38
13.1	Test Standard and Limit	38
13.2	Deviation From Test Standard	38
13.3	Antenna Connected Construction.....	38
13.4	Test Data	38
ATTACHMENT A-- CONDUCTED EMISSION TEST DATA		39
ATTACHMENT B--UNWANTED EMISSIONS DATA		41
ATTACHMENT C-- RESTRICTED BANDS REQUIREMENT TEST DATA.....		91



Revision History

Report No.	Version	Description	Issued Date
TBR-C-202506-0272-83	Rev.01	Initial issue of report	2026-07-22



1. General Information about EUT

1.1 Client Information

Applicant	:	Trimble Inc.
Address	:	5475 Kellenburger Rd, Dayton, OH 45424
Manufacturer	:	Trimble Inc.
Address	:	5475 Kellenburger Rd, Dayton, OH 45424

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	HCB2			
Models No.	:	73355046			
Model Different	:	N/A			
Product Description	:	Operation Frequency: U-NII-1: 5180MHz~5240MHz, U-NII-2A: 5260MHz~5320MHz U-NII-2C: 5500MHz~5720MHz, U-NII-3: 5745MHz~5825MHz			
		Antenna Designation:	FPC Ant.	Gain-Ant.1	Gain-Ant.2
			U-NII-1	5.5dBi	5.5dBi
			U-NII-2A	5.5dBi	5.5dBi
			U-NII-2C	5.5dBi	5.5dBi
		U-NII-3	5.5dBi	5.5dBi	
Modulation Type:	802.11a: OFDM (QPSK, BPSK, 16QAM, 64QAM) 802.11n: OFDM (QPSK, BPSK, 16QAM, 64QAM) 802.11ac: OFDM (QPSK, BPSK, 16QAM, 64QAM, 256QAM)				
Power Rating	:	DC 5V			
Software Version	:	13.35.369			
Hardware Version	:	Rev.E			
Remark:					
(1)The antenna gain provided by the applicant, the verified for the RF conduction test provided by TOBY test lab.					
(2)The above antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.					
(3)For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.					



(4) Channel List:

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5180~5240MHz (U-NII-1)	36	5180 MHz	44	5220 MHz
	38	5190 MHz	46	5230 MHz
	40	5200 MHz	48	5240 MHz
	42	5210 MHz		

For 20 MHz Bandwidth, use channel 36, 40, 44, 48. For 40 MHz Bandwidth, use channel 38, 46.

For 80 MHz Bandwidth, use channel 42.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5260~5320 MHz (U-NII-2A)	52	5260 MHz	60	5300 MHz
	54	5270 MHz	62	5310MHz
	56	5280MHz	64	5320 MHz
	58	5290MHz		

For 20 MHz Bandwidth, use channel 52, 56, 60, 64. For 40 MHz Bandwidth, use channel 54, 62.

For 80 MHz Bandwidth, use channel 58.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5500~5720 MHz (U-NII-2C)	100	5500 MHz	124	5620 MHz
	102	5510 MHz	126	5630 MHz
	104	5520 MHz	128	5640 MHz
	106	5530 MHz	132	5660 MHz
	108	5540 MHz	134	5670 MHz
	110	5550 MHz	136	5680 MHz
	112	5560 MHz	138	5690 MHz
	116	5580 MHz	140	5700 MHz
	118	5590 MHz	142	5710 MHz
	120	5600 MHz	144	5720 MHz
	122	5610 MHz		

For 20 MHz Bandwidth, use channel 100, 104, 108, 112, 116, 120, 124, 128, 132, 136, 140, 144

For 40 MHz Bandwidth, use channel 102, 110, 118, 126, 134, 142

For 80 MHz Bandwidth, use channel 106, 122, 138

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5745~5825MHz (U-NII-3)	149	5745 MHz	157	5785 MHz
	151	5755 MHz	159	5795 MHz
	153	5765 MHz	161	5805 MHz
	155	5775 MHz	165	5825 MHz


For 20 MHz Bandwidth, use channel 149, 153, 157, 161, 165. For 40 MHz Bandwidth, use channel 151, 159.

For 80 MHz Bandwidth, use channel 155.




1.3 Block Diagram Showing the Configuration of System Tested


AC Power Line conducted emission



Radiated Test



Conducted Measurements Test



1.4 Description of Support Units

Equipment Information				
Name	Model	S/N	Manufacturer	Used “√”
Notebook	Inspiron 5493	-----	DELL	√
Adapter	CD112	-----	UGREEN	√



1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test(AC POWER)		
Final Test Mode		Description
Mode 1		TX a Mode(5180MHz)
For Radiated Test Below 1GHz		
Final Test Mode		Description
Mode 1		TX a Mode(5180MHz)
For Radiated Above 1GHz and RF Conducted Test		
Test Band	Final Test Mode	Description
U-NII-1	Mode 2	TX Mode 802.11a Mode Channel 36/40/48
	Mode 3	TX Mode 802.11n(HT20) Mode Channel 36/40/48
	Mode 4	TX Mode 802.11ac(VHT20) Mode Channel 36/40/48
	Mode 5	TX Mode 802.11n(HT40) Mode Channel 38/46
	Mode 6	TX Mode 802.11ac(VHT40) Mode Channel 38/46
	Mode 7	TX Mode 802.11ac(VHT80) Mode Channel 42
U-NII-2A	Mode 8	TX Mode 802.11a Mode Channel 52/56/64
	Mode 9	TX Mode 802.11n(HT20) Mode Channel 52/56/64
	Mode 10	TX Mode 802.11ac(VHT20) Mode Channel 52/56/64
	Mode 11	TX Mode 802.11n(HT40) Mode Channel 54/62
	Mode 12	TX Mode 802.11ac(VHT40) Mode Channel 54/62
	Mode 13	TX Mode 802.11ac(VHT80) Mode Channel 58
U-NII-2C	Mode 14	TX Mode 802.11a Mode Channel 100/116/144
	Mode 15	TX Mode 802.11n(HT20) Mode Channel 100/116/144
	Mode 16	TX Mode 802.11ac(VHT20) Mode Channel 100/116/144
	Mode 17	TX Mode 802.11n(HT40) Mode Channel 102/118/142
	Mode 18	TX Mode 802.11ac(VHT40) Mode Channel 102/118/142
	Mode 19	TX Mode 802.11ac(VHT80) Mode Channel 106/122/138
U-NII-3	Mode 20	TX Mode 802.11a Mode Channel 149/157/165
	Mode 21	TX Mode 802.11n(HT20) Mode Channel 149/157/165
	Mode 22	TX Mode 802.11ac(VHT20) Mode Channel 149/157/165
	Mode 23	TX Mode 802.11n(HT40) Mode Channel 151/159
	Mode 24	TX Mode 802.11ac(VHT40) Mode Channel 151/159
	Mode 25	TX Mode 802.11ac(VHT80) Mode Channel 155

Note: Report on two types of antennas: FPC Antenna (5G Ant1 5.5dBi, 5G Ant2 5.5dBi) and Dipole Antenna (5G Ant1 5.0dBi, 5G Ant2 5.0dBi). FPC Antenna. Above 1GHz and Restricted Bands Data, only the worst mode AC 20M data is evaluated.

Dipole Antenna. Above 1GHz only the worst mode AC 20M 40M 80M data is evaluated.



Note:

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.

According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:

802.11a Mode: OFDM (6 Mbps)

802.11n (HT20) Mode: MCS 8

802.11n (HT40) Mode: MCS 8

802.11ac(VHT20) Mode: MCS 0/ Nss1

802.11ac(VHT40) Mode: MCS 0/ Nss1

802.11ac(VHT80) Mode: MCS 0/ Nss1

- (2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.
- (3) The EUT is considered a Mobile unit; in normal use it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.



1.6 Description of Test Software Setting

During testing channel & Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of RF setting.

Test Software: Terminal command			
U-NII-1			
Mode	Frequency (MHz)	Parameters	
		Ant.1	Ant.2
802.11a	5180	16	16
	5200	17	17
	5240	16	16
802.11n(HT20)	5180	10	10
	5200	11	11
	5240	10	10
802.11ac(VHT20)	5180	10	10
	5200	11	11
	5240	10	10
802.11n(HT40)	5190	10	10
	5230	13	13
802.11ac(VHT40)	5190	10	10
	5230	10	10
802.11ac(VHT80)	5210	10	10
U-NII-2A			
Mode	Frequency (MHz)	Parameters	
		Ant.1	Ant.2
802.11a	5260	14	14
	5280	17	18
	5320	14	14
802.11n(HT20)	5260	10	10
	5280	18	18
	5320	10	10
802.11ac(VHT20)	5260	10	10
	5280	18	18
	5320	10	10
802.11n(HT40)	5270	18	18
	5310	10	10
802.11ac(VHT40)	5270	10	10
	5310	10	10
802.11ac(VHT80)	5290	10	10



U-NII-2C			
Mode	Frequency (MHz)	Parameters	
		Ant.1	Ant.2
802.11a	5500	16	16
	5580	19	19
	5720	16	16
802.11n(HT20)	5500	12	12
	5580	18	18
	5720	12	12
802.11ac(VHT20)	5500	12	12
	5580	18	18
	5720	12	12
802.11n(HT40)	5510	12	12
	5590	19	19
	5710	12	12
802.11ac(VHT40)	5510	12	12
	5590	19	19
	5710	12	12
802.11ac(VHT80)	5530	12	12
	5610	12	12
	5690	12	12



U-NII-3			
Mode	Frequency (MHz)	Parameters	
		Ant.1	Ant.2
802.11a	5745	19	18
	5785	20	20
	5825	19	18
802.11n(HT20)	5745	12	12
	5785	18	18
	5825	12	12
802.11ac(VHT20)	5745	12	12
	5785	18	18
	5825	12	12
802.11n(HT40)	5755	12	12
	5795	12	12
802.11ac(VHT40)	5755	12	12
	5795	12	12
802.11ac(VHT80)	5775	12	12
Note: 802.11n/ac Support MIMO.			

1.7 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (U_{Lab})
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	± 3.50 dB ± 3.10 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	± 4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	± 4.50 dB
Radiated Emission	Level Accuracy: Above 1000MHz	± 4.20 dB
RF Power-Conducted	---	± 0.95 dB
Power Spectral Density-Conducted	---	± 3 dB
Occupied Bandwidth	---	$\pm 3.8\%$
Unwanted Emission-Conducted	---	± 2.72 dB
Temperature	---	$\pm 0.6^{\circ}\text{C}$
Humidity	---	$\pm 4\%$
Supply voltages	---	$\pm 2\%$



1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1/F., Building 6, Rundongsheng Industrial Zone, Longzhu, Xixiang, Bao'an District, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

A2LA Certificate No.: 4750.01

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.FCC Accredited Test Site Number: 854351. Designation Number: CN1223.

IC Registration No.: (11950A)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A. CAB identifier: CN0056.



2. Test Summary

Standard Section		Test Item	Test Sample(s)	Judgment	Remark
FCC	/				
FCC 15.207(a)	/	Conducted Emission	HC-C-202506-0272-02-01	PASS	N/A
FCC 15.209 & 15.407(b)	/	Radiated Unwanted Emissions	HC-C-202506-0272-02-01	PASS	N/A
FCC 15.203	/	Antenna Requirement	HC-C-202506-0272-01-01	PASS	N/A
FCC 15.407(a)	/	-26dB Emission Bandwidth	HC-C-202506-0272-01-01	PASS	N/A
FCC 15.407(a)	/	99% Occupied Bandwidth	HC-C-202506-0272-01-01	PASS	N/A
FCC 15.407(e)	/	-6dB Min Emission Bandwidth	HC-C-202506-0272-01-01	PASS	N/A
FCC 15.407(a)	/	Maximum Conducted Output Power	HC-C-202506-0272-01-01	PASS	N/A
FCC 15.407(a)	/	Power Spectral Density	HC-C-202506-0272-01-01	PASS	N/A
FCC 15.407(b)& 15.205	/	Emissions in Restricted Bands	HC-C-202506-0272-02-01	PASS	N/A
FCC 15.407(b)&15.209	/	Conducted Unwanted Emissions	HC-C-202506-0272-02-01	PASS	N/A
FCC 15.407(g)	/	Frequency Stability	HC-C-202506-0272-01-01	PASS	N/A
/	/	On Time and Duty Cycle	HC-C-202506-0272-01-01	/	N/A

Note: N/A is an abbreviation for Not Applicable.

3. Test Software

Test Item	Test Software	Manufacturer	Version No.
Conducted Emission	EZ-EMC	EZ	CDI-03A2
Radiation Emission	EZ-EMC	EZ	FA-03A2RE
Radiation Emission	EZ-EMC	EZ	FA-03A2RE+
RF Conducted Measurement	MTS-8310	MWRFTest	V2.0.0.0
RF Test System	JS1120	Tonscend	V3.2.22



4. Test Equipment and Test Site

Test Site				
No.	Test Site	Manufacturer	Specification	Used
TB-EMCSR001	Shielding Chamber #1	YIHENG	7.5*4.0*3.0 (m)	√
TB-EMCSR002	Shielding Chamber #2	YIHENG	8.0*4.0*3.0 (m)	X
TB-EMCCA001	3m Anechoic Chamber #A	ETS	9.0*6.0*6.0 (m)	X
TB-EMCCB002	3m Anechoic Chamber #B	YIHENG	9.0*6.0*6.0 (m)	√

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jun. 16, 2025	Jun. 15, 2026
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jun. 16, 2025	Jun. 15, 2026
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jun. 16, 2025	Jun. 15, 2026
LISN	Rohde & Schwarz	ENV216	101131	Jun. 16, 2025	Jun. 15, 2026

Radiation Emission Test(B Site)					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100060	Aug. 29, 2024	Aug. 28, 2025
Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102197	Jun. 16, 2025	Jun. 15, 2026
EMI Test Receiver	Rohde & Schwarz	ESU-8	100472/008	Feb. 20, 2025	Feb.19, 2026
Bilog Antenna	SCHWARZBECK	VULB 9168	1225	Nov. 13, 2023	Nov. 12, 2025
Horn Antenna	SCHWARZBECK	BBHA 9120 D	2463	Jun. 14, 2024	Jun. 13, 2026
Horn Antenna	SCHWARZBECK	BBHA 9170	1118	Feb. 27, 2024	Feb.26, 2026
Loop Antenna	SCHWARZBECK	FMZB 1519 B	1519B-059	Jun. 14, 2024	Jun. 13, 2026
HF Amplifier	Tonscend	TAP9E6343	AP21C806117	Aug. 29, 2024	Aug. 28, 2025
HF Amplifier	Tonscend	TAP051845	AP21C806141	Aug. 29, 2024	Aug. 28, 2025
HF Amplifier	Tonscend	TAP0184050	AP21C806129	Aug. 29, 2024	Aug. 28, 2025
Highpass Filter	CD	HPM-6.4/18G	---	N/A	N/A
Highpass Filter	CD	HPM-2.8/18G	---	N/A	N/A
Highpass Filter	XINBO	XBLBQ-HTA67(8-25G)	22052702-1	N/A	N/A

Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102197	Jun. 16, 2025	Jun. 15, 2026
MXA Signal Analyzer	KEYSIGHT	N9020B	MY60110172	Aug. 29, 2024	Aug. 28, 2025
MXA Signal Analyzer	Agilent	N9020A	MY47380425	Aug. 29, 2024	Aug. 28, 2025
RF Power Sensor	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO26	Aug. 29, 2024	Aug. 28, 2025
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO29	Aug. 29, 2024	Aug. 28, 2025
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO31	Aug. 29, 2024	Aug. 28, 2025
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO33	Aug. 29, 2024	Aug. 28, 2025
RF Control Unit	Tonsced	JS0806-2	21F8060439	Aug. 29, 2024	Aug. 28, 2025
Attenuator	YINSAIGE	DC-18G 10dB	DC18G	N/A	N/A
Attenuator	YINSAIGE	DC-40G 10dB	DC40G	N/A	N/A



Conducted Emission Test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	May. 15, 2026	May. 14, 2027
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	May. 15, 2026	May. 14, 2027
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	May. 15, 2026	May. 14, 2027
LISN	Rohde & Schwarz	ENV216	101131	May. 15, 2026	May. 14, 2027

Radiation Emission Test(B Site)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100060	Aug. 27, 2025	Aug. 26, 2026
Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102197	May. 15, 2026	May. 14, 2027
EMI Test Receiver	Rohde & Schwarz	ESU-8	100472/008	Jan. 30, 2026	Jan. 29, 2027
Bilog Antenna	SCHWARZBECK	VULB 9168	1225	Oct. 18, 2025	Oct. 17, 2027
Horn Antenna	SCHWARZBECK	BBHA 9120 D	2463	May. 15, 2026	May. 14, 2027
Horn Antenna	SCHWARZBECK	BBHA 9170	1118	Jan. 31, 2026	Jan. 30, 2028
HF Amplifier	Tonscend	TAP9E6343	AP21C806117	May. 15, 2026	May. 14, 2027
HF Amplifier	Tonscend	TAP051845	AP21C806141	Aug. 27, 2025	Aug. 26, 2026
HF Amplifier	Tonscend	TAP0184050	AP21C806129	Aug. 27, 2025	Aug. 26, 2026
Pre-amplifier	HP	8449B	3008A00849	Feb. 02, 2026	Feb.01, 2027
Highpass Filter	CD	HPM-6.4/18G	---	N/A	N/A
Highpass Filter	CD	HPM-2.8/18G	---	N/A	N/A
Highpass Filter	XINBO	XBLBQ-HTA67(8-25G)	22052702-1	N/A	N/A

Antenna Conducted Emission

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102197	May. 15, 2026	May. 14, 2027
MXA Signal Analyzer	KEYSIGHT	N9020B	MY60110172	Aug. 27, 2025	Aug. 26, 2026
MXA Signal Analyzer	Agilent	N9020A	MY47380425	Aug. 27, 2025	Aug. 26, 2026
Vector Signal Generator	Agilent	N5182A	MY50141294	Aug. 27, 2025	Aug. 26, 2026
Analog Signal Generator	Agilent	N5181A	MY48180463	Aug. 27, 2025	Aug. 26, 2026
Vector Signal Generator	KEYSIGHT	N5182B	MY59101429	Aug. 27, 2025	Aug. 26, 2026
Analog Signal Generator	KEYSIGHT	N5173B	MY61252685	Aug. 27, 2025	Aug. 26, 2026
RF Control Unit	Tonsced	JS0806-2	21F8060439	Aug. 27, 2025	Aug. 26, 2026
Power Control Box	Tonsced	JS0806-4ADC	21C8060387	N/A	N/A
RF Power Sensor	DARE!! Instruments	RadiPowerRPR3 006W	17I00015SNO26	Aug. 27, 2025	Aug. 26, 2026
			17I00015SNO29	Aug. 27, 2025	Aug. 26, 2026
			17I00015SNO31	Aug. 27, 2025	Aug. 26, 2026
			17I00015SNO33	Aug. 27, 2025	Aug. 26, 2026
Attenuator	YINSAIGE	DC-18G 10dB	DC18G	N/A	N/A
Attenuator	YINSAIGE	DC-40G 10dB	DC40G	N/A	N/A



5. Conducted Emission Test

5.1 Test Standard and Limit

5.1.1 Test Standard

RSS-Gen 8.8

FCC Part 15.207

5.1.2 Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50


Notes:

(1) *Decreasing linearly with logarithm of the frequency.

(2) The lower limit shall apply at the transition frequencies.

(3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.2 Test Setup



5.3 Test Procedure

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- The bandwidth of EMI test receiver is set at 9 kHz, and the test frequency band is from 0.15MHz to 30MHz.

5.4 Deviation From Test Standard

No deviation



5.5 EUT Operating Mode

Please refer to the description of test mode.

5.6 Test Data

Please refer to the Attachment A inside test report.



6. Radiated and Conducted Unwanted Emissions

6.1 Test Standard and Limit

6.1.1 Test Standard

RSS-Gen 8.9 & RSS 247 (7.3.1.3&7.3.2.3&7.3.3.3&7.3.4.4)

FCC Part 15.209 & FCC Part 15.407(b)

6.1.2 Test Limit

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table:

General field strength limits at frequencies Below 30MHz		
Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30

Note: 1, The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

General field strength limits at frequencies above 30 MHz		
Frequency (MHz)	Field strength (μV/m at 3 m)	Measurement Distance (meters)
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

General field strength limits at frequencies Above 1000MHz		
Frequency (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
Above 1000	74	54

Note:

(1) The tighter limit applies at the band edges.

(2) Emission Level(dBuV/m)=20log Emission Level(μV/m)

(3) For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Limits of unwanted emission out of the restricted bands

Frequency (MHz)	EIRP Limits (dBm)	Equivalent Field Strength at 3m (dBuV/m)
5150~5250	-27	68.3
5250~5350	-27	68.3
5470~5725	-27	68.3
5725~5825	-27(Note 2)	68.3
	10(Note 2)	105.3
	15.6(Note 2)	110.9
	27(Note 2)	122.3

NOTE:

1, The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \text{ uV/m, where P is the eirp (Watts)}$$



2, According to FCC 16-24, All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.

3, For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

IC Limit:

For transmitters with operating frequencies in the band 5150-5250 MHz:

- a. all emissions outside the 5150-5350 MHz band shall not exceed -27 dBm/MHz peak e.i.r.p. spectral density;
- b. any unwanted emissions that falls between the upper edge of the 26 dB bandwidth and 5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth.
- c. if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing DFS (see section 7.3.6) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

all emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz peak e.i.r.p spectral density.

all emissions inside the band 5150-5250 MHz shall either:

1. not exceed -27 dBm/MHz peak e.i.r.p spectral density, or
2. comply with the power spectral density for operation in section 7.3.1.2.

Equipment operating in the bands 5470-5725 MHz shall comply with the following unwanted emission limits:

- a. for devices with fundamental emissions fully contained within the 5470-5725 MHz band, all unwanted emissions outside the band 5470-5725 MHz shall not exceed -27 dBm/MHz peak e.i.r.p. spectral density.
- b. for devices with bandwidth overlapping the band edge of 5725 MHz, all unwanted emissions shall not exceed -27 dBm/MHz peak e.i.r.p. spectral density at 5850 MHz instead of 5725 MHz.


Equipment operating in the band 5725-5850 MHz shall comply with the following peak e.i.r.p. spectral density limits:

- a. 27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 dBm/MHz at 5 MHz above or below the band edges;
- b. 15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges;
- c. 10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges; and
- d. -27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.




6.2 Test Setup


Radiated measurement



Below 30MHz Test Setup




Below 1000MHz Test Setup



Above 1GHz Test Setup Conducted measurement





6.3 Test Procedure

---Radiated measurement

● The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.

● Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.

● The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.

● The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

● If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Below 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.

● Testing frequency range 30MHz-1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection. Testing frequency range 9KHz-150Hz the measuring instrument use VBW=200Hz with Quasi-peak detection. Testing frequency range 9KHz-30MHz the measuring instrument use VBW=9kHz with Quasi-peak detection.

● Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=3 MHz with Peak Detector for Average Values.

● For the actual test configuration, please see the test setup photo.

--- Conducted measurement

●Reference level measurement

Establish a reference level by using the following procedure:

- Set instrument center frequency to channel center frequency.
- Set the span to ≥ 1.5 times the bandwidth.
- Set the RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

●Emission level measurement

Establish an emission level by using the following procedure:

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.



- d) Detector = peak.
 - e) Sweep time = auto couple.
 - f) Trace mode = max hold.
 - g) Allow trace to fully stabilize.
 - h) Use the peak marker function to determine the maximum amplitude level.
- Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

6.4 Deviation From Test Standard

No deviation

6.5 EUT Operating Mode

Please refer to the description of test mode.

6.6 Test Data

Radiated measurement please refer to the Attachment B inside test report.

Conducted measurement please refer to the external appendix report of 5G Wi-Fi.



7. Restricted Bands Requirement

7.1 Test Standard and Limit

7.1.1 Test Standard

RSS-Gen 8.10 & RSS 247 (7.3.1.3&7.3.2.3&7.3.3.3&7.3.4.4)

FCC Part 15.209 & FCC Part 15.407(b)

7.1.2 Test Limit

FCC Limit:

Frequency (MHz)	EIRP Limits (dBm)	Equivalent Field Strength at 3m (dBuV/m)
5150~5250	-27	68.3
5250~5350	-27	68.3
5470~5725	-27	68.3
5725~5825	-27(Note 2)	68.3
	10(Note 2)	105.3
	15.6(Note 2)	110.9
	27(Note 2)	122.3

NOTE:

1, The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \text{ uV/m, where P is the eirp (Watts)}$$

2, According to FCC 16-24, All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.

Note: According the ANSI C63.10 11.12.2 antenna-port conducted measurements may also be used as an alternative to radiated measurements for determining compliance in the restricted frequency bands requirements. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case emissions is required.



IC Limit:

For transmitters with operating frequencies in the band 5150-5250 MHz:

- d. all emissions outside the 5150-5350 MHz band shall not exceed -27 dBm/MHz peak e.i.r.p. spectral density;
- e. any unwanted emissions that falls between the upper edge of the 26 dB bandwidth and 5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth.
- f. if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing DFS (see section 7.3.6) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

all emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz peak e.i.r.p spectral density.

all emissions inside the band 5150-5250 MHz shall either:

- 1. not exceed -27 dBm/MHz peak e.i.r.p spectral density, or
- 2. comply with the power spectral density for operation in section 7.3.1.2.

Equipment operating in the bands 5470-5725 MHz shall comply with the following unwanted emission limits:

- c. for devices with fundamental emissions fully contained within the 5470-5725 MHz band, all unwanted emissions outside the band 5470-5725 MHz shall not exceed -27 dBm/MHz peak e.i.r.p. spectral density.
- d. for devices with bandwidth overlapping the band edge of 5725 MHz, all unwanted emissions shall not exceed -27 dBm/MHz peak e.i.r.p. spectral density at 5850 MHz instead of 5725 MHz.


Equipment operating in the band 5725-5850 MHz shall comply with the following peak e.i.r.p. spectral density limits:

- a. 27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 dBm/MHz at 5 MHz above or below the band edges;
- b. 15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges;
- c. 10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges; and
- d. -27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.




7.2 Test Setup

Radiated measurement



Conducted measurement



7.3 Test Procedure

---Radiated measurement

- Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- The Peak Value and average value both need to comply with applicable limit above 1 GHz.
- Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=3 MHz with Peak Detector for Average Values.
- For the actual test configuration, please see the test setup photo.



--- Conducted measurement

- a) Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 11.12.2.3 through 11.12.2.5 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP (see 11.12.2.6 for guidance on determining the applicable antenna gain).
- c) Add the appropriate maximum ground reflection factor to the EIRP (6 dB for frequencies ≤ 30 MHz; 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive; and 0 dB for frequencies > 1000 MHz).
- d) For MIMO devices, measure the power of each chain and sum the EIRP of all chains in linear terms (i.e., watts and mW).
- e) Convert the resultant EIRP to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20 \log d + 104.8$$

where

E is the electric field strength in dBuV/m

EIRP is the equivalent isotropically radiated power in dBm

d is the specified measurement distance in m

- f) Compare the resultant electric field strength level with the applicable regulatory limit.

- g) Perform the radiated spurious emission test.

7.4 Deviation From Test Standard

No deviation

7.5 EUT Operating Mode

Please refer to the description of test mode.

7.6 Test Data

Please refer to the Attachment C inside test report.



8. Bandwidth Test

8.1 Test Standard and Limit


8.1.1 Test Standard

RSS Gen 6.7&RSS 247 (7.3.1.3&7.3.2.3&7.3.3.3&7.3.4.4)& RSS 247 (7.3.4.2)
FCC Part 15.407(a) & FCC Part 15.407(e)

8.1.2 Test Limit

Test Item	Limit	Frequency Range (MHz)
26 Bandwidth	N/A	5150~5250
		5250~5350
		5500~5725
6 dB Bandwidth	>500kHz	5725~5850
99% Bandwidth	N/A	5150~5250
		5250~5350
		5500~5725
		5725~5850

8.2 Test Setup



8.3 Test Procedure

---Emission bandwidth

● The procedure for this method is as follows:

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the peak of the emission.

Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

NOTE—The automatic bandwidth measurement capability of a spectrum analyzer or an EMI receiver may be employed if it implements the functionality described in the preceding items.

--- bandwidth



● The steps for the first option are as follows:

- a) Set RBW = 100 kHz.
- b) Set the VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

---occupied bandwidth

● The occupied bandwidth is the frequency bandwidth such that, below its lower and

above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

8.4 Deviation From Test Standard

No deviation



8.5 EUT Operating Mode

Please refer to the description of test mode.

8.6 Test Data

Please refer to the external appendix report of 5G Wi-Fi.



9. Maximum Conducted Output Power

9.1 Test Standard and Limit

9.1.1 Test Standard


RSS 247 (6.2.11&6.2.2.1&6.2.3.1&6.2.4.1)

FCC Part 15.407(a)

9.1.2 Test Limit

RSS-247				
Limit	Frequency Range(MHz)			
	5150~5250	5250~5350	5500~5725	5725~5850
Max Conducted TX Power	N/A	The maximum conducted output power shall not exceed 250 mW or 11 + 10 log10B, dBm		1 Watt (30dBm)
Max E.I.R.P	For other devices, the maximum e.i.r.p. shall not exceed 200 mW or 10 + 10 log10B, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.	The maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 log10B, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.		4 W (36 dBm) with 6 dBi antenna
TPC	NO	YES, if Max_EIRP ≥ 500 mW (27 dBm) and able to lower EIRP below 24dBm		NO
		NO, if Max_EIRP < 500mW (27dBm)		
FCC Part 15 Subpart E(15.407)				
Limit	Frequency Range(MHz)			
	5150~5250	5250~5350	5500~5725	5725~5850
Max Conducted TX Power	Master Device: 1 Watt(30dBm) Client Device: 250mW(24dBm)	24dBm (250 mW) or 11 dBm+ 10 log B, whichever is lower (B= 26-dB emission BW)		1 Watt (30dBm)
TPC	NO	YES, if Max_EIRP ≥ 500 mW (27 dBm) and able to lower EIRP below 24dBm		NO
		NO, if Max_EIRP < 500mW (27dBm)		

9.2 Test Setup



9.3 Test Procedure

- a) As an alternative to spectrum analyzer or EMI receiver measurements,

measurements may be

performed using a wideband RF power meter with a thermocouple detector or equivalent (see

Figure 24) if all of the conditions listed below are satisfied:

- 1) The EUT is configured to transmit continuously, or to transmit with a constant duty



cycle.

2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.

3) The integration period of the power meter exceeds the repetition period of the transmitted

signal by at least a factor of five.

b) If the transmitter does not transmit continuously, measure the duty cycle, D , of the transmitter

output signal as described in 11.6.

c) Measure the average power of the transmitter. This measurement is an average over both the ON

and OFF periods of the transmitter.

d) Correct the measurement in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.

9.4 Deviation From Test Standard

No deviation

9.5 EUT Operating Mode

Please refer to the description of test mode.

9.6 Test Data

Please refer to the external appendix report of 5G Wi-Fi.



10. Power Spectral Density Test

10.1 Test Standard and Limit

10.1.1 Test Standard


RSS 247 (6.2.11&6.2.2.1&6.2.3.1&6.2.4.1)

FCC Part 15.407(a)

10.1.2 Test Limit

Test Item	Limit		Frequency Range(MHz)
Power Spectral Density	FCC	Master Device: 17dBm/MHz Client Device: 11dBm/MHz	5150~5250
	IC	10dBm/MHz E.I.R.P. PSD	
		11dBm/MHz	5250~5350
		11dBm/MHz	5500~5725
		30dBm/500kHz	5725~5850

10.2 Test Setup



10.3 Test Procedure

● Method SA-2 uses trace averaging across ON and OFF times of the EUT

transmissions, followed by duty

cycle correction. The procedure for this method is as follows:

a) Measure the duty cycle D of the transmitter output signal as described in 12.2.

b) Set span to encompass the entire 99% OBW of the signal.

c) Set RBW = 1 MHz. 5.8G Set RBW = 500KHz.

d) Set VBW = 3 MHz. 5.8G Set VBW = 2 MHz.

e) Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} /$

2, so that

narrowband signals are not lost between frequency bins.)

f) Sweep time = auto.

g) Detector = Power averaging (rms), if available. Otherwise, use sample detector mode.

h) Do not use sweep triggering. Allow the sweep to “free run.”

i) Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to



be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the ON and OFF periods of the transmitter.

j) Compute power by integrating the spectrum across the 99% OBW of the signal using the instrument's band-power measurement function with band limits set equal to the EBW or OBW band-edges. If the instrument does not have a band-power function, then sum the spectrum levels (in power units) at 1 MHz intervals extending across the 99% OBW of the spectrum.

k) Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured power to compute the average power during the actual transmission times (because the measurement represents an average over both the ON and OFF times of the transmission). For example, add $[10 \log (1 / 0.25)] = 6$ dB if the duty cycle is 25%.

10.4 Deviation From Test Standard

No deviation

10.5 Antenna Connected Construction

Please refer to the description of test mode.

10.6 Test Data

Please refer to the external appendix report of 5G Wi-Fi.



11. Frequency Stability

11.1 Test Standard and Limit

11.1.1 Test Standard


RSS-Gen 8.11

FCC Part 15.407(g)

11.1.2 Test Limit

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

11.2 Test Setup



11.3 Test Procedure

Frequency stability with respect to ambient temperature

a) Supply the EUT with a nominal ac voltage or install a new or fully charged battery in the EUT. If possible, a dummy load shall be connected to the EUT because an antenna near the metallic walls of an environmental test chamber could affect the output frequency of the EUT. If the EUT is equipped with a permanently attached, adjustable-length antenna, then the EUT shall be placed in the center of the chamber with the antenna adjusted to the shortest length possible. Turn ON the EUT and tune it to one of the number of frequencies shown in 5.6.

b) Couple the unlicensed wireless device output to the measuring instrument by connecting an antenna to the measuring instrument with a suitable length of coaxial cable and placing the measuring antenna near the EUT (e.g., 15 cm away), or by connecting a dummy load to the measuring instrument, through an attenuator if necessary.

NOTE—An instrument that has an adequate level of accuracy as specified by the procuring or regulatory agency is the recommended measuring instrument.

c) Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument but is strong enough to allow measurement of the operating or fundamental frequency of the EUT).

d) Turn the EUT OFF and place it inside the environmental temperature chamber. For devices that have oscillator heaters, energize only the heater circuit.

e) Set the temperature control on the chamber to the highest specified in the regulatory requirements for the type of device and allow the oscillator heater and the chamber temperature to stabilize.

f) While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized. Four measurements in total are made.

g) Measure the frequency at each of frequencies specified in 5.6.

h) Switch OFF the EUT but do not switch OFF the oscillator heater.

i) Lower the chamber temperature by not more than 10°C, and allow the temperature



inside the chamber to stabilize.

j) Repeat step f) through step i) down to the lowest specified temperature.

Frequency stability when varying supply voltage

Unless otherwise specified, these tests shall be made at ambient room temperature (+15°C to +25°C). An antenna shall be connected to the antenna output terminals of the EUT if possible. If the EUT is equipped with or uses an adjustable-length antenna, then it shall be fully extended.

a) Supply the EUT with nominal voltage or install a new or fully charged battery in the EUT. Turn ON the EUT and couple its output to a frequency counter or other frequency-measuring instrument.

NOTE—An instrument that has an adequate level of accuracy as specified by the procuring or regulatory agency is the recommended measuring instrument.

b) Tune the EUT to one of the number of frequencies required in 5.6. Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument but is strong enough to allow measurement of the operating or fundamental frequency of the EUT).

c) Measure the frequency at each of the frequencies specified in 5.6.

d) Repeat the above procedure at 85% and 115% of the nominal supply voltage as described in 5.13.

11.4 Deviation From Test Standard

No deviation

11.5 Antenna Connected Construction

Please refer to the description of test mode.

11.6 Test Data

Please refer to the external appendix report of 5G Wi-Fi.



12. Duty cycle

12.1 Test Standard and Limit


12.1.1 Test Standard

/

12.1.2 Test Limit

/

12.2 Test Setup



12.3 Test Procedure

● Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

a) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times

of the transmitted signal:

1) Set the center frequency of the instrument to the center frequency of the transmission.

2) Set RBW $\geq 8\text{MHz}$ if possible; otherwise, set RBW to the largest available value.

3) Set VBW $\geq 8\text{MHz}$. Set detector = peak or average.

4) The zero-span 0MHz measurement method shall not be used unless both RBW and VBW are $> 1/T$

and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or

RBW are limited to 8 MHz,

12.4 Deviation From Test Standard

No deviation

12.5 Antenna Connected Construction

Please refer to the description of test mode.

12.6 Test Data

Please refer to the external appendix report of 5G Wi-Fi.



13. Antenna Requirement

13.1 Test Standard and Limit

13.1.1 Test Standard

RSS Gen 6.8

13.1.2 Requirement(FCC Part 15.203)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

(RSS-Gen 6.8)

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

13.2 Deviation From Test Standard

No deviation

13.3 Antenna Connected Construction

The Max. gains of the antenna used for transmitting is 5.5dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

13.4 Test Data


The EUT antenna is a FPC Antenna.. It complies with the standard requirement.

Antenna Type
☐ Permanent attached antenna
☒ Unique connector antenna
☐ Professional installation antenna



Attachment A-- Conducted Emission Test Data

Test Voltage:	DC 5V
Terminal:	Line
Test Mode:	Mode 1 FPC Antenna 1
Remark:	Only worse case is reported.



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
		MHz	Level	Factor	ment			Detector
			dBuV	dB	dBuV	dBuV	dB	
1		0.186	25.40	9.74	35.14	64.21	-29.07	QP
2		0.186	10.96	9.74	20.70	54.21	-33.51	AVG
3		0.366	20.65	9.81	30.46	58.59	-28.13	QP
4		0.366	10.33	9.81	20.14	48.59	-28.45	AVG
5	*	0.614	24.01	9.77	33.78	56.00	-22.22	QP
6		0.614	11.78	9.77	21.55	46.00	-24.45	AVG
7		1.176	17.19	9.87	27.06	56.00	-28.94	QP
8		1.176	8.98	9.87	18.85	46.00	-27.15	AVG
9		2.584	14.65	9.83	24.48	56.00	-31.52	QP
10		2.584	7.09	9.83	16.92	46.00	-29.08	AVG
11		4.825	14.23	9.73	23.96	56.00	-32.04	QP
12		4.825	7.42	9.73	17.15	46.00	-28.85	AVG


Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)

2. Margin (dB) = QuasiPeak/Average (dBuV) - Limit (dBuV)



Test Voltage:	DC 5V
Terminal:	Neutral
Test Mode:	Mode 1 FPC Antenna1
Remark:	Only worse case is reported.



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.181	24.97	9.70	34.67	64.44	-29.77	QP
2		0.181	10.44	9.70	20.14	54.44	-34.30	AVG
3		0.361	17.96	9.76	27.72	58.71	-30.99	QP
4		0.361	7.95	9.76	17.71	48.71	-31.00	AVG
5	*	0.640	20.87	9.74	30.61	56.00	-25.39	QP
6		0.640	9.58	9.74	19.32	46.00	-26.68	AVG
7		1.208	10.57	9.81	20.38	56.00	-35.62	QP
8		1.208	6.23	9.81	16.04	46.00	-29.96	AVG
9		4.168	11.80	9.72	21.52	56.00	-34.48	QP
10		4.168	6.25	9.72	15.97	46.00	-30.03	AVG
11		12.620	10.77	9.89	20.66	60.00	-39.34	QP
12		12.620	5.53	9.89	15.42	50.00	-34.58	AVG

Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)

2. Margin (dB) = QuasiPeak/Average (dBuV) - Limit (dBuV)



Attachment B--Unwanted Emissions Data


---Radiated Unwanted Emissions

9 KHz~30 MHz


From 9 KHz to 30 MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB
Below the permissible value has no need to be reported.

30MHz~1GHz



Test Voltage:	DC 5V
Ant. Pol.	Vertical
Test Mode:	Mode 1 FPC Antenna 1
Remark:	Only worse case is reported.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	59.0251	51.94	-23.97	27.97	40.00	-12.03	peak	P
2	107.8877	54.37	-24.55	29.82	43.50	-13.68	peak	P
3	180.0165	55.02	-23.58	31.44	43.50	-12.06	peak	P
4	239.9874	55.36	-23.92	31.44	46.00	-14.56	peak	P
5	300.3672	53.29	-21.18	32.11	46.00	-13.89	peak	P
6 *	541.3725	52.17	-15.08	37.09	46.00	-8.91	peak	P

Remark:



1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) -AMP(dB)
2. QuasiPeak (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = QuasiPeak (dBμV/m)-Limit QPK(dBμV/m)



Above 1GHz

Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5180MHz Ant.1+2-MIMO FPC Antenna

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9483.0000	44.15	-1.53	42.62	68.30	-25.68	peak	P
2 *	9483.0000	35.04	-1.53	33.51	54.00	-20.49	AVG	P
3	14787.0000	39.85	2.63	42.48	68.30	-25.82	peak	P
4	14787.0000	30.83	2.63	33.46	54.00	-20.54	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value < average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5180MHz Ant.1+2-MIMO FPC Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9381.0000	46.29	-2.65	43.64	68.30	-24.66	peak	P
2 *	9381.0000	37.21	-2.65	34.56	54.00	-19.44	AVG	P
3	14855.0000	39.48	2.85	42.33	68.30	-25.97	peak	P
4	14855.0000	30.44	2.85	33.29	54.00	-20.71	AVG	P


Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.




Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5200MHz Ant.1+2-MIMO FPC Antenna

Horizontal



Temperature: 23.9

Humidity: 52 %



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9313.0000	47.72	-4.04	43.68	68.30	-24.62	peak	P
2	9313.0000	38.30	-4.04	34.26	54.00	-19.74	AVG	P
3	17201.0000	39.14	4.49	43.63	68.30	-24.67	peak	P
4 *	17201.0000	29.85	4.49	34.34	54.00	-19.66	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5200MHz Ant.1+2-MIMO FPC Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9432.0000	44.96	-2.01	42.95	68.30	-25.35	peak	P
2 *	9432.0000	36.48	-2.01	34.47	54.00	-19.53	AVG	P
3	17830.0000	37.67	6.22	43.89	68.30	-24.41	peak	P
4	17830.0000	28.17	6.22	34.39	54.00	-19.61	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5240MHz Ant.1+2-MIMO FPC Antenna

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9432.0000	45.15	-2.01	43.14	68.30	-25.16	peak	P
2	9432.0000	36.29	-2.01	34.28	54.00	-19.72	AVG	P
3	17932.0000	38.77	6.16	44.93	68.30	-23.37	peak	P
4 *	17932.0000	28.97	6.16	35.13	54.00	-18.87	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5240MHz Ant.1+2-MIMO FPC Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9483.0000	44.66	-1.53	43.13	68.30	-25.17	peak	P
2	9483.0000	35.82	-1.53	34.29	54.00	-19.71	AVG	P
3	17830.0000	38.60	6.22	44.82	68.30	-23.48	peak	P
4 *	17830.0000	29.19	6.22	35.41	54.00	-18.59	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which mor than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5260MHz Ant.1+2-MIMO FPC Antenna

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10928.0000	44.41	-1.27	43.14	68.30	-25.16	peak	P
2 *	10928.0000	36.19	-1.27	34.92	54.00	-19.08	AVG	P
3	17473.0000	38.86	4.42	43.28	68.30	-25.02	peak	P
4	17473.0000	30.26	4.42	34.68	54.00	-19.32	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5260MHz Ant.1+2-MIMO FPC Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9449.0000	44.71	-1.72	42.99	68.30	-25.31	peak	P
2	9449.0000	35.79	-1.72	34.07	54.00	-19.93	AVG	P
3	17269.0000	39.50	4.25	43.75	68.30	-24.55	peak	P
4 *	17269.0000	30.40	4.25	34.65	54.00	-19.35	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5280MHz Ant.1+2-MIMO FPC Antenna

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10860.0000	44.85	-1.58	43.27	68.30	-25.03	peak	P
2 *	10860.0000	36.27	-1.58	34.69	54.00	-19.31	AVG	P
3	14753.0000	40.40	2.36	42.76	68.30	-25.54	peak	P
4	14753.0000	31.51	2.36	33.87	54.00	-20.13	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5280MHz Ant.1+2-MIMO FPC Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11285.0000	43.31	-0.43	42.88	68.30	-25.42	peak	P
2	11285.0000	33.75	-0.43	33.32	54.00	-20.68	AVG	P
3	14804.0000	39.29	2.74	42.03	68.30	-26.27	peak	P
4 *	14804.0000	30.71	2.74	33.45	54.00	-20.55	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5320MHz Ant.1+2-MIMO FPC Antenna

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9449.0000	44.78	-1.72	43.06	68.30	-25.24	peak	P
2 *	9449.0000	36.46	-1.72	34.74	54.00	-19.26	AVG	P
3	17575.0000	39.03	4.58	43.61	68.30	-24.69	peak	P
4	17575.0000	30.04	4.58	34.62	54.00	-19.38	AVG	P


Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.




Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5320MHz Ant.1+2-MIMO FPC Antenna

Vertical



Temperature: 23.9 °C

Humidity: 52 %



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9500.0000	44.26	-1.45	42.81	68.30	-25.49	peak	P
2 *	9500.0000	35.03	-1.45	33.58	54.00	-20.42	AVG	P
3	16742.0000	39.48	3.27	42.75	68.30	-25.55	peak	P
4	16742.0000	29.97	3.27	33.24	54.00	-20.76	AVG	P


Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.




Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5500MHz Ant.1+2-MIMO FPC Antenna

Horizontal



Temperature: 23.9

Humidity: 52 %



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10860.0000	44.38	-1.58	42.80	68.30	-25.50	peak	P
2	10860.0000	35.09	-1.58	33.51	54.00	-20.49	AVG	P
3	17048.0000	39.16	3.61	42.77	68.30	-25.53	peak	P
4 *	17048.0000	30.23	3.61	33.84	54.00	-20.16	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5500MHz Ant.1+2-MIMO FPC Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9347.0000	46.24	-2.92	43.32	68.30	-24.98	peak	P
2 *	9347.0000	37.39	-2.92	34.47	54.00	-19.53	AVG	P
3	14804.0000	40.03	2.74	42.77	68.30	-25.53	peak	P
4	14804.0000	30.76	2.74	33.50	54.00	-20.50	AVG	P


Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.




Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5580MHz Ant.1+2-MIMO FPC Antenna

Horizontal



Temperature: 23.9 °C

Humidity: 52 %



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10877.0000	44.74	-1.49	43.25	68.30	-25.05	peak	P
2 *	10877.0000	35.77	-1.49	34.28	54.00	-19.72	AVG	P
3	14753.0000	39.99	2.36	42.35	68.30	-25.95	peak	P
4	14753.0000	31.26	2.36	33.62	54.00	-20.38	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5580MHz Ant.1+2-MIMO FPC Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12186.0000	42.49	1.01	43.50	68.30	-24.80	peak	P
2 *	12186.0000	33.60	1.01	34.61	54.00	-19.39	AVG	P
3	14787.0000	39.59	2.63	42.22	68.30	-26.08	peak	P
4	14787.0000	31.31	2.63	33.94	54.00	-20.06	AVG	P


Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.




Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5720MHz Ant.1+2-MIMO FPC Antenna

Horizontal



Temperature: 23.9 °C

Humidity: 52 %



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9483.0000	44.37	-1.53	42.84	68.30	-25.46	peak	P
2	9483.0000	35.10	-1.53	33.57	54.00	-20.43	AVG	P
3	17847.0000	38.58	6.18	44.76	68.30	-23.54	peak	P
4 *	17847.0000	29.43	6.18	35.61	54.00	-18.39	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5720MHz Ant.1+2-MIMO FPC Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9483.0000	44.37	-1.53	42.84	68.30	-25.46	peak	P
2 *	9483.0000	34.82	-1.53	33.29	54.00	-20.71	AVG	P
3	14736.0000	39.67	2.23	41.90	68.30	-26.40	peak	P
4	14736.0000	30.13	2.23	32.36	54.00	-21.64	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5745MHz Ant.1+2-MIMO FPC Antenna

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9483.0000	44.42	-1.53	42.89	68.30	-25.41	peak	P
2	9483.0000	35.37	-1.53	33.84	54.00	-20.16	AVG	P
3	10911.0000	44.65	-1.33	43.32	68.30	-24.98	peak	P
4 *	10911.0000	35.92	-1.33	34.59	54.00	-19.41	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value < average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5745MHz Ant.1+2-MIMO FPC Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12152.0000	42.25	1.12	43.37	68.30	-24.93	peak	P
2	12152.0000	33.33	1.12	34.45	54.00	-19.55	AVG	P
3	17473.0000	39.89	4.42	44.31	68.30	-23.99	peak	P
4 *	17473.0000	30.86	4.42	35.28	54.00	-18.72	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5785MHz Ant.1+2-MIMO FPC Antenna

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9449.0000	44.91	-1.72	43.19	68.30	-25.11	peak	P
2 *	9449.0000	36.45	-1.72	34.73	54.00	-19.27	AVG	P
3	17218.0000	38.89	4.43	43.32	68.30	-24.98	peak	P
4	17218.0000	29.74	4.43	34.17	54.00	-19.83	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5785MHz Ant.1+2-MIMO FPC Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10979.0000	44.71	-1.10	43.61	68.30	-24.69	peak	P
2 *	10979.0000	35.28	-1.10	34.18	54.00	-19.82	AVG	P
3	14736.0000	39.87	2.23	42.10	68.30	-26.20	peak	P
4	14736.0000	31.12	2.23	33.35	54.00	-20.65	AVG	P


Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.




Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5825MHz Ant.1+2-MIMO FPC Antenna

Horizontal



Temperature: 23.9 °C

Humidity: 52 %



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9347.0000	36.12	-2.92	33.20	54.00	-20.80	AVG	P
2 *	11353.0000	33.86	-0.29	33.57	54.00	-20.43	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value < average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5825MHz Ant.1+2-MIMO FPC Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	14770.0000	39.58	2.49	42.07	68.30	-26.23	peak	P
2	14770.0000	30.80	2.49	33.29	54.00	-20.71	AVG	P
3	17235.0000	38.42	4.37	42.79	68.30	-25.51	peak	P
4 *	17235.0000	29.21	4.37	33.58	54.00	-20.42	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value < average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5180MHz Ant. 1+2-MIMO Dipole Antenna

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	7681.0000	51.23	-9.00	42.23	68.30	-26.07	peak	P
2	7681.0000	43.06	-9.00	34.06	54.00	-19.94	AVG	P
3	16912.0000	38.96	3.52	42.48	68.30	-25.82	peak	P
4 *	16912.0000	31.04	3.52	34.56	54.00	-19.44	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5180MHz Ant.1+2-MIMO Dipole Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10877.0000	44.47	-1.49	42.98	68.30	-25.32	peak	P
2	10877.0000	36.57	-1.49	35.08	54.00	-18.92	AVG	P
3	14702.0000	41.39	1.95	43.34	68.30	-24.96	peak	P
4 *	14702.0000	33.97	1.95	35.92	54.00	-18.08	AVG	P


Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.




Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5200MHz Ant.1+2-MIMO Dipole Antenna

Horizontal



Temperature: 23.8 °C

Humidity: 51 %



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10877.0000	44.96	-1.49	43.47	68.30	-24.83	peak	P
2 *	10877.0000	36.77	-1.49	35.28	54.00	-18.72	AVG	P
3	15518.0000	40.00	2.10	42.10	68.30	-26.20	peak	P
4	15518.0000	32.66	2.10	34.76	54.00	-19.24	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5200MHz Ant.1+2-MIMO Dipole Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9432.0000	44.96	-2.01	42.95	68.30	-25.35	peak	P
2	9432.0000	37.52	-2.01	35.51	54.00	-18.49	AVG	P
3	17133.0000	39.17	4.05	43.22	68.30	-25.08	peak	P
4 *	17133.0000	31.79	4.05	35.84	54.00	-18.16	AVG	P


Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.




Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5240MHz Ant.1+2-MIMO Dipole Antenna

Horizontal



Temperature: 23.8 °C

Humidity: 51 %



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9432.0000	45.15	-2.01	43.14	68.30	-25.16	peak	P
2 *	9432.0000	37.42	-2.01	35.41	54.00	-18.59	AVG	P
3	14583.0000	41.08	1.40	42.48	68.30	-25.82	peak	P
4	14583.0000	33.41	1.40	34.81	54.00	-19.19	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5240MHz Ant. 1+2-MIMO Dipole Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10486.0000	45.81	-2.50	43.31	68.30	-24.99	peak	P
2 *	10486.0000	37.79	-2.50	35.29	54.00	-18.71	AVG	P
3	14702.0000	41.15	1.95	43.10	68.30	-25.20	peak	P
4	14702.0000	33.12	1.95	35.07	54.00	-18.93	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which mor than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5260MHz Ant.1+2-MIMO Dipole Antenna

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10061.0000	46.75	-2.76	43.99	68.30	-24.31	peak	P
2 *	10061.0000	37.91	-2.76	35.15	54.00	-18.85	AVG	P
3	12016.0000	41.42	1.09	42.51	68.30	-25.79	peak	P
4	12016.0000	33.21	1.09	34.30	54.00	-19.70	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5260MHz Ant.1+2-MIMO Dipole Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9738.0000	45.79	-2.31	43.48	68.30	-24.82	peak	P
2	9738.0000	37.42	-2.31	35.11	54.00	-18.89	AVG	P
3	17099.0000	40.00	3.84	43.84	68.30	-24.46	peak	P
4 *	17099.0000	31.65	3.84	35.49	54.00	-18.51	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5280MHz Ant.1+2-MIMO Dipole Antenna

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10860.0000	44.35	-1.58	42.77	68.30	-25.53	peak	P
2	10860.0000	35.94	-1.58	34.36	54.00	-19.64	AVG	P
3	17065.0000	39.66	3.69	43.35	68.30	-24.95	peak	P
4 *	17065.0000	32.24	3.69	35.93	54.00	-18.07	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5280MHz Ant.1+2-MIMO Dipole Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9466.0000	43.49	-1.62	41.87	68.30	-26.43	peak	P
2 *	9466.0000	36.37	-1.62	34.75	54.00	-19.25	AVG	P
3	16997.0000	38.93	3.40	42.33	68.30	-25.97	peak	P
4	16997.0000	31.29	3.40	34.69	54.00	-19.31	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5320MHz Ant.1+2-MIMO Dipole Antenna

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11693.0000	43.08	0.01	43.09	68.30	-25.21	peak	P
2 *	11693.0000	35.30	0.01	35.31	54.00	-18.69	AVG	P
3	17286.0000	38.74	4.19	42.93	68.30	-25.37	peak	P
4	17286.0000	30.59	4.19	34.78	54.00	-19.22	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value < average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5320MHz Ant. 1+2-MIMO Dipole Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10945.0000	43.99	-1.21	42.78	68.30	-25.52	peak	P
2	10945.0000	35.82	-1.21	34.61	54.00	-19.39	AVG	P
3	14787.0000	40.92	2.63	43.55	68.30	-24.75	peak	P
4 *	14787.0000	32.64	2.63	35.27	54.00	-18.73	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5500MHz Ant.1+2-MIMO Dipole Antenna

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10860.0000	44.88	-1.58	43.30	68.30	-25.00	peak	P
2	10860.0000	36.67	-1.58	35.09	54.00	-18.91	AVG	P
3	17048.0000	40.17	3.60	43.77	68.30	-24.53	peak	P
4 *	17048.0000	31.78	3.60	35.38	54.00	-18.62	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5500MHz Ant.1+2-MIMO Dipole Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9347.0000	45.74	-2.92	42.82	68.30	-25.48	peak	P
2	9347.0000	37.51	-2.92	34.59	54.00	-19.41	AVG	P
3	11914.0000	42.55	1.00	43.55	68.30	-24.75	peak	P
4 *	11914.0000	34.27	1.00	35.27	54.00	-18.73	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5580MHz Ant.1+2-MIMO Dipole Antenna

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10877.0000	45.24	-1.49	43.75	68.30	-24.55	peak	P
2 *	10877.0000	37.06	-1.49	35.57	54.00	-18.43	AVG	P
3	16861.0000	39.69	3.49	43.18	68.30	-25.12	peak	P
4	16861.0000	31.73	3.49	35.22	54.00	-18.78	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5580MHz Ant.1+2-MIMO Dipole Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11999.0000	42.18	1.07	43.25	68.30	-25.05	peak	P
2 *	11999.0000	34.18	1.07	35.25	54.00	-18.75	AVG	P
3	17031.0000	39.39	3.52	42.91	68.30	-25.39	peak	P
4	17031.0000	30.63	3.52	34.15	54.00	-19.85	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5720MHz Ant.1+2-MIMO Dipole Antenna

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12135.0000	41.81	1.16	42.97	68.30	-25.33	peak	P
2	12135.0000	33.17	1.16	34.33	54.00	-19.67	AVG	P
3	16708.0000	39.12	3.18	42.30	68.30	-26.00	peak	P
4 *	16708.0000	31.51	3.18	34.69	54.00	-19.31	AVG	P


Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value < average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.




Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5720MHz Ant. 1+2-MIMO Dipole Antenna

Vertical



Temperature: 23.8 °C

Humidity: 51 %



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10588.0000	45.30	-2.21	43.09	68.30	-25.21	peak	P
2 *	10588.0000	37.39	-2.21	35.18	54.00	-18.82	AVG	P
3	14719.0000	39.94	2.09	42.03	68.30	-26.27	peak	P
4	14719.0000	32.11	2.09	34.20	54.00	-19.80	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5745MHz Ant.1+2-MIMO Dipole Antenna

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	9483.0000	45.42	-1.53	43.89	68.30	-24.41	peak	P
2	9483.0000	36.62	-1.53	35.09	54.00	-18.91	AVG	P
3	16997.0000	39.94	3.40	43.34	68.30	-24.96	peak	P
4 *	16997.0000	32.22	3.40	35.62	54.00	-18.38	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value < average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5745MHz Ant.1+2-MIMO Dipole Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10945.0000	43.74	-1.21	42.53	68.30	-25.77	peak	P
2 *	10945.0000	36.12	-1.21	34.91	54.00	-19.09	AVG	P
3	12645.0000	42.87	-0.04	42.83	68.30	-25.47	peak	P
4	12645.0000	34.45	-0.04	34.41	54.00	-19.59	AVG	P


Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.




Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5785MHz Ant.1+2-MIMO Dipole Antenna

Horizontal



Temperature: 23.8 °C

Humidity: 51 %



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11319.0000	44.01	-0.36	43.65	68.30	-24.65	peak	P
2 *	11319.0000	35.55	-0.36	35.19	54.00	-18.81	AVG	P
3	17218.0000	37.89	4.43	42.32	68.30	-25.98	peak	P
4	17218.0000	30.16	4.43	34.59	54.00	-19.41	AVG	P


Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.




Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5785MHz Ant.1+2-MIMO Dipole Antenna

Vertical



Temperature: 23.8 °C

Humidity: 51 %



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10979.0000	43.71	-1.10	42.61	68.30	-25.69	peak	P
2 *	10979.0000	35.89	-1.10	34.79	54.00	-19.21	AVG	P
3	17082.0000	39.18	3.76	42.94	68.30	-25.36	peak	P
4	17082.0000	30.51	3.76	34.27	54.00	-19.73	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5825MHz Ant.1+2-MIMO Dipole Antenna

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10945.0000	43.52	-1.21	42.31	68.30	-25.99	peak	P
2 *	10945.0000	35.76	-1.21	34.55	54.00	-19.45	AVG	P
3	13580.0000	42.96	-0.15	42.81	68.30	-25.49	peak	P
4	13580.0000	34.33	-0.15	34.18	54.00	-19.82	AVG	P



Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value < average limit, So only show the peak value. and 26.5GHz-40GHz is the noise, No other signals were detected.



Test Voltage:	DC 5V
Test Mode:	TX 802.11ac(VHT20) Mode 5825MHz Ant.1+2-MIMO Dipole Antenna

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	8123.0000	48.94	-7.30	41.64	68.30	-26.66	peak	P
2 *	8123.0000	42.14	-7.30	34.84	54.00	-19.16	AVG	P
3	14736.0000	40.23	2.23	42.46	68.30	-25.84	peak	P
4	14736.0000	32.38	2.23	34.61	54.00	-19.39	AVG	P

Remark:


1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)
4. The tests evaluated 1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).
5. No report for the emission which more than 20dB below the prescribed limit.
6. The peak value<average limit, So only show the peak value. and 26.5GHz-40GHz is the noise,No other signals were detected.



Attachment C-- Restricted Bands Requirement Test Data

Radiation Test

Test Voltage:	DC 5V
Ant. Pol.	Horizontal
Test Mode:	TX 802.11ac(VHT20) Mode 5180 MHz (U-NII-1) Ant.1+2-MIMO FPC Antenna
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.0000	44.56	9.66	54.22	74.00	-19.78	peak	P
2 *	5150.0000	36.74	9.66	46.40	54.00	-7.60	AVG	P

Remark:


1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)

2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)

3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)



Test Voltage:	DC 5V
Ant. Pol.	Vertical
Test Mode:	TX 802.11ac(VHT20) Mode 5180 MHz (U-NII-1) Ant.1+2-MIMO FPC Antenna
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.0000	45.40	9.66	55.06	74.00	-18.94	peak	P
2 *	5150.0000	39.00	9.66	48.66	54.00	-5.34	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)



Test Voltage:	DC 5V
Ant. Pol.	Horizontal
Test Mode:	TX 802.11ac(VHT20) Mode 5320 MHz (U-NII-2A) Ant.1+2-MIMO FPC Antenna
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5350.0000	45.39	10.07	55.46	74.00	-18.54	peak	P
2 *	5350.0000	38.26	10.07	48.33	54.00	-5.67	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)



Test Voltage:	DC 5V
Ant. Pol.	Vertical
Test Mode:	TX 802.11ac(VHT20) Mode 5320 MHz (U-NII-2A) Ant.1+2-MIMO FPC Antenna
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5350.0000	49.27	10.07	59.34	74.00	-14.66	peak	P
2 *	5350.0000	41.96	10.07	52.03	54.00	-1.97	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)



Test Voltage:	DC 5V
Ant. Pol.	Horizontal
Test Mode:	TX 802.11ac(VHT40) Mode 5190 MHz (U-NII-1) Ant.1+2-MIMO FPC Antenna
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.0000	44.21	9.66	53.87	74.00	-20.13	peak	P
2 *	5150.0000	37.11	9.66	46.77	54.00	-7.23	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)



Test Voltage:	DC 5V
Ant. Pol.	Vertical
Test Mode:	TX 802.11ac(VHT40) Mode 5190 MHz (U-NII-1) Ant.1+2-MIMO FPC Antenna
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.0000	46.53	9.66	56.19	74.00	-17.81	peak	P
2 *	5150.0000	39.35	9.66	49.01	54.00	-4.99	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)



Test Voltage:	DC 5V
Ant. Pol.	Horizontal
Test Mode:	TX 802.11ac(VHT40) Mode 5310 MHz (U-NII-2A) Ant.1+2-MIMO FPC Antenna
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5350.0000	45.69	10.07	55.76	74.00	-18.24	peak	P
2 *	5350.0000	38.47	10.07	48.54	54.00	-5.46	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)



Test Voltage:	DC 5V
Ant. Pol.	Vertical
Test Mode:	TX 802.11ac(VHT40) Mode 5310 MHz (U-NII-2A) Ant.1+2-MIMO FPC Antenna
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5350.0000	47.24	10.07	57.31	74.00	-16.69	peak	P
2 *	5350.0000	40.80	10.07	50.87	54.00	-3.13	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)



Test Voltage:	DC 5V
Ant. Pol.	Horizontal
Test Mode:	TX 802.11ac(VHT80) Mode 5210 MHz (U-NII-1) Ant.1+2-MIMO FPC Antenna
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.0000	44.52	9.66	54.18	74.00	-19.82	peak	P
2 *	5150.0000	37.12	9.66	46.78	54.00	-7.22	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)



Test Voltage:	DC 5V
Ant. Pol.	Vertical
Test Mode:	TX 802.11ac(VHT80) Mode 5210 MHz (U-NII-1) Ant.1+2-MIMO FPC Antenna
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.0000	47.59	9.66	57.25	74.00	-16.75	peak	P
2 *	5150.0000	40.55	9.66	50.21	54.00	-3.79	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)



Test Voltage:	DC 5V
Ant. Pol.	Horizontal
Test Mode:	TX 802.11ac(VHT20) Mode 5500 MHz (U-NII-2C) Ant.1+2-MIMO FPC Antenna
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5460.0000	44.94	10.12	55.06	68.30	-13.24	peak	P
2 *	5460.0000	37.67	10.12	47.79	54.00	-6.21	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)



Test Voltage:	DC 5V
Ant. Pol.	Vertical
Test Mode:	TX 802.11ac(VHT20) Mode 5500 MHz (U-NII-2C) Ant.1+2-MIMO FPC Antenna
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5460.0000	47.50	10.12	57.62	68.30	-10.68	peak	P
2 *	5460.0000	39.98	10.12	50.10	54.00	-3.90	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)



Test Voltage:	DC 5V
Ant. Pol.	Horizontal
Test Mode:	TX 802.11ac(VHT80) Mode 5530 MHz (U-NII-2C) Ant.1+2-MIMO FPC Antenna
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5460.0000	45.11	10.12	55.23	68.30	-13.07	peak	P
2 *	5460.0000	38.70	10.12	48.82	54.00	-5.18	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)



Test Voltage:	DC 5V
Ant. Pol.	Vertical
Test Mode:	TX 802.11ac(VHT80) Mode 5530 MHz (U-NII-2C) Ant.1+2-MIMO FPC Antenna
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5460.0000	48.79	10.12	58.91	68.30	-9.39	peak	P
2 *	5460.0000	41.50	10.12	51.62	54.00	-2.38	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)



Test Voltage:	DC 5V
Ant. Pol.	Horizontal
Test Mode:	TX 802.11ac(VHT20) Mode 5745 MHz (U-NII-3) Ant.1+2-MIMO FPC Antenna
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5725.0000	47.09	11.59	58.68	122.30	-63.62	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)



Test Voltage:	DC 5V
Ant. Pol.	Vertical
Test Mode:	TX 802.11ac(VHT20) Mode 5745 MHz (U-NII-3) Ant.1+2-MIMO FPC Antenna
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5725.0000	53.96	11.59	65.55	122.30	-56.75	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)



Test Voltage:	DC 5V
Ant. Pol.	Horizontal
Test Mode:	TX 802.11ac(VHT20) Mode 5825 MHz (U-NII-3) Ant.1+2-MIMO FPC Antenna
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5850.0000	43.89	11.90	55.79	122.30	-66.51	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)



Test Voltage:	DC 5V
Ant. Pol.	Vertical
Test Mode:	TX 802.11ac(VHT20) Mode 5825 MHz (U-NII-3) Ant.1+2-MIMO FPC Antenna
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5850.0000	52.99	11.90	64.89	122.30	-57.41	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)



Test Voltage:	DC 5V
Ant. Pol.	Horizontal
Test Mode:	TX 802.11ac(VHT40) Mode 5755 MHz (U-NII-3) Ant.1+2-MIMO FPC Antenna
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5725.0000	47.80	11.59	59.39	122.30	-62.91	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)



Test Voltage:	DC 5V
Ant. Pol.	Vertical
Test Mode:	TX 802.11ac(VHT40) Mode 5755 MHz (U-NII-3) Ant.1+2-MIMO FPC Antenna
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5725.0000	57.65	11.59	69.24	122.30	-53.06	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)
2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)



Test Voltage:	DC 5V
Ant. Pol.	Horizontal
Test Mode:	TX 802.11ac(VHT80) Mode 5775 MHz (U-NII-3) Ant.1+2-MIMO FPC Antenna
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5725.0000	46.07	11.59	57.66	122.30	-64.64	peak	P
2	5850.0000	43.80	11.90	55.70	122.30	-66.60	peak	P

Remark:


1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)

2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)

3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)



Test Voltage:	DC 5V
Ant. Pol.	Vertical
Test Mode:	TX 802.11ac(VHT80) Mode 5775 MHz (U-NII-3) Ant.1+2-MIMO FPC Antenna
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5725.0000	57.45	11.59	69.04	122.30	-53.26	peak	P
2	5850.0000	53.29	11.90	65.19	122.30	-57.11	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)+AMP(dB)

2. Peak/AVG (dBuV/m)= Corr. (dB/m)+ Read Level (dBuV)

3. Margin (dB) = Peak/AVG (dBuV/m)-Limit PK/AVG(dBuV/m)

-----END OF THE REPORT-----

