


RF EXPOSURE EVALUATION REPORT

FCC ID : S9GH670
Equipment : H670 Access Point, C670 Access Point
Brand Name : RUCKUS
Model Name : H670, C670
Applicant : Ruckus Wireless LLC
350 W. Java Dr., Sunnyvale CA 94089 USA
Manufacturer : Ruckus Wireless LLC
350 W. Java Dr., Sunnyvale CA 94089 USA
Standard : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC has been evaluated this product in accordance with 47 CFR Part2.1091 and it complies with applicable limit.

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 3786) and the FCC designation No. TW3786 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC evaluation.

The results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager



SPORTON INTERNATIONAL INC. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan



Table of Contents

1. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	4
2. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS	4
3. RF EXPOSURE LIMIT INTRODUCTION	5
4. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	6
4.1. Standalone Power Density Calculation	6
4.2. Collocated Power Density Calculation.....	6



History of this test report

Report No.	Version	Description	Issued Date
FA250402022	Rev. 01	Initial issue of report	Oct. 27, 2025

**1. Description of Equipment Under Test (EUT)**

Product Feature & Specification	
EUT Type	H670 Access Point, C670 Access Point
Brand Name	RUCKUS
Model Name	H670, C670
FCC ID	S9GH670
Wireless Technology and Frequency Range	WLAN 2.4 GHz Band: 2400 MHz ~ 2483.5 MHz WLAN 5.2 GHz Band: 5150 MHz ~ 5250 MHz WLAN 5.3 GHz Band: 5250 MHz ~ 5350 MHz WLAN 5.6 GHz Band: 5470 MHz ~ 5725 MHz WLAN 5.8 GHz Band: 5725 MHz ~ 5850 MHz WLAN 6GHz Band: 5925 MHz ~ 6425 MHz, 6425 MHz ~ 6525 MHz, 6525 MHz ~ 6875 MHz, 6875 MHz ~ 7125 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz Zigbee: 2400 MHz ~ 2483.5 MHz
Mode	WLAN: 802.11a/b/g/n/ac/ax/be HT20/HT40/VHT20/VHT40/VHT80/VHT160/HE20/HE40/HE80/HE160/EHT20/EHT40/EHT80/EHT160 Bluetooth LE Zigbee: GFSK
EUT Stage	Identical Prototype

Reviewed by: Jason Wang**Report Producer: Carlie Tsai****2. Maximum RF average output power among production units**

Mode		Maximum Average power(dBm)
WLAN	2.4GHz	19.74
	5.2GHz	22.65
	5.3GHz	22.42
	5.6GHz	22.24
	5.8GHz	22.01
	6GHz	19.58
Bluetooth LE		20.50
Zigbee		20.47

3. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



4. Radio Frequency Radiation Exposure Evaluation

4.1. Standalone Power Density Calculation

Band	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum PG (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)	Power Density / Limit
2.4GHz WLAN	1.09	19.74	20.8	121.06	0.024	1.000	0.024
5.2GHz WLAN	2.14	22.65	24.8	301.30	0.060	1.000	0.060
5.3GHz WLAN	2.34	22.42	24.8	299.23	0.060	1.000	0.060
5.5GHz WLAN	2.43	22.24	24.7	293.09	0.058	1.000	0.058
5.8GHz WLAN	2.08	22.01	24.1	256.45	0.051	1.000	0.051
6GHz WLAN	1.23	19.58	20.8	120.50	0.024	1.000	0.024
Bluetooth	0.90	20.50	21.4	138.04	0.027	1.000	0.027
Zigbee	-1.43	20.47	19.0	80.17	0.016	1.000	0.016

4.2. Collocated Power Density Calculation

<WLAN 2.4G + WLAN 5G + WLAN 6G + BT>

WLAN 2.4GHz Power Density / Limit	WLAN 5GHz Power Density / Limit	WLAN 6GHz Power Density / Limit	Bluetooth Power Density / Limit	Σ (Power Density / Limit) of WLAN 2.4G + WLAN 5G + WLAN 6G + Bluetooth
0.024	0.060	0.024	0.027	0.135

<Zigbee + WLAN 2.4G + WLAN 5G + WLAN 6G>

Zigbee Power Density / Limit	WLAN 2.4GHz Power Density / Limit	WLAN 5GHz Power Density / Limit	WLAN 6GHz Power Density / Limit	Σ (Power Density / Limit) of Zigbee + WLAN 2.4G + WLAN 5G + WLAN 6G
0.016	0.024	0.060	0.024	0.124

Note:

- Σ (Power Density / Limit): This is a summation of [(power density for each transmitter/antenna included in the simultaneous transmission)/ (corresponding MPE limit)], for WLAN 2.4G + WLAN 5G + WLAN 6G + Bluetooth and Zigbee + WLAN 2.4G + WLAN 5G + WLAN 6G.
- Considering the WLAN module collocation with the Zigbee and Bluetooth transmitter of the EIRP performance listed in the table above, the aggregated (power density /limit) is smaller than 1, and MPE of 4 collocated transmitters is compliant.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.