

4 FCC §2.1091 & §15.407(f) - RF Exposure

4.1 Applicable Standard

According to FCC §15.407(f) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* (180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

4.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

4.3 MPE Results

5250-5350 MHz:

<u>Maximum peak output power at antenna input terminal (dBm):</u>	<u>20.32</u>
<u>Maximum peak output power at antenna input terminal (mW):</u>	<u>107.582</u>
<u>Prediction distance (cm):</u>	<u>20</u>
<u>Prediction frequency (MHz):</u>	<u>5270</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>8</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>6.31</u>
<u>Power density of prediction frequency at 20.0 cm (mW/cm²):</u>	<u>0.135</u>
<u>MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):</u>	<u>1.0</u>

5470-5725 MHz :

<u>Maximum peak output power at antenna input terminal (dBm):</u>	<u>21.88</u>
<u>Maximum peak output power at antenna input terminal (mW):</u>	<u>154.135</u>
<u>Prediction distance (cm):</u>	<u>20</u>
<u>Prediction frequency (MHz):</u>	<u>5670</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>8</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>6.31</u>
<u>Power density of prediction frequency at 20.0 cm (mW/cm²):</u>	<u>0.193</u>
<u>MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):</u>	<u>1.0</u>

The device meets FCC MPE requirement for uncontrolled exposure environment at 20 cm distance.

Colocation Exposure Exclusion:

According to KDB 447498 D01 General RF Exposure Guidance v05r02, EUT has two 2.4 GHz band antenna and two 5 GHz band antenna. The power density for 2.4 GHz band is 0.2273 (refer to T301s 2.4 GHz band report R1407152-247 Final, section 4). So the sum of MPE ratio for four antennas is: 0.8406 which is smaller than 1.0. So the colocation exposure exclusion applies.