



No. DAT-P-114/01-01

TEST REPORT

No. FCC- 2006001

Test name	FCC Test
Product	CDMA 1X Fixed Wireless Phone
Model	STARTEL 9000X
Client	Hisense Communications Co.,Ltd

Telecommunication Metrology Center
of Ministry of Information Industry



Notice

1. The test report is invalid if not marked with “exclusive stamp for the test report” or the stamp of the test center.
2. Any copy of the test report is invalid if not re-marked with the “exclusive stamp for the test report” or the stamp of the test center.
3. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
4. The test report is invalid if there is any evidence of erasure and/or falsification.
5. If there is any dissidence for the test report, please file objection to the test center within 15 days from the date of receiving the test report.
6. Normally, entrust test is only responsible for the samples that have undergone the test.
7. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the test center.

Address: No. 52, Huayuanbei Road, Beijing, P. R. China

Post code: 100083

Cable: 04282

Telephone: +86 10 62302041

Fax: +86 10 62304793

**Telecommunication Metrology Center
of Ministry of Information Industry**

No. FCC- 2006001

Page 3of 40

Product	CDMA 1X Fixed Wireless Phone	Model	STARTEL 9000X
		Trade mark	
Client	Hisense Communications Co.,Ltd		
Manufacturer	Hisense Communications Co.,Ltd	Arrival Date of sample	Mar,21 2006
Place of sampling	(Blank)	Carrier of the samples	Haining Wang
Quantity of the samples	1	Date of product	/
Base of the samples	(Blank)	Items of test	8
Series number	F56110001172		
Standard(s)	FCC Part 22		
Conclusion	Final Judgment: Pass  (Stamp) Date of issue: Mar,27, 2006		
Comment	The test result relates only to the tested sample.		

Approved by 陆冰松 Reviewed by 张锐 Performed by 吴迪
 (Lu Bingsong) (Zhang Rui) (Wu Di)

TABLE OF CONTENT

1	COMPETENCE AND WARRANTIES	5
2	GENERAL CONDITIONS	5
3	ABOUT EUT	5
4	LABORATORY ENVIRONMENT	6
5	SUMMARY OF TEST RESULTS	7
6	MAIN TEST INSTRUMENTS	8
7	TEST PERIOD	8
8	TEST LOCATION	8
ANNEX A	MEASUREMENT RESULTS.....	9
ANNEX B	PHOTOGRAPH OF EUT	34
ANNEX C	TEST LAYOUT	40

1 COMPETENCE AND WARRANTIES

Telecommunication Metrology Center of Ministry of Information Industry is a test laboratory accredited by DAR (DATEch) – Deutschen Akkreditierungs Rat (Deutsche Akkreditierungsstelle Technik), for the tests indicated in the Certificate No. **DAT-P-114/01-01**.

Telecommunication Metrology Center of Ministry of Information Industry is a test laboratory accredited by CNAL – Accreditation Certificate of China National Accreditation Board for Laboratories, for the tests indicated in the Certificate No. **L0442**.

Telecommunication Metrology Center of Ministry of Information Industry has been accepted by the CETECOM Competent Body for the EMC test reports since April 2000.

Telecommunication Metrology Center of Ministry of Information Industry is a testing laboratory competent to carry out the tests described in this report.

Telecommunication Metrology Center of Ministry of Information Industry guarantees the reliability of the data presented in this report, which is the result of measurements and tests performed to the item under test on the date and under the conditions stated on the report and is based on the knowledge and technical facilities available at **Telecommunication Metrology Center of Ministry of Information Industry** at the time of execution of the test.

Telecommunication Metrology Center of Ministry of Information Industry is liable to the client for the maintenance by its personnel of the confidentiality of all information related to the item under test and the results of the test.

2 GENERAL CONDITIONS

2.1 This report only refers to the item that has undergone the test.

2.2 This report standalone does not constitute or imply by its own an approval of the product by the certification Bodies or competent Authorities.

2.3 This document is only valid if complete; no partial reproduction can be made without written approval of Telecommunication Metrology Center of Ministry of Information Industry.

2.4 This report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of Telecommunication Metrology Center of Ministry of Information Industry and the Accreditation Bodies, if it applies.

3 ABOUT EUT

3.1 Addressing Information Related to EUT

Table 1: Applicant's details (The Client)

Name or Company	Hisense Communications Co.,Ltd
Address/Post	18,Tuanjie Road,Economics and Technology Development Area,Qingdao,China Hisense Information Property Park
City	Qingdao
Postal Code	266071
Country	China
Telephone	0532- 86016016-5619
Fax	0532-86762066

**Telecommunication Metrology Center
of Ministry of Information Industry**

No. FCC- 2006001

Page 6 of 40

Table 2: Manufacturer's details

Name or Company	Hisense Communications Co.,Ltd
Address/Post	18,Tuanjie Road,Economics and Technology Development Area,Qingdao,China Hisense Information Property Park
City	Qingdao
Postal Code	266071
Country	China
Telephone	0532- 86016016-5619
Fax	0532-86762066

3.2 Equipment under test (EUT)

Model	STARTEL 9000X
Description	CDMA 1X Fixed Wireless Phone
SN number	F56110001172
Hardware status	V2.0
Software status	CEF.6.01.00.IN
Frequency	Tx frequency:824.70 - 848.31 MHz (CDMA) Rx frequency: 869.70 - 893.31 MHz (CDMA)
Antenna	External
Power supply	Battery or Charger (AC Adaptor)
Output power	23.867dBm(0.243W) maximum ERP
Extreme vol. Limits	3.6VDC to 4.3VDC (nominal: 3.9 VDC)
Extreme temp. Tolerance	-30°C to +50°C

3.3 Photographs of Equipment under test

Photographs of MS Hand Telephone Set and Charger are respectively shown in ANNEX B of this test report.

4 LABORATORY ENVIRONMENT

Semi-anechoic chamber (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 26 to 1000 MHz

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
-------------	----------------------------

**Telecommunication Metrology Center
of Ministry of Information Industry**

No. FCC- 2006001

Page 7 of 40

Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber (6.8 meters×3.08 meters×3.53 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 26 to 1000 MHz

5 SUMMARY OF TEST RESULTS

Abbreviations used in this clause:	
P	Pass
NA	Not applicable
F	Fail

Clause	List	Clause in FCC rules	Verdict
1	POWER OUTPUT	22.913(a)	P
2	FREQUENCY STABILITY	2.1055	P
3	OCCUPIED BANDWIDTH	2.1049(h)(i)	P
4	EMISSION BANDWIDTH	22.917(b)	P
5	EMISSION LIMIT	2.1051/22.917	P
6	BAND EDGE COMPLIANCE	22.917(b)	P
7	CONDUCTED SPURIOUS EMISSIONS	2.1057/22.917	P
8	CONDUCTED EMISSIONS	15.107/207	P

**Telecommunication Metrology Center
of Ministry of Information Industry**

No. FCC- 2006001

Page 8 of 40

6 MAIN TEST INSTRUMENTS

NO.	NAME	TYPE	SERIES NUMBER	PRODUCER
1	Test Receiver	ESS	847151/015	R&S
2	Test Receiver	ESI40	831564/002	R&S
3	BiLog Antenna	3142B	9908-1403	EMCO
4	BiLog Antenna	3142B	9908-1405	EMCO
5	Signal Generator	SMT06	831285/005	R&S
6	Signal Generator	SMP04	100070	R&S
7	LISN	ESH2-Z5	829991/012	R&S
8	Spectrum Analyzer	E4440A	MY41000262	Agilent
9	Universal Radio Communication Tester	CMU200	100680	R&S
10	Dual-Ridge Waveguide Horn Antenna	3115	9906-5827	EMCO
11	Dual-Ridge Waveguide Horn Antenna	3116	2663	EMCO
12	Dual-Ridge Waveguide Horn Antenna	3116	2661	EMCO
13	Climatic chamber	SH-241	92003546	ESPEC

7 TEST PERIOD

The performed test started on Mar, 21, 2006 and finished on Mar, 27, 2006.

8 TEST LOCATION

Safety & EMC laboratory of Telecommunication Metrology Center of Ministry of Information Industry.

ANNEX A MEASUREMENT RESULTS

A.1 OUTPUT POWER (§22.913(a))

A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation.

This result contains conducted output power and ERP for the EUT.

In all cases, output power is within the specified limits.

A.1.2 Conducted

A.1.2.1 Method of Measurements

The EUT was set up for the max output power.

The channel power was measured with Agilent Spectrum Analyzer E4440A.


These measurements were done at 3 channels, 1013, 363 and 777 .

Measurement result

EUT1:F56110001172

Channel	Frequency(MHz)	Channel power(dBm)
1013	824.70	24.55
363	835.89	24.15
777	848.31	24.51

Channel 1013



Channel Power

24.55 dBm /2.0000 MHz

Power Spectral Density


-38.46 dBm/Hz

Telecommunication Metrology Center
of Ministry of Information Industry

No. FCC- 2006001

Page 10 of 40

Channel 363




Channel Power

Power Spectral Density

24.15 dBm /2.0000 MHz

-38.86 dBm/Hz

Channel 777



Channel Power

Power Spectral Density

24.51 dBm /2.0000 MHz

-38.50 dBm/Hz

A.1.3 Radiated

A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.

Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 22.913(a) specifies "Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

A.1.3.2 Method of Measurement

1. In an anechoic antenna test chamber, a half-wave dipole antenna for the frequency band of interest is placed at the reference centre of the chamber. An RF Signal source for the frequency band of interest is connected to the dipole with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A known (measured) power (P_{in}) is applied to the input of the dipole, and the power received (P_r) at the chamber's probe antenna is recorded.
2. A "reference path loss" is established as $P_{in} + 2.15 - P_r$.
3. The EUT is substituted for the dipole at the reference centre of the chamber and a scan is performed to obtain the radiation pattern.
4. From the radiation pattern, the co-ordinates where the maximum antenna gain occurs are identified.
5. The EUT is then put into pulse mode at its maximum power level.
6. "Gated mode" power measurements are performed with the receiving antenna placed at the coordinates determined in Step 3 to determine the output power as defined in Rule 24.232 (b) and (c). The "reference path loss" from Step 1 is added to this result.
7. This value is EIRP since the measurement is calibrated using a half-wave dipole antenna of known gain (2.15 dBi) and known input power (P_{in}).
8. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15 \text{ dBi}$.

ERP 22.913(a)

Measurement result

Channel	Frequency(MHz)	ERP(dBm)
1013	824.70	23.741
363	835.89	23.867
777	848.31	22.520

A.2 FREQUENCY STABILITY (§2.1055)

A.2.1 Method of Measurement

In order to measure the carrier frequency, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO

**Telecommunication Metrology Center
of Ministry of Information Industry**

No. FCC- 2006001

Page 12 of 40

COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. EUT was powered via nominal voltage and connected to the CMU200. CMU200 measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing..

A.2.2 Measurement Limit

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ± 0.00025 ($\pm 2.5\text{ppm}$) of the center frequency.

A.2.3 Measurement results

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.6	9	0.011
3.9	8	0.010
4.3	10	0.012

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	9	0.011
-20	10	0.012
-10	11	0.013
0	8	0.010
10	8	0.010
20	9	0.011
30	10	0.012
40	10	0.012
50	12	0.014

A.3 OCCUPIED BANDWIDTH (§2.1049(h)(i))

A.3.1 Occupied Bandwidth Results

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. The table below lists the measured -20dBc BW (99%). Spectrum analyzer plots are included on the following pages.

**Telecommunication Metrology Center
of Ministry of Information Industry**


No. FCC- 2006001

Page 13 of 40


EUT1: F56110001172

Channel	Frequency(MHz)	Occupied Bandwidth (-20dBc BW)(MHz)
1013	824.70	1.379
363	835.89	1.370
777	848.31	1.394


Channel 1013-Occupied Bandwidth (-20dBc BW)



Channel 363-Occupied Bandwidth (-20dBc BW)



Channel 777-Occupied Bandwidth (-20dBc BW)



A.4 EMISSION BANDWIDTH (§22.917(b))

A.4.1 Emission Bandwidth Results

Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Spectrum analyzer plots are included on the following pages.

EUT1: F56110001172


Channel	Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(MHz)
1013	824.70	1.427
363	835.89	1.421
777	848.31	1.422

Telecommunication Metrology Center
of Ministry of Information Industry


No. FCC- 2006001

Page 15 of 40


Channel 1013-Occupied Bandwidth (-26dBc BW)



Channel 363-Occupied Bandwidth (-26dBc BW)



Channel 777-Occupied Bandwidth (-26dBc BW)



A.5 EMISSION LIMIT (§2.1051)

A.5.1 Measurement Method


The site is constructed in accordance with ANSI C63.4 – 1992 requirements and is recognized by the FCC. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 849 MHz. The resolution bandwidth is set 1MHz. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the operating band.

The procedure of radiated spurious emissions is as follows:

a) Pre-calibration


With pre-calibration method, the Radiated Spurious Emissions(RSE) is calculated as,
 $RSE = R_x \text{ (dBuV)} + CL \text{ (dB)} + SA \text{ (dB)} + Gain \text{ (dBi)} - 107 \text{ (dBuV to dBm)}$

The SA is calibrated using following setup.



b) EUT test

EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the test item for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the test item and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1MHz bandwidth.



A.5.2 Measurement Limit

(a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.5.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier


frequencies of the band (824.7 MHz, 835.89 MHz and 848.31 MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the cellular band into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

NOTE: The spurious emissions were done with different settings, using the relevant pre-amplifiers for the relevant frequency ranges. This is the reason that the graphs show different noise levels.

A.5.3.1 RADIATED SPURIOUS EMISSIONS-Channel 1013: 30MHz –1.2GHz

Radiated spurious emission limit :-13dBm.


NOTE: peak above the limit line is the Carrier frequency @ ch-1013



A.5.3.2 RADIATED SPURIOUS EMISSIONS-Channel 363: 30MHz – 1.2GHz

Radiated spurious emission limit :-13dBm.


NOTE: peak above the limit line is the Carrier frequency @ ch-363



A.5.3.3 RADIATED SPURIOUS EMISSIONS-Channel 777: 30MHz – 1.2GHz

Radiated spurious emission limit :-13dBm.

NOTE: peak above the limit line is the Carrier frequency @ ch-777




**Telecommunication Metrology Center
of Ministry of Information Industry**

No. FCC- 2006001

Page 20 of 40


A.5.3.4 RADIATED SPURIOUS EMISSIONS-Channel 1013: 1.2GHz – 9GHz

Radiated spurious emission limit :-13dBm.




A5.3.5 RADIATED SPURIOUS EMISSIONS-Channel 363: 1.2GHz – 9GHz

Radiated spurious emission limit :-13dBm.




A.5.3.6 RADIATED SPURIOUS EMISSIONS-Channel 777: 1.2GHz – 9GHz

Radiated spurious emission limit :-13dBm.




A.5.3.7 RADIATED SPURIOUS EMISSIONS-EUT in Idle Mode: 30MHz – 1.2GHz

Radiated spurious emission limit :-13dBm.



A.5.3.8 RADIATED SPURIOUS EMISSIONS-EUT in Idle Mode: 1.2GHz – 9GHz

Radiated spurious emission limit :-13dBm.



A.6 BAND EDGE COMPLIANCE (§22.917(b))

(a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.



(b) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 100 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power..

**Telecommunication Metrology Center
of Ministry of Information Industry**

No. FCC- 2006001

Page 23 of 40

BAND EDGE BLOCK-Channel 1013





Telecommunication Metrology Center
of Ministry of Information Industry

No. FCC- 2006001

Page 24 of 40

BAND EDGE BLOCK-Channel 777




**Telecommunication Metrology Center
of Ministry of Information Industry**


No. FCC- 2006001

Page 25 of 40

BAND EDGE BLOCK-Channel 310



BAND EDGE BLOCK-Channel 357




Telecommunication Metrology Center
of Ministry of Information Industry


No. FCC- 2006001

Page 26 of 40

BAND EDGE BLOCK-Channel 643



BAND EDGE BLOCK-Channel 690




**Telecommunication Metrology Center
of Ministry of Information Industry**


No. FCC- 2006001

Page 27 of 40

BAND EDGE BLOCK-Channel 740



BAND EDGE BLOCK-Channel 693




A.7.2 Measurement Limit

A.7.3.1 Channel 1013: 10MHz – 10GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



A.7.3.2 Channel 363: 10MHz – 10GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



A.7.3.3 Channel 777: 10MHz – 10GHz

Spurious emission limit –13dBm

NOTE: peak above the limit line is the carrier frequency.




Telecommunication Metrology Center of Ministry of Information Industry

No. FCC- 2006001

Page 32 of 40

A.7.3.4 Idle mode: 10MHz – 10GHz

Spurious emission limit -13dBm.



**Telecommunication Metrology Center
of Ministry of Information Industry**

No. FCC- 2006001

Page 33 of 40


A.8 CONDUCTED EMISSION (§15.107/§207)

A.8.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi -Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

* Decreases with logarithm of the frequency

A.8.2 Measurement result



MEASUREMENT RESULT: "HY2006002_1C_fin QP"

03/23/2006 19:20

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.390000	45.60	10.1	58	12.4	N	FLO
0.405000	37.80	10.1	58	20.0	L1	FLO
0.605000	35.60	10.1	56	20.4	L1	FLO
0.755000	37.90	10.1	56	18.1	N	FLO
1.375000	44.20	10.1	56	11.8	N	GND
1.515000	40.00	10.1	56	16.0	N	GND

ANNEX B PHOTOGRAPH OF EUT

External Photo



Fixed Wireless Phone



Fixed Wireless Phone



Fixed Wireless Phone



Fixed Wireless Phone




Fixed Wireless Phone



Fixed Wireless Phone



Charger (AC/DC Adapter)




Charger (AC/DC Adapter)

Internal Photo



Fixed Wireless Phone Disassembly



Fixed Wireless Phone PCB



Fixed Wireless Phone PCB



Fixed Wireless Phone front view

ANNEX C TEST LAYOUT



Pic1 Conducted Emission



Pic2 Radiated Spurious Emission

END OF REPORT BODY