






Test Mode:802.11n HT40 5270MHz Chain1




Test Mode:802.11n HT40 5310MHz Chain1


Test Mode: 802.11ac VHT40




Test Mode:802.11ac VHT40 5270MHz Chain0



Test Mode:802.11ac VHT40 5310MHz Chain0




Test Mode:802.11ac VHT40 5270MHz Chain1



Test Mode:802.11ac VHT40 5310MHz Chain1

Test Mode: 802.11ac VHT80



Dynamic Frequency Selection


DESCRIPTION OF Master Device

The Master Device is a SKSpruce Technologies Co., Ltd., Indoor Access Point, FCC ID: 2AHTK-WIA3300-20. The rated output power of the Master unit is > 23dBm (EIRP). Therefore the required interference threshold level is -60 dBm.

Radar Waveform Calibration Result


<20MHz / 5320 MHz> Radar Type 0

Radar / DFS detection threshold level and the burst of pulses on the Channel frequency




<80MHz / 5290 MHz> Radar Type 0

Radar / DFS detection threshold level and the burst of pulses on the Channel frequency



Date: 18 AUG. 2022 13:42:39

Data Traffic and Noise Floor Plots





Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period for Client Beacon Test

Frequency	Test Item	Test Result	Limit	Pass/Fail
5320MHz	Channel Move Time	< 10s*	< 10s	Pass
	Channel Closing Transmission Time	200ms	< 260ms	Pass
	Non-Occupancy Period	≥ 30	≥ 30 min	Pass
5290MHz	Channel Move Time	< 10s*	< 10s	Pass
	Channel Closing Transmission Time	200ms	< 260ms	Pass
	Non-Occupancy Period	≥ 30	≥ 30 min	Pass

Note*: We notice clearly that "Channel Move Time" is less than 10s from the figure.
The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 seconds period. The aggregate duration of control signals will not count quiet periods in between transmissions.


Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period for Client Beacon Test Plots





<80MHz / 5290MHz>

Channel Move Time & Channel Closing Transmission Time



Non-Occupancy Period

Note:

Dwell (0.4 ms)= Sweep Time (12000 ms) / Sweep Point Bins (30000)

Channel Closing Transmission Time (200 + 2.4 ms) = 200 + Number of beacon after 200ms(6) X Dwell (0.4 ms) < 260ms

