

**CFR 47 FCC PART 15 SUBPART E
ISED RSS-247 Issue 4**

TEST REPORT

For

wireless smart speaker

MODEL NUMBER: S59

REPORT NUMBER: 4792136987-1-RF-4

ISSUE DATE: July 15, 2026

FCC ID: SBVRM059

IC: 5373A-RM059

Prepared for

**SONOS, INC.
301 COROMAR DR. GOLETA, CA 93117, USA**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

**Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan,
Guangdong, China**

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	June 15, 2026	Initial Issue	Fanny Huang
V1	July 15, 2026	Updated the note description on page 14	Fanny Huang

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
ON TIME AND DUTY CYCLE	ANSI C63.10-2020, Clause 12.2	None; for reporting purposes only.	Pass
6dB AND 26dB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH	KDB 789033 D02 v02r01 Section C.1	FCC Part 15.407 (a)/(e), RSS-247 Issue 4, Clause 7.3.5.2 RSS-Gen Clause 6.7	Pass
CONDUCTED OUTPUT POWER	KDB 789033 D02 v02r01 Section E.3.a (Method PM)/KDB 789033 D02 v02r01 Section E.3.a (Method PM) Section E.2.d (Method SA-2)	FCC 15.407 (a) RSS-247 Clause 7.3	Pass
POWER SPECTRAL DENSITY	KDB 789033 D02 v02r01 Section F	FCC 15.407 (a) RSS-247 Clause 7.3	Pass
AC Power Line Conducted Emission	ANSI C63.10-2020, Clause 6.2.	FCC 15.207 RSS-GEN Clause 8.8	Pass
Radiated Emissions and Band Edge Measurement	KDB 789033 D02 v02r01 Section G.3, G.4, G.5, and G.6	FCC 15.407 (b) FCC 15.209 FCC 15.205 RSS-247 Clause 7.3 RSS-GEN Clause 8.9	Pass
FREQUENCY STABILITY	ANSI C63.10-2020, Clause 6.8	FCC 15.407 (g)	Pass
Antenna Requirement	N/A	FCC 47 CFR Part 15.203/ 15.407(a)(1) (2), RSS-Gen Issue 5, Clause 6.8	Pass

Note:

1. For ISED, this report is also performed according to ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024 standards.
2. For FCC, this report is also performed according to ANSI C63.10-2020 + Cor.1-2023.

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART E, ISED RSS-247 Issue 4> when <Simple Acceptance> decision rule is applied. Decision rule for statement of conformity: The measurement uncertainty is not taken into account for statement of conformity.

CONTENTS

1. ATTESTATION OF TEST RESULTS.....	7
2. TEST METHODOLOGY.....	8
3. FACILITIES AND ACCREDITATION.....	8
4. CALIBRATION AND UNCERTAINTY	9
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>9</i>
4.2. <i>MEASUREMENT UNCERTAINTY</i>	<i>9</i>
5. EQUIPMENT UNDER TEST	10
5.1. <i>DESCRIPTION OF EUT</i>	<i>10</i>
5.2. <i>CHANNEL LIST</i>	<i>11</i>
5.3. <i>MAXIMUM POWER</i>	<i>12</i>
5.4. <i>TEST CHANNEL CONFIGURATION.....</i>	<i>15</i>
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER.....</i>	<i>17</i>
5.6. <i>WORSE CASE CONFIGURATIONS.....</i>	<i>22</i>
5.7. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>24</i>
5.8. <i>SUPPORT UNITS FOR SYSTEM TEST</i>	<i>26</i>
6. MEASURING EQUIPMENT AND SOFTWARE USED.....	27
7. ANTENNA PORT TEST RESULTS	30
7.1. <i>ON TIME AND DUTY CYCLE</i>	<i>30</i>
7.2. <i>6DB AND 26DB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH ...</i>	<i>31</i>
7.3. <i>CONDUCTED OUTPUT POWER</i>	<i>33</i>
7.4. <i>POWER SPECTRAL DENSITY</i>	<i>36</i>
7.5. <i>FREQUENCY STABILITY.....</i>	<i>38</i>
8. RADIATED TEST RESULTS	40
8.1. <i>RESTRICTED BANDEDGE-RA0</i>	<i>49</i>
8.2. <i>RESTRICTED BANDEDGE-RA1</i>	<i>101</i>
8.3. <i>SPURIOUS EMISSIONS(1 GHZ~8 GHZ)-RA0</i>	<i>152</i>
8.4. <i>SPURIOUS EMISSIONS(1 GHZ~8 GHZ)-RA1</i>	<i>178</i>
8.5. <i>SPURIOUS EMISSIONS(8 GHZ~18 GHZ)-RA0</i>	<i>202</i>
8.6. <i>SPURIOUS EMISSIONS(8 GHZ~18 GHZ)-RA1</i>	<i>278</i>
8.7. <i>SPURIOUS EMISSIONS(9 KHZ~30 MHZ)-RA0 WORST CASE.....</i>	<i>356</i>
8.8. <i>SPURIOUS EMISSIONS(18 GHZ~26 GHZ)-RA0 WORST CASE.....</i>	<i>359</i>
8.9. <i>SPURIOUS EMISSIONS(26 GHZ~40 GHZ)-RA0 WORST CASE.....</i>	<i>361</i>

8.10.	SPURIOUS EMISSIONS(30 MHZ~1 GHZ) RA0 WORST CASE.....	363
9.	AC POWER LINE CONDUCTED EMISSION	365
10.	ANTENNA REQUIREMENT	369
11.	TEST DATA-ra0	370
11.1.	APPENDIX A: EMISSION BANDWIDTH.....	370
11.1.1.	Test Result.....	370
11.1.2.	Test Graphs	373
11.2.	APPENDIX B: OCCUPIED CHANNEL BANDWIDTH.....	379
11.2.1.	Test Result.....	379
11.2.2.	Test Graphs	382
11.3.	APPENDIX C: MIN EMISSION BANDWIDTH	383
11.3.1.	Test Result.....	383
11.3.2.	Test Graphs	385
11.4.	APPENDIX D: MAXIMUM CONDUCTED OUTPUT POWER.....	386
11.4.1.	Test Result.....	386
11.4.2.	Test Graphs	389
11.5.	APPENDIX E: MAXIMUM POWER SPECTRAL DENSITY	399
11.5.1.	Test Result.....	399
11.5.2.	Test Graphs	404
11.6.	APPENDIX F: FREQUENCY STABILITY.....	407
11.6.1.	Test Result.....	407
11.7.	APPENDIX G: DUTY CYCLE.....	408
11.7.1.	Test Result.....	408
11.7.2.	Test Graphs	409
12.	TEST DATA-ra1	412
12.1.	APPENDIX A: EMISSION BANDWIDTH.....	412
12.1.1.	Test Result.....	412
12.1.1.	Test Graphs	415
12.2.	APPENDIX B: OCCUPIED CHANNEL BANDWIDTH.....	421
12.2.1.	Test Result.....	421
12.2.1.	Test Graphs	424
12.3.	APPENDIX C: MIN EMISSION BANDWIDTH	425
12.3.1.	Test Result.....	425
12.3.2.	Test Graphs	427
12.4.	APPENDIX D: MAXIMUM CONDUCTED OUTPUT POWER.....	428
12.4.1.	Test Result.....	428
12.4.2.	Test Graphs	431
12.5.	APPENDIX E: MAXIMUM POWER SPECTRAL DENSITY	441
12.5.1.	Test Result.....	441
12.5.2.	Test Graphs	446
12.6.	APPENDIX F: FREQUENCY STABILITY.....	449
12.6.1.	Test Result.....	449

12.7.	<i>APPENDIX G: DUTY CYCLE</i>	450
12.7.1.	Test Result.....	450
12.7.2.	Test Graphs	451

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: SONOS, INC.
Address: 301 COROMAR DR. GOLETA, CA 93117, USA

Manufacturer Information


Company Name: SONOS, INC.
Address: 301 COROMAR DR. GOLETA, CA 93117, USA

EUT Information

EUT Name: wireless smart speaker
Model: S59
Sample Received Date: February 11, 2026
Sample Status: Normal
Sample ID: 9441057
Date of Tested: February 11, 2026 to June 12 2026


APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART E ISED RSS-247 Issue 4	Pass

Prepared By:



Fanny Huang
Project Engineer

Checked By:



Kebo Zhang
Operations Leader

Approved By:



Stephen Guo
Operations Manager

2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART E ISSED RSS-247 Issue 4, ANSI C63.10-2020 + Cor.1-2023, ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024, FCC 47 CFR Part 2, KDB 789033 D02 v02r01, RSS-GEN Issue 5, Amendment 2, KDB 414788 D01 Radiated Test Site v01r01, KDB 662911 D01 Multiple Transmitter Output v02r01.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046. VCCI (Registration No.: C-20202, G-20240, R-20248 and T-20202) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber E, the VCCI registration No. is G-20240 and R-20248 Shielding Room F, the VCCI registration No. is C-20202 and T-20202
---------------------------	---

Note 1:

All tests measurement facilities use to collect the measurement data are located at Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan, Guangdong, China.

Note 2:

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3:

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	4.36 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.47 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 40 GHz)	5.65 dB (1 GHz ~ 18 GHz)
	4.73 dB (18 GHz ~ 26 GHz)
	5.37 dB (26 GHz ~ 40 GHz)
Duty Cycle	±0.028%
Emission Bandwidth and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.766 dB
Maximum Power Spectral Density Level	±1.22 dB
Frequency Stability	±2.76%
Dynamic Frequency Selection	±1.01 dB
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

Remark: For Radiated Emission measurements (200 MHz - 18 GHz), the EUT support table is made of Expanded Polystyrene (EPS). This material is characterized by a low dielectric constant, as recognized in CISPR 16-1-4, to minimize its influence on field strength measurements. This influence has been considered in the uncertainty budget.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	wireless smart speaker
Model	S59
Frequency Range:	5180 MHz to 5240 MHz 5260 MHz to 5320 MHz 5500 MHz to 5720 MHz 5745 MHz to 5825 MHz
DFS Operational mode:	ra0: Slave without radar detection ra1: Master
Type of Modulation:	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax: OFDMA(1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Radio Technology:	IEEE802.11a, IEEE802.11n HT20/HT40, IEEE802.11ac VHT20/VHT40/VHT80, IEEE802.11ax HE20/HE40/HE80
Normal Test Voltage:	AC 120 V, 60 Hz

5.2. CHANNEL LIST

UNII-1 (For Bandwidth=20 MHz)		UNII-1 (For Bandwidth=40 MHz)		UNII-1 (For Bandwidth=80 MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190	42	5210
40	5200	46	5230		
44	5220				
48	5240				

UNII-2A (For Bandwidth=20 MHz)		UNII-2A (For Bandwidth=40 MHz)		UNII-2A (For Bandwidth=80 MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	54	5270	58	5290
56	5280	62	5310		
60	5300				
64	5320				

UNII-2C (For Bandwidth=20 MHz)		UNII-2C (For Bandwidth=40 MHz)		UNII-2C (For Bandwidth=80 MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	102	5510	106	5530
104	5520	110	5550	122	5610
108	5540	118	5590	138	5690
112	5560	126	5630		
116	5580	134	5670		
120	5600	142	5710		
124	5620				
128	5640				
132	5660				
136	5680				
140	5700				
144	5720				

UNII-3 (For Bandwidth=20 MHz)		UNII-3 (For Bandwidth=40 MHz)		UNII-3 (For Bandwidth=80 MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755	155	5775
153	5765	159	5795		
157	5785				
161	5805				
165	5825				

5.3. MAXIMUM POWER

ra0:

UNII-1 BAND(FCC&ISED)

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)	Max Average EIRP (dBm)
a	5150 ~ 5250	13.28	16.48
n HT20		13.82	17.02
n HT40		15.93	19.13
ac VHT80		18.74	21.94
ax HE20		14.05	17.25
ax HE40		16.30	19.50
ax HE80		17.30	20.50

UNII-2A BAND(FCC&ISED)

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)	Max Average EIRP (dBm)
a	5250 ~ 5350	19.32	22.42
n HT20		18.78	21.88
n HT40		19.26	22.36
ac VHT80		19.64	22.74
ax HE20		19.31	22.41
ax HE40		19.02	22.12
ax HE80		19.61	22.71

UNII-2C BAND(FCC&ISED)

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)	Max Average EIRP (dBm)
a	5470 ~ 5725	20.05	22.85
n HT20		19.48	22.28
n HT40		19.32	22.12
ac VHT80		20.39	23.19
ax HE20		19.80	22.60
ax HE40		19.67	22.47
ax HE80		20.31	23.11

UNII-3 BAND(FCC&ISED)

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)	Max Average EIRP (dBm)
a	5725 ~ 5850	23.48	26.08
n HT20		23.37	25.97
n HT40		23.60	26.20
ac VHT80		20.24	22.84
ax HE20		23.40	26.00
ax HE40		22.99	25.59
ax HE80		20.03	22.63

ra1:

UNII-1 BAND(FCC&ISED)

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)	Max Average EIRP (dBm)
a	5150 ~ 5250	13.62	16.82
n HT20		13.61	16.81
n HT40		16.21	19.41
ac VHT80		15.70	18.90
ax HE20		13.92	17.12
ax HE40		16.27	19.47
ax HE80		17.27	20.47

UNII-2A BAND(FCC&ISED)

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)	Max Average EIRP (dBm)
a	5250 ~ 5350	18.74	21.84
n HT20		18.70	21.80
n HT40		18.49	21.59
ac VHT80		18.03	21.13
ax HE20		18.54	21.64
ax HE40		18.55	21.65
ax HE80		17.54	20.64

UNII-2C BAND(FCC&ISED)

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)	Max Average EIRP (dBm)
a	5470 ~ 5725	19.09	21.89
n HT20		19.04	21.84
n HT40		19.30	22.10
ac VHT80		17.74	20.54
ax HE20		18.17	20.97
ax HE40		19.40	22.20
ax HE80		18.84	21.64

UNII-3 BAND(FCC&ISED)

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)	Max Average EIRP (dBm)
a	5725 ~ 5850	22.54	25.14
n HT20		22.73	25.33
n HT40		22.99	25.59
ac VHT80		20.89	23.49
ax HE20		22.65	25.25
ax HE40		23.09	25.69
ax HE80		20.61	23.21

Note:

1. Maximum conducted output power = measured value + cable loss (provided by UL) + cable loss (provided by UL)
2. Maximum EIRP = maximum conducted output power + antenna gain

5.4. TEST CHANNEL CONFIGURATION

UNII-1 Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 36(Low Channel), CH 40(MID Channel), CH 48(High Channel)	5180 MHz, 5200 MHz, 5240 MHz
802.11n HT20	CH 36(Low Channel), CH 40(MID Channel), CH 48(High Channel)	5180 MHz, 5200 MHz, 5240 MHz
802.11n HT40	CH 38(Low Channel), CH 46(High Channel)	5190 MHz, 5230 MHz
802.11ac VHT80	CH 42(Low Channel)	5210 MHz
802.11ax HE20	CH 36(Low Channel), CH 40(MID Channel), CH 48(High Channel)	5180 MHz, 5200 MHz, 5240 MHz
802.11ax HE40	CH 38(Low Channel), CH 46(High Channel)	5190 MHz, 5230 MHz
802.11ax HE80	CH 42(Low Channel)	5210 MHz

UNII-2A Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 52(Low Channel), CH 56(MID Channel), CH 64(High Channel)	5260 MHz, 5280 MHz, 5320 MHz
802.11n HT20	CH 52(Low Channel), CH 56(MID Channel), CH 64(High Channel)	5260 MHz, 5280 MHz, 5320 MHz
802.11n HT40	CH 54(Low Channel), CH 62(High Channel)	5270 MHz, 5310 MHz
802.11ac VHT80	CH 58(Low Channel)	5290 MHz
802.11ax HE20	CH 52(Low Channel), CH 56(MID Channel), CH 64(High Channel)	5260 MHz, 5280 MHz, 5320 MHz
802.11ax HE40	CH 54(Low Channel), CH 62(High Channel)	5270 MHz, 5310 MHz
802.11ax HE80	CH 58(Low Channel)	5290 MHz

UNII-2C Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 100(Low Channel), CH 116(MID Channel), CH 140(High Channel)	5500 MHz, 5580 MHz, 5700 MHz
802.11n HT20	CH 100(Low Channel), CH 116(MID Channel), CH 140(High Channel)	5500 MHz, 5580 MHz, 5700 MHz
802.11n HT40	CH 102(Low Channel), CH 110(MID Channel), CH 134(High Channel)	5510 MHz, 5550 MHz, 5670 MHz
802.11ac VHT80	CH 102(Low Channel), CH 122(High Channel)	5530 MHz, 5610 MHz
802.11ax HE20	CH 100(Low Channel), CH 116(MID Channel), CH 140(High Channel)	5500 MHz, 5580 MHz, 5700 MHz
802.11ax HE40	CH 102(Low Channel), CH 110(MID Channel), CH 134(High Channel)	5510 MHz, 5550 MHz, 5670 MHz
802.11ax HE80	CH 102(Low Channel), CH 122(High Channel)	5530 MHz, 5610 MHz

UNII-3 Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 149(Low Channel), CH 157(MID Channel), CH 165(High Channel)	5745 MHz, 5785 MHz, 5825 MHz
802.11n HT20	CH 149(Low Channel), CH 157(MID Channel), CH 165(High Channel)	5745 MHz, 5785 MHz, 5825 MHz
802.11n HT40	CH 151(Low Channel), CH 159(High Channel)	5755MHz, 5795MHz
802.11ac VHT80	CH 155(Low Channel)	5775 MHz
802.11ax HE20	CH 149(Low Channel), CH 157(MID Channel), CH 165(High Channel)	5745 MHz, 5785 MHz, 5825 MHz
802.11ax HE40	CH 151(Low Channel), CH 159(High Channel)	5755MHz, 5795MHz
802.11ax HE80	CH 155(Low Channel)	5775 MHz

Straddle Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 144	5720 MHz
802.11n HT20	CH 144	5720 MHz
802.11n HT40	CH 142	5710 MHz
802.11ac VHT80	CH 138	5690 MHz
802.11ax HE20	CH 144	5720 MHz
802.11ax HE40	CH 142	5710 MHz
802.11ax HE80	CH 138	5690 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter	
Test Software	SonosComplianceGUI

ra0:

Mode	Frequency (MHz)	Power setting
		ANT1 & ANT2
802.11a	5180	9
	5200	8.5
	5240	9
	5260	15
	5280	15
	5320	15
	5500	14.5
	5580	15.5
	5700	14.5
	5720-2C	14.5
	5720-3	14.5
	5745	20
	5785	20
	5825	20
802.11n 20M	5180	10
	5200	9.5
	5240	10
	5260	15
	5280	15
	5320	15
	5500	15
	5580	15.5
	5700	15
	5720-2C	15.5
	5720-3	15.5
	5745	20
	5785	20
	5825	20
802.11n 40M	5190	12
	5230	12
	5270	15
	5310	15

	5510	13
	5550	15.5
	5670	15.5
	5710-2C	15.5
	5710-3	15.5
	5755	20
	5795	20
802.11ac 80M	5210	14
	5290	15
	5530	13
	5610	15.5
	5690-2C	15.5
	5690-3	15.5
	5775	16
802.11ax 20M	5180	10
	5200	9.5
	5240	10
	5260	15
	5280	15
	5320	15
	5500	14.5
	5580	15.5
	5700	15.5
	5720-2C	15.5
	5720-3	15.5
	5745	20
	5785	20
	5825	20
802.11ax 40M	5190	12
	5230	12
	5270	15
	5310	14
	5510	12
	5550	15.5
	5670	15.5
	5710-2C	15.5
	5710-3	15.5
	5755	19
	5795	20
802.11ax 80M	5210	12.5
	5290	15

	5530	12.5
	5610	15.5
	5690-2C	15.5
	5690-3	15.5
	5775	16

ra1:

Mode	Frequency (MHz)	Power setting
		ANT1 & ANT2
802.11a	5180	10
	5200	10
	5240	10
	5260	14
	5280	14
	5320	14
	5500	15
	5580	15
	5700	15
	5720-2C	15
	5720-3	15
	5745	20
	5785	20
	5825	20
802.11n 20M	5180	10
	5200	10
	5240	10
	5260	14
	5280	14
	5320	14
	5500	15
	5580	15
	5700	15
	5720-2C	15
	5720-3	15
	5745	20
	5785	20
	5825	20
802.11n 40M	5190	12.5
	5230	12.5
	5270	14

	5310	14
	5510	15
	5550	15
	5670	15
	5710-2C	15
	5710-3	15
	5755	20
	5795	20
802.11ac 80M	5210	13
	5290	15
	5530	15
	5610	15
	5690-2C	15
	5690-3	15
	5775	18
802.11ax 20M	5180	10
	5200	10
	5240	10
	5260	14
	5280	14
	5320	14
	5500	15
	5580	15
	5700	15
	5720-2C	15
	5720-3	15
	5745	20
	5785	20
	5825	20
802.11ax 40M	5190	12.5
	5230	12
	5270	14
	5310	14
	5510	15
	5550	15
	5670	15
	5710-2C	15
	5710-3	15
	5755	20
	5795	20
	5210	13.5

802.11ax 80M	5290	14
	5530	14
	5610	15
	5690-2C	15
	5690-3	15
	5775	17.5

5.6. WORSE CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst case Data Rates declared by the customer:

802.11a 20 mode: 6 Mbps
802.11n HT20 mode: MCS0
802.11n HT40 mode: MCS0
802.11ac VHT20 mode: MCS0
802.11ac VHT40 mode: MCS0
802.11ac VHT80 mode: MCS0
802.11ax HE20 mode: MCS0
802.11ax HE40 mode: MCS0
802.11ax HE80 mode: MCS0

All modes support MIMO mode.

802.11ac VHT20, 802.11ac VHT40 modes were covered by 802.11n HT20, n HT40 modes.

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

Conducted output power, power spectral density tests separately on each port with all supported MIMO port combinations.

Radiated unwanted emissions tests were performed with the MIMO modes. These were found to be the worst modulation scheme with regards to emissions after preliminary investigations and, as this mode emits the highest conducted output power level, it was deemed to be the worst case.

802.11ax HE20/HE40/HE80 support Full RU and partial RU tone. According to Preliminary Investigation, the power and PSD of 802.11ax HE20 Partial RU (26T, 52T, 106T, SU) were lower than the Full RU, the power and PSD of 802.11ax HE40 Partial RU (26T, 52T, 106T, 242T, SU) were lower than the Full RU, the power and PSD of 802.11ax HE80 Partial RU (26T, 52T, 106T, 242T, 484T, SU) were lower than the Full RU, and there was no worst band edge and spurious in Partial RU. It was determined that Full RU modes were the worst case over Partial RU Tone in every instance. Therefore, Full RU modes were tested to represent Partial RU modes as the worst-case scenario.

The radio utilizes 4 antennas for diversity, ANT1, ANT2, ANT3 and ANT4. All these 4 antennas have the same power setting and tune up power level. UNII-1 and UNII-2A support 2 antenna combinations: ANT1+ANT2, ANT3+ANT4. UNII-2C and UNII-3 only support 1 antenna combinations: ANT1+ANT2 According to Preliminary Investigation, we separately tested the worst axis of each combination and found that ANT1 and ANT2 for UNII-1 and UNII-2A was the worst group and selected for final test.

Based on ANSI C63.10-2020 section 5.6.2.2(b), for Harmonics and Spurious Emissions, all modes have been tested, only the worst-case power and PSD modes were recorded in the report.

Worst case mode for ra0:

Band	Worst Power mode-OFDM & OFDMA	Worst PSD mode-OFDM & OFDMA
UNII-1	802.11ac VHT80 & 802.11ax HE80	802.11n HT20 & 802.11ax HE20
UNII-2A	802.11ac VHT80 & 802.11ax HE80	802.11a & 802.11ax HE20
UNII-2C	802.11ac VHT80 & 802.11ax HE80	802.11a & 802.11ax HE20
UNII-3	802.11n HT40 & 802.11ax HE20	802.11a & 802.11ax HE20

Worst case mode for ra1:

Band	Worst Power mode-OFDM & OFDMA	Worst PSD mode-OFDM & OFDMA
UNII-1	802.11n HT40 & 802.11ax HE80	802.11n HT40 & 802.11ax HE40
UNII-2A	802.11a & 802.11ax HE40	802.11a & 802.11ax HE20
UNII-2C	802.11n HT40 & 802.11ax HE40	802.11a & 802.11ax HE20
UNII-3	802.11n HT40 & 802.11ax HE40	802.11a & 802.11ax HE20

The EUT has 2 radio modules, the technologies of these 2 modules are as follows:

Module	Technology	Band	Antenna	Support modes	Partial RU supported (OFDMA)
ra0	BLE	2.4GHz	ANT3	BLE 1Mbps/2Mbps	/
ra0	BT	2.4GHz	ANT3	BR: DH1/3/5 EDR: 2DH1/3/5, 3DH1/3/5	/
ra0-slave	WiFi	2.4GHz	ANT1+ANT2	802.11 b/g/n HT20/ax HE20	Yes
		5GHz(Sub-band 1)	ANT1+ANT2	802.11a, n HT20/40, ac VHT20/40/80, ax HE20/40/80	Yes
		5GHz(Sub-band 2)	ANT1+ANT2	802.11a, n HT20/40, ac VHT20/40/80, ax HE20/40/80	Yes
		5GHz(Sub-band 3)	ANT1+ANT2	802.11a, n HT20/40, ac VHT20/40/80, ax HE20/40/80	Yes
		5GHz(Sub-band 1)	ANT3+ANT4	802.11a, n HT20/40, ac VHT20/40/80, ax HE20/40/80	Yes
		5GHz(Sub-band 1)	ANT3+ANT4	802.11a, n HT20/40, ac VHT20/40/80, ax HE20/40/80	Yes
		6GHz	ANT3+ANT4	802.11a, ax HE20/40/80	Yes
ra1-master	WiFi	5GHz(Sub-band 1)	ANT1+ANT2	802.11a, n HT20/40, ac VHT20/40/80, ax HE20/40/80	No
		5GHz(Sub-band 2)	ANT1+ANT2	802.11a, n HT20/40, ac VHT20/40/80, ax HE20/40/80	No
		5GHz(Sub-band 3)	ANT1+ANT2	802.11a, n HT20/40, ac VHT20/40/80, ax HE20/40/80	No
		5GHz(Sub-band 1)	ANT3+ANT4	802.11a, n HT20/40, ac VHT20/40/80, ax HE20/40/80	No
		5GHz(Sub-band 1)	ANT3+ANT4	802.11a, n HT20/40, ac VHT20/40/80, ax HE20/40/80	No
		6GHz	ANT3+ANT4	802.11a, ax HE20/40/80	No

5.7. DESCRIPTION OF AVAILABLE ANTENNAS

The antenna(s) gain and type, as provided by the manufacturer are as follows.

Antenna	Frequency (MHz)	Antenna type	MAX Antenna Gain (dBi)
1	5150-5250	PCB Antenna	3.4
2	5150-5250	PCB Antenna	4.6
3	5150-5250	PCB Antenna	3.8
4	5150-5250	PCB Antenna	2.6

Antenna	Frequency (MHz)	Antenna type	MAX Antenna Gain (dBi)
1	5250-5350	PCB Antenna	3.5
2	5250-5350	PCB Antenna	4.5
3	5250-5350	PCB Antenna	4.4
4	5250-5350	PCB Antenna	2.7

Antenna	Frequency (MHz)	Antenna type	MAX Antenna Gain (dBi)
1	5470-5725	PCB Antenna	3.4
2	5470-5725	PCB Antenna	4.3

Antenna	Frequency (MHz)	Antenna type	MAX Antenna Gain (dBi)
1	5725-5850	PCB Antenna	3.8
2	5725-5850	PCB Antenna	4.0

Antenna Combination:

Combination Antenna	Frequency (MHz)	MAX Correlated Antenna Gain (dBi)	MAX Uncorrelated Antenna Gain (dBi)
1+2	5150-5250	6.2	3.2
3+4	5150-5250	5.3	2.3

Combination Antenna	Frequency (MHz)	MAX Correlated Antenna Gain (dBi)	MAX Uncorrelated Antenna Gain (dBi)
1+2	5250-5350	6.1	3.1
3+4	5250-5350	5.6	2.7

Combination Antenna	Frequency (MHz)	MAX Correlated Antenna Gain (dBi)	MAX Uncorrelated Antenna Gain (dBi)
1+2	5470-5725	5.7	2.8

Combination Antenna	Frequency (MHz)	MAX Correlated Antenna Gain (dBi)	MAX Uncorrelated Antenna Gain (dBi)
1+2	5725-5850	5.6	2.6

Note: The antenna gain is provided by client.

IEE Std. 802.11	Transmit and Receive Mode	Description
802.11a	☒ 2TX, 2RX	ANT 1 & ANT 2 or ANT 3 & ANT4 can be used as transmitting/receiving antenna.
802.11n HT20	☒ 2TX, 2RX	ANT 1 & ANT 2 or ANT 3 & ANT4 can be used as transmitting/receiving antenna.
802.11n HT40	☒ 2TX, 2RX	ANT 1 & ANT 2 or ANT 3 & ANT4 can be used as transmitting/receiving antenna.
802.11ac VHT20	☒ 2TX, 2RX	ANT 1 & ANT 2 or ANT 3 & ANT4 can be used as transmitting/receiving antenna.
802.11ac VHT40	☒ 2TX, 2RX	ANT 1 & ANT 2 or ANT 3 & ANT4 can be used as transmitting/receiving antenna.
802.11ac VHT80	☒ 2TX, 2RX	ANT 1 & ANT 2 or ANT 3 & ANT4 can be used as transmitting/receiving antenna.
802.11ax HE20	☒ 2TX, 2RX	ANT 1 & ANT 2 or ANT 3 & ANT4 can be used as transmitting/receiving antenna.
802.11ax HE40	☒ 2TX, 2RX	ANT 1 & ANT 2 or ANT 3 & ANT4 can be used as transmitting/receiving antenna.
802.11ax HE80	☒ 2TX, 2RX	ANT 1 & ANT 2 or ANT 3 & ANT4 can be used as transmitting/receiving antenna.

5.8. SUPPORT UNITS FOR SYSTEM TEST

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remarks
1	Laptop	Lenovo	E42-80	R303U5AG
2	Power adapter	/	RD1200500-123GB	Input: AC 100-240V, 50/60Hz, 250mA MAX Output: DC 12V, 0.5A
3	Ethernet switch	H3C	/	Rating: DC 12V, 0.5A
4	Hub	SONOS	SD-02	/

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	Network cable*2	/	/	2.0	/
2	HDMI cable	/	/	1.5	/


ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/

TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

SETUP DIAGRAM FOR TESTS



6. MEASURING EQUIPMENT AND SOFTWARE USED

R&S TS 8997 Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Dec.26,2025	Dec.25,2026
Vector Signal Generator	R&S	SMBV100A	261637	Sep.12, 2025	Sep.11, 2026
Signal Generator	R&S	SMB100A	178553	Sep.12, 2025	Sep.11, 2026
Signal Analyzer	R&S	FSV40	101118	Sep.12, 2025	Sep.11, 2026
Software					
Description		Manufacturer	Name	Version	
For R&S TS 8997 Test System		Rohde & Schwarz	EMC 32	10.60.10	
Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.12, 2025	Sep.11, 2026
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Sep.12, 2025	Sep.11, 2026
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Sep.12, 2025	Sep.11, 2026
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Sep.12, 2025	Sep.11, 2026
DC power supply	TSSTAKASAGO	ZX-400L	409150160137	Sep.12, 2025	Sep.11, 2026
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Sep.12, 2025	Sep.11, 2026
Attenuator	Aglient	8495B	2814a12853	Sep.12, 2025	Sep.11, 2026
RF Control Unit	Tonscend	JS0806-2	23B80620666	Dec.26,2025	Dec.25,2026
Software					
Description	Manufacturer	Name		Version	
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System		V3.2.22	

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Sep.12, 2025	Sep.11, 2026
Two-Line V-Network	R&S	ENV216	101983	Sep.12, 2025	Sep.11, 2026
Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Sep.12, 2025	Sep.11, 2026
Software					
Description			Manufacturer	Name	Version
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1

Radiated Emissions(Below 1G)					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Sep.12, 2025	Sep.11, 2026
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	June 28, 2024	June.27 2027
Preamplifier	HP	8447D	2944A09099	Sep.12, 2025	Sep.11, 2026
Loop antenna	Schwarzbeck	1519B	00008	Dec.09, 2024	Dec.08, 2027
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1

Radiated Emissions(Above 1G)					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Signal Analyzer	R&S	FSV40	101117	Sep.12, 2025	Sep.11, 2026
Preamplifier	TDK	PA-02-001-3000	TRS-302-00051	Sep.12, 2025	Sep.11, 2026
Horn Antenna	ETS-Lindgren	3117	00213191	Jan.29,2026	Jan.28,2029
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Sep.12, 2025	Sep.11, 2026
High Gain Horn Antenna	Schwarzbeck	BBHA-9170	697	Jun. 30, 2024	Jun. 29, 2027
Preamplifier	TDK	PA-02-2	TRS-307-00002	Sep.12, 2025	Sep.11, 2026
Preamplifier	TDK	PA-02-3	TRS-308-00002	Sep.12, 2025	Sep.11, 2026
Highpass Filter	Wainwright	WHKX10-5850-6500-1800-40SS	4	Sep.12, 2025	Sep.11, 2026

Band Reject Filter	Wainwright	WRCJV12-5695-5725-5850-5880-40SS	4	Sep.12, 2025	Sep.11, 2026
Band Reject Filter	Wainwright	WRCJV20-5120-5150-5350-5380-60SS	2	Sep.12, 2025	Sep.11, 2026
Band Reject Filter	Wainwright	WRCJV20-5440-5470-5725-5755-60SS	1	Sep.12, 2025	Sep.11, 2026
Software					
Description	Manufacturer	Name		Version	
Test Software for Radiated Emission	Tonscend	JS32-RE		5.0.0	
Test Software for Radiated Emissions	Farad	EZ-EMC		Ver. UL-3A1	

Other Instrument					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Temperature humidity probe	OMEGA	ITHX-SD-5	18470007	Sep.16, 2025	Sep.15, 2026
Barometer	Yiyi	Baro	N/A	Sep.19, 2025	Sep.18, 2026
Attenuator	Agilent	8495B	2814a12853	Sep.12, 2025	Sep.11, 2026

7. ANTENNA PORT TEST RESULTS

7.1. ON TIME AND DUTY CYCLE

LIMITS


None; for reporting purposes only.

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.B.

The zero-span mode on a spectrum analyzer or EMI receiver, if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW $\geq$ EBW if possible; otherwise, set RBW to the largest available value. Set VBW $\geq$ RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$, where T is defined in II.B.1.a), and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

TEST SETUP



TEST ENVIRONMENT

Temperature	25.7°C	Relative Humidity	62.1%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

TEST DATE / ENGINEER

Test Date	February 27, 2026	Test By	Bairong Liu
-----------	-------------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix G

7.2. 6DB AND 26DB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

FCC 47 CFR Part15 Subpart E ISED RSS-247 ISSUE 4		
Test Item	Limit	Frequency Range (MHz)
26 dB Emission Bandwidth	For reporting purposes only.	5150 ~ 5250
26 dB Emission Bandwidth	For reporting purposes only.	5250 ~ 5350
26 dB Emission Bandwidth	For reporting purposes only.	5470 ~ 5725
6 dB Emission Bandwidth	The minimum 6 dB emission bandwidth shall be 500 kHz.	5725 ~ 5850
99 % Occupied Bandwidth	For reporting purposes only.	5150 ~ 5825 (For ISED)

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.C1. for 26 dB Emission Bandwidth; section II.C2. for 6 dB Emission Bandwidth; section II.D. for 99 % Occupied Bandwidth.

Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	For 6 dB Emission Bandwidth: RBW=100 kHz For 26 dB Emission bandwidth: approximately 1 % of the EBW. For 99 % Occupied Bandwidth: approximately 1 % ~ 5 % of the OBW.
VBW	For 6 dB Bandwidth: $\geq 3 \times \text{RBW}$ For 26 dB Bandwidth: $> 3 \times \text{RBW}$ For 99 % Bandwidth: $> 3 \times \text{RBW}$
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6/26 dB relative to the maximum level measured in the fundamental emission.

Calculation for 99 % Bandwidth of UNII-2C and UNII-3 Straddle Channel:

For Example: Fundamental Frequency: 5720 MHz

99 % OBW: 21.00 MHz

Turning Frequency: 5725 MHz

99 % Bandwidth of UNII-2C Band Portion = $(5725 - (5720 - (21.00/2))) = 15.50 \text{ MHz}$

99 % Bandwidth of UNII-3 Band Portion = $(5720 + (21.00/2) - 5725) = 5.50 \text{ MHz}$

Calculation for 26 dB Bandwidth of UNII-2C Straddle Channel:

For Example: Fundamental frequency: 5720 MHz

26 dB BW: 20.00 MHz

FL: 5710.16 MHz

FH: 5730.16 MHz

Turning Frequency: 5725 MHz

26 dB Bandwidth of UNII-2C Band Portion = $5725 - 5710.16 = 14.84$ MHz**Calculation for 6dB Bandwidth of UNII-3 Straddle Channel:**


For Example: Fundamental frequency: 5720 MHz

6 dB BW: 16.44 MHz

FL: 5711.76 MHz

FH: 5728.2 MHz

Turning Frequency: 5725 MHz

6 dB Bandwidth of UNII-3 band Portion = $5728.2 - 5725 = 3.2$ MHz**TEST SETUP****TEST ENVIRONMENT**

Temperature	25.7°C	Relative Humidity	62.1%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

TEST DATE / ENGINEER

Test Date	February 27, 2026	Test By	Bairong Liu
-----------	-------------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix A&B

7.3. CONDUCTED OUTPUT POWER

LIMITS

FCC 47 CFR Part15 Subpart E		
Test Item	Limit	Frequency Range (MHz)
Conducted Output Power	☐ Outdoor Access Point: 1 W (30 dBm) ☒ Indoor Access Point: 1 W (30 dBm) ☐ Fixed Point-To-Point Access Points: 1 W (30 dBm) ☒ Client Devices: 250 mW (24 dBm)	5150 ~ 5250
	Shall not exceed the lesser of 250 mW (24dBm) or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz.	5250 ~ 5350 5470 ~ 5725
	Shall not exceed 1 Watt (30 dBm).	5725 ~ 5850

ISED RSS-247 ISSUE 4		
Test Item	Limit	Frequency Range (MHz)
Conducted Output Power or e.i.r.p.	The maximum e.i.r.p. shall not exceed 200 mW (23 dBm) or $10 + 10 \log_{10} B$, dBm, whichever power is less. B is the 99 % emission bandwidth in megahertz.	5150 ~ 5250
	a. The maximum conducted output power shall not exceed 250 mW (24 dBm) or $11 + 10 \log_{10} B$ dBm, whichever is less. b. The maximum e.i.r.p. shall not exceed 1.0 W (30 dBm) or $17 + 10 \log_{10} B$ dBm, whichever is less. B is the 99 % emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.	5250 ~ 5350 5470 ~ 5725
	Shall not exceed 1 Watt (30 dBm). The e.i.r.p. shall not exceed 4 W	5725 ~ 5850

Note:

The above limits are based upon the maximum antenna gain does not exceed 6 dBi.
If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.E.

Method SA-2 (trace averaging across ON and OFF times of the EUT transmissions, followed by duty cycle correction.):

- Measure the duty cycle D of the transmitter output signal.
- Set span to encompass the entire 26 dB EBW or 99% OBW of the signal.


- (c) Set RBW = 1 MHz.
- (d) Set VBW $\geq$ 3 MHz.
- (e) Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- (f) Sweep time = auto.
- (g) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- (h) Do not use sweep triggering. Allow the sweep to “free run.”
- (i) Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the ON and OFF periods of the transmitter.
- j) Compute power by integrating the spectrum across the 26 dB EBW or 99% OBW of the signal using the instrument’s band power measurement function with band limits set equal to the EBW or OBW band edges. If the instrument does not have a band power function, then sum the spectrum levels (in power units) at 1 MHz intervals extending across the 26 dB EBW or 99% OBW of the spectrum.
- k) Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured power to compute the average power during the actual transmission times (because the measurement represents an average over both the ON and OFF times of the transmission). For example, add $[10 \log (1 / 0.25)] = 6 \text{ dB}$ if the duty cycle is 25%.

Method PM (Measurement using an RF average power meter):

- (i) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the following conditions are satisfied:
 - a. The EUT is configured to transmit continuously or to transmit with a constant duty cycle.
 - b. At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.
 - c. The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- (ii) If the transmitter does not transmit continuously, measure the duty cycle, x, of the transmitter output signal as described in II.B.
- (iii) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
- (iv) Adjust the measurement in dBm by adding $10 \log (1/x)$ where x is the duty cycle (e.g., $10 \log (1/0.25)$ if the duty cycle is 25 %).

Note: Method SA-2 was used for straddle channel output power test, and Method PM was used for testing rest channels

TEST SETUP



TEST ENVIRONMENT

Temperature	25.7°C	Relative Humidity	62.1%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

TEST DATE / ENGINEER

Test Date	February 27, 2026	Test By	Bairong Liu
-----------	-------------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix D

7.4. POWER SPECTRAL DENSITY

LIMITS

FCC 47 CFR Part15 Subpart E		
Test Item	Limit	Frequency Range (MHz)
Power Spectral Density	☐ Outdoor Access Point: 17 dBm/MHz ☒ Indoor Access Point: 17 dBm/MHz ☐ Fixed Point-To-Point Access Points: 17 dBm/MHz ☒ Client Devices: 11 dBm/MHz	5150 ~ 5250
	11 dBm/MHz	5250 ~ 5350 5470 ~ 5725
	30 dBm/500kHz	5725 ~ 5850

ISED RSS-247 ISSUE 4		
Test Item	Limit	Frequency Range (MHz)
Power Spectral Density	The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.	5150 ~ 5250
	The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.	5250 ~ 5350 5470 ~ 5725
	30 dBm / 500 kHz	5725 ~ 5850

Note:

The above limits are based upon the maximum antenna gain does not exceed 6 dBi.

If transmitting antennas of directional gain greater than 6 dBi are used, maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.F.

Connect the EUT to the spectrum analyzer and use the following settings:

For U-NII-1, U-NII-2A and U-NII-2C band:

Center Frequency	The center frequency of the channel under test
Detector	RMS
RBW	1 MHz
VBW	$\geq 3 \times \text{RBW}$
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Average
Sweep time	Auto


For U-NII-3:

Center Frequency	The center frequency of the channel under test
Detector	RMS
RBW	500 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Average
Sweep time	Auto

Allow trace to fully stabilize and use the peak search function on the instrument to find the peak of the spectrum and record its value.

Add $10 \log (1/x)$, where x is the duty cycle, to the peak of the spectrum, the result is the Maximum PSD over 1 MHz / 500 kHz reference bandwidth.

TEST SETUP



TEST ENVIRONMENT

Temperature	25.7°C	Relative Humidity	62.1%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

TEST DATE / ENGINEER

Test Date	February 27, 2026	Test By	Bairong Liu
-----------	-------------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix E

7.5. FREQUENCY STABILITY

LIMITS

The frequency of the carrier signal shall be maintained within band of operation.

TEST PROCEDURE

1. The EUT was placed inside an environmental chamber as the temperature in the chamber was varied between 0 °C ~ 40 °C (declared by customer).
2. The temperature was incremented by 10 °C intervals and the unit allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded.
3. The primary supply voltage is varied from 85 % to 115 % of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Connect the EUT to the spectrum analyzer and use the following settings:


Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	10 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Max hold
Sweep time	Auto

4. While maintaining a constant temperature inside the environmental chamber, turn the EUT on and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized.
5. Allow the trace to stabilize, find the peak value of the power envelope and record the frequency, then calculated the frequency drift.

TEST ENVIRONMENT

	Normal Test Conditions	Extreme Test Conditions
Relative Humidity	20 % ~ 75 %	/
Atmospheric Pressure	100 kPa ~ 102 kPa	/
Temperature	T _N (Normal Temperature): 25.1 °C	T _L (Low Temperature): 0 °C
		T _H (High Temperature): 40 °C
Supply Voltage	V _N (Normal Voltage): AC 120 V, 60 Hz	V _L (Low Voltage): AC 102 V
		V _H (High Voltage): AC 138 V

TEST SETUP



TEST ENVIRONMENT

Temperature	25.7°C	Relative Humidity	62.1%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

TEST DATE / ENGINEER

Test Date	February 27, 2026	Test By	Bairong Liu
-----------	-------------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix F

8. RADIATED TEST RESULTS

LIMITS

Refer to FCC 47 CFR §15.205, §15.209 and §15.407 (b).

Refer to ISSED RSS-GEN Clause 8.9, Clause 8.10 and ISSED RSS-247 7.3.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISSED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (μA/m)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

ISED Restricted bands refer to ISED RSS-GEN Clause 8.10

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC 47 CFR §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

Limits of unwanted/undesirable emission out of the restricted bands refer to FCC 47 CFR §15.407 (b) and ISSED RSS-247 7.3.

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1GHz)		
Frequency Range (MHz)	EIRP Limit	Field Strength Limit (dBuV/m) at 3 m
5150~5250 MHz	PK: -27 (dBm/MHz)	PK:68.2(dBμV/m)
5250~5350 MHz		
5470~5725 MHz		
5725~5850 MHz	PK: -27 (dBm/MHz) *1 PK: 10 (dBm/MHz) *2 PK: 15.6 (dBm/MHz) *3 PK: 27 (dBm/MHz) *4	PK: 68.2(dBμV/m) *1 PK: 105.2 (dBμV/m) *2 PK: 110.8(dBμV/m) *3 PK: 122.2 (dBμV/m) *4
Note: *1 beyond 75 MHz or more above of the band edge. *2 below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above. *3 below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above. *4 from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.		

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the

applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.

7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1 GHz

The setting of the spectrum analyzer

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.G.3 ~ II.G.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

For Restricted Bandedge:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. PK=Peak: Peak detector.
4. AV=Average: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.1.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes have been tested, but only the worst data was recorded in the report.
5. $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}[120\pi] = \text{dBuV/m} - 51.5$

For Radiate Spurious Emission (30 MHz ~ 1 GHz):

Note:

1. Result Level = Read Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 7 GHz):

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27 dBm/MHz (68.2 dBuV/m) limit.
9. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (7 GHz ~ 18 GHz):

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27 dBm/MHz (68.2 dBuV/m) limit.
9. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (18 GHz ~ 26 GHz):

Note:


1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (26 GHz ~ 40 GHz):


Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.


TEST SETUP



Below 1 GHz and above 30 MHz



Above 1GHz



TEST ENVIRONMENT

Temperature	22.6°C	Relative Humidity	55%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz


TEST DATE / ENGINEER

Test Date	March 10, 2026	Test By	Leslie Xie
-----------	----------------	---------	------------

TEST RESULTS

8.1. RESTRICTED BANDEDGE-RA0

TX Radiated Test Result



PEAK Data List


NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5137.19	41.81	55.23	13.42	74.00	18.77	PK	Horizontal	PASS
2	5150.00	39.43	52.90	13.47	74.00	21.10	PK	Horizontal	PASS

AVG Data List

NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5137.19	13.42	29.80	43.22	54.00	10.78	Horizontal	PASS
2	5150.00	13.46	29.84	43.30	54.00	10.70	Horizontal	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5131.86	41.74	55.14	13.40	74.00	18.86	PK	Vertical	PASS
2	5150.00	41.28	54.75	13.47	74.00	19.25	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5131.86	13.40	30.46	43.86	54.00	10.14	Vertical	PASS
2	5150.00	13.46	30.99	44.45	54.00	9.55	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result



PEAK Data List

NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4956.23	49.88	63.59	13.71	74.00	10.41	PK	Vertical	PASS
2	5150.00	48.09	61.56	13.47	74.00	12.44	PK	Vertical	PASS
3	5350.00	46.58	60.96	14.38	74.00	13.04	PK	Vertical	PASS
4	5444.15	47.50	63.46	15.96	74.00	10.54	PK	Vertical	PASS


AVG Data List

NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4956.23	13.71	29.87	43.58	54.00	10.42	Vertical	PASS
2	5150.00	13.46	30.20	43.66	54.00	10.34	Vertical	PASS
3	5350.00	14.38	28.77	43.15	54.00	10.85	Vertical	PASS
4	5444.15	15.96	28.32	44.28	54.00	9.72	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

TX Radiated Test Result



PEAK Data List

NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4984.56	50.29	63.77	13.48	74.00	10.23	PK	Vertical	PASS
2	5150.00	48.24	61.71	13.47	74.00	12.29	PK	Vertical	PASS
3	5350.00	45.83	60.21	14.38	74.00	13.79	PK	Vertical	PASS
4	5418.22	48.39	63.86	15.47	74.00	10.14	PK	Vertical	PASS


AVG Data List

NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4984.56	13.48	29.20	42.68	54.00	11.32	Vertical	PASS
2	5150.00	13.46	30.89	44.35	54.00	9.65	Vertical	PASS
3	5350.00	14.38	30.23	44.61	54.00	9.39	Vertical	PASS
4	5418.22	15.47	27.92	43.39	54.00	10.61	Vertical	PASS

Note: (1) Level = Reading + Factor

(2) Margin = Limit - Level

TX Radiated Test Result



PEAK Data List

NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5350.00	44.60	57.32	12.72	74.00	16.68	PK	Vertical	PASS
2	5350.72	45.16	57.89	12.73	74.00	16.11	PK	Vertical	PASS


AVG Data List

NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5350.00	12.72	23.27	35.99	54.00	18.01	Vertical	PASS
2	5350.72	12.73	22.03	34.76	54.00	19.24	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

TX Radiated Test Result



PEAK Data List

NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5452.29	45.23	61.34	16.11	74.00	12.66	PK	Vertical	PASS
2	5460.00	43.55	59.80	16.25	74.00	14.20	PK	Vertical	PASS
3	5467.96	50.23	66.64	16.41	68.20	1.56	PK	Vertical	PASS
4	5470.00	47.50	63.95	16.45	68.20	4.25	PK	Vertical	PASS


AVG Data List

NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5452.29	16.11	31.59	47.70	54.00	6.30	Vertical	PASS
2	5460.00	16.25	33.33	49.58	54.00	4.42	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5725.00	48.21	60.83	12.62	68.20	7.37	PK	Vertical	PASS
2	5731.68	53.47	66.10	12.63	68.20	2.10	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5632.68	48.15	63.23	15.08	68.20	4.97	PK	Vertical	PASS
2	5724.64	75.25	89.42	14.17	121.38	31.96	PK	Vertical	PASS
3	5725.00	72.35	86.52	14.17	122.20	35.68	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5850.00	69.03	83.32	14.29	122.20	38.88	PK	Vertical	PASS
2	5850.50	71.71	86.00	14.29	121.06	35.06	PK	Vertical	PASS
3	5977.69	47.32	61.92	14.60	68.20	6.28	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5076.81	42.28	55.58	13.30	74.00	18.42	PK	Vertical	PASS
2	5150.00	42.46	55.93	13.47	74.00	18.07	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5076.81	13.30	29.84	43.14	54.00	10.86	Vertical	PASS
2	5150.00	13.46	31.22	44.68	54.00	9.32	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4941.34	50.75	64.59	13.84	74.00	9.41	PK	Vertical	PASS
2	5150.00	48.22	61.69	13.47	74.00	12.31	PK	Vertical	PASS
3	5350.00	45.62	60.00	14.38	74.00	14.00	PK	Vertical	PASS
4	5432.63	47.61	63.34	15.73	74.00	10.66	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4941.34	13.84	29.80	43.64	54.00	10.36	Vertical	PASS
2	5150.00	13.46	29.86	43.32	54.00	10.68	Vertical	PASS
3	5350.00	14.38	28.81	43.19	54.00	10.81	Vertical	PASS
4	5432.63	15.73	28.22	43.95	54.00	10.05	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4900.04	49.68	63.87	14.19	74.00	10.13	PK	Vertical	PASS
2	5150.00	48.20	61.67	13.47	74.00	12.33	PK	Vertical	PASS
3	5350.00	46.28	60.66	14.38	74.00	13.34	PK	Vertical	PASS
4	5452.32	47.76	63.87	16.11	74.00	10.13	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4900.04	14.19	29.51	43.70	54.00	10.30	Vertical	PASS
2	5150.00	13.46	29.97	43.43	54.00	10.57	Vertical	PASS
3	5350.00	14.38	29.58	43.96	54.00	10.04	Vertical	PASS
4	5452.31	16.11	28.17	44.28	54.00	9.72	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5350.00	40.68	53.40	12.72	74.00	20.60	PK	Vertical	PASS
2	5361.61	42.76	55.66	12.90	74.00	18.34	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5350.00	12.72	23.54	36.26	54.00	17.74	Vertical	PASS
2	5361.61	12.90	21.66	34.56	54.00	19.44	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5450.22	44.86	60.93	16.07	74.00	13.07	PK	Vertical	PASS
2	5460.00	43.62	59.87	16.25	74.00	14.13	PK	Vertical	PASS
3	5469.31	50.25	66.68	16.43	68.20	1.52	PK	Vertical	PASS
4	5470.00	48.06	64.51	16.45	68.20	3.69	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5450.22	16.07	30.23	46.30	54.00	7.70	Vertical	PASS
2	5460.00	16.25	31.85	48.10	54.00	5.90	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5725.00	47.84	60.46	12.62	68.20	7.74	PK	Vertical	PASS
2	5732.49	51.85	64.50	12.65	68.20	3.70	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5725.00	50.08	62.70	12.62	68.20	5.50	PK	Vertical	PASS
2	5737.80	51.00	63.65	12.65	68.20	4.55	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5622.80	48.22	63.45	15.23	68.20	4.75	PK	Vertical	PASS
2	5724.83	75.40	89.57	14.17	121.81	32.24	PK	Vertical	PASS
3	5725.00	74.88	89.05	14.17	122.20	33.15	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5850.00	75.97	90.26	14.29	122.20	31.94	PK	Vertical	PASS
2	5853.03	77.49	91.78	14.29	115.29	23.51	PK	Vertical	PASS
3	5991.95	47.84	62.52	14.68	68.20	5.68	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result



PEAK Data List


NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5142.36	43.31	56.75	13.44	74.00	17.25	PK	Vertical	PASS
2	5150.00	42.52	55.99	13.47	74.00	18.01	PK	Vertical	PASS

AVG Data List

NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5142.36	13.44	33.48	46.92	54.00	7.08	Vertical	PASS
2	5150.00	13.46	35.82	49.28	54.00	4.72	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4929.81	50.09	64.03	13.94	74.00	9.97	PK	Vertical	PASS
2	5150.00	48.29	61.76	13.47	74.00	12.24	PK	Vertical	PASS
3	5350.00	45.59	59.97	14.38	74.00	14.03	PK	Vertical	PASS
4	5432.15	48.45	64.17	15.72	74.00	9.83	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4929.81	13.94	30.58	44.52	54.00	9.48	Vertical	PASS
2	5150.00	13.46	31.66	45.12	54.00	8.88	Vertical	PASS
3	5350.00	14.38	30.10	44.48	54.00	9.52	Vertical	PASS
4	5432.15	15.72	29.17	44.89	54.00	9.11	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4950.47	50.36	64.12	13.76	74.00	9.88	PK	Vertical	PASS
2	5150.00	48.85	62.32	13.47	74.00	11.68	PK	Vertical	PASS
3	5350.00	46.17	60.55	14.38	74.00	13.45	PK	Vertical	PASS
4	5410.54	48.19	63.50	15.31	74.00	10.50	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4950.47	13.76	30.24	44.00	54.00	10.00	Vertical	PASS
2	5150.00	13.46	30.89	44.35	54.00	9.65	Vertical	PASS
3	5350.00	14.38	30.62	45.00	54.00	9.00	Vertical	PASS
4	5410.53	15.31	28.70	44.01	54.00	9.99	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5350.00	51.99	64.71	12.72	74.00	9.29	PK	Vertical	PASS
2	5352.07	55.49	68.24	12.75	74.00	5.76	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5350.00	12.72	32.66	45.38	54.00	8.62	Vertical	PASS
2	5352.07	12.75	30.97	43.72	54.00	10.28	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5451.99	45.80	61.90	16.10	74.00	12.10	PK	Vertical	PASS
2	5460.00	40.60	56.85	16.25	74.00	17.15	PK	Vertical	PASS
3	5466.91	48.48	64.87	16.39	68.20	3.33	PK	Vertical	PASS
4	5470.00	49.09	65.54	16.45	68.20	2.66	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5451.99	16.10	31.05	47.15	54.00	6.85	Vertical	PASS
2	5460.00	16.25	32.50	48.75	54.00	5.25	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5725.00	47.44	60.06	12.62	68.20	8.14	PK	Vertical	PASS
2	5726.67	48.93	61.56	12.63	68.20	6.64	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5643.51	51.83	66.75	14.92	68.20	1.45	PK	Vertical	PASS
2	5720.46	72.52	86.67	14.15	111.85	25.18	PK	Vertical	PASS
3	5725.00	67.66	81.83	14.17	122.20	40.37	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5850.00	54.50	68.79	14.29	122.20	53.41	PK	Vertical	PASS
2	5853.26	57.86	72.14	14.28	114.77	42.63	PK	Vertical	PASS
3	5994.71	47.47	62.16	14.69	68.20	6.04	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
 (2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5134.80	50.54	63.95	13.41	74.00	10.05	PK	Vertical	PASS
2	5150.00	47.43	60.90	13.47	74.00	13.10	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5134.80	13.41	32.71	46.12	54.00	7.88	Vertical	PASS
2	5150.00	13.46	32.43	45.89	54.00	8.11	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result



PEAK Data List


NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5350.00	52.90	65.62	12.72	74.00	8.38	PK	Vertical	PASS
2	5353.47	56.89	69.66	12.77	74.00	4.34	PK	Vertical	PASS

AVG Data List

NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5350.00	12.72	34.20	46.92	54.00	7.08	Vertical	PASS
2	5353.47	12.77	34.04	46.81	54.00	7.19	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5453.55	47.10	63.23	16.13	74.00	10.77	PK	Vertical	PASS
2	5460.00	42.80	59.05	16.25	74.00	14.95	PK	Vertical	PASS
3	5465.98	50.82	67.19	16.37	68.20	1.01	PK	Vertical	PASS
4	5470.00	48.02	64.47	16.45	68.20	3.73	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5453.55	16.13	34.83	50.96	54.00	3.04	Vertical	PASS
2	5460.00	16.25	33.23	49.48	54.00	4.52	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5725.00	46.87	59.49	12.62	68.20	8.71	PK	Vertical	PASS
2	5726.70	47.83	60.46	12.63	68.20	7.74	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5632.42	49.78	64.87	15.09	68.20	3.33	PK	Vertical	PASS
2	5690.85	64.00	78.23	14.23	98.43	20.20	PK	Vertical	PASS
3	5725.00	62.17	76.34	14.17	122.20	45.86	PK	Vertical	PASS
4	5850.00	56.80	71.09	14.29	122.20	51.11	PK	Vertical	PASS
5	5851.13	62.76	77.05	14.29	119.63	42.58	PK	Vertical	PASS
6	5976.79	41.08	55.68	14.60	68.20	12.52	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4595.90	41.36	55.92	14.56	74.00	18.08	PK	Vertical	PASS
2	5150.00	40.64	54.11	13.47	74.00	19.89	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4595.90	14.56	29.53	44.09	54.00	9.91	Vertical	PASS
2	5150.00	13.46	30.46	43.92	54.00	10.08	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5020.58	51.05	64.38	13.33	74.00	9.62	PK	Vertical	PASS
2	5150.00	48.22	61.69	13.47	74.00	12.31	PK	Vertical	PASS
3	5350.00	46.17	60.55	14.38	74.00	13.45	PK	Vertical	PASS
4	5456.16	47.34	63.52	16.18	74.00	10.48	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5020.58	13.33	30.73	44.06	54.00	9.94	Vertical	PASS
2	5150.00	13.46	30.65	44.11	54.00	9.89	Vertical	PASS
3	5350.00	14.38	30.30	44.68	54.00	9.32	Vertical	PASS
4	5456.16	16.18	28.77	44.95	54.00	9.05	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4922.13	49.92	63.92	14.00	74.00	10.08	PK	Vertical	PASS
2	5150.00	48.87	62.34	13.47	74.00	11.66	PK	Vertical	PASS
3	5350.00	45.74	60.12	14.38	74.00	13.88	PK	Vertical	PASS
4	5457.12	47.38	63.58	16.20	74.00	10.42	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4922.13	14.00	30.13	44.13	54.00	9.87	Vertical	PASS
2	5150.00	13.46	30.81	44.27	54.00	9.73	Vertical	PASS
3	5350.00	14.38	31.42	45.80	54.00	8.20	Vertical	PASS
4	5457.12	16.20	28.84	45.04	54.00	8.96	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result



PEAK Data List

NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5350.00	42.81	55.53	12.72	74.00	18.47	PK	Vertical	PASS
2	5353.47	43.21	55.98	12.77	74.00	18.02	PK	Vertical	PASS


AVG Data List

NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5350.00	12.72	28.66	41.38	54.00	12.62	Vertical	PASS
2	5353.47	12.77	26.81	39.58	54.00	14.42	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5453.55	44.29	60.42	16.13	74.00	13.58	PK	Vertical	PASS
2	5460.00	43.15	59.40	16.25	74.00	14.60	PK	Vertical	PASS
3	5468.41	48.89	65.31	16.42	68.20	2.89	PK	Vertical	PASS
4	5470.00	46.83	63.28	16.45	68.20	4.92	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5453.55	16.13	33.99	50.12	54.00	3.88	Vertical	PASS
2	5460.00	16.25	35.19	51.44	54.00	2.56	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5725.00	50.63	63.25	12.62	68.20	4.95	PK	Vertical	PASS
2	5725.11	53.52	66.14	12.62	68.20	2.06	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5618.62	48.05	63.34	15.29	68.20	4.86	PK	Vertical	PASS
2	5724.45	71.58	85.75	14.17	120.95	35.20	PK	Vertical	PASS
3	5725.00	66.97	81.14	14.17	122.20	41.06	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5850.00	64.05	78.34	14.29	122.20	43.86	PK	Vertical	PASS
2	5851.88	66.18	80.47	14.29	117.91	37.44	PK	Vertical	PASS
3	5994.48	49.50	64.19	14.69	68.20	4.01	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5148.56	44.18	57.64	13.46	74.00	16.36	PK	Vertical	PASS
2	5150.00	42.14	55.61	13.47	74.00	18.39	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5148.57	13.46	32.13	45.59	54.00	8.41	Vertical	PASS
2	5150.00	13.46	31.72	45.18	54.00	8.82	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result



PEAK Data List

NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4630.63	50.26	64.38	14.12	74.00	9.62	PK	Vertical	PASS
2	5150.00	48.82	62.29	13.47	74.00	11.71	PK	Vertical	PASS
3	5350.00	46.29	60.67	14.38	74.00	13.33	PK	Vertical	PASS
4	5459.52	47.11	63.35	16.24	74.00	10.65	PK	Vertical	PASS


AVG Data List

NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4630.63	14.12	30.24	44.36	54.00	9.64	Vertical	PASS
2	5150.00	13.46	31.33	44.79	54.00	9.21	Vertical	PASS
3	5350.00	14.38	30.12	44.50	54.00	9.50	Vertical	PASS
4	5459.52	16.24	28.86	45.10	54.00	8.90	Vertical	PASS

Note: (1) Level = Reading + Factor

(2) Margin = Limit - Level

TX Radiated Test Result



PEAK Data List

NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4903.88	50.16	64.32	14.16	74.00	9.68	PK	Vertical	PASS
2	5150.00	48.03	61.50	13.47	74.00	12.50	PK	Vertical	PASS
3	5350.00	46.31	60.69	14.38	74.00	13.31	PK	Vertical	PASS
4	5456.64	47.76	63.95	16.19	74.00	10.05	PK	Vertical	PASS


AVG Data List

NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4903.88	14.16	30.16	44.32	54.00	9.68	Vertical	PASS
2	5150.00	13.46	31.95	45.41	54.00	8.59	Vertical	PASS
3	5350.00	14.38	32.65	47.03	54.00	6.97	Vertical	PASS
4	5456.64	16.19	28.77	44.96	54.00	9.04	Vertical	PASS

Note: (1) Level = Reading + Factor

(2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5350.00	53.86	66.58	12.72	74.00	7.42	PK	Vertical	PASS
2	5353.57	56.59	69.36	12.77	74.00	4.64	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5350.00	12.72	31.59	44.31	54.00	9.69	Vertical	PASS
2	5353.57	12.77	28.70	41.47	54.00	12.53	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5457.50	46.83	63.03	16.20	74.00	10.97	PK	Vertical	PASS
2	5460.00	42.99	59.24	16.25	74.00	14.76	PK	Vertical	PASS
3	5468.62	50.14	66.56	16.42	68.20	1.64	PK	Vertical	PASS
4	5470.00	47.32	63.77	16.45	68.20	4.43	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5457.50	16.20	31.35	47.55	54.00	6.45	Vertical	PASS
2	5460.00	16.25	32.19	48.44	54.00	5.56	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5725.00	47.25	59.87	12.62	68.20	8.33	PK	Vertical	PASS
2	5726.98	54.32	66.95	12.63	68.20	1.25	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5648.64	50.66	65.51	14.85	68.20	2.69	PK	Vertical	PASS
2	5723.12	74.50	88.67	14.17	117.91	29.24	PK	Vertical	PASS
3	5725.00	67.69	81.86	14.17	122.20	40.34	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5850.00	65.91	80.20	14.29	122.20	42.00	PK	Vertical	PASS
2	5852.34	69.52	83.81	14.29	116.86	33.05	PK	Vertical	PASS
3	5981.14	48.10	62.72	14.62	68.20	5.48	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5145.20	55.89	69.34	13.45	74.00	4.66	PK	Vertical	PASS
2	5150.00	53.18	66.65	13.47	74.00	7.35	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5145.20	13.45	38.26	51.71	54.00	2.29	Vertical	PASS
2	5150.00	13.46	38.72	52.18	54.00	1.82	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5350.00	57.04	69.76	12.72	74.00	4.24	PK	Vertical	PASS
2	5356.00	58.32	71.13	12.81	74.00	2.87	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5350.00	12.72	39.59	52.31	54.00	1.69	Vertical	PASS
2	5356.00	12.81	37.68	50.49	54.00	3.51	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5456.20	48.36	64.54	16.18	74.00	9.46	PK	Vertical	PASS
2	5460.00	45.56	61.81	16.25	74.00	12.19	PK	Vertical	PASS
3	5465.06	50.68	67.03	16.35	68.20	1.17	PK	Vertical	PASS
4	5470.00	47.78	64.23	16.45	68.20	3.97	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5456.20	16.18	33.02	49.20	54.00	4.80	Vertical	PASS
2	5460.00	16.25	33.94	50.19	54.00	3.81	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5725.00	44.34	56.96	12.62	68.20	11.24	PK	Vertical	PASS
2	5730.30	48.72	61.35	12.63	68.20	6.85	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5646.02	51.15	66.04	14.89	68.20	2.16	PK	Vertical	PASS
2	5721.46	63.75	77.92	14.17	114.13	36.21	PK	Vertical	PASS
3	5725.00	61.31	75.48	14.17	122.20	46.72	PK	Vertical	PASS
4	5850.00	62.66	76.95	14.29	122.20	45.25	PK	Vertical	PASS
5	5850.13	62.66	76.95	14.29	121.91	44.96	PK	Vertical	PASS
6	5996.00	40.55	55.25	14.70	68.20	12.95	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

8.2. RESTRICTED BANDEDGE-RA1

TX Radiated Test Result



PEAK Data List


NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4870.10	42.23	56.13	13.90	74.00	17.87	PK	Horizontal	PASS
2	5150.00	39.84	53.31	13.47	74.00	20.69	PK	Horizontal	PASS

AVG Data List

NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4870.09	13.90	30.68	44.58	54.00	9.42	Horizontal	PASS
2	5150.00	13.46	30.58	44.04	54.00	9.96	Horizontal	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4938.29	41.79	55.65	13.86	74.00	18.35	PK	Vertical	PASS
2	5150.00	39.24	52.71	13.47	74.00	21.29	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4938.29	13.86	30.52	44.38	54.00	9.62	Vertical	PASS
2	5150.00	13.46	30.72	44.18	54.00	9.82	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4974.48	41.99	55.55	13.56	74.00	18.45	PK	Vertical	PASS
2	5150.00	39.85	53.32	13.47	74.00	20.68	PK	Vertical	PASS
3	5350.00	38.42	52.80	14.38	74.00	21.20	PK	Vertical	PASS
4	5444.15	40.20	56.16	15.96	74.00	17.84	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4974.48	13.56	30.47	44.03	54.00	9.97	Vertical	PASS
2	5150.00	13.46	30.89	44.35	54.00	9.65	Vertical	PASS
3	5350.00	14.38	29.83	44.21	54.00	9.79	Vertical	PASS
4	5444.15	15.96	29.38	45.34	54.00	8.66	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5066.68	42.14	55.45	13.31	74.00	18.55	PK	Vertical	PASS
2	5150.00	40.81	54.28	13.47	74.00	19.72	PK	Vertical	PASS
3	5350.00	38.84	53.22	14.38	74.00	20.78	PK	Vertical	PASS
4	5430.71	39.60	55.30	15.70	74.00	18.70	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5066.68	13.31	30.97	44.28	54.00	9.72	Vertical	PASS
2	5150.00	13.46	31.23	44.69	54.00	9.31	Vertical	PASS
3	5350.00	14.38	29.91	44.29	54.00	9.71	Vertical	PASS
4	5430.70	15.70	29.28	44.98	54.00	9.02	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5350.00	36.09	48.81	12.72	74.00	25.19	PK	Vertical	PASS
2	5358.42	40.07	52.92	12.85	74.00	21.08	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5350.00	12.72	22.66	35.38	54.00	18.62	Vertical	PASS
2	5358.42	12.85	21.52	34.37	54.00	19.63	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5447.43	40.00	56.02	16.02	74.00	17.98	PK	Vertical	PASS
2	5460.00	38.63	54.88	16.25	74.00	19.12	PK	Vertical	PASS
3	5470.00	40.15	56.60	16.45	68.20	11.60	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5447.43	16.02	29.63	45.65	54.00	8.35	Vertical	PASS
2	5460.00	16.25	29.31	45.56	54.00	8.44	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5725.00	40.40	53.02	12.62	68.20	15.18	PK	Vertical	PASS
2	5787.60	42.92	55.73	12.81	68.20	12.47	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5623.18	48.70	63.92	15.22	68.20	4.28	PK	Vertical	PASS
2	5725.00	62.86	77.03	14.17	122.20	45.17	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5850.00	55.29	69.58	14.29	122.20	52.62	PK	Vertical	PASS
2	5942.96	48.88	63.30	14.42	68.20	4.90	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5005.42	42.22	55.56	13.34	74.00	18.44	PK	Vertical	PASS
2	5150.00	40.14	53.61	13.47	74.00	20.39	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5005.42	13.34	30.29	43.63	54.00	10.37	Vertical	PASS
2	5150.00	13.46	31.29	44.75	54.00	9.25	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4965.35	41.98	55.61	13.63	74.00	18.39	PK	Vertical	PASS
2	5150.00	39.66	53.13	13.47	74.00	20.87	PK	Vertical	PASS
3	5350.00	38.71	53.09	14.38	74.00	20.91	PK	Vertical	PASS
4	5428.78	40.40	56.06	15.66	74.00	17.94	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4965.35	13.63	30.44	44.07	54.00	9.93	Vertical	PASS
2	5150.00	13.46	30.99	44.45	54.00	9.55	Vertical	PASS
3	5350.00	14.38	29.67	44.05	54.00	9.95	Vertical	PASS
4	5428.78	15.66	29.53	45.19	54.00	8.81	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4906.28	41.48	55.62	14.14	74.00	18.38	PK	Vertical	PASS
2	5150.00	40.24	53.71	13.47	74.00	20.29	PK	Vertical	PASS
3	5350.00	38.58	52.96	14.38	74.00	21.04	PK	Vertical	PASS
4	5404.29	40.20	55.40	15.20	74.00	18.60	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4906.28	14.14	30.20	44.34	54.00	9.66	Vertical	PASS
2	5150.00	13.46	30.96	44.42	54.00	9.58	Vertical	PASS
3	5350.00	14.38	29.88	44.26	54.00	9.74	Vertical	PASS
4	5404.29	15.20	29.29	44.49	54.00	9.51	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5350.00	38.16	50.88	12.72	74.00	23.12	PK	Vertical	PASS
2	5375.80	39.21	52.32	13.11	74.00	21.68	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5350.00	12.72	22.94	35.66	54.00	18.34	Vertical	PASS
2	5375.80	13.11	21.24	34.35	54.00	19.65	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5447.34	39.95	55.97	16.02	74.00	18.03	PK	Vertical	PASS
2	5460.00	38.71	54.96	16.25	74.00	19.04	PK	Vertical	PASS
3	5470.00	41.11	57.56	16.45	68.20	10.64	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5447.34	16.02	29.85	45.87	54.00	8.13	Vertical	PASS
2	5460.00	16.25	30.49	46.74	54.00	7.26	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5725.00	42.59	55.21	12.62	68.20	12.99	PK	Vertical	PASS
2	5785.44	42.61	55.42	12.81	68.20	12.78	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5609.12	47.52	62.95	15.43	68.20	5.25	PK	Vertical	PASS
2	5725.00	70.23	84.40	14.17	122.20	37.80	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5850.00	60.27	74.56	14.29	122.20	47.64	PK	Vertical	PASS
2	5949.63	47.97	62.43	14.46	68.20	5.77	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5022.21	41.57	54.90	13.33	74.00	19.10	PK	Vertical	PASS
2	5150.00	41.79	55.26	13.47	74.00	18.74	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5022.21	13.33	30.85	44.18	54.00	9.82	Vertical	PASS
2	5150.00	13.46	32.60	46.06	54.00	7.94	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4866.42	41.80	55.67	13.87	74.00	18.33	PK	Vertical	PASS
2	5150.00	42.32	55.79	13.47	74.00	18.21	PK	Vertical	PASS
3	5350.00	38.63	53.01	14.38	74.00	20.99	PK	Vertical	PASS
4	5446.07	39.41	55.40	15.99	74.00	18.60	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4866.43	13.87	30.48	44.35	54.00	9.65	Vertical	PASS
2	5150.00	13.46	33.32	46.78	54.00	7.22	Vertical	PASS
3	5350.00	14.38	30.01	44.39	54.00	9.61	Vertical	PASS
4	5446.07	15.99	29.13	45.12	54.00	8.88	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4955.75	41.69	55.41	13.72	74.00	18.59	PK	Vertical	PASS
2	5150.00	40.36	53.83	13.47	74.00	20.17	PK	Vertical	PASS
3	5350.00	41.22	55.60	14.38	74.00	18.40	PK	Vertical	PASS
4	5362.99	41.59	56.17	14.58	74.00	17.83	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4955.75	13.72	30.71	44.43	54.00	9.57	Vertical	PASS
2	5150.00	13.46	32.38	45.84	54.00	8.16	Vertical	PASS
3	5350.00	14.38	32.12	46.50	54.00	7.50	Vertical	PASS
4	5362.99	14.58	30.72	45.30	54.00	8.70	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5274.16	70.56	82.51	11.95	-	-	PK	Vertical	NA
2	5350.00	42.13	54.85	12.72	74.00	19.15	PK	Vertical	PASS
3	5351.62	42.79	55.53	12.74	74.00	18.47	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5350.00	12.72	26.49	39.21	54.00	14.79	Vertical	PASS
2	5351.62	12.74	24.24	36.98	54.00	17.02	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5457.59	40.88	57.09	16.21	74.00	16.91	PK	Vertical	PASS
2	5460.00	38.94	55.19	16.25	74.00	18.81	PK	Vertical	PASS
3	5470.00	41.94	58.39	16.45	68.20	9.81	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5457.59	16.21	31.40	47.61	54.00	6.39	Vertical	PASS
2	5460.00	16.25	30.63	46.88	54.00	7.12	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5725.00	39.40	52.02	12.62	68.20	16.18	PK	Vertical	PASS
2	5740.43	42.16	54.83	12.67	68.20	13.37	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5648.26	48.57	63.43	14.86	68.20	4.77	PK	Vertical	PASS
2	5725.00	73.61	87.78	14.17	122.20	34.42	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5850.00	60.24	74.53	14.29	122.20	47.67	PK	Vertical	PASS
2	5965.50	47.64	62.18	14.54	68.20	6.02	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result



PEAK Data List


NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5138.65	51.83	65.26	13.43	74.00	8.74	PK	Vertical	PASS
2	5150.00	49.81	63.28	13.47	74.00	10.72	PK	Vertical	PASS

AVG Data List

NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5138.65	13.43	37.01	50.44	54.00	3.56	Vertical	PASS
2	5150.00	13.46	39.10	52.56	54.00	1.44	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5350.00	49.86	62.58	12.72	74.00	11.42	PK	Vertical	PASS
2	5362.27	51.27	64.18	12.91	74.00	9.82	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5350.00	12.72	33.20	45.92	54.00	8.08	Vertical	PASS
2	5362.27	12.91	29.41	42.32	54.00	11.68	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5458.61	48.58	64.80	16.22	74.00	9.20	PK	Vertical	PASS
2	5460.00	41.64	57.89	16.25	74.00	16.11	PK	Vertical	PASS
3	5470.00	48.38	64.83	16.45	68.20	3.37	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5458.61	16.22	34.52	50.74	54.00	3.26	Vertical	PASS
2	5460.00	16.25	31.55	47.80	54.00	6.20	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5725.00	40.33	52.95	12.62	68.20	15.25	PK	Vertical	PASS
2	5741.10	45.68	58.35	12.67	68.20	9.85	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5648.02	51.97	66.83	14.86	68.20	1.37	PK	Vertical	PASS
2	5725.00	67.38	81.55	14.17	122.20	40.65	PK	Vertical	PASS
3	5850.00	62.82	77.11	14.29	122.20	45.09	PK	Vertical	PASS
4	5977.59	41.17	55.77	14.60	68.20	12.43	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4874.36	41.37	55.32	13.95	74.00	18.68	PK	Vertical	PASS
2	5150.00	40.42	53.89	13.47	74.00	20.11	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4874.36	13.95	30.58	44.53	54.00	9.47	Vertical	PASS
2	5150.00	13.46	31.33	44.79	54.00	9.21	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4873.15	41.58	55.51	13.93	74.00	18.49	PK	Vertical	PASS
2	5150.00	39.87	53.34	13.47	74.00	20.66	PK	Vertical	PASS
3	5350.00	38.72	53.10	14.38	74.00	20.90	PK	Vertical	PASS
4	5437.43	39.79	55.61	15.82	74.00	18.39	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4873.15	13.93	30.72	44.65	54.00	9.35	Vertical	PASS
2	5150.00	13.46	30.76	44.22	54.00	9.78	Vertical	PASS
3	5350.00	14.38	29.85	44.23	54.00	9.77	Vertical	PASS
4	5437.43	15.82	28.97	44.79	54.00	9.21	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result



PEAK Data List


NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5132.96	42.18	55.58	13.40	74.00	18.42	PK	Vertical	PASS
2	5150.00	40.23	53.70	13.47	74.00	20.30	PK	Vertical	PASS
3	5350.00	41.59	55.97	14.38	74.00	18.03	PK	Vertical	PASS
4	5440.79	39.43	55.32	15.89	74.00	18.68	PK	Vertical	PASS

AVG Data List

NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5132.96	13.40	31.40	44.80	54.00	9.20	Vertical	PASS
2	5150.00	13.46	31.04	44.50	54.00	9.50	Vertical	PASS
3	5350.00	14.38	31.00	45.38	54.00	8.62	Vertical	PASS
4	5440.79	15.89	29.21	45.10	54.00	8.90	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result



PEAK Data List


NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5350.00	37.02	49.74	12.72	74.00	24.26	PK	Vertical	PASS
2	5373.16	39.04	52.11	13.07	74.00	21.89	PK	Vertical	PASS

AVG Data List

NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5350.00	12.72	23.15	35.87	54.00	18.13	Vertical	PASS
2	5373.16	13.07	21.87	34.94	54.00	19.06	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5426.63	41.47	57.09	15.62	74.00	16.91	PK	Vertical	PASS
2	5460.00	38.96	55.21	16.25	74.00	18.79	PK	Vertical	PASS
3	5470.00	43.01	59.46	16.45	68.20	8.74	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5426.63	15.62	30.18	45.80	54.00	8.20	Vertical	PASS
2	5460.00	16.25	29.56	45.81	54.00	8.19	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5725.00	45.78	58.40	12.62	68.20	9.80	PK	Vertical	PASS
2	5730.96	44.53	57.16	12.63	68.20	11.04	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5604.37	47.95	63.45	15.50	68.20	4.75	PK	Vertical	PASS
2	5725.00	71.75	85.92	14.17	122.20	36.28	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5850.00	64.56	78.85	14.29	122.20	43.35	PK	Vertical	PASS
2	5941.35	47.97	62.39	14.42	68.20	5.81	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5127.02	42.68	56.06	13.38	74.00	17.94	PK	Vertical	PASS
2	5150.00	43.76	57.23	13.47	74.00	16.77	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5127.02	13.38	31.51	44.89	54.00	9.11	Vertical	PASS
2	5150.00	13.46	34.91	48.37	54.00	5.63	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4833.29	42.09	55.65	13.56	74.00	18.35	PK	Vertical	PASS
2	5150.00	41.65	55.12	13.47	74.00	18.88	PK	Vertical	PASS
3	5350.00	38.62	53.00	14.38	74.00	21.00	PK	Vertical	PASS
4	5450.88	38.95	55.03	16.08	74.00	18.97	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	4833.28	13.56	30.04	43.60	54.00	10.40	Vertical	PASS
2	5150.00	13.46	32.31	45.77	54.00	8.23	Vertical	PASS
3	5350.00	14.38	29.87	44.25	54.00	9.75	Vertical	PASS
4	5450.87	16.08	29.03	45.11	54.00	8.89	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5114.23	42.28	55.62	13.34	74.00	18.38	PK	Vertical	PASS
2	5150.00	41.06	54.53	13.47	74.00	19.47	PK	Vertical	PASS
3	5350.00	42.12	56.50	14.38	74.00	17.50	PK	Vertical	PASS
4	5355.79	43.75	58.21	14.46	74.00	15.79	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5114.22	13.34	31.15	44.49	54.00	9.51	Vertical	PASS
2	5150.00	13.46	32.57	46.03	54.00	7.97	Vertical	PASS
3	5350.00	14.38	34.26	48.64	54.00	5.36	Vertical	PASS
4	5355.79	14.46	31.29	45.75	54.00	8.25	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5350.00	44.65	57.37	12.72	74.00	16.63	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5350.00	12.72	28.36	41.08	54.00	12.92	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5447.14	42.94	58.95	16.01	74.00	15.05	PK	Vertical	PASS
2	5460.00	38.82	55.07	16.25	74.00	18.93	PK	Vertical	PASS
3	5470.00	47.79	64.24	16.45	68.20	3.96	PK	Vertical	PASS

AVG Data List								
NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	5447.14	16.01	31.10	47.11	54.00	6.89	Vertical	PASS
2	5460.00	16.25	31.31	47.56	54.00	6.44	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5725.00	43.87	56.49	12.62	68.20	11.71	PK	Vertical	PASS
2	5743.69	42.50	55.17	12.67	68.20	13.03	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level

TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5618.05	47.15	62.44	15.29	68.20	5.76	PK	Vertical	PASS
2	5725.00	49.67	63.84	14.17	122.20	58.36	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level