

TEST REPORT

Product : Smart Access Controller
Trade mark : BYD
Model/Type reference : K3CJ
Serial Number : N/A
Report Number : EED32S820484
FCC ID : SD4-K3CJ
Date of Issue : September 20, 2026
Test Standards : 47 CFR Part 15 Subpart C
Test result : PASS

Prepared for:

BYD Auto Industry Company Limited
No.3001 and 3007, Pingshan Hengping Road, Pingshan New District,
Shenzhen, Guangdong, China

Prepared by:

Centre Testing International Group Co., Ltd.
Building C, Hongwei Industrial Park Block 70, Bao'an District,
Shenzhen, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385



Compiled by:

Frazer Li

Frazer Li

Approved by:

Aaron Ma

Aaron Ma

Reviewed by:

Tom Chen

Tom Chen

Date:

September 20, 2026

Check No.: 5718240826

1 Content

1 CONTENT	2
2 TEST SUMMARY	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 TEST CONFIGURATION	5
3.4 TEST ENVIRONMENT	6
3.5 DESCRIPTION OF SUPPORT UNITS	6
3.6 TEST LOCATION	6
3.7 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2)	7
4 EQUIPMENT LIST	8
5 TEST RESULTS AND MEASUREMENT DATA	10
5.1 ANTENNA REQUIREMENT	10
5.2 MAXIMUM CONDUCTED OUTPUT POWER	11
5.3 DTS BANDWIDTH	12
5.4 MAXIMUM POWER SPECTRAL DENSITY	13
5.5 BAND EDGE MEASUREMENTS AND CONDUCTED SPURIOUS EMISSION	14
5.6 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS	15
6 APPENDIX A	53
7 PHOTOGRAPHS	54

2 Test Summary

Test Item	Test Requirement	Result
Antenna Requirement	47 CFR Part 15 Subpart C Section 15.203/15.247 (c)	PASS
AC Power Line Conducted Emission	47 CFR Part 15 Subpart C Section 15.207	N/A
DTS Bandwidth	47 CFR Part 15 Subpart C Section 15.247 (a)(2)	PASS
Maximum Conducted Output Power	47 CFR Part 15 Subpart C Section 15.247 (b)(3)	PASS
Maximum Power Spectral Density	47 CFR Part 15 Subpart C Section 15.247 (e)	PASS
Band Edge Measurements	47 CFR Part 15 Subpart C Section 15.247(d)	PASS
Conducted Spurious Emissions	47 CFR Part 15 Subpart C Section 15.247(d)	PASS
Radiated Spurious Emission & Restricted bands	47 CFR Part 15 Subpart C Section 15.205/15.209	PASS

N/A:The product is powered by DC and is not applicable.

3 General Information

3.1 Client Information

Applicant:	BYD Auto Industry Company Limited
Address of Applicant:	No.3001 and 3007, Pingshan Hengping Road, Pingshan New District, Shenzhen, Guangdong, China
Manufacturer:	BYD Auto Industry Company Limited
Address of Manufacturer:	No.3001 and 3007, Pingshan Hengping Road, Pingshan New District, Shenzhen, Guangdong, China
Factory:	Changsha BYD Automobile Co., Ltd.
Address of Factory:	No.88, Environmental Protection East Road, Yuhua District, Changsha City, Hunan Province, China

3.2 General Description of EUT

Product Name:	Smart Access Controller	
Model No.:	K3CJ	
Test Model No.:	K3CJ	
Model difference:	N/A	
Trade mark:	BYD	
Product Type:	Fixed Use	
Operation Frequency:	2402MHz~2480MHz	
Modulation Type:	GFSK	
Transfer Rate:	1Mbps, 2Mbps	
Number of Channel:	40	
Antenna Type:	PCB antenna	
Antenna Gain:	ANT1: 4.65 dBi;	
Power Supply:	Adapter:	Model No.: N/A Input: N/A Output: N/A
	Battery:	N/A
	USB Port:	5V DC
Test Voltage:	5V DC	
Sample Received Date:	Aug. 24, 2026	
Sample tested Date:	Aug. 24, 2026 to Sep. 18, 2026	

Operation Frequency each of channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency(MHz)
The lowest channel (CH0)	2402
The middle channel (CH19)	2440
The highest channel (CH39)	2480

3.3 Test Configuration

EUT Test Software Settings:

Test Software:

EUT Power Grade:

Default (Power level is built-in set parameters and cannot be changed and selected)

Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.

Test Mode	Modulation	Rate	Channel	Frequency(MHz)
Mode a	GFSK	1Mbps	CH0	2402
Mode b	GFSK	1Mbps	CH19	2440
Mode c	GFSK	1Mbps	CH39	2480
Mode d	GFSK	2Mbps	CH0	2402
Mode e	GFSK	2Mbps	CH19	2440
Mode f	GFSK	2Mbps	CH39	2480

3.4 Test Environment

Operating Environment:	
Radiated Spurious Emissions:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar
Conducted Emissions:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar
RF Conducted:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar

3.5 Description of Support Units

The EUT has been tested with associated equipment below.

1) Support equipment

No.	Device Type	Brand	Series No.	Model	Data Cable	Power Cord
--	--	--	--	--	--	--

3.6 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164, Test Firm Registration No.: 260439

3.7 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.9×10^{-8}
2	RF power, conducted	0.46dB (30MHz-1GHz)
		0.55dB (1GHz-40GHz)
3	Radiated Spurious emission test	3.3dB (9kHz-30MHz)
		4.3dB (30MHz-1GHz)
		4.5dB (1GHz-18GHz)
		3.4dB (18GHz-40GHz)
4	Conduction emission	3.5dB (9kHz-150kHz)
		3.1dB (150kHz-30MHz)
5	Temperature test	0.64°C
6	Humidity test	3.8%
7	DC power voltages	0.026%

4 Equipment List

RF test system					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Spectrum Analyzer	Keysight	N9010A	MY54510339	11-25-2025	11-24-2026
Spectrum Analyzer	R&S	FSVS3044	101509	05-14-2026	05-13-2027
Spectrum Analyzer	R&S	FSW43	102978	08-07-2026	07-06-2027
Signal Generator	Keysight	N5182B	MY53051549	11-13-2025	11-12-2026
Signal Generator	Agilent	N5181A	MY46240094	11-25-2025	11-24-2026
DC Power	Keysight	E3642A	MY56376072	11-13-2025	11-12-2026
Communication test set	R&S	CMW500	169004	02-06-2026	02-05-2027
RF control unit(power unit)	JS Tonscend	JS0806-2	24180620925	07-21-2025 07-15-2026	07-20-2026 07-14-2027
Wi-Fi 7GHz Band Extender	JS Tonscend	TS-WF7U2	2206200002	05-09-2026	05-08-2027
high-low temperature test chamber	Dong Guang Qin Zhuo	LK-80GA	QZ20150611879	11-13-2025	11-12-2026
Temperature/ Humidity Indicator	biaozhi	HM10	1804186	05-22-2026	05-21-2027
BT&WI-FI Automatic test software	JS Tonscend	JS1120-3	V3.6.21	---	---
Digital multimeter	FLUKE	17B MAX	59545050WS	10-15-2025	10-14-2026


3M full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Fully Anechoic Chamber	TDK	FAC-3	---	01-29-2024	01-28-2027
Receiver	Keysight	N9038A	MY57290136	12-22-2025	12-21-2026
Spectrum Analyzer	Keysight	N9020B	MY57111112	12-21-2025	12-20-2026
Spectrum Analyzer	Keysight	N9030B	MY57140871	12-21-2025	12-20-2026
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-1148	03-29-2026	03-28-2027
Horn Antenna	Schwarzbeck	BBHA 9170	9170-832	04-03-2026	04-02-2027
Horn Antenna	ETS-LINDGREN	3117	57407	05-10-2026	05-09-2027
Preamplifier	EMCI	EMC001330	980563	02-06-2026	02-05-2027
Preamplifier	EMCI	EMC051845SE	980380	11-25-2025	11-24-2026
Preamplifier	Tonscend	TAP-011858	AP21B806112	07-07-2025 06-22-2026	07-06-2026 06-21-2027
Communication test set	R&S	CMW500	104466	11-25-2025	11-24-2026
Temperature/ Humidity Indicator	biaozhi	GM1360	EE1186631	03-24-2026	03-23-2027
RSE Automatic test software	JS Tonscend	JS36-RSE	V5.0.0.1	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0001	01-29-2024	01-28-2027
Cable line	Times	SFT205-NMSM-2.50M	394812-0002	01-29-2024	01-28-2027
Cable line	Times	SFT205-NMSM-2.50M	394812-0003	01-29-2024	01-28-2027
Cable line	Times	SFT205-NMSM-2.50M	393495-0001	01-29-2024	01-28-2027
Cable line	Times	EMC104-NMNM-1000	SN160710	01-29-2024	01-28-2027
Cable line	Times	SFT205-NMSM-3.00M	394813-0001	01-29-2024	01-28-2027
Cable line	Times	SFT205-NMNM-1.50M	381964-0001	01-29-2024	01-28-2027
Cable line	Times	SFT205-NMSM-7.00M	394815-0001	01-29-2024	01-28-2027
Cable line	Times	HF160-KMKM-3.00M	393493-0001	01-29-2024	01-28-2027

5 Test results and Measurement Data


5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	Please see Internal photos
The antenna is PCB antenna. The best case gain of the antenna is ANT1: 4.65 dBi;.	


5.2 Maximum Conducted Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10-2020
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	a) Set the RBW ≥ DTS bandwidth. b) Set VBW ≥ 3 × RBW. c) Set span ≥ 3 × RBW d) Sweep time = auto couple. e) Detector = peak. f) Trace mode = max hold. g) Allow trace to fully stabilize. h) Use peak marker function to determine the peak amplitude level.
Limit:	30dBm
Test Mode:	Refer to clause 3.3
Test Results:	Refer to Appendix A


5.3 DTS Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10-2020
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	a) Set RBW = 100 kHz. b) Set the VBW $\geq [3 \times \text{RBW}]$. c) Detector = peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize. g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
Limit:	$\geq 500 \text{ kHz}$
Test Mode:	Refer to clause 3.3
Test Results:	Refer to Appendix A

5.4 Maximum Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10-2020
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	a) Set analyzer center frequency to DTS channel center frequency. b) Set the span to 1.5 times the DTS bandwidth. c) Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. d) Set the VBW to $\geq [3 \times \text{RBW}]$. e) Detector = peak. f) Sweep time = auto couple. g) Trace mode = max hold. h) Allow trace to fully stabilize. i) Use the peak marker function to determine the maximum amplitude level within the RBW. j) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.
Limit:	$\leq 8.00 \text{ dBm}/3 \text{ kHz}$
Test Mode:	Refer to clause 3.3
Test Results:	Refer to Appendix A

5.5 Band Edge measurements and Conducted Spurious Emission

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10-2020
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	a) Set RBW =100KHz. b) Set VBW = 300KHz. c) Sweep time = auto couple. d) Detector = peak. e) Trace mode = max hold. f) Allow trace to fully stabilize. g) Use peak marker function to determine the peak amplitude level.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Refer to clause 3.3
Test Results:	Refer to Appendix A

5.6 Radiated Spurious Emission & Restricted bands

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10-2020				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10kHz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
Note: For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case


	and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel (2402MHz),the middle channel (2440MHz),the Highest channel (2480MHz) h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete.
Test Mode:	Refer to clause 3.3
Test Results:	Pass

Radiated Spurious Emission below 1GHz:

During the test, the Radiates Emission from 30MHz to 1GHz was performed in all modes, only the worst case mode a was recorded in the report.

Test Graph

Horizontal:




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Antenna Height cm	Table Degree degree	Comment
1		30.4664	1.96	12.50	14.46	40.00	-25.54	QP	100	209
2		63.1247	1.22	12.73	13.95	40.00	-26.05	QP	100	158
3		165.9225	11.62	10.87	22.49	43.50	-21.01	QP	100	286
4		273.6655	10.02	15.35	25.37	46.00	-20.63	QP	100	235
5	*	366.3730	13.47	18.44	31.91	46.00	-14.09	QP	100	252
6		600.0571	6.86	22.97	29.83	46.00	-16.17	QP	100	73

Remark:

1. $\text{Margin} = \text{Measurement}(\text{Level}) - \text{Limit}$.
2. $\text{Measurement}(\text{Level}) = \text{Reading Level} + \text{Correct Factor}$.
3. In the test results, an asterisk (*) indicates Maximum Data, a cross (X) indicates over Limit, an exclamation mark (!) indicates over -6dB margin Limit.

Vertical:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		30.9945	2.33	12.54	14.87	40.00	-25.13	100	219	
2		63.1802	4.27	12.71	16.98	40.00	-23.02	100	99	
3		147.0423	10.16	10.29	20.45	43.50	-23.05	100	6	
4		409.5918	10.02	19.58	29.60	46.00	-16.40	100	184	
5	*	446.0229	10.25	19.94	30.19	46.00	-15.81	100	167	
6		600.0573	6.80	22.97	29.77	46.00	-16.23	100	14	


Remark:

1. $\text{Margin} = \text{Measurement(Level)} - \text{Limit}$.
2. $\text{Measurement(Level)} = \text{Reading Level} + \text{Correct Factor}$.
3. In the test results, an asterisk (*) indicates Maximum Data, a cross (X) indicates over Limit, an exclamation mark (!) indicates over -6dB margin Limit.

Radiated Spurious Emission above 1GHz:

Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2402MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1899.9267	14.60	40.70	55.30	74.00	18.70	PASS	Horizontal	PK
2	2897.8599	17.70	36.98	54.68	74.00	19.32	PASS	Horizontal	PK
3	4804.1203	-8.60	59.94	51.34	74.00	22.66	PASS	Horizontal	PK
4	9338.4226	1.00	51.77	52.77	74.00	21.23	PASS	Horizontal	PK
5	13727.7152	7.21	51.01	58.22	74.00	15.78	PASS	Horizontal	PK
6	16343.8896	11.51	48.87	60.38	74.00	13.62	PASS	Horizontal	PK
7	1900.06	14.60	24.52	39.12	54.00	14.88	PASS	Horizontal	AV
8	2896.1264	17.67	18.36	36.03	54.00	17.97	PASS	Horizontal	AV
9	4805.1203	-8.59	52.48	43.89	54.00	10.11	PASS	Horizontal	AV
10	13750.7167	7.17	38.67	45.84	54.00	8.16	PASS	Horizontal	AV
11	16272.8849	10.68	37.93	48.61	54.00	5.39	PASS	Horizontal	AV

Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2402MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	1899.5266	14.59	41.58	56.17	74.00	17.83	PASS	Vertical	PK
2	2952.7969	17.64	36.71	54.35	74.00	19.65	PASS	Vertical	PK
3	4804.1203	-8.60	58.27	49.67	74.00	24.33	PASS	Vertical	PK
4	8223.3482	-1.19	51.76	50.57	74.00	23.43	PASS	Vertical	PK
5	13722.7148	7.21	50.38	57.59	74.00	16.41	PASS	Vertical	PK
6	16343.8896	11.51	48.73	60.24	74.00	13.76	PASS	Vertical	PK
7	1899.9267	14.60	32.03	46.63	54.00	7.37	PASS	Vertical	AV
8	2967.3312	17.89	17.93	35.82	54.00	18.18	PASS	Vertical	AV
9	4805.1203	-8.59	51.34	42.75	54.00	11.25	PASS	Vertical	AV
10	13703.7136	7.25	38.72	45.97	54.00	8.03	PASS	Vertical	AV
11	16276.8851	10.72	37.72	48.44	54.00	5.56	PASS	Vertical	AV

Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2402MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	18376.055	-26.73	62.63	35.90	74.00	38.10	PASS	Horizontal	PK
2	19854.0942	-25.07	60.02	34.95	74.00	39.05	PASS	Horizontal	PK
3	20974.779	-25.96	61.39	35.43	74.00	38.57	PASS	Horizontal	PK
4	22314.7726	-25.23	59.68	34.45	74.00	39.55	PASS	Horizontal	PK
5	23533.7213	-23.23	57.76	34.53	74.00	39.47	PASS	Horizontal	PK
6	25601.3441	-20.71	57.78	37.07	74.00	36.93	PASS	Horizontal	PK

Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2402MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18579.0432	-26.69	62.37	35.68	74.00	38.32	PASS	Vertical	PK
2	20022.4009	-24.72	60.85	36.13	74.00	37.87	PASS	Vertical	PK
3	21577.2831	-25.75	61.16	35.41	74.00	38.59	PASS	Vertical	PK
4	22998.5399	-25.67	58.53	32.86	74.00	41.14	PASS	Vertical	PK
5	24318.4727	-22.07	57.43	35.36	74.00	38.64	PASS	Vertical	PK
6	25716.2687	-20.78	57.19	36.41	74.00	37.59	PASS	Vertical	PK

Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2440MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1899.7933	14.60	37.12	51.72	74.00	22.28	PASS	Horizontal	PK
2	2969.3313	17.93	35.75	53.68	74.00	20.32	PASS	Horizontal	PK
3	5433.1622	-6.52	52.62	46.10	74.00	27.90	PASS	Horizontal	PK
4	10213.4809	1.64	51.37	53.01	74.00	20.99	PASS	Horizontal	PK
5	13713.7142	7.24	50.10	57.34	74.00	16.66	PASS	Horizontal	PK
6	16346.8898	11.54	48.26	59.80	74.00	14.20	PASS	Horizontal	PK
7	1899.7933	14.60	21.15	35.75	54.00	18.25	PASS	Horizontal	AV
8	13759.7173	7.28	38.52	45.80	54.00	8.20	PASS	Horizontal	AV
9	16277.8852	10.73	37.22	47.95	54.00	6.05	PASS	Horizontal	AV

Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2440MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	1899.66	14.59	41.66	56.25	74.00	17.75	PASS	Vertical	PK
2	2985.8657	17.90	35.33	53.23	74.00	20.77	PASS	Vertical	PK
3	4880.1253	-8.36	56.00	47.64	74.00	26.36	PASS	Vertical	PK
4	10360.4907	1.85	49.80	51.65	74.00	22.35	PASS	Vertical	PK
5	13769.718	7.40	49.97	57.37	74.00	16.63	PASS	Vertical	PK
6	16245.8831	10.43	49.30	59.73	74.00	14.27	PASS	Vertical	PK
7	1900.1933	14.60	32.46	47.06	54.00	6.94	PASS	Vertical	AV
8	2983.5989	17.88	17.83	35.71	54.00	18.29	PASS	Vertical	AV
9	4881.1254	-8.36	48.36	40.00	54.00	14.00	PASS	Vertical	AV
10	13764.7176	7.34	38.60	45.94	54.00	8.06	PASS	Vertical	AV
11	16264.8843	10.59	36.89	47.48	54.00	6.52	PASS	Vertical	AV

Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2440MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18631.0652	-26.63	62.62	35.99	74.00	38.01	PASS	Horizontal	PK
2	20309.0324	-25.49	59.99	34.50	74.00	39.50	PASS	Horizontal	PK
3	21993.4597	-25.80	59.87	34.07	74.00	39.93	PASS	Horizontal	PK
4	23718.0087	-22.63	57.42	34.79	74.00	39.21	PASS	Horizontal	PK
5	25199.788	-21.04	56.80	35.76	74.00	38.24	PASS	Horizontal	PK
6	26172.2269	-21.29	56.98	35.69	74.00	38.31	PASS	Horizontal	PK

Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2440MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18499.82	-26.70	63.65	36.95	74.00	37.05	PASS	Vertical	PK
2	19769.7708	-25.29	61.23	35.94	74.00	38.06	PASS	Vertical	PK
3	21272.9709	-25.80	61.09	35.29	74.00	38.71	PASS	Vertical	PK
4	23130.1252	-24.76	59.22	34.46	74.00	39.54	PASS	Vertical	PK
5	24680.2472	-21.91	56.52	34.61	74.00	39.39	PASS	Vertical	PK
6	26278.9912	-21.29	56.66	35.37	74.00	38.63	PASS	Vertical	PK

Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2480MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	1895.9264	14.50	38.09	52.59	74.00	21.41	PASS	Horizontal	PK
2	2982.3988	17.88	35.45	53.33	74.00	20.67	PASS	Horizontal	PK
3	5388.1592	-6.77	53.38	46.61	74.00	27.39	PASS	Horizontal	PK
4	7440.296	-2.50	53.03	50.53	74.00	23.47	PASS	Horizontal	PK
5	13813.7209	7.58	49.58	57.16	74.00	16.84	PASS	Horizontal	PK
6	16349.89	11.58	48.65	60.23	74.00	13.77	PASS	Horizontal	PK
7	1895.7931	14.49	23.41	37.90	54.00	16.10	PASS	Horizontal	AV
8	13785.719	7.58	38.04	45.62	54.00	8.38	PASS	Horizontal	AV
9	16350.8901	11.56	36.02	47.58	54.00	6.42	PASS	Horizontal	AV

Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2480MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	1900.5934	14.61	41.56	56.17	74.00	17.83	PASS	Vertical	PK
2	2862.6575	17.38	37.00	54.38	74.00	19.62	PASS	Vertical	PK
3	5203.1469	-7.73	54.40	46.67	74.00	27.33	PASS	Vertical	PK
4	9881.4588	1.43	50.30	51.73	74.00	22.27	PASS	Vertical	PK
5	13669.7113	7.37	49.59	56.96	74.00	17.04	PASS	Vertical	PK
6	16485.8991	11.67	48.70	60.37	74.00	13.63	PASS	Vertical	PK
7	1900.7267	14.61	29.73	44.34	54.00	9.66	PASS	Vertical	AV
8	2874.1249	17.42	17.69	35.11	54.00	18.89	PASS	Vertical	AV
9	13754.717	7.22	39.08	46.30	54.00	7.70	PASS	Vertical	AV
10	16334.889	11.40	37.09	48.49	54.00	5.51	PASS	Vertical	AV

Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2480MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18666.0866	-26.56	62.21	35.65	74.00	38.35	PASS	Horizontal	PK
2	20239.3296	-25.50	60.39	34.89	74.00	39.11	PASS	Horizontal	PK
3	21909.1364	-25.68	59.81	34.13	74.00	39.87	PASS	Horizontal	PK
4	23071.6429	-25.17	58.27	33.10	74.00	40.90	PASS	Horizontal	PK
5	24207.2883	-22.60	57.02	34.42	74.00	39.58	PASS	Horizontal	PK
6	25785.6314	-20.81	57.17	36.36	74.00	37.64	PASS	Horizontal	PK

Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2480MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18823.1729	-26.29	61.38	35.09	74.00	38.91	PASS	Vertical	PK
2	20281.8313	-25.50	59.73	34.23	74.00	39.77	PASS	Vertical	PK
3	21637.1255	-25.70	60.74	35.04	74.00	38.96	PASS	Vertical	PK
4	23402.1361	-23.56	57.68	34.12	74.00	39.88	PASS	Vertical	PK
5	24621.7649	-21.88	57.15	35.27	74.00	38.73	PASS	Vertical	PK
6	26159.6464	-21.27	57.30	36.03	74.00	37.97	PASS	Vertical	PK

Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2402MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	1900.46	14.61	34.59	49.20	74.00	24.80	PASS	Horizontal	PK
2	2959.0639	17.73	35.13	52.86	74.00	21.14	PASS	Horizontal	PK
3	4804.1203	-8.60	56.16	47.56	74.00	26.44	PASS	Horizontal	PK
4	8231.3488	-1.13	50.53	49.40	74.00	24.60	PASS	Horizontal	PK
5	13674.7116	7.36	50.50	57.86	74.00	16.14	PASS	Horizontal	PK
6	16430.8954	10.60	49.41	60.01	74.00	13.99	PASS	Horizontal	PK
7	13765.7177	7.35	38.32	45.67	54.00	8.33	PASS	Horizontal	AV
8	16426.8951	10.51	38.21	48.72	54.00	5.28	PASS	Horizontal	AV

Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2402MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	1895.7931	14.49	43.49	57.98	74.00	16.02	PASS	Vertical	PK
2	2965.5977	17.85	35.98	53.83	74.00	20.17	PASS	Vertical	PK
3	5344.1563	-6.95	54.10	47.15	74.00	26.85	PASS	Vertical	PK
4	10054.4703	1.70	50.32	52.02	74.00	21.98	PASS	Vertical	PK
5	13759.7173	7.28	49.43	56.71	74.00	17.29	PASS	Vertical	PK
6	16194.8797	10.42	49.23	59.65	74.00	14.35	PASS	Vertical	PK
7	1899.9267	14.60	33.25	47.85	54.00	6.15	PASS	Vertical	AV
8	13721.7148	7.22	38.21	45.43	54.00	8.57	PASS	Vertical	AV
9	16335.8891	11.41	36.12	47.53	54.00	6.47	PASS	Vertical	AV

Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2402MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18594.6838	-26.69	62.62	35.93	74.00	38.07	PASS	Horizontal	PK
2	19996.2198	-24.63	60.75	36.12	74.00	37.88	PASS	Horizontal	PK
3	21797.6119	-25.53	61.01	35.48	74.00	38.52	PASS	Horizontal	PK
4	23894.4758	-22.14	57.70	35.56	74.00	38.44	PASS	Horizontal	PK
5	25354.8342	-21.35	56.56	35.21	74.00	38.79	PASS	Horizontal	PK
6	26431.6573	-21.17	57.24	36.07	74.00	37.93	PASS	Horizontal	PK

Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2402MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18339.3336	-26.78	63.56	36.78	74.00	37.22	PASS	Vertical	PK
2	20137.3255	-25.23	60.74	35.51	74.00	38.49	PASS	Vertical	PK
3	21973.0589	-25.78	60.14	34.36	74.00	39.64	PASS	Vertical	PK
4	23453.8182	-23.43	57.73	34.30	74.00	39.70	PASS	Vertical	PK
5	24929.8172	-22.08	56.17	34.09	74.00	39.91	PASS	Vertical	PK
6	26214.3886	-21.35	57.03	35.68	74.00	38.32	PASS	Vertical	PK

Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2440MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	1897.1265	14.53	35.68	50.21	74.00	23.79	PASS	Horizontal	PK
2	2912.6608	17.72	34.60	52.32	74.00	21.68	PASS	Horizontal	PK
3	5795.1863	-5.79	53.21	47.42	74.00	26.58	PASS	Horizontal	PK
4	11706.5804	2.62	52.19	54.81	74.00	19.19	PASS	Horizontal	PK
5	13785.719	7.58	50.19	57.77	74.00	16.23	PASS	Horizontal	PK
6	16489.8993	11.74	47.74	59.48	74.00	14.52	PASS	Horizontal	PK
7	1900.7267	14.61	19.76	34.37	54.00	19.63	PASS	Horizontal	AV
8	13824.7216	7.44	38.48	45.92	54.00	8.08	PASS	Horizontal	AV
9	16424.895	10.47	37.39	47.86	54.00	6.14	PASS	Horizontal	AV

Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2440MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	1899.5266	14.59	41.47	56.06	74.00	17.94	PASS	Vertical	PK
2	2984.399	17.89	35.52	53.41	74.00	20.59	PASS	Vertical	PK
3	5932.1955	-5.56	51.58	46.02	74.00	27.98	PASS	Vertical	PK
4	10239.4826	1.89	50.42	52.31	74.00	21.69	PASS	Vertical	PK
5	13740.716	7.18	49.27	56.45	74.00	17.55	PASS	Vertical	PK
6	16259.884	10.54	49.59	60.13	74.00	13.87	PASS	Vertical	PK
7	1900.06	14.60	32.48	47.08	54.00	6.92	PASS	Vertical	AV
8	13677.7118	7.35	38.46	45.81	54.00	8.19	PASS	Vertical	AV
9	16349.89	11.58	36.00	47.58	54.00	6.42	PASS	Vertical	AV

Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2440MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18522.6009	-26.69	62.59	35.90	74.00	38.10	PASS	Horizontal	PK
2	19819.7528	-25.17	60.97	35.80	74.00	38.20	PASS	Horizontal	PK
3	21316.8327	-25.83	60.11	34.28	74.00	39.72	PASS	Horizontal	PK
4	22942.4377	-25.49	58.49	33.00	74.00	41.00	PASS	Horizontal	PK
5	24505.8202	-21.78	56.69	34.91	74.00	39.09	PASS	Horizontal	PK
6	25967.5387	-20.89	57.27	36.38	74.00	37.62	PASS	Horizontal	PK

Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2440MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	18527.7011	-26.69	62.61	35.92	74.00	38.08	PASS	Vertical	PK
2	20043.8218	-24.82	60.94	36.12	74.00	37.88	PASS	Vertical	PK
3	21878.8752	-25.64	60.30	34.66	74.00	39.34	PASS	Vertical	PK
4	23377.9951	-23.64	57.96	34.32	74.00	39.68	PASS	Vertical	PK
5	25085.2034	-21.67	56.54	34.87	74.00	39.13	PASS	Vertical	PK
6	26350.054	-21.22	56.72	35.50	74.00	38.50	PASS	Vertical	PK

Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2480MHz
Tset_Engineer	\	Test_Date	2026/9/8


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1900.1933	14.60	37.92	52.52	74.00	21.48	PASS	Horizontal	PK
2	2996.9331	17.85	36.12	53.97	74.00	20.03	PASS	Horizontal	PK
3	5310.154	-7.05	52.84	45.79	74.00	28.21	PASS	Horizontal	PK
4	10217.4812	1.69	50.37	52.06	74.00	21.94	PASS	Horizontal	PK
5	13739.716	7.19	50.23	57.42	74.00	16.58	PASS	Horizontal	PK
6	16618.9079	10.82	49.18	60.00	74.00	14.00	PASS	Horizontal	PK
7	1900.1933	14.60	23.41	38.01	54.00	15.99	PASS	Horizontal	AV
8	13755.717	7.23	38.32	45.55	54.00	8.45	PASS	Horizontal	AV
9	16511.9008	11.92	36.47	48.39	54.00	5.61	PASS	Horizontal	AV

Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2480MHz
Tset_Engineer	\	Test_Date	2026/9/8

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1899.9267	14.60	41.65	56.25	74.00	17.75	PASS	Vertical	PK
2	2975.065	17.90	34.06	51.96	74.00	22.04	PASS	Vertical	PK
3	6155.2103	-4.74	50.90	46.16	74.00	27.84	PASS	Vertical	PK
4	10296.4864	1.90	50.09	51.99	74.00	22.01	PASS	Vertical	PK
5	13756.7171	7.24	49.40	56.64	74.00	17.36	PASS	Vertical	PK
6	16346.8898	11.54	47.97	59.51	74.00	14.49	PASS	Vertical	PK
7	1900.06	14.60	29.99	44.59	54.00	9.41	PASS	Vertical	AV
8	13759.7173	7.28	38.22	45.50	54.00	8.50	PASS	Vertical	AV
9	16414.8943	10.27	37.87	48.14	54.00	5.86	PASS	Vertical	AV