RF MEASUREMENT REPORT

FCC ID:	SFKWF196
Applicant:	CIG Shanghai Co., Ltd.
Product:	Tri-band 4x4 Wi-Fi 6E Wireless AP
Model No.:	WF-196, API7340
Brand Name:	CIG, Actiontec
FCC Classification:	Digital Transmission System (DTS)
FCC Rule Part(s):	Part 15 Subpart C (Section 15.247)
Result:	Complies
Test Date:	2022-07-23 ~ 2022-08-22

Reviewed By: Kevin Guo

Approved By: Robin Wu

ACCREDITED
TESTING LABORATORY
CERTIFICATE #3628.01

The test results relate only to the samples tested.
This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.
The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2207RSU033-U2	Rev. 01	Initial Report	2022-09-02	Valid

CONTENTS

Description Page

1. General Information 5

1.1. Applicant 5

1.2. Manufacturer 5

1.3. Testing Facility 5

1.4. Product Information 6

1.5. Radio Specification under Test 6

1.6. Working Frequencies 7

1.7. Antenna Details 7

2. Test Configuration 9

2.1. Test Mode 9

2.2. Test System Connection Diagram 9

2.3. Test Software 10

2.4. Applied Standards 10

2.5. Test Environment Condition 10

3. Antenna Requirements 11

4. Measuring Instrument 12

5. Decision Rules and Measurement Uncertainty 13

5.1. Decision Rules 13

5.2. Measurement Uncertainty 13

6. Test Result 14

6.1. Summary 14

6.2. 6dB Bandwidth Measurement 15

6.2.1. Test Limit 15

6.2.2. Test Procedure 15

6.2.3. Test Setting 15

6.2.4. Test Setup 15

6.2.5. Test Result 15

6.3. Output Power Measurement 16

6.3.1. Test Limit 16

6.3.2. Test Procedure 16

6.3.3. Test Setting 16

6.3.4. Test Setup 16

6.3.5. Test Result 16

6.4. Power Spectral Density Measurement 17

6.4.1. Test Limit 17

6.4.2. Test Procedure 17

6.4.3. Test Setting 17
6.4.4. Test Setup 17
6.4.5. Test Result 18
6.5. Conducted Band Edge and Out-of-Band Emissions Measurement 19
6.5.1. Test Limit 19
6.5.2. Test Procedure 19
6.5.3. Test Settitng 19
6.5.4. Test Setup 19
6.5.5. Test Result 20
6.6. Radiated Spurious Emission Measurement 21
6.6.1. Test Limit 21
6.6.2. Test Procedure 21
6.6.3. Test Setting 21
6.6.4. Test Setup 23
6.6.5. Test Result 23
6.7. Radiated Restricted Band Edge Measurement 24
6.7.1. Test Limit 24
6.7.2. Test Procedure 25
6.7.3. Test Setting 25
6.7.4. Test Setup 26
6.7.5. Test Result 26
6.8. AC Conducted Emissions Measurement 27
6.8.1. Test Limit 27
6.8.2. Test Setup 27
6.8.3. Test Result 27
Appendix A – Test Result 28
A.1 Duty Cycle Test Result 28
A.2 6dB Bandwidth Test Result 30
A.3 Output Power Test Result 37
A.4 Power Spectral Density Test Result 39
A.5 Conducted Band Edge and Out-of-Band Emissions Test Result 64
A.6 Radiated Spurious Emission Test Result 113
A.7 Radiated Restricted Band Edge Test Result 121
A.8 AC Conducted Emissions Test Result 169
Appendix B – Test Setup Photograph 171
Appendix C – EUT Photograph 172

1. General Information

1.1. Applicant

CIG Shanghai Co., Ltd.

5F, Building 8, NO.2388 CHENGHANG ROAD, MINHANG DISTRTCT, SHANGHAI

1.2. Manufacturer

CIG Shanghai Co., Ltd.

5F, Building 8, NO.2388 CHENGHANG ROAD, MINHANG DISTRTCT, SHANGHAI

1.3. Testing Facility

☒	**Test Site – MRT Suzhou Laboratory**
	Laboratory Location (Suzhou - Wuzhong) D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China **Laboratory Location (Suzhou - SIP)** 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China
	Laboratory Accreditations
	A2LA: 3628.01 CNAS: L10551 FCC: CN1166 ISED: CN0001 VCCI: ☐R-20025 ☐G-20034 ☐C-20020 ☐T-20020 ☐R-20141 ☐G-20134 ☐C-20103 ☐T-20104
☒	**Test Site – MRT Shenzhen Laboratory**
	Laboratory Location (Shenzhen) 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China
	Laboratory Accreditations
	A2LA: 3628.02 CNAS: L10551 FCC: CN1284 ISED: CN0105
☐	**Test Site – MRT Taiwan Laboratory**
	Laboratory Location (Taiwan) No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
	Laboratory Accreditations
	TAF: L3261-190725 FCC: 291082, TW3261 ISED: TW3261

1.4. Product Information

Product Name	Tri-band 4x4 Wi-Fi 6E Wireless AP
Model No.	WF-196, API7340
EUT Identification No.	20220719Sample#05 (Conducted) 20220719Sample#08 (Radiated)
Wi-Fi Specification	802.11a/b/g/n/ac/ax
Bluetooth Specification	V5.0 (BLE only)
Antenna Information	Refer to Section 1.7
Power Type	AC Adapter Input or PoE Input
Operating Environment	Indoor Use

Remark:

1. The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.
2. Different models correspond to different brands, and the others are exactly the same.

1.5. Radio Specification under Test

Frequency Range	802.11b/g/n-HT20/ax-HE20: 2412 ~ 2462MHz 802.11n-HT40/ax-HE40: 2422 ~ 2452MHz
Channel Number	802.11b/g/n-HT20/ax-HE20: 11 802.11n-HT40/ax-HE40: 9
Type of Modulation	802.11b: DSSS 802.11g/n: OFDM 802.11ax: OFDMA
Data Rate	802.11b: 1/2/5.5/11Mbps 802.11g: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 600Mbps 802.11ax: up to 1147.2Mbps

1.6. Working Frequencies

802.11b/g/n-HT20/ax-HE20

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz	--	--

802.11n-HT40/ax-HE40

Channel	Frequency	Channel	Frequency	Channel	Frequency
03	2422 MHz	04	2427 MHz	05	2432 MHz
06	2437 MHz	07	2442 MHz	08	2447 MHz
09	2452 MHz	--	--	--	--

1.7. Antenna Details

Antenna Type	Frequency (MHz)	TX Path	Antenna Gain (dBi)				Directional Gain (dBi)	
			Ant 0	Ant 1	Ant 2	Ant 3	Correlated	Uncorrelated
Wi-Fi Antenna								
PIFA	2412 ~ 2462	4	4.1	3.2	4.4	3.7	8.3	2.3
	5150 ~ 5850	4	4.4	4.2	3.7	4.1	9.0	3.0
	5925 ~ 7125	4	6.6	6.2	3.3	6.1	8.8	3.1
Bluetooth Antenna								
PIFA	2402 ~ 2480	1	4.2				--	

Remark:

1. The antenna gain and directional gain refer to manufacturer's antenna specification.
2. The device supports CDD Mode and STBC mode, details refer to the table as below.
3. CDD signals are correlated, the directional gain as follows,

   For power measurements: Array Gain = 0 dB for $N_{ANT} \leq 4$, the directional gain = max antenna gain + array gain

   For power spectral density (PSD) measurements: the max directional gain (each angle) = $10 \log[(10^{G1/20} + 10^{G2/20} + \ldots + 10^{GN/20})^2 / N_{ANT}]$
4. STBC signals are uncorrelated, the directional gain as follows,

   the max directional gain (each angle) = $10 \log[(10^{G1/10} + 10^{G2/10} + \ldots + 10^{GN/10})/N_{ANT}]$

Test Mode	T_X Paths	CDD Mode	STBC Mode
Wi-Fi 2.4G			
802.11b/g	4	√	X
802.11n/ax	4	X	√
Wi-Fi 5G			
802.11a	4	√	X
802.11n/ac/ax	4	X	√
Wi-Fi 6G			
802.11ax	4	X	√
Remark: “√” means “Support”, “X” means “Not support”.			

2. Test Configuration

2.1. Test Mode

Mode 1: Transmit by 802.11b (5.5Mbps) _ Nss=1 (CDD Mode)
Mode 2: Transmit by 802.11g (6Mbps) _ Nss=1 (CDD Mode)
Mode 3: Transmit by 802.11n-HT20 (MCS4) _ Nss=4 (STBC Mode)
Mode 4: Transmit by 802.11n-HT40 (MCS7) _ Nss=4 (STBC Mode)
Mode 5: Transmit by 802.11ax-HE20 (MCS5) _ Nss=4 (STBC Mode)
Mode 6: Transmit by 802.11ax-HE40 (MCS11) _ Nss=4 (STBC Mode)
Remark: 1. For Radiated emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power. 2. For CDD mode, this device supports 4 Nss and power level is the same of spatial multiplexing. The worst case is Nss=1. 3. EUT supports one configuration only in 802.11ax full RU mode.

2.2. Test System Connection Diagram

The device was tested per the guidance ANSI C63.10: 2013 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.

Connection Diagram – Radiated Emission testing & AC Conducted Emissions



No.	Cable Type	Cable Spec.	Length
A	LAN Cable	Non-Shielded	>10 m
B	LAN Cable	Non-Shielded	1.2m

No.	Product	Manufacturer	Model No.
1	Adapter	Shenzhen Honor Electronic Co., Ltd	ADT-38FKJ-PCU00F
2	Notebook	Lenovo	E431

Note: Adapter is provided by manufacturer for test only, it will not be sold with product.

2.3. Test Software

The test utility software used during testing was “QRCT”, and the version was 4.0.

Note: Final power setting please refer to operational description

2.4. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.247
- KDB 558074 D01v05r02
- KDB 662911 D01v02r01
- ANSI C63.10-2013

2.5. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20 ~ 75%RH

3. Antenna Requirements

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antenna of the device is **permanently attached.**
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

4. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2022-12-29	WZ-AC1
Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06023	1 year	2022-09-16	WZ-AC1
Preamplifier	Agilent	83017A	MRTSUE06076	1 year	2022-11-12	WZ-AC1
TRILOG Antenna	Schwarzbeck	VULB 9168	MRTSUE06172	1 year	2023-06-21	WZ-AC1
Anechoic Chamber	TDK	WZ-AC1	MRTSUE06212	1 year	2023-04-21	WZ-AC1
Thermohygrometer	testo	608-H1	MRTSUE06403	1 year	2023-06-06	WZ-AC1
Signal Analyzer	Keysight	N9010B	MRTSUE06607	1 year	2022-12-29	WZ-AC1
Thermohygrometer	testo	Testo 608-H1	MRTSUE11039	1 year	2022-11-11	WZ-AC1
Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06597	1 year	2022-12-01	WZ-AC1
Preamplifier	EMCI	EMC184045SE	MRTSUE06640	1 year	2023-01-13	WZ-AC1
Two-Line V-Network	R&S	ENV216	MRTSUE06002	1 year	2023-06-04	WZ-SR2
Shielding Room	MIX-BEP	WZ-SR2	MRTSUE06215	N/A	N/A	WZ-SR2
Thermohygrometer	testo	608-H1	MRTSUE06404	1 year	2023-06-06	WZ-SR2
Four-Line V-Network	R&S	ENV432	MRTSUE06615	1 year	2022-10-13	WZ-SR2
EMI Test Receiver	R&S	ESR3	MRTSUE06909	1 year	2022-11-01	WZ-SR2
Signal Analyzer	Agilent	N9010A	MRTSUE06195	1 year	2023-04-13	NS-TR2
Signal Analyzer	Keysight	N9020A	MRTSUE10065	1 year	2023-01-11	NS-TR2
USB Power Sensor	Keysight	U2021XA	MRTSUE06581	1 year	2022-08-15	NS-TR2
Thermohygrometer	DELI	NO.8813	MRTSUE06783	1 year	2023-04-14	NS-TR2
Temperature Chamber	OUKE	OK-TH-100C	MRTSUE06899	1 year	2022-11-01	NS-TR2
Attenuator	MVE	MVE2213	MRTSUE11062	1 year	2023-06-09	NS
Attenuator	MVE	MVE2213	MRTSUE11063	1 year	2023-06-09	NS
Attenuator	MVE	MVE2213	MRTSUE11064	1 year	2023-06-09	NS

Software	Version	Function
EMI Software	V3.0.0	EMI Test Software
Controller_MF 7802	2.03C	RE Antenna & Turntable
BenchVue Power Meter	2021	Power

5. Decision Rules and Measurement Uncertainty

5.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2.

(Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

AC Conducted Emission Measurement
Measurement Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 9kHz~150kHz: 3.74dB 150kHz~30MHz: 3.44dB
Radiated Disturbance
Measurement Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): Horizontal: 30MHz~300MHz: 5.04dB 300MHz~1GHz: 4.95dB 1GHz~40GHz: 6.40dB Vertical: 30MHz~300MHz: 5.24dB 300MHz~1GHz: 6.03dB 1GHz~40GHz: 6.40dB
Spurious Emissions, Conducted
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 0.78dB
Output Power
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 1.13dB
Power Spectrum Density
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 1.15dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 0.28%

6. Test Result

6.1. Summary

FCC Section(s)	Test Description	Test Condition	Verdict
15.247(a)(2)	6dB Bandwidth	Conducted	Pass
15.247(b)(3)	Output Power		Pass
15.247(e)	Power Spectral Density		Pass
15.247(d)	Band Edge / Out-of-Band Emissions		Pass
15.205 15.209	General Field Strength (Restricted Bands and Radiated Emission)	Radiated	Pass
15.207	AC Conducted Emissions 150kHz - 30MHz	Line Conducted	Pass

Remark:

1. The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
2. For radiated emission tests, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.

6.2. 6dB Bandwidth Measurement

6.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.

6.2.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.8

6.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3. VBW ≥ 3 × RBW
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace to stabilize

6.2.4. Test Setup



6.2.5. Test Result

Refer to Appendix A.2.

6.3. Output Power Measurement

6.3.1. Test Limit

The maximum output power shall be less 1 Watt (30dBm).

The conducted output power limit specified in paragraph FCC Part 15.247(b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs FCC Part 15.247(b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.3.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.9.2.3.2

6.3.3. Test Setting

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

6.3.4. Test Setup

6.3.5. Test Result

Refer to Appendix A.3.

6.4. Power Spectral Density Measurement

6.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

The same method of determining the conducted output power shall be used to determine the power spectral density.

6.4.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.10.5

6.4.3. Test Setting

1. Measure the duty cycle (x) of the transmitter output signal.
2. Set instrument center frequency to DTS channel center frequency.
3. Set span to at least 1.5 times the OBW.
4. RBW = 10 kHz.
5. VBW = 30 kHz.
6. Detector = RMS.
7. Ensure that the number of measurement points in the sweep ≥ 2 x span/RBW.
8. Sweep time = auto couple.
9. Don’t use sweep triggering. Allow sweep to “free run”.
10. Employ trace averaging (RMS) mode over a minimum of 100 traces.
11. Use the peak marker function to determine the maximum amplitude level.
12. Add 10 log (1/x), where x is the duty cycle measured in step (a, to the measured PSD to compute the average PSD during the actual transmission time. If measured value exceeds requirement specified by regulatory agency, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

6.4.4. Test Setup



6.4.5. Test Result

Refer to Appendix A.4.

6.5. Conducted Band Edge and Out-of-Band Emissions Measurement

6.5.1. Test Limit

The limit for out-of-band spurious emissions at the band edge is 30dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth per the PSD procedure.

6.5.2. Test Procedure

ANSI C63.10-2013 - Section 11.11

6.5.3. Test Settitng

Reference level measurement

1. Set instrument center frequency to DTS channel center frequency
2. Set the span to ≥ 1.5 times the DTS bandwidth
3. Set the RBW = 100 kHz
4. Set the VBW ≥ 3 x RBW
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Allow trace to fully stabilize

Emission level measurement

1. Set the center frequency and span to encompass frequency range to be measured
2. RBW = 100kHz
3. VBW = 300kHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

6.5.4. Test Setup



6.5.5. Test Result

Refer to Appendix A.5.

6.6. Radiated Spurious Emission Measurement

6.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.6.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.11 & 11.12

ANSI C63.10 - 2013 - Section 6.3 (General Requirements)

ANSI C63.10 - 2013 - Section 6.4 (Standard test method below 30MHz)

ANSI C63.10 - 2013 - Section 6.5 (Standard test method above 30MHz to 1GHz)

ANSI C63.10 - 2013 - Section 6.6 (Standard test method above 1GHz)

6.6.3. Test Setting

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000MHz	1MHz

Quasi-Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest

2. Span was set greater than 1MHz

3. RBW = as specified in Table 1

4. Detector = CISPR quasi-peak

5. Sweep time = auto couple

6. Trace was allowed to stabilize

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest

2. RBW = 1MHz

3. VBW = 3MHz

4. Detector = peak

5. Sweep time = auto couple

6. Trace mode = max hold

7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest

2. RBW = 1MHz

3. VBW; If the EUT is configured to transmit with duty cycle ≥ 98%, set VBW = 10 Hz.

If the EUT duty cycle is < 98%, set VBW ≥ 1/T. T is the minimum transmission duration.

4. Detector = Peak

5. Sweep time = auto

6. Trace mode = max hold

7. Trace was allowed to stabilize

6.6.4. Test Setup

Below 1GHz Test Setup:



Above 1GHz Test Setup:



6.6.5. Test Result

Refer to Appendix A.6.

6.7. Radiated Restricted Band Edge Measurement

6.7.1. Test Limit

For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1] 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	([2])
13.36 - 13.41	--	--	--

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.7.2. Test Procedure

ANSI C63.10-2013 Section 6.3 & 6.6 & 11.13

6.7.3. Test Setting

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW ≥ 1/T
4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces

6.7.4. Test Setup



6.7.5. Test Result

Refer to Appendix A.7.

6.8. AC Conducted Emissions Measurement

6.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50
Note 1: The lower limit shall apply at the transition frequencies. Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.		

6.8.2. Test Setup



6.8.3. Test Result

Refer to Appendix A.8.

Appendix A – Test Result

A.1 Duty Cycle Test Result

Test Site	NS-TR2	Test Engineer	Summer Tang
Test Date	2022-08-04		

Test Mode	Duty Cycle	Test Mode	Duty Cycle
802.11b	75.96%	802.11n-HT40	94.27%
802.11g	96.58%	802.11ax-HE20	94.53%
802.11n-HT20	94.75%	802.11ax-HE40	95.03%

Duty Cycle (T = Transmission Duration)

802.11b (T = 4.740ms)



802.11g (T = 1.975ms)

802.11n-HT20 (T = 5.415ms)



802.11n-HT40 (T = 5.430ms)



Duty Cycle (T = Transmission Duration)	
802.11ax-HE20 (T = 5.445ms)	802.11ax-HE40 (T = 5.445ms)
	

A.2 6dB Bandwidth Test Result

Test Site	NS-TR2	Test Engineer	Summer Tang
Test Date	2022-08-05		

Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
11b	5.5Mbps	01	2412	8.317	≥ 0.5
11b	5.5Mbps	06	2437	6.716	≥ 0.5
11b	5.5Mbps	11	2462	6.709	≥ 0.5
11g	6Mbps	01	2412	16.39	≥ 0.5
11g	6Mbps	06	2437	16.38	≥ 0.5
11g	6Mbps	11	2462	16.34	≥ 0.5
11n-HT20	MCS4	01	2412	17.76	≥ 0.5
11n-HT20	MCS4	06	2437	17.77	≥ 0.5
11n-HT20	MCS4	11	2462	17.73	≥ 0.5
11n-HT40	MCS7	03	2422	36.55	≥ 0.5
11n-HT40	MCS7	06	2437	36.50	≥ 0.5
11n-HT40	MCS7	09	2452	36.53	≥ 0.5
11ax-HE20	MCS5	01	2412	19.15	≥ 0.5
11ax-HE20	MCS5	06	2437	19.14	≥ 0.5
11ax-HE20	MCS5	11	2462	19.14	≥ 0.5
11ax-HE40	MCS11	03	2422	38.25	≥ 0.5
11ax-HE40	MCS11	06	2437	38.26	≥ 0.5
11ax-HE40	MCS11	09	2452	38.26	≥ 0.5

802.11b 6dB Bandwidth

Channel 01 (2412MHz)



Channel 06 (2437MHz)



Channel 11 (2462MHz)



802.11g 6dB Bandwidth	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11n-HT20 6dB Bandwidth	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11n-HT40 6dB Bandwidth	
Channel 03 (2422MHz)	Channel 06 (2437MHz)
	
Channel 09 (2452MHz)	
	

802.11ax-HE20 6dB Bandwidth	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11ax-HE40 6dB Bandwidth	
Channel 03 (2422MHz)	Channel 06 (2437MHz)
	
Channel 09 (2452MHz)	
	

A.3 Output Power Test Result

Power output test was verified over all data rates of each mode shown as below, and then choose the maximum power output (gray marker) for final test of each channel.

Test Mode	Bandwidth (MHz)	Channel No.	Frequency (MHz)	Data Rate / MCS	Average Power (dBm)
802.11b	20	1	2412	1Mbps	18.72
				5.5Mbps	18.80
				11Mbps	18.78
802.11g	20	1	2412	6Mbps	18.76
				24Mbps	18.24
				54Mbps	18.02
802.11n	20	1	2412	MCS0	18.65
				MCS4	18.72
				MCS7	18.63
802.11n	40	3	2422	MCS0	18.67
				MCS4	18.69
				MCS7	18.73
802.11ax	20	1	2412	MCS0	19.16
				MCS5	19.41
				MCS11	19.37
802.11ax	40	3	2422	MCS0	19.04
				MCS5	19.17
				MCS11	19.19

Test Site	NS-TR2	Test Engineer	Summer Tang
Test Date	2022-08-05		

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Average Power (dBm)				Total Power (dBm)	Limit (dBm)
				Ant 0	Ant 1	Ant 2	Ant 3		
11b	5.5Mbps	01	2412	17.61	17.66	17.73	17.88	23.74	≤ 30.00
11b	5.5Mbps	06	2437	17.60	17.79	17.69	17.37	23.64	≤ 30.00
11b	5.5Mbps	11	2462	17.81	17.93	17.92	17.54	23.82	≤ 30.00
11g	6Mbps	01	2412	15.70	15.71	15.74	15.80	21.76	≤ 30.00
11g	6Mbps	06	2437	17.45	17.63	17.54	17.86	23.64	≤ 30.00
11g	6Mbps	11	2462	15.04	15.18	15.21	15.06	21.14	≤ 30.00
11n-HT20	MCS4	01	2412	15.72	15.62	15.98	15.49	21.73	≤ 30.00
11n-HT20	MCS4	06	2437	17.55	17.50	17.63	17.57	23.58	≤ 30.00
11n-HT20	MCS4	11	2462	15.68	15.65	15.52	15.67	21.65	≤ 30.00
11n-HT40	MCS7	03	2422	14.95	15.17	14.92	15.31	21.11	≤ 30.00
11n-HT40	MCS7	06	2437	17.45	17.61	17.81	17.63	23.65	≤ 30.00
11n-HT40	MCS7	09	2452	15.07	15.45	15.03	15.25	21.22	≤ 30.00
11ax-HE20	MCS5	01	2412	14.97	15.20	15.45	14.95	21.17	≤ 30.00
11ax-HE20	MCS5	06	2437	17.53	17.72	17.86	17.76	23.74	≤ 30.00
11ax-HE20	MCS5	11	2462	15.25	15.38	15.15	15.40	21.32	≤ 30.00
11ax-HE40	MCS11	03	2422	15.52	15.69	15.97	15.72	21.75	≤ 30.00
11ax-HE40	MCS11	06	2437	17.57	17.68	17.44	17.96	23.69	≤ 30.00
11ax-HE40	MCS11	09	2452	15.06	15.40	15.63	15.27	21.37	≤ 30.00

Note: Total Power (dBm) = $10*\log \{10^{(\text{Ant 0 Average Power /10})} + 10^{(\text{Ant 1 Average Power /10})} + 10^{(\text{Ant 2 Average Power /10})} + 10^{(\text{Ant 3 Average Power /10})}\}$.

A.4 Power Spectral Density Test Result

Test Site	NS-TR2	Test Engineer	Summer Tang
Test Date	2022-08-05~2022-08-08		

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	PSD (dBm/10kHz)				Total PSD (dBm/10kHz)	Limit (dBm/3kHz)	Result
				Ant 0	Ant 1	Ant 2	Ant 3			
11b	5.5Mbps	01	2412	-6.602	-6.585	-6.087	-6.348	0.81	≤ 8.00	Pass
11b	5.5Mbps	06	2437	-6.519	-6.500	-6.810	-6.338	0.68	≤ 8.00	Pass
11b	5.5Mbps	11	2462	-6.730	-6.294	-6.048	-6.813	0.75	≤ 8.00	Pass
11g	6Mbps	01	2412	-13.462	-12.847	-12.761	-12.990	-6.83	≤ 8.00	Pass
11g	6Mbps	06	2437	-12.096	-11.218	-11.940	-11.002	-5.37	≤ 8.00	Pass
11g	6Mbps	11	2462	-13.953	-14.035	-13.786	-14.095	-7.79	≤ 8.00	Pass
11n-HT20	MCS4	01	2412	-13.384	-13.597	-12.250	-13.446	-6.88	≤ 8.00	Pass
11n-HT20	MCS4	06	2437	-11.140	-11.849	-10.979	-11.619	-5.13	≤ 8.00	Pass
11n-HT20	MCS4	11	2462	-12.992	-13.488	-12.760	-13.560	-6.93	≤ 8.00	Pass
11n-HT40	MCS7	03	2422	-16.588	-16.084	-15.527	-16.445	-9.86	≤ 8.00	Pass
11n-HT40	MCS7	06	2437	-13.908	-14.138	-13.286	-13.633	-7.45	≤ 8.00	Pass
11n-HT40	MCS7	09	2452	-16.307	-16.210	-15.783	-16.094	-9.82	≤ 8.00	Pass
11ax-HE20	MCS5	01	2412	-15.931	-16.043	-15.680	-15.740	-9.58	≤ 8.00	Pass
11ax-HE20	MCS5	06	2437	-13.039	-12.811	-12.683	-13.094	-6.64	≤ 8.00	Pass
11ax-HE20	MCS5	11	2462	-15.465	-14.615	-15.401	-14.621	-8.74	≤ 8.00	Pass
11ax-HE40	MCS11	03	2422	-18.096	-17.373	-17.258	-17.685	-11.35	≤ 8.00	Pass
11ax-HE40	MCS11	06	2437	-15.361	-16.046	-15.968	-16.133	-9.62	≤ 8.00	Pass
11ax-HE40	MCS11	09	2452	-17.639	-18.473	-17.668	-18.604	-11.83	≤ 8.00	Pass

Note: When EUT duty cycle < 98%, the total PSD (dBm/10kHz) =10*log {$10^{(\text{Ant 0 AVGPSD}/10)}$ + $10^{(\text{Ant 1 AVGPSD}/10)}$ +$10^{(\text{Ant 2 AVGPSD}/10)}$ + $10^{(\text{Ant 3 AVGPSD}/10)}$} +10*log (1/Duty cycle).

When EUT duty cycle ≥ 98%, the total PSD (dBm/10kHz) =10*log {$10^{(\text{Ant 0 AVGPSD}/10)}$ + $10^{(\text{Ant 1 AVGPSD}/10)}$ +$10^{(\text{Ant 2 AVGPSD}/10)}$ + $10^{(\text{Ant 3 AVGPSD}/10)}$}.

802.11b - Ant 0	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11g - Ant 0	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11n-HT20 - Ant 0	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11n-HT40 - Ant 0	
Channel 03 (2422MHz)	Channel 06 (2437MHz)
	
Channel 09 (2452MHz)	
	

802.11ax-HE20 - Ant 0	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11ax-HE40 - Ant 0	
Channel 03 (2422MHz)	Channel 06 (2437MHz)
	
Channel 09 (2452MHz)	
	

802.11b - Ant 1	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11g - Ant 1	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11n-HT20 - Ant 1	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11n-HT40 - Ant 1	
Channel 03 (2422MHz)	Channel 06 (2437MHz)
	
Channel 09 (2452MHz)	
	

802.11ax-HE20 - Ant 1	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11ax-HE40 - Ant 1	
Channel 03 (2422MHz)	Channel 06 (2437MHz)
	
Channel 09 (2452MHz)