REPORT No. : SZ14110027W09

FCC RF TEST REPORT

APPLICANT	:	Haier Telecom CO, Ltd
PRODUCT NAME	:	Smart phone
MODEL NAME	:	W717
TRADE NAME	:	Haier
BRAND NAME	:	Haier
FCC ID	:	SG71411HW-W717
STANDARD(S)	:	47 CFR Part 15 Subpart C
ISSUE DATE	:	2014-11-24

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB GROUP FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China Tel: 86-755-36698555 Http://www.morlab.com Fax: 86-755-36698525 E-mail: service@morlab.cn

DIRECTORY

TEST REPORT DECLARATION 4

1. TECHNICAL INFORMATION 5

1.1 APPLICANT INFORMATION 5
1.2 EQUIPMENT UNDER TEST (EUT) DESCRIPTION 5
1.2.1 IDENTIFICATION OF ALL USED EUTS 5
1.3 TEST STANDARDS AND RESULTS 6
1.3.1 TEST ENVIRONMENT CONDITIONS 6

2. 47 CFR PART 15C REQUIREMENTS 7

2.1 ANTENNA REQUIREMENT 7
2.1.1 APPLICABLE STANDARD 7
2.1.2 RESULT: COMPLIANT 7
2.2 PEAK OUTPUT POWER 7
2.2.1 REQUIREMENT 7
2.2.2 TEST DESCRIPTION 7
2.2.3 TEST RESULT 8
2.3 6DB BANDWIDTH 10
2.3.1 REQUIREMENT 10
2.3.2 TEST DESCRIPTION 10
2.3.3 TEST RESULT 10
2.4 CONDUCTED SPURIOUS EMISSIONS AND BAND EDGE 13
2.4.1 REQUIREMENT 13
2.4.2 TEST DESCRIPTION 13
2.4.3 TEST RESULT 13
2.5 POWER SPECTRAL DENSITY (PSD) 17
2.5.1 REQUIREMENT 17
2.5.2 TEST DESCRIPTION 17
2.5.3 TEST RESULT 17
2.6 RESTRICTED FREQUENCY BANDS 20
2.6.1 REQUIREMENT 20
2.6.2 TEST DESCRIPTION 20
2.6.3 TEST RESULT 21

2.7 CONDUCTED EMISSION 24
2.7.1 REQUIREMENT 24
2.7.2 TEST DESCRIPTION 24
2.7.3 TEST RESULT 25
2.8 RADIATED EMISSION 27
2.8.1 REQUIREMENT 27
2.8.2 TEST DESCRIPTION 28
2.8.3 TEST RESULT 30
2.9 RF EXPOSURE EVALUATION 34
2.9.1 REQUIREMENT 34
2.9.2 RESULT 34

ANNEX A GENERAL INFORMATION 35

Change History		
Issue	Date	Reason for change
1.0	2014-11-24	First edition

TEST REPORT DECLARATION

Applicant	Haier Telecom CO, Ltd
Applicant Address	Haier Information Park,Laoshan District, Qingdao China
Manufacturer	Haier Telecom CO, Ltd
Manufacturer Address	Haier Information Park,Laoshan District, Qingdao China
Product Name	Smart phone
Model Name	W717
Brand Name	Haier
HW Version	M08_V1.02_PCB_(140911)
SW Version	HW-W717-H01-S003-ES
Test Standards	47 CFR Part 15 Subpart C
Test Date	2014-11-11 to 2014-11-19
Test Result	PASS

Tested by : Wu Jianwu

Wu Jianwu

Reviewed by : Qiu Xiaojun

Qiu Xiaojun

Approved by : Zeng Dexin

Zeng Dexin

1. TECHNICAL INFORMATION

Note： Provide by applicant.

1.1 Applicant Information

Company:	Haier Telecom CO, Ltd
Address:	Haier Information Park,Laoshan District, Qingdao China

1.2 Equipment under Test (EUT) Description

Brand Name:	Haier
Trade Name:	Haier
Model Name:	W717
Frequency Range:	The frequency range used is 2402MHz - 2480MHz (40 channels, at intervals of 2MHz);
Modulation Type:	GFSK
Antenna Type:	PIFA Antenna
Antenna Gain:	-1dBi

NOTE:

The EUT is Smart phone, it contain Bluetooth 4.0 LE Module operating at 2.4GHz ISM band; the frequencies allocated for the Bluetooth 4.0 LE is F(MHz)=2402+2*n (0<=n<=39). The lowest, middle, highest channel numbers of the Bluetooth Module used and tested in this report are separately 0 (2402MHz), 19 (2440MHz) and 39 (2480MHz).

For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.2.1 Identification of all used EUTs

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
A01	M08_V1.02_PCB_(140911)	HW-W717-H01-S003-ES

1.3 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Bluetooth, 2.4GHz ISM band radiators) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-13 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	15.203	Antenna Requirement	**PASS**
2	15.247(b)	Peak Output Power	**PASS**
3	15.247(a)	Bandwidth	**PASS**
4	15.247(d)	Conducted Spurious Emission and Band Edge	**PASS**
5	15.247(d)	Restricted Frequency Bands	**PASS**
6	15.207	Conducted Emission	**PASS**
7	15.209 ,15.247(d)	Radiated Emission	**PASS**
8	15.247(e)	Power spectral density (PSD)	**PASS**
9	15.247(i),1.1307& 2.1093	RF exposure evaluation	**PASS**

The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.4 2009.

These RF tests were performed according to the method of measurements prescribed in KDB558074 D01 v03r02 (05/06/2014).

1.3.1 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106

2. 47 CFR PART 15C REQUIREMENTS

2.1 Antenna requirement

2.1.1 Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2 Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2 Peak Output Power

2.2.1 Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

2.2.2 Test Description

The measured output power was calculated by the reading of the spectrum analyzer and calibration.

A. Test Setup:



The EUT (Equipment under the test) which is powered by the Battery is coupled to the Spectrum analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in Spectrum analyzer.

B. Equipments List:

Please reference ANNEX A (1.4).

2.2.3 Test Result

The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Refer to Plot	Limit		Verdict
		dBm	W		dBm	W	
0	2402	-5.481	0.000283	Plot A	30	1	PASS
19	2440	-5.296	0.000295	Plot B			PASS
39	2480	-5.110	0.000310	Plot C			PASS

B. Test Plots:



(Plot A: Channel 0: 2402MHz)



(Plot B: Channel 19: 2440MHz)



(Plot C: Channel 39: 2480MHz)

2.3 6dB Bandwidth

2.3.1 Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

2.3.2 Test Description

A. Test Set:



The EUT which is powered by the battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

B. Equipments List:

Please reference ANNEX A(1.4).

2.3.3 Test Result

The lowest, middle and highest channels are selected to perform testing to record the 6 dB bandwidth of the module.

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Refer to Plot	Limits(kHz)	Result
0	2402	0.7321	Plot A	≥500	PASS
19	2440	0.7327	Plot B	≥500	PASS
39	2480	0.7267	Plot C	≥500	PASS

C. Test Plots:



(Plot A: Channel 0: 2402MHz)



(Plot B: Channel 19: 2440 MHz)



(Plot C: Channel 39: 2480MHz)

2.4 Conducted Spurious Emissions and Band Edge

2.4.1 Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.4.2 Test Description

A. Test Set:

The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

B. Equipments List:

Please reference ANNEX A (1.4).

2.4.3 Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
0	2402	-44.64	Plot A.1	-6.147	-26.1	PASS
19	2440	-46.88	Plot B.1	4.357	-15.6	PASS
39	2480	-47.42	Plot C.1	-7.377	-27.4	PASS

B. Test Plots:

Note: the power of the Module transmitting frequency should be ignored.



(Plot A.1: Channel = 0, 30MHz to 25GHz)



(Band Edge@ Channel = 0)



(Plot B.1: Channel = 19, 30MHz to 25GHz)



(Plot C.1: Channel = 39, 30MHz to 25GHz)



(Band Edge@ Channel = 39)

2.5 Power spectral density (PSD)

2.5.1 Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

2.5.2 Test Description

A. Test Set:



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

B. Equipments List:

Please reference ANNEX A (1.4).

2.5.3 Test Result

The lowest, middle and highest channels are tested.

A. Test Verdict:

Spectral power density (dBm/3kHz)					
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Refer to Plot	Limit (dBm/3kHz)	Verdict
0	2402	-20.13	Plot A	8	PASS
19	2440	-19.90	Plot B	8	PASS
39	2480	-19.77	Plot C	8	PASS
Measurement uncertainty: ±1.3dB					

B. Test Plots:



(Plot A: Channel = 0)



(Plot B: Channel = 19)



(Plot C: Channel = 39)

2.6 Restricted Frequency Bands

2.6.1 Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

2.6.2 Test Description

A. Test Setup



The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

B. Equipments List:

Please reference ANNEX A(1.4).

2.6.3 Test Result

The lowest and highest channels are tested to verify the Restricted Frequency Bands.

The measurement results are obtained as below:

E [dBμV/m] $=U_R + A_T + A_{Factor}$ [dB]; $A_T = L_{Cable\ loss}$ [dB]-G_{preamp} [dB]

A_T: Total correction Factor except Antenna

U_R: Receiver Reading

G_{preamp}: Preamplifier Gain

A_{Factor}: Antenna Factor at 3m

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.

A. Test Verdict:

Channel	Frequency (MHz)	Detector PK/ AV	Receiver Reading UR (dBuV)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
0	2387.52	PK	53.31	-33.63	32.56	52.24	74	Pass
0	2381.90	AV	34.72	-33.63	32.56	33.65	54	Pass
39	2487.41	PK	54.82	-33.18	32.5	54.14	74	Pass
39	2483.89	AV	34.98	-33.18	32.5	34.30	54	Pass

B. Test Plots:



(Plot A1: Channel = 0 PEAK)



(Plot A2: Channel = 0 AVG)



(Plot B1: Channel = 39 PEAK)



(Plot B2: Channel = 39 AVG)

2.7 Conducted Emission

2.7.1 Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dBμV)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

(a) The lower limit shall apply at the band edges.

(b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.7.2 Test Description

A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4:2009

B. Equipments List:

Please reference ANNEX A(1.4).

2.7.3 Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

A. Test setup:

The EUT configuration of the emission tests is EUT + Link.

B. Test Plots:



(Plot A: L Phase)



(Plot B: N Phase)

2.8 Radiated Emission

2.8.1 Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)

2.8.2 Test Description

C. Test Setup:

1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to1GHz



3) For radiated emissions above 1GHz



The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4 (2009). The EUT was set-up on insulator 80cm above the Ground Plane. The set-up and test methods were according to ANSI C63.4.

The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

(a) In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
(b) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

D. Equipments List:

Please reference ANNEX A(1.4).

2.8.3 Test Result

According to ANSI C63.4 selection 4.2.2, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

E [dBμV/m] $= U_R + A_T + A_{Factor}$ [dB]; $A_T = L_{Cable\ loss}$ [dB]$-G_{preamp}$ [dB]

A_T: Total correction Factor except Antenna

U_R: Receiver Reading

G_{preamp}: Preamplifier Gain

A_{Factor}: Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

The low frequency, which started from 9KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

E. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 0



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
78.379	27.31	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
102.569	16.90	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
233.192	22.85	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
436.384	25.19	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2402.000	49.52	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
13039.900	47.50	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
54.190	29.83	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
78.379	30.95	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
238.030	23.79	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
571.845	22.59	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2402.000	50.15	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
16825.436	47.66	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 19



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
59.027	23.23	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
78.379	26.42	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
233.192	20.30	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
511.372	26.23	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2440.000	51.54	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
18965.087	48.11	N.A	N.A	54.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
54.190	28.80	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
78.379	30.89	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
245.287	23.28	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
632.319	23.54	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2440.000	51.47	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
16825.436	47.64	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 39



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
78.379	26.56	N.A	N.A	N.A	40.0	N.A	Horizontal	PASS
182.394	16.48	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
233.192	20.51	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
504.115	26.69	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2480.000	48.07	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
15728.180	47.69	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
78.379	30.79	N.A	N.A	N.A	40.0	N.A	Vertical	PASS
233.192	24.63	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
571.845	22.49	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
1289.277	39.35	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
2480.000	47.39	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
13039.900	48.87	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

2.9 RF exposure evaluation

2.9.1 Requirement

According to § 1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy lever in excess of Commission's guideline.

2.9.2 Result

Please refer to SAR report.

ANNEX A GENERAL INFORMATION

1.1 Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

1.2 Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

1.3 Facilities and Accreditations

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at FL.1, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10 2009, ANSI C63.4 2009 and CISPR Publication 22; the FCC registration number is 695796.

The IC registration number is 7183A-2.

1.4 Test Equipments Utilized

1.4.1 Conducted Test Equipments

Conducted Test Equipment						
No.	**Equipment Name**	**Serial No.**	**Type**	**Manufacturer**	**Cal. Date**	**Cal. Due**
1	Spectrum Analyzer	MY45101810	E4407B	Agilent	2014.02.26	2015.02.25
2	Power Splitter	NW521	1506A	Weinschel	2014.02.26	2015.02.25
3	Attenuator 1	(n.a.)	10dB	Resnet	2014.02.26	2015.02.25
4	Attenuator 2	(n.a.)	3dB	Resnet	2014.02.26	2015.02.25
5	USB Wideband Power Sensor	MY52280010	U2021XA	Agilent	2014.02.26	2015.02.25
6	EXA Signal Analzyer	MY51440152	N9010A	Agilent	2014.02.26	2015.02.25
7	RF cable	CB01	RF01	Morlab	N/A	N/A
8	Coaxial cable	CB02	RF02	Morlab	N/A	N/A
9	SMA connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.4.2 Conducted Emission Test Equipments

Conducted Emission Test Equipments						
No.	**Equipment Name**	**Serial No.**	**Type**	**Manufacturer**	**Cal. Date**	**Cal. Due**
1	Receiver	US44210471	E7405A	Agilent	2014.02.26	2015.02.25
2	LISN	812744	NSLK 8127	Schwarzbeck	2014.02.26	2015.02.25
3	Service Supplier	100448	CMU200	R&S	2014.02.26	2015.02.25
4	Pulse Limiter (20dB)	9391	VTSD 9561-D	Schwarzbeck	2014.02.26	2015.02.25
5	Coaxial cable(BNC)	CB01	EMC01	Morlab	N/A	N/A

1.4.3 Radiated Test Equipments

Radiated Test Equipments						
No.	**Equipment Name**	**Serial No.**	**Type**	**Manufacturer**	**Cal. Date**	**Cal.Due Date**
1	Receiver	US44210471	E7405A	Agilent	2014.02.26	2015.02.25
2	Test Antenna - Bi-Log	9163-274	9m*6m*6m	Albatross	2014.02.26	2015.02.25
3	Test Antenna - Horn	9120D-963	VULB 9163	Schwarzbeck	2014.02.26	2015.02.25
4	Test Antenna - Horn	71688	BBHA 9120D	Schwarzbeck	2014.02.26	2015.02.25
5	Test Antenna - Loop	1519-022	HL050S7	R&S	2014.02.26	2015.02.25
6	Reject Filter	(n.a.)	BRM50702	Micro-Tronics	2014.02.26	2015.02.25
7	Coaxial cable (N male)	CB02	EMC02	Morlab	N/A	N/A
8	Coaxial cable (N male)	CB03	EMC03	Morlab	N/A	N/A

1.4.4 Climate Chamber

Climate Chamber						
No.	**Equipment Name**	**Serial No.**	**Type**	**Manufacturer**	**Cal.Date**	**Cal.Due Date**
1	Climate Chamber	2004012	HL4003T	Yinhe	2014.02.26	2015.02.25

1.4.5 Vibration Table

Vibration Table						
No.	**Equipment Name**	**Serial No.**	**Type**	**Manufacturer**	**Cal.Date**	**Cal.Due Date**
1	Vibration Table	N/A	ACT2000-S015L	CMI-COM	2014.02.26	2015.02.25

1.4.6 Anechoic Chamber

Anechoic Chamber						
No.	**Equipment Name**	**Serial No.**	**Type**	**Manufacturer**	**Cal.Date**	**Cal.Due Date**
1	Anechoic Chamber	N/A	9m*6m*6m	Albatross	2014.02.26	2015.02.25

***** END OF REPORT *****