



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Nanshan District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM160300168001
Rev.00
Page : 1 of 74

FCC SAR TEST REPORT

Application No: SZEM1603001680RG
Applicant: Haier Telecom (Qingdao) Co., Ltd.
Manufacturer/ Factory: Haier Telecom (Qingdao) Co., Ltd.
 Product Name: Mobilephone
 Model No.(EUT): V4
 Trade Mark: Haier
FCC ID: SG7201603V4
Standards: FCC 47CFR §2.1093
Date of Receipt: 2016-04-10
Date of Test: 2016-04-10 to 2016-04-22
Date of Issue: 2016-06-14
Test Result : **PASS ***

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



REVISION HISTORY

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2016-06-14		Original



TEST SUMMARY

Frequency Band	Test position	Test mode	Max Report SAR (W/kg)	SAR limit (W/kg)	Verdict
GSM850	Head	GSM	0.318	1.6	PASS
	Body-worn	GSM	0.442	1.6	PASS
	Hotspot	GPRS 4TS	0.911	1.6	PASS
GSM1900	Head	GSM	0.211	1.6	PASS
	Body-worn	GSM	0.270	1.6	PASS
	Hotspot	GPRS 2TS	0.787	1.6	PASS
WCDMA850	Head	RMC	0.280	1.6	PASS
	Body-worn	RMC	0.314	1.6	PASS
	Hotspot	RMC	0.481	1.6	PASS
WCDMA1700	Head	RMC	0.111	1.6	PASS
	Body-worn	RMC	0.267	1.6	PASS
	Hotspot	RMC	0.738	1.6	PASS
WCDMA1900	Head	RMC	0.229	1.6	PASS
	Body-worn	RMC	0.460	1.6	PASS
	Hotspot	RMC	0.852	1.6	PASS
LTE Band 2	Head	QPSK	0.220	1.6	PASS
	Body-worn	QPSK	0.496	1.6	PASS
	Hotspot	QPSK	1.091	1.6	PASS
LTE Band 4	Head	QPSK	0.063	1.6	PASS
	Body-worn	QPSK	0.297	1.6	PASS
	Hotspot	QPSK	0.669	1.6	PASS
LTE Band 7	Head	QPSK	0.033	1.6	PASS
	Body-worn	QPSK	0.138	1.6	PASS
	Hotspot	QPSK	0.330	1.6	PASS
LTE Band 17	Head	QPSK	0.017	1.6	PASS
	Body-worn	QPSK	0.042	1.6	PASS
	Hotspot	QPSK	0.057	1.6	PASS
Wi-Fi (2.4GHz)	Head	802.11b	0.193	1.6	PASS
	Body-worn	802.11b	0.033	1.6	PASS
	Hotspot	802.11b	0.087	1.6	PASS
Maximum Simultaneous SAR for Head			0.488		PASS
Maximum Simultaneous SAR for Body-worn			0.556		PASS
Maximum Simultaneous SAR for Hotspot			1.178		PASS

Approved & Released by

Simon Ling

Simon Ling

SAR Manager

Tested by

Evan Mi

Evan Mi

SAR Engineer



CONTENTS

1	GENERAL INFORMATION	7
1.1	DETAILS OF CLIENT	7
1.2	TEST LOCATION	7
1.3	TEST FACILITY	8
1.4	GENERAL DESCRIPTION OF EUT	9
1.5	TEST SPECIFICATION	10
1.6	RF EXPOSURE LIMITS	10
2	SAR MEASUREMENTS SYSTEM CONFIGURATION	11
2.1	THE SAR MEASUREMENT SYSTEM	11
2.2	ISOTROPIC E-FIELD PROBE EX3DV4	12
2.3	DATA ACQUISITION ELECTRONICS (DAE)	13
2.4	SAM TWIN PHANTOM	13
2.5	ELI PHANTOM	14
2.6	DEVICE HOLDER FOR TRANSMITTERS	15
2.7	MEASUREMENT PROCEDURE	16
2.7.1	Scanning procedure	16
2.7.2	Data Storage	18
2.7.3	Data Evaluation by SEMCAD	18
3	DESCRIPTION OF TEST POSITION	20
3.1	THE HEAD TEST POSITION	20
3.1.1	SAM Phantom Shape	20
3.1.2	EUT constructions	21
3.1.3	Definition of the "cheek" position	21
3.1.4	Definition of the "tilted" position	22
3.2	THE BODY TEST POSITION	23
3.2.1	Body-worn accessory exposure conditions	23
3.2.2	Wireless Router exposure conditions	24
4	SAR SYSTEM VERIFICATION PROCEDURE	25
4.1	TISSUE SIMULATE LIQUID	25
4.1.1	Recipes for Tissue Simulate Liquid	25
4.1.2	Measurement for Tissue Simulate Liquid	26
4.2	SAR SYSTEM VALIDATION	27



4.2.1	Justification for Extended SAR Dipole Calibrations	28
4.2.2	Summary System Validation Result(s).....	29
4.2.3	Detailed System Validation Results.....	29
5	TEST RESULTS AND MEASUREMENT DATA	30
5.1	3G SAR TEST REDUCTION PROCEDURE	30
5.2	OPERATION CONFIGURATIONS	30
5.2.1	GSM Test Configuration.....	30
5.2.2	WCDMA Test Configuration.....	31
5.2.3	WiFi Test Configuration.....	35
5.2.4	LTE Test Configuration.....	37
5.2.5	DUT Antenna Locations	38
5.2.6	EUT side for SAR Testing.....	38
5.2.7	Stand-alone SAR test evaluation.....	39
5.3	MEASUREMENT OF RF CONDUCTED POWER.....	40
5.3.1	Conducted Power Of GSM	40
5.3.2	Conducted Power Of WCDMA.....	41
5.3.3	Conducted Power Of LTE	43
5.3.4	Conducted Power Of WIFI and BT	52
5.4	MEASUREMENT OF SAR DATA	53
5.4.1	SAR Result Of GSM850.....	53
5.4.2	SAR Result Of GSM1900.....	54
5.4.3	SAR Result Of WCDMA850.....	55
5.4.4	SAR Result Of WCDMA1700	56
5.4.5	SAR Result Of WCDMA1900	57
5.4.6	SAR Result Of LTE 1900(20MHz)	58
5.4.1	SAR Result Of LTE 1700(20MHz)	60
5.4.2	SAR Result Of LTE 2600(20MHz)	61
5.4.3	SAR Result Of LTE 750(10MHz)	63
5.4.4	SAR Result Of WIFI.....	65
5.5	MULTIPLE TRANSMITTER EVALUATION.....	66
5.5.1	Simultaneous SAR SAR test evaluation	66
5.5.2	Estimated SAR.....	66
6	EQUIPMENT LIST	71
7	MEASUREMENT UNCERTAINTY	72
8	CALIBRATION CERTIFICATE	73

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



9	PHOTOGRAPHS.....	73
	APPENDIX A: DETAILED SYSTEM VALIDATION RESULTS	74
	APPENDIX B: DETAILED TEST RESULTS	74
	APPENDIX C: CALIBRATION CERTIFICATE.....	74
	APPENDIX D: PHOTOGRAPHS	74



1 General Information

1.1 Details of Client

Applicant:	Haier Telecom (Qingdao) Co., Ltd.
Address:	No.1 Haier Road, Hi-tech Zone, Qingdao, 266101 P.R. China
Manufacturer:	Haier Telecom (Qingdao) Co., Ltd.
Address:	No.1 Haier Road, Hi-tech Zone, Qingdao, 266101 P.R. China
Factory:	Haier Telecom (Qingdao) Co., Ltd.
Address:	No.1 Haier Road, Hi-tech Zone, Qingdao, 266101 P.R. China

1.2 Test Location

Company: SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch E&E Lab
Address: No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
Post code: 518057
Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
E-mail: ee.shenzhen@sgs.com



1.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.



1.4 General Description of EUT

Product Name:	Mobilephone		
Model No.(EUT):	V4		
Trade Mark:	Haier		
Product Phase:	production unit		
Device Type :	portable device		
Exposure Category:	uncontrolled environment / general population		
FCC ID:	SG7201603V4		
IMEI/SN:	FINJSGKN9999999		
Hardware Version:	T99_MBA3		
Software Version:	S001		
Antenna Type:	Inner Antenna		
Device Operating Configurations :			
Modulation Mode:	GSM:GMSK, 8PSK WCDMA: QPSK LTE:QPSK,16QAM WIFI:IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(T20 and T40) : OFDM (64QAM, 16QAM, QPSK,BPSK) BT:GFSK, π /4DQPSK,8DPSK		
Device Class:	B		
GPRS Multi-slots Class:	12	EGPRS Multi-slots Class:	12
HSDPA UE Category:	14	HSUPA UE Category	6
Frequency Bands:	Band	Tx (MHz)	Rx (MHz)
	GSM850	824-849	869-894
	GSM1900	1850-1910	1930-1990
	WCDMA850	824-849	869-894
	WCDMA1700	1710-1755	2110- 2155
	WCDMA1900	1850-1910	1930-1990
	LTE Band 2	1850-1910	1930-1990
	LTE Band 4	1710-1755	2110- 2155
	LTE Band 7	2500-2570	2620- 2690
	LTE Band 17	704-716	734-746
	WIFI	2412-2462	2412-2462
	BT	2402-2480	2402-2480
Battery Information:	Model:366481PH		
	Normal Voltage :3.8V		
	Rated capacity :2800mAh		
	Battery Type :Rechargeable Li-ion Battery		



1.5 Test Specification

Identity	Document Title
FCC 47CFR §2.1093	Radiofrequency Radiation Exposure Evaluation: Portable Devices
IEEE Std C95.1 – 1991	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz.
IEEE 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
KDB 941225 D01 v03r01	3G SAR Procedures
KDB 941225 D05 v02r05	SAR for LTE Devices
KDB 248227 D01 v02r02	802.11 Wi-Fi SAR
KDB 941225 D06 v02r01	Hot Spot SAR
KDB 648474 D04 v01r03	Handset SAR
KDB447498 D01 v06	General RF Exposure Guidance
KDB447498 D03 v01	Supplement C Cross-Reference
KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
KDB 865664 D02 v01r02	RF Exposure Reporting

1.6 RF exposure limits

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
Spatial Peak SAR* (Brain)	1.60 mW/g	8.00 mW/g
Spatial Average SAR** (Whole Body)	0.08 mW/g	0.40 mW/g
Spatial Peak SAR*** (Hands/Feet/Ankle/Wrist)	4.00 mW/g	20.00 mW/g

Notes:

* The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time

** The Spatial Average value of the SAR averaged over the whole body.

*** The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation.)

2 SAR Measurements System Configuration

2.1 The SAR Measurement System

This SAR Measurement System uses a Computer-controlled 3-D stepper motor system (SPEAG DASY5 professional system). A E-field probe is used to determine the internal electric fields. The SAR can be obtained from the equation $SAR = \sigma (|E|^2) / \rho$ where σ and ρ are the conductivity and mass density of the tissue-Simulate.


The DASY5 system for performing compliance tests consists of the following items:

A standard high precision 6-axis robot (Stabile RX family) with controller, teach pendant and software .An arm extension for accommodation the data acquisition electronics (DAE).

A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.




F-1. SAR Measurement System Configuration

- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 7.
- DASY5 software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand, right-hand and Body Worn usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing to validating the proper functioning of the system.

2.2 Isotropic E-field Probe EX3DV4

	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available.
Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.
Compatibility	DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI

2.3 Data Acquisition Electronics (DAE)

Model	DAE3, DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY4/5 embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
Input Offset Voltage	< 5µV (with auto zero)	
Input Bias Current	< 50 f A	
Dimensions	60 x 60 x 68 mm	

2.4 SAM Twin Phantom

Material	Vinylester, glass fiber reinforced (VE-GF)	
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions (incl. Wooden Support)	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	
Wooden Support	SPEAG standard phantom table	

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.

Twin SAM V5.0 has the same shell geometry and is manufactured from the same material as Twin SAM V4.0, but has reinforced top structure.

2.5 ELI Phantom

Material	Vinylester, glass fiber reinforced (VE-GF)
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)
Shell Thickness	2.0 ± 0.2 mm (bottom plate)
Dimensions	Major axis: 600 mm Minor axis: 400 mm
Filling Volume	approx. 30 liters
Wooden Support	SPEAG standard phantom table



Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.

ELI V5.0 has the same shell geometry and is manufactured from the same material as ELI4, but has reinforced top structure.

2.6 Device Holder for Transmitters



F-2. Device Holder for Transmitters

- The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation centres for both scales are the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.
- The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon=3$ and loss tangent $\delta=0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



2.7 Measurement procedure

2.7.1 Scanning procedure

Step 1: Power reference measurement

The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure.

Step 2: Area scan

The SAR distribution at the exposed side of the head was measured at a distance of 4mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15mm*15mm or 12mm*12mm or 10mm*10mm. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation.

Step 3: Zoom scan

Around this point, a volume of 30mm*30mm*30mm (fine resolution volume scan, zoom scan) was assessed by measuring 5x5x7 points ($\leq 2\text{GHz}$) and 7x7x7 points ($\geq 2\text{GHz}$). On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:

The data at the surface was extrapolated, since the centre of the dipoles is 2.0mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2mm. (This can be variable. Refer to the probe specification). The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The volume was integrated with the trapezoidal algorithm. One thousand points were interpolated to calculate the average. All neighbouring volumes were evaluated until no neighboring volume with a higher average value was found.

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements. Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std. 1528-2003.



			$\leq 3 \text{ GHz}$	$> 3 \text{ GHz}$
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			$5 \pm 1 \text{ mm}$	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$			$\leq 2 \text{ GHz}: \leq 15 \text{ mm}$ $2 - 3 \text{ GHz}: \leq 12 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 12 \text{ mm}$ $4 - 6 \text{ GHz}: \leq 10 \text{ mm}$
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			$\leq 2 \text{ GHz}: \leq 8 \text{ mm}$ $2 - 3 \text{ GHz}: \leq 5 \text{ mm}^*$	$3 - 4 \text{ GHz}: \leq 5 \text{ mm}^*$ $4 - 6 \text{ GHz}: \leq 4 \text{ mm}^*$
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		$\leq 5 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 4 \text{ mm}$ $4 - 5 \text{ GHz}: \leq 3 \text{ mm}$ $5 - 6 \text{ GHz}: \leq 2 \text{ mm}$
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	$\leq 4 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 3 \text{ mm}$ $4 - 5 \text{ GHz}: \leq 2.5 \text{ mm}$ $5 - 6 \text{ GHz}: \leq 2 \text{ mm}$
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		$\geq 30 \text{ mm}$	$3 - 4 \text{ GHz}: \geq 28 \text{ mm}$ $4 - 5 \text{ GHz}: \geq 25 \text{ mm}$ $5 - 6 \text{ GHz}: \geq 22 \text{ mm}$
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the <u>area scan based 1-g SAR estimation</u> procedures of KDB 447498 is $\leq 1.4 \text{ W/kg}$, $\leq 8 \text{ mm}$, $\leq 7 \text{ mm}$ and $\leq 5 \text{ mm}$ zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

Step 4: Power reference measurement (drift)

The Power Drift Measurement job measures the field at the same location as the most recent power reference measurement job within the same procedure, and with the same settings. The indicated drift is mainly the variation of the DUT's output power and should vary max. $\pm 5 \%$

2.7.2 Data Storage

The DASY software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension ".DAE3". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated. The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [m W/g], [m W/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

2.7.3 Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Normi, ai0, ai1, ai2
- Conversion factor	ConvFi	
- Diode compression point	Dcpi	
Device parameters:	- Frequency	f
- Crest factor	cf	
Media parameters:	- Conductivity	ε
- Density	ρ	

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power.

The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot cf / dcpi$$

With V_i = compensated signal of channel i (i = x, y, z)

U_i = input signal of channel i (i = x, y, z)

cf = crest factor of exciting field (DASY parameter)

dcpi = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:



$$E_i = (V_i / Norm_i \cdot ConvF)^{1/2}$$

H-field probes:

$$H_i = (V_i)^{1/2} \cdot (a_{i0} + a_{i1}f + a_{i2}f^2) / f$$

With V_i = compensated signal of channel i (i = x, y, z)

$Norm_i$ = sensor sensitivity of channel i (i = x, y, z)

[mV/(V/m)²] for E-field Probes

$ConvF$ = sensitivity enhancement in solution

a_{ij} = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

E_i = electric field strength of channel i in V/m

H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (E_{tot}^2 \cdot \sigma) / (\epsilon \cdot 1000)$$

with SAR = local specific absorption rate in mW/g

E_{tot} = total field strength in V/m

σ = conductivity in [mho/m] or [Siemens/m]

ϵ = equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = E_{tot}^2 / 3770 \text{ or } P_{pwe} = H_{tot}^2 \cdot 37.7$$

with P_{pwe} = equivalent power density of a plane wave in mW/cm²

E_{tot} = total electric field strength in V/m

H_{tot} = total magnetic field strength in A/m

3 Description of Test Position


3.1 The Head Test Position

3.1.1 SAM Phantom Shape




F-3. Front, back, and side views of SAM (model for the phantom shell). Full-head model is for illustration purposes only-procedures in this recommended practice are intended primarily for the phantom setup.


Note: The centre strip including the nose region has a different thickness tolerance.



F-4. Sagittally bisected phantom with extended perimeter (shown placed on its side as used for SAR measurements)




F-5. Close-up side view of phantom, showing the ear region, N-F and B-M lines, and seven cross-sectional plane locations




F-6. Side view of the phantom showing relevant markings and seven cross-sectional plane locations

3.1.2 EUT constructions



F-7. Handset vertical and horizontal reference lines—"fixed case"




F-8. Handset vertical and horizontal reference lines—"clam-shell case"

3.1.3 Definition of the "cheek" position


- Position the device with the vertical centre line of the body of the device and the horizontal line crossing the centre of the ear piece in a plane parallel to the sagittal plane of the phantom ("initial position"). While maintaining the device in this plane, align the vertical centre line with the reference plane containing the three ear and mouth reference points (M, RE and LE) and align the centre of the ear piece with the line RE-LE.
- Translate the mobile phone box towards the phantom with the ear piece aligned with the line LE-RE until telephone touches the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the box until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost.

3.1.4 Definition of the “tilted” position

- Position the device in the “cheek” position described above;
- While maintaining the device in the reference plane described above and pivoting against the ear, move it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost.



F-9. Definition of the reference lines and points, on the phone and on the phantom and initial position



F-10. “Cheek” and “tilt” positions of the mobile phone on the left side

3.2 The Body Test Position


3.2.1 Body-worn accessory exposure conditions

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations.

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration. Per FCC KDB Publication 648474 D04, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.



F-11. Test positions for body-worn devices



3.2.2 Wireless Router exposure conditions

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. For devices with form factors smaller than $9 \text{ cm} \times 5 \text{ cm}$, a test separation distance of 5 mm is required.

4 SAR System Verification Procedure

4.1 Tissue Simulate Liquid

4.1.1 Recipes for Tissue Simulate Liquid

The bellowing tables give the recipes for tissue simulating liquids to be used in different frequency bands:

Ingredients (% by weight)	Frequency (MHz)							
	450		835		1800-2000		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	40.30	50.75	55.24	70.17	55.00	68.53
Salt (NaCl)	3.95	1.49	1.38	0.94	0.31	0.39	0.2	0.1
Sucrose	56.32	46.78	57.90	48.21	0	0	0	0
HEC	0.98	0.52	0.24	0	0	0	0	0
Bactericide	0.19	0.05	0.18	0.10	0	0	0	0
Tween	0	0	0	0	44.45	29.44	44.80	31.37
Salt: 99+ % Pure Sodium Chloride					Sucrose: 98+ % Pure Sucrose			
Water: De-ionized, 16 MΩ ⁺ resistivity					HEC: Hydroxyethyl Cellulose			
Tween: Polyoxyethylene (20) sorbitan monolaurate								

Table 1 : Recipe of Tissue Simulate Liquid

4.1.2 Measurement for Tissue Simulate Liquid


The dielectric properties for this Tissue Simulate Liquids were measured by using the Agilent Model 85070E Dielectric Probe in conjunction with Agilent E5071C Network Analyzer (300 KHz-8500 MHz). The Conductivity (σ) and Permittivity (ρ) are listed in Table 1. For the SAR measurement given in this report. The temperature variation of the Tissue Simulate Liquids was $22 \pm 2^\circ\text{C}$.

Tissue Type	Measured Frequency (MHz)	Target Tissue ($\pm 5\%$)		Measured Tissue		Liquid Temp. ($^\circ\text{C}$)	Measured Date
		ϵ_r	$\sigma(\text{S/m})$	ϵ_r	$\sigma(\text{S/m})$		
750 Head	750	41.9 (39.81~44.00)	0.89 (0.85~0.93)	41.885	0.885	22.3	2016/4/22
750 Body	750	55.5 (52.75~58.31)	0.96 (0.91~1.01)	56.086	0.942	22.3	2016/4/22
835 Head	835	41.5 (39.43~43.58)	0.9 (0.86~0.95)	40.953	0.926	22.1	2016/4/10
835 Body	835	55.2 (52.44~57.96)	0.97 (0.92~1.02)	55.395	0.981	22.1	2016/4/11
1800 Head	1800	40.08 (38.08~42.08)	1.37 (1.30~1.44)	40.096	1.396	21.8	2016/4/18
1800 Body	1800	53.43 (50.76~56.10)	1.49 (1.42~1.56)	54.359	1.535	21.8	2016/4/19
1900 Head	1900	40 (38.00~42.00)	1.4 (1.33~1.47)	40.578	1.437	21.8	2016/4/18
1900 Body	1900	53.3 (50.64~55.97)	1.52 (1.44~1.60)	51.921	1.551	21.8	2016/4/20
2450 Head	2450	39.20 (37.24~41.15)	1.80 (1.71~1.88)	38.561	1.781	21.9	2016/4/13
2450 Body	2450	52.70 (50.07~55.34)	1.95 (1.85~2.05)	51.68	1.951	21.9	2016/4/13
2600 Head	2600	39.0 (35.1~42.9)	1.96 (1.764~2.156)	38.1	1.937	22.1	2016/4/14
2600 Body	2600	52.50 (47.25~57.75)	2.16 (1.944~2.376)	52.866	2.171	22.1	2016/4/14

Table 2 : Measurement result of Tissue electric parameters

4.2 SAR System Validation

The microwave circuit arrangement for system verification is sketched in F-12. The daily system accuracy verification occurs within the flat section of the SAM phantom. A SAR measurement was performed to see if the measured SAR was within $\pm 10\%$ from the target SAR values. The tests were conducted on the same days as the measurement of the EUT. The obtained results from the system accuracy verification are displayed in the table 5 (A power level of 250mw was input to the dipole antenna). During the tests, the ambient temperature of the laboratory was in the range $22 \pm 1^\circ\text{C}$, the relative humidity was in the range 60% and the liquid depth above the ear reference points was above 15 cm in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.



F-12. the microwave circuit arrangement used for SAR system verification



4.2.1 Justification for Extended SAR Dipole Calibrations

1) Referring to KDB865664 D01 requirements for dipole calibration, instead of the typical annual calibration recommended by measurement standards, longer calibration intervals of up to three years may be considered when it is demonstrated that the SAR target, impedance and return loss of a dipole have remain stable according to the following requirements. Each measured dipole is expected to evaluate with the following criteria at least on annual interval in Appendix C.

- a) There is no physical damage on the dipole;
- b) System check with specific dipole is within 10% of calibrated value;
- c) Return-loss is within 10% of calibrated measurement;
- d) Impedance is within 5Ω from the previous measurement.

2) Network analyzer probe calibration against air, distilled water and a shorting block performed before measuring liquid parameters.



4.2.2 Summary System Validation Result(s)

Validation Kit		Measured SAR 250mW	Measured SAR normalized to 1w)	Target SAR (normalized to 1w) (±10%)	Liquid Temp. (°C)	Measured Date
		1g (W/kg)	1g (W/kg)	1-g(W/kg)		
D750V2	Head	2.08	8.32	8.26 (7.434~9.086)	22.3	2016/4/22
	Body	2.26	9.04	8.65 (7.785~9.515)	22.3	2016/4/22
D835V2	Head	2.3	9.2	9.64 (8.676~10.604)	22.1	2016/4/10
	Body	2.23	8.92	9.28 (8.352~10.208)	22.1	2016/4/11
D1800V2	Head	9.19	36.76	38.8 (34.92~42.68)	21.8	2016/4/18
	Body	9.85	39.4	38.6 (34.74~42.46)	21.8	2016/4/19
D1900V2	Head	9.73	38.92	40.9 (36.81~44.99)	21.8	2016/4/18
	Body	10.4	41.6	40.6 (36.54~44.66)	21.8	2016/4/20
D2450V2	Head	13.3	53.2	52.4 (47.16~57.64)	21.9	2016/4/13
	Body	12.8	51.2	49.4 (44.46~54.34)	21.9	2016/4/13
D2600V2	Head	14	56	56.2 (50.58~61.82)	22.1	2016/4/14
	Body	14.1	56.4	56.7 (51.03~62.37)	22.1	2016/4/14

Table 3 : SAR System Validation Result

4.2.3 Detailed System Validation Results

Please see the Appendix A



5 Test results and Measurement Data

5.1 3G SAR Test Reduction Procedure

According to KDB 941225D01 v03, in the following procedures, the mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode. This is referred to as the 3G SAR test reduction procedure in the following SAR test guidance, where the primary mode is identified in the applicable wireless mode test procedures and the secondary mode is wireless mode being considered for SAR test reduction by that procedure. When the 3G SAR test reduction procedure is not satisfied, it is identified as "otherwise" in the applicable procedures; SAR measurement is required for the secondary mode.

5.2 Operation Configurations

5.2.1 GSM Test Configuration

SAR tests for GSM 850 and GSM 1900, a communication link is set up with a base station by air link. Using CMU200 the power lever is set to "5" and "0" in SAR of GSM 850 and GSM 1900. The tests in the band of GSM 850 and GSM 1900 are performed in the mode of GPRS/EGPRS function. Since the GPRS class is 12 for this EUT, it has at most 4 timeslots in uplink and at most 4 timeslots in downlink, the maximum total timeslot is 5. The EGPRS class is 12 for this EUT, it has at most 4 timeslots in uplink, and at most 4 timeslots in downlink, the maximum total timeslot is 5.

SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.

When SAR tests for EGPRS mode is necessary, GMSK modulation should be used to minimize SAR measurement error due to higher peak-to-average power (PAR) ratios inherent in 8-PSK.

The 3G SAR test reduction procedure is applied to 8-PSK EDGE with GMSK GPRS/EDGE as the primary mode



5.2.2 WCDMA Test Configuration

1) . Output Power Verification

Maximum output power is verified on the high, middle and low channels according to procedures described in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all "1's" for WCDMA/HSDPA or by applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HSDPA, HSPA) are required in the SAR report. All configurations that are not supported by the handset or cannot be measured due to technical or equipment limitations must be clearly identified.

2) . Head SAR

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure

3) . Body SAR

SAR for body configurations is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCHn configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCHn, for the highest reported body-worn accessory exposure SAR configuration in 12.2 kbps RMC. When more than 2 DPDCHn are supported by the handset, it may be necessary to configure additional DPDCHn using FTM (Factory Test Mode) or other chipset based test approaches with parameters similar to those used in 384 kbps and 768 kbps RMC.

4) . HSDPA / HSUPA / DC-HSDPA

According to KDB 941225 D01v03, RMC 12.2kbps setting is used to evaluate SAR. If the maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA

a) HSDPA

HSDPA is configured according to the applicable UE category of a test device. The number of HS-DSCH/HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms and a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors (β_c , β_d), and HS-DPCCH power offset parameters (Δ_{ACK} , Δ_{NACK} , Δ_{CQI}) are set according to values indicated in the following table. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.



Sub-test	β_c	Bd	$\beta_d(\text{SF})$	β_c/β_d	β_{hs}	CM(dB)	MPR (dB)
1	2/15	15/15	64	2/15	4/15	0.0	0
2	12/15(3)	15/15(3)	64	12/15(3)	24/15	1.0	0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5
Note1: ΔACK, ΔNACK and $\Delta\text{CQI}=8$ $A_{hs} = \beta_{hs}/\beta_c=30/15$ $\beta_{hs}=30/15*\beta_c$ Note2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1.A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, ΔACK and $\Delta\text{NACK}=8$ ($A_{hs}=30/15$) with $\beta_{hs}=30/15*\beta_c$, and $\Delta\text{CQI}=7$ ($A_{hs}=24/15$) with $\beta_{hs}=24/15*\beta_c$. Note3: CM=1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c=24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.							

The measurements were performed with a Fixed Reference Channel (FRC) and H-Set 1 QPSK.

Parameter	Value
Nominal average inf. bit rate	534 kbit/s
Inter-TTI Distance	3 TTI"s
Number of HARQ Processes	2 Processes
Information Bit Payload	3202 Bits
MAC-d PDU size	336 Bits
Number Code Blocks	1 Block
Binary Channel Bits Per TTI	4800 Bits
Total Available SMLs in UE	19200 SMLs
Number of SMLs per HARQ Process	9600 SMLs
Coding Rate	0.67
Number of Physical Channel Codes	5

Table 4 : settings of required H-Set 1 QPSK acc. to 3GPP 34.121



HS-DSCH Category	Maximum HS-DSCH Codes Received	Minimum Inter-TTI Interval	MaximumH S-DSCH Transport BlockBits/HS-DSCH TTI	Total Soft Channel Bits
1	5	3	7298	19200
2	5	3	7298	28800
3	5	2	7298	28800
4	5	2	7298	38400
5	5	1	7298	57600
6	5	1	7298	67200
7	10	1	14411	115200
8	10	1	14411	134400
9	15	1	25251	172800
10	15	1	27952	172800
11	5	2	3630	14400
12	5	1	3630	28800
13	15	1	34800	259200
14	15	1	42196	259200
15	15	1	23370	345600
16	15	1	27952	345600

Table 5 : HSDPA UE category

b) HSUPA

Due to inner loop power control requirements in HSUPA, a commercial communication test set should be used for the output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSUPA should be configured according to the values indicated below as well as other applicable procedures described in the „WCDMA Handset“ and „Release 5 HSUPA Data Device“ sections of 3G device.



Sub-test ^⓪	β_c ^⓪	β_d ^⓪	β_d (SF) ^⓪	β_o/β_d ^⓪	β_{hs} ⁽¹⁾ ^⓪	β_{sc} ^⓪	β_{sd} ^⓪	β_c ^(SF) ^⓪	β_{sd} (code) ^⓪	CM ⁽²⁾ (dB) ^⓪	MP R ^⓪ (dB) ^⓪	AG ⁽⁴⁾ Inde x ^⓪	E- TFC I ^⓪
1 ^⓪	11/15 ⁽³⁾ ^⓪	15/15 ⁽³⁾ ^⓪	64 ^⓪	11/15 ⁽³⁾ ^⓪	22/15 ^⓪	209/225 ^⓪	1039/225 ^⓪	4 ^⓪	1 ^⓪	1.0 ^⓪	0.0 ^⓪	20 ^⓪	75 ^⓪
2 ^⓪	6/15 ^⓪	15/15 ^⓪	64 ^⓪	6/15 ^⓪	12/15 ^⓪	12/15 ^⓪	94/75 ^⓪	4 ^⓪	1 ^⓪	3.0 ^⓪	2.0 ^⓪	12 ^⓪	67 ^⓪
3 ^⓪	15/15 ^⓪	9/15 ^⓪	64 ^⓪	15/9 ^⓪	30/15 ^⓪	30/15 ^⓪	$\beta_{sd1}:47/15$ $\beta_{sd2}:47/15$ ^⓪	4 ^⓪	2 ^⓪	2.0 ^⓪	1.0 ^⓪	15 ^⓪	92 ^⓪
4 ^⓪	2/15 ^⓪	15/15 ^⓪	64 ^⓪	2/15 ^⓪	4/15 ^⓪	2/15 ^⓪	56/75 ^⓪	4 ^⓪	1 ^⓪	3.0 ^⓪	2.0 ^⓪	17 ^⓪	71 ^⓪
5 ^⓪	15/15 ⁽⁴⁾ ^⓪	15/15 ⁽⁴⁾ ^⓪	64 ^⓪	15/15 ⁽⁴⁾ ^⓪	30/15 ^⓪	24/15 ^⓪	134/15 ^⓪	4 ^⓪	1 ^⓪	1.0 ^⓪	0.0 ^⓪	21 ^⓪	81 ^⓪
Note 1: ΔACK , $\Delta NACK$ and $\Delta CQI=8$ $A_{hs} = \beta_{hs}/\beta_o = 30/15$ $\beta_{hs} = 30/15 * \beta_{sc}$ Note 2: CM = 1 for $\beta_o/\beta_d = 12/15$, $\beta_{hs}/\beta_o = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference ^⓪ Note 3 : For subtest 1 the β_o/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$ ^⓪ Note 4 : For subtest 5 the β_o/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$ ^⓪ Note 5 : Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g ^⓪ Note 6: β_{sd} can not be set directly; it is set by Absolute Grant Value. ^⓪													

Table 6 : Subtests for UMTS Release 6 HSUPA

UE E-DCH Category	Maximum E-DCH Codes Transmitted	Number of HARQ Processes	E-DCH TTI(ms)	Minimum Spreading Factor	Maximum E-DCH Transport Block Bits	Max Rate (Mbps)
1	1	4	10	4	7110	0.7296
2	2	8	2	4	2798	1.4592
	2	4	10	4	14484	
3	2	4	10	4	14484	1.4592
4	2	8	2	2	5772	2.9185
	2	4	10	2	20000	2.00
5	2	4	10	2	20000	2.00
6 (No DPDCH)	4	8	10	2SF2&2SF	11484	5.76
	4	4	2	4	20000	2.00
7 (No DPDCH)	4	8	2	2SF2&2SF	22996	?
	4	4	10	4	20000	?
NOTE: When 4 codes are transmitted in parallel, two codes shall be transmitted with SF2 and two with SF4. UE categories 1 to 6 support QPSK only. UE category 7 supports QPSK and 16QAM. (TS25.306-7.3.0).						

Table 7 : HSUPA UE category

5.2.3 WiFi Test Configuration

A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement.

5.2.3.1 Initial Test Position SAR Test Reduction Procedure

DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures. The initial test position procedure is described in the following:

- 1) . When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other (remaining) test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band. SAR is also not required for that exposure configuration in the subsequent test configuration(s).
- 2) . When the reported SAR of the initial test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position using subsequent highest extrapolated or estimated 1-g SAR conditions determined by area scans or next closest/smallest test separation distance and maximum RF coupling test positions based on manufacturer justification, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg or all required test positions (left, right, touch, tilt or subsequent surfaces and edges) are tested.
- 3) . For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested. a) Additional power measurements may be required for this step, which should be limited to those necessary for identifying the subsequent highest output power channels.

5.2.3.2 Initial Test Configuration Procedures

An initial test configuration is determined for OFDM transmission modes according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. SAR is measured using the highest measured maximum output power channel. For configurations with the same specified or measured maximum output power, additional transmission mode and test channel selection procedures are required. SAR test reduction for subsequent highest output test channels is determined according to *reported* SAR of the initial test configuration.

For next to the ear, hotspot mode and UMC mini-tablet exposure configurations where multiple test positions are required, the initial test position procedure is applied to minimize the number of test positions required for SAR measurement using the initial test configuration transmission mode. For fixed exposure conditions that do not have multiple SAR test positions, SAR is measured in the transmission mode determined by the initial test configuration.

When the *reported* SAR of the initial test configuration is > 0.8 W/kg, SAR measurement is required for subsequent next highest measured output power channel(s) in the initial test configuration until *reported* SAR is ≤ 1.2 W/kg or all required channels are tested.

5.2.3.3 Subsequent Test Configuration Procedures

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. The initial test position procedure is applied to next to the ear, UMPC mini-tablet and hotspot mode configurations. When the same maximum output power is specified for multiple transmission modes, additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. The subsequent test configuration and SAR measurement procedures are described in the following.

- 1) . When SAR test exclusion provisions of KDB Publication 447498 are applicable and SAR measurement



is not required for the initial test configuration, SAR is also not required for the next highest maximum output power transmission mode subsequent test configuration(s) in that frequency band or aggregated band and exposure configuration.

- 2) . When the highest *reported* SAR for the initial test configuration (when applicable, include subsequent highest output channels), according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.
- 3) . The number of channels in the initial test configuration and subsequent test configuration can be different due to differences in channel bandwidth. When SAR measurement is required for a subsequent test configuration and the channel bandwidth is smaller than that in the initial test configuration, all channels in the subsequent test configuration that overlap with the larger bandwidth channel tested in the initial test configuration should be used to determine the highest maximum output power channel. This step requires additional power measurement to identify the highest maximum output power channel in the subsequent test configuration to determine SAR test reduction.
 - a) SAR should first be measured for the channel with highest measured output power in the subsequent test configuration.
 - b) SAR for subsequent highest measured maximum output power channels in the subsequent test configuration is required only when the *reported* SAR of the preceding higher maximum output power channel(s) in the subsequent test configuration is > 1.2 W/kg or until all required channels are tested. i) For channels with the same measured maximum output power, SAR should be measured using the channel closest to the center frequency of the larger channel bandwidth channel in the initial test configuration.
- 4) . SAR measurements for the remaining highest specified maximum output power OFDM transmission mode configurations that have not been tested in the initial test configuration (highest maximum output) or subsequent test configuration(s) (subsequent next highest maximum output power) is determined by recursively applying the subsequent test configuration procedures in this section to the remaining configurations according to the following:
 - a) replace "subsequent test configuration" with "next subsequent test configuration" (i.e., subsequent next highest specified maximum output power configuration)
 - b) replace "initial test configuration" with "all tested higher output power configurations"

5.2.3.4 2.4 GHz SAR Procedures

Separate SAR procedures are applied to DSSS and OFDM configurations in the 2.4 GHz band to simplify DSSS test requirements. For 802.11b DSSS SAR measurements, DSSS SAR procedure applies to fixed exposure test position and initial test position procedure applies to multiple exposure test positions. When SAR measurement is required for an OFDM configuration, the initial test configuration, subsequent test configuration and initial test position procedures are applied. The SAR test exclusion requirements for 802.11g/n OFDM configurations are described in following.

- **802.11b DSSS SAR Test Requirements**

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) . When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) . When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

- **2.4 GHz 802.11g/n OFDM SAR Test Exclusion Requirements**

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied (section 5.3, including sub-sections). SAR is not required for the following 2.4 GHz OFDM conditions.

- 1) . When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
- 2) . When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.



5.2.4 LTE Test Configuration

LTE modes were tested according to FCC KDB 941225 D05 publication. Please see notes after the tabulated SAR data for required test configurations. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 was used for LTE output power measurements and SAR testing. Max power control was used so the UE transmits with maximum output power during SAR testing. SAR must be measured with the maximum TTI (transmit time interval) supported by the device in each LTE configuration.

A) Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

B) MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

C) A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

D) Largest channel bandwidth standalone SAR test requirements

1) QPSK with 1 RB allocation

Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

2) QPSK with 50% RB allocation

The procedures required for 1 RB allocation in 1) are applied to measure the SAR for QPSK with 50% RB allocation.

3) QPSK with 100% RB allocation

For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in 1) and 2) are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.


4) Higher order modulations

For each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in above sections to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> \frac{1}{2}$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

E) Other channel bandwidth standalone SAR test requirements

For the other channel bandwidths used by the device in a frequency band, apply all the procedures required for the largest channel bandwidth in section A) to determine the channels and RB configurations that need SAR testing and only measure SAR when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is $> \frac{1}{2}$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

5.2.5 DUT Antenna Locations



5.2.6 EUT side for SAR Testing

According to the distance between LTE/WCDMA/GSM&WIFI antennas and the sides of the EUT we can draw the conclusion that:

EUT Sides for SAR Testing						
Mode	Front	Back	Left	Right	Top	Bottom
GSM	Yes	Yes	Yes	No	No	Yes
WCDMA	Yes	Yes	Yes	No	No	Yes
LTE	Yes	Yes	Yes	No	No	Yes
Wi-Fi (2.4GHz)	Yes	Yes	Yes	No	Yes	No

Table 8: EUT Sides for SAR Testing

Note: When the antenna-to-edge distance is greater than 2.5cm, such position does not need to be tested.



5.2.7 Stand-alone SAR test evaluation

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

Freq. Band	Frequency (GHz)	Position	Average Power		Test Separation (mm)	Calculate Value	Exclusion Threshold	Exclusion (Y/N)
			dBm	mW				
Wi-Fi	2450	Head	17	50.12	0	15.7	3.0	N
		Body-worn	17	50.12	15	5.2	3.0	N
		hotspot	17	50.12	10	7.8	3.0	N
Bluetooth	2450	Head	4	2.51	0	0.8	3.0	Y
		Body-worn	4	2.51	15	0.3	3.0	Y
		hotspot	4	2.51	10	0.4	3.0	Y

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.



5.3 Measurement of RF conducted Power

5.3.1 Conducted Power Of GSM

GSM 850								
Burst Output Power(dBm)					Division Factors	Frame-Average Output Power(dBm)		
Channel		128	190	251		128	190	251
GSM(GMSK)	GSM	33.06	32.97	33.02	-9.19	23.87	23.78	23.83
GPRS/EGPRS (GMSK)	1 TX Slot	33.06	32.98	33.03	-9.19	23.87	23.79	23.84
	2 TX Slots	32.37	32.3	32.37	-6.18	26.19	26.12	26.19
	3 TX Slots	30.76	30.55	30.57	-4.42	26.34	26.13	26.15
	4 TX Slots	29.56	29.34	29.36	-3.17	26.39	26.17	26.19
EGPRS(8PSK)	1 TX Slot	26.69	26.61	26.58	-9.19	17.5	17.42	17.39
	2 TX Slots	25.73	25.69	25.57	-6.18	19.55	19.51	19.39
	3 TX Slots	23.73	23.66	23.59	-4.42	19.31	19.24	19.17
	4 TX Slots	22.81	22.63	22.67	-3.17	19.64	19.46	19.5
GSM 1900								
Burst Output Power(dBm)					Division Factors	Frame-Average Output Power(dBm)		
Channel		512	661	810		512	661	810
GSM(GMSK)	GSM	30.59	30.53	30.52	-9.19	21.4	21.34	21.33
GPRS/EGPRS (GMSK)	1 TX Slot	30.55	30.49	30.47	-9.19	21.36	21.3	21.28
	2 TX Slots	29.66	29.71	29.79	-6.18	23.48	23.53	23.61
	3 TX Slots	27.42	27.61	27.91	-4.42	23	23.19	23.49
	4 TX Slots	26.14	26.42	26.77	-3.17	22.97	23.25	23.6
EGPRS(8PSK)	1 TX Slot	26.18	26.12	26.05	-9.19	16.99	16.93	16.86
	2 TX Slots	25.01	24.99	24.92	-6.18	18.83	18.81	18.74
	3 TX Slots	22.91	22.95	22.91	-4.42	18.49	18.53	18.49
	4 TX Slots	21.81	21.79	21.77	-3.17	18.64	18.62	18.6

Table 9: Conducted Power Of GSM

Note:

- 1) . CMU200 measures GSM peak and average output power for active timeslots. For SAR the time based average power is relevant. The difference in between depends on the duty cycle of the TDMA signal:

No. of timeslots	1	2	3	4
Duty Cycle	1:8.3	1:4.15	1:2.77	1:2.075
Time based avg. power compared to slotted avg. power	-9.19	-6.18	-4.42	-3.17

- 2) . The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum burst-averaged power based on time slots. The calculated method is shown as below:

Frame-averaged power = $10 \times \log (\text{Burst-averaged power mW} \times \text{Slot used} / 8)$

- 3) . When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel must be used



5.3.2 Conducted Power Of WCDMA

WCDMA850				
Average Conducted Power(dBm)				
Channel		4132	4182	4233
WCDMA	12.2kbps RMC	23.23	23.36	23.41
	64kbps RMC	23.27	23.29	23.4
	144kbps RMC	23.24	23.23	23.38
	384kbps RMC	23.29	23.29	23.39
HSDPA	Subtest 1	22.16	22.29	22.38
	Subtest 2	22.15	22.26	22.36
	Subtest 3	22.14	22.27	22.37
	Subtest 4	22.15	22.25	22.32
HSUPA	Subtest 1	21.21	21.29	21.49
	Subtest 2	21.15	21.28	21.44
	Subtest 3	21.19	21.27	21.41
	Subtest 4	21.18	21.25	21.45
	Subtest 5	21.17	21.23	21.46
WCDMA1700				
Average Conducted Power(dBm)				
Channel		1312	1412	1513
WCDMA	12.2kbps RMC	23.11	23.12	23.03
	64kbps RMC	23.08	23.07	22.95
	144kbps RMC	23.11	23.08	22.96
	384kbps RMC	23.03	23.11	22.98
HSDPA	Subtest 1	22.53	22.11	22.02
	Subtest 2	22.49	22.05	21.98
	Subtest 3	22.46	22.04	21.97
	Subtest 4	22.48	22.08	22.01
HSUPA	Subtest 1	22.05	21.66	21.58
	Subtest 2	22.04	21.61	21.53
	Subtest 3	22.03	21.63	21.56
	Subtest 4	22.04	21.62	21.54
	Subtest 5	22.01	21.65	21.51



WCDMA1900				
Average Conducted Power(dBm)				
Channel		9262	9400	9538
WCDMA	12.2kbps RMC	23.24	23.26	23.34
	64kbps RMC	23.11	23.05	23..3
	144kbps RMC	23.05	23.04	23.28
	384kbps RMC	23.04	23.04	23.29
HSDPA	Subtest 1	22.15	21.99	22.32
	Subtest 2	22.07	21.91	22.31
	Subtest 3	22.08	21.95	22.3
	Subtest 4	22.11	21.95	22.3
HSUPA	Subtest 1	21.19	21.03	21.32
	Subtest 2	21.16	21.03	21.24
	Subtest 3	21.15	21.02	21.25
	Subtest 4	21.18	21.01	21.28
	Subtest 5	21.17	20.99	21.29

Table 10: Conducted Power Of WCDMA

- 1) when the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel must be used.



5.3.3 Conducted Power Of LTE

LTE FDD Band 2				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				18607	18900	19193
1.4MHz	QPSK	1	0	22.6	22.74	22.76
		1	2	22.55	22.73	22.73
		1	5	22.54	22.71	22.69
		3	0	21.55	21.62	21.68
		3	2	21.52	21.57	21.68
		3	3	21.51	21.54	21.63
		6	0	21.59	21.7	21.71
	16QAM	1	0	22.68	22.76	22.8
		1	2	22.65	22.74	22.79
		1	5	22.64	22.69	22.79
		3	0	21.72	21.76	21.82
		3	2	21.72	21.72	21.78
		3	3	21.71	21.69	21.73
		6	0	21.76	21.84	21.83
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				18615	18900	19185
3MHz	QPSK	1	0	22.72	22.79	22.9
		1	7	22.68	22.77	22.86
		1	14	22.64	22.77	22.82
		8	0	21.59	21.75	21.77
		8	4	21.55	21.72	21.73
		8	7	21.52	21.71	21.69
		15	0	21.65	21.78	21.85
	16QAM	1	0	22.8	22.86	22.84
		1	7	22.76	22.84	22.82
		1	14	22.75	22.82	22.82
		8	0	21.81	21.9	21.86
		8	4	21.77	21.87	21.82
		8	7	21.73	21.85	21.81
		15	0	21.88	21.97	21.93



Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				18625	18900	19175
5MHz	QPSK	1	0	22.77	22.92	22.99
		1	13	22.76	22.89	22.97
		1	24	22.75	22.87	22.93
		12	0	21.69	21.81	21.8
		12	6	21.66	21.8	21.77
		12	13	21.63	21.76	21.75
		25	0	21.7	21.91	21.88
	16QAM	1	0	22.87	22.9	22.94
		1	13	22.82	22.87	22.89
		1	24	22.81	22.85	22.87
		12	0	21.9	21.9	21.98
		12	6	21.9	21.87	21.98
		12	13	21.9	21.82	21.94
		25	0	21.98	21.97	21.99
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				18650	18900	19150
10MHz	QPSK	1	0	22.86	22.96	22.87
		1	25	22.82	22.94	22.68
		1	49	22.81	22.9	22.73
		25	0	21.79	21.84	21.94
		25	13	21.76	21.82	21.92
		25	25	21.75	21.81	21.9
		50	0	21.84	21.89	21.94
	16QAM	1	0	22.92	22.99	23.01
		1	25	22.89	22.97	22.98
		1	49	22.86	22.95	22.94
		25	0	21.93	22.03	22.01
		25	13	21.92	21.99	21.98
		25	25	21.9	21.97	21.93
		50	0	22.02	22.09	22.04

Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				18675	18900	19125
15MHz	QPSK	1	0	22.92	23.05	23.07
		1	38	22.88	23.02	23.02
		1	74	22.87	23.01	23.01
		36	0	21.84	21.92	21.98
		36	18	21.83	21.87	21.96
		36	39	21.81	21.85	21.91
		75	0	21.91	21.96	22
	16QAM	1	0	23.02	23.06	23.05
		1	38	22.99	23.04	23.09
		1	74	22.99	23.04	23.06
		36	0	22.03	22.08	22.14
		36	18	22.02	22.06	22.1
		36	39	21.97	22.06	22.05
		75	0	22.06	22.09	22.15
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				18700	18900	19100
20MHz	QPSK	1	0	23.01	23.13	23.17
		1	50	22.98	23.12	23.16
		1	99	22.96	23.1	23.14
		50	0	21.94	22.01	22.07
		50	25	21.93	21.98	22.03
		50	50	21.89	21.98	22
		100	0	21.99	22.09	22.13
	16QAM	1	0	23.07	23.13	23.15
		1	50	23.03	23.13	23.16
		1	99	23.02	23.1	23.13
		50	0	22.12	22.14	22.21
		50	25	22.08	22.1	22.19
		50	50	22.07	22.1	22.18
		100	0	22.17	22.22	22.29

Table 11: Conducted Power Of LTE



LTE FDD Band 4				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				19957	20175	20393
1.4MHz	QPSK	1	0	22.77	22.69	22.47
		1	2	22.74	22.69	22.44
		1	5	22.72	22.65	22.39
		3	0	22.84	22.77	22.51
		3	2	22.84	22.76	22.5
		3	3	22.82	22.72	22.49
		6	0	22.86	22.86	22.61
	16QAM	1	0	21.72	21.74	21.73
		1	2	21.67	21.72	21.71
		1	5	21.64	21.72	21.67
		3	0	21.82	21.91	21.64
		3	2	21.81	21.91	21.61
		3	3	21.78	21.9	21.56
		6	0	21.88	21.99	21.68
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				19965	20175	20385
3MHz	QPSK	1	0	22.74	22.66	22.49
		1	7	22.72	22.64	22.47
		1	14	22.71	22.64	22.46
		8	0	21.79	21.71	21.49
		8	4	21.77	21.67	21.47
		8	7	21.73	21.64	21.47
		15	0	21.85	21.77	21.5
	16QAM	1	0	22.19	21.81	21.44
		1	7	22.15	21.77	21.39
		1	14	22.11	21.74	21.36
		8	0	20.76	20.77	20.38
		8	4	20.72	20.73	20.34
		8	7	20.69	20.69	20.31
		15	0	20.83	20.82	20.46

Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				19975	20175	20375
5MHz	QPSK	1	0	22.86	22.79	22.65
		1	13	22.84	22.75	22.63
		1	24	22.81	22.71	22.6
		12	0	21.86	21.79	21.61
		12	6	21.84	21.77	21.58
		12	13	21.82	21.73	21.55
		25	0	21.94	21.82	21.61
	16QAM	1	0	21.91	21.74	21.77
		1	13	21.9	21.73	21.76
		1	24	21.88	21.72	21.75
		12	0	20.83	20.82	20.86
		12	6	20.81	20.78	20.82
		12	13	20.81	20.75	20.79
		25	0	20.91	20.83	20.89
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				20000	20175	20350
10MHz	QPSK	1	0	22.88	22.81	22.68
		1	25	22.85	22.8	22.64
		1	49	22.83	22.77	22.59
		25	0	21.81	21.73	21.54
		25	13	21.78	21.71	21.53
		25	25	21.75	21.7	21.53
		50	0	21.83	21.8	21.6
	16QAM	1	0	21.95	21.78	22.02
		1	25	21.91	21.74	21.99
		1	49	21.88	21.71	21.97
		25	0	20.97	20.83	21.06
		25	13	20.94	20.83	21.04
		25	25	20.91	20.82	21.04
		50	0	21	20.87	21.09

Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				20025	20175	20325
15MHz	QPSK	1	0	22.88	22.83	22.82
		1	38	22.85	22.81	22.82
		1	74	22.81	22.78	22.79
		36	0	21.91	21.83	21.72
		36	18	21.91	21.8	21.7
		36	39	21.88	21.75	21.66
		75	0	22.01	21.89	21.74
	16QAM	1	0	21.97	22.09	22.16
		1	38	21.92	22.05	22.12
		1	74	21.88	22.04	22.08
		36	0	21	21.1	21.21
		36	18	20.96	21.06	21.21
		36	39	20.93	21.05	21.17
		75	0	21.05	21.11	21.29
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				20050	20175	20300
20MHz	QPSK	1	0	22.96	22.9	22.82
		1	50	22.93	22.86	22.79
		1	99	22.91	22.86	22.75
		50	0	21.85	21.81	21.7
		50	25	21.81	21.77	21.66
		50	50	21.8	21.74	21.63
		100	0	21.91	21.84	21.76
	16QAM	1	0	22.07	22.07	22.22
		1	50	22.04	22.06	22.21
		1	99	22	22.03	22.19
		50	0	21.12	21.1	21.23
		50	25	21.08	21.06	21.19
		50	50	21.07	21.04	21.15
		100	0	21.14	21.19	21.25



LTE FDD Band 7				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				20775	21100	21425
5MHz	QPSK	1	0	22.43	22.74	22.51
		1	13	22.38	22.72	22.48
		1	24	22.37	22.69	22.48
		12	0	21.53	21.64	21.48
		12	6	21.48	21.62	21.47
		12	13	21.46	21.6	21.47
		25	0	21.61	21.7	21.49
	16QAM	1	0	21.62	22.09	21.97
		1	13	21.61	22.09	21.95
		1	24	21.57	22.06	21.95
		12	0	20.65	21.11	20.97
		12	6	20.64	21.11	20.92
		12	13	20.6	21.1	20.91
		25	0	20.7	21.14	21.01
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				20800	21100	21400
10MHz	QPSK	1	0	22.47	22.8	22.57
		1	25	22.44	22.8	22.52
		1	49	22.43	22.76	22.47
		25	0	21.61	21.77	21.55
		25	13	21.6	21.76	21.5
		25	25	21.57	21.74	21.48
		50	0	21.69	21.84	21.56
	16QAM	1	0	21.75	22.2	22.04
		1	25	21.72	22.17	21.99
		1	49	21.72	22.15	21.98
		25	0	20.78	21.21	21.05
		25	13	20.78	21.18	21
		25	25	20.74	21.16	20.99
		50	0	20.81	21.28	21.06



Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				20825	21100	21375
15MHz	QPSK	1	0	22.54	22.85	22.65
		1	38	22.5	22.84	22.64
		1	74	22.46	22.81	22.62
		36	0	21.69	21.83	21.62
		36	18	21.66	21.8	21.57
		36	39	21.65	21.79	21.54
		75	0	21.73	21.85	21.71
	16QAM	1	0	21.79	22.3	22.1
		1	38	21.76	22.29	22.06
		1	74	21.75	22.25	22.05
		36	0	20.82	21.35	21.11
		36	18	20.8	21.31	21.1
		36	39	20.8	21.29	21.07
		75	0	20.87	21.37	21.18
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				20850	21100	21350
20MHz	QPSK	1	0	22.62	22.95	22.75
		1	50	22.59	22.92	22.73
		1	99	22.54	22.89	22.71
		50	0	21.75	21.91	21.71
		50	25	21.72	21.89	21.69
		50	50	21.69	21.88	21.66
		100	0	21.65	21.87	21.67
	16QAM	1	0	21.89	22.36	22.19
		1	50	21.83	22.34	21.15
		1	99	21.79	22.31	21.11
		50	0	20.61	21.02	20.85
		50	25	20.58	20.99	20.81
		50	50	20.55	20.95	20.79
		100	0	20.67	20.94	20.77



LTE FDD Band 17				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				23755	23790	23825
5MHz	QPSK	1	0	23.14	23.09	23.11
		1	13	23.1	23.08	23.06
		1	24	23.06	23.07	23.04
		12	0	22.11	22.11	22.09
		12	6	22.08	22.08	22.09
		12	13	22.03	22.06	22.07
		25	0	22.19	22.16	22.14
	16QAM	1	0	22.25	22.27	22.29
		1	13	22.24	22.27	22.29
		1	24	22.22	22.26	22.25
		12	0	21.29	21.3	21.33
		12	6	21.25	21.28	21.32
		12	13	21.23	21.26	21.29
		25	0	21.33	21.38	21.41
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				23780	23790	23800
10MHz	QPSK	1	0	23.21	23.17	23.18
		1	25	23.18	23.13	23.16
		1	49	23.15	23.1	23.14
		25	0	22.18	22.17	22.16
		25	13	22.17	22.14	22.17
		25	25	22.12	22.11	22.14
		50	0	22.18	22.21	22.27
	16QAM	1	0	22.35	22.33	22.34
		1	25	22.35	22.29	22.3
		1	49	22.33	22.27	22.3
		25	0	21.36	21.36	21.35
		25	13	21.35	21.34	21.33
		25	25	21.35	21.32	21.32
		50	0	21.38	21.38	21.37



5.3.4 Conducted Power Of WIFI and BT

Wi-Fi 2450MHz	Average Power (dBm) for Data Rates (Mbps)								
	Channel	1	2	5.5	11	/	/	/	/
802.11b	1	15.82	15.88	15.8	15.31	/	/	/	/
	6	16.35	16.07	15.75	15.41	/	/	/	/
	11	16.53	16.09	15.98	15.84	/	/	/	/
802.11g	Channel	6	9	12	18	24	36	48	54
	1	11.6	11.38	11.22	10.88	10.76	10.23	9.75	9.56
	6	13.66	13.46	13.44	12.86	12.63	11.93	11.11	10.94
	11	11.48	13.45	11.31	10.75	10.21	9.69	9.64	9.48
802.11n HT20	Channel	6.5	13	19.5	26	39	52	58.5	65
	1	11.78	11.35	11.04	10.29	9.79	9.76	9.61	9.43
	6	13.64	13.04	12.48	12.17	11.68	10.89	10.49	10.33
	11	11.45	11.06	10.48	10.43	9.68	9.68	9.53	9.34
802.11n HT40	Channel	13.5	27	40.5	54	81	108	121.5	135
	3	9.56	8.66	8.11	7.47	7.04	6.74	6.48	6.39
	6	12.91	12.25	11.73	11.09	10.45	8.71	8.45	8.1
	9	12.85	12.23	11.33	10.91	10.49	8.46	8.22	8.11

Table 12: Conducted Power Of WIFI

BT		Average Conducted Power(dBm)		
Band	Channel	GFSK	$\pi/4$ DQPSK	8DPSK
BT	0	2.88	0.87	0.94
	39	3.3	1.2	1.26
	78	3.38	0.827	1.21
BLE	0	-4.94	/	/
	19	-4.59	/	/
	39	-4.79	/	/

Table 13: Conducted Power Of BT



5.4 Measurement of SAR Data

5.4.1 SAR Result Of GSM850

Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	Power drift(dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp.	SAR limit (W/kg)
Head Test data											
Left touch cheek	GSM	190/836.6	1:8.3	0.251	-0.13	32.97	34	1.268	0.318	22.1	1.6
Left tilted 15 degree	GSM	190/836.6	1:8.3	0.156	0.07	32.97	34	1.268	0.198	22.1	1.6
Right touch cheek	GSM	190/836.6	1:8.3	0.216	-0.02	32.97	34	1.268	0.274	22.1	1.6
Right tilted 15 degree	GSM	190/836.6	1:8.3	0.148	-0.09	32.97	34	1.268	0.188	22.1	1.6
Body worn Test data(Separate 15mm)											
Front side	GSM	190/836.6	1:8.3	0.334	-0.11	32.97	34	1.268	0.423	22.1	1.6
Back side	GSM	190/836.6	1:8.3	0.349	0.02	32.97	34	1.268	0.442	22.1	1.6
Hotspot Test data(Separate 10mm)											
Front side	GPRS 4TS	190/836.6	1:2.075	0.498	0.01	29.34	30.5	1.306	0.650	22.1	1.6
Back side	GPRS 4TS	190/836.6	1:2.075	0.573	0.08	29.34	30.5	1.306	0.748	22.1	1.6
Left side	GPRS 4TS	128/824.2	1:2.075	0.734	-0.03	29.56	30.5	1.242	0.911	22.1	1.6
Left side	GPRS 4TS	190/836.6	1:2.075	0.625	-0.05	29.34	30.5	1.306	0.816	22.1	1.6
Left side	GPRS 4TS	251/848.8	1:2.075	0.492	-0.01	29.36	30.5	1.300	0.640	22.1	1.6
Bottom side	GPRS 4TS	190/836.6	1:2.075	0.391	-0.04	29.34	30.5	1.306	0.511	22.1	1.6

Table 14: SAR of GSM850 for Head and Body.

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B
- 2) Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).



5.4.2 SAR Result Of GSM1900

Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	Power drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp.	SAR limit (W/kg)
Head Test data											
Left touch cheek	GSM	661/1880	1:8.3	0.189	0.18	30.53	31	1.114	0.211	21.8	1.6
Left tilted 15 degree	GSM	661/1880	1:8.3	0.0421	0.18	30.53	31	1.114	0.047	21.8	1.6
Right touch cheek	GSM	661/1880	1:8.3	0.0524	-0.16	30.53	31	1.114	0.058	21.8	1.6
Right tilted 15 degree	GSM	661/1880	1:8.3	0.119	0.12	30.53	31	1.114	0.133	21.8	1.6
Body worn Test data(Separate 15mm)											
Front side	GSM	661/1880	1:8.3	0.154	0.19	30.53	31	1.114	0.172	21.8	1.6
Back side	GSM	661/1880	1:8.3	0.242	-0.04	30.53	31	1.114	0.270	21.8	1.6
Hotspot Test data(Separate 10mm)											
Front side	GPRS 2TS	661/1880	1:4.15	0.524	-0.1	29.71	30	1.069	0.560	21.8	1.6
Back side	GPRS 2TS	661/1880	1:4.15	0.736	-0.02	29.71	30	1.069	0.787	21.8	1.6
Left side	GPRS 2TS	661/1880	1:4.15	0.186	-0.04	29.71	30	1.069	0.199	21.8	1.6
Bottom side	GPRS 2TS	661/1880	1:4.15	0.594	-0.06	29.71	30	1.069	0.635	21.8	1.6

Table 15: SAR of GSM1900 for Head and Body.

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B
- 2) Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).



5.4.3 SAR Result Of WCDMA850

Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	Power drift(dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp.	SAR limit (W/kg)
Head Test data											
Left touch cheek	RMC	4182/836.6	1:1	0.242	-0.04	23.36	24	1.159	0.280	22.1	1.6
Left tilted 15 degree	RMC	4182/836.6	1:1	0.134	0.08	23.36	24	1.159	0.155	22.1	1.6
Right touch cheek	RMC	4182/836.6	1:1	0.18	0.17	23.36	24	1.159	0.209	22.1	1.6
Right tilted 15 degree	RMC	4182/836.6	1:1	0.114	0.08	23.36	24	1.159	0.132	22.1	1.6
Body worn Test data (Separate 15mm)											
Front side	RMC	4182/836.6	1:1	0.216	0.01	23.36	24	1.159	0.250	22.1	1.6
Back side	RMC	4182/836.6	1:1	0.271	0.02	23.36	24	1.159	0.314	22.1	1.6
Hotspot Test data (Separate 10mm)											
Front side	RMC	4182/836.6	1:1	0.283	-0.01	23.36	24	1.159	0.328	22.1	1.6
Back side	RMC	4182/836.6	1:1	0.264	0.02	23.36	24	1.159	0.306	22.1	1.6
Left side	RMC	4182/836.6	1:1	0.415	-0.02	23.36	24	1.159	0.481	22.1	1.6
Bottom side	RMC	4182/836.6	1:1	0.282	-0.1	23.36	24	1.159	0.327	22.1	1.6

Table 16: SAR of WCDMA850 for Head and Body.

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph Results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).



5.4.4 SAR Result Of WCDMA1700

Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	Power drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp.	SAR limit (W/kg)
Head Test data											
Left touch cheek	RMC	1412/1732.4	1:1	0.102	0.12	23.12	23.5	1.091	0.111	22.1	1.6
Left tilted 15 degree	RMC	1412/1732.4	1:1	0.087	0.02	23.12	23.5	1.091	0.095	22.1	1.6
Right touch cheek	RMC	1412/1732.4	1:1	0.061 3	0.01	23.12	23.5	1.091	0.067	22.1	1.6
Right tilted 15 degree	RMC	1412/1732.4	1:1	0.033	0.06	23.12	23.5	1.091	0.036	22.1	1.6
Body worn Test data (Separate 15mm)											
Front side	RMC	1412/1732.4	1:1	0.225	0.1	23.12	23.5	1.091	0.246	22.1	1.6
Back side	RMC	1412/1732.4	1:1	0.245	0.07	23.12	23.5	1.091	0.267	22.1	1.6
Hotspot Test data (Separate 10mm)											
Front side	RMC	1412/1732.4	1:1	0.427	0.13	23.12	23.5	1.091	0.466	22.1	1.6
Back side	RMC	1412/1732.4	1:1	0.604	-0.18	23.12	23.5	1.091	0.659	22.1	1.6
Left side	RMC	1412/1732.4	1:1	0.153	-0.01	23.12	23.5	1.091	0.167	22.1	1.6
Bottom side	RMC	1412/1732.4	1:1	0.676	-0.17	23.12	23.5	1.091	0.738	22.1	1.6

Table 17: SAR of WCDMA1700 for Head and Body.

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph Results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).



5.4.5 SAR Result Of WCDMA1900

Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	Power drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp.	SAR limit (W/kg)
Head Test data											
Left touch cheek	RMC	9400/1880	1:1	0.217	0.12	23.26	23.5	1.057	0.229	22.1	1.6
Left tilted 15 degree	RMC	9400/1880	1:1	0.0945	0.1	23.26	23.5	1.057	0.100	22.1	1.6
Right touch cheek	RMC	9400/1880	1:1	0.115	0.09	23.26	23.5	1.057	0.122	22.1	1.6
Right tilted 15 degree	RMC	9400/1880	1:1	0.0995	0.11	23.26	23.5	1.057	0.105	22.1	1.6
Body worn Test data(Separate 15mm)											
Front side	RMC	9400/1880	1:1	0.279	0.08	23.26	23.5	1.057	0.295	22.1	1.6
Back side	RMC	9400/1880	1:1	0.435	-0.04	23.26	23.5	1.057	0.460	22.1	1.6
Hotspot Test data (Separate 10mm)											
Front side	RMC	9400/1880	1:1	0.585	0.05	23.26	23.5	1.057	0.618	22.1	1.6
Back side	RMC	9400/1880	1:1	0.806	0.02	23.26	23.5	1.057	0.852	22.1	1.6
Back side	RMC	9262/1852.4	1:1	0.751	0.05	23.24	23.5	1.062	0.797	22.1	1.6
Back side	RMC	9538/1907.6	1:1	0.802	0.12	23.34	23.5	1.038	0.832	22.1	1.6
Left side	RMC	9400/1880	1:1	0.223	-0.08	23.26	23.5	1.057	0.236	22.1	1.6
Bottom side	RMC	9400/1880	1:1	0.572	0.08	23.26	23.5	1.057	0.604	22.1	1.6

Table 18: SAR of WCDMA1900 for Head and Body.

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph Results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).



5.4.6 SAR Result Of LTE 1900(20MHz)

Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	Power drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp.	SAR limit (W/kg)
Head Test data(1RB)											
Left touch cheek	QPSK	19100/1900	1:1	0.182	0.06	23.17	24	1.211	0.220	22.1	1.6
Left tilted 15 degree	QPSK	19100/1900	1:1	0.0307	-0.16	23.17	24	1.211	0.037	22.1	1.6
Right touch cheek	QPSK	19100/1900	1:1	0.0763	-0.18	23.17	24	1.211	0.092	22.1	1.6
Right tilted 15 degree	QPSK	19100/1900	1:1	0.0605	0.19	23.17	24	1.211	0.073	22.1	1.6
Head Test data(50%RB)											
Left touch cheek	QPSK	19100/1900	1:1	0.189	0.08	22.07	22.5	1.104	0.209	22.1	1.6
Left tilted 15 degree	QPSK	19100/1900	1:1	0.0513	0.19	22.07	22.5	1.104	0.057	22.1	1.6
Right touch cheek	QPSK	19100/1900	1:1	0.069	0.15	22.07	22.5	1.104	0.076	22.1	1.6
Right tilted 15 degree	QPSK	19100/1900	1:1	0.056	0.18	22.07	22.5	1.104	0.062	22.1	1.6
Body worn Test data(Separate 15mm 1RB)											
Front side	QPSK	19100/1900	1:1	0.41	0.13	23.17	24	1.211	0.496	22.1	1.6
Back side	QPSK	19100/1900	1:1	0.388	0.15	23.17	24	1.211	0.470	22.1	1.6
Body worn Test data (Separate 15mm 50%RB)											
Front side	QPSK	19100/1900	1:1	0.332	0.01	22.07	22.5	1.104	0.367	22.1	1.6
Back side	QPSK	19100/1900	1:1	0.324	0.08	22.07	22.5	1.104	0.358	22.1	1.6
Hotspot Test data(Separate 10mm 1RB)											
Front side	QPSK	18700/1860	1:1	0.649	-0.02	23.01	24	1.256	0.815	22.1	1.6
Front side	QPSK	18900/1880	1:1	0.686	0.15	23.13	24	1.222	0.838	22.1	1.6
Front side	QPSK	19100/1900	1:1	0.772	0.09	23.17	24	1.211	0.935	22.1	1.6
Back side	QPSK	18700/1860	1:1	0.682	-0.04	23.01	24	1.256	0.857	22.1	1.6
Back side	QPSK	18900/1880	1:1	0.736	0.05	23.13	24	1.222	0.899	22.1	1.6
Back side	QPSK	19100/1900	1:1	0.901	0.06	23.17	24	1.211	1.091	22.1	1.6
Left side	QPSK	19100/1900	1:1	0.26	0	23.17	24	1.211	0.315	22.1	1.6
Bottom side	QPSK	19100/1900	1:1	0.538	-0.05	23.17	24	1.211	0.651	22.1	1.6
Back side-repeat	QPSK	19100/1900	1:1	0.871	0.02	23.17	24	1.211	1.054	22.1	1.6
Hotspot Test data (Separate 10mm 50%RB)											
Front side	QPSK	19100/1900	1:1	0.639	-0.08	22.07	22.5	1.104	0.706	22.1	1.6
Back side	QPSK	18700/1860	1:1	0.558	-0.1	21.94	22.5	1.138	0.635	22.1	1.6
Back side	QPSK	18900/1880	1:1	0.668	-0.08	22.01	22.5	1.119	0.748	22.1	1.6
Back side	QPSK	19100/1900	1:1	0.739	0.04	22.07	22.5	1.104	0.816	22.1	1.6
Left side	QPSK	19100/1900	1:1	0.218	-0.06	22.07	22.5	1.104	0.241	22.1	1.6
Bottom side	QPSK	19100/1900	1:1	0.449	0	22.07	22.5	1.104	0.496	22.1	1.6
Hotspot Test data (Separate 10mm 100%RB)											
Front side	QPSK	19100/1900	1:1	0.613	0.09	22.13	23	1.222	0.749	22.1	1.6
Back side	QPSK	19100/1900	1:1	0.645	0.04	22.13	23	1.222	0.788	22.1	1.6

Table 19: SAR of LTE 1900 for Head and Body.



Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).

Test Position	Channel/ Frequency (MHz)	Measured SAR (1g)	1 st Repeated SAR (1g)	Ratio	2 nd Repeated SAR (1g)	3 rd Repeated SAR (1g)
Back Side	19100/1900	0.901	0.871	1.03	N/A	N/A
1) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg 2) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once. 3) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit). 4) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.						

Table 20: SAR Measurement Variability Results (LTE 1900)



5.4.1 SAR Result Of LTE 1700(20MHz)

Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	Power drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp.	SAR limit (W/kg)
Head Test data (1RB)											
Left touch cheek	QPSK	20050/1720	1:1	0.111	0.03	22.96	23.5	1.132	0.126	22.1	1.6
Left tilted 15 degree	QPSK	20050/1720	1:1	0.0549	-0.15	22.96	23.5	1.132	0.062	22.1	1.6
Right touch cheek	QPSK	20050/1720	1:1	0.056	0.2	22.96	23.5	1.132	0.063	22.1	1.6
Right tilted 15 degree	QPSK	20050/1720	1:1	0.0289	-0.08	22.96	23.5	1.132	0.033	22.1	1.6
Head Test data (50%RB)											
Left touch cheek	QPSK	20050/1720	1:1	0.0532	0.08	21.85	22.5	1.161	0.062	22.1	1.6
Left tilted 15 degree	QPSK	20050/1720	1:1	0.0484	0.04	21.85	22.5	1.161	0.056	22.1	1.6
Right touch cheek	QPSK	20050/1720	1:1	0.0449	0.05	21.85	22.5	1.161	0.052	22.1	1.6
Right tilted 15 degree	QPSK	20050/1720	1:1	0.0211	0.05	21.85	22.5	1.161	0.025	22.1	1.6
Body worn Test data(Separate 15mm 1RB)											
Front side	QPSK	20050/1720	1:1	0.242	-0.11	22.96	23.5	1.132	0.274	22.1	1.6
Back side	QPSK	20050/1720	1:1	0.262	-0.03	22.96	23.5	1.132	0.297	22.1	1.6
Body worn Test data (Separate 15mm 50%RB)											
Front side	QPSK	20050/1720	1:1	0.134	0.08	21.85	22.5	1.161	0.156	22.1	1.6
Back side	QPSK	20050/1720	1:1	0.189	0.02	21.85	22.5	1.161	0.220	22.1	1.6
Hotspot Test data(Separate 10mm 1RB)											
Front side	QPSK	20050/1720	1:1	0.401	-0.16	22.96	23.5	1.132	0.454	22.1	1.6
Back side	QPSK	20050/1720	1:1	0.539	0.03	22.96	23.5	1.132	0.610	22.1	1.6
Left side	QPSK	20050/1720	1:1	0.141	0.14	22.96	23.5	1.132	0.160	22.1	1.6
Bottom side	QPSK	20050/1720	1:1	0.539	-0.02	22.96	23.5	1.132	0.610	22.1	1.6
Hotspot Test data (Separate 10mm 50%RB)											
Front side	QPSK	20050/1720	1:1	0.381	0.17	21.85	22.5	1.161	0.443	22.1	1.6
Back side	QPSK	20050/1720	1:1	0.576	-0.19	21.85	22.5	1.161	0.669	22.1	1.6
Left side	QPSK	20050/1720	1:1	0.159	-0.06	21.85	22.5	1.161	0.185	22.1	1.6
Bottom side	QPSK	20050/1720	1:1	0.519	0	21.85	22.5	1.161	0.603	22.1	1.6

Table 21: SAR of LTE 1700 for Head and Body.

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).



5.4.2 SAR Result Of LTE 2600(20MHz)

Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	Power drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp.	SAR limit (W/kg)
Head Test data (1RB)											
Left touch cheek	QPSK	21100/2535.5	1:1	0.0161	0.02	22.95	24	1.274	0.021	22.1	1.6
Left tilted 15 degree	QPSK	21100/2535.5	1:1	0.0101	0.19	22.95	24	1.274	0.013	22.1	1.6
Right touch cheek	QPSK	21100/2535.5	1:1	0.0256	0.15	22.95	24	1.274	0.033	22.1	1.6
Right tilted 15 degree	QPSK	21100/2535.5	1:1	0.0206	-0.11	22.95	24	1.274	0.026	22.1	1.6
Head Test data (50%RB)											
Left touch cheek	QPSK	21100/2535.5	1:1	0.0125	0.11	21.91	22.5	1.146	0.014	22.1	1.6
Left tilted 15 degree	QPSK	21100/2535.5	1:1	0.0063	0.09	21.91	22.5	1.146	0.007	22.1	1.6
Right touch cheek	QPSK	21100/2535.5	1:1	0.0156	0	21.91	22.5	1.146	0.018	22.1	1.6
Right tilted 15 degree	QPSK	21100/2535.5	1:1	0.0099	-0.13	21.91	22.5	1.146	0.011	22.1	1.6
Body worn Test data(Separate 15mm 1RB)											
Front side	QPSK	21100/2535.5	1:1	0.108	-0.18	22.95	24	1.274	0.138	22.1	1.6
Back side	QPSK	21100/2535.5	1:1	0.0935	0.12	22.95	24	1.274	0.119	22.1	1.6
Body worn Test data(Separate 15mm 50%RB)											
Front side	QPSK	21100/2535.5	1:1	0.0334	0.18	21.91	22.5	1.146	0.038	22.1	1.6
Back side	QPSK	21100/2535.5	1:1	0.071	0.17	21.91	22.5	1.146	0.081	22.1	1.6
Hotspot Test data(Separate 10mm 1RB)											
Front side	QPSK	21100/2535.5	1:1	0.133	0.11	22.95	24	1.274	0.169	22.1	1.6
Back side	QPSK	21100/2535.5	1:1	0.259	0.1	22.95	24	1.274	0.330	22.1	1.6
Left side	QPSK	21100/2535.5	1:1	0.137	0.18	22.95	24	1.274	0.174	22.1	1.6
Bottom side	QPSK	21100/2535.5	1:1	0.081	-0.2	22.95	24	1.274	0.103	22.1	1.6
Hotspot Test data (Separate 10mm 50%RB)											
Front side	QPSK	21100/2535.5	1:1	0.0606	0.07	21.91	22.5	1.146	0.069	22.1	1.6
Back side	QPSK	21100/2535.5	1:1	0.139	0.15	21.91	22.5	1.146	0.159	22.1	1.6
Left side	QPSK	21100/2535.5	1:1	0.104	0.05	21.91	22.5	1.146	0.119	22.1	1.6
Bottom side	QPSK	21100/2535.5	1:1	0.0614	0.03	21.91	22.5	1.146	0.070	22.1	1.6

Table 22: SAR of LTE 2600 for Head and Body.



Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).



5.4.3 SAR Result Of LTE 750(10MHz)

Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	Power drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp.	SAR limit (W/kg)
Head Test data (1RB)											
Left touch cheek	QPSK	23780/709	1:1	0.014	0.02	23.21	24	1.199	0.017	22.1	1.6
Left tilted 15 degree	QPSK	23780/709	1:1	0.00838	0.19	23.21	24	1.199	0.010	22.1	1.6
Right touch cheek	QPSK	23780/709	1:1	0.0128	-0.11	23.21	24	1.199	0.015	22.1	1.6
Right tilted 15 degree	QPSK	23780/709	1:1	0.00692	0.19	23.21	24	1.199	0.008	22.1	1.6
Head Test data (50%RB)											
Left touch cheek	QPSK	23780/709	1:1	0.0134	-0.05	22.18	23	1.208	0.016	22.1	1.6
Left tilted 15 degree	QPSK	23780/709	1:1	0.00723	0.07	22.18	23	1.208	0.009	22.1	1.6
Right touch cheek	QPSK	23780/709	1:1	0.0105	0	22.18	23	1.208	0.013	22.1	1.6
Right tilted 15 degree	QPSK	23780/709	1:1	0.00575	0.14	22.18	23	1.208	0.007	22.1	1.6
Body worn Test data(Separate 15mm 1RB)											
Front side	QPSK	23780/709	1:1	0.0278	0	23.21	24	1.199	0.033	22.1	1.6
Back side	QPSK	23780/709	1:1	0.035	0.09	23.21	24	1.199	0.042	22.1	1.6
Body worn Test data(Separate 15mm 50%RB)											
Front side	QPSK	23780/709	1:1	0.0234	0.06	22.18	23	1.208	0.028	22.1	1.6
Back side	QPSK	23780/709	1:1	0.0296	0	22.18	23	1.208	0.036	22.1	1.6
Hotspot Test data(Separate 10mm 1RB)											
Front side	QPSK	23780/709	1:1	0.0367	0.1	23.21	24	1.199	0.044	22.1	1.6
Back side	QPSK	23780/709	1:1	0.047	-0.03	23.21	24	1.199	0.056	22.1	1.6
Left side	QPSK	23780/709	1:1	0.0336	0.08	23.21	24	1.199	0.040	22.1	1.6
Bottom side	QPSK	23780/709	1:1	0.0111	-0.05	23.21	24	1.199	0.013	22.1	1.6
Hotspot Test data(Separate 10mm 50%RB)											
Front side	QPSK	23780/709	1:1	0.031	-0.08	22.18	23	1.208	0.037	22.1	1.6
Back side	QPSK	23780/709	1:1	0.0398	0.04	22.18	23	1.208	0.048	22.1	1.6
Left side	QPSK	23780/709	1:1	0.0279	0.02	22.18	23	1.208	0.034	22.1	1.6
Bottom side	QPSK	23780/709	1:1	0.00858	0.02	22.18	23	1.208	0.010	22.1	1.6

Table 23: SAR of LTE 750 for Head and Body.



Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).



5.4.4 SAR Result Of WIFI

Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	Power drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp.	SAR limit (W/kg)
Head Test data											
Left touch cheek	802.11b	11/2462	1:1	0.0922	0.07	16.53	17	1.114	0.103	21.9	1.6
Left tilted 15 degree	802.11b	11/2462	1:1	0.0759	0.11	16.53	17	1.114	0.085	21.9	1.6
Right touch cheek	802.11b	11/2462	1:1	0.132	0.05	16.53	17	1.114	0.147	21.9	1.6
Right tilted 15 degree	802.11b	11/2462	1:1	0.173	0.05	16.53	17	1.114	0.193	21.9	1.6
Body worn Test data(Separate 15mm)											
Front side	802.11b	11/2462	1:1	0.0139	0.1	16.53	17	1.114	0.015	21.9	1.6
Back side	802.11b	11/2462	1:1	0.03	0.18	16.53	17	1.114	0.033	21.9	1.6
Hotspot Test data (Separate 10mm)											
Front side	802.11b	11/2462	1:1	0.0337	0.14	16.53	17	1.114	0.038	21.9	1.6
Back side	802.11b	11/2462	1:1	0.078	0.11	16.53	17	1.114	0.087	21.9	1.6
Left side	802.11b	11/2462	1:1	0.0071	0.14	16.53	17	1.114	0.008	21.9	1.6
Top side	802.11b	11/2462	1:1	0.0375	-0.01	16.53	17	1.114	0.042	21.9	1.6

Table 24: SAR of WIFI for Head and Body

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).
- 3) Each channel was tested at the lowest data rate.
- 4) When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, 802.11g/n OFDM SAR Test is not required.



5.5 Multiple Transmitter Evaluation

5.5.1 Simultaneous SAR test evaluation

1) Simultaneous Transmission

NO.	Simultaneous Transmission Configuration	Head	Body worn	Hotspot
1	GSM(Voice) + WiFi	Yes	Yes	-
2	GSM(Voice) + BT	Yes	Yes	-
3	WCDMA(Voice) + WiFi	Yes	Yes	-
4	WCDMA(Voice) + BT	Yes	Yes	-
5	GPRS / EDGE(Data) + WiFi	-	-	Yes
6	GPRS / EDGE(Data) + BT	-	-	Yes
7	WCDMA(Data) + WiFi	-	-	Yes
8	WCDMA(Data) + BT	-	-	Yes
9	LTE(Data) + WiFi	Yes	Yes	Yes
10	LTE(Data) + BT	Yes	Yes	Yes
11	BT+WIFI (They share the same antenna and cannot transmit at the same time by design.)	No	No	No

5.5.2 Estimated SAR

When the standalone SAR test exclusion is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following to determine simultaneous transmission SAR test exclusion:

- $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})} / x] \text{ W/kg}$ for test separation distances $\leq 50 \text{ mm}$;

Where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.

- 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is $> 50 \text{ mm}$.

Estimated SAR Result

Freq. Band	Frequency (MHz)	Test Position	Test Separation (mm)	max. power(dBm)	Estimated 1g SAR (W/kg)
Bluetooth	2480	Head	0	4	0.17
Bluetooth	2480	Body-worn	15	4	0.06
Bluetooth	2480	hotspot	10	4	0.08



2) Simultaneous Transmission SAR Summation Scenario for head

WWAN Band	Exposure position	①MAX.WW AN SAR(W/kg)	② MAX.WLAN SAR(W/kg)	③ MAX.BT SAR(W/kg)	Summed SAR①+②	Summed SAR①+③	Case NO.
GSM850	Left Touch	0.318	0.103	0.170	0.421	0.488	No
	Left Tilt	0.198	0.085	0.170	0.282	0.368	No
	Right Touch	0.274	0.147	0.170	0.421	0.444	No
	Right Tilt	0.188	0.193	0.170	0.380	0.358	No
GSM1900	Left Touch	0.211	0.103	0.170	0.313	0.381	No
	Left Tilt	0.047	0.085	0.170	0.131	0.217	No
	Right Touch	0.058	0.147	0.170	0.205	0.228	No
	Right Tilt	0.133	0.193	0.170	0.325	0.303	No
WCDMA 850	Left Touch	0.280	0.103	0.170	0.383	0.450	No
	Left Tilt	0.155	0.085	0.170	0.240	0.325	No
	Right Touch	0.209	0.147	0.170	0.356	0.379	No
	Right Tilt	0.132	0.193	0.170	0.325	0.302	No
WCDMA 1700	Left Touch	0.111	0.103	0.170	0.214	0.281	No
	Left Tilt	0.095	0.085	0.170	0.180	0.265	No
	Right Touch	0.067	0.147	0.170	0.214	0.237	No
	Right Tilt	0.036	0.193	0.170	0.229	0.206	No
WCDMA 1900	Left Touch	0.229	0.103	0.170	0.332	0.399	No
	Left Tilt	0.100	0.085	0.170	0.184	0.270	No
	Right Touch	0.122	0.147	0.170	0.269	0.292	No
	Right Tilt	0.105	0.193	0.170	0.298	0.275	No
LTE Band 2	Left Touch	0.220	0.103	0.170	0.323	0.390	No
	Left Tilt	0.057	0.085	0.170	0.141	0.227	No
	Right Touch	0.092	0.147	0.170	0.239	0.262	No
	Right Tilt	0.073	0.193	0.170	0.266	0.243	No
LTE Band 4	Left Touch	0.126	0.103	0.170	0.228	0.296	No
	Left Tilt	0.062	0.085	0.170	0.147	0.232	No
	Right Touch	0.063	0.147	0.170	0.211	0.233	No
	Right Tilt	0.033	0.193	0.170	0.225	0.203	No
LTE Band 7	Left Touch	0.021	0.103	0.170	0.123	0.191	No
	Left Tilt	0.013	0.085	0.170	0.097	0.183	No
	Right Touch	0.033	0.147	0.170	0.180	0.203	No
	Right Tilt	0.026	0.193	0.170	0.219	0.196	No
LTE Band 17	Left Touch	0.017	0.103	0.170	0.120	0.187	No
	Left Tilt	0.010	0.085	0.170	0.095	0.180	No
	Right Touch	0.015	0.147	0.170	0.162	0.185	No
	Right Tilt	0.008	0.193	0.170	0.201	0.178	No



3) Simultaneous Transmission SAR Summation Scenario for body worn

WWAN Band	Exposure position	①MAX.WWAN SAR(W/kg)	②MAX.WLAN SAR(W/kg)	③MAX.BT SAR(W/kg)	Summed SAR①+②	Summed SAR①+③	Case NO.
GSM850	Front	0.423	0.015	0.060	0.439	0.483	No
	Back	0.442	0.033	0.060	0.476	0.502	No
GSM1900	Front	0.172	0.015	0.060	0.187	0.232	No
	Back	0.270	0.033	0.060	0.303	0.330	No
WCDMA 850	Front	0.250	0.015	0.060	0.266	0.310	No
	Back	0.314	0.033	0.060	0.347	0.374	No
WCDMA 1700	Front	0.246	0.015	0.060	0.261	0.306	No
	Back	0.267	0.033	0.060	0.301	0.327	No
WCDMA 1900	Front	0.295	0.015	0.060	0.310	0.355	No
	Back	0.460	0.033	0.060	0.493	0.520	No
LTE Band 2	Front	0.496	0.015	0.060	0.512	0.556	No
	Back	0.470	0.033	0.060	0.503	0.530	No
LTE Band 4	Front	0.274	0.015	0.060	0.290	0.334	No
	Back	0.297	0.033	0.060	0.330	0.357	No
LTE Band 7	Front	0.138	0.015	0.060	0.153	0.198	No
	Back	0.119	0.033	0.060	0.153	0.179	No
LTE Band 17	Front	0.033	0.015	0.060	0.049	0.093	No
	Back	0.042	0.033	0.060	0.076	0.102	No



4) Simultaneous Transmission SAR Summation Scenario for hotspot

WWAN Band	Exposure position	①MAX.WWAN SAR(W/kg)	②MAX.WLAN SAR(W/kg)	③MAX.BT SAR(W/kg)	Summed SAR①+②	Summed SAR①+③	Case NO.
GSM850	Front	0.650	0.038	0.080	0.688	0.730	No
	Back	0.650	0.087	0.080	0.737	0.730	No
	Left	0.911	0.008	0.080	0.919	0.991	No
	Right	/	/	0.080	/	0.080	No
	Top	/	0.042	0.080	0.038	0.080	No
	Bottom	0.511	/	0.080	0.391	0.591	No
GSM1900	Front	0.560	0.038	0.080	0.598	0.640	No
	Back	0.787	0.087	0.080	0.874	0.867	No
	Left	0.199	0.008	0.080	0.207	0.279	No
	Right	/	/	0.080	/	0.080	No
	Top	/	0.042	0.080	0.038	0.080	No
	Bottom	0.635	/	0.080	0.594	0.715	No
WCDMA 850	Front	0.328	0.038	0.080	0.365	0.408	No
	Back	0.306	0.087	0.080	0.393	0.386	No
	Left	0.481	0.008	0.080	0.489	0.561	No
	Right	/	/	0.080	/	0.080	No
	Top	/	0.042	0.080	0.038	0.080	No
	Bottom	0.327	/	0.080	0.282	0.407	No
WCDMA 1700	Front	0.466	0.038	0.080	0.504	0.546	No
	Back	0.659	0.087	0.080	0.746	0.739	No
	Left	0.167	0.008	0.080	0.175	0.247	No
	Right	/	/	0.080	/	0.080	No
	Top	/	0.042	0.080	0.038	0.080	No
	Bottom	0.738	/	0.080	0.676	0.818	No
WCDMA 1900	Front	0.618	0.038	0.080	0.656	0.698	No
	Back	0.852	0.087	0.080	0.939	0.932	No
	Left	0.236	0.008	0.080	0.244	0.316	No
	Right	/	/	0.080	/	0.080	No
	Top	/	0.042	0.080	0.038	0.080	No
	Bottom	0.604	/	0.080	0.572	0.684	No
LTE Band 2	Front	0.935	0.038	0.080	0.972	1.015	No
	Back	1.091	0.087	0.080	1.178	1.171	No
	Left	0.315	0.008	0.080	0.323	0.395	No
	Right	/	/	0.080	/	0.080	No
	Top	/	0.042	0.080	0.038	0.080	No
	Bottom	0.651	/	0.080	0.538	0.731	No



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM160300168001

Rev.00

Page: 70 of 74

WWAN Band	Exposure position	①MAX.WWAN SAR(W/kg)	②MAX.WLAN SAR(W/kg)	③MAX.BT SAR(W/kg)	Summed SAR①+②	Summed SAR①+③	Case NO.
LTE Band 4	Front	0.454	0.038	0.080	0.492	0.534	No
	Back	0.669	0.087	0.080	0.756	0.749	No
	Left	0.185	0.008	0.080	0.193	0.265	No
	Right	/	/	0.080	/	0.080	No
	Top	/	0.042	0.080	0.038	0.080	No
	Bottom	0.610	/	0.080	0.539	0.690	No
LTE Band 7	Front	0.169	0.038	0.080	0.207	0.249	No
	Back	0.330	0.087	0.080	0.417	0.410	No
	Left	0.174	0.008	0.080	0.182	0.254	No
	Right	/	/	0.080	/	0.080	No
	Top	/	0.042	0.080	0.038	0.080	No
	Bottom	0.103	/	0.080	0.081	0.183	No
LTE Band 17	Front	0.044	0.038	0.080	0.082	0.124	No
	Back	0.056	0.087	0.080	0.143	0.136	No
	Left	0.040	0.008	0.080	0.048	0.120	No
	Right	/	/	0.080	/	0.080	No
	Top	/	0.042	0.080	0.038	0.080	No
	Bottom	0.013	/	0.080	0.011	0.093	No



6 Equipment list

Test Platform		SPEAG DASY5 Professional				
Location		SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch E&E Lab				
Description		SAR Test System (Frequency range 300MHz-6GHz)				
Software Reference		DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)				
Hardware Reference						
Equipment		Manufacturer	Model	Serial Number	Calibration Date	Due date of calibration
☒	Robot	Staubli	RX90L	F03/5V32A1/A01	NCR	NCR
☒	Twin Phantom	SPEAG	SAM 1	TP-1283	NCR	NCR
☐	Flat Phantom	SPEAG	ELI 5.0	1128	NCR	NCR
☒	DAE	SPEAG	DAE3	569	2015-11-24	2016-11-23
☒	E-Field Probe	SPEAG	EX3DV4	3962	2015-11-27	2016-11-26
☒	Validation Kits	SPEAG	D750V3	1126	2014-09-19	2017-09-18
☒	Validation Kits	SPEAG	D835V2	4d015	2013-11-25	2016-11-24
☒	Validation Kits	SPEAG	D1800V2	2d070	2013-11-27	2016-11-26
☒	Validation Kits	SPEAG	D1900V2	184	2013-11-27	2016-11-26
☒	Validation Kits	SPEAG	D2450V2	733	2013-11-26	2016-11-25
☒	Validation Kits	SPEAG	D2600V2	1093	2014-09-23	2017-09-22
☒	Agilent Network Analyzer	Agilent	E5071C	MY46523590	2016-03-08	2017-03-08
☒	Dielectric Probe Kit	Agilent	85070E	US01440210	NCR	NCR
☒	Universal Radio Communication Tester	R&S	CMU200	123090	2015-10-23	2016-10-23
☒	Universal Radio Communication Tester	R&S	CMW500	152271	2016-03-08	2017-03-08
☒	RF Bi-Directional Coupler	Agilent	86205-60001	MY31400031	NCR	NCR
☒	Signal Generator	Agilent	N5171B	MY53050736	2016-03-08	2017-03-08
☒	Preamplifier	Mini-Circuits	ZHL-42W	15542	NCR	NCR
☒	Power Meter	Agilent	E4416A	GB41292095	2016-03-08	2017-03-08
☒	Power Sensor	Agilent	8481H	MY41091234	2016-03-08	2017-03-08
☒	Power Sensor	R&S	NRP-Z92	100025	2016-03-08	2017-03-08
☒	Attenuator	SHX	TS2-3dB	30704	NCR	NCR
☒	Coaxial low pass filter	Mini-Circuits	VLF-2500(+)	NA	NCR	NCR
☒	Coaxial low pass filter	Microlab Fxr	LA-F13	NA	NCR	NCR
☒	50 Ω coaxial load	Mini-Circuits	KARN-50+	00850	NCR	NCR
☒	DC POWER SUPPLY	SAKO	SK1730SL 5A	NA	NCR	NCR



7 Measurement Uncertainty

Measurements and results are all in compliance with the standards listed in section 12 of this report. All measurements and results are recorded and maintained at the laboratory performing the tests and measurement uncertainties are taken into account when comparing measurements to pass/ fail criteria. The Expanded uncertainty (95% CONFIDENCE INTERVAL) is **21.36%**.

A	b1	c	d	e = f(d,k)	g	i = C*g/e	k
Uncertainty Component	Section in P1528	Tol (%)	Prob . Dist.	Div.	Ci (1g)	1g ui (%)	Vi (Veff)
Probe calibration	E.2.1	6.3	N	1	1	6.30	∞
Axial isotropy	E.2.2	0.5	R	$\sqrt{3}$	$(1 - C_p)1/2$	0.20	∞
hemispherical isotropy	E.2.2	2.6	R	$\sqrt{3}$	$\sqrt{C_p}$	1.06	∞
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	1	0.58	∞
Linearity	E.2.4	0.6	R	$\sqrt{3}$	1	0.35	∞
System detection limit	E.2.5	0.25	R	$\sqrt{3}$	1	0.14	∞
Readout electronics	E.2.6	0.3	N	1	1	0.30	∞
Response time	E.2.7	0	R	$\sqrt{3}$	1	0.00	∞
Integration time	E.2.8	2.6	R	$\sqrt{3}$	1	1.50	∞
RF ambient Condition –Noise	E.6.1	3	R	$\sqrt{3}$	1	1.73	∞
RF ambient Condition - reflections	E.6.1	3	R	$\sqrt{3}$	1	1.73	∞
Probe positioning- mechanical tolerance	E.6.2	1.5	R	$\sqrt{3}$	1	0.87	∞
Probe positioning- with respect to phantom	E.6.3	2.9	R	$\sqrt{3}$	1	1.67	∞
Max. SAR evaluation	E.5.2	1	R	$\sqrt{3}$	1	0.58	∞
Test sample positioning	E.4.2	3.7	N	1	1	3.70	9
Device holder uncertainty	E.4.1	3.6	N	1	1	3.60	∞
Output power variation –SAR drift measurement	6.6.2	5	R	$\sqrt{3}$	1	2.89	∞
Phantom uncertainty (shape and thickness tolerances)	E.3.1	4	R	$\sqrt{3}$	1	2.31	∞
Liquid conductivity - deviation from target values	E.3.2	5	R	$\sqrt{3}$	0.64	1.85	∞
Liquid conductivity - measurement uncertainty	E.3.2	5.78	N	1	0.64	3.68	5
Liquid permittivity - deviation from target values	E.3.3	5	R	$\sqrt{3}$	0.6	1.73	∞

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Liquid permittivity - measurement uncertainty	E.3.3	0.62	N	1	0.6	0.372	5
Combined standard uncertainty				RSS		10.68	430
Expanded uncertainty (95% CONFIDENCE INTERVAL)				K=2		21.36	

Table 25 : Measurement Uncertainty

8 Calibration certificate

Please see the Appendix C

9 Photographs

Please see the Appendix D



Appendix A: Detailed System Validation Results

Appendix B: Detailed Test Results

Appendix C: Calibration certificate

Appendix D: Photographs

---END---



Appendix A

Detailed System Validation Results

1. System Performance Check for Head
System Performance Check 750 MHz Head
System Performance Check 835 MHz Head
System Performance Check 1800 MHz Head
System Performance Check 1900 MHz Head
System Performance Check 2450 MHz Head
System Performance Check 2600 MHz Head
2. System Performance Check for Body
System Performance Check 750 MHz Body
System Performance Check 835 MHz Body
System Performance Check 1800 MHz Body
System Performance Check 1900 MHz Body
System Performance Check 2450 MHz Body
System Performance Check 2600 MHz Body

Test Laboratory: SGS-SAR Lab

System Performance Check 750 MHz Head

DUT: D750V3; Type: D750V3; Serial: 1126

Communication System: UID 0, CW (0); Frequency: 750 MHz; Duty Cycle: 1:1


Medium: HSL750; Medium parameters used: $f = 750$ MHz; $\sigma = 0.885$ S/m; $\epsilon_r = 41.885$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(10.67, 10.67, 10.67); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=15mm, Pin=250mW/Area Scan (7x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 2.17 W/kg

Body/d=15mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:
 $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 50.42 V/m; Power Drift = -0.00 dB
Peak SAR (extrapolated) = 3.05 W/kg
SAR(1 g) = 2.08 W/kg; SAR(10 g) = 1.39 W/kg
Maximum value of SAR (measured) = 2.23 W/kg



Test Laboratory: SGS-SAR Lab

System Performance Check 750 MHz Body

DUT: D750V3; Type: D750V3; Serial: 1126

Communication System: UID 0, CW (0); Frequency: 750 MHz; Duty Cycle: 1:1


Medium: MSL750; Medium parameters used: $f = 750$ MHz; $\sigma = 0.942$ S/m; $\epsilon_r = 56.086$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(10.41, 10.41, 10.41); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=15mm, Pin=250mW/Area Scan (7x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 2.37 W/kg

Body/d=15mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:
 $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 51.04 V/m; Power Drift = -0.00 dB
Peak SAR (extrapolated) = 3.33 W/kg
SAR(1 g) = 2.26 W/kg; SAR(10 g) = 1.51 W/kg
Maximum value of SAR (measured) = 2.43 W/kg



0 dB = 2.37 W/kg = 3.74 dBW/kg

Test Laboratory: SGS-SAR Lab

System Performance Check 835 MHz Head

DUT: D835V2; Type: D835V2; Serial: 4d105

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1


Medium: HSL835; Medium parameters used: $f = 835$ MHz; $\sigma = 0.926$ S/m; $\epsilon_r = 40.953$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(10.17, 10.17, 10.17); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=15mm, Pin=250mW/Area Scan (7x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 2.48 W/kg

Body/d=15mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:
 $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 53.38 V/m; Power Drift = -0.32 dB
Peak SAR (extrapolated) = 3.39 W/kg
SAR(1 g) = 2.3 W/kg; SAR(10 g) = 1.54 W/kg



0 dB = 2.48 W/kg = 3.94 dBW/kg

Test Laboratory: SGS-SAR Lab

System Performance Check 835 MHz Body

DUT: D835V2; Type: D835V2; Serial: 4d105

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1


Medium: MSL835; Medium parameters used: $f = 835$ MHz; $\sigma = 0.981$ S/m; $\epsilon_r = 55.395$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(10.16, 10.16, 10.16); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=15mm, Pin=250mW/Area Scan (7x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 2.33 W/kg

Body/d=15mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:
 $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 49.88 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 3.25 W/kg
SAR(1 g) = 2.23 W/kg; SAR(10 g) = 1.5 W/kg
Maximum value of SAR (measured) = 2.40 W/kg



$$0 \text{ dB} = 2.40 \text{ W/kg} = 3.80 \text{ dBW/kg}$$

Test Laboratory: SGS-SAR Lab

System Performance Check 1800 MHz Head

DUT: D1800V2; Type: D1800V2; Serial: 2d070

Communication System: UID 0, CW (0); Frequency: 1800 MHz; Duty Cycle: 1:1

Medium: HSL1800; Medium parameters used: $f = 1800$ MHz; $\sigma = 1.396$ S/m; $\epsilon_r = 40.096$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(8.77, 8.77, 8.77); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=10mm, Pin=250mW/Area Scan (7x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 9.12 W/kg

Body/d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:


$dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 85.81 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 16.7 W/kg

SAR(1 g) = 9.19 W/kg; SAR(10 g) = 4.89 W/kg

Maximum value of SAR (measured) = 10.3 W/kg



$$0 \text{ dB} = 10.3 \text{ W/kg} = 10.13 \text{ dBW/kg}$$

Test Laboratory: SGS-SAR Lab

System Performance Check 1800 MHz Body

DUT: D1800V2; Type: D1800V2; Serial: 2d070

Communication System: UID 0, CW (0); Frequency: 1800 MHz; Duty Cycle: 1:1

Medium: MSL1750; Medium parameters used: $f = 1800$ MHz; $\sigma = 1.535$ S/m; $\epsilon_r = 54.359$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(8.49, 8.49, 8.49); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=10mm, Pin=250mW/Area Scan (7x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 9.85 W/kg

Body/d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:


$dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 93.66 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 18.7 W/kg

SAR(1 g) = 9.85W/kg; SAR(10 g) = 5.38 W/kg

Maximum value of SAR (measured) = 12.6 W/kg



$$0 \text{ dB} = 12.6 \text{ W/kg} = 10.94 \text{ dBW/kg}$$

Test Laboratory: SGS-SAR Lab

System Performance Check 1900 MHz Head

DUT: D1900V2; Type: D1900V2; Serial: 5d028

Communication System: UID 0, CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL1900; Medium parameters used: $f = 1900$ MHz; $\sigma = 1.437$ S/m; $\epsilon_r = 40.578$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(8.49, 8.49, 8.49); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=10mm, Pin=250mW/Area Scan (7x11x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 10.4 W/kg

Body/d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:


$dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 83.65 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 18.1 W/kg

SAR(1 g) = 9.73 W/kg; SAR(10 g) = 5.04 W/kg

Maximum value of SAR (measured) = 11.0 W/kg



0 dB = 10.4 W/kg = 10.18 dBW/kg

Test Laboratory: SGS-SAR Lab

System Performance Check 1900 MHz Body

DUT: D1900V2; Type: D1900V2; Serial: 5d028

Communication System: UID 0, CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL1900; Medium parameters used: $f = 1900$ MHz; $\sigma = 1.551$ S/m; $\epsilon_r = 51.921$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(8.2, 8.2, 8.2); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=10mm, Pin=250mW/Area Scan (7x11x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 11.4 W/kg

Body/d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:


$dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 87.68 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 21.4 W/kg

SAR(1 g) = 10.4 W/kg; SAR(10 g) = 5.46 W/kg

Maximum value of SAR (measured) = 12.1 W/kg



$$0 \text{ dB} = 12.1 \text{ W/kg} = 10.83 \text{ dBW/kg}$$

Test Laboratory: SGS-SAR Lab

System Performance Check 2450MHz Head

DUT: D2450V2; Type: D2450V2; Serial: 733

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: HSL2450; Medium parameters used: $f = 2450$ MHz; $\sigma = 1.781$ S/m; $\epsilon_r = 38.561$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(7.65, 7.65, 7.65); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=10mm, Pin=250mW/Area Scan (7x11x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 14.0 W/kg

Body/d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:


$dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 90.36 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 30.2 W/kg

SAR(1 g) = 13.3 W/kg; SAR(10 g) = 5.95 W/kg

Maximum value of SAR (measured) = 14.9 W/kg



0 dB = 14.9 W/kg = 11.73 dBW/kg

Test Laboratory: SGS-SAR Lab

System Performance Check 2450MHz Body

DUT: D2450V2; Type: D2450V2; Serial: 733

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: MSL2450; Medium parameters used: $f = 2450$ MHz; $\sigma = 1.951$ S/m; $\epsilon_r = 51.68$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(7.7, 7.7, 7.7); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=10mm, Pin=250mW/Area Scan (7x11x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 11.8 W/kg

Body/d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:


$dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 93.93 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 26.2 W/kg

SAR(1 g) = 12.8 W/kg; SAR(10 g) = 5.88 W/kg

Maximum value of SAR (measured) = 16.4 W/kg



0 dB = 16.4 W/kg = 12.31 dBW/kg

Test Laboratory: SGS-SAR Lab

System Performance Check 2600MHz Head

DUT: D2600V2; Type: D2600V2; Serial: 1093

Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1


Medium: HSL2600; Medium parameters used: $f = 2600$ MHz; $\sigma = 1.937$ S/m; $\epsilon_r = 38.1$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(7.35, 7.35, 7.35); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=10mm, Pin=250mW/Area Scan (10x13x1): Measurement grid: $dx=10$ mm, $dy=10$ mm
Maximum value of SAR (measured) = 13.8 W/kg

Body/d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:
 $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 88.16 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 32.7 W/kg
SAR(1 g) = 14 W/kg; SAR(10 g) = 6.13 W/kg
Maximum value of SAR (measured) = 16.1 W/kg



Test Laboratory: SGS-SAR Lab

System Performance Check 2600MHz Body

DUT: D2600V2; Type: D2600V2; Serial: 1093

Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: MSL2600; Medium parameters used: $f = 2600$ MHz; $\sigma = 2.171$ S/m; $\epsilon_r = 52.866$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(7.63, 7.63, 7.63); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=10mm, Pin=250mW/Area Scan (7x11x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 16.2 W/kg

Body/d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:


$dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 96.35 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 30.3 W/kg

SAR(1 g) = 14.1 W/kg; SAR(10 g) = 6.22 W/kg

Maximum value of SAR (measured) = 18.4 W/kg



0 dB = 18.4 W/kg = 13.58 dBW/kg



Appendix B

Detailed Test Results

1. GSM
GSM850 for Head &Body
GSM1900 for Head &Body
2. WCDMA
WCDMA850 for Head &Body
WCDMA1700 for Head &Body
WCDMA1900 for Head &Body
3. LTE
LTE Band 2 for Head &Body
LTE Band 4 for Head &Body
LTE Band 7 for Head &Body
LTE Band 17 for Head &Body
4. WIFI
WIFI for Head &Body

Test Laboratory: SGS-SAR Lab

Haier i701 GSM850 190CH Left touch cheek

DUT: Haier-i701; Type: Mobile Phone ; Serial: FINJSGKN9999999

Communication System: UID 0, GSM Only Communication System (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium: HSL835; Medium parameters used: $f = 837$ MHz; $\sigma = 0.907$ S/m; $\epsilon_r = 42.907$; $\rho = 1000$ kg/m³
Phantom section: Left Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(10.17, 10.17, 10.17); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.257 W/kg


Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 6.385 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.317 W/kg

SAR(1 g) = 0.251 W/kg; SAR(10 g) = 0.194 W/kg

Maximum value of SAR (measured) = 0.262 W/kg



0 dB = 0.262 W/kg = -5.82 dBW/kg

Test Laboratory: SGS-SAR Lab

Haier i701 GSM850 190CH Back side 15mm

DUT: Haier-i701; Type: Mobile Phone ; Serial: FINJSGKN9999999

Communication System: UID 0, GSM Only Communication System (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium: HSL835; Medium parameters used: $f = 837$ MHz; $\sigma = 0.907$ S/m; $\epsilon_r = 42.907$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(10.17, 10.17, 10.17); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = -14.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.368 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 19.98 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.433 W/kg

SAR(1 g) = 0.349 W/kg; SAR(10 g) = 0.272 W/kg

Maximum value of SAR (measured) = 0.366 W/kg



0 dB = 0.368 W/kg = -4.34 dBW/kg

Test Laboratory: SGS-SAR Lab

Haier i701 GSM850 GPRS 4TS 128CH Left side 10mm

DUT: Haier-i701; Type: Mobile Phone ; Serial: FINJSGKN9999999

Communication System: UID 0, GPRS/EGPRS Mode(4up) Communication System (0); Frequency: 824.2 MHz; Duty Cycle: 1:2.0797

Medium: HSL835; Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.893$ S/m; $\epsilon_r = 43.079$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(10.17, 10.17, 10.17); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = -14.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.745 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm


Reference Value = 29.25 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.05 W/kg

SAR(1 g) = 0.734 W/kg; SAR(10 g) = 0.507 W/kg

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.787 W/kg



$$0 \text{ dB} = 0.745 \text{ W/kg} = -1.28 \text{ dBW/kg}$$

Test Laboratory: SGS-SAR Lab

Haier i701 GSM1900 661CH Left touch cheek

DUT: Haier-i701; Type: Mobile Phone ; Serial: FINJSGKN9999999

Communication System: UID 0, GSM Only Communication System (0); Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium: HSL1900; Medium parameters used: $f = 1880$ MHz; $\sigma = 1.419$ S/m; $\epsilon_r = 40.582$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(8.49, 8.49, 8.49); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.433 W/kg


Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 2.365 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.461 W/kg

SAR(1 g) = 0.189 W/kg; SAR(10 g) = 0.131 W/kg

Maximum value of SAR (measured) = 0.461 W/kg



Test Laboratory: SGS-SAR Lab

Haier i701 GSM1900 661CH Back side 15mm

DUT: Haier-i701; Type: Mobile Phone ; Serial: FINJSGKN9999999

Communication System: UID 0, GSM Only Communication System (0); Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium: MSL1900; Medium parameters used: $f = 1880$ MHz; $\sigma = 1.493$ S/m; $\epsilon_r = 52.273$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(8.2, 8.2, 8.2); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = -14.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.247 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 6.251 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.393 W/kg

SAR(1 g) = 0.242 W/kg; SAR(10 g) = 0.141 W/kg

Maximum value of SAR (measured) = 0.259 W/kg



Test Laboratory: SGS-SAR Lab

Haier i701 GSM1900 GPRS 2TS 661CH Back side 10mm

DUT: Haier-i701; Type: Mobile Phone ; Serial: FINJSGKN9999999

Communication System: UID 0, GPRS/EGPRS Mode(2up) Communication System (0); Frequency: 1880 MHz; Duty Cycle: 1:4.14954

Medium: MSL1900; Medium parameters used: $f = 1880$ MHz; $\sigma = 1.493$ S/m; $\epsilon_r = 52.273$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(8.2, 8.2, 8.2); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = -14.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.776 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 10.29 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.25 W/kg

SAR(1 g) = 0.736 W/kg; SAR(10 g) = 0.417 W/kg

Maximum value of SAR (measured) = 0.781 W/kg



0 dB = 0.781 W/kg = -1.07 dBW/kg

Test Laboratory: SGS-SAR Lab

Haier i701 WCDMA850 4182CH Left touch cheek

DUT: Haier-i701; Type: Mobile Phone ; Serial: FINJSGKN9999999

Communication System: UID 0, WCDMA (0); Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium: HSL835; Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.906$ S/m; $\epsilon_r = 42.92$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(10.17, 10.17, 10.17); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.253 W/kg

Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm


Reference Value = 8.687 V/m; Power Drift = -0.04dB

Peak SAR (extrapolated) = 0.296 W/kg

SAR(1 g) = 0.242 W/kg; SAR(10 g) = 0.190 W/kg

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.255 W/kg



0 dB = 0.253 W/kg = -5.97 dBW/kg

Test Laboratory: SGS-SAR Lab

Haier i701 WCDMA850 4182CH Back side 15mm

DUT: Haier-i701; Type: Mobile Phone ; Serial: FINJSGKN9999999

Communication System: UID 0, WCDMA (0); Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium: MSL835; Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.984$ S/m; $\epsilon_r = 55.294$;
 $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(10.16, 10.16, 10.16); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = -14.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.282 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm


Reference Value = 16.73 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.343 W/kg

SAR(1 g) = 0.271 W/kg; SAR(10 g) = 0.208 W/kg

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.284 W/kg



Test Laboratory: SGS-SAR Lab

Haier i701 WCDMA850 4182CH Left side 10mm

DUT: Haier-i701; Type: Mobile Phone ; Serial: FINJSGKN9999999

Communication System: UID 0, WCDMA (0); Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium: MSL835; Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.984$ S/m; $\epsilon_r = 55.294$;
 $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(10.16, 10.16, 10.16); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.433 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm


Reference Value = 20.80 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.592 W/kg

SAR(1 g) = 0.415 W/kg; SAR(10 g) = 0.286 W/kg

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.443 W/kg



0 dB = 0.443 W/kg = -3.54 dBW/kg

Test Laboratory: SGS-SAR Lab

Haier i701 WCDMA1700 1412CH Left touch cheek

DUT: Haier-i701; Type: Mobile Phone ; Serial: FINJSGKN9999999

Communication System: UID 0, WCDMA (0); Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: HSL1800; Medium parameters used (interpolated): $f = 1732.4$ MHz; $\sigma = 1.328$ S/m; $\epsilon_r = 40.534$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(8.77, 8.77, 8.77); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.155 W/kg

Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm


Reference Value = 2.753 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.150 W/kg

SAR(1 g) = 0.102 W/kg; SAR(10 g) = 0.066 W/kg

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.108 W/kg



0 dB = 0.155 W/kg = -8.09 dBW/kg

Test Laboratory: SGS-SAR Lab

Haier i701 WCDMA1700 1412CH Back side 15mm

DUT: Haier-i701; Type: Mobile Phone ; Serial: FINJSGKN9999999

Communication System: UID 0, WCDMA (0); Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: MSL1750; Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.472$ S/m; $\epsilon_r = 54.659$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(8.49, 8.49, 8.49); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (9x16x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.243 W/kg


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 6.287 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.404 W/kg

SAR(1 g) = 0.245 W/kg; SAR(10 g) = 0.148 W/kg

Maximum value of SAR (measured) = 0.275 W/kg



Test Laboratory: SGS-SAR Lab

Haier i701 WCDMA1700 1412CH Bottom side 10mm

DUT: Haier-i701; Type: Mobile Phone ; Serial: FINJSGKN9999999

Communication System: UID 0, WCDMA (0); Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: MSL1750; Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.472$ S/m; $\epsilon_r = 54.659$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(8.49, 8.49, 8.49); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (9x16x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.654 W/kg


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 20.24 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 1.20 W/kg

SAR(1 g) = 0.676 W/kg; SAR(10 g) = 0.349 W/kg

Maximum value of SAR (measured) = 0.780 W/kg



0 dB = 0.654 W/kg = -1.84 dBW/kg

Test Laboratory: SGS-SAR Lab

Haier i701 WCDMA1900 9400CH Left touch cheek

DUT: Haier-i701; Type: Mobile Phone ; Serial: FINJSGKN9999999

Communication System: UID 0, WCDMA (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: HSL1900; Medium parameters used: $f = 1880$ MHz; $\sigma = 1.419$ S/m; $\epsilon_r = 40.582$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3962; ConvF(8.49, 8.49, 8.49); Calibrated: 2015-11-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn569; Calibrated: 2015-11-24
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.220 W/kg


Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 4.480 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.329 W/kg

SAR(1 g) = 0.217 W/kg; SAR(10 g) = 0.136 W/kg

Maximum value of SAR (measured) = 0.234 W/kg



0 dB = 0.220 W/kg = -6.57 dBW/kg