

1

2

3

4

5

6

7

8

A

B

C

D

80mm

110mm

2.4G Wireless Mouse



User Manual

Thank you for choosing this wireless office mouse. Please read user manual carefully when using this product.

► Contents:

- Wireless office mouseX1
- User manualX1
- USB nano receiverX1
- AA battery(Optional)X1

► Button Function:

1. Left click	6. Backward
2. Right click	7. ON/OFF switch
3. Scroll wheel	8. AA battery
4. DPI cycle	9. USB nano receiver
5. Forward	

①

②

③

④

⑤

⑥

⑦

⑧

⑨

1

► Features

- Vertical shape
- With RGB light
- For home user and business office

► Installation

Plug the USB nano receiver to the USB port in the computer, after detecting successfully it will work normally.

RGB LED Light

Press the forward key and backward key at the same time for 3s to turn on or turn off the RGB light.

► Specification

DPI	1000/1200/1600
Polling rate	150Hz
Working voltage	1.5V
Working current	≤32mA
Compatible system	Windows 8/10/mac OS

► Receiver Connection

Equipping the mouse with battery, insert the nano receiver to the USB port of your computer, pushing the ON button on the bottom of the mouse, and the receiver will detect the device automatically, plug and play.

2

► Rebuilding up the Connection between Mouse and Receiver

If your mouse cannot work normally, you can try to build up the connection again between mouse and receiver, as following steps:

- Take out the nano receiver from computer and insert again, it will detect automatically for about 15 seconds.
- Keep the mouse in ON mode and with battery in correct direction.
- Keep the effective distance within 10CM between the mouse and receiver
- Press the left button and right button at the same time for about 1-3 seconds, then release it. The connection is being built for about 10 seconds.
- If you cannot build up the connection in 10 seconds, please repeat the above steps.

► Debugging Tips

- Check the receiver if it s connected to the USB port.
- Check the ON/OFF button if in ON mode.
- Check the effective distance between mouse and the receiver, and shorten it.
- Rebuild up the connection between the mouse and receiver.

FC

CE







3

设计说明:

1、尺寸: 80x110mm(公差+/-1mm)

2、材质: 157g双面铜版纸

3、颜色: CMYK

4、表面处理: 过哑油

5、装订方式: 风琴折页 (双面印刷)

分 发

☐研发部

☒产品部

☒资材部

☒品保部

☒生产部


☒工程部

☒海外营销部


☐国内营销部

☒文控中心

批 准




审 核



DELUX 多彩

深圳市多彩实业有限公司
SHENZHEN DELUX INDUSTRY CO., LTD.



名 称

M618C海外2.4G版说明书

料 号

R3.4.M618C06001A

设 计

李世彬/190823

1

2

3

4

5

6

7

8

FCC Caution:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.