

**SK TECH CO., LTD.**

Page 1 of 17

Certificate of Compliance

Test Report No.:	SKTFCE-040825-078		
NVLAP CODE :	200220-0		
Applicant:	Deca System & Consulting Inc.		
Applicant Address:	Korea Business Center 1310, 1338-21 Seocho-dong, Seocho-gu, Seoul 137-070 Korea		
Manufacturer:	Deca System & Consulting Inc.		
Manufacturer Address:	Korea Business Center 1310, 1338-21 Seocho-dong, Seocho-gu, Seoul 137-070 Korea		
Product:	GolfBuddy		
FCC ID:	SGYDSC-GB100K	Model No.:	DSC-GB100K
Buyer Model/ Multi Model No:	N/A		
Receipt No.:	SKTEU04-0393	Date of receipt:	Jun. 7, 2004
Date of Issue:	Aug. 25, 2004		
Testing location:	SK TECH CO., LTD. 820-2, Wolmoon-Ri, Wabu-Up, Namyangju-Si, Kyunggi-Do, Korea		
Test Standards:	ANSI C63.4 / 2001		
Rule Parts:	FCC part 15 Subpart B		
Equipment Class :	Class B Digital Device Peripheral		
※ This device has shown compliance with the conducted emissions limits in 15.107, 15.207 or 18.307 adopted under FCC 02-157(ET Docket 98-80). The device may be marketed after July 11, 2005, and is not affected by the 15.37(j) or 18.123 transition provisions.			
Test Result:	The above mentioned product has been tested and passed.		
Tested by: H.P.Kim / Engineer  _____ Signature Date		Approved by: C.H.Jeong / Manager & Chief Engineer  _____ Signature Date	
Other Aspects :			
Abbreviations :	· OK, Pass = passed · Fail = failed · N/A = not applicable		
☛ •This test report is not permitted to copy partly without our permission. •This test result is dependent on only equipment to be used. •This test result is based on a single evaluation of one sample of the above mentioned. •This test report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S Government. • We certify that this test report has been based on the measurement standards that is traceable to the national or International standards.			
 NVLAP Lab. Code: 200220-0			



» » Contents « «

Contents	2
List of Tables	2
List of Figures	2
1. General	3
2. Test Site	3
2.1 Location	3
2.2 List of Test and Measurement Instruments	4
2.3 Test Date	4
2.4 Test Environment	4
3. Description of the tested samples	5
3.1 Rating and Physical Characteristics	5
3.2 Submitted Documents	5
4. Measurement Conditions	6
4.1 Modes of Operation	6
4.2 List of Peripherals	6
4.3 Type of Used cables	7
4.4 Test Setup	7
4.5 Uncertainty	8
5. EMISSION Test	11
5.1 Conducted Emissions	11
5.2 Radiated Emissions	16

» List of Supplements

Supplement 1	Spectral Diagram, LINE-PE	12
Supplement 2	Test Data, LINE – PE	13
Supplement 3	Spectral Diagram, Neutral-PE	14
Supplement 4	Test Data, Neutral – PE	15

» List of Tables

Table 1	List of test and measurement Equipment	4
Table 2	Test Data, Radiated Emissions	17



1. General

This equipment has been shown to be capable of compliance with the applicable technical standards and was tested in accordance with the measurement procedures as indicated in this report.

We attest to the accuracy of data. All measurements reported herein were performed by SK Tech Co., Ltd. and were made under Chief Engineer's supervision.

We assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

2. Test Site

SK TECH Co., Ltd.

2.1 Location

820-2, Wolmoon Ri, Wabu-Up, Namyangju-Si, Kyunggi-Do, Korea

The test site is in compliance with ISO/IEC 17025 for general requirements for the competence of testing and calibration laboratories.

This laboratory is accredited by NVLAP for NVLAP Lab. Code : 200220-0 and DATech for DAR-Registration No.:DAT-P-076/97-01



2.2 List of Test and Measurement Instruments

Table 1 : List of Test and Measurement Equipment

- **Conducted Disturbance**

Kind of Equipment	Type	S/N	Calibrated until
EMI Receiver	ESHS10	862970/019	10.2004
Artificial Mains Network	ESH2-Z5	834549/011	08.2005
EMI Receiver	ESHS10	835871/002	10.2004
Artificial Mains Network	ESH3-Z5	836679/018	08.2005

- **Radiated Disturbance**

Kind of Equipment	Type	S/N	Calibrated until
EMI Receiver	ESVS 10	825120/013	10.2004
EMI Receiver	ESVS 10	834468/008	10.2004
Spectrum Analyzer	R3361A	11730187	10.2004
Amplifier	8447F	3113A05153	08.2005
Log Periodic Antenna	UHALP9107	1819	10.2004
Biconical Antenna	BBA9106	91031626	10.2004
Open Site Cable	N/A	N/A	N/A
Antenna Turntable Driver	5907	N/A	N/A
Antenna Turntable controller	5906	N/A	N/A
Amp & Receiver connection cable	N/A	N/A	N/A
Amp & Spectrum connection cable	N/A	N/A	N/A
50Ω Switcher	MP59B	6100214538	N/A

2.3 Test Date

Date of Application : Jun. 7, 2004

Date of Test : Jul. 8, 2004 ~ Jul. 10, 2004

2.4 Test Environment

See each test item's description.



3. Description of the tested samples

The EUT is the GolfBuddy.

(GolfBuddy is the world's simplest, most powerful rangefinder created especially for golfers. Regardless your handicap, GolfBuddy can elevate your game by providing better information about the golf courses throughout the world. GolfBuddy automatically provides distances to critical targets on a hole from wherever you are on the course whether you can see them or not. Once you start using GolfBuddy, you won't want to play golf without it again. Ultimate in simplicity, yet powerful, you will enjoy easy access to professional information right in the palm of your hand.)

3.1 Rating and Physical Characteristics

Dimension(mm)	53(w) X 82(l) X 26(d)
Weight	85g
Display	LCD(128X64)
PC interface	Serial
GPS Channel	8
Error range	1~5 m
Course	30EA(bases on 18 holes)
Working Temp	0~40 C
Battery	AAA size X 2

3.2 Submitted Documents

N/A



4. Measurement Conditions

The operating voltage of EUT(DC 3V) is supplied by the battery.

(The battery Input Voltage : 1.5V(AAA size) X 2)

4.1 Modes of Operation

The EUT was in the following operation mode during all testing;

The EUT is connected to Desktop PC.

The test was made on the mode of downloading file

4.2 List of Peripherals

Description	Manufacturer	Model Name	Serial No.	FCC ID
GolfBuddy (EUT)	Deca System & Consulting Inc..	DSC-GB100K	N/A	-
Desktop PC	LG	W8S	203KI00552	-
Keyboard	Jing Mold Enterprise Co., Ltd.	LKB-0107	20103196	-
Mouse	LG	LMULBGS01I	04CU000254	-
Printer	EPSON PRICISION INC.	EPSON STYLUS PHOTO 830	ELTK014633	-
LCD Monitor	LG.	1510TFT Rev B	304KG04896	-




4.3 Type of Used Cables

Description	Length	Type of shield	Manufacturer	Remark
RS232C Cable	1.0m	Non-Shield	None	For EUT
VGA Cable	1.2m	Shield	None	For LCD Monitor
PS/2 cable	1.0m	Non-Shield	None	For Keyboard
USB cable	1.2m	Non-Shield	None	For Mouse
Parallel cable	1.2m	Shield	None	For Printer
Power cable X 3	1.2m	Non-Shield	None	For Desktop PC For Printer For LCD Monitor

4.4 Test Setup

The test setup photographs showed the external supply connections and interfaces.





4.5 Uncertainty

1) Radiated disturbance

- ⊙ Horizontally polarized radiated disturbances from 30MHz to 1000MHz at a distance of 3m

Input quantity	Uncertainty of Xi		U(Xi) dB	Ci	Ciu(xi)	CISPR 16-4
	dB	Probability distribution function				
1) Receiver reading	±0.1	K =1	0.1	1	0.1	0.10
2) Attenuation: antenna-receiver	±0.18	K=2	0.09	1	0.09	0.05
3) Antenna factor	±1.5	K=2	0.75	1	0.75	1.00
RECEIVER CORRECTIONS:						
4) Sine wave voltage	±0.56	K=2	0.28	1	0.50	0.50
5) Pulse amplitude response	±1.5	Rectangular (√3)	0.87	1	0.87	0.87
6) Pulse repetition rate response	±1.5	Rectangular (√3)	0.87	1	0.87	0.87
7) Noise floor proximity	±0.5	K=2	0.25	1	0.25	0.25
8) AF frequency interpolation	±0.3	Rectangular (√3)	0.17	1	0.17	0.17
9) Balance	±0.3	Rectangular (√3)	0.17	1	0.17	0.53
10) AF height deviations	±0.5	Rectangular (√3)	0.29	1	0.29	0.29
11) Phase center location	±0.3	Rectangular (√3)	0.17	1	0.17	0.17
12) Directive difference	+1.0	Rectangular (√3)	0.29	1	0.29	0.29
13) Cross polarization	±0.9	Rectangular (√3)	0.52	1	0.52	0.52
14) Site corrections	±2.6	Rectangular (√3)	1.5	1	1.5	1.63
15) Mismatch (ant-receiver)	±1.06	U-shaped (√2)	0.75	1	0.75	0.67

Combined Uncertainty

$$U_c(x_i) = \sqrt{(1)^2 + (2)^2 + (3)^2 + (4)^2 + (5)^2 + (6)^2 + (7)^2 + (8)^2 + (9)^2 + (10)^2 + (11)^2 + (12)^2 + (13)^2 + (14)^2 + (15)^2} = 2.37$$

Expanded Uncertainty

$$U = k \cdot U_c(x_i) = 2 \cdot 2.37 = 4.74 \text{ dB} \quad (\text{The coverage factor } k=2 \text{ yields approximately a 95\% level of confidence})$$



② Vertically polarized radiated disturbances from 30MHz to 1000MHz at a distance of 3m

Input quantity	Uncertainty of Xi		U(Xi) dB	Ci	Ciu(xi)	CISPR 16-4
	dB	Probability distribution function				
1) Receiver reading	±0.1	K =1	0.1	1	0.1	0.10
2) Attenuation: antenna-receiver	±0.18	K=2	0.09	1	0.09	0.05
3) Antenna factor	±1.5	K=2	0.75	1	0.75	1.00
RECEIVER CORRECTIONS:						
4) Sine wave voltage	±0.56	K=2	0.28	1	0.50	0.50
5) Pulse amplitude response	±1.5	Rectangular (√3)	0.87	1	0.87	0.87
6) Pulse repetition rate response	±1.5	Rectangular (√3)	0.87	1	0.87	0.87
7) Noise floor proximity	±0.5	K=2	0.25	1	0.25	0.25
8) AF frequency interpolation	±0.3	Rectangular (√3)	0.17	1	0.17	0.17
9) Balance	±0.9	Rectangular (√3)	0.52	1	0.52	0.52
10) AF height deviations	±0.3	Rectangular (√3)	0.17	1	0.17	0.17
11) phase center location	±0.3	Rectangular (√3)	0.17	1	0.17	0.17
12) directive difference	+1.0	Rectangular (√3)	0.29	1	0.29	0.29
13) cross polarization	±0.9	Rectangular (√3)	0.52	1	0.52	0.52
14) site corrections	±2.6	Rectangular (√3)	1.5	1	1.5	1.63
15) Mismatch (ant-receiver)	±1.06	U-shaped (√2)	0.75	1	0.75	0.67

Combined Uncertainty

$$U_c(x_i) = \sqrt{(1)^2 + (2)^2 + (3)^2 + (4)^2 + (5)^2 + (6)^2 + (7)^2 + (8)^2 + (9)^2 + (10)^2 + (11)^2 + (12)^2 + (13)^2 + (14)^2 + (15)^2} = 2.43$$

Expanded Uncertainty

$$U = k \cdot U_c(x_i) = 2 \cdot 2.43 = 4.86 \text{ dB}$$

(The coverage factor k =2 yields approximately a 95% level of confidence)

**2) Conducted disturbance**

⊙ **Conducted disturbance from 150KHz to 30MHz using a 50Ω/50uH AMN**

input quantity	Uncertainty of Xi		U(Xi) dB	Ci	Ciu(xi)	CISPR 16-4
	dB	Probability distribution function				
1) Receiver Readeing	±0.1	K =1	0.1	1	0.1	0.10
2) Attenuation:AMN-receiver	±0.36	Triangular (√6)	0.15	1	0.15	0.05
RECEIVER CORRECTIONS:						
3) Sine wave voltage	±0.5	K=2	0.25	1	0.25	0.50
4) Pulse amplitude response	±1.5	Rectangular (√3)	0.87	1	0.87	0.87
5) Pulse repetition rate response	±1.5	Rectangular (√3)	0.87	1	0.87	0.87
6) AMN voltage division factor	±0.07	K=2	0.04	1	0.04	0.1
7) Mismatch : AMN-receiver	±0.55	U-shaped (√2)	0.39	1	0.39	0.53
8) AMN impedance	±1.52	Triangular (√6)	0.62	1	0.62	1.08

- 1)~8) For numbered comments, refer to following articles

Combined Uncertainty

$$U_c(x_i) = \sqrt{(1)^2 + (2)^2 + (3)^2 + (4)^2 + (5)^2 + (6)^2 + (7)^2 + (8)^2} = \mathbf{1.47}$$

Expanded uncertainty

$$U = k \cdot U_c(x_i) = 2 * 1.47 = \mathbf{2.94dB}$$

The coverage factor k =2 yields approximately a 95% level of confidence

⊙ **Refer**

- 1) receiver's resolution capacity
- 2) refer to the sub clause 11. of a calibration report
- 3) quoted from CISPR 16-4
- 4) refer to a calibration report
- 5) refer to CISPR 16-4 article 5. 7)
- 6) refer to a calibration report and a measured AMN impedance data



5. EMISSION Test

5. Test Results

5.1 Conducted Emissions

Result

PASS

The line-conducted facility is located inside a 2.0M x 3.6M x 7.2M shielded enclosure.

The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 604-05.

A 1m x 1.5m wooden table 80cm. high is placed 40cm. away from the vertical wall and 1.5m away

from the side wall of the shielded room. ROHDE & SCHWARZ Model ESH3-Z5 (10kHz-30MHz)

50ohm/50 uH Line-Impedance Stabilization Networks(LISNs) are bonded to the shielded room.

The EUT is powered from the ROHDE & SCHWARZ LISN and the support equipment is

powered from the ROHDE & SCHWARZ LISN. Power to the LISNs are filtered by a high-current high-insertion loss Lindgren enclosures power line filters (100dB 14kHz-10GHz).

The purpose of the filter is to attenuate ambient signal interference and this filter is also bonded to the shielded enclosure.

All electrical cables are shielded by braided tinned copper zipper tubing with inner diameter of 1/2".

If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the ROHDE & SCHWARZ LISN.

All interconnecting cables more than 1 meter were shortened by non-inductive bundling (serpentine fashion) to a 1-meter length.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT.

The spectrum was scanned from 150kHz to 30MHz with 100msec. sweep time.

The frequency producing the maximum level was reexamined using EMI/field Intensity Meter (ESHS 10) and Quasi-Peak adapter. The detector function was set to CISPR quasi-peak mode.

The bandwidth of the receiver was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission.

Each emission was maximized by: switching power lines; varying the mode of operation or resolution; clock or data exchange speed; if applicable; whichever determined the worst-case emission.

Photographs of the worst-case emission can be seen in photograph of conducted test.

Each EME reported was calibrated using self-calibrating mode.

✧ *Supplementing the conduction graphs and data to next 4 pages.*



Supplement 1 : Spectral Diagram, LINE – PE


CONDUCTED DISTURBANCE

EUT: DSC-GB100K
Manuf:
Op Cond:
Operator:
Test Spec:
Comment: LINE-PE

Result File: fcc1.dat : GolfBuddy

Scan Settings			Receiver Settings		
(1 Range)					
Start	Frequencies	Step	IF BW	Detector	M-Time
150kHz	Stop	10kHz	10kHz	PK	100msec
	30MHz				Atten
					Auto
					Preamp
					OFF
					OpRge
					60dB

Final Measurement: Detector: X QP
Meas Time: 1sec
Peaks: 8
Acc Margin: 35 dB



**SK TECH CO., LTD.**

Page 13 of 17

Supplement 2 : Test Data, LINE – PE**CONDUCTED DISTURBANCE**

EUT: DSC-GB100K

Manuf:

Op Cond:

Operator:

Test Spec:

Comment: LINE-PE

Result File: fcc1.dat : GolfBuddy

Scan Settings (1 Range)

Frequencies		Step	IF BW	Detector	Receiver Settings			
Start	Stop				M-Time	Atten	Preamp	OpRge
150kHz	30MHz	10kHz	10kHz	PK	100msec	Auto	OFF	60dB

Final Measurement: Detector: X QP
 Meas Time: 1sec
 Peaks: 8
 Acc Margin: 35 dB

Final Measurement Results

Frequency MHz	QP Level dBμV	QP Limit dBμV	QP Delta dB
0.15	42.27	66.00	23.73
0.19	34.16	64.04	29.88
0.23	36.45	62.45	26.00
0.27	32.97	61.12	28.15
0.29	34.00	60.52	26.52
0.39	37.73	58.06	20.33
0.88	38.68	56.00	17.32
1.34	35.20	56.00	20.80
1.95	38.70	56.00	17.30
2.73	39.06	56.00	16.94
2.83	39.31	56.00	16.69
3.12	36.07	56.00	19.93
5.17	36.01	60.00	23.99
5.27	34.68	60.00	25.32
5.95	34.40	60.00	25.60
6.05	34.63	60.00	25.37
7.32	32.36	60.00	27.64
19.75	27.16	60.00	32.84

* limit exceeded




Supplement 3 : Spectral Diagram, Neutral – PE

CONDUCTED DISTURBANCE

EUT: DSC-GB100K
Manuf:
Op Cond:
Operator:
Test Spec:
Comment: NEUTRAL-PE
Result File: fcc N.dat : GolfBuddy

Scan Settings			(1 Range)			Receiver Settings			
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge	
150kHz	30MHz	10kHz	10kHz	PK	100msec	Auto	OFF	60dB	
Final Measurement:			Detector:	X QP					
			Meas Time:	1sec					
			Peaks:	8					
			Acc Margin:	35 dB					



**SK TECH CO., LTD.**

Page 15 of 17

Supplement 4 : Test Data, Neutral – PE**CONDUCTED DISTURBANCE**

EUT: DSC-GB100K

Manuf:

Op Cond:

Operator:

Test Spec:

Comment: NEUTRAL-PE

Result File: fcc N.dat : GolfBuddy

Scan Settings (1 Range)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
150kHz	30MHz	10kHz	10kHz	PK	100msec	Auto	OFF	60dB

Final Measurement: Detector: X QP
 Meas Time: 1sec
 Peaks: 8
 Acc Margin: 35 dB

Final Measurement Results

Frequency MHz	QP Level dBμV	QP Limit dBμV	QP Delta dB
0.15	43.01	66.00	22.99
0.19	33.18	64.04	30.86
0.23	37.00	62.45	25.45
0.27	34.67	61.12	26.45
0.39	36.79	58.06	21.27
0.42	35.79	57.45	21.66
0.88	38.86	56.00	17.14
1.11	37.95	56.00	18.05
1.27	34.75	56.00	21.25
1.46	37.03	56.00	18.97
2.73	38.56	56.00	17.44
2.83	39.07	56.00	16.93
2.93	37.20	56.00	18.80
3.03	34.79	56.00	21.21
5.17	35.46	60.00	24.54
16.53	25.80	60.00	34.20
20.01	28.40	60.00	31.60

* limit exceeded



5.2 Radiated Emissions

Result :**PASS**

Preliminary measurements were made indoors at 3 meter using broadband antennas, broadband amplifier, and spectrum analyzer to determine the frequency producing the maximum EME.

Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, turntable azimuth with respect to the antenna were noted for each frequency found.

The spectrum was scanned from 30 to 300 MHz using biconical antenna and from 300 to 1000 MHz using log-periodic antenna. Above 1GHz, linearly polarized double ridge horn antennas were used.

Final measurements were made outdoors at 3-meter test range using SCHWARZBECK dipole antennas.

The test equipment was placed on a wooden table situated on a 4x4 meter area adjacent to the measurement area. Turntable was to protect from weather in the dome that made with FRP.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined and investigated using EMI/Field Intensity Meter(ESVS 10) and Quasi-Peak Adapter.

The detector function was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 100kHz or 1MHz depending on the frequency or type of signal.

The half-wave dipole antenna was tuned to the frequency found during preliminary radiated measurements. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8-meter high non-metallic 1 x 1.5 meter table.

The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each EME emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission.

Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed, and/or support equipment, if applicable; and changing the polarity of the antenna, whichever determined the worst-case emission.

Photographs of the worst-case emission can be seen in photograph of radiated emission test.

Each EME reported was calibrated using self-calibrating mode.

**Table 2 : Test Data, Radiated Emissions**

Frequency [MHz]	Pol.	Height [m]	Real Reading	Correction Factor		T-Fact [dB]	Data [dBuV/m]	Limits [dBuV/m]	Margin [dB]
				Antenna	Cable				
94.28	H	4.0	20.1	9.1	1.3	10.4	30.5	43.5	13.0
112.05	H	4.0	15.1	11.8	1.5	13.3	28.4	43.5	15.1
243.41	H	3.8	17.6	17.4	2.6	20.0	37.6	46.0	8.4
400.20	H	4.0	16.2	18.3	3.8	22.1	38.3	46.0	7.7

Table2. Radiated Measurements at 3-meters

NOTES:

1. All modes of operation were investigated
and the worst-case emission are reported.
2. All other emission are non-significant.
3. All readings are calibrated by self-mode in receiver.
4. Measurements using CISPR quasi-peak mode.
5. H = Horizontal, V = Vertical Polarization
6. DATA = Real Reading + T-FACTOR(=Antenna + Cable)
7. Margin = Limit - DATA