



FCC LISTED, REGISTRATION
NUMBER: 2764.01

ISED LISTED REGISTRATION
NUMBER: 23595-1

Test report No:
3007ERM.002A1

Test report

USA FCC Part 15.247, 15.209, 15.207
CANADA RSS-247, RSS-Gen

Radio Frequency Devices. Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and
5725 - 5850 MHz

Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and License-
Exempt Local Area Network (LE-LAN) Devices.

(*) Identification of item tested	Bluetooth LE device for data gathering as it relates to sports activities.
(*) Trademark	UA
(*) Model and /or type reference tested	UAFP3
Other identification of the product	--
(*) Features	Bluetooth LE
Manufacturer	Under Armour 211 Walter Seaholm Dr, Suite 200 Austin, TX 78701, USA.
Test method requested, standard	USA FCC Part 15.247, 10-1-20 Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz USA FCC Part 15.209, 10-1-20 Edition: Radiated emission limits; general requirements CANADA RSS-247 Issue 2 (February 2017). CANADA RSS-Gen Issue 5 (March 2019). 558074 D01 15.247 Meas. Guidance v05r02 (April 2019): Guidance for Compliance Measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating Under section §15.247 of the FCC Rules ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Domingo Galvez EMC&RF Lab Manager 
Date of issue	11-29-2021
Report template No	FDT08_23 (*) "Data provided by the client"

Digitally signed by Domingo Galvez
DN: cn=Domingo Galvez, o=DEKRA
Certification Inc., ou=Regulatory Lab,
email=dgalvez@dekra.com, c=US
Date: 2021.11.30 17:49:00 -05'00'

Index

Competences and guarantees.....3

General conditions.....3

Uncertainty3

Data provided by the client4

Usage of samples.....4

Test sample description.....5

Identification of the client6

Testing period and place6

Document history6

Modifications to the reference test report.....7

Environmental conditions.....7

Remarks and comments.....8

Testing verdicts8

Summary8

List of equipment used during the test9

Appendix A: Test results (Bluetooth Low Energy)10

Competences and guarantees

DEKRA Certification Inc. is a testing laboratory accredited by A2LA (The American Association for Laboratory Accreditation), to perform the tests indicated in the Certificate 2764.01

DEKRA Certification Inc. is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA Certification Inc. has a calibration and maintenance program for its measurement equipment.

DEKRA Certification Inc. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Certification at the time of performance of the test.

DEKRA Certification Inc. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Certification Inc.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Certification Inc.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Certification Inc. and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the DEKRA Certification internal document PODT000.

Test case	Frequency (MHz)	U(k=2)	Units
RF Power and PSD	2402-2483	0.88	dB
Occupied Bandwidth		1.87	%
Band Edge		0.64	dB
Radiated Spurious Emission	30-180	4.27	dB
	180-1000	3.14	dB
	1000-18000	3.30	dB
	18000-40000	3.49	dB

Data provided by the client

Data gathering (Accelerometer) device intended for wearable products.

DEKRA declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

Usage of samples

Samples undergoing test have been selected by: The client.

Sample S/01 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
3007/03	Conducted sample	Titan	MLCD010DB0V4K	08/10/2021

Following Auxiliary items were used with Sample S/01 to perform testing:

Control N°	Description	Model	Serial N°
Dekra 6	iPhone 8	MQ6V2LL/A	356396101339598

1. Sample S/01 has undergone following test(s)
All Conducted tests indicated in appendix A.

Sample S/02 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
3007/05	Radiated sample	280721	A22199	08/10/2021

Following Auxiliary items were used with Sample S/01 to perform testing:

Control N°	Description	Model	Serial N°
Dekra 6	iPhone 8	MQ6V2LL/A	356396101339598

1. Sample S/02 has undergone following test(s)
All Radiated tests indicated in appendix A.

Test sample description

Ports..... :	Port name and description	Cable					
		Specified length [m]	Attached during test	Shielded			
			☐	☐			
			☐	☐			
Supplementary information to the ports..... :	No Data Provided						
Rated power supply..... :	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	☐	AC:	☐	☐	☐	☐	☐
	☐	AC:	☐	☐	☐	☐	☐
	☒	DC: 3.0 V					
	☐	DC:					
Rated Power..... :	0.05W						
Clock frequencies..... :	38.5MHz						
Other parameters..... :	No Data Provided						
Software version..... :	0.15						
Hardware version..... :	Rev B2						
Dimensions in mm (W x H x D):	23.3mm x 35.1mm x 5.5mm						
Mounting position..... :	☐	Tabletop equipment					
	☐	Wall/Ceiling mounted equipment					
	☐	Floor standing equipment					
	☐	Hand-held equipment					
	☐	Other:					
Modules/parts..... :	Module/parts of test item	Type			Manufacturer		
	No Data Provided						
Accessories (not part of the test item)..... :	Description	Type			Manufacturer		
	No Data Provided						

Documents as provided by the applicant	Description	File name	Issue date
	Declaration Equipment Data	FDT30_18 Declaration Equipment Data_rev2	08/26/2021
Copy of marking plate:			
			

Identification of the client

Under Armour
211 Walter Seaholm Dr, Suite 200
Austin, TX 78701, USA.

Testing period and place

Test Location	DEKRA Certification Inc.
Date (start)	08-16-2021
Date (finish)	08-25-2021

Document history

Report number	Date	Description
3007ERM.002	09-29-2021	First release
3007ERM.002A1	11-29-2021	Second release

Modifications to the reference test report

It was introduced the following modification in respect to the test report number 3007ERM.002 related with the same samples:

Clauses/ Sub-Clauses	Modification	Justification
Page 12: Product Information / Table	Antenna gain value is updated	Typo Error

This modification test report cancels and replaces the test report 3007ERM.002.

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 30 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

In the semianechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 30 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

In the chamber for conducted measurements, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 30 % Max. = 60 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

Remarks and comments

The tests have been performed by the technical personnel: Sravani Gollamudi, Nasir Khan, Lourdes Maria Valverde and Koji Nishimoto.

Testing verdicts

Not applicable :	N/A
Pass :	P
Fail :	F
Not measured :	N/M

Summary

FCC PART 15 PARAGRAPH (Bluetooth LE)					
Section	FCC Spec Clause	RSS Spec Clause	Test Description	Verdict	Remark
A.1	§ 2.1049	RSS-GEN 6.7	99% Occupied Bandwidth	P	N/A
A.2	§15.247 (a) (2)	RSS-247 5.2 (a)	6dB Bandwidth	P	N/A
A.3	§ 15.247 (b)	RSS-247 5.4 (d)	Maximum Output Power and antenna gain	P	N/A
A.4	§ 15.247 (d)	RSS-247 5.5	Band-edge conducted emissions compliance (Transmitter)	P	N/A
A.5	§ 15.247 (e)	RSS-247 5.2 (b)	Power Spectral Density	P	N/A
-	§15.247(d)	RSS-247 5.5	Emission limitations Conducted (Transmitter)	N/A	Refer 1
A.6	§15.247 (d)	RSS-247 5.5	Emission limitations Radiated (Transmitter)	P	N/A
<u>Supplementary information and remarks:</u> 1. DUT has integral antenna.					

List of equipment used during the test

Conducted Measurements

CONTROL NUMBER	DESCRIPTION	MANUFACTURER	MODEL	LAST CALIBRATION	NEXT CALIBRATION
1038	TS8997 TEST SYSTEM	Rohde & Schwarz	TS8997	N/A	N/A
1107	ETHERNET SNMP THERMOMETER	HW GROUP	HWg-STE Plain	2020/08	2022/08
1313	WIRELESS MEASUREMENT SOFTWARE R&S WMS32	Rohde & Schwarz	N/A	N/A	N/A

Radiated Measurements

CONTROL NUMBER	DESCRIPTION	MANUFACTURER	MODEL	LAST CALIBRATION	NEXT CALIBRATION
0981	RF pre-amplifier	Bonn Elektronik	BLMA0118-2A	2020/11	2022/11
1012	EMI TEST RECEIVER	Rohde & Schwarz	ESR 26	2019/12	2021/12
1014	Spectrum analyzer	Rohde & Schwarz	FSV40	2021/05	2023/05
1056	Double-ridge Waveguide Horn antenna 18-40 GHz	ETS LINDGREN	3116C	2020/01	2023/01
1057	Double-ridge Waveguide Horn antenna 1-18 GHz	ETS LINDGREN	3115	2020/06	2023/06
1065	Biconical Log antenna	ETS LINDGREN	3142E	2020/08	2023/08
1111	ETHERNET SNMP THERMOMETER	HW GROUP	HWg-STE Plain	2020/08	2022/08
1179	Semi anechoic Absorber Lined Chamber	Frankonia	SAC 3 plus "L"	N/A	N/A
1314	WIRELESS MEASUREMENT SOFTWARE R&S EMC32	Rohde & Schwarz	N/A	N/A	N/A

Appendix A: Test results (Bluetooth Low Energy)

Appendix A Content

PRODUCT INFORMATION 12

DESCRIPTION OF TEST CONDITIONS 13

TEST A.1: 99% OCCUPIED BANDWIDTH 14

TEST A.2: 6DB BANDWIDTH 19

TEST A.3: MAXIMUM PEAK CONDUCTED OUTPUT POWER AND ANTENNA GAIN 24

TEST A.4: BAND-EDGE EMISSIONS COMPLIANCE (TRANSMITTER) 29

TEST A.5: POWER SPECTRAL DENSITY 34

TEST A.6: EMISSION LIMITATIONS RADIATED (TRANSMITTER) 39

PRODUCT INFORMATION

The following information is provided by the client

Information	Description
Modulation	GFSK
Adaptive	Non-adaptive equipment
Operation mode	
- Operating Frequency Range	2402 – 2480 MHz
- Nominal Channel Bandwidth	2 MHz
- RF Output Power	6 dBm
Extreme operating conditions	
- Temperature range	0 °C to 70 °C
Antenna type	Integrated Antenna
Antenna gain	+ 1.5 dBi
Nominal Voltage	
- Supply Voltage	3.0 V nominal
- Type of power source	DC Power supply
Equipment type	Bluetooth Low Energy
Geo-location capability	No

DESCRIPTION OF TEST CONDITIONS

TEST CONDITIONS	DESCRIPTION
TC#01 (1 Mbps)	<u>Power supply (V):</u> $V_{\text{nominal}} = 3.0 \text{ V dc}$ Data Rate: 1 Mbps Bandwidth: 1 MHz <u>Test Frequencies for Conducted/ Radiated tests:</u> Lowest channel: 2402 MHz Middle channel: 2440 MHz Highest channel: 2480 MHz
TC#02 (2 Mbps)	<u>Power supply (V):</u> $V_{\text{nominal}} = 3.0 \text{ V dc}$ Data Rate: 2 Mbps Bandwidth: 2 MHz <u>Test Frequencies for Conducted/ Radiated tests:</u> Lowest channel: 2402 MHz Middle channel: 2440 MHz Highest channel: 2480 MHz


TEST A.1: 99% OCCUPIED BANDWIDTH

LIMITS:	Product standard:	§ 2.1049 and RSS-Gen
	Test standard:	§ 2.1049 and RSS-Gen 6.7

LIMITS

The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs

TEST SETUP




TESTED SAMPLES:	S/01
TESTED CONDITIONS MODES:	TC#01 (1 Mbps)
TEST RESULTS:	PASS


	Lowest frequency 2402 MHz	Middle frequency 2440 MHz	Highest frequency 2480 MHz
99% bandwidth (MHz)	1.005	1.010	1.010

TEST RESULTS (Cont.):


Lowest Channel



Middle Channel



Highest Channel



TEST RESULTS (Cont.):


Measurement

Setting	Instrument Value	Instrument Value	Instrument Value
Start Frequency	2.40100 GHz	2.43925 GHz	2.47900 GHz
Stop Frequency	2.40300 GHz	2.44075 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz	2.000 MHz
RBW	10.000 kHz	10.000 kHz	10.000 kHz
VBW	30.000 kHz	30.000 kHz	30.000 kHz
Sweep Points	400	400	400
Sweep time	189.648 μs	189.648 μs	189.648 μs
Reference Level	0.000 dBm	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	20.000 dB	20.000 dB
Detector	MaxPeak	MaxPeak	MaxPeak
Sweep Count	100	100	100
Filter	3 dB	3 dB	3 dB
Trace Mode	Max Hold	Max Hold	Max Hold
Sweep type	FFT	FFT	FFT
Preamp	Off	Off	off
Stable mode	Trace	Trace	Trace
Stable value	0.30 dB	0.30 dB	0.30 dB
Run	8 / max. 150	6 / max. 150	10 / max. 150
Stable	3 / 3	3 / 3	3 / 3
Max Stable Difference	0.03 dB	0.12 dB	0.08 dB


TESTED SAMPLES:	S/01
TESTED CONDITIONS MODES:	TC#02 (2 Mbps)
TEST RESULTS:	PASS

	Lowest frequency 2402 MHz	Middle frequency 2440 MHz	Highest frequency 2480 MHz
99% bandwidth (MHz)	2.010	2.010	2.010

Lowest Channel




Middle Channel



TEST RESULTS (Cont.):

Highest Channel



Measurement

Setting	Instrument Value	Instrument Value	Instrument Value
Start Frequency	2.40000 GHz	2.43800 GHz	2.47800 GHz
Stop Frequency	2.40400 GHz	2.44200 GHz	2.48200 GHz
Span	4.000 MHz	4.000 MHz	4.000 MHz
RBW	20.000 kHz	20.000 kHz	20.000 kHz
VBW	100.000 kHz	100.000 kHz	100.000 kHz
Sweep Points	400	400	400
Sweep time	94.824 μ s	94.824 μ s	94.824 μ s
Reference Level	0.000 dBm	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	20.000 dB	20.000 dB
Detector	MaxPeak	MaxPeak	MaxPeak
Sweep Count	100	100	100
Filter	3 dB	3 dB	3 dB
Trace Mode	Max Hold	Max Hold	Max Hold
Sweep type	FFT	FFT	FFT
Preamp	Off	Off	Off
Stable mode	Trace	Trace	Trace
Stable value	0.30 dB	0.30 dB	0.30 dB
Run	6 / max. 150	7 / max. 150	7 / max. 150
Stable	3 / 3	3 / 3	3 / 3
Max Stable Difference	0.07 dB	0.17 dB	0.08 dB


TEST A.2: 6DB BANDWIDTH

LIMITS:	Product standard:	Part 15 Subpart C §15.247 and RSS-247
	Test standard:	Part 15 Subpart C §15.247(a)(2) and RSS-247 5.2(a)

LIMITS

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

TEST SETUP




TESTED SAMPLES:	S/01
TESTED CONDITIONS MODES:	TC#01 (1 Mbps)
TEST RESULTS:	PASS


	Lowest frequency	Middle frequency	Highest frequency
	2402 MHz	2440 MHz	2480 MHz
6 dB Spectrum bandwidth (kHz)	673.268	673.268	673.268

TEST RESULTS (Cont.):


Lowest Channel:



Mid Channel:



High Channel:




TEST RESULTS (Cont.):			
Measurement			
Setting	Instrument Value	Instrument Value	Instrument Value
Start Frequency	2.40100 GHz	2.43900 GHz	2.47900 GHz
Stop Frequency	2.40300 GHz	2.44100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz	2.000 MHz
RBW	100.000 kHz	100.000 kHz	100.000 kHz
VBW	300.000 kHz	300.000 kHz	300.000 kHz
Sweep Points	101	101	101
Sweep time	18.938 μ s	18.938 μ s	18.938 μ s
Reference Level	0.000 dBm	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	20.000 dB	20.000 dB
Detector	MaxPeak	MaxPeak	MaxPeak
Sweep Count	100	100	100
Filter	3 dB	3 dB	3 dB
Trace Mode	Max Hold	Max Hold	Max Hold
Sweep type	FFT	FFT	FFT
Preamp	off	Off	off
Stable mode	Trace	Trace	Trace
Stable value	0.50 dB	0.50 dB	0.50 dB
Run	10 / max. 150	8 / max. 150	11 / max. 150
Stable	5 / 5	5 / 5	5 / 5
Max Stable Difference	0.00 dB	0.21 dB	0.04 dB


TESTED SAMPLES:	S/01
TESTED CONDITIONS MODES:	TC#02 (2 Mbps)
TEST RESULTS:	PASS

	Lowest frequency 2402 MHz	Middle frequency 2440 MHz	Highest frequency 2480 MHz
6 dB Spectrum bandwidth (MHz)	1.228	1.228	1.188

Lowest Channel:




Mid Channel:



TEST RESULTS (Cont.):

High Channel:



Measurement

Setting	Instrument Value	Instrument Value	Instrument Value
Start Frequency	2.40000 GHz	2.43800 GHz	2.47800 GHz
Stop Frequency	2.40400 GHz	2.44200 GHz	2.48200 GHz
Span	4.000 MHz	4.000 MHz	4.000 MHz
RBW	100.000 kHz	100.000 kHz	100.000 kHz
VBW	300.000 kHz	300.000 kHz	300.000 kHz
Sweep Points	101	101	101
Sweep time	18.938 μ s	18.938 μ s	18.938 μ s
Reference Level	0.000 dBm	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	20.000 dB	20.000 dB
Detector	MaxPeak	MaxPeak	MaxPeak
Sweep Count	100	100	100
Filter	3 dB	3 dB	3 dB
Trace Mode	Max Hold	Max Hold	Max Hold
Sweep type	FFT	FFT	FFT
Preamp	Off	Off	Off
Stable mode	Trace	Trace	Trace
Stable value	0.50 dB	0.50 dB	0.50 dB
Run	12 / max. 150	10 / max. 150	11 / max. 150
Stable	5 / 5	5 / 5	5 / 5
Max Stable Difference	0.02 dB	0.06 dB	0.06 dB

TEST A.3: MAXIMUM PEAK CONDUCTED OUTPUT POWER AND ANTENNA GAIN

LIMITS:	Product standard:	Part 15 Subpart C §15.247 and RSS-247
	Test standard:	Part 15 Subpart C §15.247(b)(3) and RSS-247 5.4(d)

LIMITS


§15.247(b)(3) and RSS-247 5.4(d): For systems using digital modulation in the 2400-2483.5 MHz band: 1 watt (30 dBm).

RSS-247 5.4(d): The e.i.r.p. shall not exceed 4 W (36 dBm)

TEST SETUP

The maximum peak conducted output power was measured using the method according to point 9.1.1. of Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 558074 D01 DTS Meas Guidance v04 dated 05/04/2017.

The EIRP power (dBm) is calculated by adding the declared maximum antenna gain to the measured conducted power




TESTED SAMPLES:	S/01
TESTED CONDITIONS MODES:	TC#01 (1 Mbps)
TEST RESULTS:	PASS

Maximum declared antenna gain: +1.5 dBi

	Lowest frequency 2402 MHz	Middle frequency 2440 MHz	Highest frequency 2480 MHz
Maximum conducted power (dBm)	2.3	2.8	2.7
Maximum EIRP power (dBm)	3.8	4.3	4.2


The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.

Lowest Channel




— Connector 1 × Peak Connector 1

Middle Channel



— Connector 1 × Peak Connector 1




TESTED SAMPLES:	S/01
TESTED CONDITIONS MODES:	TC#02 (2 Mbps)
TEST RESULTS:	PASS

Maximum declared antenna gain: +1.5 dBi

	Lowest frequency 2402 MHz	Middle frequency 2440 MHz	Highest frequency 2480 MHz
Maximum conducted power (dBm)	3.8	2.8	2.9
Maximum EIRP power (dBm)	5.3	4.3	4.4


The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.

Lowest Channel




— Connector 1 × Peak Connector 1

Middle Channel



— Connector 1 × Peak Connector 1




TEST A.4: BAND-EDGE EMISSIONS COMPLIANCE (TRANSMITTER)

LIMITS:	Product standard:	Part 15 Subpart C §15.247 and RSS-247
	Test standard:	Part 15 Subpart C §15.247(d) and RSS-247 5.5

LIMITS

In any 100 kHz bandwidth outside the frequency band in which the digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB.

TEST SETUP




TESTED SAMPLES:	S/01
TESTED CONDITIONS MODES:	TC#01 (1 Mbps)
TEST RESULTS:	PASS

Note: Radiated measurements are used to show compliance with the limits in the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz.

TEST RESULTS (Cont.):

Lowest Channel




Measurement

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2399.875000	-48.3	30.5	-17.7	PASS
2399.625000	-48.3	30.6	-17.7	PASS
2399.825000	-48.4	30.7	-17.7	PASS
2399.925000	-48.4	30.7	-17.7	PASS
2399.575000	-48.7	30.9	-17.7	PASS
2399.675000	-48.8	31.1	-17.7	PASS
2399.525000	-49.1	31.3	-17.7	PASS
2399.775000	-49.2	31.5	-17.7	PASS
2399.725000	-49.8	32.1	-17.7	PASS
2399.475000	-49.8	32.1	-17.7	PASS
2399.975000	-50.0	32.2	-17.7	PASS
2399.375000	-50.0	32.3	-17.7	PASS
2399.425000	-50.0	32.3	-17.7	PASS
2399.225000	-51.1	33.4	-17.7	PASS
2399.325000	-51.2	33.5	-17.7	PASS

TEST RESULTS (Cont.):

Highest Channel



— Limit — Sum Level × Fail


Measurement

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2484.525000	-51.8	34.3	-17.5	PASS
2483.525000	-52.2	34.7	-17.5	PASS
2484.575000	-52.3	34.8	-17.5	PASS
2484.625000	-52.4	34.9	-17.5	PASS
2483.875000	-52.9	35.4	-17.5	PASS
2484.475000	-53.0	35.5	-17.5	PASS
2484.425000	-53.0	35.6	-17.5	PASS
2483.575000	-53.3	35.8	-17.5	PASS
2483.625000	-53.4	35.9	-17.5	PASS
2483.925000	-53.5	36.0	-17.5	PASS
2483.775000	-53.6	36.1	-17.5	PASS
2484.675000	-53.6	36.1	-17.5	PASS
2484.125000	-53.7	36.2	-17.5	PASS
2484.725000	-53.8	36.3	-17.5	PASS
2483.975000	-53.8	36.4	-17.5	PASS

TESTED SAMPLES:	S/01
TESTED CONDITIONS MODES:	TC#02 (2 Mbps)
TEST RESULTS:	PASS


Note: Radiated measurements were used to show compliance with the limits in the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz.

TEST RESULTS (Cont.):	Lowest Channel
------------------------------	-----------------------



Measurement

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2399.975000	-30.1	12.0	-18.1	PASS
2399.925000	-31.2	13.1	-18.1	PASS
2399.875000	-32.7	14.6	-18.1	PASS
2399.825000	-34.7	16.6	-18.1	PASS
2399.775000	-35.4	17.3	-18.1	PASS
2399.725000	-37.3	19.2	-18.1	PASS
2399.675000	-38.9	20.7	-18.1	PASS
2399.625000	-39.9	21.8	-18.1	PASS
2399.575000	-40.0	21.9	-18.1	PASS
2399.425000	-40.6	22.5	-18.1	PASS
2399.475000	-40.7	22.5	-18.1	PASS
2399.525000	-40.8	22.7	-18.1	PASS
2399.375000	-42.3	24.2	-18.1	PASS
2399.125000	-42.6	24.5	-18.1	PASS
2399.275000	-43.0	24.9	-18.1	PASS



TEST A.5: POWER SPECTRAL DENSITY


LIMITS:	Product standard:	Part 15 Subpart C §15.247 and RSS-247
	Test standard:	Part 15 Subpart C §15.247(e) and RSS-247 5.2 (b)

LIMITS

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST SETUP

The maximum power spectral density level in the fundamental emission was measured using the method PKPSD (Peak PSD) according to point 10.2. of Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 558074 D01 DTS Meas Guidance v04 dated 05/04/2017.




TESTED SAMPLES:	S/01
TESTED CONDITIONS MODES:	TC#01(1 Mbps)
TEST RESULTS:	PASS


	Lowest frequency	Middle frequency	Highest frequency
	2402 MHz	2440 MHz	2480 MHz
Power spectral density (dBm)	-7.395	-6.865	-7.046

TEST RESULTS (Cont.):


Lowest Channel:



Mid Channel:



High Channel:




TEST RESULTS (Cont.):

Measurement			
Setting	Instrument Value	Instrument Value	Instrument Value
Start Frequency	2.40125 GHz	2.43925 GHz	2.47925 GHz
Stop Frequency	2.40275 GHz	2.44075 GHz	2.48075 GHz
Span	1.500 MHz	1.500 MHz	1.500 MHz
RBW	10.000 kHz	10.000 kHz	10.000 kHz
VBW	30.000 kHz	30.000 kHz	30.000 kHz
Sweep Points	300	300	300
Sweep time	1.500 ms	1.500 ms	1.500 ms
Reference Level	0.000 dBm	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	20.000 dB	20.000 dB
Detector	MaxPeak	MaxPeak	MaxPeak
Sweep Count	100	100	100
Filter	3 dB	3 dB	3 dB
Trace Mode	Max Hold	Max Hold	Max Hold
Sweep type	Sweep	Sweep	Sweep
Preamp	off	Off	off
Stable mode	Trace	Trace	Trace
Stable value	0.50 dB	0.50 dB	0.50 dB
Run	5 / max. 150	6 / max. 150	6 / max. 150
Stable	2 / 2	2 / 2	2 / 2
Max Stable Difference	0.20 dB	0.32 dB	0.07 dB


TESTED SAMPLES:	S/01
TESTED CONDITIONS MODES:	TC#02(2 Mbps)
TEST RESULTS:	PASS

	Lowest frequency 2402 MHz	Middle frequency 2440 MHz	Highest frequency 2480 MHz
Power spectral density (dBm)	-10.203	-9.664	-9.787

Lowest Channel:




Mid Channel:



TEST RESULTS (Cont.):

High Channel:



Measurement

Setting	Instrument Value	Instrument Value	Instrument Value
Start Frequency	2.40050 GHz	2.43850 GHz	2.47850 GHz
Stop Frequency	2.40350 GHz	2.44150 GHz	2.48150 GHz
Span	3.000 MHz	3.000 MHz	3.000 MHz
RBW	10.000 kHz	10.000 kHz	10.000 kHz
VBW	30.000 kHz	30.000 kHz	30.000 kHz
Sweep Points	600	600	600
Sweep time	3.000 ms	3.000 ms	3.000 ms
Reference Level	0.000 dBm	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	20.000 dB	20.000 dB
Detector	MaxPeak	MaxPeak	MaxPeak
Sweep Count	100	100	100
Filter	3 dB	3 dB	3 dB
Trace Mode	Max Hold	Max Hold	Max Hold
Sweep type	Sweep	Sweep	Sweep
Preamplifier	off	Off	off
Stable mode	Trace	Trace	Trace
Stable value	0.50 dB	0.50 dB	0.50 dB
Run	6 / max. 150	5 / max. 150	5 / max. 150
Stable	2 / 2	2 / 2	2 / 2
Max Stable Difference	0.11 dB	0.42 dB	0.36 dB

TEST A.6: EMISSION LIMITATIONS RADIATED (TRANSMITTER)

LIMITS:	Product standard:	Part 15 Subpart C §15.247 and RSS-247
	Test standard:	Part 15 Subpart C §15.247(d) and RSS-Gen 8.9 and 8.10

LIMITS

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c) / RSS-Gen):

Frequency Range (MHz)	Field strength (μV/m)	Field strength (dBμV/m)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RSS-247. Attenuation below the general field strength limits specified in RSS-Gen is not required

TEST SETUP

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at 3 m for the frequency range 30-1000 MHz (Bilog antenna) and 1-18 GHz Double ridge horn antennas, and 1m for the frequency range 18 GHz- 26 GHz Double ridge horn antenna.

For radiated emissions in the range 18 - 26 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.


The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.


The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

TEST SETUP (CONT.)


Radiated measurements Setup $f < 1$ GHz



Radiated measurements setup $f > 1-18$ GHz



Radiated measurements setup $f > 18$ GHz



TESTED SAMPLES:	S/02
TESTED CONDITIONS MODES:	TC#01(1 Mbps)
TEST RESULTS:	PASS

Frequency range 30 MHz – 1000 MHz

The spurious emissions below 1 GHz do not depend on the operating channel selected in the EUT.

Frequency range 1 GHz – 26 GHz


The results in the next tables show the maximum measured levels in the 1-26 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz (see next plots).

TEST RESULTS (Cont.):

30-1000 MHz

Mid Channel

RF_FCC_15.247_E Field_30MHz_1GHz



- PK+_MAXH
- PK+_CLRWR
- TX limits to Spurious Emission FCC15.247 (30MHz to 1GHz) Restricted Bands QPK Limit
- ▽ MaxPeak-PK+ (Single)
- × QuasiPeak-QPK (Single)


Maximizations

Frequency (MHz)	MaxPeak (dBµV/m)	QuasiPeak (dBµV/m)	Pol	Margin - QPK (dB)	Limit - QPK (dBµV/m)
37.517500	27.9	17.5	V	22.5	40.0
172.105000	24.9	15.0	V	28.5	43.5
334.434500	30.9	20.3	V	25.7	46.0
407.815000	36.4	24.4	V	21.6	46.0
611.030000	41.0	29.8	V	16.2	46.0
963.431000	43.9	33.5	H	20.5	54.0

TEST RESULTS (Cont.):

1-18 GHz (Lowest Channel)

Lowest Channel




- AVG_MAXH
- PK+ MAXH
- TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands PK Limit
- TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands AVG Limit

Frequency (MHz)	PK+ MAXH (dBμV/m)	AVG_MAXH (dBμV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBμV/m)	Comment
2402.000000	97.9	97.3	V	---	---	Fundamental
4798.500000	48.2	33.6	V	20.4	54.0	
7206.000000	53.0	47.1	V	---	---	
12011.000000	56.5	48.6	H	5.4	54.0	

TEST RESULTS (Cont.):

1-18 GHz (Middle Channel)

Middle Channel




— AVG_MAXH
 — PK+_MAXH
 — TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands PK Limit
 — TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands AVG Limit

Frequency (MHz)	PK+_MAXH (dBμV/m)	AVG_MAXH (dBμV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBμV/m)	Comment
2440.000000	98.2	97.4	V	---	---	Fundamental
4880.000000	48.1	43.2	V	10.8	54.0	
7319.500000	50.3	44.4	V	9.6	54.0	
12199.000000	56.0	49.7	V	4.3	54.0	

TEST RESULTS (Cont.):

1-18 GHz (Highest Channel)

Highest Channel




— AVG_MAXH
 — PK+_MAXH
 — TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands PK Limit
 — TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands AVG Limit

Frequency (MHz)	PK+_MAXH (dBμV/m)	AVG_MAXH (dBμV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBμV/m)	Comment
2480.000000	98.8	97.9	V	---	---	Fundamental
4959.500000	48.6	44.3	V	9.7	54.0	
7439.500000	52.9	46.2	V	7.8	54.0	
12398.500000	54.6	48.4	V	5.6	54.0	

TEST RESULTS (Cont.):

18 – 26 GHz

Lowest Channel




- AVG_MAXH
- PK+_MAXH
- TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands PK Limit
- TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands AVG Limit

Frequency (MHz)	PK+_MAXH (dBμV/m)	AVG_MAXH (dBμV/m)	Pol
21615.500000	55.9	48.5	V

TEST RESULTS (Cont.):

18 – 26 GHz

Middle Channel




- AVG_MAXH
- PK+_MAXH
- TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands AVG Limit
- TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands PK Limit

Frequency (MHz)	PK+_MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	Pol
21958.000000	54.1	45.8	V

TEST RESULTS (Cont.):

18 – 26 GHz

Highest Channel




- AVG_MAXH
- PK+_MAXH
- TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands PK Limit
- TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands AVG Limit

Frequency (MHz)	PK+_MAXH (dBμV/m)	AVG_MAXH (dBμV/m)	Pol
22317.500000	55.5	46.7	V

TEST RESULTS (Cont.):


Restricted Bands (2.31 GHz – 2.5 GHz)

Lowest Channel



— AVG_MAXH
— PK+_MAXH
— TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands PK Limit
— TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands AVG Limit

Highest Channel



— AVG_MAXH
— PK+_MAXH
— TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands PK Limit
— TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands AVG Limit

TESTED SAMPLES:	S/02
TESTED CONDITIONS MODES:	TC#02(2 Mbps)
TEST RESULTS:	PASS

Frequency range 30 MHz – 1000 MHz

The spurious emissions below 1 GHz do not depend on the operating channel selected in the EUT.


Frequency range 1 GHz – 26 GHz

The results in the next tables show the maximum measured levels in the 1-26 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz (see next plots).

TEST RESULTS (Cont.):

1-18 GHz (Lowest Channel)

Lowest Channel




— AVG_MAXH
 — PK+_MAXH
 — TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands PK Limit
 — TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands AVG Limit

Frequency (MHz)	PK+_MAXH (dBμV/m)	AVG_MAXH (dBμV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBμV/m)	Comment
2402.500000	97.7	94.6	V	---	---	Fundamental
4803.500000	45.2	38.2	V	15.8	54.0	
7207.000000	51.3	44.6	V	---	---	
12012.000000	56.6	50.0	H	4.0	54.0	

TEST RESULTS (Cont.):

1-18 GHz (Middle Channel)

Middle Channel




— AVG_MAXH
 — PK+_MAXH
 — TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands PK Limit
 — TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands AVG Limit

Frequency (MHz)	PK+_MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBµV/m)	Comment
2440.500000	97.9	94.9	V	---	---	Fundamental
4880.000000	47.9	41.2	V	6.1	54.0	
7318.500000	50.0	42.4	V	4.0	54.0	
12200.000000	57.5	46.0	H	-3.5	54.0	

TEST RESULTS (Cont.):

1-18 GHz (Highest Channel)

Highest Channel




— AVG_MAXH
 — PK+_MAXH
 — TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands PK Limit
 — TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands AVG Limit

Frequency (MHz)	PK+_MAXH (dBμV/m)	AVG_MAXH (dBμV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBμV/m)	Comment
2479.500000	98.5	93.9	V	---	---	Fundamental
4960.500000	49.2	41.2	V	12.8	54.0	
7441.500000	52.2	45.0	V	9.0	54.0	
12402.500000	55.7	46.4	V	7.6	54.0	

TEST RESULTS (Cont.):

18 – 26 GHz

Lowest Channel




- AVG_MAXH
- PK+_MAXH
- TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands AVG Limit
- TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands PK Limit

Frequency (MHz)	PK+_MAXH (dBμV/m)	AVG_MAXH (dBμV/m)	Pol
21958.000000	54.1	45.8	V

TEST RESULTS (Cont.):

18 – 26 GHz

Middle Channel




- AVG_MAXH
- PK+_MAXH
- TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands AVG Limit
- TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands PK Limit

Frequency (MHz)	PK+_MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	Pol
21955.500000	58.7	50.1	V

TEST RESULTS (Cont.):

18 – 26 GHz

Highest Channel




- AVG_MAXH
- PK+_MAXH
- TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands AVG Limit
- TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands PK Limit

Frequency (MHz)	PK+_MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	Pol
22315.500000	58.7	50.6	V

TEST RESULTS (Cont.):


Restricted Bands (2.31 GHz – 2.5 GHz)

Lowest Channel



— AVG_MAXH
— PK+_MAXH
— TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands PK Limit
— TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands AVG Limit

Highest Channel



— AVG_MAXH
— PK+_MAXH
— TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands PK Limit
— TX limits to Spurious Emission FCC15.247 (1-26 GHz) Restricted Bands AVG Limit