

TEST REPORT No.: (5216)257-0559

TEST REPORT

To:	MR. CHRISTMAS LIMITED	To:	-
Attn:	Daniel Liao	Attn:	-
Address:	Suite 901, Railway Plaza, 39 Chatham Road South, TST, Kowloon, Hong Kong.	Address:	-
Fax:	2369 0136	Fax:	-
E-mail:	dliao@mrchristmas.com	E-mail:	-
Folder No.:	MRC-16SE077MTHS-B-A		
Factory Name:	--		
Location:	--		
Product:	Mr. Christmas Pre-Programmed LED Holiday Banner with Remote MODEL: 67319		
		Sample No:	HK160909/014
		Date of Receipt:	September 09, 2016
		Test Date(s):	September 23, 2016
		Test Requested:	FCC Part 15 – 2015
		Test Method:	ANSI C63.10 – 2013
		FCC ID:	SHV67319
The results given in this report are related to the tested specimen of the described electrical apparatus.			
CONCLUSION: The submitted sample was found to <u>COMPLY</u> with requirement of FCC Part 15 Subpart C.			
Authorized Signature:			
			
Reviewed by: Keith Yeung		Approved by: Law Man Kit	
Date: September 26, 2016		Date: September 26, 2016	



TEST REPORT No.: (5216)257-0559

Test Result Summary

EMISSION TEST			
Test requirement: FCC Part 15 - 2015			
Test Condition	Test Method	Test Result	
		Pass	Failed
Radiated Emission Test, 9kHz to 5GHz	ANSI C63.10	☒	☐
Frequency range of Fundamental Emission	ANSI C63.10	☒	☐
20dB Bandwidth of Fundamental Emission	ANSI C63.10	☒	☐
Duty Cycle Correction During 100mesc	ANSI C63.10	☒	☐
Duration of Transmission	ANSI C63.10	☒	☐

Report Revision & Sample Re-submit History:

--



TEST REPORT No.: (5216)257-0559

Test Laboratory & Test Instruments List

Radiated and Conducted emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.10 – 2013. An Open Area Test Site and Full Anechoic Chamber are set up for investigation and located at:

BUREAU VERITAS HONG KONG LIMITED, EMC CENTRE

No. 2106-2107, 21/F., Westin Centre,
26 Hung To Road,
Kwun Tong, Kowloon,
Hong Kong

Test Instrument List

Radiated Emission

EQUIPMENT	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE DATE
EMI TEST RECEIVER	R&S	ESCI	100379	23-FEB-2016	22-FEB-2017
SIGNAL ANALYZER 40GHZ	R&S	FSV 40	100977	16-AUG-2016	15-AUG-2017
BILOG ANTENNA	SCHAFFNER	CBL6112D	25229	27-FEB-2016	26-FEB-2018
OPEN AREA TEST SITE	BVCPS	N/A	N/A	18-JUN-2016	17-JUN-2017
ANECHOIC CHAMBER	ALBATROSS	M-CDC	80374004499B	11-MAY-2016	10-MAY-2017
BICONICAL ANTENNA	R&S	HK116	100179	14-APR-2016	13-APR-2018
LOG-PERIODIC DIPOLE ARRAY ANTENNA	R&S	HL223	832369/001	07-APR-2016	06-APR-2018
LOOP ANTENNA	ETS-LINDGREN	6502	00102266	06-NOV-2015	05-NOV-2017
HORN ANTENNA (1-18GHZ)	SCHWARZBECK	BBHA9120D	9120D-692	05-NOV-2016	04-NOV-2018
COAXIAL CABLE	SUHNER	N/A	N/A	07-JAN-2016	06-JAN-2017

Measurement Uncertainty

MEASUREMENT	FREQUENCY	UNCERTAINTY
Radiated emissions	9kHz to 30MHz	4.2dB
	30MHz to 200MHz	4.5dB
	200MHZ to 1GHz	5.6dB
	1GHz to 18GHz	4.7dB
	18GHz to 40GHz	5.2dB

Remarks: -

N/A: Not Applicable or Not Available

The measurement instrumentation uncertainty would be taking into consideration on each of the test result

TEST REPORT No.: (5216)257-0559

Equipment Under Test [EUT]

Description of Sample:

Product: Mr. Christmas Pre-Programmed LED Holiday Banner with Remote
Model No.: 67319
Additional Model name: --
Additional Model number: --
Additional Model Information: --
Power Supply: 12Vd.c. ("23A" size battery x 1)

Description of EUT Operation:

The Equipment Under Test (EUT) is a **Mr. Christmas Limited** of RF Controller. The transmitter is a 4 buttons transmitter and operating at 315MHz. The EUT continues to transmit while buttons is being pressed. Modulation by IC, and type is OOK and ASK modulation.

The transmitter has different control:

1. "ON" button – control the light on
2. "OFF" button – control the light off
3. "Up Arrow" button – select the light show
4. "Down Arrow" button – select the light show

Antenna Requirement (Section 15.203)

The EUT is use of a permanently antenna. It is soldered on the PCB. The antenna is not replaceable or user serviceable. The requirements of S15.203 are met. There are no deviations or exceptions to the specifications.

Photo of Antenna



TEST REPORT No.: (5216)257-0559

Test Results

Radiated Emissions (Fundamental)

Test Requirement: FCC Part 15 Section 15.231(b)
Test Method: ANSI C63.10 Clause 6
Test Date(s): 2016-09-23
Temperature: 31.0 °C
Humidity: 72.0 %
Atmospheric Pressure: 99.8 kPa
Mode of Operation: Transmission mode
Tested Voltage: 12Vd.c. ("23A" size battery x 1)

Test Method:


Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.10 – 2013.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground for measurement frequency below 1GHz and 1.5m high above the ground for measurement frequency above 1GHz. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using new battery. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.

Location: The Roof, Westin Centre, 26 Hung To Road, Kwun Tong, Kowloon, Hong Kong

Test Setup: Open Area Test Site





TEST REPORT No.: (5216)257-0559

Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.231(b)]:

Frequency Range of Fundamental [MHz]	Field Strength of Fundamental Emission [Peak] [μV/m]	Field Strength of Fundamental Emission [Average] [μV/m]
260-470	3,750 to 12,500**	375 to 1,250**

**linear interpolations

[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 260-470MHz, $\mu\text{V/m}$ at 3 meters = $41.6667(F) - 7083.3333$. The maximum permitted unwanted emission level is 20dB below the maximum permitted fundamental level]

Measurement Data

Test Result of (Transmission mode): PASS

Frequency (MHz)	Polarity (H/V)	Antenna Factor & Cable Loss (dB/m)	Duty-cycle correction (dB)	Field Strength at 3m – Peak (dBμV/m)	Limit at 3m – Peak (dBμV/m)	Margin - Peak (dB)	Field Strength at 3m – Average (dBμV/m)	Limit at 3m – Average (dBμV/m)	Margin - Average (dB)
315.07	H	14.7	-11.7	76.5	95.6	-19.1	**64.8	75.6	-10.8
315.07	V	14.7	-11.7	72.4	95.6	-23.2	**60.7	75.6	-14.9

For pulse modulated devices and using measuring equipment employing a peak detection mode, properly adjusted for such factor as pulse desensitisation.

**Duty Cycle Correction = $20\log(0.26) = -11.7\text{dB}$.

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting: RBW = 100KHz
VBW = 300KHz



TEST REPORT No.: (5216)257-0559

Radiated Emissions (Spurious Emission)

Test Requirement: FCC Part 15 Section 15.231(b)
 Test Method: ANSI C63.10 Clause 6
 Test Date(s): 2016-09-23
 Temperature: 31.0 °C
 Humidity: 72.0 %
 Atmospheric Pressure: 99.8 kPa
 Mode of Operation: Transmission mode
 Tested Voltage: 12Vd.c. ("23A" size battery x 1)

Measurement Data

Test Result of (Transmission mode): PASS

Frequency (MHz)	Polarity (H/V)	Antenna Factor & Cable Loss (dB/m)	Duty-cycle correction (dB)	Field Strength at 3m – Peak (dBμV/m)	Limit at 3m – Peak (dBμV/m)	Margin - Peak (dB)	Field Strength at 3m – Average (dBμV/m)	Limit at 3m – Average (dBμV/m)	Margin - Average (dB)
630.14	H	21.9	-11.7	60.0	75.6	-15.6	**48.3	55.6	-7.3
945.21	H	24.8	-11.7	51.9	75.6	-23.7	**40.2	55.6	-15.4
1260.28	H	-8.1	-11.7	39.0	75.6	-36.6	**27.3	55.6	-28.3
1575.35	H	-6.3	-11.7	55.6	74.0	-18.4	**43.9	54.0	-10.1
1890.42	H	-5.2	-11.7	45.9	75.6	-29.7	**34.2	55.6	-21.4
2205.49	H	-3.0	-11.7	43.0	74.0	-31.0	**31.3	54.0	-22.7
2520.56	H	-3.5	-11.7	35.1	75.6	-40.5	**23.4	55.6	-32.2
2835.63	H	-2.6	-11.7	36.7	74.0	-37.3	**25.0	54.0	-29.0
3150.70	H	-2.5	-11.7	40.7	75.6	-34.9	**29.0	55.6	-26.6
3465.77	H	-2.6	-11.7	41.9	75.6	-33.7	**30.2	55.6	-25.4

For pulse modulated devices and using measuring equipment employing a peak detection mode, properly adjusted for such factor as pulse desensitisation.

**Duty Cycle Correction = $20\log(0.26) = -11.7\text{dB}$.

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting (30-1000MHz) :RBW = 100KHz
:VBW = 300KHz

Receiver setting (1-18GHz) :RBW = 1MHz
:VBW = 1MHz



TEST REPORT No.: (5216)257-0559

Measurement Data

Test Result of (Transmission mode): PASS

Frequency (MHz)	Polarity (H/V)	Antenna Factor & Cable Loss (dB/m)	Duty-cycle correction (dB)	Field Strength at 3m – Peak (dBμV/m)	Limit at 3m – Peak (dBμV/m)	Margin - Peak (dB)	Field Strength at 3m – Average (dBμV/m)	Limit at 3m – Average (dBμV/m)	Margin - Average (dB)
630.14	V	21.9	-11.7	52.6	75.6	-23.0	**40.9	55.6	-14.7
945.21	V	24.8	-11.7	48.2	75.6	-27.4	**36.5	55.6	-19.1
1260.28	V	-8.1	-11.7	49.5	75.6	-26.1	**37.8	55.6	-17.8
1575.35	V	-6.3	-11.7	50.8	74.0	-23.2	**39.1	54.0	-14.9
1890.42	V	-5.2	-11.7	46.5	75.6	-29.1	**34.8	55.6	-20.8
2205.49	V	-3.0	-11.7	42.7	74.0	-31.3	**31.0	54.0	-23.0
2520.56	V	-3.5	-11.7	34.9	75.6	-40.7	**23.2	55.6	-32.4
2835.63	V	-2.6	-11.7	34.3	74.0	-39.7	**22.6	54.0	-31.4
3150.70	V	-2.5	-11.7	39.9	75.6	-35.7	**28.2	55.6	-27.4
3465.77	V	-2.6	-11.7	39.3	75.6	-36.3	**27.6	55.6	-28.0

For pulse modulated devices and using measuring equipment employing a peak detection mode, properly adjusted for such factor as pulse desensitisation.

**Duty Cycle Correction = $20\log(0.26) = -11.7\text{dB}$.

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting (30-1000MHz) :RBW = 100KHz
:VBW = 300KHz

Receiver setting (1-18GHz) :RBW = 1MHz
:VBW = 1MHz



TEST REPORT No.: (5216)257-0559

Radiated Emissions (9kHz – 2GHz)

Test Requirement: FCC Part 15 Section 15.209
Test Method: ANSI C63.10 Clause 6
Test Date(s): 2016-09-23
Temperature: 31.0 °C
Humidity: 72.0 %
Atmospheric Pressure: 99.8 kPa
Mode of Operation: Transmission mode
Tested Voltage: 12Vd.c. ("23A" size battery x 1)

Limits for Radiated Emissions [FCC 47 CFR 15.209]:

Frequency Range [MHz]	Quasi-Peak Limits [μV/m]	Measurement Distance m
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Measurement Data

Test Result of (On mode): PASS

Detection mode: Quasi-Peak

Frequency	Polarity (H/V)	Field Strength	Limit	Margin (dB)
Emissions detected are more than 20 dB below the limit line(s) in 9kHz to 30MHz				



TEST REPORT No.: (5216)257-0559

Measurement Data

Test Result of (Transmission mode): PASS

Detection mode: Quasi-Peak

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
47.22	H	10.2	26.2	40.0	-13.8
72.14	H	9.1	21.5	40.0	-18.5
153.82	H	12.8	23.2	43.5	-20.3
214.48	H	10.8	24.5	43.5	-19.0
282.26	H	13.7	25.3	46.0	-20.7
341.72	H	14.9	27.4	46.0	-18.6

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
47.22	V	10.2	26.5	40.0	-13.5
72.14	V	9.1	20.7	40.0	-19.3
153.82	V	12.8	24.1	43.5	-19.4
214.48	V	10.8	24.6	43.5	-18.9
282.26	V	13.7	25.3	46.0	-20.7
341.72	V	14.9	26.5	46.0	-19.5

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting: RBW = 120KHz
VBW = 120KHz



TEST REPORT No.: (5216)257-0559

20dB Bandwidth of Fundamental Emission

Test Requirement: FCC 47 CFR 15.231(c)
Test Method: ANSI C63.10 Clause 6.9
Test Date(s): 2016-09-23
Temperature: 31.0 °C
Humidity: 72.0 %
Atmospheric Pressure: 99.8 kPa
Mode of Operation: Transmission mode
Tested Voltage: 12Vd.c. ("23A" size battery x 1)

Test Method:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

Limits for 20dB Bandwidth of Fundamental Emission:

Frequency [MHz]	20dB Bandwidth [kHz]	Limits [kHz]
315.07	24.0	787.6




BUREAU
VERITAS

TEST REPORT No.: (5216)257-0559

Measurement Data

Test Result of 20dB Bandwidth of Fundamental Emission: **PASS**





TEST REPORT No.: (5216)257-0559

Duty Cycle Correction During 100msec:

Each function key sends a different series of characters, but each packet period (100msec) never exceeds a series of 30 short (0.2msec) pulses and 20 long (1msec) pulses. Assuming any combination of short or long pulses may be obtained due to encoding the worst case transmit duty cycle would be considered $(30 \times 0.2) + (20 \times 1)$ per 100msec = 26% duty cycle. Figure A to B show the characteristics of the pulse train for one of these functions.

Remarks:

Duty Cycle Correction = $20\text{Log}(0.26) = -11.7\text{dB}$

The following figures [Figure A to Figure B] show the characteristics of the pulse train for one of these functions.

TEST REPORT No.: (5216)257-0559

Figure A [Long Pulse]





Figure B [Short Pulse]



TEST REPORT No.: (5216)257-0559

Duration of Transmission

Test Requirement: FCC 47 CFR 15.231(a)(1)
 Test Date(s): 2016-09-23
 Temperature: 31.0 °C
 Humidity: 72.0 %
 Atmospheric Pressure: 99.8 kPa
 Mode of Operation: Transmission mode
 Tested Voltage: 12Vd.c. ("23A" size battery x 1)


Test requirement: 15.231(a)(1)

A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 second of being released.

Result: Pass

The transmitter is manually operated employing a push-to-operate switch and Figure C shows that it has been deactivated immediately of being released

Figure C [Each transmission]



TEST REPORT No.: (5216)257-0559

Photographs of EUT

Front View of the product



Rear View of the product



Top View of the product



Bottom View of the product



Side View of the product



Side View of the product



Battery compartment



Battery Cover



TEST REPORT No.: (5216)257-0559

Photographs of EUT

Internal View of the product



Internal View of the product



Inner Circuit Top View



Inner Circuit Bottom View



Antenna



TEST REPORT No.: (5216)257-0559

Measurement of Radiated Emission Test Set Up



******* End of Report *******