FCC 47 CFR PART 15 SUBPART C AND ANSI C63.4:2009
TEST REPORT

For

DreamTab HD8

Model : DMTAB-IN08A

Trade Name : nabi

Issued for

Foxconn International Inc.

No.2,Ziyou St.,Tucheng Dist., New Taipei City 236,Taiwan

Issued by

Compliance Certification Services Inc.
Hsinchu Lab.
NO. 989-1 Wen Shan Rd., Shang Shan Village,
Qionglin Shiang Hsinchu County 30741, Taiwan, R.O.C
TEL: +886-3-5921698
FAX: +886-3-5921108

http://www.ccsrf.com
E-Mail : service@ccsrf.com

Issued Date: March 31, 2014

Testing Laboratory
0240

Note: *This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF or any government agencies. The test results of this report relate only to the tested sample identified in this report.*

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	03/31/2014	Initial Issue	All Page 80	Gloria Chang

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

TABLE OF CONTENTS

TITLE PAGE NO.

1. TEST REPORT CERTIFICATION 4

2. EUT DESCRIPTION 5

3. DESCRIPTION OF TEST MODES 6-7

4. TEST METHODOLOGY 8

5. FACILITIES AND ACCREDITATION 8

5.1 FACILITIES 8

5.2 ACCREDITATIONS 8

5.3 MEASUREMENT UNCERTAINTY 9

6. SETUP OF EQUIPMENT UNDER TEST 10

7. FCC PART 15.247 REQUIREMENTS 11

7.1 20dB BANDWIDTH FOR HOPPING 11-16

7.2 MAXIMUM PEAK OUTPUT POWER 17-18

7.3 AVERAGE POWER 19-20

7.4 HOPPING CHANNEL SEPARATION 21-26

7.5 NUMBER OF HOPPING FREQUENCY USED 27-29

7.6 DWELL TIME ON EACH CHANNEL 30-44

7.7 CONDUCTED SPURIOUS EMISSION 45-51

7.8 RADIATED EMISSION 52-71

7.9 CONDUCTED EMISSION 72-76

APPENDIX SETUP PHOTOS 77-80

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

1. TEST REPORT CERTIFICATION

Applicant	：	Foxconn International Inc.
Address	：	No.2,Ziyou St.,Tucheng Dist., New Taipei City 236,Taiwan
Equipment Under Test	：	DreamTab HD8
Model	：	DMTAB-IN08A
Trade Name	：	nabi
Tested Date	：	March 12 ~ 28, 2014

APPLICABLE STANDARD	
Standard	**Test Result**
FCC Part 15 Subpart C AND ANSI C63.4:2009	PASS

WE HEREBY CERTIFY THAT: The above equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:

Rex Liao
Deputy Manager

Reviewed by:

Jacky Chen
Section Manager

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

2. EUT DESCRIPTION

Product Name	DreamTab HD8
Model Number	DMTAB-IN08A
Identify Number	T140312D11
Received Date	March 12, 2014
Frequency Range	2402MHz to 2480MHz f = 2402 + nMHz, n = 0, …..78
Transmit Power	9.75 dBm (0.0094W)
Channel Spacing	1MHz
Channel Number	79 Channels
Transmit Data Rate	GFSK (1Mbps), π/4-DQPSK (2Mbps), 8-DPSK (3Mbps)
Type of Modulation	Frequency Hopping Spread Spectrum
Antenna Type	PIFA Antenna, Antenna Gain 3.3dBi
Power Rating	3.7Vdc, 4500mAh, 16.65Wh (For Battery) 5Vdc (For Charging)
Test Voltage	120Vac, 60Hz
I/O Port	USB Port × 1, Micro SD Port × 1, Audio Port × 1
Signal Cable	Shielded USB Cable 1m × 1

Power Adapter :

No.	Manufacturer	Model No.	Power Input	Power Output
1	Chicony	W12-010N3A	100-240Vac, 50/60Hz, 0.3A	5Vdc, 2A

Remark :

1. *The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.*
2. *For more details, please refer to the User's manual of the EUT.*
3. *This submittal(s) (test report) is intended for FCC ID:SIB-DMTAB-IN08A filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.*

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

3. DESCRIPTION OF TEST MODES

The EUT (DreamTab HD8) had been tested under operating condition.

There are three channels have been tested as following :

Channel	Frequency (MHz)
Low	2402
Middle	2441
High	2480

Conducted Emission / Radiated Emission Test (Below 1 GHz)

1. The following test modes were scanned during the preliminary test:

No.	Pre-Test Mode
1	Charge Mode + Play Video
2	Charge Mode + REC (with Front Camera)
3	Charge Mode + REC (with Back Camera)
4	Normal Operating + Link Notebook PC Read
5	Normal Operating + Link Notebook PC Write

2. After the preliminary scan, the following test mode was found to produce the highest emission level.

Final Test Mode		
Emission	Radiated Emission	Normal Operating + Link Notebook PC Write
	Conducted Emission	Charge Mode + Play Video

Remark : *Then, the above highest emission mode of the configuration of the EUT and cable was chosen for all final test items.*

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

Radiated Emission Test (Above 1 GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

Tested Channel	Modulation Technology	Modulation Type	Packet Type
Low, Mid, High	FHSS	GFSK	DH5
Low, Mid, High	FHSS	8-DPSK	3-DH5

Bandedge Measurement :

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

Tested Channel	Modulation Technology	Modulation Type	Packet Type
Low, High	FHSS	GFSK	DH5
Low, High	FHSS	8-DPSK	3-DH5

Antenna Port Conducted Measurement :

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

Tested Channel	Modulation Technology	Modulation Type	Packet Type
Low, Mid, High	FHSS	GFSK	DH5
Low, Mid, High	FHSS	8-DPSK	3-DH5

Remark：*The field strength of spurious emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X, Y axis). The worst emission was found in lie-down position(Y axis) and the worst case was recorded.*

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

4. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4: 2009 and FCC CFR 47, 15.207, 15.209 and 15.247.

5. FACILITIES AND ACCREDITATION

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

NO. 989-1 Wen Shan Rd., Shang Shan Village,
Qionglin Shiang Hsinchu County 30741, Taiwan, R.O.C

The sites are constructed in conformance with the requirements of ANSI C63.4:2009 and CISPR 22. All receiving equipment conforms to CISPR 16-1-1, CISPR 16-1-2, CISPR 16-1-3, CISPR 16-1-4, CISPR 16-1-5.

5.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

Taiwan	TAF

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada	INDUSTRY CANADA
Japan	VCCI
Taiwan	BSMI
USA	FCC MRA

Copies of granted accreditation certificates are available for downloading from our web site, http:///www.ccsrf.com

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

5.3 MEASUREMENT UNCERTAINTY

The following table is for the measurement uncertainty, which is calculated as per the document CISPR 16-4-2.

PARAMETER	UNCERTAINTY
Semi Anechoic Chamber (966 Chamber_A) / Radiated Emission, 30 to 1000 MHz	+/- 3.59
Semi Anechoic Chamber (966 Chamber_A) / Radiated Emission, 1 to 18GHz	+/- 3.59
Semi Anechoic Chamber (966 Chamber_A) / Radiated Emission, 18 to 26 GHz	+/- 3.59
Semi Anechoic Chamber (966 Chamber_A) / Radiated Emission, 26 to 40 GHz	+/- 3.82
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 30 to 1000 MHz	+/- 3.97
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 1 to 18GHz	+/- 3.58
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 18 to 26 GHz	+/- 3.59
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 26 to 40 GHz	+/- 3.81
Conducted Emission (Mains Terminals), 9kHz to 30MHz	+/- 2.48

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Consistent with industry standard (e.g. CISPR 22, clause 11, Measurement Uncertainty) determining compliance with the limits shall be base on the results of the compliance measurement. Consequently the measure emissions being less than the maximum allowed emission result in this be a compliant test or passing test.

The acceptable measurement uncertainty value without requiring revision of the compliance statement is base on conducted and radiated emissions being less than U_{CISPR} which is 3.6dB and 5.2dB respectively. CCS values (called U_{Lab} in CISPR 16-4-2) is less than U_{CISPR} as shown in the table above. Therefore, MU need not be considered for compliance.

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

6. SETUP OF EQUIPMENT UNDER TEST

SUPPORT EQUIPMENT

No.	Product	Manufacturer	Model No.	Serial No.	FCC ID
1	Notebook PC	TOSHIBA	M840	9C104267C	DoC
2	LCD Monitor	DELL	2407WFPb	CN-0FC255-4663 3-6CP-06JS	DoC
3	Keyboard	HP	KU-0316	35563-AB1	DoC
4	Mouse	HP	M-UAE96	265986-011	DoC
5	Headset	Acon	CW-010.V	---	---

SETUP DIAGRAM FOR TESTS

EUT & peripherals setup diagram is shown in appendix setup photos.

EUT OPERATING CONDITION

RF Mode :
1. EUT & peripherals setup diagram is shown in appendix setup photos.
2. Select the following settings.
3. TX mode(GFSK)
   TXDATA1
   LO Freq: 2402, 2441, 2480
   CFG PKT, Packet Type: 15
   Packet Size: 339
   TX mode (8-DPSK)
   TXDATA1
   LO Freq: 2402, 2441, 2480
   CFG PKT, Packet Type: 31
   Packet Size: 1021
5. All of the functions are under run.
6. Start test.

Normal Mode :
1. EUT & peripherals setup diagram is shown in appendix setup photos.
2. a. Notebook PC software to write with EUT.
   b. Charge Mode and play video.
3. All of the functions are under run.
4. Start test.

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

7. FCC PART 15.247 REQUIREMENTS

7.1 20dB BANDWIDTH FOR HOPPING

LIMITS

Limit : N/A

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360132	06/10/2014

Remark: *Each piece of equipment is scheduled for calibration once a year.*

TEST SETUP



TEST PROCEDURE

1. The 20dB band width was measured with a spectrum analyzer connected to RF antenna connector(conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency. The analyzer center frequency was set to the EUT carrier frequency, using the analyzer. Display Line and Marker Delta functions, the 20dB band width of the emission was determined.
2. Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel.
3. RBW ≥ 1% of the 20 dB bandwidth.
4. VBW ≥ RBW.
5. Sweep = auto.

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

TEST RESULTS

Modulation Type: GFSK, CFG PKT Packet Type: 15 Packet Size: 339 (DH5)

Channel	Channel Frequency (MHz)	20dB Bandwidth (MHz)	Result
Low	2402	0.933	N/A
Middle	2441	0.933	N/A
High	2480	0.933	N/A

Modulation Type: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021 (3-DH5)

Channel	Channel Frequency (MHz)	20dB Bandwidth (MHz)	Result
Low	2402	1.308	N/A
Middle	2441	1.305	N/A
High	2480	1.299	N/A

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

20dB BANDWIDTH

CH Low (GFSK)



CH Middle (GFSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

CH High (GFSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

CH Low (8-DPSK)



CH Middle (8-DPSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

CH High (8-DPSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

7.2 MAXIMUM PEAK OUTPUT POWER

LIMITS

§15.247(b)(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Power Meter	Anritsu	ML2495A	1149001	12/06/2014
Power Sensor	Anritsu	MA2411B	1126148	12/06/2014

Remark: *Each piece of equipment is scheduled for calibration once a year.*

TEST SETUP

TEST PROCEDURE

The transmitter output is connected to the Power Meter. The Power Meter is set to the peak power detection.

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

TEST RESULTS

Modulation Type: GFSK ,CFG PKT Packet Type: 15 Packet Size: 339 (DH5)

Channel	Channel Frequency (MHz)	Peak Power		Peak Power Limit		Result
		(dBm)	(W)	(dBm)	(W)	
Low	2402	9.69	0.0093	20.97	0.125	PASS
Middle	2441	9.75	0.0094	20.97	0.125	PASS
High	2480	9.71	0.0094	20.97	0.125	PASS

Remark: *The cable assembly insertion loss of 11.5dB (including 10 dB pad and 1.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.*

Modulation Type: 8-DPSK ,CFG PKT Packet Type: 31 Packet Size: 1021 (3-DH5)

Channel	Channel Frequency (MHz)	Peak Power		Peak Power Limit		Result
		(dBm)	(W)	(dBm)	(W)	
Low	2402	9.47	0.0089	20.97	0.125	PASS
Middle	2441	8.61	0.0073	20.97	0.125	PASS
High	2480	8.31	0.0068	20.97	0.125	PASS

Remark: *The cable assembly insertion loss of 11.5dB (including 10 dB pad and 1.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.*

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

7.3 AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Power Meter	ANRITSU	ML2495A	1149001	12/06/2014
Power Sensor	ANRITSU	MA2411B	1126148	12/06/2014

Remark: *Each piece of equipment is scheduled for calibration once a year.*

TEST SETUP



TEST PROCEDURE

The transmitter output is connected to the Power Meter. The Power Meter is set to the average power detection.

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

TEST RESULTS

Modulation Type: GFSK ,CFG PKT Packet Type: 15 Packet Size: 339 (DH5)

Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2402	8.04
Middle	2441	8.13
High	2480	8.06

Remark: *The cable assembly insertion loss of 11.5dB (including 10dB pad and 1.5dB cable) was Entered as an offset in the power meter to allow for direct reading of power.*

Modulation Type: 8-DPSK ,CFG PKT Packet Type: 31 Packet Size: 1021 (3-DH5)

Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2402	7.56
Middle	2441	6.56
High	2480	6.36

Remark: *The cable assembly insertion loss of 11.5dB (including 10dB pad and 1.5dB cable) was Entered as an offset in the power meter to allow for direct reading of power.*

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

7.4 HOPPING CHANNEL SEPARATION

LIMITS

§15.247(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360132	06/10/2014

Remark: *Each piece of equipment is scheduled for calibration once a year.*

TEST SETUP

TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of adjacent channels.
4. Measure the frequency difference of these two adjacent channels by spectrum analyzer MARK function. And then plot the result on spectrum analyzer screen.
5. Span = wide enough to capture the peaks of two adjacent channels.
6. Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span.
7. Video (or Average) Bandwidth (VBW) ≥ RBW.
8. Sweep = auto.
9. Repeat above procedures until all frequencies measured were complete.

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

TEST RESULTS

Refer to section 7.1, 20dB bandwidth measurement, the measured channel separation should be greater than two-third of 20dB bandwidth or Minimum bandwidth.

Modulation Type: GFSK, CFG PKT Packet Type: 15 Packet Size: 339 (DH5)

Channel	Channel Frequency (MHz)	Adjacent Hopping Channel Separation (kHz)	Two –third of 20dB bandwidth (kHz)	Minimum Bandwidth	Result
Low	2402	1000	622	25 kHz	PASS
Middle	2441	1000	622	25 kHz	PASS
High	2480	1000	622	25 kHz	PASS

Modulation Type: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021 (3-DH5)

Channel	Channel Frequency (MHz)	Adjacent Hopping Channel Separation (kHz)	Two –third of 20dB bandwidth (kHz)	Minimum Bandwidth	Result
Low	2402	1000	872	25 kHz	PASS
Middle	2441	1000	870	25 kHz	PASS
High	2480	1000	866	25 kHz	PASS

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

HOPPING CHANNEL SEPARATION

CH Low (GFSK)



CH Middle (GFSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

CH High (GFSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

CH Low (8-DPSK)



Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.402 010 GHz	7.90 dBm
2	(1)	Freq	2.403 010 GHz	8.13 dBm
3	(1)	Freq	2.404 010 GHz	8.12 dBm
4R	(1)	Freq	2.403 010 GHz	8.13 dBm
4Δ	(1)	Freq	1.000 MHz	-0.01 dB

CH Middle (8-DPSK)



Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.440 007 GHz	8.15 dBm
2	(1)	Freq	2.441 007 GHz	8.18 dBm
3	(1)	Freq	2.442 007 GHz	8.13 dBm
4R	(1)	Freq	2.441 007 GHz	8.18 dBm
4Δ	(1)	Freq	1.000 MHz	-0.05 dB

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

CH High (8-DPSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

7.5 NUMBER OF HOPPING FREQUENCY USED

LIMITS

§15.247(a)(1)(iii) For frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360132	06/10/2014

Remark: *Each piece of equipment is scheduled for calibration once a year.*

TEST SETUP

TEST PROCEDURE

1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set the spectrum analyzer on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
4. Set the spectrum analyzer on View mode and then plot the result on spectrum analyzer screen.
5. Span = the frequency band of operation.
6. RBW ≥ 1% of the span.
7. VBW ≥ RBW.
8. Sweep = auto.
9. Repeat above procedures until all frequencies measured were complete.

TEST RESULTS

Refer to the attached plot.
There are 79 hopping frequencies in a hopping sequence.

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

NUMBER OF HOPPING FREQUENCY USED

GFSK



GFSK



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

8-DPSK



8-DPSK



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

7.6 DWELL TIME ON EACH CHANNEL

LIMITS

§15.247(a)(1)(iii) For frequency hopping system operating in the 2400-2483.5MHz band, the average time of occupancy on any frequency shall not be greater than 0.4 second within a 31.6 second period.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360132	06/10/2014

Remark: *Each piece of equipment is scheduled for calibration once a year.*

TEST SETUP

TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of spectrum analyzer on any frequency be measured and set spectrum analyzer to zero span mode.
4. RBW = 1 MHz.
5. VBW ≥ RBW.
6. Sweep = as necessary to capture the entire dwell time per hopping channel.
7. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
8. Repeat above procedures until all frequencies measured were complete.
9. The EUT has 3 type of payload, DH1, DH3, DH5. The hopping rate is 1600 per second. The longer the payload is, the slower the hopping rate is.

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

TEST RESULTS

Time of occupancy on the TX channel in 31.6sec = time domain slot length × hop rate ÷ number of hop per channel × 31.6

Refer to the attached graph.

The hopping rates of Bluetooth devices change with different types of payload. The longer the payload is, the slower the hopping rate. The hopping rate scenario is defined in Bluetooth core specification.

Modulation Type: GFSK, CFG PKT Packet Type: 15 Packet Size: 339 (DH5)

Channel	Channel Frequency (MHz)	Packet type	Dwell time (ms)	Time of occupancy on the TX channel in 31.6sec (ms)	Limit for Time of occupancy on the TX channel in 31.6sec (ms)	Results
Low	2402	DH1	0.40	128.00	400	PASS
	2402	DH3	1.65	264.00	400	PASS
	2402	DH5	2.90	309.33	400	PASS
Middle	2441	DH1	0.40	128.00	400	PASS
	2441	DH3	1.65	264.00	400	PASS
	2441	DH5	2.90	309.33	400	PASS
High	2480	DH1	0.40	128.00	400	PASS
	2480	DH3	1.65	264.00	400	PASS
	2480	DH5	2.90	309.33	400	PASS

Remark:

Ch Low
DH1 : 0.40 ms × (1600÷2) ÷ 79 × 31.6 = 128.00 (ms)
DH3 : 1.65 ms × (1600÷4) ÷ 79 × 31.6 = 264.00 (ms)
DH5 : 2.90 ms × (1600÷6) ÷ 79 × 31.6 = 309.33 (ms)
Ch Middle
DH1 : 0.40 ms × (1600÷2) ÷ 79 × 31.6 = 128.00 (ms)
DH3 : 1.65 ms × (1600÷4) ÷ 79 × 31.6 = 264.00 (ms)
DH5 : 2.90 ms × (1600÷6) ÷ 79 × 31.6 = 309.33 (ms)
Ch High
DH1 : 0.40 ms × (1600÷2) ÷ 79 × 31.6 = 128.00 (ms)
DH3 : 1.65 ms × (1600÷4) ÷ 79 × 31.6 = 264.00 (ms)
DH5 : 2.90 ms × (1600÷6) ÷ 79 × 31.6 = 309.33 (ms)

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

Modulation Type: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021 (3-DH5)

Channel	Channel Frequency (MHz)	Packet type	Dwell time (ms)	Time of occupancy on the TX channel in 31.6sec (ms)	Limit for Time of occupancy on the TX channel in 31.6sec (ms)	Results
Low	2402	DH1	0.40	128.00	400	PASS
	2402	DH3	1.65	264.00	400	PASS
	2402	DH5	2.90	309.33	400	PASS
Middle	2441	DH1	0.40	128.00	400	PASS
	2441	DH3	1.65	264.00	400	PASS
	2441	DH5	2.90	309.33	400	PASS
High	2480	DH1	0.40	128.00	400	PASS
	2480	DH3	1.65	264.00	400	PASS
	2480	DH5	2.90	309.33	400	PASS

Remark:

Ch Low
DH1 : 0.40 ms × (1600÷2) ÷ 79 × 31.6 = 128.00 (ms)
DH3 : 1.65 ms × (1600÷4) ÷ 79 × 31.6 = 264.00 (ms)
DH5 : 2.90 ms × (1600÷6) ÷ 79 × 31.6 = 309.33 (ms)
Ch Middle
DH1 : 0.40 ms × (1600÷2) ÷ 79 × 31.6 = 128.00 (ms)
DH3 : 1.65 ms × (1600÷4) ÷ 79 × 31.6 = 264.00 (ms)
DH5 : 2.90 ms × (1600÷6) ÷ 79 × 31.6 = 309.33 (ms)
Ch High
DH1 : 0.40 ms × (1600÷2) ÷ 79 × 31.6 = 128.00 (ms)
DH3 : 1.65 ms × (1600÷4) ÷ 79 × 31.6 = 264.00 (ms)
DH5 : 2.90 ms × (1600÷6) ÷ 79 × 31.6 = 309.33 (ms)

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

DWELL TIME ON EACH PAYLOAD

DH1 CH Low (GFSK)



DH3 CH Low (GFSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

DH5 CH Low (GFSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

DH1 CH Middle (GFSK)



DH3 CH Middle (GFSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

DH5 CH Middle (GFSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

DH1 CH High (GFSK)



DH3 CH High (GFSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

DH5 CH High (GFSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

DH1 CH Low (8-DPSK)



DH3 CH Low (8-DPSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

DH5 CH Low (8-DPSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

DH1 CH Middle (8-DPSK)



DH3 CH Middle (8-DPSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

DH5 CH Middle (8-DPSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

DH1 CH High (8-DPSK)



DH3 CH High (8-DPSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

DH5 CH High (8-DPSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

7.7 CONDUCTED SPURIOUS EMISSION

LIMITS

§ 15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the and that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360132	06/10/2014

Remark: *Each piece of equipment is scheduled for calibration once a year.*

TEST SETUP

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.

The spectrum from 30 MHz to 26.5 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

TEST RESULTS

OUT-OF-BAND SPURIOUS EMISSIONS-CONDUCTED MEASUREMENT

CH Low (2.38GHz ~ 2.5GHz / GFSK)



Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.402 20 GHz	9.42 dBm
2	(1)	Freq	2.400 00 GHz	-31.69 dBm
3	(1)	Freq	2.450 20 GHz	-51.41 dBm
4	(1)	Freq	2.497 96 GHz	-44.32 dBm

CH Low (30MHz ~ 26.5GHz / GFSK)



Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	4.795 GHz	-50.75 dBm
2	(1)	Freq	7.195 GHz	-51.84 dBm
3	(1)	Freq	12.021 GHz	-47.45 dBm
4	(1)	Freq	24.674 GHz	-48.74 dBm

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

CH Middle (2.38GHz ~ 2.5GHz / GFSK)



CH Middle (30MHz ~ 26.5GHz / GFSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

CH High (2.38GHz ~ 2.5GHz / GFSK)



CH High (30MHz ~ 26.5GHz / GFSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

CH Low (2.38GHz ~ 2.5GHz / 8-DPSK)



CH Low (30MHz ~ 26.5GHz / 8-DPSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

CH Middle (2.38GHz ~ 2.5GHz / 8-DPSK)



CH Middle (30MHz ~ 26.5GHz / 8-DPSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

CH High (2.38GHz ~ 2.5GHz / 8-DPSK)



Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.479 96 GHz	8.75 dBm
2	(1)	Freq	2.383 96 GHz	-49.06 dBm
3	(1)	Freq	2.432 20 GHz	-53.62 dBm
4	(1)	Freq	2.456 08 GHz	-56.69 dBm

CH High (30MHz ~ 26.5GHz / 8-DPSK)



Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	4.953 GHz	-57.03 dBm
2	(1)	Freq	13.768 GHz	-53.92 dBm
3	(1)	Freq	20.756 GHz	-51.96 dBm
4	(1)	Freq	24.912 GHz	-49.03 dBm

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

7.8 RADIATED EMISSION

LIMITS

(1) According to § 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1]0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 -1710	10.6 -12.7
6.26775 - 6.26825	108 -121.94	1718.8 - 1722.2	13.25 -13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 – 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 -16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3338	36.43 - 36.5
12.57675 - 12.57725	322 -335.4	3600 - 4400	([2])
13.36 - 13.41			

Remark:

1. *[1] Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.*
2. *[2] Above 38.6*

(2) According to § 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown is Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

(3) According to § 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30.0	30	30
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

Remark: ***Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.*

(4) According to § 15.209 (b) In the emission table above, the tighter limit applies at the band edges.

TEST EQUIPMENT

Radiated Emission / 966Chamber_A

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360132	06/10/2014
EMI Receiver	ROHDE & SCHWARZ	ESCI	100221	04/29/2014
Bi-log Antenna	SCHWARZBECK	VULB 9168	9168-249	09/12/2014
Broad-Band Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-778	09/12/2014
Pre-Amplifier	Agilent	8449B	3008A01471	07/16/2014
Pre-Amplifier	HP	8447F	2944A03748	07/16/2014
Band Reject Notch Filter	Micro-Tronics	BRM05702-01	009	N.C.R

Remark: *1. Each piece of equipment is scheduled for calibration once a year.*
2. N.C.R = No Calibration Request.

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

Radiated Emission / 966Chamber_B

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY46180323	04/15/2014
EMI Test Receiver	ROHDE & SCHWARZ	ESCI	101387	10/09/2014
Bi-log Antenna	SCHWARZBECK	VULB 9168	9168-250	09/12/2014
Broad-Band Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-778	09/12/2014
Double-Ridged Waveguide Horn	ETS-LINDGREN	3117	00078733	12/05/2014
Horn Antenna	COM-POWER	AH-840	03077	12/18/2014
Pre-Amplifier	Agilent	8447D	2944A10052	07/16/2014
Pre-Amplifier	Agilent	8449B	3008A01916	07/16/2014
LOOP Antenna	EMCO	6502	8905-2356	08/20/2014
Notch Filters Band Reject	Micro-Tronics	BRM05702-01	026	N.C.R

Remark: *1. Each piece of equipment is scheduled for calibration once a year.*
2. N.C.R = No Calibration Request.

TEST SETUP

The diagram below shows the test setup that is utilized to make the measurements for emission below 1GHz.

9kHz ~ 30MHz



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

30MHz ~ 1GHz



The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

TEST PROCEDURE

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground. The table was rotated 360 degrees to determine the position of the highest radiation.
2. While measuring the radiated emission below 1GHz, the EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. While measuring the radiated emission above 1GHz, the EUT was set 3 meters away from the interference-receiving antenna.
3. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Remark：

1. *The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.*
2. *The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.*
3. *The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.*

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

TEST RESULTS

Below 1 GHz (9kHz ~ 30MHz)

No emission found between lowest internal used/generated frequency to 30MHz.

Below 1 GHz (30MHz ~ 1GHz)

Product Name	DreamTab HD8	**Test By**	Alan Wu
Test Model	DMTAB-IN08A	**Test Date**	2014/03/25
Test Mode	Normal Operating + Link Notebook PC Write	**Temp. & Humidity**	24°C, 50%

966 Chamber_A at 3Meter / Horizontal						
Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Remark
66.86	36.24	-11.66	24.58	40.00	-15.42	Peak
159.98	38.26	-9.89	28.37	43.50	-15.13	Peak
239.52	48.02	-11.16	36.86	46.00	-9.14	Peak
421.88	42.00	-5.67	36.34	46.00	-9.66	Peak
600.36	41.30	-1.83	39.47	46.00	-6.53	Peak
961.20	31.93	4.34	36.27	54.00	-17.73	Peak
1000.00	32.56	4.76	37.32	74.00	-36.68	Peak

966 Chamber_A at 3Meter / Vertical						
Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Remark
158.04	39.43	-9.92	29.51	43.50	-13.99	Peak
239.52	48.98	-11.16	37.81	46.00	-8.19	Peak
419.94	43.10	-5.73	37.37	46.00	-8.63	Peak
482.02	43.51	-4.26	39.25	46.00	-6.75	Peak
600.36	45.40	-1.83	43.57	46.00	-2.43	Peak
840.92	33.99	2.08	36.07	46.00	-9.93	Peak
901.06	32.00	3.43	35.43	46.00	-10.57	Peak
961.20	29.84	4.34	34.18	54.00	-19.82	Peak

Remark:

1. *Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit.*
2. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
3. *Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) – PreAmp.Gain (dB)*
4. *Result (dBuV/m) = Reading (dBuV) + Correction Factor (dB/m)*
5. *Margin (dB) = Remark result (dBuV/m) - Quasi-peak limit (dBuV/m).*

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

Above 1 GHz

Product Name	DreamTab HD8	**Test By**	Rueyyan Lin
Test Model	DMTAB-IN08A	**Test Date**	2014/03/25
Test Mode	GFSK TX / CH Low	**Temp. & Humidity**	25°C, 49%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1050.00	55.07	---	-4.36	50.71	---	74.00	54.00	-3.29	Peak
1252.00	54.03	---	-3.89	50.14	---	74.00	54.00	-3.86	Peak
1474.00	53.56	---	-3.36	50.20	---	74.00	54.00	-3.80	Peak
1622.00	53.31	---	-1.95	51.36	---	74.00	54.00	-2.64	Peak
3210.00	41.86	---	4.95	46.81	---	74.00	54.00	-7.19	Peak
3855.00	41.05	---	6.30	47.35	---	74.00	54.00	-6.65	Peak
4800.00	38.66	---	8.67	47.33	---	74.00	54.00	-6.67	Peak

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1014.00	54.85	---	-4.45	50.40	---	74.00	54.00	-3.60	Peak
1166.00	54.57	---	-4.09	50.48	---	74.00	54.00	-3.52	Peak
1436.00	54.26	---	-3.45	50.81	---	74.00	54.00	-3.19	Peak
1676.00	53.34	---	-1.36	51.98	---	74.00	54.00	-2.02	Peak
3270.00	41.73	---	5.00	46.74	---	74.00	54.00	-7.26	Peak
4005.00	41.96	---	6.77	48.73	---	74.00	54.00	-5.27	Peak
4800.00	38.23	---	8.67	46.90	---	74.00	54.00	-7.10	Peak

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Average test would be performed if the peak result were greater than the average limit.*
3. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
4. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
5. *Result = Reading + Correction Factor*
   Margin = Result – Limit
   Remark Peak = Result(PK) – Limit(AV)
   Remark AVG = Result(AV) – Limit(AV)

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

Product Name	DreamTab HD8	Test By	Rueyyan Lin
Test Model	DMTAB-IN08A	Test Date	2014/03/25
Test Mode	GFSK TX / CH Middle	Temp. & Humidity	25°C, 49%

966 Chamber_B at 3Meter / Horizontal

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1122.00	54.68	---	-4.19	50.49	---	74.00	54.00	-3.51	Peak
1314.00	55.29	---	-3.74	51.55	---	74.00	54.00	-2.45	Peak
1454.00	54.16	---	-3.41	50.75	---	74.00	54.00	-3.25	Peak
1616.00	53.61	---	-2.02	51.59	---	74.00	54.00	-2.41	Peak
3120.00	41.84	---	4.88	46.72	---	74.00	54.00	-7.28	Peak
4020.00	40.52	---	6.80	47.33	---	74.00	54.00	-6.67	Peak
4875.00	39.26	---	8.88	48.14	---	74.00	54.00	-5.86	Peak

966 Chamber_B at 3Meter / Vertical

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1016.00	55.28	---	-4.44	50.84	---	74.00	54.00	-3.16	Peak
1186.00	54.96	---	-4.04	50.92	---	74.00	54.00	-3.08	Peak
1370.00	54.25	---	-3.61	50.64	---	74.00	54.00	-3.36	Peak
1610.00	53.83	---	-2.09	51.75	---	74.00	54.00	-2.25	Peak
3270.00	42.77	---	5.00	47.77	---	74.00	54.00	-6.23	Peak
3720.00	41.20	---	5.88	47.08	---	74.00	54.00	-6.92	Peak
3855.00	40.81	---	6.30	47.12	---	74.00	54.00	-6.88	Peak
4860.00	38.47	---	8.84	47.31	---	74.00	54.00	-6.69	Peak

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Average test would be performed if the peak result were greater than the average limit.*
3. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
4. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
5. *Result = Reading + Correction Factor*
   Margin = Result – Limit
   Remark Peak = Result(PK) – Limit(AV)
   Remark AVG = Result(AV) – Limit(AV)

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

Product Name	DreamTab HD8	Test By	Rueyyan Lin
Test Model	DMTAB-IN08A	Test Date	2014/03/25
Test Mode	GFSK TX / CH High	Temp. & Humidity	25°C, 49%

966 Chamber_B at 3Meter / Horizontal

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1044.00	54.28	---	-4.38	49.90	---	74.00	54.00	-4.10	Peak
1192.00	54.96	---	-4.03	50.93	---	74.00	54.00	-3.07	Peak
1354.00	53.98	---	-3.64	50.34	---	74.00	54.00	-3.66	Peak
1630.00	53.16	---	-1.86	51.30	---	74.00	54.00	-2.70	Peak
3120.00	41.08	---	4.88	45.96	---	74.00	54.00	-8.04	Peak
3720.00	39.70	---	5.88	45.59	---	74.00	54.00	-8.41	Peak
4305.00	39.70	---	7.40	47.10	---	74.00	54.00	-6.90	Peak
4965.00	39.28	---	9.14	48.42	---	74.00	54.00	-5.58	Peak

966 Chamber_B at 3Meter / Vertical

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1032.00	55.39	---	-4.40	50.98	---	74.00	54.00	-3.02	Peak
1196.00	54.52	---	-4.02	50.50	---	74.00	54.00	-3.50	Peak
1378.00	53.52	---	-3.59	49.93	---	74.00	54.00	-4.07	Peak
1668.00	54.21	---	-1.45	52.76	---	74.00	54.00	-1.24	Peak
3270.00	42.93	---	5.00	47.93	---	74.00	54.00	-6.07	Peak
4005.00	42.39	---	6.77	49.16	---	74.00	54.00	-4.84	Peak
4305.00	40.44	---	7.40	47.84	---	74.00	54.00	-6.16	Peak
4965.00	40.25	---	9.14	49.39	---	74.00	54.00	-4.61	Peak

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Average test would be performed if the peak result were greater than the average limit.*
3. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
4. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
5. *Result = Reading + Correction Factor*
   Margin = Result – Limit
   Remark Peak = Result(PK) – Limit(AV)
   Remark AVG = Result(AV) – Limit(AV)

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

Product Name	DreamTab HD8	Test By	Rueyyan Lin
Test Model	DMTAB-IN08A	Test Date	2014/03/25
Test Mode	8-DPSK TX / CH Low	Temp. & Humidity	25°C, 49%

966 Chamber_B at 3Meter / Horizontal

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1048.00	54.79	---	-4.37	50.42	---	74.00	54.00	-3.58	Peak
1246.00	54.66	---	-3.90	50.76	---	74.00	54.00	-3.24	Peak
1490.00	54.05	---	-3.32	50.73	---	74.00	54.00	-3.27	Peak
1612.00	52.78	---	-2.06	50.72	---	74.00	54.00	-3.28	Peak
3195.00	41.69	---	4.94	46.63	---	74.00	54.00	-7.37	Peak
4170.00	39.96	---	7.12	47.08	---	74.00	54.00	-6.92	Peak
4860.00	38.69	---	8.84	47.53	---	74.00	54.00	-6.47	Peak

966 Chamber_B at 3Meter / Vertical

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1028.00	55.14	---	-4.41	50.73	---	74.00	54.00	-3.27	Peak
1184.00	54.63	---	-4.05	50.58	---	74.00	54.00	-3.42	Peak
1368.00	54.13	---	-3.61	50.52	---	74.00	54.00	-3.48	Peak
1602.00	53.96	---	-2.17	51.79	---	74.00	54.00	-2.21	Peak
3270.00	43.15	---	5.00	48.16	---	74.00	54.00	-5.84	Peak
3720.00	43.75	---	5.88	49.63	---	74.00	54.00	-4.37	Peak
3855.00	43.05	---	6.30	49.36	---	74.00	54.00	-4.64	Peak
4845.00	37.98	---	8.80	46.77	---	74.00	54.00	-7.23	Peak

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Average test would be performed if the peak result were greater than the average limit.*
3. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
4. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
5. *Result = Reading + Correction Factor*
   Margin = Result – Limit
   Remark Peak = Result(PK) – Limit(AV)
   Remark AVG = Result(AV) – Limit(AV)

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

Product Name	DreamTab HD8	Test By	Rueyyan Lin
Test Model	DMTAB-IN08A	Test Date	2014/03/25
Test Mode	8-DPSK TX / CH Middle	Temp. & Humidity	25°C, 49%

966 Chamber_B at 3Meter / Horizontal

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1036.00	54.78	---	-4.40	50.38	---	74.00	54.00	-3.62	Peak
1264.00	55.52	---	-3.86	51.66	---	74.00	54.00	-2.34	Peak
1434.00	53.43	---	-3.46	49.97	---	74.00	54.00	-4.03	Peak
1654.00	52.74	---	-1.60	51.14	---	74.00	54.00	-2.86	Peak
3240.00	41.58	---	4.98	46.55	---	74.00	54.00	-7.45	Peak
3855.00	41.50	---	6.30	47.80	---	74.00	54.00	-6.20	Peak
4905.00	39.63	---	8.97	48.60	---	74.00	54.00	-5.40	Peak

966 Chamber_B at 3Meter / Vertical

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1040.00	55.14	---	-4.39	50.76	---	74.00	54.00	-3.24	Peak
1252.00	54.67	---	-3.89	50.79	---	74.00	54.00	-3.21	Peak
1472.00	53.90	---	-3.37	50.54	---	74.00	54.00	-3.46	Peak
1664.00	53.41	---	-1.49	51.92	---	74.00	54.00	-2.08	Peak
3270.00	41.97	---	5.00	46.98	---	74.00	54.00	-7.02	Peak
3855.00	42.99	---	6.30	49.29	---	74.00	54.00	-4.71	Peak
4425.00	39.96	---	7.65	47.61	---	74.00	54.00	-6.39	Peak
4905.00	38.49	---	8.97	47.45	---	74.00	54.00	-6.55	Peak

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Average test would be performed if the peak result were greater than the average limit.*
3. *Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
4. *Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
5. *Result = Reading + Correction Factor*
   Margin = Result – Limit
   Remark Peak = Result(PK) – Limit(AV)
   Remark AVG = Result(AV) – Limit(AV)

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

Product Name	DreamTab HD8	Test By	Rueyyan Lin
Test Model	DMTAB-IN08A	Test Date	2014/03/25
Test Mode	8-DPSK TX / CH High	Temp. & Humidity	25°C, 49%

966 Chamber_B at 3Meter / Horizontal

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1038.00	55.13	---	-4.39	50.74	---	74.00	54.00	-3.26	Peak
1234.00	55.04	---	-3.93	51.12	---	74.00	54.00	-2.88	Peak
1464.00	54.43	---	-3.38	51.05	---	74.00	54.00	-2.95	Peak
1654.00	53.28	---	-1.60	51.68	---	74.00	54.00	-2.32	Peak
3225.00	41.25	---	4.96	46.21	---	74.00	54.00	-7.79	Peak
3870.00	41.29	---	6.35	47.64	---	74.00	54.00	-6.36	Peak
4170.00	40.23	---	7.12	47.34	---	74.00	54.00	-6.66	Peak
4950.00	38.86	---	9.10	47.95	---	74.00	54.00	-6.05	Peak

966 Chamber_B at 3Meter / Vertical

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1060.00	55.63	---	-4.34	51.29	---	74.00	54.00	-2.71	Peak
1264.00	55.09	---	-3.86	51.23	---	74.00	54.00	-2.77	Peak
1426.00	54.23	---	-3.47	50.75	---	74.00	54.00	-3.25	Peak
1668.00	52.65	---	-1.45	51.20	---	74.00	54.00	-2.80	Peak
3285.00	42.59	---	5.01	47.61	---	74.00	54.00	-6.39	Peak
3855.00	42.76	---	6.30	49.07	---	74.00	54.00	-4.93	Peak
4950.00	39.30	---	9.10	48.40	---	74.00	54.00	-5.60	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor
Margin = Result – Limit
Remark Peak = Result(PK) – Limit(AV)
Remark AVG = Result(AV) – Limit(AV)

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

Restricted Band Edges

Detector Mode : Peak **Polarity : Horizontal**

CH Low (GFSK)



Detector Mode : Average **Polarity : Horizontal**

CH Low (GFSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

Detector Mode : Peak **Polarity : Vertical**

CH Low (GFSK)



Detector Mode : Average **Polarity : Vertical**

CH Low (GFSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

Detector Mode : Peak **Polarity : Horizontal**

CH High (GFSK)



Detector Mode : Average **Polarity : Horizontal**

CH High (GFSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

Detector Mode : Peak **Polarity : Vertical**

CH High (GFSK)



Detector Mode : Average **Polarity : Vertical**

CH High (GFSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

Detector Mode : Peak **Polarity : Horizontal**

CH Low (8-DPSK)



Detector Mode : Average **Polarity : Horizontal**

CH Low (8-DPSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

Detector Mode : Peak **Polarity : Vertical**

CH Low (8-DPSK)



Detector Mode : Average **Polarity : Vertical**

CH Low (8-DPSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

Detector Mode : Peak **Polarity : Horizontal**

CH High (8-DPSK)



Detector Mode : Average **Polarity : Horizontal**

CH High (8-DPSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

Detector Mode : Peak **Polarity : Vertical**

CH High (8-DPSK)



Detector Mode : Average **Polarity : Vertical**

CH High (8-DPSK)



This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

7.9 CONDUCTED EMISSION

LIMITS

§ 15.207 (a) Except as shown in paragraph (b) and (c) this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 µH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Conducted Limit (dBµv)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5.00	56	46
5.00 - 30.0	60	50

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
L.I.S.N	SCHWARZBECK	NSLK 8127	8127-465	08/11/2014
L.I.S.N	SCHWARZBECK	NSLK 8127	8127-473	03/10/2015
EMI Receiver	ROHDE & SCHWARZ	ESCS 30	835418/008	10/16/2014
Pulse Limiter	ROHDE & SCHWARZ	ESH3-Z2	100117	07/01/2014

Remark: *Each piece of equipment is scheduled for calibration once a year.*

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

TEST SETUP





This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

TEST PROCEDURE

The basic test procedure was in accordance with ANSI C63.4:2009.

The test procedure is performed in a 4m × 3m × 2.4m (L×W×H) shielded room.

The EUT along with its peripherals were placed on a 1.0m (W) × 1.5m (L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.

The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.

The EUT was located so that the distance between the boundary of the EUT and the closest surface of the LISN is 0.8 m. Where a mains flexible cord was provided by the manufacturer shall be 1 m long, or if in excess of 1 m, the excess cable was folded back and forth as far as possible so as to form a bundle not exceeding 0.4 m in length.

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

TEST RESULTS

Product Name	DreamTab HD8	Test By	Alan Wu
Test Model	DMTAB-IN08A	Test Date	2014/03/26
Test Mode	Charge Mode + Play Video	Temp. & Humidity	21˚C, 50%

LINE



Freq. MHz	Corr. Factor dB	Reading Value dBuV Q.P.	Reading Value dBuV AV.	Emission Level dBuV Q.P.	Emission Level dBuV AV.	Limit dBuV Q.P.	Limit dBuV AV.	Margin dB Q.P.	Margin dB AV.
0.151	0.12	43.25	28.07	43.37	28.19	65.96	55.96	-22.59	-27.77
0.194	0.12	38.27	24.85	38.39	24.97	63.84	53.84	-25.45	-28.87
0.468	0.55	43.56	33.52	44.11	34.07	56.55	46.55	-12.44	-12.48
0.771	0.45	30.81	17.50	31.26	17.95	56.00	46.00	-24.74	-28.05
1.016	0.40	28.51	16.26	28.91	16.66	56.00	46.00	-27.09	-29.34
1.918	0.27	27.48	12.45	27.75	12.72	56.00	46.00	-28.25	-33.28

Remark:

1. Correction Factor = Insertion loss + Cable loss
2. Emission level = Reading Value + Correction factor
3. Margin value = Emission level – Limit value

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.

Product Name	DreamTab HD8	Test By	Alan Wu
Test Model	DMTAB-IN08A	Test Date	2014/03/26
Test Mode	Charge Mode + Play Video	Temp. & Humidity	21°C, 50%

NEUTRAL



Freq. MHz	Corr. Factor dB	Reading Value dBuV Q.P.	Reading Value dBuV AV.	Emission Level dBuV Q.P.	Emission Level dBuV AV.	Limit dBuV Q.P.	Limit dBuV AV.	Margin dB Q.P.	Margin dB AV.
0.154	0.05	41.45	28.75	41.50	28.80	65.78	55.78	-24.28	-26.98
0.186	0.05	37.77	26.05	37.82	26.10	64.20	54.20	-26.38	-28.10
0.471	0.09	45.07	40.35	45.16	40.44	56.50	46.50	-11.35	-6.07
0.735	0.11	32.91	23.74	33.02	23.85	56.00	46.00	-22.98	-22.15
1.810	0.14	31.32	23.16	31.46	23.30	56.00	46.00	-24.54	-22.70
2.692	0.15	29.95	23.56	30.10	23.71	56.00	46.00	-25.90	-22.29

Remark:

1. *Correction Factor = Insertion loss + Cable loss*
2. *Emission level = Reading Value + Correction factor*
3. *Margin value = Emission level – Limit value*

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.