

FCC ID: SJ8-VC160

Maximum Permissible Exposure (MPE)

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

BLE:

Measurement Result

Operation Frequency: 2402MHz~2480MHz

Power density limited: 1mW/ cm²

Antenna Type: FPC Antenna

Antenna gain:3.61 dBi;

R=20cm

mW=10^{^(dBm/10)}

antenna gain Numeric=10^{^(dBi/10)}= 10^{^(3.61/10)}=2.30

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
2402	BLE 1M	8.49	9±1	10	10.000	3.61	2.30	0.0046	1
2440		8.86	9±1	10	10.000	3.61	2.30	0.0046	1
2480		9	9±1	10	10.000	3.61	2.30	0.0046	1
2402	BLE 2M	8.42	9±1	10	10.000	3.61	2.30	0.0046	1
2440		8.83	9±1	10	10.000	3.61	2.30	0.0046	1
2480		8.98	9±1	10	10.000	3.61	2.30	0.0046	1

2.4GWIFI:

Measurement Result

Operation Frequency: 2412MHz~2462MHz (20M)
2422MHz~2452MHz (40M)

Power density limited: 1mW/ cm²

Antenna Type: FPC Antenna

Antenna gain:3.61 dBi;

R=20cm

mW=10^{^(dBm/10)}

antenna gain Numeric=10^{^(dBi/10)}= 10^{^(3.61/10)}=2.30

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
2412	11b	14.47	14±1	15	31.623	3.61	2.30	0.0144	1
2437		13.43	14±1	15	31.623	3.61	2.30	0.0144	1
2462		13.78	14±1	15	31.623	3.61	2.30	0.0144	1
2412	11g	14.71	15±1	16	39.811	3.61	2.30	0.0182	1
2437		15.57	15±1	16	39.811	3.61	2.30	0.0182	1
2462		14.99	15±1	16	39.811	3.61	2.30	0.0182	1
2412	11n20	11.73	12±1	13	19.953	3.61	2.30	0.0091	1
2437		12.68	12±1	13	19.953	3.61	2.30	0.0091	1
2462		11.74	12±1	13	19.953	3.61	2.30	0.0091	1
2422	11n40	11.47	12±1	13	19.953	3.61	2.30	0.0091	1
2437		12.01	12±1	13	19.953	3.61	2.30	0.0091	1
2452		11.97	12±1	13	19.953	3.61	2.30	0.0091	1
2412	11ax20	11.68	12±1	13	19.953	3.61	2.30	0.0091	1
2437		12.5	12±1	13	19.953	3.61	2.30	0.0091	1
2462		11.64	12±1	13	19.953	3.61	2.30	0.0091	1
2422	11ax40	11.29	12±1	13	19.953	3.61	2.30	0.0091	1
2437		11.67	12±1	13	19.953	3.61	2.30	0.0091	1
2452		11.28	12±1	13	19.953	3.61	2.30	0.0091	1

5G WIFI:

Operation Frequency:

U-NII-1: 5150 MHz ~5250MHz

U-NII-2A: 5250MHz~5350MHz

U-NII-2C: 5470MHz~5725MHz

U-NII-3: 5725 MHz ~5850 MHz

Power density limited: 1mW/cm

Antenna Type: FPC Antenna

Antenna gain: **3.69dBi**

R=20cm

$mW=10^{(dBm/10)}$

5.2 Max antenna gain Numeric= $10^{(dBi/10)}=10^{(3.69/10)}=2.34$

5.2G

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density limits
		(dBm)		tune-up power		Gain			(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
5180	a	14.7	15±1	16	39.811	3.69	2.34	0.0185	1
5200	a	14.84	15±1	16	39.811	3.69	2.34	0.0185	1
5240	a	14.99	15±1	16	39.811	3.69	2.34	0.0185	1
5180	n20	14.48	15±1	16	39.811	3.69	2.34	0.0185	1
5200	n20	14.95	15±1	16	39.811	3.69	2.34	0.0185	1
5240	n20	15.13	15±1	16	39.811	3.69	2.34	0.0185	1
5190	n40	14.75	15±1	16	39.811	3.69	2.34	0.0185	1
5230	n40	14.9	15±1	16	39.811	3.69	2.34	0.0185	1
5180	ac20	14.54	15±1	16	39.811	3.69	2.34	0.0185	1
5200	ac20	14.63	15±1	16	39.811	3.69	2.34	0.0185	1
5240	ac20	15.36	15±1	16	39.811	3.69	2.34	0.0185	1
5190	ac40	14.47	15±1	16	39.811	3.69	2.34	0.0185	1
5230	ac40	15.13	15±1	16	39.811	3.69	2.34	0.0185	1
5180	ax20	14.62	15±1	16	39.811	3.69	2.34	0.0185	1
5200	ax20	14.82	15±1	16	39.811	3.69	2.34	0.0185	1
5240	ax20	15.22	15±1	16	39.811	3.69	2.34	0.0185	1
5190	ax40	14.46	15±1	16	39.811	3.69	2.34	0.0185	1
5230	ax40	14.94	15±1	16	39.811	3.69	2.34	0.0185	1

5.3G

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric	(mW/cm2)	(mW/cm2)
5260	a	13.2	13±1	14	25.119	3.69	2.34	0.0117	1
5280	a	13.12	13±1	14	25.119	3.69	2.34	0.0117	1
5320	a	13.11	13±1	14	25.119	3.69	2.34	0.0117	1
5260	n20	13.07	13±1	14	25.119	3.69	2.34	0.0117	1
5280	n20	13.05	13±1	14	25.119	3.69	2.34	0.0117	1
5320	n20	13.25	13±1	14	25.119	3.69	2.34	0.0117	1
5270	n40	13.25	13±1	14	25.119	3.69	2.34	0.0117	1
5310	n40	12.99	13±1	14	25.119	3.69	2.34	0.0117	1
5260	ac20	13.02	13±1	14	25.119	3.69	2.34	0.0117	1
5280	ac20	13.22	13±1	14	25.119	3.69	2.34	0.0117	1
5320	ac20	13.06	13±1	14	25.119	3.69	2.34	0.0117	1
5270	ac40	13.33	13±1	14	25.119	3.69	2.34	0.0117	1
5310	ac40	12.85	13±1	14	25.119	3.69	2.34	0.0117	1
5260	ax20	12.84	13±1	14	25.119	3.69	2.34	0.0117	1
5280	ax20	13.13	13±1	14	25.119	3.69	2.34	0.0117	1
5320	ax20	12.98	13±1	14	25.119	3.69	2.34	0.0117	1
5270	ax40	13.23	13±1	14	25.119	3.69	2.34	0.0117	1
5310	ax40	12.88	13±1	14	25.119	3.69	2.34	0.0117	1

5.6G

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm2)	Power density Limits
		(dBm)		tune-up power		Gain			(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
5500	a	13.43	13±1	14	25.119	1.62	1.45	0.0073	1
5600	a	12.42	13±1	14	25.119	1.62	1.45	0.0073	1
5700	a	13.12	13±1	14	25.119	1.62	1.45	0.0073	1
5500	n20	13.28	13±1	14	25.119	1.62	1.45	0.0073	1
5600	n20	12.43	13±1	14	25.119	1.62	1.45	0.0073	1
5700	n20	13.18	13±1	14	25.119	1.62	1.45	0.0073	1
5510	n40	12.96	13±1	14	25.119	1.62	1.45	0.0073	1
5590	n40	12.55	13±1	14	25.119	1.62	1.45	0.0073	1
5670	n40	13.32	13±1	14	25.119	1.62	1.45	0.0073	1
5500	ac20	13.13	13±1	14	25.119	1.62	1.45	0.0073	1
5600	ac20	12.23	13±1	14	25.119	1.62	1.45	0.0073	1
5700	ac20	13.44	13±1	14	25.119	1.62	1.45	0.0073	1
5510	ac40	13.21	13±1	14	25.119	1.62	1.45	0.0073	1
5590	ac40	12.45	13±1	14	25.119	1.62	1.45	0.0073	1
5670	ac40	13.23	13±1	14	25.119	1.62	1.45	0.0073	1
5500	ax20	13.11	13±1	14	25.119	1.62	1.45	0.0073	1
5600	ax20	12.62	13±1	14	25.119	1.62	1.45	0.0073	1
5700	ax20	13.24	13±1	14	25.119	1.62	1.45	0.0073	1
5510	ax40	13.07	13±1	14	25.119	1.62	1.45	0.0073	1
5590	ax40	12.39	13±1	14	25.119	1.62	1.45	0.0073	1
5670	ax40	13.42	13±1	14	25.119	1.62	1.45	0.0073	1

5.8G

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain			(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
5745	a	13.53	13±1	14	25.119	3.69	2.34	0.0117	1
5785	a	13.67	13±1	14	25.119	3.69	2.34	0.0117	1
5825	a	13.29	13±1	14	25.119	3.69	2.34	0.0117	1
5745	n20	13.33	13±1	14	25.119	3.69	2.34	0.0117	1
5785	n20	13.92	13±1	14	25.119	3.69	2.34	0.0117	1
5825	n20	13.19	13±1	14	25.119	3.69	2.34	0.0117	1
5755	n40	13.59	13±1	14	25.119	3.69	2.34	0.0117	1
5795	n40	13.72	13±1	14	25.119	3.69	2.34	0.0117	1
5745	ac20	13.37	13±1	14	25.119	3.69	2.34	0.0117	1
5785	ac20	13.75	13±1	14	25.119	3.69	2.34	0.0117	1
5825	ac20	13.16	13±1	14	25.119	3.69	2.34	0.0117	1
5755	ac40	13.65	13±1	14	25.119	3.69	2.34	0.0117	1
5795	ac40	13.75	13±1	14	25.119	3.69	2.34	0.0117	1
5745	ax20	13.61	13±1	14	25.119	3.69	2.34	0.0117	1
5785	ax20	13.89	13±1	14	25.119	3.69	2.34	0.0117	1
5825	ax20	13.24	13±1	14	25.119	3.69	2.34	0.0117	1
5755	ax40	13.52	13±1	14	25.119	3.69	2.34	0.0117	1

SIMULTANEOUS TRANSMISSIONS

When a number of sources at different frequencies, and/or broadband sources, contribute to the total exposure, it becomes necessary to weigh each contribution relative to the MPE. To comply with the MPE, the fraction of the MPE in terms of E^2 , H^2 (or power density) incurred within each frequency interval should be determined and the sum of all such fractions should not exceed unity. In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity. That is

$$\sum_{i=1}^n \frac{S_i}{MPE_i} \leq 1$$

Max. SIMULTANEOUS TRANSMISSIONS MODE

Band	Evaluation result	Power density Limits	Evaluation result	Power density Limits	Verdict
	(mW/cm2)	(mW/cm2)			
Wi-Fi 2.4G + BT	0.0046	1	0.019000	1	PASS
	0.0144	1			

Signature:

Date: 2025-12-31



NAME AND TITLE (Please print or type): alex li/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.