

FCC ID: SJ8-WS26

Maximum Permissible Exposure (MPE)

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

BT:

Measurement Result

Operation Frequency: 2402MHz~2480MHz

Power density limited: 1mW/ cm²

Antenna Type: External Antenna

Antenna gain: 1.69dBi,

R=20cm

mW=10^{^(dBi/10)}

Max antenna gain Numeric=10^{^(dBi/10)}=10^{^(1.69/10)}=1.48

BR EDR

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK	3.33	4±1	5	3.162	1.69	1.48	0.0009	1
2441		3.73	4±1	5	3.162	1.69	1.48	0.0009	1
2480		4.09	4±1	5	3.162	1.69	1.48	0.0009	1
2402	π/4-DQPSK	2.77	3±1	4	2.512	1.69	1.48	0.0007	1
2441		3.2	3±1	4	2.512	1.69	1.48	0.0007	1
2480		3.56	3±1	4	2.512	1.69	1.48	0.0007	1
2402	8-DPSK	3.05	3±1	4	2.512	1.69	1.48	0.0007	1
2441		3.43	3±1	4	2.512	1.69	1.48	0.0007	1
2480		3.73	3±1	4	2.512	1.69	1.48	0.0007	1

BLE

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK(1M)	3.3	4±1	5	3.162	1.69	1.48	0.0009	1
2440		3.37	4±1	5	3.162	1.69	1.48	0.0009	1
2480		3.98	4±1	5	3.162	1.69	1.48	0.0009	1
2402	GFSK(2M)	3.19	4±1	5	3.162	1.69	1.48	0.0009	1
2440		3.25	4±1	5	3.162	1.69	1.48	0.0009	1
2480		3.88	4±1	5	3.162	1.69	1.48	0.0009	1

2.4G WIFI:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,
WIFI 802.11n HT40:2422-2452MHz
Power density limited: 1mW/ cm²

Antenna Type: External Antenna

Antenna gain: 1.69dBi,

R=20cm

$mW=10^{(dBm/10)}$

Max antenna gain Numeric= $10^{(dBi/10)}=10^{(1.69/10)}=1.48$

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
2412	802.11b	16.06	16±1	17	50.119	1.69	1.48	0.0147	1
2437		16.52	16±1	17	50.119	1.69	1.48	0.0147	1
2462		15.63	16±1	17	50.119	1.69	1.48	0.0147	1
2412	802.11g	11.27	11±1	12	15.849	1.69	1.48	0.0047	1
2437		11.85	11±1	12	15.849	1.69	1.48	0.0047	1
2462		11.08	11±1	12	15.849	1.69	1.48	0.0047	1
2412	802.11n H20	11.11	11±1	12	15.849	1.69	1.48	0.0047	1
2437		11.85	11±1	12	15.849	1.69	1.48	0.0047	1
2462		10.95	11±1	12	15.849	1.69	1.48	0.0047	1
2422	802.11n(H T40)	11.05	11±1	12	15.849	1.69	1.48	0.0047	1
2437		11.44	11±1	12	15.849	1.69	1.48	0.0047	1
2452		11.06	11±1	12	15.849	1.69	1.48	0.0047	1
2412	802.11 ax20	11.36	11±1	12	15.849	1.69	1.48	0.0047	1
2437		11.58	11±1	12	15.849	1.69	1.48	0.0047	1
2462		11.23	11±1	12	15.849	1.69	1.48	0.0047	1
2422	802.11ax4 0	10.06	11±1	12	15.849	1.69	1.48	0.0047	1
2437		11.05	11±1	12	15.849	1.69	1.48	0.0047	1
2452		11.42	11±1	12	15.849	1.69	1.48	0.0047	1

5G WIFI:

Operation Frequency: WIFI 802.11a/ax/ac/n(HT20): 5180-5240MHz; 5745-5825MHz;

WIFI 802.11ax/ac/n(HT40): 5190-5230MHz;5755-5795MHz;

Power density limited: 1mW/cm

Antenna Type: External Antenna

Antenna gain: **1.62dBi**

R=20cm

$mW=10^{(dBm/10)}$

5.2 Max antenna gain $Numeric=10^{(dBi/10)}=10^{(1.62/10)}=1.45$

5.2G

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain			(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
5180	a	11.17	12±1	13	19.953	1.62	1.45	0.0058	1
5200	a	11.41	12±1	13	19.953	1.62	1.45	0.0058	1
5240	a	11.87	12±1	13	19.953	1.62	1.45	0.0058	1
5180	n20	11.35	12±1	13	19.953	1.62	1.45	0.0058	1
5200	n20	11.28	12±1	13	19.953	1.62	1.45	0.0058	1
5240	n20	11.75	12±1	13	19.953	1.62	1.45	0.0058	1
5190	n40	10.95	12±1	13	19.953	1.62	1.45	0.0058	1
5230	n40	11.48	12±1	13	19.953	1.62	1.45	0.0058	1
5180	ac20	11.62	12±1	13	19.953	1.62	1.45	0.0058	1
5200	ac20	11.57	12±1	13	19.953	1.62	1.45	0.0058	1
5240	ac20	12	12±1	13	19.953	1.62	1.45	0.0058	1
5190	ac40	11.06	12±1	13	19.953	1.62	1.45	0.0058	1
5230	ac40	12.05	12±1	13	19.953	1.62	1.45	0.0058	1
5180	ax20	11.35	12±1	13	19.953	1.62	1.45	0.0058	1
5200	ax20	11.52	12±1	13	19.953	1.62	1.45	0.0058	1
5240	ax20	12.15	12±1	13	19.953	1.62	1.45	0.0058	1
5190	ax40	11.12	12±1	13	19.953	1.62	1.45	0.0058	1
5230	ax40	11.7	12±1	13	19.953	1.62	1.45	0.0058	1

5.3G

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain			
				(dBm)	(dBm)	(mW)	(dBi)	Numeric	(mW/cm2)
5260	a	12.23	12±1	13	19.953	1.62	1.45	0.0058	1
5280	a	11.45	12±1	13	19.953	1.62	1.45	0.0058	1
5320	a	12.59	12±1	13	19.953	1.62	1.45	0.0058	1
5260	n20	12.38	12±1	13	19.953	1.62	1.45	0.0058	1
5280	n20	12.05	12±1	13	19.953	1.62	1.45	0.0058	1
5320	n20	12.43	12±1	13	19.953	1.62	1.45	0.0058	1
5270	n40	11.92	12±1	13	19.953	1.62	1.45	0.0058	1
5310	n40	12.3	12±1	13	19.953	1.62	1.45	0.0058	1
5260	ac20	12.19	12±1	13	19.953	1.62	1.45	0.0058	1
5280	ac20	11.66	12±1	13	19.953	1.62	1.45	0.0058	1
5320	ac20	12.07	12±1	13	19.953	1.62	1.45	0.0058	1
5270	ac40	11.97	12±1	13	19.953	1.62	1.45	0.0058	1
5310	ac40	11.92	12±1	13	19.953	1.62	1.45	0.0058	1
5260	ax20	11.51	12±1	13	19.953	1.62	1.45	0.0058	1
5280	ax20	11.64	12±1	13	19.953	1.62	1.45	0.0058	1
5320	ax20	12.15	12±1	13	19.953	1.62	1.45	0.0058	1
5270	ax40	11.94	12±1	13	19.953	1.62	1.45	0.0058	1
5310	ax40	12.07	12±1	13	19.953	1.62	1.45	0.0058	1

5.6G

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric	(mW/cm2)	(mW/cm2)
5500	a	11.87	12±1	13	19.953	1.62	1.45	0.0058	1
5600	a	11.99	12±1	13	19.953	1.62	1.45	0.0058	1
5700	a	11.7	12±1	13	19.953	1.62	1.45	0.0058	1
5500	n20	11.75	12±1	13	19.953	1.62	1.45	0.0058	1
5600	n20	11.94	12±1	13	19.953	1.62	1.45	0.0058	1
5700	n20	11.68	12±1	13	19.953	1.62	1.45	0.0058	1
5510	n40	11.72	12±1	13	19.953	1.62	1.45	0.0058	1
5590	n40	11.92	12±1	13	19.953	1.62	1.45	0.0058	1
5670	n40	11.88	12±1	13	19.953	1.62	1.45	0.0058	1
5500	ac20	11.93	12±1	13	19.953	1.62	1.45	0.0058	1
5600	ac20	11.93	12±1	13	19.953	1.62	1.45	0.0058	1
5700	ac20	11.72	12±1	13	19.953	1.62	1.45	0.0058	1
5510	ac40	11.72	12±1	13	19.953	1.62	1.45	0.0058	1
5590	ac40	11.77	12±1	13	19.953	1.62	1.45	0.0058	1
5670	ac40	11.95	12±1	13	19.953	1.62	1.45	0.0058	1
5500	ax20	11.82	12±1	13	19.953	1.62	1.45	0.0058	1
5600	ax20	11.9	12±1	13	19.953	1.62	1.45	0.0058	1
5700	ax20	11.48	12±1	13	19.953	1.62	1.45	0.0058	1
5510	ax40	11.54	12±1	13	19.953	1.62	1.45	0.0058	1
5590	ax40	11.9	12±1	13	19.953	1.62	1.45	0.0058	1
5670	ax40	12.02	12±1	13	19.953	1.62	1.45	0.0058	1

5.8G

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
5745	a	11.45	12±1	13	19.953	1.62	1.45	0.0058	1
5785	a	11.23	12±1	13	19.953	1.62	1.45	0.0058	1
5825	a	10.75	12±1	13	19.953	1.62	1.45	0.0058	1
5745	n20	11.33	12±1	13	19.953	1.62	1.45	0.0058	1
5785	n20	11.39	12±1	13	19.953	1.62	1.45	0.0058	1
5825	n20	10.89	12±1	13	19.953	1.62	1.45	0.0058	1
5755	n40	11.48	12±1	13	19.953	1.62	1.45	0.0058	1
5795	n40	11.22	12±1	13	19.953	1.62	1.45	0.0058	1
5745	ac20	11.33	12±1	13	19.953	1.62	1.45	0.0058	1
5785	ac20	11.55	12±1	13	19.953	1.62	1.45	0.0058	1
5825	ac20	10.69	12±1	13	19.953	1.62	1.45	0.0058	1
5755	ac40	11.32	12±1	13	19.953	1.62	1.45	0.0058	1
5795	ac40	11.15	12±1	13	19.953	1.62	1.45	0.0058	1
5745	ax20	11.36	12±1	13	19.953	1.62	1.45	0.0058	1
5785	ax20	11.35	12±1	13	19.953	1.62	1.45	0.0058	1
5825	ax20	10.65	12±1	13	19.953	1.62	1.45	0.0058	1
5755	ax40	11.27	12±1	13	19.953	1.62	1.45	0.0058	1
5795	ax40	11.16	12±1	13	19.953	1.62	1.45	0.0058	1

SIMULTANEOUS TRANSMISSIONS

When a number of sources at different frequencies, and/or broadband sources, contribute to the total exposure, it becomes necessary to weigh each contribution relative to the MPE. To comply with the MPE, the fraction of the MPE in terms of E^2 , H^2 (or power density) incurred within each frequency interval should be determined and the sum of all such fractions should not exceed unity. In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity. That is

$$\sum_{i=1}^n \frac{S_i}{MPE_i} \leq 1$$

Max. SIMULTANEOUS TRANSMISSIONS MODE

Band	Evaluation result	Power density Limits	Evaluation result	Power density Limits	Verdict
	(mW/cm2)	(mW/cm2)			
Wi-Fi 2.4G + BT	0.0009	1	0.015600	1	PASS
	0.0147	1			

Signature:

Date: 2025-11-20



NAME AND TITLE (Please print or type): alex li/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.