
PROG
J1
5P1.25MM
U1
ATTINY26L-8SC
PB0-MOSI
PB1-MISO
PB2-SCK
PB3
VCC
GND
PB4-XTL1-AD7
PB5-XTL2-AD8
PB6-AD9-INT0
/RESET-AD10
PA0-AD0
PA1-AD1
PA2-AD2
PA3-AREF
GND
AVCC
PA4-AD3
PA5-AD4
PA6-AD5-AIN0
PA7-AD6-AIN1
LED SMT 0603 RED (8)
D1
87.7 MHZ
D2
D3
D4
D5
D6
D7
D8
R1
560 OHM
FREQ SELECTION
+5V
C20
0.1MFD
SW1
TACT-SW
7.60MHZ
C1
27PF
C2
27PF
Y1
10MFD/16
C15
C19
0.1MFD
C5
1MFD
C3
100PF
R3
220
R5
2.2K
R6
1K
C10
2200PF
C13
150PF
U2
BH1415F
LCHIN
PETC-L
LPF-L
PILOT
MUTE
DATA
CLOCK
CE
XTL2
XTL1
PLLVCC
RCHIN
PETC-R
LTC-R
FLTR
COMP
GND
PLLDET
VCC
RFOSC
RFGND
RFOUT
R7
2.2K
C4
R4
220
R8
1K
100PF
C6
1MFD
2200PF
C11
C14
150PF
C29
10MFD
C7
1MFD
C30
0.01MFD
C17
1000PF
R13
1K
C8
1MFD
R14
10K
R17
20K
C16
1000PF
R11
NU
R10
NU
R12
NU
0.100UH
L1
0.100UH
L2
L3
NU
C22
NU
C23
NU
C24
NU
L4
0.068UH
3-10PF
C26
C34
33PF
C28
22PF
C37
10PF
C32
330PF
R15
10K
R16
10K
C31
0.047MFD
R18
100 OHM
C33
R20
3.3K
R21
3.3K
100MFD/6.3
R9
2.2K
R22
220 OHM
C9
1MFD
Q1
MPSA13
C12
2200PF
J7
TEST POINT
D9
BB200
NC
J10
(NOT INSTALLED)
W1
SMT-JUMPER
JUMPER WIRE
L5
BEAD
L
L6
BEAD
R
L7
4.7UH
A
J11
C27
33PF
C25
NU
1 TOP 30
IPOD2 CONN
AGND 29
R-CH 28
L-CH 27
+12V 11
GND 1
AD 20
GND 30
AID 10
100K,1%
152847D CABLE ASSY
J2
J3
J4
10MFD/16
J5
J6
C39
L8
BEAD 11 OHM@100MHZ
L9
BEAD 11 OHM@100MHZ
R23
47 OHM
C35
10MFD/16
J8
CONPAD2
IPOD CHARGER
J9
CONPAD2
D10
1N4148
C18
1000pf
C38
470PF
U3
NJM78L05UA
(SOT-89)
IN
OUT
GND
C21
0.1MFD
+5V
R2 = 1k, C26 = 10pf, C30 = 100pf.
With above configuration, if RF power output is still too high, increase value of R2. If RF output is too low, decrease value of R2.