



Registration
No. 788871

TEST REPORT FOR WLAN TESTING

Report No: SRTC2018-9004(F)-18052301(F)

Product Name: Data terminal

Product Model: N5000

Applicant: Fujian Newland Auto-ID Tech. Co.,Ltd.

Manufacturer: Fujian Newland Auto-ID Tech. Co.,Ltd.

Specification: FCC Part 15, Subpart C (2018)

FCC ID: SL9N5000

The State Radio_monitoring_center Testing Center (SRTC)

15th Building, No.30, Shixing Street, Shijingshan District,

Beijing, P.R.China

Tel: 86-10-57996183 Fax: 86-10-57996388

CONTENTS

1. GENERAL INFORMATION.....	2
@ HYPERLINK\L "_Toc516070609" 1.1 NOTES OF THE TEST REPORT.....	2
1.2 INFORMATION ABOUT THE TESTING LABORATORY	2
1.3 APPLICANT'S DETAILS	2
1.4 MANUFACTURER'S DETAILS	2
1.5 TEST ENVIRONMENT	3
2 DESCRIPTION OF THE DEVICE UNDER TEST.....	4
2.1 FINAL EQUIPMENT BUILD STATUS.....	4
2.2 DESCRIPTION OF TEST MODES	5
2.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	5
2.3 DUTY CYCLE OF TEST SIGNAL.....	6
2.4 EUT OPERATING CONDITIONS	7
3 REFERENCE SPECIFICATION	8
4 KEY TO NOTES AND RESULT CODES.....	9
5 RESULT SUMMARY	10
6 TEST RESULT	11
6.1 PEAK POWER OUTPUT.....	11
6.2 OCCUPIED BANDWIDTH.....	12
6.3 TRANSMITTER POWER SPECTRAL DENSITY.....	13
6.4 CONDUCTED OUT OF BAND EMISSION MEASUREMENT.....	14
6.5 BAND-EDGE MEASUREMENT	15
6.6 SPURIOUS RADIATED EMISSIONS.....	16
6.7 AC POWER LINE CONDUCTED EMISSION	21
7 MEASUREMENT UNCERTAINTIES	23
8 TEST EQUIPMENTS	24
APPENDIX A – TEST DATA OF CONDUCTED EMISSION	25
APPENDIX B – TEST DATA OF RADIATED EMISSION	48

1. GENERAL INFORMATION

1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio_monitoring_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested.

1.2 Information about the testing laboratory

Company:	The State Radio_monitoring_center Testing Center (SRTC)
Address:	15th Building, No.30 Shixing Street, Shijingshan District, P.R.China
City:	Beijing
Country or Region:	P.R.China
Contacted person:	Liu Jia
Tel:	+86 10 57996183
Fax:	+86 10 57996388
Email:	liujiaf@srtc.org.cn

1.3 Applicant's details

Company:	Fujian Newland Auto-ID Tech. Co.,Ltd.
Address:	Newland Science & Technology Park, No.1 Rujiang West Rd,Mawei,Fuzhou,Fujian, P.R.China
City:	Fuzhou
Country or Region:	P.R.China
Contacted person:	Huang Junjun
Tel:	0591-83979235
Fax:	0591-83979250
Email:	hjj@nlscan.com

1.4 Manufacturer's details

Company:	Fujian Newland Auto-ID Tech. Co.,Ltd.
Address:	Newland Science & Technology Park, No.1 Rujiang West Rd,Mawei,Fuzhou,Fujian, P.R.China
City:	Fuzhou
Country or Region:	P.R.China
Contacted person:	Huang Junjun
Tel:	0591-83979235
Fax:	0591-83979250
Email:	hjj@nlscan.com

1.5 Test Environment

Date of Receipt of test sample at SRTC:	2018-05-23
Testing Start Date:	2018-05-25
Testing End Date:	2018-06-25

Environmental Data:	Temperature (°C)	Humidity (%)
Ambient	25	30

Normal Supply Voltage (V d.c.):	3.80
---------------------------------	------

2 DESCRIPTION OF THE DEVICE UNDER TEST

2.1 Final Equipment Build Status

Frequency Band	2.412GHz~2.462GHz
Number of Channel For 20MHz	11
Number of Channel For 40MHz	7
Modulation Type	DBPSK/DQPSK/CCK/BPSK/QPSK/16QAM/64QAM
Duplex Mode	TDD
Channel Spacing	5MHz
Data Rate	1Mbps/2Mbps/5.5Mbps/11Mbps/6Mbps/9Mbps/12Mbps /18Mbps/24Mbps/36Mbps/48Mbps/54Mbps/6.5Mbps /13.0Mbps/13.5Mbps/19.5Mbps/26.0Mbps/27.0Mbps /39.0Mbps/40.5Mbps/52.0Mbps/58.5Mbps/65Mbps /81.0Mbps/108.0Mbps/121.5Mbps/135.0Mbps
Duty Cycles	98%
Power Supply	Battery/AC adapter
Rated Power Supply Voltage	3.80V
HW Version	P0
SW Version	v1.1.1_03
IMEI	868501020051809
Antenna type	Refer to Note
Antenna connector	Refer to Note

Note:

The antenna provide to the EUT, please refer to the following table:

Brand	Model	Antenna gain	Frequency range(GHz)	Antenna type	Connector Type
N/A	N/A	1.3dBi	2.402GHz~2.480GHz	PIFA Antenna	N/A
Manufacturers ensure that their designs will not be modified by the user or third parties arbitrary antenna parameters and performance.					

2.2 Description of Test Modes

11 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	---	---

2.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE $\geq$ 1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE 1G**: Radiated Emission above 1GHz

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Radiated Emission Test (Above 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
1 to 11	Low、mid、high	DBPSK/ BPSK	1,6,6.5,13.5

Radiated Emission Test (Below 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
1 to 11	Low、 mid、 high	DBPSK/ BPSK	1,6,6.5,13.5

Power Line Conducted Emission Test:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
1 to 11	6	DBPSK	1

Antenna Port Conducted Measurement:

This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
1 to 11	1,3, 6,9, 11	DBPSK/ BPSK	1,6,6.5,13.5

2.3 Duty Cycle of Test Signal

Modulation Type	Data Rate	Duty Cycle	Correction factor
11b	1Mbps	98.5%	N/A
11g	6Mbps	93.5%	0.29dB
11n(HT20)	6.5Mbps	93.1%	0.31dB
11n(HT40)	13.5Mbps	87.2%	0.59dB
Duty cycle of test signal is $> 98\%$, duty factor shall not be considered. Correction factor = $10 * \log(1/\text{duty cycle})$			

2.4 EUT Operating conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually. EUT uses USB charging to work.

The following support equipment was used to exercise the DUT during testing:

Equipment	Charger
Manufacturer	SHENZHEN FUJIA APPLIANCE CO., LTD.
Model Number	FJ-SW1260502000DN
Serial Number	---

Equipment	Battery
Manufacturer	SHENZHEN CHOLIPower TECHNOLOGY CO., LTD.
Model Number	CLP519/n5000 3.8V 2500mAh
Serial Number	---

3 REFERENCE SPECIFICATION

Specification	Version	Title
15.35	2018	Measurement detector functions and bandwidths.
15.209	2018	Radiated emission limits; general requirements.
15.247	2018	Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.
15.203	2018	Antenna requirement
ANSI C63.10	2013	Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
KDB 558074	April 5, 2017	GUIDANCE FOR PERFORMING COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEMS (DTS) OPERATING UNDER SECTION 15.247


4 KEY TO NOTES AND RESULT CODES

The following are the definition of the test result.

Code	Meaning
PASS	Test result shows that the requirements of the relevant specification have been met.
FAIL	Test result shows that the requirements of the relevant specification have not been met.
N/T	Test case is not tested.
NTC	Nominal voltage, Normal Temperature
HV	High voltage, Normal Temperature
LV	Low voltage, Normal Temperature
HTHV	high voltage, High Temperature
LTHV	High voltage, Low Temperature
HTLV	Low voltage, High Temperature
LTLV	Low voltage, Low Temperature

5 RESULT SUMMARY

No.	Test case	Reference	Verdict
1	Peak Power Output	15.247(a)(2)	Pass
2	Occupied Bandwidth	15.247(b)(3))	Pass
3	Transmitter Power Spectral Density	15.247(e))	Pass
4	Conducted Out of band emission measurement	15.247(d)	Pass
5	Band Edge	15.247(d)	Pass
6	Spurious Radiated Emissions	15.247(d)/15.35(b)/15.209	Pass
7	AC Power line Conducted Emission	15.207	Pass
8	Antenna requirement	15.203	Pass (refer to section 2.1)

This Test Report Is Issued by: Mr. Peng Zhen 	Checked by: Mr. Li Bin 
Tested by: Mr. HeDengshun 	Issued date: 20180625

6 TEST RESULT

6.1 Peak Power Output

6.1.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

6.1.2 Test Description

A transmitter antenna terminal of EUT is connected to the power meter. Measurement is made using a broadband power meter capable of making peak and average measurements while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies.

6.1.3 Test limit

FCC Part15.247(b)(3)

The maximum permissible conducted output power is 1 Watt.

Used conversion factor: Limit (dBm) = 10 log (Limit (W)/1mW)

==> Maximum Output Power: 30.0 dBm

6.1.4 Test Procedure Used


KDB 558074 D01 DTS Meas Guidance v04 - Section 9.1.3

6.1.5 Test Settings

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

6.1.6 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.1.7 Test result

The test results are shown in Appendix A .

6.2 Occupied Bandwidth

6.2.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

6.2.2 Test Description

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer and Bluetooth test set via a power splitter with a known loss. Which connected to the transmitter antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies. All modes of operation were investigated and the worst case configuration results are reported in this section.

6.2.3 Test limit

FCC Part15.247(a)(2)

The minimum permissible 6dB bandwidth is 500 kHz

6.2.4 Test Procedure Used


KDB 558074 D01 DTS Meas Guidance v04 – Section 8.1 Option 1

6.2.5 Test Settings

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.2.6 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.2.7 Test result

The test results are shown in Appendix A.

6.3 Transmitter Power Spectral Density

6.3.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

6.3.2 Test Description

The peak power density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies. All data rates were investigated and the worst case configuration results are reported in this section.

6.3.3 Test limit

FCC Part15.247(e)

The maximum permissible power spectral density is 8.0 dBm in any 3 kHz band.

6.3.4 Test Procedure Used


KDB 558074 D01 DTS Meas Guidance v04 Section 10.2.

6.3.5 Test Settings

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3.6 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.3.7 Test result

The test results are shown in Appendix A.

6.4 Conducted Out of band emission measurement

6.4.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

6.4.2 Test Description

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration.

6.4.3 Test limit

FCC Part 15.247(d)

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth.


6.4.4 Test Procedure Used

KDB 558074 D01 DTS Meas Guidance v04 Section 11.3

6.4.5 Test Settings

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100kHz.
- Set the VBW $\geq$ 300kHz.
- Detector = peak.
- Set span to encompass the spectrum to be examined
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

6.4.6 Test Setup



6.4.7 Test result

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

The test results are shown in Appendix A.


6.5 Band-edge measurement

6.5.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

6.5.2 Test Description

For the following out of band conducted spurious emissions plots, the EUT was set to transmit at maximum power with the largest packet size available. The worst case spurious emissions were found in this configuration.



6.5.3 Test limit

Part 15.247(d)

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth.

6.5.4 Test Procedure Used

KDB 558074 D01 DTS Meas Guidance v04 Section 12.1

6.5.5 Test Settings

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100kHz.
- Set the VBW $\geq$ 300kHz.
- Detector = peak.
- Set span to encompass the spectrum to be examined
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

6.5.6 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.

6.5.7 Test result

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement. The test results are shown in Appendix A .

6.6 Spurious Radiated Emissions

6.6.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

6.6.2 Test Description

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

6.6.3 Test limit

Part15.205, 15.209, 15.247(d)

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in below Table per Section 15.209.

Frequency [MHz]	Field strength [$\mu\text{V/m}$]	Measured Distance [meters]
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Radiated Limits

Part15.35(b):

there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit

Used conversion factor: Limit (dB $\mu\text{V/m}$) = 20 log (Limit ($\mu\text{V/m}$)/1 $\mu\text{V/m}$)

Frequency [MHz]	Detector	Unit (dB $\mu\text{V/m}$)
30~88	Quasi-peak	40.0
88~216	Quasi-peak	43.5
216~960	Quasi-peak	46.0
960~1000	Quasi-peak	54.0
1000~5th harmonic of the highest frequency or 40GHz, whichever is lower	Average	54.0
	Peak	74.0

Conversion Radiated limits

6.6.4 Test Procedure Used

KDB 558074 D01 DTS Meas Guidance v04 – Section 12.2.7

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the

emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Average detection (AV) at frequency above 1GHz. If duty cycle of test signal is < 98%, the duty factor need added to measured value.
4. All modes of operation were investigated and the worst-case emissions are reported.

6.6.5 Test Settings

Average Field Strength Measurements per Section 12.2.7 of KDB 558074 (Part 15.35)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz > 1/T
4. Averaging type was set to RMS to ensure that video filtering was applied in the power domain
5. Detector = peak
6. Sweep time = auto
7. Trace mode = max hold
8. Trace was allowed to run for at least 50 times (1/duty cycle) traces

Peak Field Strength Measurements per Section 12.2.7 of KDB 558074 (Part 15.35)


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW is set depending on measurement frequency, as specified in following table

Frequency	RBW
9-150kHz	200-300Hz
0.15-30MHz	9-10kHz
30-1000MHz	100-120kHz
>1000MHz	1MHz


3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

6.6.6 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



6.6.7 Test result

The test results are shown in Appendix B.

6.7 AC Power line Conducted Emission

6.7.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

6.7.2 Test limit

FCC Part15.207, RSS-247

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

The measurement is made according to ANSI C63.10-2013

6.7.3 Test Procedures


a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.
The EUT shall test under the power AC120V/60Hz.

6.7.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.5 Test result

The test results are shown in AppendixB .

7 MEASUREMENT UNCERTAINTIES

Items	Uncertainty	
Occupied Bandwidth	3kHz	
Peak power output	0.67dB	
Band edge compliance	1.20dB	
Spurious emissions	30MHz~1GHz	2.83dB
	1GHz~12.75GHz	2.50dB
	12.75GHz~25GHz	2.75dB

8 TEST EQUIPMENTS

No.	Name/ Model	Manufacturer	S/N	Cal date	Cal Due date
1.	Spectrum Analyzer FSV	ROHDE&SCHWARZ	101065	2017.08.20	2018.08.19
2.	Power Meter E4416A	Agilent	MY52370013	2018.03.01	2019.02.28
3.	Power Sensor E9327A	Agilent	MY52420006	2018.03.01	2019.02.28
4.	23.18m×16.88m×9.60m Semi-Anechoic Chamber	FRANKONIA	---	----	----
5.	12.65m×8.03m×7.50m Fully-Anechoic Chamber	FRANKONIA	----	----	----
6.	Turn table Diameter:5m	HD	----	----	----
7.	Turn table Diameter:1m	HD	----	----	----
8.	Antenna master FAC(MA4.0)	MATURO	----	----	----
9.	Antenna master SAC(MA4.0)	MATURO	----	----	----
10.	9.080m×5.255m×3.525m Shielding room	FRANKONIA	----	----	----
11.	HF 906 Double-Ridged Waveguide Horn Antenna	R&S	100029	2017.08.20	2018.08.19
12.	HF 906 Double-Ridged Waveguide Horn Antenna	R&S	100030	2017.08.20	2018.08.19
13.	HL562 Ultra log antenna	R&S	100016	2017.08.20	2018.08.19
14.	3160-09 Receive antenna	SCHWARZ-BECK	002058-002	2017.08.20	2018.08.19
15.	ESI 40 EMI test receiver	R&S	100015	2017.08.20	2018.08.19
16.	ESCS30 EMI test receiver	R&S	100029	2017.08.20	2018.08.19
17.	ESH3-Z5 LISN	R&S	100020	2017.08.20	2018.08.19
18.	HFH2-Z2	R&S	100340	2017.08.20	2018.08.19

APPENDIX A – TEST DATA OF CONDUCTED EMISSION

Please refer to the attachment.

APPENDIX B – TEST DATA OF RADIATED EMISSION

Please refer to the attachment.

APPENDIX A – TEST DATA OF CONDUCTED EMISSION

Peak Power Output test result

Modulation type		Peak power output (dBm)		
		2412MHz	2437MHz	2462MHz
11b	1 Mbps	14.69	14.07	13.69
	2 Mbps	14.62	14.04	13.67
	5.5 Mbps	14.54	14.01	13.64
	11 Mbps	14.47	13.98	13.62
11g	6 Mbps	20.80	20.14	19.57
	9 Mbps	20.88	20.28	19.74
	12 Mbps	20.96	20.41	19.90
	18 Mbps	21.04	20.55	20.07
	24 Mbps	21.11	20.69	20.23
	36 Mbps	21.19	20.83	20.40
	48 Mbps	21.27	20.96	20.56
	54 Mbps	21.35	21.10	20.73
11n HT20	6.5 Mbps	19.97	19.71	18.85
	13 Mbps	20.07	19.81	18.94
	19.5 Mbps	20.16	19.91	19.03
	26 Mbps	20.26	20.01	19.12
	39 Mbps	20.36	20.10	19.22
	52 Mbps	20.46	20.20	19.31
	58.5 Mbps	20.55	20.30	19.40
	65 Mbps	20.65	20.40	19.49
Modulation type		Peak power output (dBm)		
		2422MHz	2437MHz	2452MHz
11n HT40	13.5 Mbps	18.88	18.57	18.41
	27 Mbps	18.85	18.53	18.44
	40.5 Mbps	18.82	18.48	18.47
	54 Mbps	18.79	18.44	18.50
	81 Mbps	18.77	18.40	18.53
	108 Mbps	18.74	18.36	18.56
	121.5 Mbps	18.71	18.31	18.59
	135 Mbps	18.68	18.27	18.62

Modulation type		Average power output (dBm)		
		2412MHz	2437MHz	2462MHz
11b	1 Mbps	12.24	11.66	11.22
	2 Mbps	12.19	11.62	11.18
	5.5 Mbps	12.14	11.58	11.15
	11 Mbps	12.09	11.54	11.11
11g	6 Mbps	12.18	11.48	11.07
	9 Mbps	12.02	11.37	10.98
	12 Mbps	11.87	11.25	10.89
	18 Mbps	11.71	11.14	10.80
	24 Mbps	11.55	11.02	10.70
	36 Mbps	11.39	10.91	10.61
	48 Mbps	11.24	10.79	10.52
	54 Mbps	11.08	10.68	10.43
11n HT20	6.5 Mbps	11.35	10.64	10.21
	13 Mbps	11.25	10.55	10.11
	19.5 Mbps	11.15	10.46	10.02
	26 Mbps	11.05	10.37	9.92
	39 Mbps	10.95	10.29	9.82
	52 Mbps	10.85	10.20	9.72
	58.5 Mbps	10.75	10.11	9.63
	65 Mbps	10.65	10.02	9.53
Modulation type		Average power output (dBm)		
		2422MHz	2437MHz	2452MHz
11n HT40	13.5 Mbps	11.26	10.82	10.63
	27 Mbps	11.06	10.61	10.42
	40.5 Mbps	10.86	10.40	10.22
	54 Mbps	10.66	10.19	10.01
	81 Mbps	10.45	9.97	9.80
	108 Mbps	10.25	9.76	9.59
	121.5 Mbps	10.05	9.55	9.39
	135 Mbps	9.85	9.34	9.18

In order to find the worst case condition, Pre-tests are needed at the presence of different data rate. Worst-case data rates are shown as following table.


Test Mode	Data Rate
802.11b	1Mbps
802.11g	6Mbps
802.11n HT20	MCS0(6.5 Mbps)
802.11n HT40	MCS0(13.5 Mbps)

Occupied Bandwidth

Offset 10.5dB = Attenuator 10dB+ Temporary Ant connector loss 0.5dB


Test Mode: 802.11b

Carrier frequency (MHz)	Channel No.	6 dB bandwidth(kHz)
2412	1	9554
2437	6	9079.1
2462	11	9079




Date: 25.MAY.2018 15:39:58

Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11b



Date: 25.MAY.2018 15:44:03

Carrier frequency (MHz): 2437
Channel No.:6
Test Mode: 802.11b




Date: 25.MAY.2018 15:45:51

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11b

Test Mode: 802.11g

Carrier frequency (MHz)	Channel No.	6 dB bandwidth(kHz)
2412	1	15663.4
2437	6	15138.5
2462	11	15353.5




Date: 25.MAY.2018 15:50:37


Carrier frequency (MHz): 2412

Channel No.:1

Test Mode: 802.11g




Carrier frequency (MHz): 2437
Channel No.:6
Test Mode: 802.11g



Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11g

Test Mode: 802.11n (HT20)

Carrier frequency (MHz)	Channel No.	6 dB bandwidth(kHz)
2412	1	16253.4
2437	6	16758.3
2462	11	16768.3




Date: 25.MAY.2018 16:21:28

Carrier frequency (MHz): 2412


Channel No.:1

Test Mode: 802.11n (HT20)



Date: 25.MAY.2018 16:23:05

Carrier frequency (MHz): 2437
Channel No.:6
Test Mode: 802.11n (HT20)




Date: 25.MAY.2018 16:24:22

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11n (HT20)

Test Mode: 802.11n (HT40)

Carrier frequency (MHz)	Channel No.	6 dB bandwidth(kHz)
2422	3	35140
2437	6	35136
2452	9	35136




Date: 25.MAY.2018 16:30:08


Carrier frequency (MHz): 2422

Channel No.:3

Test Mode: 802.11n (HT40)



Carrier frequency (MHz): 2437
Channel No.:6
Test Mode: 802.11n (HT40)




Carrier frequency (MHz): 2452
Channel No.:9
Test Mode: 802.11n (HT40)

Transmitter Power Spectral Density

Offset 10.5dB = Attenuator 10dB+ Temporary Ant connector loss 0.5dB


Test Mode: 802.11b

Carrier frequency (MHz)	Channel No	Power Density (dBm)
2412	1	-9.66
2437	6	-11.25
2462	11	-11.59




Date: 26.MAY.2018 10:35:29

Carrier frequency (MHz): 2412
Channel No.1
Test Mode: 802.11b




Carrier frequency (MHz): 2437
Channel No.6
Test Mode: 802.11b




Carrier frequency (MHz): 2462
Channel No.11
Test Mode: 802.11b

Test Mode: 802.11g


Carrier frequency (MHz)	Channel No	Power Density (dBm)
2412	1	-10.95
2442	6	-12.49
2472	11	-11.22



Carrier frequency (MHz): 2412
Channel No.1
Test Mode: 802.11g




Carrier frequency (MHz): 2437
Channel No.6
Test Mode: 802.11g



Carrier frequency (MHz): 2462
Channel No.11
Test Mode: 802.11g

Test Mode: 802.11n (HT20)


Carrier frequency (MHz)	Channel No	Power Density (dBm)
2412	1	-12.66
2437	6	-13.98
2462	11	-13.70




Carrier frequency (MHz): 2412

Channel No.1

Test Mode: 802.11n (HT20)




Carrier frequency (MHz): 2437
Channel No.6
Test Mode: 802.11n (HT20)



Carrier frequency (MHz): 2462
Channel No.11
Test Mode: 802.11n (HT20)


Test Mode: 802.11n (HT40)

Carrier frequency (MHz)	Channel No	Power Density (dBm)
2422	3	-14.41
2437	6	-16.65
2452	9	-14.43




Date: 26.MAY.2018 10:47:08

Carrier frequency (MHz): 2422
Channel No.3
Test Mode: 802.11n (HT40)



Carrier frequency (MHz): 2437
Channel No.6
Test Mode: 802.11n (HT40)





Carrier frequency (MHz): 2452
Channel No.9
Test Mode: 802.11n (HT40)

Conducted Out of band emission measurement



Offset 10.5dB = Attenuator 10dB+ Temporary Ant connector loss 0.5dB

802.11b



CH1



CH6





CH11





802.11g



CH1



CH6




CH11




802.11n (20MHz)

CH1




Date: 26.MAY.2018 11:18:39




Date: 26.MAY.2018 11:19:52

CH6




Date: 26.MAY.2018 11:21:43




Date: 26.MAY.2018 11:22:57

CH11




Date: 26.MAY.2018 11:24:07




Date: 26.MAY.2018 11:25:07

802.11n (40MHz)

CH3




Date: 26.MAY.2018 11:26:54




Date: 26.MAY.2018 11:27:49

CH6




Date: 26.MAY.2018 11:49:55




Date: 26.MAY.2018 11:53:55

CH9



Date: 26.MAY.2018 12:01:20




Date: 26.MAY.2018 12:03:20

Band edge measurement (RF Conducted measurement)


Offset 10.5dB = Attenuator 10dB+ Temporary Ant connector loss 0.5dB

802.11b

CH1




CH11




802.11g

CH1




CH11




802.11n (HT20)

CH1



Date: 26.MAY.2018 13:13:42


CH11



Date: 26.MAY.2018 13:13:26


802.11n (HT40)

CH3



Date: 26.MAY.2018 13:17:26

CH9



Date: 26.MAY.2018 13:19:36

APPENDIX B – TEST DATA OF RADIATED EMISSION

Radiated Emission Band Edge

The worst case attitude: The mobile lay down.

Peak detector: RBW=1MHz,VBW=3MHz,sweep time=200ms;

Average detector: RBW=1MHz,VBW=3MHz,sweep time=auto;

Carrier frequency (MHz): 2412

Channel No.:1

Test Mode: 802.11b

Polarity:Vertical

Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	96.68	62.68	N/A	N/A	8.90	25.10
2	2390	50.25	16.25	-23.75	74.00	8.90	25.10

Carrier frequency (MHz): 2412

Channel No.:1

Test Mode: 802.11b

Polarity:Horizontal

Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	94.12	60.12	N/A	N/A	8.90	25.10
2	2390	49.75	15.75	-24.25	74.00	8.90	25.10

Carrier frequency (MHz): 2412

Channel No.:1

Test Mode: 802.11b

Polarity:Vertical

Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	87.68	53.68	N/A	N/A	8.90	25.10
2	2390	38.85	4.85	-15.15	54.00	8.90	25.10

Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11b
Polarity:Horizontal
Detector: AVerage

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuv/m)	cable loss (dB)	antenna factor (dB)
1	2412	86.39	52.39	N/A	N/A	8.90	25.10
2	2390	37.10	3.10	-16.90	54.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11b
Polarity:Vertical
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuv/m)	cable loss (dB)	antenna factor (dB)
1	2462	96.29	62.29	N/A	N/A	8.90	25.10
2	2483.5	49.66	15.66	-24.34	74.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11b
Polarity:Horizontal
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuv/m)	cable loss (dB)	antenna factor (dB)
1	2462	94.83	60.83	N/A	-18.62	8.90	25.10
2	2483.5	50.18	16.18	-23.82	74.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11b
Polarity:Vertical
Detector: AVerage

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuv/m)	cable loss (dB)	antenna factor (dB)
1	2462	87.16	53.16	N/A	N/A	8.90	25.10
2	2483.5	38.39	4.39	-15.61	54.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11b
Polarity:Horizontal
Detector: AVerage

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuv/m)	cable loss (dB)	antenna factor (dB)
1	2462	85.54	51.54	N/A	N/A	8.90	25.10
2	2483.5	38.33	4.33	-15.67	54.00	8.90	25.10

Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11g
Polarity: Vertical
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuv/m)	cable loss (dB)	antenna factor (dB)
1	2412	97.97	63.97	N/A	N/A	8.90	25.10
2	2390	49.34	15.34	-24.66	74.00	8.90	25.10

Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11g
Polarity:Horizontal
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	95.23	61.23	N/A	N/A	8.90	25.10
2	2390	50.13	16.13	-23.87	74.00	8.90	25.10

Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11g
Polarity: Vertical
Detector: AVerage

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	87.20	53.20	N/A	N/A	8.90	25.10
2	2390	38.39	4.39	-15.61	54.00	8.90	25.10

Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11g
Polarity:Horizontal
Detector: AVerage

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	86.48	52.48	N/A	N/A	8.90	25.10
2	2390	38.51	4.51	-15.49	54.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11g
Polarity: Vertical
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	98.91	64.91	N/A	N/A	8.90	25.10
2	2483.5	50.77	16.77	-23.23	74.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11g
Polarity:Horizontal
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	96.62	62.62	N/A	N/A	8.90	25.10
2	2483.5	49.81	15.81	-24.19	74.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11g
Polarity: Vertical
Detector: AVerage

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	86.46	52.46	N/A	N/A	8.90	25.10
2	2483.5	37.79	3.79	-16.21	54.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11g
Polarity:Horizontal
Detector: AVerage

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuv/m)	cable loss (dB)	antenna factor (dB)
1	2462	86.16	52.16	N/A	N/A	8.90	25.10
2	2483.5	37.33	3.33	-16.67	54.00	8.90	25.10

Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11n(HT20)
Polarity: Vertical
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuv/m)	cable loss (dB)	antenna factor (dB)
1	2412	98.01	64.01	N/A	N/A	8.90	25.10
2	2390	50.28	16.28	-23.72	74.00	8.90	25.10

Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11n(HT20)
Polarity:Horizontal
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuv/m)	cable loss (dB)	antenna factor (dB)
1	2412	97.13	63.13	N/A	N/A	8.90	25.10
2	2390	50.62	16.62	-23.38	74.00	8.90	25.10

Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11n(HT20)
Polarity: Vertical
Detector: AVerage

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	87.44	53.44	N/A	N/A	8.90	25.10
2	2390	37.90	3.90	-16.10	54.00	8.90	25.10

Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11n(HT20)
Polarity:Horizontal
Detector: AVerage

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	86.66	52.66	N/A	N/A	8.90	25.10
2	2390	38.32	4.32	-15.68	54.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11n(HT20)
Polarity: Vertical
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	97.59	63.59	N/A	N/A	8.90	25.10
2	2483.5	50.28	16.28	-23.72	74.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11n(HT20)
Polarity:Horizontal
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	95.95	61.95	N/A	N/A	8.90	25.10
2	2483.5	49.61	15.61	-24.39	74.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11n(HT20)
Polarity: Vertical
Detector: AVerage

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	87.89	53.89	N/A	N/A	8.90	25.10
2	2483.5	38.27	4.27	-15.73	54.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11n(HT20)
Polarity:Horizontal
Detector: AVerage

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	86.59	52.59	N/A	N/A	8.90	25.10
2	2483.5	38.97	4.97	-15.03	54.00	8.90	25.10

Carrier frequency (MHz): 2422
Channel No.:3
Test Mode: 802.11n(HT40)
Polarity: Vertical
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2422	98.53	64.53	N/A	N/A	8.90	25.10
2	2390	49.65	15.65	-24.35	74.00	8.90	25.10

Carrier frequency (MHz): 2422
Channel No.:3
Test Mode: 802.11n(HT40)
Polarity:Horizontal
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2422	97.61	63.61	N/A	N/A	8.90	25.10
2	2390	50.27	16.27	-23.73	74.00	8.90	25.10

Carrier frequency (MHz): 2422
Channel No.:3
Test Mode: 802.11n(HT40)
Polarity: Vertical
Detector: AVerage

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2422	86.89	52.89	N/A	N/A	8.90	25.10
2	2390	38.05	4.05	-15.95	54.00	8.90	25.10

Carrier frequency (MHz): 2422
Channel No.:3
Test Mode: 802.11n(HT40)
Polarity:Horizontal
Detector: AVerage

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2422	85.46	51.46	N/A	N/A	8.90	25.10
2	2390	37.43	3.43	-16.57	54.00	8.90	25.10

Carrier frequency (MHz): 2452
Channel No.:9
Test Mode: 802.11n(HT40)
Polarity: Vertical
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	98.90	64.90	N/A	N/A	8.90	25.10
2	2483.5	49.26	15.26	-24.74	74.00	8.90	25.10

Carrier frequency (MHz): 2452
Channel No.:9
Test Mode: 802.11n(HT40)
Polarity:Horizontal
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	97.28	63.28	N/A	N/A	8.90	25.10
2	2483.5	50.78	16.78	-23.22	74.00	8.90	25.10

Carrier frequency (MHz): 2452
Channel No.:9
Test Mode: 802.11n(HT40)
Polarity: Vertical
Detector: AVerage

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	86.07	52.07	N/A	N/A	8.90	25.10
2	2483.5	37.25	3.25	-16.75	54.00	8.90	25.10

Carrier frequency (MHz): 2452
Channel No.9
Test Mode: 802.11n(HT40)
Polarity:Horizontal
Detector: AVerage

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	86.53	52.53	N/A	N/A	8.90	25.10
2	2483.5	37.52	3.52	-16.48	54.00	8.90	25.10

For 802.11b with data rate 1 Mbps

Note: For each mode, just record the worst case data of low/mid/ high channel.

Channel 1

Frequency (MHz)	Result (dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
30.309583	20.29	-13.6	33.89	Vertical	40.00
30.560000	20.20	-13.7	33.9	Vertical	40.00
31.432500	20.50	-14.2	34.7	Vertical	40.00
39.562083	19.14	-17.9	37.04	Vertical	40.00
42.987083	21.20	-19.9	41.1	Vertical	40.00
43.282917	22.50	-20.0	42.5	Vertical	40.00

Channel 6

Frequency (MHz)	Result (dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
60.007083	26.78	6.2	20.58	Horizontal	40.00
101.605833	26.44	12.4	14.04	Vertical	43.50
101.636667	26.61	12.4	14.21	Vertical	43.50
101.641250	26.64	12.4	14.24	Vertical	43.50
834.925833	29.51	27.0	2.51	Horizontal	46.00
936.927500	31.89	28.4	3.49	Horizontal	46.00

Channel 11

Frequency (MHz)	Result (dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
30.466250	19.58	-13.7	33.28	Vertical	40.00
39.520000	19.24	-17.8	37.04	Vertical	40.00
43.763750	23.61	-20.3	43.91	Vertical	40.00
44.253333	23.30	-20.6	43.9	Vertical	40.00
48.203750	17.63	-23.1	40.73	Vertical	40.00
65.949167	16.85	-25.5	42.35	Vertical	40.00

For 802.11g with data rate 54 Mbps

Note: For each mode, just record the worst case data of low/mid/ high channel.

Channel 1

Frequency (MHz)	Result (dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
30.280000	20.08	-13.6	33.68	Vertical	40.00
30.710833	20.17	-13.8	33.97	Vertical	40.00
39.041667	18.75	-17.6	36.35	Vertical	40.00
39.353333	19.10	-17.8	36.9	Vertical	40.00
39.436250	19.18	-17.8	36.98	Horizontal	40.00
43.521667	22.69	-20.2	42.89	Vertical	40.00

Channel 6

Frequency (MHz)	Result (dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
59.434583	26.11	6.4	19.71	Vertical	40.00
59.763750	26.21	6.3	19.91	Vertical	40.00
59.808333	26.16	6.3	19.86	Horizontal	40.00
59.850417	26.20	6.3	19.9	Vertical	40.00
847.117917	29.94	27.2	2.74	Horizontal	46.00
932.162917	31.86	28.3	3.56	Vertical	46.00

Channel 11

Frequency (MHz)	Result (dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
31.555000	20.33	-14.2	34.53	Vertical	40.00
39.512917	19.39	-17.8	37.19	Vertical	40.00
39.765417	19.31	-17.9	37.21	Horizontal	40.00
39.797917	19.28	-18.0	37.28	Vertical	40.00
43.397917	23.15	-20.1	43.25	Vertical	40.00
43.722917	23.38	-20.3	43.68	Vertical	40.00

For 802.11n(HT20) with data rate 65 Mbps

Note: For each mode, just record the worst case data of low/mid/ high channel.

Channel 1

Frequency (MHz)	Result (dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
30.120000	20.31	-13.5	33.81	Vertical	40.00
30.480000	20.34	-13.7	34.04	Vertical	40.00
30.592500	20.35	-13.8	34.15	Vertical	40.00
31.275833	20.09	-14.1	34.19	Vertical	40.00
39.632500	18.84	-17.9	36.74	Vertical	40.00
43.276667	22.38	-20.0	42.38	Vertical	40.00

Channel 6

Frequency (MHz)	Result (dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
59.676667	26.07	6.3	19.77	Horizontal	40.00
59.685833	26.04	6.3	19.74	Vertical	40.00
59.686667	26.02	6.3	19.72	Vertical	40.00
59.735000	25.55	6.3	19.25	Vertical	40.00
121.527500	23.22	12.9	10.32	Vertical	43.50
958.634167	31.66	28.6	3.06	Horizontal	46.00

Channel 11

Frequency (MHz)	Result (dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
30.149583	19.48	-13.5	32.98	Vertical	40.00
30.720000	19.99	-13.8	33.79	Vertical	40.00
30.915000	19.78	-13.9	33.68	Vertical	40.00
31.467083	20.38	-14.2	34.58	Horizontal	40.00
43.798750	23.10	-20.4	43.5	Vertical	40.00
799.997917	24.93	-7.0	31.93	Horizontal	46.00

For 802.11n(HT40) with data rate 13.5 Mbps

Note: For each mode, just record the worst case data of low/mid/ high channel.

Channel 3

Frequency (MHz)	Result (dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
30.120000	20.24	-13.5	33.74	Vertical	40.00
30.640000	20.19	-13.8	33.99	Vertical	40.00
31.117917	19.72	-14.0	33.72	Vertical	40.00
31.354583	20.03	-14.1	34.13	Vertical	40.00
39.318333	18.96	-17.8	36.76	Vertical	40.00
43.237500	22.02	-20.0	42.02	Vertical	40.00


Channel 6

Frequency (MHz)	Result (dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
59.529167	25.93	6.4	19.53	Horizontal	40.00
101.198750	26.44	12.4	14.04	Vertical	43.50
101.274583	26.32	12.4	13.92	Vertical	43.50
101.350000	26.09	12.4	13.69	Vertical	43.50
101.403333	26.35	12.4	13.95	Vertical	43.50
931.110833	31.75	28.3	3.45	Horizontal	46.00

Channel 9

Frequency (MHz)	Result (dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
30.000000	19.98	-13.5	33.48	Vertical	40.00
30.520000	20.07	-13.7	33.77	Vertical	40.00
31.434167	20.44	-14.2	34.64	Horizontal	40.00
39.274167	19.21	-17.7	36.91	Vertical	40.00
39.391250	19.14	-17.8	36.94	Horizontal	40.00
43.278750	22.83	-20.0	42.83	Vertical	40.00

Full Spectrum




Preview Result 1-PK+ Copy of FCC CLASS B Final_Result QPK

Comment

Frequency Range: 9kHz -30MHz
Detector: QP mode
Test Mode: 802.11b channel 1

Full Spectrum




Preview Result 1V-PK+ FCC CLASS B Final_Result QPK

Comment

Frequency Range: 30MHz -1GHz
Detector: QP mode
Test Mode: 802.11b channel 1


Full Spectrum



Comment


Frequency Range: 1GHz -3GHz
Detector: AV mode and PK mode
Modulation type: 802.11b channel 1

Full Spectrum




Frequency Range: 3GHz -18GHz
Detector: AV mode and PK mode
Modulation type: 802.11b channel 1

Full Spectrum



Frequency Range: 18GHz -26.5GHz
Detector: AV mode and PK mode
Modulation type: 802.11b channel 1

Full Spectrum




Preview Result 1-PK+ Copy of FCC CLASS B Final_Result QPK

Comment


Frequency Range: 9kHz -30MHz
Detector: QP mode
Test Mode: 802.11b channel 6

Full Spectrum




Frequency Range: 30MHz -1GHz
Detector: QP mode
Test Mode: 802.11b channel 6

Full Spectrum




Frequency Range: 1GHz -3GHz
Detector: AV mode and PK mode
Modulation type: 802.11b channel6

Full Spectrum




Frequency Range: 3GHz -18GHz
Detector: AV mode and PK mode
Modulation type: 802.11b channel 6

Full Spectrum



Frequency Range: 18GHz -26.5GHz
Detector: AV mode and PK mode
Modulation type: 802.11b channel 6


Full Spectrum



Comment

Frequency Range: 9kHz -30MHz
Detector: QP mode
Test Mode: 802.11b channel 11


Full Spectrum



Comment

Frequency Range: 30MHz -1GHz
Detector: QP mode
Test Mode: 802.11b channel 11


Full Spectrum



Comment


Frequency Range: 1GHz -3GHz
Detector: AV mode and PK mode
Modulation type: 802.11b channel 11

Full Spectrum




Frequency Range: 3GHz -18GHz
Detector: AV mode and PK mode
Modulation type: 802.11b channel 11

Full Spectrum



Frequency Range: 18GHz -26.5GHz
Detector: AV mode and PK mode
Modulation type: 802.11b channel 11

Full Spectrum




Preview Result 1-PK+ Copy of FCC CLASS B Final_Result QPK

Comment


Frequency Range: 9kHz -30MHz
Detector: QP mode
Modulation type: 802.11g channel 1

Full Spectrum




Frequency Range: 30MHz -1GHz
Detector: QP mode
Modulation type: 802.11g channel 1

Full Spectrum




Frequency Range: 1GHz -3GHz
Detector: AV mode and PK mode
Modulation type: 802.11g channel 1

Full Spectrum




Frequency Range: 3GHz -18GHz
Detector: AV mode and PK mode
Modulation type: 802.11g channel 1

Full Spectrum



Frequency Range: 18GHz -26.5GHz
Detector: AV mode and PK mode
Modulation type: 802.11g channel 1

Full Spectrum




Preview Result 1-PK+ Copy of FCC CLASS B Final_Result QPK

Comment

Frequency Range: 9kHz -30MHz
Detector: QP mode
Modulation type: 802.11g channel 6

Full Spectrum




Preview Result 1-PK+ FCC CLASS B Final_Result QPK

Comment

Frequency Range: 30MHz -1GHz
Detector: QP mode
Modulation type: 802.11g channel 6


Full Spectrum



Comment


Frequency Range: 1GHz -3GHz
Detector: AV mode and PK mode
Modulation type: 802.11g channel 6

Full Spectrum




Frequency Range: 3GHz -18GHz
Detector: AV mode and PK mode
Modulation type: 802.11g channel 6

Full Spectrum



Frequency Range: 18GHz -26.5GHz
Detector: AV mode and PK mode
Modulation type: 802.11g channel 6

Full Spectrum




Preview Result 1-PK+ Copy of FCC CLASS B Final_Result QPK

Comment


Frequency Range: 9kHz -30MHz
Detector: QP mode
Modulation type: 802.11g channel 11

Full Spectrum




Frequency Range: 30MHz -1GHz
Detector: QP mode
Modulation type: 802.11g channel 11

Full Spectrum




Frequency Range: 1GHz -3GHz
Detector: AV mode and PK mode
Modulation type: 802.11g channel 11

Full Spectrum




Frequency Range: 3GHz -18GHz
Detector: AV mode and PK mode
Modulation type: 802.11g channel 11

Full Spectrum




Frequency Range: 18GHz -26.5GHz
Detector: AV mode and PK mode
Modulation type: 802.11g channel 11

Full Spectrum




Frequency Range: 9kHz -30MHz
Detector: QP mode
Test Mode: 802.11n(HT20) channel 1

Full Spectrum




Frequency Range: 30MHz -1GHz
Detector: QP mode
Test Mode: 802.11n(HT20) channel 1

Full Spectrum




Frequency Range: 1GHz -3GHz
Detector: AV mode and PK mode
Modulation type: 802.11n(HT20) channel 1

Full Spectrum




Frequency Range: 3GHz -18GHz
Detector: AV mode and PK mode
Modulation type: 802.11n(HT20) channel 1

Full Spectrum



Frequency Range: 18GHz -26.5GHz
Detector: AV mode and PK mode
Modulation type: 802.11n(HT20) channel 1

Full Spectrum




Preview Result 1-PK+ Copy of FCC CLASS B Final_Result QPK

Comment


Frequency Range: 9kHz -30MHz
Detector: QP mode
Test Mode: 802.11n(HT20) channel 6

Full Spectrum




Frequency Range: 30MHz -1GHz
Detector: QP mode
Test Mode: 802.11n(HT20) channel 7

Full Spectrum




Frequency Range: 1GHz -3GHz
Detector: AV mode and PK mode
Modulation type: 802.11n(HT20) channel 6

Full Spectrum




Frequency Range: 3GHz -18GHz
Detector: AV mode and PK mode
Modulation type: 802.11n(HT20) channel 6

Full Spectrum




Frequency Range: 18GHz -26.5GHz
Detector: AV mode and PK mode
Modulation type: 802.11n(HT20) channel 6

Full Spectrum




Frequency Range: 9kHz -30MHz
Detector: QP mode
Test Mode: 802.11n(HT20) channel 11

Full Spectrum



Frequency Range: 30MHz -1GHz
Detector: QP mode
Test Mode: 802.11n(HT20) channel 11


Full Spectrum



Comment


Frequency Range: 1GHz -3GHz
Detector: AV mode and PK mode
Modulation type: 802.11n(HT20) channel 11

Full Spectrum




Frequency Range: 3GHz -18GHz
Detector: AV mode and PK mode
Modulation type: 802.11n(HT20) channel 11

Full Spectrum



Frequency Range: 18GHz -26.5GHz
Detector: AV mode and PK mode
Modulation type: 802.11n(HT20) channel 11


Full Spectrum



Comment


Frequency Range: 9kHz -30MHz
Detector: QP mode
Modulation type: 802.11n(HT40) channel 3

Full Spectrum




Frequency Range: 30MHz -1GHz
Detector: QP mode
Modulation type: 802.11n(HT40) channel 3

Full Spectrum




Frequency Range: 1GHz -3GHz
Detector: AV mode and PK mode
Modulation type: 802.11n(HT40) channel 3

Full Spectrum




Frequency Range: 3GHz -18GHz
Detector: AV mode and PK mode
Modulation type: 802.11n(HT40) channel 3

Full Spectrum



Frequency Range: 18GHz -26.5GHz
Detector: AV mode and PK mode
Modulation type: 802.11n(HT40) channel 3

Full Spectrum




Preview Result 1-PK+ Copy of FCC CLASS B Final_Result QPK

Comment

Frequency Range: 9kHz -30MHz
Detector: QP mode
Modulation type: 802.11n(HT40) channel 6

Full Spectrum




Preview Result 1-PK+ FCC CLASS B Final_Result QPK

Comment

Frequency Range: 30MHz -1GHz
Detector: QP mode
Modulation type: 802.11n(HT40) channel 6


Full Spectrum



Comment


Frequency Range: 1GHz -3GHz
Detector: AV mode and PK mode
Modulation type: 802.11n(HT40) channel 6

Full Spectrum




Frequency Range: 3GHz -18GHz
Detector: AV mode and PK mode
Modulation type: 802.11n(HT40) channel 6

Full Spectrum



Frequency Range: 18GHz -26.5GHz
Detector: AV mode and PK mode
Modulation type: 802.11n(HT40) channel 6

Full Spectrum




Preview Result 1-PK+ Copy of FCC CLASS B Final_Result QPK

Comment


Frequency Range: 9kHz -30MHz
Detector: QP mode
Modulation type: 802.11n(HT40) channel 9

Full Spectrum




Frequency Range: 30MHz -1GHz
Detector: QP mode
Modulation type: 802.11n(HT40) channel 9

Full Spectrum




Frequency Range: 1GHz -3GHz
Detector: AV mode and PK mode
Modulation type: 802.11n(HT40) channel 9

Full Spectrum



Frequency Range: 3GHz -18GHz
Detector: AV mode and PK mode
Modulation type: 802.11n(HT40) channel 9


Full Spectrum



Frequency Range: 18GHz -26.5GHz
Detector: AV mode and PK mode
Modulation type: 802.11n(HT40) channel 9

AC Power line Conducted Emission

Full Spectrum



Comment

L +N Line

MEASUREMENT RESULT:

Frequency (MHz)	MaxPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.171864	---	42.10	54.87	12.77	L1	30.2
0.171864	51.45	---	64.87	13.42	L1	30.2
0.209654	45.69	---	63.22	17.53	L1	29.9
0.217654	---	38.65	52.91	14.26	L1	30.0
0.217654	45.91	---	62.91	17.00	L1	30.0
1.381701	---	24.99	46.00	21.01	L1	29.9

---End of Test Report---