



REPORT No. : SZ18030225S01

# RF EXPOSURE EVALUATION REPORT

**APPLICANT** : Fujian Newland Auto-ID Tech Co.,Ltd.

**PRODUCT NAME** : Information Terminal

**MODEL NAME** : NLS-NQuire1000

**BRAND NAME** : Newland

**FCC ID** : SL9NLS-NQUIRE1000

**STANDARD(S)** : 47CFR 2.1091  
KDB 447498

**ISSUE DATE** : 2018-07-25

Tested by:

Gan Yueming(Test engineer)

Approved by:

Peng Huarui (Supervisor)

**NOTE:** This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.



SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.  
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555

[Http://www.morlab.cn](http://www.morlab.cn)

Fax: 86-755-36698525

E-mail: [service@morlab.cn](mailto:service@morlab.cn)





# DIRECTORY

|                                                  |    |
|--------------------------------------------------|----|
| 1. Technical Information.....                    | 3  |
| 1.1 Applicant and Manufacturer Information.....  | 3  |
| 1.2 Equipment Under Test (EUT) Description ..... | 3  |
| 1.3 Photographs of the EUT.....                  | 4  |
| 1.4 Applied Reference Documents .....            | 5  |
| 2. Device Category and RF Exposure Limit .....   | 6  |
| 3. Measurement of RF Output Power .....          | 7  |
| 4. RF Exposure Evaluation .....                  | 10 |
| Annex A General Information.....                 | 11 |

| Change History |            |                   |
|----------------|------------|-------------------|
| Issue          | Date       | Reason for change |
| 1.0            | 2018-07-25 | First edition     |
|                |            |                   |



# 1. Technical Information

**Note:** Provide by manufacturer.

## 1.1 Applicant and Manufacturer Information

|                              |                                                                                                               |
|------------------------------|---------------------------------------------------------------------------------------------------------------|
| <b>Applicant:</b>            | Fujian Newland Auto-ID Tech Co.,Ltd.                                                                          |
| <b>Applicant Address:</b>    | Newland Science & Technology Park, No.1 Rujiang West Rd.,Mawei district,Fuzhou,Fujian,P.R.China               |
| <b>Manufacturer:</b>         | Shenzhen Chuangwei Electronic Appliance Tech Co., Ltd.                                                        |
| <b>Manufacturer Address:</b> | 4F & 6F, Overseas plant south, Skyworth Industrial Park, Shiyan Street, Bao'an District, Shenzhen, P.R. China |

## 1.2 Equipment Under Test (EUT) Description

|                          |                                                                                                                                                                                                                                |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>EUT Type:</b>         | Information Terminal                                                                                                                                                                                                           |
| <b>Hardware Version:</b> | NQ1000-MB-D6-V02                                                                                                                                                                                                               |
| <b>Software Version:</b> | NQ1000-Android-7-1-V005                                                                                                                                                                                                        |
| <b>Frequency Bands:</b>  | WLAN 2.4GHz: 2412 MHz ~ 2462 MHz<br>WLAN 5.2GHz: 5180 MHz ~ 5240 MHz<br>WLAN 5.3GHz: 5260 MHz ~ 5320 MHz<br>WLAN 5.5GHz: 5500 MHz ~ 5700 MHz<br>WLAN 5.8GHz: 5745 MHz ~ 5825 MHz<br>Bluetooth (BR+EDR+LE): 2402 MHz ~ 2480 MHz |
| <b>Modulation Mode:</b>  | WLAN2.4GHz 802.11b:DSSS<br>WLAN2.4GHz 802.11g/n HT20: OFDM<br>WLAN5GHz 802.11a/n HT20/HT40: OFDM<br>WLAN5GHz 802.11ac VHT20/VHT40/VHT80: OFDM<br>Bluetooth: GFSK, $\pi/4$ -DQPSK, 8-DPSK                                       |
| <b>Antenna Type:</b>     | FPC Antenna                                                                                                                                                                                                                    |
| <b>Antenna Gain:</b>     | 2.4GHz Band: 3.98dBi<br>WLAN5GHz: 4.77dBi                                                                                                                                                                                      |

## 1.3 Photographs of the EUT

### 1. EUT front view



### 2. EUT rear view





### 1.3.1 Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

| EUT Identity | Hardware Version | Software Version        |
|--------------|------------------|-------------------------|
| 1#           | NQ1000-MB-D6-V02 | NQ1000-Android-7-1-V005 |

## 1.4 Applied Reference Documents

Leading reference documents for testing:

| No. | Identity          | Document Title                                                |
|-----|-------------------|---------------------------------------------------------------|
| 1   | 47 CFR§2.1091     | Radio frequency Radiation Exposure Evaluation: mobile devices |
| 2   | KDB 447498 D01v06 | General RF Exposure Guidance                                  |



## 2. Device Category and RF Exposure Limit

Per user manual, Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

### Mobile Devices:

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

### GENERAL POPULATION / UNCONTROLLED EXPOSURE

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

**TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

| Frequency range (MHz)                                          | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|----------------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| <b>(B) Limits for General Population/Uncontrolled Exposure</b> |                               |                               |                                     |                          |
| 0.3-1.34                                                       | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34-30                                                        | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |
| 30-300                                                         | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300-1500                                                       | -                             | -                             | f/1500                              | 30                       |
| 1500-100,000                                                   | -                             | -                             | 1.0                                 | 30                       |

f = frequency in MHz

\* = Plane-wave equivalent power density



### 3. Measurement of RF Output Power

#### <WLAN2.4GHz Mode>

| WLAN<br>2.4GHz | Mode                 | Channel | Frequency<br>(MHz) | Peak power (dBm) | Tune-Up<br>Limit |
|----------------|----------------------|---------|--------------------|------------------|------------------|
|                | 802.11b<br>1Mbps     | CH 1    | 2412               | 12.52            | 13.00            |
|                |                      | CH 6    | 2437               | 13.33            | 14.00            |
|                |                      | CH 11   | 2462               | 13.86            | 14.00            |
|                | 802.11g<br>6Mbps     | CH 1    | 2412               | 19.37            | 20.00            |
|                |                      | CH 6    | 2437               | 20.03            | 20.50            |
|                |                      | CH 11   | 2462               | 20.43            | 21.00            |
|                | 802.11n-HT20<br>MCS0 | CH 1    | 2412               | 19.19            | 20.00            |
|                |                      | CH 6    | 2437               | 19.85            | 20.00            |
|                |                      | CH 11   | 2462               | <b>20.48</b>     | 21.00            |

#### <WLAN5GHz Mode>

| WLAN<br>5.2GHz | Mode                   | Channel | Frequency<br>(MHz) | Peak power (dBm) | Tune-Up<br>Limit |
|----------------|------------------------|---------|--------------------|------------------|------------------|
|                | 802.11a 6Mbps          | CH 36   | 5180               | 17.18            | 18.00            |
|                |                        | CH 44   | 5220               | 17.54            | 18.00            |
|                |                        | CH 48   | 5240               | <b>17.77</b>     | 18.00            |
|                | 802.11n-HT20<br>MCS0   | CH 36   | 5180               | 16.50            | 17.00            |
|                |                        | CH 44   | 5220               | 16.84            | 17.50            |
|                |                        | CH 48   | 5240               | 17.28            | 17.50            |
|                | 802.11n-HT40<br>MCS0   | CH 38   | 5190               | 16.53            | 17.00            |
|                |                        | CH 46   | 5230               | 17.06            | 17.50            |
|                | 802.11ac-VHT20<br>MCS0 | CH 36   | 5180               | 16.44            | 17.00            |
|                |                        | CH 44   | 5220               | 16.83            | 17.50            |
|                |                        | CH 48   | 5240               | 17.35            | 17.50            |
|                | 802.11ac-VHT40<br>MCS0 | CH 38   | 5190               | 16.65            | 17.00            |
|                |                        | CH 46   | 5230               | 16.77            | 17.00            |
|                | 802.11ac-VHT80<br>MCS0 | CH 42   | 5210               | 16.21            | 17.00            |



| WLAN<br>5.3GHz | Mode                   | Channel | Frequency<br>(MHz) | Peak power (dBm) | Tune-Up<br>Limit |
|----------------|------------------------|---------|--------------------|------------------|------------------|
|                | 802.11a 6Mbps          | CH 52   | 5260               | 18.16            | 19.00            |
|                |                        | CH 60   | 5300               | 18.45            | 19.00            |
|                |                        | CH 64   | 5320               | <b>18.78</b>     | 19.00            |
|                | 802.11n-HT20<br>MCS0   | CH 52   | 5260               | 17.82            | 18.50            |
|                |                        | CH 60   | 5300               | 18.15            | 18.50            |
|                |                        | CH 64   | 5320               | 18.69            | 19.00            |
|                | 802.11n-HT40<br>MCS0   | CH 54   | 5270               | 17.79            | 18.00            |
|                |                        | CH 62   | 5310               | 18.35            | 18.50            |
|                | 802.11ac-VHT20<br>MCS0 | CH 52   | 5260               | 17.87            | 18.00            |
|                |                        | CH 60   | 5300               | 18.06            | 18.50            |
|                |                        | CH 64   | 5320               | 18.57            | 19.00            |
|                | 802.11ac-VHT40<br>MCS0 | CH 54   | 5270               | 17.87            | 18.00            |
|                |                        | CH 62   | 5310               | 18.47            | 19.00            |
|                | 802.11ac-VHT80<br>MCS0 | CH 58   | 5290               | 17.90            | 18.50            |

| WLAN<br>5.5GHz | Mode                   | Channel | Frequency<br>(MHz) | Peak power (dBm) | Tune-Up<br>Limit |
|----------------|------------------------|---------|--------------------|------------------|------------------|
|                | 802.11a 6Mbps          | CH 100  | 5500               | <b>19.78</b>     | 20.00            |
|                |                        | CH 120  | 5600               | 19.19            | 20.00            |
|                |                        | CH 140  | 5700               | 18.50            | 19.00            |
|                | 802.11n-HT20<br>MCS0   | CH 100  | 5500               | 19.60            | 20.00            |
|                |                        | CH 120  | 5600               | 19.13            | 20.00            |
|                |                        | CH 140  | 5700               | 18.51            | 19.00            |
|                | 802.11n-HT40<br>MCS0   | CH 102  | 5510               | 19.47            | 20.00            |
|                |                        | CH 126  | 5630               | 18.81            | 19.00            |
|                |                        | CH 142  | 5710               | 18.23            | 19.00            |
|                | 802.11ac-VHT20<br>MCS0 | CH 100  | 5500               | 19.60            | 20.00            |
|                |                        | CH 120  | 5600               | 19.06            | 19.50            |
|                |                        | CH 140  | 5700               | 18.47            | 19.00            |
|                | 802.11ac-VHT40<br>MCS0 | CH 102  | 5510               | 19.46            | 20.00            |
|                |                        | CH 126  | 5630               | 18.78            | 19.00            |
|                |                        | CH 142  | 5710               | 18.23            | 19.00            |



|  |                        |        |      |       |       |
|--|------------------------|--------|------|-------|-------|
|  | 802.11ac-VHT80<br>MCS0 | CH 106 | 5530 | 18.97 | 19.50 |
|  |                        | CH 122 | 5610 | 18.72 | 19.50 |
|  |                        | CH 138 | 5690 | 18.17 | 19.00 |

|                |                        |         |                    |                  |                  |
|----------------|------------------------|---------|--------------------|------------------|------------------|
| WLAN<br>5.8GHz | Mode                   | Channel | Frequency<br>(MHz) | Peak power (dBm) | Tune-Up<br>Limit |
|                | 802.11a MCS0           | CH 149  | 5745               | 18.30            | 19.00            |
|                |                        | CH 157  | 5785               | 17.79            | 18.50            |
|                |                        | CH 165  | 5825               | 17.46            | 18.00            |
|                | 802.11n-HT20<br>MCS0   | CH 149  | 5745               | 18.22            | 19.00            |
|                |                        | CH 157  | 5785               | 17.61            | 18.00            |
|                |                        | CH 165  | 5825               | 17.43            | 18.00            |
|                | 802.11n-HT40<br>MCS0   | CH 151  | 5755               | 18.10            | 18.50            |
|                |                        | CH 159  | 5795               | 17.62            | 18.00            |
|                | 802.11ac-VHT20<br>MCS0 | CH 149  | 5745               | <b>18.41</b>     | 19.00            |
|                |                        | CH 157  | 5785               | 17.62            | 18.00            |
|                |                        | CH 165  | 5825               | 17.44            | 18.00            |
|                | 802.11ac-VHT40<br>MCS0 | CH 151  | 5755               | 18.07            | 18.50            |
|                |                        | CH 159  | 5795               | 17.76            | 18.00            |
|                | 802.11ac-VHT80<br>MCS0 | CH 155  | 5775               | 17.76            | 18.00            |

#### <Bluetooth Mode>

| Mode          | Channel | Frequency<br>(MHz) | Peak power (dBm) |       |       |
|---------------|---------|--------------------|------------------|-------|-------|
|               |         |                    | 1Mbps            | 2Mbps | 3Mbps |
| BR / EDR      | CH 00   | 2402               | 5.62             | 1.94  | 2.39  |
|               | CH 39   | 2441               | 7.62             | 3.68  | 4.04  |
|               | CH 78   | 2480               | 6.90             | 3.62  | 3.87  |
| Tune-up Limit |         |                    | 8                | 4     | 4.5   |

| Mode          | Channel | Frequency<br>(MHz) | Peak power (dBm) |
|---------------|---------|--------------------|------------------|
|               |         |                    | GFSK             |
| LE            | CH 00   | 2402               | 7.52             |
|               | CH 19   | 2440               | 9.81             |
|               | CH 39   | 2480               | 8.97             |
| Tune-up Limit |         |                    | 10.5             |

## 4. RF Exposure Evaluation

### Standalone transmission MPE evaluation

| Bands     | Frequency (MHz) | Maximum Tune-up Limit (dBm) | Antenna Gain (dBi) | EIRP (mW) | Power density (mW/cm <sup>2</sup> ) | Limit for MPE (mW/cm <sup>2</sup> ) |
|-----------|-----------------|-----------------------------|--------------------|-----------|-------------------------------------|-------------------------------------|
| WLAN2.4G  | 2462            | 21.0                        | 3.98               | 314.7     | 0.063                               | 1.0                                 |
| WLAN5.2G  | 5240            | 18.0                        | 4.77               | 189.3     | 0.038                               | 1.0                                 |
| WLAN5.3G  | 5320            | 19.0                        | 4.77               | 237.9     | 0.047                               | 1.0                                 |
| WLAN5.5G  | 5500            | 20.0                        | 4.77               | 300.0     | 0.06                                | 1.0                                 |
| WLAN5.8G  | 5745            | 19.0                        | 4.77               | 237.9     | 0.047                               | 1.0                                 |
| Bluetooth | 2440            | 10.5                        | 3.98               | 28        | 0.006                               | 1.0                                 |

#### 1. MPE calculation method

$$\text{Power Density} = \text{EIRP} / 4\pi R^2$$

Where:  $\text{EIRP} = P \cdot G$

P = Peak output power

G = Antenna gain

R = Separation distance (20cm)

### Simultaneous transmission MPE evaluation

According to the Characteristics of the device, it cannot operate at the same time with one common antenna, so simultaneous transmission MPE evaluation is unnecessary.



## Annex A General Information

### 1. Identification of the Responsible Testing Laboratory

|                               |                                                                                                                                  |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Company Name:                 | Shenzhen Morlab Communications Technology Co., Ltd.                                                                              |
| Department:                   | Morlab Laboratory                                                                                                                |
| Address:                      | FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China |
| Responsible Test Lab Manager: | Mr. Su Feng                                                                                                                      |
| Telephone:                    | +86 755 36698555                                                                                                                 |
| Facsimile:                    | +86 755 36698525                                                                                                                 |

### 2. Identification of the Responsible Testing Location

|          |                                                                                                                                  |
|----------|----------------------------------------------------------------------------------------------------------------------------------|
| Name:    | Shenzhen Morlab Communications Technology Co., Ltd.<br>Morlab Laboratory                                                         |
| Address: | FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China |

\_\_\_\_\_ END OF REPORT \_\_\_\_\_