

RF Exposure Evaluation Report

Product Name : Wireless module

Model No. : WAPC003

FCC ID : SLE-WAPC003

Applicant : Moxa Inc.

Address : No. 1111, Heping Rd., Bade Dist., Taoyuan City 334004, Taiwan

Date of Receipt : Apr. 25, 2022

Date of Declaration : Jun. 23, 2022

Report No. : 2240703R-RFUSMPEV01-A

Report Version : V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.


Issued Date: Jun. 23, 2022

Report No.: 2240703R-RFUSMPEV01-A




Product Name	Wireless module	
Applicant	Moxa Inc.	
Address	No. 1111, Heping Rd., Bade Dist., Taoyuan City 334004, Taiwan	
Manufacturer	Moxa Inc.	
Model No.	WAPC003	
FCC ID	SLE-WAPC003	
EUT Rated Voltage	12-48 VDC, PoE	
EUT Test Voltage	12 VDC	
Trade Name	MOXA	
Applicable Standard	KDB 447498 D01 v06	☒ Minimum test separation distance ≥ 20 cm ☐ For low power devices
Test Result	Complied	

Documented By :



(Supervisor / Jinn Chen)

Tested By :



(Senior Engineer / Jack Hsu)

Approved By :



(Manager / Tim Sung)

Revision History

Report No.	Version	Description	Issued Date
2240703R-RFUSMPEV01-A	V1.0	Initial issue of report.	Jun. 23, 2022

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	Wireless module
Trade Name	MOXA
Model No.	WAPC003
FCC ID	SLE-WAPC003
Frequency Range	802.11b/g/n/ac-20MHz: 2412-2462MHz, 802.11n/ac-40MHz: 2422-2452MHz 802.11a/n/ac-20MHz: 5180-5320MHz, 5500-5720MHz, 5745-5825MHz 802.11n/ac-40MHz: 5190-5310, 5510-5710MHz, 5755-5795MHz 802.11ac-80MHz: 5210-5290MHz, 5530-5690MHz, 5775MHz
Antenna Type	Dipole Antenna, Panel Antenna
Antenna Gain	Refer to the table “Antenna List”
Channel Control	Auto

For 2.4GHz

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	MOXA	ANT-WDB-ANM-0306	Dipole	3.80 dBi For 2.4GHz
2	MOXA	ANT-WDB-ANM-0502	Dipole	4.62 dBi For 2.4GHz
3	MOXA	ANT-WDB-ARM-02	Dipole	2.04 dBi For 2.4GHz
4	MOXA	ANT-WDB-ARM-0202	Dipole	1.80 dBi For 2.4GHz
5	MOXA	ANT-WSB-AHRM-05-1.5m	Dipole	5.00 dBi For 2.4GHz
6	MOXA	MAT-WDB-CA-RM-2-0205	Dipole	2.50 dBi For 2.4GHz
7	MOXA	MAT-WDB-DA-RM-2-0203-1m	Dipole	2.45 dBi For 2.4GHz
8	MOXA	MAT-WDB-PA-NF-2-0708	Panel	7.63 dBi For 2.4GHz
9	MOXA	ANT-WDB-PNF-1011	Panel	10.33 dBi For 2.4GHz
10	MOXA	ANT-WDB-ONM-0707	Dipole	7.10 dBi For 2.4GHz
11	MOXA	ANT-WDB-ONF-0709	Dipole	7.40 dBi For 2.4GHz
12	MOXA	ANT-WSB-PNF-12-02	Panel	12.34 dBi For 2.4GHz

For 5GHz

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	MOXA	ANT-WDB-ANM-0306	Dipole	5.7dBi For 5.15~5.25GHz 5.7dBi For 5.25~5.35GHz 6.3dBi For 5.47~5.725GHz 6.3dBi For 5.725~5.825GHz
2	MOXA	ANT-WDB-ANM-0502	Dipole	1.41dBi For 5GHz
3	MOXA	ANT-WDB-ARM-02	Dipole	0.81dBi For 5.15~5.25GHz 0.36dBi For 5.25~5.35GHz 0.36dBi For 5.47~5.725GHz -0.39dBi For 5.725~5.825GHz
4	MOXA	ANT-WDB-ARM-0202	Dipole	1.8dBi For 5GHz
5	MOXA	MAT-WDB-CA-RM-2-0205	Dipole	5.7dBi For 5.15~5.25GHz 5.76dBi For 5.25~5.35GHz 5.7dBi For 5.47~5.725GHz 5.2dBi For 5.725~5.825GHz
6	MOXA	MAT-WDB-DA-RM-2-0203-1m	Dipole	2.72dBi For 5.15~5.25GHz 2.72dBi For 5.25~5.35GHz 2.72dBi For 5.47~5.725GHz 2.34dBi For 5.725~5.825GHz
7	MOXA	MAT-WDB-PA-NF-2-0708	Panel	8.77dBi For 5.15~5.25GHz 8.77dBi For 5.25~5.35GHz 8.61dBi For 5.47~5.725GHz 8.18dBi For 5.725~5.825GHz
8	MOXA	ANT-WDB-PNF-1011	Panel	12.04dBi For 5.15~5.25GHz 12.04dBi For 5.25~5.35GHz 11.06dBi For 5.47~5.725GHz 11.06dBi For 5.725~5.825GHz
9	MOXA	ANT-WDB-ONM-0707	Dipole	7.3dBi For 5.15~5.25GHz 7.3dBi For 5.25~5.35GHz 7.5dBi For 5.47~5.725GHz 7.6dBi For 5.725~5.825GHz
10	MOXA	ANT-WDB-ONF-0709	Dipole	8.61dBi For 5.15~5.25GHz 8.15dBi For 5.25~5.35GHz 8.87dBi For 5.47~5.725GHz 8.87dBi For 5.725~5.825GHz
11	MOXA	ANT-WSB5-PNF-16	Panel	16.38dBi For 5.15~5.25GHz 16.38dBi For 5.25~5.35GHz 16.94dBi For 5.47~5.725GHz 16.94dBi For 5.725~5.825GHz

1.2. Test Facility

USA : **FCC Registration Number: TW0033**

Canada : **CAB Identifier Number: TW3023 / Company Number: 26930**

Site Description : Accredited by TAF
Accredited Number: 3023

Test Laboratory : DEKRA Testing and Certification Co., Ltd
Address : No. 5-22, Ruishukeng Linkou District, New Taipei City,
24451, Taiwan

Performed Location : No. 26, Huaya 1st Rd., Guishan Dist., Taoyuan City
333411, Taiwan, R.O.C.

Phone number : +886-3-275-7255

Fax number : +866-3-327-8031

Email address : info.tw@dekra.com

Website : <http://www.dekra.com.tw>

2. RF Exposure Evaluation

2.1. Standard Applicable

According to KDB 447498 D01 (7.1), A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits.

2.2. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3. Test Result of RF Exposure Evaluation

Product : Wireless module
Test Item : RF Exposure Evaluation

WLAN 2.4GHz Peak Gain: 7.40dBi (Dipole Ant no.11)

Band	Frequency	Conducted Peak Power (dBm)	Duty Cycle (%)	Output Power to Antenna (mW)	Power Density at R = 50 cm (mW/cm ²)	Limit (mW/cm ²)	Pass/Fail
WLAN 2.4G	2462	28.58	93.93	767.707	0.1343	1	Pass

Note: The conducted output power is refer to report No.: 2110552R-E3032110118 from the DEKRA.

WLAN 2.4GHz Peak Gain: 12.34dBi (Panel Ant no.12)

Band	Frequency	Conducted Peak Power (dBm)	Duty Cycle (%)	Output Power to Antenna (mW)	Power Density at R = 50 cm (mW/cm ²)	Limit (mW/cm ²)	Pass/Fail
WLAN 2.4G	2437	27.92	93.93	659.471	0.3598	1	Pass

Note: The conducted output power is refer to report No.: 2110552R-E3032110118 from the DEKRA.

WLAN 5GHz Peak Gain: 8.87dBi (Dipole Ant no.10)

Band	Frequency	Conducted Peak Power (dBm)	Duty Cycle (%)	Output Power to Antenna (mW)	Power Density at R = 50 cm (mW/cm ²)	Limit (mW/cm ²)	Pass/Fail
WLAN 5G	5785	26.83	85.87	561.253	0.1377	1	Pass

Note: The conducted output power is refer to report No.: 2110552R-E3032110128 from the DEKRA.

WLAN 5GHz Peak Gain: 16.94dBi (Panel Ant no.11)

Band	Frequency	Conducted Peak Power (dBm)	Duty Cycle (%)	Output Power to Antenna (mW)	Power Density at R = 50 cm (mW/cm ²)	Limit (mW/cm ²)	Pass/Fail
WLAN 5G	5785	26.83	85.87	561.253	0.8831	1	Pass

Note: The conducted output power is refer to report No.: 2110552R-E3032110128 from the DEKRA.