



REPORT No.: SZ25120106W01

TEST REPORT

APPLICANT : iHealth Labs, Inc.

PRODUCT NAME : iHealth Jurni Connected Blood Pressure Monitor

MODEL NAME : BP-300CL

BRAND NAME : iHealth

FCC ID : SLR300CL

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2025-12-10

TEST DATE : 2025-12-12 to 2025-12-23

ISSUE DATE : 2026-01-07



Edited by:

Zeng Xiaoying
Zeng Xiaoying (Rapporteur)

Approved by:

Shen Junsheng
Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555
Http://www.morlab.cn

Fax: 86-755-36698525
E-mail: service@morlab.cn





DIRECTORY

1. Summary of Test Result	4
1.1. Testing Applied Standards	4
1.2. Test Equipment List	5
1.3. Measurement Uncertainty	7
1.4. Testing Laboratory	7
2. General Description	8
2.1. Information of Applicant and Manufacturer	8
2.2. Information of EUT	8
2.3. Channel List of EUT	9
2.4. Test Configuration of EUT	10
2.5. Test Conditions	10
2.6. Test Setup Layout Diagram	10
3. Test Results	13
3.1. Antenna Requirement	13
3.2. Duty Cycle of Test Signal	14
3.3. Maximum Peak Conducted Output Power	15
3.4. Maximum Average Conducted Output Power	16
3.5. 6 dB Bandwidth	17
3.6. Conducted Spurious Emissions and Band Edge	18
3.7. Power Spectral Density	19
3.8. Conducted Emission	20
3.9. Restricted Frequency Bands	21
3.10. Radiated Emission	22
Annex A Test Data and Result	24



REPORT No.: SZ25120106W01

Change History		
Version	Date	Reason for change
1.0	2026-01-07	First edition

1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	/
2	N/A	Duty Cycle of Test Signal	Dec. 15, 2025	Zhu Peihong	PASS	/
3	15.247(b)	Maximum Peak Conducted Output Power	Dec. 15, 2025	Zhu Peihong	PASS	/
4	15.247(b)	Maximum Average Conducted Output Power	Dec. 15, 2025	Zhu Peihong	PASS	/
5	15.247(a)	Bandwidth	Dec. 15, 2025	Zhu Peihong	PASS	/
6	15.247(d)	Conducted Spurious Emission and Band Edge	Dec. 15, 2025	Zhu Peihong	PASS	/
7	15.247(e)	Power Spectral Density	Dec. 15, 2025	Zhu Peihong	PASS	/
8	15.207	Conducted Emission	Dec. 19, 2025	Fan Zehang	PASS	/
9	15.247(d)	Restricted Frequency Bands	Dec. 23, 2025	Xiong Xianhong	PASS	/
10	15.209, 15.247(d)	Radiated Emission	Dec. 23, 2025	Xiong Xianhong	PASS	/

Note 1: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2020 and KDB 558074 D01 v05r02.

Note 2: Any additions, deviation, or exclusions from the method shall be noted in the “Remark”.

1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices



1.2. Test Equipment List

1.2.1 Conducted Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2025.01.15	2026.01.14
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.2.2 Conducted Emission Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	101052	ESPI	R&S	2025.05.15	2026.05.14
LISN	103131	ENV 216	R&S	2025.03.20	2026.03.19
RF Coaxial Cable (DC-100MHz)	BNC	MRE04	Qualwave	2025.05.06	2026.05.05

1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
JS32-RE	Tonscend	5.0.0
TS+ -[JS32-CE]	Tonscend	2.5.0.0

**1.2.4 Radiated Test Equipment**

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Signal Analyzer	MY56060145	N9020A	Agilent	2025.05.13	2026.05.12
Test Antenna - Bi-Log	9163-274	VULB 9163	Schwarzbeck	2025.06.28	2026.06.27
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2025.05.16	2026.05.15
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2025.06.20	2026.06.19
Test Antenna – Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2025.06.20	2026.06.19
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2025.05.13	2026.05.12
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2025.05.13	2026.05.12
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-KK-0.5	Qualwave	2025.09.03	2026.09.02
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-KKF-2	Qualwave	2025.09.03	2026.09.02
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-NN-5	Qualwave	2025.09.03	2026.09.02
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2025.06.21	2028.06.20
Anechoic Chamber	N/A	9m*6m*6m	CRT	2025.04.19	2028.04.18



1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Peak Output Power	$\pm 2.22\text{dB}$	Confidence levels of 95%
Power Spectral Density	$\pm 2.22\text{dB}$	Confidence levels of 95%
Bandwidth	$\pm 5\%$	Confidence levels of 95%
Conducted Spurious Emission	$\pm 2.77\text{dB}$	Confidence levels of 95%
Restricted Frequency Bands	$\pm 5\%$	Confidence levels of 95%
Radiated Emission	$\pm 2.95\text{dB}$	Confidence levels of 95%
Conducted Emission	$\pm 2.44\text{dB}$	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525
FCC Designation Number:	CN1192
FCC Test Firm Registration Number:	226174



2. General Description

2.1. Information of Applicant and Manufacturer

Applicant:	iHealth Labs, Inc.
Applicant Address:	880 W Maude Ave, Sunnyvale, CA 94085 USA
Manufacturer:	ANDON HEALTH CO.,LTD.
Manufacturer Address:	NO.3 Jin Ping Street,Ya An Road,Nankai District, Tianjin 300190, China

2.2. Information of EUT

Product Name:	iHealth Jurni Connected Blood Pressure Monitor
Sample No.:	1#, 4#
Hardware Version:	KD-300-ZFMP01 V1.1
Software Version:	BPM-SH86F7088-V0113-1.0.0
Equipment Type:	Bluetooth LE
Bluetooth Version:	5.3
Modulation Type:	GFSK
Data Rate:	1Mbps
Operating Frequency Range:	2402MHz-2480MHz
Antenna Type:	PCB Antenna
Antenna Gain:	-4.39dBi

Note 1: The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



2.3.Channel List of EUT

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Note 1: The black bold channels were selected for test.

2.4. Test Configuration of EUT


Test mode is used to control the EUT under the maximum power level during test.

2.5. Test Conditions


Temperature (°C):	15–35
Relative Humidity (%):	30–60
Atmospheric Pressure (kPa):	86–106

2.6. Test Setup Layout Diagram

2.6.1. Conducted Measurement




2.6.2. Conducted Emission Measurement




2.6.3.Radiation Measurement


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz





3. Test Results

3.1. Antenna Requirement

3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.2. Test Result

Antenna location	Antenna Type	Coupling Method
☒ Internal ☐ External	☐ FPC Antenna ☐ Spring Antenna ☐ Ceramic Antenna ☐ Integrated Antenna ☐ Dipole Antenna ☒ PCB Antenna ☐ PIFA Antenna ☐ ABS Antenna	☐ I-PEX Connector ☐ SMA Connector ☐ RP-SMA Connector ☐ Metal Shrapnel ☒ Layout

3.2. Duty Cycle of Test Signal

3.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration(T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e.,no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be non constant.

3.2.2. Test Result

Refer to Annex A.1 in this report.



3.3. Maximum Peak Conducted Output Power

3.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

3.3.2. Test Procedures

KDB 558074 Section 8.3.1 was used in order to prove compliance.

3.3.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.3.4. Test Result

Refer to Annex A.2 in this report.



3.4. Maximum Average Conducted Output Power

3.4.1. Requirement

According to FCC section 15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum average conducted output power of the intentional radiator shall not exceed 1 Watt.

3.4.2. Test Procedures

KDB 558074 Section 8.3.2 was used in order to prove compliance.

3.4.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.4.4. Test Result

Refer to Annex A.3 in this report.



3.5.6 dB Bandwidth

3.5.1.Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

3.5.1.Test Procedures

The steps for the first option are as follows:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 100kHz
- c) Set VBW to 300kHz
- d) Detector = peak.
- e) Trace mode = max hold
- f) Sweep time = auto couple
- g) Allow the trace to fully stabilize
- h) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., $RBW = 100\text{ kHz}$, $VBW \geq 3 \times RBW$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be $\geq 6\text{ dB}$.

3.5.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.5.3.Test Result

Refer to Annex A.4 in this report.



3.6. Conducted Spurious Emissions and Band Edge

3.6.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.6.2. Test Procedures

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.

3.6.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.6.4. Test Result

Refer to Annex A.5 and A.6 in this report.

3.7. Power Spectral Density

3.7.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.7.2. Test Procedures

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 3kHz
- d) Set VBW to 10kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level within the RBW

3.7.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.7.4. Test Result

Refer to Annex A.7 in this report.

3.8. Conducted Emission

3.8.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.8.2. Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10.

Test Setup Layout

Refer to chapter 2.6.2 in this report.

3.8.3. Test Result

Refer to Annex A.8 in this report.

3.9. Restricted Frequency Bands

3.9.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

3.9.2. Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

3.9.3. Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.9.4. Test Result

Refer to Annex A.9 in this report.

3.10. Radiated Emission

3.10.1.Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2:For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).



3.10.2.Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

3.10.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.10.4.Test Result

Refer to Annex A.10 in this report.




Annex A Test Data and Result

A.1. Duty Cycle of Test Signal


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1M	2402	Ant1	6.48	11.89	1.12
NVNT	BLE 1M	2440	Ant1	6.48	11.89	1.12
NVNT	BLE 1M	2480	Ant1	6.48	11.89	1.12

Test Graphs

Duty Cycle NVNT BLE 1M 2402MHz Ant1




Duty Cycle NVNT BLE 1M 2440MHz Ant1





Duty Cycle NVNT BLE 1M 2480MHz Ant1




**A.2. Maximum Peak Conducted Output Power**


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	1.08	0	1.08	0.00128	30	Pass
NVNT	BLE 1M	2440	Ant1	0.95	0	0.95	0.00124	30	Pass
NVNT	BLE 1M	2480	Ant1	0.56	0	0.56	0.00114	30	Pass

Test Graphs

Peak Power NVNT BLE 1M 2402MHz Ant1




Peak Power NVNT BLE 1M 2440MHz Ant1





Peak Power NVNT BLE 1M 2480MHz Ant1




**A.3. Maximum Average Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-11.43	11.89	0.46	0.00111	30	Pass
NVNT	BLE 1M	2440	Ant1	-11.66	11.89	0.23	0.00105	30	Pass
NVNT	BLE 1M	2480	Ant1	-11.99	11.89	-0.1	0.00098	30	Pass





Test Graphs

Average Power NVNT BLE 1M 2402MHz Ant1



Average Power NVNT BLE 1M 2440MHz Ant1






**A.4. 6 dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.6889	0.5	Pass
NVNT	BLE 1M	2440	Ant1	0.6675	0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.6729	0.5	Pass





Test Graphs

-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2440MHz Ant1






**A.5. Conducted Spurious Emissions**


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-39.82	-20	Pass
NVNT	BLE 1M	2440	Ant1	-38.91	-20	Pass
NVNT	BLE 1M	2480	Ant1	-35.54	-20	Pass

Test Graphs


Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission




Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission




**A.6. Band Edge**

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-48.37	-20	Pass
NVNT	BLE 1M	2480	Ant1	-50.55	-20	Pass




Test Graphs


Band Edge NVNT BLE 1M 2402MHz Ant1 Ref




Band Edge NVNT BLE 1M 2402MHz Ant1 Emission



Band Edge NVNT BLE 1M 2480MHz Ant1 Ref



Band Edge NVNT BLE 1M 2480MHz Ant1 Emission




**A.7. Power Spectral Density**

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1M	2402	Ant1	-12.86	0	-12.86	8	Pass
NVNT	BLE 1M	2440	Ant1	-13	0	-13	8	Pass
NVNT	BLE 1M	2480	Ant1	-14.11	0	-14.11	8	Pass




Test Graphs

PSD NVNT BLE 1M 2402MHz Ant1




PSD NVNT BLE 1M 2440MHz Ant1





PSD NVNT BLE 1M 2480MHz Ant1





A.8. Conducted Emission

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT + Serial port board + Notebook + Notebook adapter + BT TX

Test voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss}} \text{ [dB]} + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1635	52.83	36.57	65.28	55.28	Line	PASS
2	0.1905	47.43	33.92	64.02	54.02		PASS
3	0.2445	38.57	27.10	61.94	51.94		PASS
4	0.4650	31.53	25.22	56.60	46.60		PASS
5	1.0679	28.79	22.62	56.00	46.00		PASS
6	2.8812	25.57	17.80	56.00	46.00		PASS




(N Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1500	55.37	35.68	66.00	56.00	Neutral	PASS
2	0.1905	47.01	32.68	64.02	54.02		PASS
3	0.2400	39.35	26.93	62.10	52.10		PASS
4	0.7305	28.39	23.01	56.00	46.00		PASS
5	1.8239	27.04	21.91	56.00	46.00		PASS
6	3.0927	28.10	22.28	56.00	46.00		PASS

A.9. Restricted Frequency Bands

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (Horizontal) was recorded in this test report.

Plot for Channel 0



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2374.78	4.4	36.91	32.490	54.00	17.09	150	18	AV	PASS
2378.70	17.9	50.36	32.510	74.00	23.64	150	268	PK	PASS
2381.74	4.5	37.00	32.510	54.00	17.00	150	36	AV	PASS
2386.09	4.5	37.06	32.530	54.00	16.94	150	44	AV	PASS
2386.09	19.8	52.28	32.530	74.00	21.72	150	44	PK	PASS
2387.39	20.3	52.78	32.530	74.00	21.22	150	120	PK	PASS



Level [dBμV/m]

Frequency [Hz]

PK Limit AV Limit Horizontal PK Horizontal AV

AV Detector

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2484.42	17.3	50.31	33.030	74.00	23.69	150	317	PK	PASS
2484.92	4.7	37.70	33.030	54.00	16.30	150	349	AV	PASS
2485.68	17.5	50.48	33.030	74.00	23.52	150	178	PK	PASS
2486.18	4.7	37.73	33.030	54.00	16.27	150	20	AV	PASS
2488.19	17.7	50.69	33.020	74.00	23.31	150	359	PK	PASS
2488.44	4.8	37.81	33.020	54.00	16.19	150	11	AV	PASS



A.10. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m


During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.


Note3: For the frequency, which started from 18GHz to 10th harmonic of the highest frequency, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Plot for Channel 0




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
60.22	60.9	29.90	-30.990	40.00	10.10	150	86	PK	PASS
95.96	64.5	33.95	-30.520	43.50	9.55	150	123	PK	PASS
203.96	62.8	32.64	-30.190	43.50	10.86	150	24	PK	PASS
479.93	57.0	34.68	-22.330	46.00	11.32	150	174	PK	PASS
528.02	56.9	35.51	-21.430	46.00	10.49	150	111	PK	PASS
932.15	48.7	34.20	-14.490	46.00	11.80	150	274	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2314.96	30.9	30.28	-0.590	54.00	23.72	150	85	AV	PASS
2386.09	50.5	51.22	0.690	74.00	22.78	150	96	PK	PASS
3186.01	48.1	32.50	-15.560	54.00	21.50	150	360	AV	PASS
3194.15	56.8	41.30	-15.520	74.00	32.70	150	360	PK	PASS
4803.48	58.9	48.18	-10.720	74.00	25.82	150	311	PK	PASS
4803.48	55.6	44.83	-10.720	54.00	9.17	150	287	AV	PASS
7170.98	41.2	37.43	-3.800	54.00	16.57	150	37	AV	PASS
7178.26	49.7	45.95	-3.740	74.00	28.05	150	111	PK	PASS
9607.05	45.0	43.49	-1.500	54.00	10.51	150	261	AV	PASS
9608.76	51.2	49.74	-1.490	74.00	24.26	150	261	PK	PASS
13327.58	46.0	51.28	5.280	74.00	22.72	150	360	PK	PASS
13520.01	38.2	42.97	4.730	54.00	11.03	150	287	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)


Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
38.94	61.6	32.18	-29.430	40.00	7.82	150	1	PK	PASS
60.22	65.9	34.87	-30.990	40.00	5.13	150	0	PK	PASS
96.02	64.5	34.03	-30.510	43.50	9.47	150	299	PK	PASS
203.96	65.1	34.92	-30.190	43.50	8.58	150	287	PK	PASS
250.00	66.5	38.33	-28.120	46.00	7.67	150	350	PK	PASS
432.02	54.5	31.24	-23.290	46.00	14.76	150	111	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)


Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2313.18	32.0	31.34	-0.630	54.00	22.66	150	84	AV	PASS
2483.89	40.9	41.83	0.900	74.00	32.17	150	108	PK	PASS
3186.43	63.3	47.71	-15.550	74.00	26.29	150	135	PK	PASS
3188.15	51.0	35.49	-15.540	54.00	18.51	150	135	AV	PASS
4803.48	53.9	43.15	-10.720	74.00	30.85	150	311	PK	PASS
4803.48	47.8	37.09	-10.720	54.00	16.91	150	311	AV	PASS
6383.67	53.3	47.98	-5.360	74.00	26.02	150	185	PK	PASS
6390.95	43.9	38.64	-5.280	54.00	15.36	150	185	AV	PASS
7205.26	48.4	44.71	-3.640	54.00	9.29	150	236	AV	PASS
7205.26	54.7	51.10	-3.640	74.00	22.90	150	236	PK	PASS
11089.95	49.2	50.53	1.310	74.00	23.47	150	360	PK	PASS
11243.81	39.2	40.70	1.510	54.00	13.30	150	236	AV	PASS

Plot for Channel 19




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
60.16	61.2	30.21	-30.970	40.00	9.79	150	98	PK	PASS
96.02	64.9	34.35	-30.510	43.50	9.15	150	136	PK	PASS
199.91	62.4	32.19	-30.210	43.50	11.31	150	110	PK	PASS
252.00	64.1	36.07	-28.070	46.00	9.93	150	360	PK	PASS
479.58	57.5	35.12	-22.340	46.00	10.88	150	249	PK	PASS
564.00	56.2	35.40	-20.840	46.00	10.60	150	10	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2442.10	41.7	42.76	1.020	-	-	150	79	PK	NA
2483.00	29.4	30.29	0.900	54.00	23.71	150	350	AV	PASS
3189.86	62.3	46.76	-15.540	74.00	27.24	150	213	PK	PASS
3189.86	52.8	37.24	-15.540	54.00	16.76	150	213	AV	PASS
4249.75	49.7	37.74	-11.960	54.00	16.26	150	37	AV	PASS
4249.75	56.7	44.70	-11.960	74.00	29.30	150	37	PK	PASS
7319.27	59.7	56.00	-3.670	74.00	18.00	150	139	PK	PASS
7319.27	53.3	49.62	-3.670	54.00	4.38	150	111	AV	PASS
9759.19	42.6	41.45	-1.160	54.00	12.55	150	342	AV	PASS
10052.77	49.9	49.41	-0.450	74.00	24.59	150	359	PK	PASS
13784.45	45.7	51.12	5.410	74.00	22.88	150	213	PK	PASS
13966.17	37.3	42.49	5.180	54.00	11.51	150	61	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)


Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
38.94	62.7	33.22	-29.430	40.00	6.78	150	349	PK	PASS
60.16	65.0	34.05	-30.970	40.00	5.95	150	0	PK	PASS
96.02	61.8	31.27	-30.510	43.50	12.23	150	260	PK	PASS
252.00	64.2	36.10	-28.070	46.00	9.90	150	6	PK	PASS
395.98	53.8	29.60	-24.230	46.00	16.40	150	109	PK	PASS
533.20	53.5	32.10	-21.380	46.00	13.90	150	109	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)


Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2439.43	40.5	41.46	1.000	-	-	150	104	PK	NA
2440.32	29.4	30.40	1.010	-	-	150	0	AV	NA
3188.15	50.9	35.37	-15.540	54.00	18.63	150	60	AV	PASS
3192.86	58.6	43.07	-15.520	74.00	30.93	150	36	PK	PASS
5092.35	45.4	36.68	-8.670	54.00	17.32	150	112	AV	PASS
5097.06	52.5	43.91	-8.600	74.00	30.09	150	138	PK	PASS
6390.95	44.4	39.13	-5.280	54.00	14.87	150	341	AV	PASS
6391.38	53.0	47.71	-5.270	74.00	26.29	150	360	PK	PASS
9623.33	49.6	48.12	-1.450	74.00	25.88	150	360	PK	PASS
9632.76	41.0	39.54	-1.420	54.00	14.46	150	36	AV	PASS
11515.96	39.7	42.39	2.680	54.00	11.61	150	354	AV	PASS
11548.96	47.4	50.17	2.750	74.00	23.83	150	138	PK	PASS

Plot for Channel 39




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
60.16	61.5	30.52	-30.970	40.00	9.48	150	111	PK	PASS
96.02	64.0	33.47	-30.510	43.50	10.03	150	149	PK	PASS
209.49	63.0	33.09	-29.860	43.50	10.41	150	74	PK	PASS
396.04	56.7	32.42	-24.230	46.00	13.58	150	49	PK	PASS
481.17	53.3	31.02	-22.310	46.00	14.98	150	174	PK	PASS
816.04	51.6	35.25	-16.330	46.00	10.75	150	99	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2479.88	29.4	30.34	0.920	-	-	150	61	AV	NA
2483.44	40.4	41.33	0.900	-	-	150	6	PK	NA
3196.29	49.9	34.37	-15.520	54.00	19.63	150	355	AV	PASS
3196.72	60.2	44.66	-15.520	74.00	29.34	150	359	PK	PASS
4959.48	46.7	36.53	-10.130	54.00	17.47	150	264	AV	PASS
4959.91	52.9	42.77	-10.130	74.00	31.23	150	242	PK	PASS
7439.27	48.9	44.44	-4.440	54.00	9.56	150	189	AV	PASS
7439.27	53.9	49.44	-4.440	74.00	24.56	150	189	PK	PASS
9522.19	49.5	48.07	-1.470	74.00	25.93	150	60	PK	PASS
9634.48	40.9	39.53	-1.410	54.00	14.47	150	189	AV	PASS
12303.27	48.2	50.94	2.760	74.00	23.06	150	344	PK	PASS
12480.27	38.0	41.74	3.710	54.00	12.26	150	317	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
39.47	61.9	32.65	-29.270	40.00	7.35	150	0	PK	PASS
60.16	65.2	34.22	-30.970	40.00	5.78	150	0	PK	PASS
96.02	64.7	34.21	-30.510	43.50	9.29	150	250	PK	PASS
191.91	56.0	26.35	-29.610	43.50	17.15	150	73	PK	PASS
246.41	58.4	30.19	-28.220	46.00	15.81	150	174	PK	PASS
480.34	51.8	29.47	-22.320	46.00	16.53	150	299	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2438.99	29.4	30.44	1.000	54.00	23.56	150	104	AV	PASS
2439.88	40.9	41.86	1.010	74.00	32.14	150	0	PK	PASS
3190.72	51.4	35.88	-15.540	54.00	18.12	150	242	AV	PASS
3190.72	60.0	44.46	-15.540	74.00	29.54	150	242	PK	PASS
7440.13	62.4	57.94	-4.460	74.00	16.06	150	191	PK	PASS
7440.13	57.6	53.14	-4.460	54.00	0.86	150	191	AV	PASS
9552.62	41.6	40.30	-1.260	54.00	13.70	150	139	AV	PASS
9567.62	51.0	49.61	-1.340	74.00	24.39	150	139	PK	PASS
11173.09	48.9	50.10	1.180	74.00	23.90	150	360	PK	PASS
11569.96	39.4	42.23	2.800	54.00	11.77	150	163	AV	PASS
16485.39	45.3	51.00	5.700	74.00	23.00	150	87	PK	PASS
16900.68	35.7	42.96	7.270	54.00	11.04	150	191	AV	PASS

END OF REPORT