TEST REPORT

Applicant	Maison Battat Inc.
Address	8440 Darnely, Montreal, QC Canada H4T 1M4，Quebec，Canada

Manufacturer or Supplier	Maison Battat Inc.
Address	8440 Darnely, Montreal, QC Canada H4T 1M4，Quebec，Canada
Product	Musical Light Show Microphone
Brand Name	N/A
Model	BT2523Z
Additional Model & Model Difference	BT2523; see items 3.1
Date of tests	Aug. 09, 2018 ~ Aug. 22, 2018

the tests have been carried out according to the requirements of the following standards:

☒ **FCC Part 15, Subpart C, Section 15.247**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Ryan Lu Project Engineer / EMC Department	Approved by Glyn He Supervisor / EMC Department
	 Date: Oct. 08, 2018

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD 4
1 SUMMARY OF TEST RESULTS 5
2 MEASUREMENT UNCERTAINTY 5
3 GENERAL INFORMATION 6
3.1 GENERAL DESCRIPTION OF EUT 6
3.2 DESCRIPTION OF TEST MODES 7
3.2.1. CONFIGURATION OF SYSTEM UNDER TEST 8
3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL 8
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS 10
3.4 DESCRIPTION OF SUPPORT UNITS 10
4 TEST TYPES AND RESULTS 11
4.1. RADIATED EMISSION AND BANDEDGE MEASUREMENT 11
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT 11
4.1.2 TEST INSTRUMENTS 12
4.1.3 TEST PROCEDURES 13
4.1.4 DEVIATION FROM TEST STANDARD 14
4.1.5 TEST SETUP 14
4.1.6 EUT OPERATING CONDITIONS 15
4.1.7 TEST RESULTS 16
4.2 NUMBER OF HOPPING FREQUENCY USED 24
4.2.1 LIMIT OF HOPPING FREQUENCY USED 24
4.2.2 TEST SETUP 24
4.2.3 TEST INSTRUMENTS 24
4.2.4 TEST PROCEDURES 25
4.2.5 DEVIATION FROM TEST STANDARD 25
4.2.6 TEST RESULTS 25
4.3 DWELL TIME ON EACH CHANNEL 28
4.3.1 LIMIT OF DWELL TIME USED 28
4.3.2 TEST SETUP 28
4.3.3 TEST INSTRUMENTS 28
4.3.4 TEST PROCEDURES 28
4.3.5 DEVIATION FROM TEST STANDARD 29
4.3.6 TEST RESULTS 29
4.4 CHANNEL BANDWIDTH 32

4.4.1 LIMITS OF CHANNEL BANDWIDTH 32
4.4.2 TEST SETUP 32
4.4.3 TEST INSTRUMENTS 32
4.4.4 TEST PROCEDURE 32
4.4.5 DEVIATION FROM TEST STANDARD 32
4.4.6 EUT OPERATING CONDITION 32
4.4.7 TEST RESULTS 33
4.5 HOPPING CHANNEL SEPARATION 37
4.5.1 LIMIT OF HOPPING CHANNEL SEPARATION 37
4.5.2 TEST SETUP 37
4.5.3 TEST INSTRUMENTS 37
4.5.4 TEST PROCEDURES 37
4.5.5 DEVIATION FROM TEST STANDARD 37
4.5.6 TEST RESULTS 38
4.6 CONDUCTED OUTPUT POWER 42
4.6.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT 42
4.6.2 TEST SETUP 42
4.6.3 TEST INSTRUMENTS 42
4.6.4 TEST PROCEDURES 42
4.6.5 DEVIATION FROM TEST STANDARD 42
4.6.6 EUT OPERATING CONDITION 42
4.6.7 TEST RESULTS 43
4.7 OUT OF BAND EMISSION MEASUREMENT 44
4.7.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT 44
4.7.2 TEST INSTRUMENTS 44
4.7.3 TEST PROCEDURE 44
4.7.4 DEVIATION FROM TEST STANDARD 44
4.7.5 EUT OPERATING CONDITION 44
4.7.6 TEST RESULTS 44
5 PHOTOGRAPHS OF THE TEST CONFIGURATION 49
6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB 50

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF180809N014	Original release	Aug. 24, 2018
RF180809N014R1	Supersede original report RF180809N014, change FCC ID number and model number, but don't retest after engineer evaluate.	Oct. 08, 2018

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	**TEST TYPE AND LIMIT**	**RESULT**	**REMARK**
15.207	AC Power Conducted Emission	N/A	Power by Battery
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.247(d)& 15.209	Transmitter Radiated Emission	PASS	Meet the requirement of limit.
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Radiated emissions	9KHz ~ 30MHz	2.90dB
	30MHz ~ 1GMHz	3.76dB
	1GHz ~ 18GHz	4.84dB
	18GHz ~ 40GHz	4.96dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Musical Light Show Microphone
MODEL NO.	BT2523Z
ADDITIONAL MODEL	BT2523
FCC ID	SLURFBT2523Z
POWER SUPPLY	DC 4.5V(1.5V*AAA*3) from Battery
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK, π/4 DQPSK, 8DPSK
OPERATING FREQUENCY	2402MHz~2480MHz
NUMBER OF CHANNEL	79
PEAK OUTPUT POWER	1.578 mW (Max. Measured)
ANTENNA TYPE	PCB Antenna, 0dBi Gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
3. Please refer to the EUT photo document (Reference No.: 180809N014) for detailed product photo.
4. Additional model BT2523 is identical with the test model BT2523Z except the model no. for trading purpose.

3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.2.1. CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports
The worst case was found when positioned on Y axis for radiated emission.
Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
A	√	√	-	√	Powered By New Battery

Where **RE<1G:** Radiated Emission below 1GHz **RE≥1G:** Radiated Emission above 1GHz
PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

RADIATED EMISSION TEST (BELOW 1 GHz):

RADIATED EMISSION TEST (BELOW 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	39	FHSS	GFSK	DH5

For the test results, only the worst case was shown in test report.

RADIATED EMISSION TEST (ABOVE 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.

☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	25deg. C, 55%RH	DC 4.5V from New Battery	Xue Wang
RE≥1G	25deg. C, 55%RH	DC 4.5V from New Battery	Xue Wang
PLC	-	-	-
APCM	25deg. C, 60%RH	DC 4.5V from New Battery	Sen He

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. Section 15.247
ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit without any other necessary accessory or support units.

4 TEST TYPES AND RESULTS

4.1. RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU40	100449	Mar. 21,18	Mar. 20,19
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV7	102331	Nov. 04,17	Nov. 03,18
Active Loop Antenna (9KHz -30MHz)	SCHWARZBECK	FMZB 1519B	1519B-045	May 31,18	May 30,19
Amplifier (9KHz -1GHz)	Burgeon	BPA-530	100210	Apr. 18,18	Apr. 18,19
Bilog Antenna (20MHz -2GHz)	Teseq	CBL 6111D	30643	Jul. 28, 18	Jul. 27, 19
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	Jun. 02,18	Jun. 01,19
Horn Antenna (18GHz -40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170242	May 05,18	May 04,19
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Feb. 10,18	Feb. 09,19
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A
Broadband Preamplifier (1GHz~18GHz)	SCHWARZBECK	BBV9718	305	Apr. 18,18	Apr. 18,19
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 08,17	Nov. 07,18
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug. 10,18	Aug. 09,19

NOTE:

1. The test was performed in 966 Chamber.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
3. The horn antenna is used only for the measurement of emission frequency above1GHz if tested.
4. The FCC Site Registration No. is 749762.

4.1.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 1.5 meters(above 1GHz) and 0.8 meters(below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. For below 1GHz was used bilog antenna, and above 1GHz was used horn antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.

g. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.

2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.

3. Bluetooth duty factor correction is not correct as it is based on 79 channels, worst case would be with AFH enabled and device using the minimum of 20 channels. Channel hop rate = 800 hops/second (AFH Mode), Adjusted channel hop rate for DH5 mode = 133.33 hops/second, Time per channel hop = 1 / 133.33 hops/second = 7.5 ms, Time to cycle through all channels = 7.5 x 20 channels = 150 ms, Number of times transmitter hits on one channel = 100 ms / 150 ms = 1 time(s), Worst case dwell time = 7.5 ms, Duty cycle connection factor = 20log10(7.5ms / 100ms) = -22.5 dB. Average value = peak reading + 20log(duty cycle).

4. All modes of operation were investigated and the worst-case emissions are reported.

5. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file test setup photo.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP

Below 30MHz test setup



Below 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

Above 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

a. Set the EUT under full load condition and placed them on a testing table.

b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.

c. The necessary accessories enable the EUT in full functions.

4.1.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:

GFSK DH5

CHANNEL	Channel 39	**DETECTOR FUNCTION**	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	30.00	19.99 QP	40.00	-20.01	1.00 H	323	31.12	-11.13
2	87.52	19.76 QP	40.00	-20.24	1.00 H	311	39.61	-19.85
3	561.63	26.23 QP	46.00	-19.77	1.00 H	359	29.92	-3.69
4	631.59	26.90 QP	46.00	-19.10	1.00 H	85	29.97	-3.07
5	836.78	29.20 QP	46.00	-16.80	1.00 H	123	30.10	-0.90
6	**875.64**	**32.25 QP**	**46.00**	**-13.75**	**1.00 H**	**294**	**32.69**	**-0.44**

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.



CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.00	20.40 QP	40.00	-19.60	1.00 V	251	31.53	-11.13
2	87.52	18.88 QP	40.00	-21.12	1.00 V	69	38.73	-19.85
3	406.19	21.31 QP	46.00	-24.69	1.00 V	125	29.63	-8.32
4	446.60	21.26 QP	46.00	-24.74	1.00 V	158	29.82	-8.56
5	533.65	24.09 QP	46.00	-21.91	1.00 V	226	29.85	-5.76
6	874.09	32.05 QP	46.00	-13.95	1.00 V	234	32.40	-0.35

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.



ABOVE 1GHz DATA

BT_GFSK

CHANNEL	TX Channel 0	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	2390.00	57.98 PK	74.00	-16.02	1.00 H	5	55.93	2.05
2	2390.00	35.48 AV	54.00	-18.52	1.00 H	5	33.43	2.05
3	*2402.00	85.62 PK			1.00 H	5	83.48	2.14
4	*2402.00	63.12 AV			1.00 H	5	60.98	2.14
5	4804.00	55.68 PK	74.00	-18.32	1.12 H	248	50.86	4.82
6	4804.00	33.18 AV	54.00	-20.82	1.12 H	248	28.36	4.82
7	#7206.00	55.17 PK	74.00	-18.83	1.00 H	135	46.54	8.63
8	#7206.00	32.67 AV	54.00	-21.33	1.00 H	135	24.04	8.63
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	2390.00	54.86 PK	74.00	-19.14	1.00 V	204	52.81	2.05
2	2390.00	32.36 AV	54.00	-21.64	1.00 V	204	30.31	2.05
3	*2402.00	83.68 PK			1.00 V	204	81.54	2.14
4	*2402.00	61.18 AV			1.00 V	204	59.04	2.14
5	4804.00	54.56 PK	74.00	-19.44	1.42 V	215	49.74	4.82
6	4804.00	32.06 AV	54.00	-21.94	1.42 V	215	27.24	4.82
7	#7206.00	56.34 PK	74.00	-17.66	1.00 V	228	47.71	8.63
8	#7206.00	33.84 AV	54.00	-20.16	1.00 V	228	25.21	8.63

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	86.25 PK			1.45 H	225	83.84	2.41
2	*2441.00	63.75 AV			1.45 H	225	61.34	2.41
3	4882.00	55.81 PK	74.00	-18.19	1.42 H	305	50.82	4.99
4	4882.00	33.31 AV	54.00	-20.69	1.42 H	305	28.32	4.99
5	7323.00	56.18 PK	74.00	-17.82	1.68 H	244	47.41	8.77
6	7323.00	33.68 AV	54.00	-20.32	1.68 H	244	24.91	8.77
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	84.65 PK			1.00 V	145	82.24	2.41
2	*2441.00	62.15 AV			1.00 V	145	59.74	2.41
3	4882.00	55.23 PK	74.00	-18.77	1.00 V	185	50.24	4.99
4	4882.00	32.73 AV	54.00	-21.27	1.00 V	185	27.74	4.99
5	7323.00	56.48 PK	74.00	-17.52	1.28 V	248	47.71	8.77
6	7323.00	33.98 AV	54.00	-20.02	1.28 V	248	25.21	8.77

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	85.50 PK			1.56 H	141	82.82	2.68
2	*2480.00	63.00 AV			1.56 H	141	60.32	2.68
3	2483.50	65.78 PK	74.00	-8.22	1.56 H	141	63.08	2.70
4	2483.50	43.28 AV	54.00	-10.72	1.56 H	141	40.58	2.70
5	4960.00	54.26 PK	74.00	-19.74	1.00 H	225	49.09	5.17
6	4960.00	31.76 AV	54.00	-22.24	1.00 H	225	26.59	5.17
7	7440.00	56.22 PK	74.00	-17.78	1.42 H	223	47.32	8.90
8	7440.00	33.72 AV	54.00	-20.28	1.42 H	223	24.82	8.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	83.57 PK			1.42 V	236	80.89	2.68
2	*2480.00	61.07 AV			1.42 V	236	58.39	2.68
3	2483.50	61.23 PK	74.00	-12.77	1.42 V	236	58.53	2.70
4	2483.50	38.73 AV	54.00	-15.27	1.42 V	236	36.03	2.70
5	4960.00	53.26 PK	74.00	-20.74	1.00 V	145	48.09	5.17
6	4960.00	30.76 AV	54.00	-23.24	1.00 V	145	25.59	5.17
7	7440.00	55.18 PK	74.00	-18.82	1.00 V	271	46.28	8.90
8	7440.00	32.68 AV	54.00	-21.32	1.00 V	271	23.78	8.90

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

BT_8DPSK

CHANNEL	TX Channel 0	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	2390.00	55.39 PK	74.00	-18.61	1.00 H	263	53.34	2.05
2	2390.00	32.89 AV	54.00	-21.11	1.00 H	263	30.84	2.05
3	*2402.00	83.80 PK			1.00 H	225	81.66	2.14
4	*2402.00	61.30 AV			1.00 H	225	59.16	2.14
5	4804.00	54.82 PK	74.00	-19.18	1.35 H	296	50.00	4.82
6	4804.00	32.32 AV	54.00	-21.68	1.35 H	296	27.50	4.82
7	#7206.00	55.73 PK	74.00	-18.27	1.52 H	42	47.10	8.63
8	#7206.00	33.23 AV	54.00	-20.77	1.52 H	42	24.60	8.63
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	2390.00	53.27 PK	74.00	-20.73	1.15 V	241	51.22	2.05
2	2390.00	30.77 AV	54.00	-23.23	1.15 V	241	28.72	2.05
3	*2402.00	82.56 PK			1.00 V	325	80.42	2.14
4	*2402.00	60.06 AV			1.00 V	325	57.92	2.14
5	4804.00	53.64 PK	74.00	-20.36	1.25 V	201	48.82	4.82
6	4804.00	31.14 AV	54.00	-22.86	1.25 V	201	26.32	4.82
7	#7206.00	54.82 PK	74.00	-19.18	1.00 V	11	46.19	8.63
8	#7206.00	32.32 AV	54.00	-21.68	1.00 V	11	23.69	8.63

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	86.68 PK			1.68 H	326	84.27	2.41
2	*2441.00	64.18 AV			1.68 H	326	61.77	2.41
3	4882.00	52.41 PK	74.00	-21.59	1.00 H	236	47.42	4.99
4	4882.00	29.91 AV	54.00	-24.09	1.00 H	236	24.92	4.99
5	7323.00	54.39 PK	74.00	-19.61	1.28 H	257	45.62	8.77
6	7323.00	31.89 AV	54.00	-22.11	1.28 H	257	23.12	8.77
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	82.62 PK			1.45 V	228	80.21	2.41
2	*2441.00	60.12 AV			1.45 V	228	57.71	2.41
3	4882.00	54.85 PK	74.00	-19.15	1.00 V	274	49.86	4.99
4	4882.00	32.35 AV	54.00	-21.65	1.00 V	274	27.36	4.99
5	7323.00	55.92 PK	74.00	-18.08	1.57 V	264	47.15	8.77
6	7323.00	33.42 AV	54.00	-20.58	1.57 V	264	24.65	8.77

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	79.36 PK			1.00 H	57	76.68	2.68
2	*2480.00	56.86 AV			1.00 H	57	54.18	2.68
3	**2483.50**	**69.04 PK**	**74.00**	**-4.96**	**1.00 H**	**167**	**66.34**	**2.70**
4	2483.50	46.54 AV	54.00	-7.46	1.00 H	167	43.84	2.70
5	4960.00	55.26 PK	74.00	-18.74	1.00 H	153	50.09	5.17
6	4960.00	32.76 AV	54.00	-21.24	1.00 H	153	27.59	5.17
7	7440.00	56.32 PK	74.00	-17.68	1.58 H	236	47.42	8.90
8	7440.00	33.82 AV	54.00	-20.18	1.58 H	236	24.92	8.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	76.80 PK			1.54 V	236	74.12	2.68
2	*2480.00	54.30 AV			1.54 V	236	51.62	2.68
3	2483.50	63.97 PK	74.00	-10.03	1.53 V	268	61.27	2.70
4	2483.50	41.47 AV	54.00	-12.53	1.53 V	268	38.77	2.70
5	4960.00	54.18 PK	74.00	-19.82	1.00 V	228	49.01	5.17
6	4960.00	31.68 AV	54.00	-22.32	1.00 V	228	26.51	5.17
7	7440.00	55.84 PK	74.00	-18.16	1.65 V	284	46.94	8.90
8	7440.00	33.34 AV	54.00	-20.66	1.65 V	284	24.44	8.90

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

4.2 NUMBER OF HOPPING FREQUENCY USED

4.2.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

4.2.2 TEST SETUP



4.2.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	Jun. 13,18	Jun. 12,19
Power Sensor	Keysight	U2021XA	MY55060018	Jun. 13,18	Jun. 12,19
Power Meter	Anritsu	ML2495A	1139001	Apr. 13,18	Apr. 13,19
Power Sensor	Anritsu	MA2411B	1531155	Apr. 13,18	Apr. 13,19
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 21, 17	Oct.20, 18
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.05,17	Sep. 04,18
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 08,17	Nov. 07,18
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 04,17	Nov. 03,18
Signal Generator	Agilent	N5183A	MY50140980	Jan. 02,18	Jan. 01,19
Agile Signal Generator	Agilent	8645A	Agilent	Sep.01, 17	Aug.31, 18
Spectrum Analyzer	Keysight	N9020A	MY55400499	Mar. 21,18	Mar. 20,19
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY56200288	Jan. 02,18	Jan. 01,19
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Jul.06, 18	Jul. 05, 19
Attenuator	MINI	BW-S10W2+	S130129FGE2	N/A	N/A
DC Source	Keysight	E3642A	MY56146098	N/A	N/A

NOTE:

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

4.2.4 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.

d. Set the SA on View mode and then plot the result on SA screen.

e. Repeat above procedures until all frequencies measured were completed.

4.2.5 DEVIATION FROM TEST STANDARD

No deviation.

4.2.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

GFSK


RBW 100 kHz
VBW 300 kHz
SWT 1.09 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-1.57 dBm
2.40200 GHz
Marker 2 [T1]
-1.75 dBm
2.44200 GHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
Center 2.42142 GHz
4.2 MHz/
Span 42 MHz


RBW 100 kHz
VBW 300 kHz
SWT 1.09 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-2.07 dBm
2.44300 GHz
Marker 2 [T1]
-2.99 dBm
2.48000 GHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
Center 2.4634 GHz
4.2 MHz/
Span 42 MHz

8DPSK


RBW 100 kHz
VBW 300 kHz
SWT 1.09 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-6.00 dBm
2.40200 GHz
Marker 2 [T1]
-7.23 dBm
2.44200 GHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
Center 2.42142 GHz
4.2 MHz/
Span 42 MHz


RBW 100 kHz
VBW 300 kHz
SWT 1.09 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-6.89 dBm
2.44300 GHz
Marker 2 [T1]
-9.16 dBm
2.48000 GHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
Center 2.4634 GHz
4.2 MHz/
Span 42 MHz

4.3 DWELL TIME ON EACH CHANNEL

4.3.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.3.4 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.

d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.

e. Repeat above procedures until all different time-slot modes have been completed.

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 TEST RESULTS

GFSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	5	48	303.36	0.426	129.23	400	PASS
DH3	79	31.6	5	25	158	1.67	263.86	400	PASS
DH5	79	31.6	5	16	101.12	2.72	275.05	400	PASS

8DPSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
3DH1	79	31.6	5	48	303.36	0.306	92.828	400	PASS
3DH3	79	31.6	5	25	158	1.69	267.02	400	PASS
3DH5	79	31.6	5	16	101.12	2.752	278.28	400	PASS

NOTE: Test plots of the transmitting time slot are shown on next page.

GFSK

DH1





DH3





DH5





8DPSK

3DH1





3DH3





3DH5





4.4 CHANNEL BANDWIDTH

4.4.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.4.4 TEST PROCEDURE

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.

d. Repeat above procedures until all frequencies measured were complete.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.4.7 TEST RESULTS

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.10
39	2441	1.04
78	2480	1.04

CH 0



CH 39


RBW 30 kHz
VBW 100 kHz
SWT 1.06 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-23.87 dBm
2.44044 GHz
Delta 2 [T1]
0.00 dB
1.04 MHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
D1 -3.87 dBm
D2 -23.87 dBm
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
F1
F2
Center 2.441 GHz
250 kHz/
Span 2.5 MHz

CH 78


RBW 30 kHz
VBW 100 kHz
SWT 1.06 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-24.63 dBm
2.47944 GHz
Delta 2 [T1]
0.00 dB
1.04 MHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
D1 -4.63 dBm
D2 -24.63 dBm
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
F1
F2
Center 2.48 GHz
250 kHz/
Span 2.5 MHz

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.35
39	2441	1.36
78	2480	1.37

CH 0



CH 39


RBW 30 kHz
VBW 100 kHz
SWT 1.06 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-28.96 dBm
2.44028 GHz
Delta 2 [T1]
0.00 dB
1.36 MHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
D1 -8.96 dBm
D2 -28.96 dBm
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
F1
F2
Center 2.441 GHz
250 kHz/
Span 2.5 MHz

CH 78


RBW 30 kHz
VBW 100 kHz
SWT 1.06 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-31.02 dBm
2.47929 GHz
Delta 2 [T1]
0.00 dB
1.37 MHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
D1 -11.02 dBm
D2 -31.02 dBm
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
F1
F2
Center 2.48 GHz
250 kHz/
Span 2.5 MHz

4.5 HOPPING CHANNEL SEPARATION

4.5.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.5.4 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 TEST RESULTS

GFSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.01	1.10	0.73	PASS
39	2441	1.00	1.04	0.69	PASS
78	2480	1.01	1.04	0.69	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

CH 0



CH 39


RBW 30 kHz
VBW 100 kHz
SWT 1.06 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-3.88 dBm
2.44104 GHz
Delta 2 [T2]
0.01 dB
1.00 MHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
Center 2.4415 GHz
250 kHz/
Span 2.5 MHz

CH 78


RBW 30 kHz
VBW 100 kHz
SWT 1.06 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T2]
-4.68 dBm
2.47904 GHz
Delta 2 [T1]
0.45 dB
1.01 MHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
Center 2.4795 GHz
250 kHz/
Span 2.5 MHz

8DPSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	1.35	0.90	PASS
39	2441	1.00	1.36	0.91	PASS
78	2480	1.01	1.37	0.91	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

CH 0



CH 39


RBW 30 kHz
VBW 100 kHz
SWT 1.06 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-8.66 dBm
2.44084 GHz
Delta 2 [T2]
2.35 dB
1.00 MHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
Center 2.4415 GHz
250 kHz/
Span 2.5 MHz

CH 78


RBW 30 kHz
VBW 100 kHz
SWT 1.06 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T2]
-11.31 dBm
2.47886 GHz
Delta 2 [T1]
0.94 dB
1.01 MHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
Center 2.4795 GHz
250 kHz/
Span 2.5 MHz

4.6 CONDUCTED OUTPUT POWER

4.6.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 125mW.

4.6.2 TEST SETUP



10dB ATTENUATION PAD

4.6.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.6.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A peak power meter was used to read the response of the peak power sensor. Record the peak power level.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.6.7 TEST RESULTS

MAXIMUM PEAK OUTPUT POWER

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	**1.98**	**1.578**	125	PASS
39	2441	1.48	1.406	125	PASS
78	2480	1.07	1.279	125	PASS

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	1.24	1.33	125	PASS
39	2441	0.86	1.219	125	PASS
78	2480	0.27	1.064	125	PASS

AVERAGE OUTPUT POWER(FOR REFERENCE)

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	**0.07**	**1.016**
39	2441	-0.41	0.910
78	2480	-0.93	0.807

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	-3.62	0.435
39	2441	-3.94	0.404
78	2480	-4.58	0.348

4.7 OUT OF BAND EMISSION MEASUREMENT

4.7.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100KHz RBW).

4.7.2 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.7.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. of Spectrum Analyzer was set RBW to 100 kHz and VBW to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. Detector = PEAK and Trace mode = Max Hold. The band edges was measured and recorded.

4.7.4 DEVIATION FROM TEST STANDARD

No deviation.

4.7.5 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.7.6 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.

GFSK

Low Channel





High Channel





8DPSK

Low Channel





High Channel





GFSK

Hopping on Low Channel





Hopping on High Channel





8DPSK

Hopping on Low Channel





Hopping on High Channel





5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---