

TEST REPORT

Product Name : Smart Portable Projector
Model Number : J61-7K4, J61-7KA, J61-7KB, J61-7KC, J61-7KD,
J61-7KE, J61-7KF
FCC ID : SMC-C62A

Prepared for : SHENZHEN HOLATEK CO., LTD.
Address : #12,Building 1,Chongwen Park, Nanshan Zhiyuan,3370
Liuxian Ave, Nanshan District, Shenzhen, China

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone,Nanshan District,
Shenzhen, Guangdong, China

Tel: (0755) 26954280
Fax: (0755) 26954282

Report Number : ENS2502280323W00103R
Date(s) of Tests : March 1, 2025 to March 25, 2025
Date of issue : March 26, 2025

TABLE OF CONTENTS

1 TEST RESULT CERTIFICATION	3
2 EUT TECHNICAL DESCRIPTION	5
3 SUMMARY OF TEST RESULT	6
4 TEST METHODOLOGY	7
4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS	7
4.2 MEASUREMENT EQUIPMENT USED	7
4.3 DESCRIPTION OF TEST MODES	8
5 FACILITIES AND ACCREDITATIONS	9
5.1 FACILITIES	9
5.2 EQUIPMENT	9
5.3 LABORATORY ACCREDITATIONS AND LISTINGS	9
6 TEST SYSTEM UNCERTAINTY	10
7 SETUP OF EQUIPMENT UNDER TEST	11
7.1 RADIO FREQUENCY TEST SETUP 1	11
7.2 RADIO FREQUENCY TEST SETUP 2	11
7.3 CONDUCTED EMISSION TEST SETUP	14
7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM	15
7.5 SUPPORT EQUIPMENT	15
8 TEST REQUIREMENTS	16
8.1 DTS 6DB BANDWIDTH	16
8.2 DTS 99%BANDWIDTH	18
8.3 MAXIMUM PEAK CONDUCTED OUTPUT POWER	32
8.4 MAXIMUM POWER SPECTRAL DENSITY	46
8.5 UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS	60
8.6 RADIATED SPURIOUS EMISSION	84
8.7 CONDUCTED EMISSION TEST	132
8.8 ANTENNA APPLICATION	135
9 APPENDIX PHOTOGRAPHS OF EUT	136
10 APPENDIX PHOTOGRAPHS OF TEST SETUP	137

1 TEST RESULT CERTIFICATION

Applicant : SHENZHEN HOLATEK CO., LTD.
Address : #12,Building 1,Chongwen Park, Nanshan Zhiyuan,3370 Liuxian Ave, Nanshan District, Shenzhen, China
Manufacturer : SHENZHEN HOLATEK CO., LTD.
Address : #12,Building 1,Chongwen Park, Nanshan Zhiyuan,3370 Liuxian Ave, Nanshan District, Shenzhen, China
EUT : Smart Portable Projector
Model Name : J61-7K4, J61-7KA, J61-7KB, J61-7KC, J61-7KD, J61-7KE, J61-7KF
Trademark : JMGO

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C	PASS
IC RSS-GEN, Issue 5(04-2018)+A1(03-2019)+A2(02-2021) IC RSS-247 Issue 3(08-2017)	PASS

The above equipment was tested by EMTEK(SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2, Part 15.247, IC RSS-247 Issue 3 and IC RSS-GEN, Issue 5.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : March 1, 2025 to March 25, 2025

Prepared by : 
Una Yu /Editor

Reviewer : 
Joe Xia /Supervisor

Approve & Authorized Signer : 
Lisa Wang/Manager



Modified History

Version	Report No.	Revision Date	Summary
Ver.1.0	ENS2502280323W00103R	/	Original Report



2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
Product:	Smart Portable Projector
Model Number:	J61-7K4, J61-7KA, J61-7KB, J61-7KC, J61-7KD, J61-7KE, J61-7KF (Note: All models are identical in circuitry and electrical, mechanical and physical construction; It is just that the number of laser light sources used by different models is not the same. Mode J61-7K4 was Chosen final test.)
Test Sample S/N:	N/A
Variant Number:	N/A
IEEE 802.11 WLAN Mode Supported:	802.11b 802.11g 802.11n(20MHz channel bandwidth) 802.11n(40MHz channel bandwidth)
Modulation:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Operating Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20); 2422-2452MHz for 802.11n(HT40);
Number of Channels:	11 channels for 802.11b/g/n(HT20); 7 Channels for 802.11n(HT40);
Antenna Port:	☒ Antenna port 1, ☒ Antenna port 2
Antenna Type:	☒ ANT 1: FPC Antenna ☒ ANT 2: FPC Antenna
Antenna Gain:	☒ ANT 1: 1.7 dBi ☒ ANT 2: 1.8 dBi (Note: The antenna information is provided by the customers, which will have a certain impact on the test results.)
Power Supply:	DC 20V from adapter
Adapter:	Adapter 1 MODEL:PD065E-G1C0AVU INPUT:100-240V~50/60Hz 1.5A OUTPUT:5.0V/3A or 9.0V/3A or 12.0V/3A or 15.0V/3A or 20.0V/3.25A Adapter 2: MODEL:XY-PD065U75 INPUT:100-240V~50/60Hz 1.5A OUTPUT:5.0V/3A or 9.0V/3A or 12.0V/3A or 15.0V/3A or 20.0V/3.25A 65W
Test Voltage:	AC 120V/60Hz
Temperature Range:	0°C ~ +40°C
Software Version:	1.1.21.6
Hardware Version:	Ver B

3 SUMMARY OF TEST RESULT

FCC PartClause	IC Part Clause	Test Parameter	Verdict	Remark
15.247(a)(2)	RSS-247, 5.2(a) RSS-Gen6.7	Emission Bandwidth	PASS	
15.247(b)(3)	RSS-247, 5.4(d) RSS-Gen6.12	Maximum Peak Conducted Output Power	PASS	
15.247(e)	RSS-247, 5.2(b) RSS-Gen6.12	Maximum Power Spectral Density Level	PASS	
15.247(d)	RSS-247, 5.5	Unwanted Emission Into Non-Restricted Frequency Bands	PASS	
15.247(d)	RSS-247, 5.5	Unwanted Emission Into Restricted Frequency Bands (conducted)	PASS	
15.247(d) 15.209 15.205	RSS-Gen 8.9 RSS-Gen 8.10 RSS-Gen 6.13 RSS-247, 3.3 RSS-247, 5.5	Radiated Spurious Emission	PASS	
15.207	RSS-Gen 8.8	Conducted EmissionTest	PASS	
15.203 15.247(b)	RSS-Gen 6.8 RSS-247, 5.4	Antenna Application	PASS	
NOTE1:N/A (Not Applicable) NOTE2:According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.				

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for **FCC ID: SMC-C62A** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:

FCC 47 CFR Part 2, Subpart J

FCC 47 CFR Part 15, Subpart C

IC RSS-GEN, Issue 5(04-2018)+A1(03-2019)+A2(02-2021)

IC RSS-247 Issue 3(08-2017)

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

4.2 MEASUREMENT EQUIPMENT USED

Conducted Emission Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	Rohde & Schwarz	ESCI	101384	2024/5/11	1Year
AMN	Rohde & Schwarz	ENV216	101161	2024/5/10	1Year

For Spurious Emissions Test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	Rohde & Schwarz	ESU 26	100154	2024/5/10	1Year
Pre-Amplifie	Lunar EM	LNA30M3G-25	J10100000070	2024/5/10	1Year
Bilog Antenna	Schwarzbeck	VULB9163	661	2023/6/2	2 Year
Horn antenna	Schwarzbeck	BBHA9120D	9120D-1177	2023/5/12	2 Year
Pre-Amplifie	SKET	LNPA_0118G-45	SK2019051801	2024/5/10	1Year
Loop Antenna	Schwarzbeck	FMZB1519	1519-012	2023/5/12	2 Year
Spectrum Analyzer	Rohde & Schwarz	FSV40	100967	2024/5/10	1Year
Horn antenna	Schwarzbeck	BBHA9170	9170-399	2023/5/12	2 Year
Coaxial Cable	TIMES	NmNm-7-C15702	N/A	2024/5/23	1Year
Coaxial Cable	TIMES	HF290-NMSM-6.5M	N/A	2024/5/23	1Year
Coaxial Cable	TIMES	LMR-240 N-N	N/A	2024/5/23	1Year

For other test items:

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Signal Analyzer	Agilent	N9010A	MY53470879	2024/5/10	1Year
Vector Signal Generater	Agilent	N5182B	MY53050878	2024/5/10	1Year
Analog Signal Generator	Agilent	N5171B	MY53050553	2024/5/10	1Year
RF Control Unit(Power Meter)	Tonscend	JS0806-2	\	2024/5/10	1Year
Temperature&Humidity Chamber	ESPEC	EL-02KA	12107166	2024/5/10	1Year

4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; 802.11n (HT40): MCS0;) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for 802.11 b/g/n(HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Frequency and Channel list for 802.11n(HT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	6	2437	9	2452

Test Frequency and Channel for 802.11 b/g/n(HT20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462

Test Frequency and channel for 802.11n(HT40):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	6	2437	9	2452

Multi-antenna correlation:

☒	Transmit Signals are Correlated
	Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N_{ANT}]$ dBi
☐	All Transmit Signals are Completely Uncorrelated
	Directional gain = $10 \log[(10^{G1/10} + 10^{G2/10} + \dots + 10^{GN/10}) / N_{ANT}]$ dBi
Directional gain = $10 \log [(10^{1.7/20} + 10^{1.8/20})^2 / 2]$ dBi=4.76dBi	

5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at:

EMTEK (Shenzhen) Co., Ltd.

Building 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with preselectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab.

: **Accredited by CNAS**

The Certificate Registration Number is L2291

The Laboratory has been assessed and proved to be in compliance with
CNAS-CL01 (identical to ISO/IEC 17025:2017)

Accredited by FCC

Designation Number: CN1204

Test Firm Registration Number: 882943

Accredited by A2LA

The Certificate Number is 4321.01

Accredited by Industry Canada

The Conformity Assessment Body Identifier is CN0008

Name of Firm : EMTEK (SHENZHEN) CO., LTD.

Site Location : Building 69, Majialong Industry Zone, Nanshan District, Shenzhen,
Guangdong, China

6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:


Test Parameter	Measurement Uncertainty
Frequency error	$\pm 20\text{Hz}$
Occupied Bandwidth	$\pm 0.5\text{KHz}$
Transmitter output power	$\pm 0.6\text{dB}$
Conducted spurious emissions	$\pm 3.2\text{dB}$
Radiated spurious emissions	$\pm 4.5\text{dB}$
Temperature	$\pm 1.2^\circ\text{C}$
Humidity	$\pm 3\%$
DC voltages	$\pm 0.25\text{V}$
Time	$\pm 1\%$

Measurement Uncertainty for a level of Confidence of 95%

7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP 1

The WLAN component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.

Above 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Above 1GHz:

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Measurements shall be taken, using the following steps, at a test site that has been validated using the procedures of ANSI C63.4 or the latest CISPR 16-1-4 for measurements above 1 GHz, so as to simulate a near free-space environment (see RSS-Gen for applicable versions of ANSI and CISPR standards).

(1) Line the ground plane with absorbers between the transmitter and the receive antenna to minimize reflections. The absorbers used should have a minimum-rated attenuation of 20 dB through the measurement frequency range of interest. The absorbers shall be positioned to replicate the layout used when compliance with the applicable acceptability criterion was achieved, as set forth in the aforementioned standards on site validation.

(2) Set the height of the receive antenna to 1.5 m. The receive antenna must be one that was designed and fabricated to operate over the entire frequency range of interest, for example, an appropriate standard gain horn.

(3) The distance between the receive antenna and the radiating source shall be sufficient in order to ensure far-field conditions.

(4) Mount the transmitter at a height of 1.5 m.

(5) Configure the device under test (DUT) to produce the maximum power spectral density as measured while assessing compliance with Section 6.2.2 (i.e. channel frequency, modulation type and data rate). If the DUT is equipped with a detachable antenna and the antenna is intended for remote installation (i.e.

tower-mounted), the DUT may be substituted with a suitable signal generator. The level and frequency settings on the generator shall be set so as to reproduce the maximum power spectral density, measured within a 1 MHz bandwidth, obtained while assessing compliance to Section 6.2.2.

(6) Position the transmitter or the radiating antenna so that elevation pattern measurements can be taken.

(7) Find the 0° reference point in the horizontal plane.

(8) Care should be taken when positioning the receive antenna to avoid cross-polarization. Antennas of known mounting polarization should be assessed with the receive antenna oriented in the same polarity. If the polarization of the transmit antenna is unknown or the transmit antenna can be mounted in either polarization, e.i.r.p. measurements should be performed to find which mounting polarity provides the highest e.i.r.p. value. Testing shall be carried out with the receive antenna and the DUT mounted in each polarity.

(9) The emission shall be centred on the display of the spectrum analyzer with the following settings:

i. If the power spectral density of the DUT was assessed with a peak detector and the antenna cannot be detached from the DUT, the spectrum analyzer shall be set to a peak detector with a resolution bandwidth and video bandwidth of 1 MHz.

ii. If the power spectral density of the DUT was assessed using a sample detector with power averaging and the antenna cannot be detached from the DUT, the spectrum analyzer shall be set to a sample detector, configured to produce 100 power averages and set with a resolution bandwidth, as well as a video bandwidth of 1 MHz.

iii. If the antenna can be detached from the DUT, a continuous wave (CW) signal equal to that of the power spectral density measurement may be used, the spectrum analyzer shall be set to peak detector with a resolution bandwidth and video bandwidth of 1 MHz.

(10) Rotate the turntable 360° recording the field strength at each step. Throughout the main beam of the antenna, the step size shall be kept to a maximum of 1°.

Once outside the main beam of the antenna, the maximum step size shall be as follows, when compared to the requirements of Section 6.2.2:

i. Between 0° and 8°, maximum step size of 2°;

ii. Between 8° and 40°, maximum step size of 4°;

iii. Between 40° and 45°, maximum step size of 1°;

iv. Between 45° and 90°, maximum step size of 5°.

Once the mask reaches 90°, the mask will be inverted and the step size will follow in the same manner as above.

For the purpose of this procedure, the main beam of the antenna is defined as the 3 dB beamwidth.

(11) Convert the measured field strength values in terms of e.i.r.p. density (dBW/1 MHz) using the following equation:

$$\text{e.i.r.p. density (dBW/MHz)} = 10 \log((E \cdot r)^2 / 30)$$

E = field strength in V/m

r = measurement distance in metres

(12) Plot the results against the emission mask with reference to the horizontal plane.


(13) Using the plot, the 0° can be rotated to determine the worst-case installation tilt angle.

(14) Testing shall be performed using the highest gain antenna for every antenna type, if applicable.


(15) Antenna type(s), antenna model number(s), and worst-case tilt angle(s) necessary to remain compliant with the elevation mask requirement set forth in Section 6.2.2(3) of RSS-247 shall be clearly indicated in the user manual.

The following figure is an example of a polar elevation mask measured using the Method 1 reference to dBμV/m at 3 m.


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




7.3 CONDUCTED EMISSION TEST SETUP


The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.8 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



7.5 SUPPORT EQUIPMENT

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

8 TEST REQUIREMENTS

8.1 DTS 6DB BANDWIDTH

8.1.1 Applicable Standard

According to FCC Part15.247 (a)(2) and KDB 558074 D01 15.247 Meas Guidance v05r02
According to RSS-247, 5.2(a)

8.1.2 Conformance Limit

The minimum -6 dB bandwidth shall be at least 500 kHz.

8.1.3 Test Configuration

Test according to clause 6.1 radio frequency test setup

8.1.4 Test Procedure

The EUT was operating in WIFI mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 100 kHz.

Set the video bandwidth (VBW) =300kHz.

Set Span=2 times OBW

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


Measure and record the results in the test report.

8.1.5 Test Results


Temperature:	25°C
Relative Humidity:	45%
ATM Pressure:	1011 mbar

Note: N/A


TestMode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	8.560	2407.480	2416.040	0.5	PASS
11B	Ant2	2412	9.000	2407.520	2416.520	0.5	PASS
11B	Ant1	2437	9.000	2432.480	2441.480	0.5	PASS
11B	Ant2	2437	9.520	2432.480	2442.000	0.5	PASS
11B	Ant1	2462	8.080	2457.960	2466.040	0.5	PASS
11B	Ant2	2462	8.560	2457.480	2466.040	0.5	PASS
11G	Ant1	2412	15.080	2404.440	2419.520	0.5	PASS
11G	Ant2	2412	15.080	2404.440	2419.520	0.5	PASS
11G	Ant1	2437	13.640	2430.480	2444.120	0.5	PASS
11G	Ant2	2437	15.400	2429.120	2444.520	0.5	PASS
11G	Ant1	2462	14.720	2454.840	2469.560	0.5	PASS
11G	Ant2	2462	15.040	2454.480	2469.520	0.5	PASS
11N20MIMO	Ant1	2412	15.320	2404.440	2419.760	0.5	PASS
11N20MIMO	Ant2	2412	16.520	2403.600	2420.120	0.5	PASS
11N20MIMO	Ant1	2437	15.360	2429.440	2444.800	0.5	PASS
11N20MIMO	Ant2	2437	15.040	2429.480	2444.520	0.5	PASS
11N20MIMO	Ant1	2462	15.120	2454.440	2469.560	0.5	PASS
11N20MIMO	Ant2	2462	15.680	2453.840	2469.520	0.5	PASS
11N40MIMO	Ant1	2422	34.960	2404.480	2439.440	0.5	PASS
11N40MIMO	Ant2	2422	35.120	2404.400	2439.520	0.5	PASS
11N40MIMO	Ant1	2437	32.640	2420.680	2453.320	0.5	PASS
11N40MIMO	Ant2	2437	35.040	2419.480	2454.520	0.5	PASS
11N40MIMO	Ant1	2452	35.040	2434.480	2469.520	0.5	PASS
11N40MIMO	Ant2	2452	35.040	2434.480	2469.520	0.5	PASS




11B-Ant1-2412-PASS




11B-Ant2-2412-PASS




11B-Ant1-2437-PASS




11B-Ant2-2437-PASS




11B-Ant1-2462-PASS




11B-Ant2-2462-PASS




11G-Ant1-2412-PASS




11G-Ant2-2412-PASS




11G-Ant1-2437-PASS




11G-Ant2-2437-PASS




11G-Ant1-2462-PASS




11G-Ant2-2462-PASS




11N20MIMO-Ant1-2412-PASS




11N20MIMO-Ant2-2412-PASS




11N20MIMO-Ant1-2437-PASS




11N20MIMO-Ant2-2437-PASS




11N20MIMO-Ant1-2462-PASS




11N20MIMO-Ant2-2462-PASS




11N40MIMO-Ant1-2422-PASS




11N40MIMO-Ant2-2422-PASS




11N40MIMO-Ant1-2437-PASS



11N40MIMO-Ant2-2437-PASS



11N40MIMO-Ant1-2452-PASS



11N40MIMO-Ant2-2452-PASS

8.2 DTS 99%BANDWIDTH

8.2.1 Applicable Standard

According to RSS-Gen6.7 and KDB 558074 D01 DTS Meas Guidance v05r02

8.2.2 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.2.3 Test Procedure

The EUT was operating in Bluetooth mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 1%-5% OBW.

Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.

Set Span=approximately 2 to 3 times the 20 dB bandwidth.

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

Allow the trace to stabilize.

Use the 99 % power bandwidth function of the instrument

Measure the maximum width of the emission.

If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.


Measure and record the results in the test report.

8.2.4 Test Results


Temperature:	25°C
Relative Humidity:	45%
ATM Pressure:	1011 mbar

Note: N/A


TestMode	Antenna	Channel Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	13.421	2405.3170	2418.7380	---	---
11B	Ant2	2412	13.460	2405.2929	2418.7529	---	---
11B	Ant1	2437	13.417	2430.3138	2443.7308	---	---
11B	Ant2	2437	13.419	2430.3054	2443.7244	---	---
11B	Ant1	2462	13.396	2455.3071	2468.7031	---	---
11B	Ant2	2462	13.419	2455.2953	2468.7143	---	---
11G	Ant1	2412	16.768	2403.6243	2420.3923	---	---
11G	Ant2	2412	16.815	2403.5646	2420.3796	---	---
11G	Ant1	2437	16.818	2428.5535	2445.3715	---	---
11G	Ant2	2437	16.782	2428.5674	2445.3494	---	---
11G	Ant1	2462	16.771	2453.5428	2470.3138	---	---
11G	Ant2	2462	16.746	2453.6200	2470.3660	---	---
11N20MIMO	Ant1	2412	17.833	2403.1000	2420.9330	---	---
11N20MIMO	Ant2	2412	17.646	2403.1727	2420.8187	---	---
11N20MIMO	Ant1	2437	17.803	2428.0797	2445.8827	---	---
11N20MIMO	Ant2	2437	17.611	2428.1859	2445.7969	---	---
11N20MIMO	Ant1	2462	17.763	2453.1368	2470.8998	---	---
11N20MIMO	Ant2	2462	17.648	2453.1678	2470.8158	---	---
11N40MIMO	Ant1	2422	36.067	2403.9630	2440.0300	---	---
11N40MIMO	Ant2	2422	36.228	2403.9309	2440.1589	---	---
11N40MIMO	Ant1	2437	35.940	2419.0358	2454.9758	---	---
11N40MIMO	Ant2	2437	36.181	2418.9619	2455.1429	---	---
11N40MIMO	Ant1	2452	36.067	2433.9897	2470.0567	---	---
11N40MIMO	Ant2	2452	36.217	2433.9412	2470.1582	---	---




11B-Ant1-2412




11B-Ant2-2412




11B-Ant1-2437




11B-Ant2-2437




11B-Ant1-2462



11B-Ant2-2462




11G-Ant1-2412




11G-Ant2-2412







11G-Ant1-2462




11G-Ant2-2462




11N20MIMO-Ant1-2412




11N20MIMO-Ant2-2412




11N20MIMO-Ant1-2437




11N20MIMO-Ant2-2437




11N20MIMO-Ant1-2462




11N20MIMO-Ant2-2462




11N40MIMO-Ant1-2422




11N40MIMO-Ant2-2422





11N40MIMO-Ant1-2452



11N40MIMO-Ant2-2452

8.3 MAXIMUM PEAK CONDUCTED OUTPUT POWER

8.3.1 Applicable Standard

According to FCC Part15.247 (b)(3) and KDB 558074 D01 15.247 Meas Guidance v05r02
According to RSS-247, 5.4(d) and RSS-Gen6.12

8.3.2 Conformance Limit

The maximum conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm).

8.3.3 Test Configuration

Test according to clause 6.1 radio frequency test setup

8.3.4 Test Procedure

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This gives bin-to-bin spacing $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run” .
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

■ According to FCC Part 15.247(b)(4):

Conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note: If antenna Gain exceeds 6 dBi, then Output power Limit=30-(Gain- 6)


8.3.5 Test Results

Temperature:	25 °C
Relative Humidity:	45%
ATM Pressure:	1011 mbar


Note: N/A

Note: EIRP = conducted power + directional gain


Test Mode	Antenna	Frequency [MHz]	Duty Cycle [%]	DC Factor [dBm]	Result [dBm]	Limit [dBm]	Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Verdict
11B	Ant1	2412	99.41	0.03	13.13	≤30.00	1.70	14.83	≤36.00	PASS
11B	Ant2	2412	99.41	0.03	12.77	≤30.00	1.80	14.57	≤36.00	PASS
11B	Ant1	2437	99.53	0.02	13.47	≤30.00	1.70	15.17	≤36.00	PASS
11B	Ant2	2437	99.41	0.03	13.28	≤30.00	1.80	15.08	≤36.00	PASS
11B	Ant1	2462	99.41	0.03	13.65	≤30.00	1.70	15.35	≤36.00	PASS
11B	Ant2	2462	99.41	0.03	13.40	≤30.00	1.80	15.20	≤36.00	PASS
11G	Ant1	2412	95.86	0.18	12.07	≤30.00	1.70	13.77	≤36.00	PASS
11G	Ant2	2412	95.86	0.18	11.87	≤30.00	1.80	13.67	≤36.00	PASS
11G	Ant1	2437	95.86	0.18	12.06	≤30.00	1.70	13.76	≤36.00	PASS
11G	Ant2	2437	95.86	0.18	11.85	≤30.00	1.80	13.65	≤36.00	PASS
11G	Ant1	2462	95.86	0.18	12.35	≤30.00	1.70	14.05	≤36.00	PASS
11G	Ant2	2462	95.86	0.18	12.26	≤30.00	1.80	14.06	≤36.00	PASS
11N20MIMO	Ant1	2412	95.59	0.20	11.58	≤30.00	1.70	13.28	≤36.00	PASS
11N20MIMO	Ant2	2412	95.59	0.20	11.95	≤30.00	1.80	13.75	≤36.00	PASS
11N20MIMO	total	2412	---	---	14.78	≤30.00	1.80	16.58	≤36.00	PASS
11N20MIMO	Ant1	2437	95.59	0.20	11.80	≤30.00	1.70	13.50	≤36.00	PASS
11N20MIMO	Ant2	2437	95.59	0.20	11.67	≤30.00	1.80	13.47	≤36.00	PASS
11N20MIMO	total	2437	---	---	14.75	≤30.00	1.80	16.55	≤36.00	PASS
11N20MIMO	Ant1	2462	95.59	0.20	12.11	≤30.00	1.70	13.81	≤36.00	PASS
11N20MIMO	Ant2	2462	95.59	0.20	12.28	≤30.00	1.80	14.08	≤36.00	PASS
11N20MIMO	total	2462	---	---	15.21	≤30.00	1.80	17.01	≤36.00	PASS
11N40MIMO	Ant1	2422	91.43	0.39	12.00	≤30.00	1.70	13.70	≤36.00	PASS
11N40MIMO	Ant2	2422	91.43	0.39	11.83	≤30.00	1.80	13.63	≤36.00	PASS
11N40MIMO	total	2422	---	---	14.93	≤30.00	1.80	16.73	≤36.00	PASS
11N40MIMO	Ant1	2437	91.43	0.39	12.05	≤30.00	1.70	13.75	≤36.00	PASS
11N40MIMO	Ant2	2437	91.43	0.39	11.91	≤30.00	1.80	13.71	≤36.00	PASS
11N40MIMO	total	2437	---	---	14.99	≤30.00	1.80	16.79	≤36.00	PASS
11N40MIMO	Ant1	2452	91.43	0.39	12.24	≤30.00	1.70	13.94	≤36.00	PASS
11N40MIMO	Ant2	2452	91.43	0.39	12.15	≤30.00	1.80	13.95	≤36.00	PASS
11N40MIMO	total	2452	---	---	15.21	≤30.00	1.80	17.01	≤36.00	PASS




11B-Ant1-2412-PASS




11B-Ant2-2412-PASS




11B-Ant1-2437-PASS




11B-Ant2-2437-PASS



11B-Ant1-2462-PASS



11B-Ant2-2462-PASS




11G-Ant1-2412-PASS




11G-Ant2-2412-PASS



11G-Ant1-2437-PASS




11G-Ant2-2437-PASS




11G-Ant1-2462-PASS




11G-Ant2-2462-PASS



11N20MIMO-Ant1-2412-PASS




11N20MIMO-Ant2-2412-PASS



11N20MIMO-Ant1-2437-PASS




11N20MIMO-Ant2-2437-PASS







11N40MIMO-Ant1-2422-PASS




11N40MIMO-Ant2-2422-PASS




11N40MIMO-Ant1-2437-PASS



11N40MIMO-Ant2-2437-PASS



11N40MIMO-Ant1-2452-PASS



11N40MIMO-Ant2-2452-PASS

8.4 MAXIMUM POWER SPECTRAL DENSITY

8.4.1 Applicable Standard

According to FCC Part15.247(e) and KDB 558074 D01 15.247 Meas Guidance v05r02
According to RSS-247, 5.2(b) and RSS-Gen6.12

8.4.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

8.4.3 Test Configuration

Test according to clause 6.1 radio frequency test setup

8.4.4 Test Procedure

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance

The transmitter output (antenna port) was connected to the spectrum analyzer

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz

Set the VBW to: 10 kHz.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

8.4.5 Test Results

Temperature:	25 °C
Relative Humidity:	45%
ATM Pressure:	1011 mbar

Note: N/A

TestMode	Antenna	Frequency[MHz]	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-17.12	≤8.00	PASS
11B	Ant2	2412	-15.56	≤8.00	PASS
11B	Ant1	2437	-15.07	≤8.00	PASS
11B	Ant2	2437	-16.49	≤8.00	PASS
11B	Ant1	2462	-14.91	≤8.00	PASS
11B	Ant2	2462	-14.13	≤8.00	PASS
11G	Ant1	2412	-19.57	≤8.00	PASS
11G	Ant2	2412	-19.76	≤8.00	PASS
11G	Ant1	2437	-19.72	≤8.00	PASS
11G	Ant2	2437	-19.81	≤8.00	PASS
11G	Ant1	2462	-19.02	≤8.00	PASS
11G	Ant2	2462	-19.53	≤8.00	PASS
11N20MIMO	Ant1	2412	-19.98	≤8.00	PASS
11N20MIMO	Ant2	2412	-20.13	≤8.00	PASS
11N20MIMO	total	2412	-17.04	≤8.00	PASS
11N20MIMO	Ant1	2437	-20.40	≤8.00	PASS
11N20MIMO	Ant2	2437	-20.08	≤8.00	PASS
11N20MIMO	total	2437	-17.23	≤8.00	PASS
11N20MIMO	Ant1	2462	-19.83	≤8.00	PASS
11N20MIMO	Ant2	2462	-19.52	≤8.00	PASS
11N20MIMO	total	2462	-16.66	≤8.00	PASS
11N40MIMO	Ant1	2422	-22.13	≤8.00	PASS
11N40MIMO	Ant2	2422	-22.12	≤8.00	PASS
11N40MIMO	total	2422	-19.11	≤8.00	PASS
11N40MIMO	Ant1	2437	-21.49	≤8.00	PASS
11N40MIMO	Ant2	2437	-21.87	≤8.00	PASS
11N40MIMO	total	2437	-18.67	≤8.00	PASS
11N40MIMO	Ant1	2452	-21.78	≤8.00	PASS
11N40MIMO	Ant2	2452	-21.62	≤8.00	PASS
11N40MIMO	total	2452	-18.69	≤8.00	PASS



11B-Ant1-2412-PASS



11B-Ant2-2412-PASS



11B-Ant1-2437-PASS




11B-Ant2-2437-PASS




11B-Ant1-2462-PASS




11B-Ant2-2462-PASS




11G-Ant1-2412-PASS



11G-Ant2-2412-PASS



11G-Ant1-2437-PASS



11G-Ant2-2437-PASS