

# FCC Test Report

**Report No.** : 1812C60437412501

---

**Applicant** : SHENZHEN HOLATEK CO.,LTD.

---

**Address** : #12,Building 1,Chongwen Park, Nanshan  
Zhiyuan, 3370 Liuxian Ave, Nanshan District,  
Shenzhen, China

---

**Product Name** : Smart Projector

---

**Report Date** : 2026-09-30

---

**Shenzhen Anbotek Compliance Laboratory Limited**



# Contents

|                                                      |    |
|------------------------------------------------------|----|
| 1. General Information .....                         | 6  |
| 1.1. Client Information .....                        | 6  |
| 1.2. Description of Device (EUT) .....               | 6  |
| 1.3. Auxiliary Equipment Used During Test .....      | 7  |
| 1.4. Operation channel list .....                    | 8  |
| 1.5. Description of Test Mode(s) .....               | 9  |
| 1.6. Measurement Uncertainty .....                   | 9  |
| 1.7. Additional Instructions .....                   | 10 |
| 1.8. Test Summary .....                              | 10 |
| 1.9. Description of Test Facility .....              | 11 |
| 1.10. Disclaimer .....                               | 11 |
| 1.11. Test Equipment List .....                      | 12 |
| 2. Antenna requirement .....                         | 14 |
| 2.1. Conclusion .....                                | 14 |
| 3. Conducted Emission at AC power line .....         | 15 |
| 3.1. EUT Operation .....                             | 15 |
| 3.2. Test Setup .....                                | 15 |
| 3.3. Test Data .....                                 | 16 |
| 4. 20dB Bandwidth .....                              | 20 |
| 4.1. EUT Operation .....                             | 21 |
| 4.2. Test Setup .....                                | 21 |
| 4.3. Test Data .....                                 | 21 |
| 5. Maximum Conducted Output Power .....              | 22 |
| 5.1. EUT Operation .....                             | 22 |
| 5.2. Test Setup .....                                | 22 |
| 5.3. Test Data .....                                 | 22 |
| 6. Channel Separation .....                          | 23 |
| 6.1. EUT Operation .....                             | 23 |
| 6.2. Test Setup .....                                | 24 |
| 6.3. Test Data .....                                 | 24 |
| 7. Number of Hopping Frequencies .....               | 25 |
| 7.1. EUT Operation .....                             | 25 |
| 7.2. Test Setup .....                                | 26 |
| 7.3. Test Data .....                                 | 26 |
| 8. Dwell Time .....                                  | 27 |
| 8.1. EUT Operation .....                             | 28 |
| 8.2. Test Setup .....                                | 28 |
| 8.3. Test Data .....                                 | 28 |
| 9. Emissions in non-restricted frequency bands ..... | 29 |
| 9.1. EUT Operation .....                             | 29 |
| 9.2. Test Setup .....                                | 29 |

9.3. Test Data .....29

10. Band edge emissions (Radiated) .....30

10.1. EUT Operation .....30

10.2. Test Setup .....31

10.3. Test Data .....32

11. Emissions in restricted frequency bands (below 1GHz) .....33

11.1. EUT Operation .....33

11.2. Test Setup .....34

11.3. Test Data .....35

12. Emissions in restricted frequency bands (above 1GHz).....39

12.1. EUT Operation .....39

12.2. Test Setup .....40

12.3. Test Data .....41

APPENDIX I -- TEST SETUP PHOTOGRAPH .....44

APPENDIX II -- EXTERNAL PHOTOGRAPH .....44

APPENDIX III -- INTERNAL PHOTOGRAPH.....44

## TEST REPORT

Applicant : SHENZHEN HOLATEK CO.,LTD.  
Manufacturer : SHENZHEN HOLATEK CO.,LTD.  
Product Name : Smart Projector  
Model No. : J9B-9K2, J9F-9K2, J9B-9K0, J9B-9K1, J9B-9K3, J9F-9K0, J9F-9K1, J9F-9K3  
Trade Mark : JMGO  
Rating(s) : J9B series Input: 24V=12.5A  
J9F series Input: 24V=10A  
**47 CFR Part 15.247**  
Test Standard(s) : **KDB 558074 D01 15.247 Meas Guidance v05r02\***  
**ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024\***

**Note: \* denotes that this test standard is not included in CNAS accredited scope.**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with above listed standard(s) requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt: 2026-07-30

Date of Test: 2026-07-30 to 2026-09-29

Prepared By:

*Lene Chen*

(Lene Chen)

Approved & Authorized Signer:

*Jules Guo*

(Jules Guo)

Revision History

| Report Version | Description     | Issued Date |
|----------------|-----------------|-------------|
| R00            | Original Issue. | 2026-09-30  |
|                |                 |             |
|                |                 |             |

## 1. General Information

### 1.1. Client Information

|              |   |                                                                                                                                     |
|--------------|---|-------------------------------------------------------------------------------------------------------------------------------------|
| Applicant    | : | SHENZHEN HOLATEK CO.,LTD.                                                                                                           |
| Address      | : | #12,Building 1,Chongwen Park, Nanshan Zhiyuan, 3370 Liuxian Ave,<br>Nanshan District, Shenzhen, China                               |
| Manufacturer | : | SHENZHEN HOLATEK CO.,LTD.                                                                                                           |
| Address      | : | #12,Building 1,Chongwen Park, Nanshan Zhiyuan, 3370 Liuxian Ave,<br>Nanshan District, Shenzhen, China                               |
| Factory      | : | Anhui MuKe High-tech Co., Ltd                                                                                                       |
| Address      | : | A15 Plant at the intersection of Hongxing Road and Lixin Road, Zhoupeng<br>Street, Yingquan District, Fuyang, Anhui Province, China |

### 1.2. Description of Device (EUT)

|                                                                                                                                                                                    |   |                                                                                                                                                                                                                                                                                                                                                                                                           |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Name                                                                                                                                                                       | : | Smart Projector                                                                                                                                                                                                                                                                                                                                                                                           |
| Model No.                                                                                                                                                                          | : | J9B-9K2, J9F-9K2, J9B-9K0, J9B-9K1, J9B-9K3, J9F-9K0, J9F-9K1, J9F-9K3<br>(Note: All samples are the same except the model name, input ratings, adapter supplied with the product, laser source and J9F series reduce circuitry associated with the LED beads. So we prepare all test items for model "J9B-9K2", conducted emission and radiation spurious emission (below 1G) test for model "J9F-9K2".) |
| Trade Mark                                                                                                                                                                         | : | JMGO                                                                                                                                                                                                                                                                                                                                                                                                      |
| Test Power Supply                                                                                                                                                                  | : | AC 120V/60Hz for Adapter                                                                                                                                                                                                                                                                                                                                                                                  |
| Test Sample No.                                                                                                                                                                    | : | J9B-9K2: 1-3-1(Normal Sample), 1-3-2(Engineering Sample)<br>J9F-9K2: 1-3-3(Normal Sample)                                                                                                                                                                                                                                                                                                                 |
| Adapter1<br>(for J9B series)                                                                                                                                                       | : | Manufacturer: Shenzhen JingQuanHua & Everrise Intelligent Electric Co.,Ltd.<br>Model: NSA300EF-24012500<br>Input: 100-240V~ 50/60Hz 3.5A<br>Output: 24.0V=12.5A 300.0W                                                                                                                                                                                                                                    |
| Adapter2<br>(for J9F series)                                                                                                                                                       | : | Manufacturer: Shenzhen JingQuanHua & Everrise Intelligent Electric Co.,Ltd.<br>Model: NSA240EC-2401001<br>Input: 100-240V~ 50/60Hz, 2.5A<br>Output: 24.0V=10.0A                                                                                                                                                                                                                                           |
| <b>RF Specification</b>                                                                                                                                                            |   |                                                                                                                                                                                                                                                                                                                                                                                                           |
| Operation Frequency                                                                                                                                                                | : | 2402MHz to 2480MHz                                                                                                                                                                                                                                                                                                                                                                                        |
| Number of Channel                                                                                                                                                                  | : | 79                                                                                                                                                                                                                                                                                                                                                                                                        |
| Modulation Type                                                                                                                                                                    | : | GFSK, $\pi/4$ -DQPSK, 8DPSK                                                                                                                                                                                                                                                                                                                                                                               |
| Antenna Type                                                                                                                                                                       | : | FPC Antenna                                                                                                                                                                                                                                                                                                                                                                                               |
| Antenna Gain(Peak)                                                                                                                                                                 | : | 1.80dBi                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Remark:</b> (1) All of the RF specification are provided by customer.<br>(2) For a more detailed features description, please refer to the manufacturer's specifications or the |   |                                                                                                                                                                                                                                                                                                                                                                                                           |

#### Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

User's Manual.

1.3. Auxiliary Equipment Used During Test

| Title | Manufacturer | Model No. | Serial No. |
|-------|--------------|-----------|------------|
| /     | /            | /         | /          |

## 1.4. Operation channel list

Operation Band:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| 0       | 2402            | 20      | 2422            | 40      | 2442            | 60      | 2462            |
| 1       | 2403            | 21      | 2423            | 41      | 2443            | 61      | 2463            |
| 2       | 2404            | 22      | 2424            | 42      | 2444            | 62      | 2464            |
| 3       | 2405            | 23      | 2425            | 43      | 2445            | 63      | 2465            |
| 4       | 2406            | 24      | 2426            | 44      | 2446            | 64      | 2466            |
| 5       | 2407            | 25      | 2427            | 45      | 2447            | 65      | 2467            |
| 6       | 2408            | 26      | 2428            | 46      | 2448            | 66      | 2468            |
| 7       | 2409            | 27      | 2429            | 47      | 2449            | 67      | 2469            |
| 8       | 2410            | 28      | 2430            | 48      | 2450            | 68      | 2470            |
| 9       | 2411            | 29      | 2431            | 49      | 2451            | 69      | 2471            |
| 10      | 2412            | 30      | 2432            | 50      | 2452            | 70      | 2472            |
| 11      | 2413            | 31      | 2433            | 51      | 2453            | 71      | 2473            |
| 12      | 2414            | 32      | 2434            | 52      | 2454            | 72      | 2474            |
| 13      | 2415            | 33      | 2435            | 53      | 2455            | 73      | 2475            |
| 14      | 2416            | 34      | 2436            | 54      | 2456            | 74      | 2476            |
| 15      | 2417            | 35      | 2437            | 55      | 2457            | 75      | 2477            |
| 16      | 2418            | 36      | 2438            | 56      | 2458            | 76      | 2478            |
| 17      | 2419            | 37      | 2439            | 57      | 2459            | 77      | 2479            |
| 18      | 2420            | 38      | 2440            | 58      | 2460            | 78      | 2480            |
| 19      | 2421            | 39      | 2441            | 59      | 2461            | -       | -               |

### 1.5. Description of Test Mode(s)

| Test Mode(s) | Description(s)                                                                               |
|--------------|----------------------------------------------------------------------------------------------|
| TM1          | Keep the EUT in continuously transmitting mode (non-hopping) with GFSK modulation.           |
| TM2          | Keep the EUT in continuously transmitting mode (non-hopping) with $\pi/4$ -DQPSK modulation. |
| TM3          | Keep the EUT in continuously transmitting mode (non-hopping) with 8DPSK modulation.          |
| TM4          | Keep the EUT in continuously transmitting mode (hopping) with GFSK modulation,.              |
| TM5          | Keep the EUT in continuously transmitting mode (hopping) with $\pi/4$ -DQPSK modulation.     |
| TM6          | Keep the EUT in continuously transmitting mode (hopping) with 8DPSK modulation.              |

### 1.6. Measurement Uncertainty

| Parameter                                                                                                                                                                                                                    | Uncertainty                                               |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------|
| Conducted emissions (AMN 150kHz~30MHz)                                                                                                                                                                                       | 2.8dB                                                     |
| Occupied Bandwidth                                                                                                                                                                                                           | 552Hz                                                     |
| Conducted Output Power                                                                                                                                                                                                       | 0.84dB                                                    |
| Dwell Time                                                                                                                                                                                                                   | 2%                                                        |
| Conducted Spurious Emission                                                                                                                                                                                                  | 1.24dB                                                    |
| Radiated spurious emissions (above 1GHz)                                                                                                                                                                                     | 1G-6GHz: 4.64dB;<br>6G-18GHz: 4.82dB<br>18G-40GHz: 5.62dB |
| Radiated emissions (Below 30MHz)                                                                                                                                                                                             | 3.14dB                                                    |
| Radiated spurious emissions (30MHz~1GHz)                                                                                                                                                                                     | Horizontal: 4.44dB; Vertical: 4.82dB                      |
| The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2. |                                                           |

## 1.7. Additional Instructions

Power level setup in software: SecureCRSecureFXPortable64

Operation Band:

| Mode      | Channel(MHz) | Power level | Transmitting type |
|-----------|--------------|-------------|-------------------|
| BDR_1Mbps | 2402         | default     | data pack TX      |
| BDR_1Mbps | 2441         | default     | data pack TX      |
| BDR_1Mbps | 2480         | default     | data pack TX      |
| EDR_2Mbps | 2402         | default     | data pack TX      |
| EDR_2Mbps | 2441         | default     | data pack TX      |
| EDR_2Mbps | 2480         | default     | data pack TX      |
| EDR_3Mbps | 2402         | default     | data pack TX      |
| EDR_3Mbps | 2441         | default     | data pack TX      |
| EDR_3Mbps | 2480         | default     | data pack TX      |

## 1.8. Test Summary

| Test Items                                           | Test Mode(s)    | Status |
|------------------------------------------------------|-----------------|--------|
| Antenna requirement                                  | /               | P      |
| Conducted Emission at AC power line                  | Mode1,2,3       | P      |
| 20dB Bandwidth                                       | Mode1,2,3       | P      |
| Maximum Conducted Output Power                       | Mode1,2,3       | P      |
| Channel Separation                                   | Mode4,5,6       | P      |
| Number of Hopping Frequencies                        | Mode4,5,6       | P      |
| Dwell Time                                           | Mode4,5,6       | P      |
| Emissions in non-restricted frequency bands          | Mode1,2,3,4,5,6 | P      |
| Band edge emissions (Radiated)                       | Mode1,2,3       | P      |
| Emissions in restricted frequency bands (below 1GHz) | Mode1,2,3       | P      |
| Emissions in restricted frequency bands (above 1GHz) | Mode1,2,3       | P      |
| Note:<br>P: Pass<br>N: N/A, not applicable           |                 |        |

## 1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

### **FCC-Registration No.:279531**

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 279531.

### **Test Location**

Shenzhen Anbotek Compliance Laboratory Limited.  
Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.

## 1.10. Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The effect that the results relate only to the items tested.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. This report shall not be reproduced except in full without approval of the anbotek.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.
7. The data in this report will be synchronized with the corresponding national market supervision and management departments and cross-border e-commerce platforms as required by regulatory agencies.
8. Unless otherwise specified, use the binary decision rule of simple acceptance ( $w=0$ ) for conformity determination with reference to ILAC-G8:09/2019.

### 1.11. Test Equipment List

| Conducted Emission at AC power line |                                                       |                  |              |            |              |
|-------------------------------------|-------------------------------------------------------|------------------|--------------|------------|--------------|
| Item                                | Equipment                                             | Manufacturer     | Model No.    | Last Cal.  | Cal.Due Date |
| 1                                   | L.I.S.N. Artificial Mains Network                     | Rohde & Schwarz  | ENV216       | 2026-06-08 | 2027-06-07   |
| 2                                   | Software Name EZ-EMC                                  | Farad Technology | ANB-03A      | /          | /            |
| 3                                   | EMI Test Receiver(CE2#)                               | Rohde & Schwarz  | ESCI3        | 2025-12-29 | 2026-12-28   |
| 4                                   | Three Phase V-type Artificial Power Network LISN 200A | EMtrace          | PWL-50-3200A | 2025-12-29 | 2026-12-28   |
| 5                                   | 10dB Attenuator                                       | Emtrace          | 10dB100W     | 2025-12-29 | 2026-12-28   |
| 6                                   | Pulse limiter                                         | EMtrace          | PL00903-2#   | 2025-12-29 | 2026-12-28   |

| Channel Separation<br>Number of Hopping Frequencies<br>Dwell Time<br>Emissions in non-restricted frequency bands<br>20dB Bandwidth<br>Maximum Conducted Output Power |                                       |                 |            |            |              |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|-----------------|------------|------------|--------------|
| Item                                                                                                                                                                 | Equipment                             | Manufacturer    | Model No.  | Last Cal.  | Cal.Due Date |
| 1                                                                                                                                                                    | MXG RF Vector Signal Generator        | Agilent         | N5182A     | 2025-12-29 | 2026-12-28   |
| 2                                                                                                                                                                    | Constant Temperature Humidity Chamber | ZHONGJIAN       | ZJ-HWHS80B | 2026-06-08 | 2027-06-07   |
| 3                                                                                                                                                                    | Signal Generator                      | Agilent         | E4421B     | 2025-12-29 | 2026-12-28   |
| 4                                                                                                                                                                    | DC Power Supply                       | IVYTECH         | IV3605     | 2026-06-08 | 2027-06-07   |
| 5                                                                                                                                                                    | RF Control Unit                       | Tonscend        | JS0806-2   | 2026-06-08 | 2027-06-07   |
| 6                                                                                                                                                                    | Wideband Radio Communication Tester   | Rohde & Schwarz | CMW500     | 2025-12-29 | 2026-12-28   |
| 7                                                                                                                                                                    | MXA Spectrum Analysis                 | KEYSIGHT        | N9020A     | 2025-12-29 | 2026-12-28   |
| 8                                                                                                                                                                    | RF Test software                      | Toscend         | JS1120-3   | /          | /            |

| Band edge emissions (Radiated)            |                            |                  |                  |            |              |
|-------------------------------------------|----------------------------|------------------|------------------|------------|--------------|
| Emissions in frequency bands (above 1GHz) |                            |                  |                  |            |              |
| Item                                      | Equipment                  | Manufacturer     | Model No.        | Last Cal.  | Cal.Due Date |
| 1                                         | EMI Test Receiver(RE2/3#)  | Rohde & Schwarz  | ESR26            | 2025-12-30 | 2026-12-29   |
| 2                                         | EMI Preamplifier           | SKET Electronic  | LNPA-0118G-45    | 2025-12-30 | 2026-12-29   |
| 3                                         | Double Ridged Horn Antenna | SCHWARZBECK      | BBHA 9120D       | 2025-10-27 | 2028-10-26   |
| 4                                         | EMI Test Software EZ-EMC   | SHURPLE          | N/A              | /          | /            |
| 5                                         | Horn Antenna               | A-INFO           | LB-180400-KF     | 2024-01-22 | 2027-01-21   |
| 6                                         | Spectrum Analyzer          | Rohde & Schwarz  | FSV40-N          | 2025-12-29 | 2026-12-28   |
| 7                                         | Amplifier                  | Talent Microwave | TLLA18G40G-53-30 | 2026-01-05 | 2027-01-04   |

| Emissions in frequency bands (below 1GHz) |                                       |                 |                    |            |              |
|-------------------------------------------|---------------------------------------|-----------------|--------------------|------------|--------------|
| Item                                      | Equipment                             | Manufacturer    | Model No.          | Last Cal.  | Cal.Due Date |
| 1                                         | EMI Test Receiver(RE2/3#)             | Rohde & Schwarz | ESR26              | 2025-12-30 | 2026-12-29   |
| 2                                         | Pre-amplifier                         | SONOMA          | 310N               | 2025-12-30 | 2026-12-29   |
| 3                                         | Bilog Broadband Antenna               | Schwarzbeck     | VULB9163           | 2025-10-26 | 2028-10-25   |
| 4                                         | EMI Preamplifier                      | SKET Electronic | LNPA-0118G-45      | 2025-12-30 | 2026-12-29   |
| 5                                         | Double Ridged Horn Antenna            | SCHWARZBECK     | BBHA 9120D         | 2025-10-27 | 2028-10-26   |
| 6                                         | Loop Antenna (9K-30M)                 | Schwarzbeck     | FMZB1519B          | 2026-06-24 | 2029-06-23   |
| 7                                         | EMI Test Software EZ-EMC              | SHURPLE         | N/A                | /          | /            |
| 8                                         | MXG RF Vector Signal Generator        | Agilent         | N5182A             | 2025-12-29 | 2026-12-28   |
| 9                                         | DC Power Supply                       | LW              | TPR-6420D          | 2025-10-10 | 2026-10-09   |
| 10                                        | Constant Temperature Humidity Chamber | ZHONGJIAN       | ZJ-HWHS80B         | 2026-06-08 | 2027-06-07   |
| 11                                        | Wideband Radio Communication Tester   | Rohde & Schwarz | CMW 500            | 2025-12-29 | 2026-12-28   |
| 12                                        | High-Pass Filter                      | CDKMV           | ZHPF-BM1100-4730   | 2025-10-10 | 2026-10-09   |
| 13                                        | High-Pass Filter                      | CDKMV           | ZHPF-M3.5-18G-3834 | 2025-12-30 | 2026-12-29   |
| 14                                        | MXA Spectrum Analysis                 | KEYSIGHT        | N9020A             | 2026-06-08 | 2027-06-07   |

#### Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: [www.anbotek.com](http://www.anbotek.com) E-mail: [service@anbotek.com](mailto:service@anbotek.com)

## 2. Antenna requirement

|                   |                                                                                                                                                                                                                                                                                                                                                                                     |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. |
| Test Method:      | ---                                                                                                                                                                                                                                                                                                                                                                                 |

### 2.1. Conclusion

The antenna is a **FPC Antenna** which permanently attached, and the best case gain of the antenna is **1.80dBi**. It complies with the standard requirement.


3. Conducted Emission at AC power line

|                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                        |           |
|-------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|-----------|
| Test Requirement:                               | Refer to 47 CFR 15.207(a), Except as shown in paragraphs (b)and (c)of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μH/50 ohms line impedance stabilization network (LISN). |                        |           |
| Test Limit:                                     | Frequency of emission (MHz)                                                                                                                                                                                                                                                                                                                                                                                                                                              | Conducted limit (dBμV) |           |
|                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Quasi-peak             | Average   |
|                                                 | 0.15-0.5                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 66 to 56*              | 56 to 46* |
|                                                 | 0.5-5                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 56                     | 46        |
|                                                 | 5-30                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 60                     | 50        |
| *Decreases with the logarithm of the frequency. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                        |           |
| Test Method:                                    | ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.2                                                                                                                                                                                                                                                                                                                                                                                         |                        |           |
| Procedure:                                      | Refer to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices                                                                                                                                                                                                                                                                                   |                        |           |

3.1. EUT Operation

|                        |                                                                                                                                                                                                                                                                                                                                                    |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating Environment: |                                                                                                                                                                                                                                                                                                                                                    |
| Test mode:             | 1:TX-GFSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with GFSK modulation.<br>2:TX-π/4-DQPSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with π/4-DQPSK modulation.<br>3:TX-8DPSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with 8DPSK modulation. |


3.2. Test Setup



### 3.3. Test Data

Test Sample: **J9B-9K2**


|              |         |           |      |                       |         |
|--------------|---------|-----------|------|-----------------------|---------|
| Temperature: | 23.8 °C | Humidity: | 57 % | Atmospheric Pressure: | 101 kPa |
|--------------|---------|-----------|------|-----------------------|---------|



|              |         |           |      |                       |         |
|--------------|---------|-----------|------|-----------------------|---------|
| Temperature: | 23.8 °C | Humidity: | 57 % | Atmospheric Pressure: | 101 kPa |
|--------------|---------|-----------|------|-----------------------|---------|

TM1 / Line: Neutral / Band: 2400-2483.5 MHz / BW: 1 / CH: L

Test Power Supply: AC 120V/60Hz for Adapter



| No. | Freq. (MHz) | Reading (dBμV) | Factor (dB) | Result (dBμV) | Limit (dBμV) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|-------------|---------------|--------------|-----------------|----------|--------|
| 1   | 0.1500      | 31.12          | 19.78       | 50.90         | 65.99        | -15.09          | QP       |        |
| 2   | 0.1500      | 6.79           | 19.78       | 26.57         | 55.99        | -29.42          | AVG      |        |
| 3   | 0.1819      | 30.27          | 19.78       | 50.05         | 64.39        | -14.34          | QP       |        |
| 4   | 0.2340      | 29.08          | 19.79       | 48.87         | 62.30        | -13.43          | QP       |        |
| 5   | 0.2740      | 21.63          | 19.79       | 41.42         | 60.99        | -19.57          | QP       |        |
| 6   | 0.3260      | 11.15          | 19.79       | 30.94         | 49.55        | -18.61          | AVG      |        |
| 7   | 0.3820      | 19.19          | 19.80       | 38.99         | 58.23        | -19.24          | QP       |        |
| 8   | 0.7620      | 15.71          | 19.83       | 35.54         | 56.00        | -20.46          | QP       |        |
| 9   | 0.7620      | 0.27           | 19.83       | 20.10         | 46.00        | -25.90          | AVG      |        |
| 10  | 1.1940      | -1.43          | 19.84       | 18.41         | 46.00        | -27.59          | AVG      |        |
| 11  | 1.9260      | -2.61          | 19.83       | 17.22         | 46.00        | -28.78          | AVG      |        |
| 12  | 3.3740      | -3.66          | 19.82       | 16.16         | 46.00        | -29.84          | AVG      |        |

Note:


- Only record the worst data in the report.
- Result(dBμV) = Reading(dBμV) + Factor(dB);  
Over Limit(dB) = Result(dBμV) - Limit(dBμV)

Test Sample: J9F-9K2

|              |         |           |      |                       |         |
|--------------|---------|-----------|------|-----------------------|---------|
| Temperature: | 23.8 °C | Humidity: | 57 % | Atmospheric Pressure: | 101 kPa |
|--------------|---------|-----------|------|-----------------------|---------|

TM1 / Line: Line / Band: 2400-2483.5 MHz / BW: 1 / CH: L

Test Power Supply: AC 120V/60Hz for Adapter




| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit (dBuV) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|-------------|---------------|--------------|-----------------|----------|--------|
| 1   | 0.1660      | 32.09          | 19.78       | 51.87         | 65.15        | -13.28          | QP       |        |
| 2   | 0.1660      | 17.39          | 19.78       | 37.17         | 55.15        | -17.98          | AVG      |        |
| 3   | 0.2020      | 31.60          | 19.78       | 51.38         | 63.52        | -12.14          | QP       |        |
| 4   | 0.2100      | 22.54          | 19.78       | 42.32         | 53.20        | -10.88          | AVG      |        |
| 5   | 0.2380      | 29.84          | 19.79       | 49.63         | 62.16        | -12.53          | QP       |        |
| 6   | 0.2460      | 26.78          | 19.79       | 46.57         | 61.89        | -15.32          | QP       |        |
| 7   | 0.3060      | 19.93          | 19.79       | 39.72         | 50.08        | -10.36          | AVG      |        |
| 8   | 0.3100      | 29.68          | 19.79       | 49.47         | 59.97        | -10.50          | QP       |        |
| 9   | 0.4180      | 10.95          | 19.80       | 30.75         | 47.49        | -16.74          | AVG      |        |
| 10  | 0.4780      | 23.52          | 19.80       | 43.32         | 56.37        | -13.05          | QP       |        |
| 11  | 0.4780      | 13.02          | 19.80       | 32.82         | 46.37        | -13.55          | AVG      |        |
| 12  | 0.6740      | 8.19           | 19.82       | 28.01         | 46.00        | -17.99          | AVG      |        |

|              |         |           |      |                       |         |
|--------------|---------|-----------|------|-----------------------|---------|
| Temperature: | 23.8 °C | Humidity: | 57 % | Atmospheric Pressure: | 101 kPa |
|--------------|---------|-----------|------|-----------------------|---------|

TM1 / Line: Neutral / Band: 2400-2483.5 MHz / BW: 1 / CH: L

Test Power Supply: AC 120V/60Hz for Adapter



| No. | Freq. (MHz) | Reading (dBμV) | Factor (dB) | Result (dBμV) | Limit (dBμV) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|-------------|---------------|--------------|-----------------|----------|--------|
| 1   | 0.1660      | 27.80          | 19.78       | 47.58         | 65.15        | -17.57          | QP       |        |
| 2   | 0.1780      | 13.61          | 19.78       | 33.39         | 54.57        | -21.18          | AVG      |        |
| 3   | 0.1940      | 27.85          | 19.78       | 47.63         | 63.86        | -16.23          | QP       |        |
| 4   | 0.2100      | 18.50          | 19.78       | 38.28         | 53.20        | -14.92          | AVG      |        |
| 5   | 0.2500      | 14.13          | 19.79       | 33.92         | 51.75        | -17.83          | AVG      |        |
| 6   | 0.2980      | 25.57          | 19.79       | 45.36         | 60.30        | -14.94          | QP       |        |
| 7   | 0.3020      | 20.06          | 19.79       | 39.85         | 50.19        | -10.34          | AVG      |        |
| 8   | 0.4820      | 13.32          | 19.80       | 33.12         | 46.30        | -13.18          | AVG      |        |
| 9   | 0.5060      | 21.03          | 19.80       | 40.83         | 56.00        | -15.17          | QP       |        |
| 10  | 0.7019      | 7.22           | 19.82       | 27.04         | 46.00        | -18.96          | AVG      |        |
| 11  | 0.8420      | 14.24          | 19.84       | 34.08         | 56.00        | -21.92          | QP       |        |
| 12  | 1.1700      | 11.81          | 19.85       | 31.66         | 56.00        | -24.34          | QP       |        |

Note:

- Only record the worst data in the report.
- Result(dBμV) = Reading(dBμV) + Factor(dB);  
Over Limit(dB) = Result(dBμV) - Limit(dBμV)

## 4. 20dB Bandwidth


|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | 47 CFR 15.247(a)(1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Test Limit:       | Refer to 47 CFR 15.215(c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Test Method:      | ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 7.8.6, For occupied bandwidth measurements, use the procedure in 6.9.2. Frequency hopping shall be disabled for this test.<br>KDB 558074 D01 15.247 Meas Guidance v05r02                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Procedure:        | <p>A dBc bandwidth is measured as the width of the spectral envelope of the modulated signal, at an amplitude level reduced from a reference value by a specified ratio (or in decibels, a specified number of dB down from the reference value). Typical ratios, expressed in dB, are -6 dB, -20 dB, and -26 dB, corresponding to 6 dB BW, 20 dB BW, and 26 dB BW, respectively. In this subclause, the ratio is designated by “-xx dB.” The reference value is either the level of the unmodulated carrier or the highest level of the spectral envelope of the modulated signal, as stated by the applicable requirement. Some requirements might specify a specific maximum or minimum value for the “-xx dB” bandwidth; other requirements might specify that the “-xx dB” bandwidth be entirely contained within the authorized or designated frequency band.<sup>51</sup></p> <p>a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.</p> <p>b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be at least three times RBW, unless otherwise specified by the applicable requirement.</p> <p>c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level. Specific guidance is given in 4.1.6.2.</p> <p>d) Steps a) through c) might require iteration to adjust within the specified tolerances.</p> <p>e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.</p> <p>f) Set detection mode to peak and trace mode to max-hold.</p> <p>g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).</p> <p>h) Determine the “-xx dB down amplitude” using [(reference value) - xx]. Alternatively, this calculation may be made by using the marker-delta function of the instrument.</p> |

|  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|--|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <p>i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).</p> <p>j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The dBc bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.</p> <p>k) The dBc bandwidth shall be reported by providing spectral plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).</p> |
|--|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

#### 4.1. EUT Operation

|                        |                                                                                                                                                                                                                                                                                                                                                                                                 |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating Environment: |                                                                                                                                                                                                                                                                                                                                                                                                 |
| Test mode:             | <p>1:TX-GFSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with GFSK modulation.</p> <p>2:TX-<math>\pi/4</math>-DQPSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with <math>\pi/4</math>-DQPSK modulation.</p> <p>3:TX-8DPSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with 8DPSK modulation.</p> |

#### 4.2. Test Setup



#### 4.3. Test Data

|              |         |           |      |                       |          |
|--------------|---------|-----------|------|-----------------------|----------|
| Temperature: | 23.5 °C | Humidity: | 51 % | Atmospheric Pressure: | 99.5 kPa |
|--------------|---------|-----------|------|-----------------------|----------|

Please Refer to Appendix for Details.


5. Maximum Conducted Output Power

|                   |                                                                                                                                                                                                                                                                                                                  |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | 47 CFR 15.247(b)(1)                                                                                                                                                                                                                                                                                              |
| Test Limit:       | Refer to 47 CFR 15.247(b)(1), For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts. |
| Test Method:      | ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 7.8.5<br>KDB 558074 D01 15.247 Meas Guidance v05r02                                                                                                                                                                                |

5.1. EUT Operation

|                        |                                                                                                                                                                                                                                                                                                                                                               |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating Environment: |                                                                                                                                                                                                                                                                                                                                                               |
| Test mode:             | 1:TX-GFSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with GFSK modulation.<br>2:TX- $\pi/4$ -DQPSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with $\pi/4$ -DQPSK modulation.<br>3:TX-8DPSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with 8DPSK modulation. |

5.2. Test Setup



5.3. Test Data

|              |         |           |      |                       |          |
|--------------|---------|-----------|------|-----------------------|----------|
| Temperature: | 23.5 °C | Humidity: | 51 % | Atmospheric Pressure: | 99.5 kPa |
|--------------|---------|-----------|------|-----------------------|----------|

Please Refer to Appendix for Details.


## 6. Channel Separation

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | 47 CFR 15.247(a)(1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Test Limit:       | Refer to 47 CFR 15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.                                                                                                                                                                                                                                                                                                                                                                   |
| Test Method:      | ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 7.8.2<br>KDB 558074 D01 15.247 Meas Guidance v05r02                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Procedure:        | <p>The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:</p> <ul style="list-style-type: none"> <li>a) Span: Wide enough to capture the peaks of two adjacent channels.</li> <li>b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.</li> <li>c) Video (or average) bandwidth (VBW) <math>\geq</math> RBW.</li> <li>d) Sweep: No faster than coupled (auto) time.</li> <li>e) Detector function: Peak.</li> <li>f) Trace: Max-hold.</li> <li>g) Allow the trace to stabilize.</li> </ul> <p>Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A spectral plot of the data shall be included in the test report.</p> |

### 6.1. EUT Operation

|                        |                                                                                                                                                                                                                                                                                                                                                                          |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating Environment: |                                                                                                                                                                                                                                                                                                                                                                          |
| Test mode:             | <p>4:TX-GFSK (Hopping):Keep the EUT in continuously transmitting mode (hopping) with GFSK modulation,.</p> <p>5:TX-<math>\pi/4</math>-DQPSK (Hopping):Keep the EUT in continuously transmitting mode (hopping) with <math>\pi/4</math>-DQPSK modulation.</p> <p>6:TX-8DPSK (Hopping):Keep the EUT in continuously transmitting mode (hopping) with 8DPSK modulation.</p> |

6.2. Test Setup



6.3. Test Data

|              |         |           |      |                       |          |
|--------------|---------|-----------|------|-----------------------|----------|
| Temperature: | 23.5 °C | Humidity: | 51 % | Atmospheric Pressure: | 99.5 kPa |
|--------------|---------|-----------|------|-----------------------|----------|

Please Refer to Appendix for Details.


## 7. Number of Hopping Frequencies

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | 47 CFR 15.247(a)(1)(iii)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Test Limit:       | Refer to 47 CFR 15.247(a)(1)(iii), Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Test Method:      | ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 7.8.3<br>KDB 558074 D01 15.247 Meas Guidance v05r02                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Procedure:        | <p>The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:</p> <ul style="list-style-type: none"> <li>a) Span: The frequency band of operation. Depending on the number of channels the device supports, it could be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.</li> <li>b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.</li> <li>c) VBW <math>\geq</math> RBW.</li> <li>d) Sweep: No faster than coupled (auto) time.</li> <li>e) Detector function: Peak.</li> <li>f) Trace: Max-hold.</li> <li>g) Allow the trace to stabilize.</li> </ul> <p>It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A spectral plot of the data shall be included in the test report.</p> |

### 7.1. EUT Operation

|                        |                                                                                                                                                                                                                                                                                                                                                                          |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating Environment: |                                                                                                                                                                                                                                                                                                                                                                          |
| Test mode:             | <p>4:TX-GFSK (Hopping):Keep the EUT in continuously transmitting mode (hopping) with GFSK modulation,.</p> <p>5:TX-<math>\pi/4</math>-DQPSK (Hopping):Keep the EUT in continuously transmitting mode (hopping) with <math>\pi/4</math>-DQPSK modulation.</p> <p>6:TX-8DPSK (Hopping):Keep the EUT in continuously transmitting mode (hopping) with 8DPSK modulation.</p> |

7.2. Test Setup



7.3. Test Data

|              |         |           |      |                       |          |
|--------------|---------|-----------|------|-----------------------|----------|
| Temperature: | 23.5 °C | Humidity: | 51 % | Atmospheric Pressure: | 99.5 kPa |
|--------------|---------|-----------|------|-----------------------|----------|

Please Refer to Appendix for Details.

## 8. Dwell Time

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|-------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | 47 CFR 15.247(a)(1)(iii)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Test Limit:       | Refer to 47 CFR 15.247(a)(1)(iii), Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Test Method:      | ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 7.8.4<br>KDB 558074 D01 15.247 Meas Guidance v05r02                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Procedure:        | <p>The dwell time per hop on a channel is the time from the start of the first transmission to the end of the last transmission for that hop. If the device has a single transmission per hop then the dwell time is the duration of that transmission. If the device has a multiple transmissions per hop then the dwell time is measured from the start of the first transmission to the end of the last transmission.</p> <p>The time of occupancy is the total time that the device dwells on a channel over an observation period specified in the regulatory requirement. To determine the time of occupancy the spectrum analyzer will be configured to measure both the dwell time per hop and the number of times the device transmits on a specific channel in a given period.</p> <p>The EUT shall have its hopping function enabled. Compliance with the requirements shall be made with the minimum and with the maximum number of channels enabled. If the dwell time per channel does not vary with the number of channels then compliance with the requirements may be based on the minimum number of channels. If the device supports different dwell times per channel (example Bluetooth devices can dwell on a channel for 1, 3 or 5 time slots) then measurements can be limited to the longest dwell time with the minimum number of channels.</p> <p>Use the following spectrum analyzer settings to determine the dwell time per hop:</p> <ul style="list-style-type: none"> <li>a) Span: Zero span, centered on a hopping channel.</li> <li>b) RBW shall be <math>\leq</math> channel spacing and where possible RBW should be set <math>\gg 1/T</math>, where T is the expected transmission time per hop.</li> <li>c) Sweep time: Set so that the start of the first transmission and end of the last transmission for the hop are clearly captured. Setting the sweep time to be slightly longer than the hopping period per channel (hopping period = <math>1/\text{hopping rate}</math>) should achieve this.</li> <li>d) Use a video trigger, where possible with a trigger delay, so that the start of the transmission is clearly observed. The trigger level might need adjustment to reduce the chance of triggering when the system hops on an adjacent channel.</li> <li>e) Detector function: Peak.</li> <li>f) Trace: Clear-write, single sweep.</li> </ul> |

### Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.


Hotline: 400-003-0500 web: [www.anbotek.com](http://www.anbotek.com) E-mail: [service@anbotek.com](mailto:service@anbotek.com)

|  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <p>g) Place markers at the start of the first transmission on the channel and at the end of the last transmission. The dwell time per hop is the time between these two markers.</p> <p>To determine the number of hops on a channel in the regulatory observation period repeat the measurement using a longer sweep time. When the device uses a single hopping sequence the period of measurement should be sufficient to capture at least 2 hops. When the device uses a dynamic hopping sequence, or the sequence varies, the period of measurement may need to capture multiple hops to better determine the average time of occupancy. Count the number of hops on the channel across the sweep time.</p> <p>The average number of hops on the same channel within the regulatory observation period is calculated from the number of hops on the channel divided by the spectrum analyzer sweep time multiplied by the regulatory observation period. For example, if three hops are counted with an analyzer sweep time of 500 ms and the regulatory observation period is 10 s, then the number of hops in that ten seconds is <math>3 / 0.5 \times 10</math>, or 60 hops.</p> <p>The average time of occupancy is calculated by multiplying the dwell time per hop by the number of hops in the observation period.</p> |
|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## 8.1. EUT Operation

|                        |                                                                                                                                                                                                                                                                                                                                                                          |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating Environment: |                                                                                                                                                                                                                                                                                                                                                                          |
| Test mode:             | <p>4:TX-GFSK (Hopping):Keep the EUT in continuously transmitting mode (hopping) with GFSK modulation,.</p> <p>5:TX-<math>\pi/4</math>-DQPSK (Hopping):Keep the EUT in continuously transmitting mode (hopping) with <math>\pi/4</math>-DQPSK modulation.</p> <p>6:TX-8DPSK (Hopping):Keep the EUT in continuously transmitting mode (hopping) with 8DPSK modulation.</p> |

## 8.2. Test Setup



## 8.3. Test Data

|              |         |           |      |                       |         |
|--------------|---------|-----------|------|-----------------------|---------|
| Temperature: | 23.5 °C | Humidity: | 51 % | Atmospheric Pressure: | 101 kPa |
|--------------|---------|-----------|------|-----------------------|---------|

Please Refer to Appendix for Details.


## 9. Emissions in non-restricted frequency bands

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | 47 CFR 15.247(d)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Test Limit:       | Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. |
| Test Method:      | ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 7.8.7<br>KDB 558074 D01 15.247 Meas Guidance v05r02                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

### 9.1. EUT Operation

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating Environment: |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Test mode:             | 1:TX-GFSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with GFSK modulation.<br>2:TX- $\pi/4$ -DQPSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with $\pi/4$ -DQPSK modulation.<br>3:TX-8DPSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with 8DPSK modulation.<br>4:TX-GFSK (Hopping):Keep the EUT in continuously transmitting mode (hopping) with GFSK modulation.,<br>5:TX- $\pi/4$ -DQPSK (Hopping):Keep the EUT in continuously transmitting mode (hopping) with $\pi/4$ -DQPSK modulation.<br>6:TX-8DPSK (Hopping):Keep the EUT in continuously transmitting mode (hopping) with 8DPSK modulation. |

### 9.2. Test Setup



### 9.3. Test Data

|              |         |           |      |                       |          |
|--------------|---------|-----------|------|-----------------------|----------|
| Temperature: | 23.5 °C | Humidity: | 51 % | Atmospheric Pressure: | 99.5 kPa |
|--------------|---------|-----------|------|-----------------------|----------|

Please Refer to Appendix for Details.


## 10. Band edge emissions (Radiated)

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                                                                                                         |                                   |                               |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|-------------------------------|
| Test Requirement:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)). |                                   |                               |
| Test Limit:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Frequency (MHz)                                                                                                                                                                                                         | Field strength (microvolts/meter) | Measurement distance (meters) |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 0.009-0.490                                                                                                                                                                                                             | 2400/F(kHz)                       | 300                           |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 0.490-1.705                                                                                                                                                                                                             | 24000/F(kHz)                      | 30                            |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 1.705-30.0                                                                                                                                                                                                              | 30                                | 30                            |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 30-88                                                                                                                                                                                                                   | 100 **                            | 3                             |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 88-216                                                                                                                                                                                                                  | 150 **                            | 3                             |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 216-960                                                                                                                                                                                                                 | 200 **                            | 3                             |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Above 960                                                                                                                                                                                                               | 500                               | 3                             |
| <p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p> |                                                                                                                                                                                                                         |                                   |                               |
| Test Method:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.10<br>KDB 558074 D01 15.247 Meas Guidance v05r02                                                                                         |                                   |                               |
| Procedure:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.10.5.2                                                                                                                                   |                                   |                               |

### 10.1. EUT Operation

|                        |                                                                                                                                                                                                                                                                                                                                                                                                 |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating Environment: |                                                                                                                                                                                                                                                                                                                                                                                                 |
| Test mode:             | <p>1:TX-GFSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with GFSK modulation.</p> <p>2:TX-<math>\pi/4</math>-DQPSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with <math>\pi/4</math>-DQPSK modulation.</p> <p>3:TX-8DPSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with 8DPSK modulation.</p> |

## 10.2. Test Setup



### 10.3. Test Data

|              |         |           |      |                       |          |
|--------------|---------|-----------|------|-----------------------|----------|
| Temperature: | 23.5 °C | Humidity: | 51 % | Atmospheric Pressure: | 99.5 kPa |
|--------------|---------|-----------|------|-----------------------|----------|

| TM1 / CH: L                                          |                |               |                 |                |                 |              |
|------------------------------------------------------|----------------|---------------|-----------------|----------------|-----------------|--------------|
| Peak value:                                          |                |               |                 |                |                 |              |
| Frequency (MHz)                                      | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | polarization |
| 2390.000                                             | 32.56          | 9.73          | 42.29           | 74.00          | -31.71          | Vertical     |
| 2310.000                                             | 37.17          | 9.58          | 46.75           | 74.00          | -27.25          | Vertical     |
| 2390.000                                             | 29.02          | 9.73          | 38.75           | 74.00          | -35.25          | Horizontal   |
| 2310.000                                             | 31.61          | 9.58          | 41.19           | 74.00          | -32.81          | Horizontal   |
| TM1 / CH: H                                          |                |               |                 |                |                 |              |
| Peak value:                                          |                |               |                 |                |                 |              |
| Frequency (MHz)                                      | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | polarization |
| 2483.500                                             | 34.15          | 9.91          | 44.06           | 74.00          | -29.94          | Vertical     |
| 2500.000                                             | 35.99          | 9.94          | 45.93           | 74.00          | -28.07          | Vertical     |
| 2483.500                                             | 37.22          | 9.91          | 47.13           | 74.00          | -26.87          | Horizontal   |
| 2500.000                                             | 32.13          | 9.94          | 42.07           | 74.00          | -31.93          | Horizontal   |
| Note: Result=Reading+Factor, Over Limit=Result-Limit |                |               |                 |                |                 |              |

#### Remark:

1. When the PK measure result value is less than the AVG limit value, the AV measure result values test not applicable.
2. During the test, pre-scan all modes, the report only record the worse case mode.


## 11. Emissions in restricted frequency bands (below 1GHz)

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                         |                                   |                               |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|-------------------------------|
| Test Requirement:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)). |                                   |                               |
| Test Limit:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Frequency (MHz)                                                                                                                                                                                                         | Field strength (microvolts/meter) | Measurement distance (meters) |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 0.009-0.490                                                                                                                                                                                                             | 2400/F(kHz)                       | 300                           |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 0.490-1.705                                                                                                                                                                                                             | 24000/F(kHz)                      | 30                            |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 1.705-30.0                                                                                                                                                                                                              | 30                                | 30                            |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 30-88                                                                                                                                                                                                                   | 100 **                            | 3                             |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 88-216                                                                                                                                                                                                                  | 150 **                            | 3                             |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 216-960                                                                                                                                                                                                                 | 200 **                            | 3                             |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Above 960                                                                                                                                                                                                               | 500                               | 3                             |
| <p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges.</p> <p>The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p> |                                                                                                                                                                                                                         |                                   |                               |
| Test Method:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.5.4<br>KDB 558074 D01 15.247 Meas Guidance v05r02                                                                                        |                                   |                               |
| Procedure:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.5.4                                                                                                                                      |                                   |                               |

### 11.1. EUT Operation

|                        |                                                                                                                                                                                                                                                                                                                                                                                                 |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating Environment: |                                                                                                                                                                                                                                                                                                                                                                                                 |
| Test mode:             | <p>1:TX-GFSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with GFSK modulation.</p> <p>2:TX-<math>\pi/4</math>-DQPSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with <math>\pi/4</math>-DQPSK modulation.</p> <p>3:TX-8DPSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with 8DPSK modulation.</p> |

## 11.2. Test Setup




11.3. Test Data

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Test Sample: J9B-9K2


|              |         |           |      |                       |         |
|--------------|---------|-----------|------|-----------------------|---------|
| Temperature: | 24.8 °C | Humidity: | 51 % | Atmospheric Pressure: | 101 kPa |
|--------------|---------|-----------|------|-----------------------|---------|



|              |         |           |      |                       |         |
|--------------|---------|-----------|------|-----------------------|---------|
| Temperature: | 24.8 °C | Humidity: | 51 % | Atmospheric Pressure: | 101 kPa |
|--------------|---------|-----------|------|-----------------------|---------|

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: L

Test Power Supply: AC 120V/60Hz for Adapter



| No. | Freq.<br>(MHz) | Reading<br>(dBuV) | Factor<br>(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Over Limit<br>(dB) | Detector | Remark |
|-----|----------------|-------------------|------------------|--------------------|-------------------|--------------------|----------|--------|
| 1   | 250.082        | 51.80             | -24.27           | 27.53              | 46.00             | -18.47             | QP       |        |
| 2   | 325.025        | 54.20             | -21.02           | 33.18              | 46.00             | -12.82             | QP       |        |
| 3   | 380.247        | 54.36             | -18.17           | 36.19              | 46.00             | -9.81              | QP       |        |
| 4   | 486.461        | 50.63             | -15.79           | 34.84              | 46.00             | -11.16             | QP       |        |
| 5   | 567.119        | 48.96             | -14.26           | 34.70              | 46.00             | -11.30             | QP       |        |
| 6   | 600.110        | 53.32             | -13.59           | 39.73              | 46.00             | -6.27              | QP       |        |


Note:

- Only record the worst data in the report.
- Result(dBuV/m) = Reading(dBuV) + Factor(dB/m);  
Over Limit(dB) = Result(dBuV/m) - Limit(dBuV/m)

Test Sample: J9F-9K2


|              |         |           |      |                       |         |
|--------------|---------|-----------|------|-----------------------|---------|
| Temperature: | 24.8 °C | Humidity: | 51 % | Atmospheric Pressure: | 101 kPa |
|--------------|---------|-----------|------|-----------------------|---------|

|                                                                        |
|------------------------------------------------------------------------|
| TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: L |
| Test Power Supply: AC 120V/60Hz for Adapter                            |



| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|---------------|-----------------|----------------|-----------------|----------|--------|
| 1   | 188.082     | 54.20          | -24.96        | 29.24           | 43.50          | -14.26          | QP       |        |
| 2   | 250.082     | 58.17          | -24.27        | 33.90           | 46.00          | -12.10          | QP       |        |
| 3   | 312.316     | 52.94          | -22.09        | 30.85           | 46.00          | -15.15          | QP       |        |
| 4   | 400.081     | 51.22          | -17.55        | 33.67           | 46.00          | -12.33          | QP       |        |
| 5   | 643.707     | 44.34          | -12.92        | 31.42           | 46.00          | -14.58          | QP       |        |
| 6   | 702.069     | 42.75          | -12.20        | 30.55           | 46.00          | -15.45          | QP       |        |

|              |         |           |      |                       |         |
|--------------|---------|-----------|------|-----------------------|---------|
| Temperature: | 24.8 °C | Humidity: | 51 % | Atmospheric Pressure: | 101 kPa |
|--------------|---------|-----------|------|-----------------------|---------|



Note:

- Only record the worst data in the report.
- Result(dBuV/m) = Reading(dBuV) + Factor(dB/m);  
Over Limit(dB) = Result(dBuV/m) - Limit(dBuV/m)


## 12. Emissions in restricted frequency bands (above 1GHz)

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                                                                                                         |                                   |                               |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|-------------------------------|
| Test Requirement:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Refer to 47 CFR 15.247(d), in addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)). |                                   |                               |
| Test Limit:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Frequency (MHz)                                                                                                                                                                                                         | Field strength (microvolts/meter) | Measurement distance (meters) |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 0.009-0.490                                                                                                                                                                                                             | 2400/F(kHz)                       | 300                           |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 0.490-1.705                                                                                                                                                                                                             | 24000/F(kHz)                      | 30                            |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 1.705-30.0                                                                                                                                                                                                              | 30                                | 30                            |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 30-88                                                                                                                                                                                                                   | 100 **                            | 3                             |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 88-216                                                                                                                                                                                                                  | 150 **                            | 3                             |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 216-960                                                                                                                                                                                                                 | 200 **                            | 3                             |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Above 960                                                                                                                                                                                                               | 500                               | 3                             |
| <p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p> |                                                                                                                                                                                                                         |                                   |                               |
| Test Method:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.5.4<br>KDB 558074 D01 15.247 Meas Guidance v05r02                                                                                        |                                   |                               |
| Procedure:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.5.4                                                                                                                                      |                                   |                               |

### 12.1. EUT Operation

|                        |                                                                                                                                                                                                                                                                                                                                                                                                 |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating Environment: |                                                                                                                                                                                                                                                                                                                                                                                                 |
| Test mode:             | <p>1:TX-GFSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with GFSK modulation.</p> <p>2:TX-<math>\pi/4</math>-DQPSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with <math>\pi/4</math>-DQPSK modulation.</p> <p>3:TX-8DPSK (Non-Hopping):Keep the EUT in continuously transmitting mode (non-hopping) with 8DPSK modulation.</p> |

## 12.2. Test Setup



### 12.3. Test Data

|              |         |           |      |                       |         |
|--------------|---------|-----------|------|-----------------------|---------|
| Temperature: | 24.5 °C | Humidity: | 57 % | Atmospheric Pressure: | 101 kPa |
|--------------|---------|-----------|------|-----------------------|---------|

| TM1 / CH: L     |                |               |                 |                |                 |              |
|-----------------|----------------|---------------|-----------------|----------------|-----------------|--------------|
| Peak value:     |                |               |                 |                |                 |              |
| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | polarization |
| 4804.00         | 28.98          | 15.27         | 44.25           | 74.00          | -29.75          | Vertical     |
| 7206.00         | 29.83          | 18.09         | 47.92           | 74.00          | -26.08          | Vertical     |
| 9608.00         | 31.28          | 23.76         | 55.04           | 74.00          | -18.96          | Vertical     |
| 12010.00        | *              |               |                 | 74.00          |                 | Vertical     |
| 14412.00        | *              |               |                 | 74.00          |                 | Vertical     |
| 4804.00         | 29.20          | 15.27         | 44.47           | 74.00          | -29.53          | Horizontal   |
| 7206.00         | 30.68          | 18.09         | 48.77           | 74.00          | -25.23          | Horizontal   |
| 9608.00         | 29.01          | 23.76         | 52.77           | 74.00          | -21.23          | Horizontal   |
| 12010.00        | *              |               |                 | 74.00          |                 | Horizontal   |
| 14412.00        | *              |               |                 | 74.00          |                 | Horizontal   |
| Average value:  |                |               |                 |                |                 |              |
| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | polarization |
| 4804.00         | 18.36          | 15.27         | 33.63           | 54.00          | -20.37          | Vertical     |
| 7206.00         | 18.86          | 18.09         | 36.95           | 54.00          | -17.05          | Vertical     |
| 9608.00         | 20.30          | 23.76         | 44.06           | 54.00          | -9.94           | Vertical     |
| 12010.00        | *              |               |                 | 54.00          |                 | Vertical     |
| 14412.00        | *              |               |                 | 54.00          |                 | Vertical     |
| 4804.00         | 17.55          | 15.27         | 32.82           | 54.00          | -21.18          | Horizontal   |
| 7206.00         | 19.74          | 18.09         | 37.83           | 54.00          | -16.17          | Horizontal   |
| 9608.00         | 18.32          | 23.76         | 42.08           | 54.00          | -11.92          | Horizontal   |
| 12010.00        | *              |               |                 | 54.00          |                 | Horizontal   |
| 14412.00        | *              |               |                 | 54.00          |                 | Horizontal   |

| TM1 / CH: M     |                |               |                 |                |                 |              |
|-----------------|----------------|---------------|-----------------|----------------|-----------------|--------------|
| Peak value:     |                |               |                 |                |                 |              |
| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | polarization |
| 4882.00         | 29.00          | 15.42         | 44.42           | 74.00          | -29.58          | Vertical     |
| 7323.00         | 29.68          | 18.02         | 47.70           | 74.00          | -26.30          | Vertical     |
| 9764.00         | 30.29          | 23.80         | 54.09           | 74.00          | -19.91          | Vertical     |
| 12205.00        | *              |               |                 | 74.00          |                 | Vertical     |
| 14646.00        | *              |               |                 | 74.00          |                 | Vertical     |
| 4882.00         | 28.90          | 15.42         | 44.32           | 74.00          | -29.68          | Horizontal   |
| 7323.00         | 30.67          | 18.02         | 48.69           | 74.00          | -25.31          | Horizontal   |
| 9764.00         | 28.71          | 23.80         | 52.51           | 74.00          | -21.49          | Horizontal   |
| 12205.00        | *              |               |                 | 74.00          |                 | Horizontal   |
| 14646.00        | *              |               |                 | 74.00          |                 | Horizontal   |
| Average value:  |                |               |                 |                |                 |              |
| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | polarization |
| 4882.00         | 18.09          | 15.42         | 33.51           | 54.00          | -20.49          | Vertical     |
| 7323.00         | 18.96          | 18.02         | 36.98           | 54.00          | -17.02          | Vertical     |
| 9764.00         | 20.16          | 23.80         | 43.96           | 54.00          | -10.04          | Vertical     |
| 12205.00        | *              |               |                 | 54.00          |                 | Vertical     |
| 14646.00        | *              |               |                 | 54.00          |                 | Vertical     |
| 4882.00         | 17.46          | 15.42         | 32.88           | 54.00          | -21.12          | Horizontal   |
| 7323.00         | 19.30          | 18.02         | 37.32           | 54.00          | -16.68          | Horizontal   |
| 9764.00         | 18.83          | 23.80         | 42.63           | 54.00          | -11.37          | Horizontal   |
| 12205.00        | *              |               |                 | 54.00          |                 | Horizontal   |
| 14646.00        | *              |               |                 | 54.00          |                 | Horizontal   |

| TM1 / CH: H     |                |               |                 |                |                 |              |
|-----------------|----------------|---------------|-----------------|----------------|-----------------|--------------|
| Peak value:     |                |               |                 |                |                 |              |
| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | polarization |
| 4960.00         | 29.27          | 15.58         | 44.85           | 74.00          | -29.15          | Vertical     |
| 7440.00         | 29.69          | 17.93         | 47.62           | 74.00          | -26.38          | Vertical     |
| 9920.00         | 30.84          | 23.83         | 54.67           | 74.00          | -19.33          | Vertical     |
| 12400.00        | *              |               |                 | 74.00          |                 | Vertical     |
| 14880.00        | *              |               |                 | 74.00          |                 | Vertical     |
| 4960.00         | 28.97          | 15.58         | 44.55           | 74.00          | -29.45          | Horizontal   |
| 7440.00         | 30.70          | 17.93         | 48.63           | 74.00          | -25.37          | Horizontal   |
| 9920.00         | 29.39          | 23.83         | 53.22           | 74.00          | -20.78          | Horizontal   |
| 12400.00        | *              |               |                 | 74.00          |                 | Horizontal   |
| 14880.00        | *              |               |                 | 74.00          |                 | Horizontal   |
| Average value:  |                |               |                 |                |                 |              |
| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | polarization |
| 4960.00         | 19.21          | 15.58         | 34.79           | 54.00          | -19.21          | Vertical     |
| 7440.00         | 19.97          | 17.93         | 37.90           | 54.00          | -16.10          | Vertical     |
| 9920.00         | 20.71          | 23.83         | 44.54           | 54.00          | -9.46           | Vertical     |
| 12400.00        | *              |               |                 | 54.00          |                 | Vertical     |
| 14880.00        | *              |               |                 | 54.00          |                 | Vertical     |
| 4960.00         | 18.90          | 15.58         | 34.48           | 54.00          | -19.52          | Horizontal   |
| 7440.00         | 20.67          | 17.93         | 38.60           | 54.00          | -15.40          | Horizontal   |
| 9920.00         | 18.73          | 23.83         | 42.56           | 54.00          | -11.44          | Horizontal   |
| 12400.00        | *              |               |                 | 54.00          |                 | Horizontal   |
| 14880.00        | *              |               |                 | 54.00          |                 | Horizontal   |

Remark:

1. Result =Reading + Factor
2. Test frequency are from 1GHz to 25GHz, “\*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.
3. Only the worst case is recorded in the report.

## **APPENDIX I -- TEST SETUP PHOTOGRAPH**

Please refer to separated files Appendix I -- Test Setup Photograph\_RF

## **APPENDIX II -- EXTERNAL PHOTOGRAPH**

Please refer to separated files Appendix II -- External Photograph

## **APPENDIX III -- INTERNAL PHOTOGRAPH**

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----

