



**Shenzhen GUOREN Certification Technology Service Co., Ltd.**

101#, Building K & Building T, The Second Industrial Zone, Jiazitang Community,  
Fenghuang Street, Guangming District, Shenzhen, China

**FCC PART 15 SUBPART E TEST REPORT**

**FCC PART 15 SUBPART E 15.407**

**Report Reference No.**.....: **GRCTR240702037-04**

**FCC ID**.....: **SMC-V93**

Compiled by

( position+printed name+signature)..: Testing Engineer Jimmy Wang

Supervised by

( position+printed name+signature)..: Project Engineer Kelley Zhang

Approved by

( position+printed name+signature)..: Manager Sam Wang

**Date of issue**.....: **Aug. 07, 2024**

**Testing Laboratory Name**.....: **Shenzhen GUOREN Certification Technology Service Co., Ltd.**

**Address**.....: 101#, Building K & Building T, The Second Industrial Zone,  
Jiazitang Community, Fenghuang Street, Guangming District,  
Shenzhen, China

**Applicant's name**.....: **SHENZHEN HOLATEK CO., LTD.**

**Address**.....: #12,Building 1,Chongwen Park, Nanshan Zhiyuan,3370 Liuxian  
Ave, Nanshan District, Shenzhen, China.

**Test specification**.....:

**Standard**.....: **FCC Part 15 Subpart E 15.407**

**Shenzhen GUOREN Certification Technology Service Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen GUOREN Certification Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen GUOREN Certification Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test item description**.....: **Smart Projector**

**Trade Mark**.....: **JMGO**

**Manufacturer**.....: **SHENZHEN HOLATEK CO., LTD.**

**Model/Type reference**.....: **J92-5D5**

**Listed Models** .....: J92-5D2,J92-5D3,J92-5D4,J92-5D6,J92-5D7,J92-5D8,J92-  
5D9,J92-5DA,J92-5DB,J92-5DC,J92-5DD,J92-5DE,J92-5DF,J92-  
5DG,J92-5DH,J92-5DI,J92-5DJ,J92-5DK,J92-5DM,J92-5DN,J92-  
5DL,J92-5DO,J92-5DP,J92-5DQ,J92-5DR,J92-5DS,J92-5DT,J92-  
5DU,J92-5DV,J92-5DW,J92-5DX,J92-5DY,J92-5DZ

**Firmware Version**.....: **1.1.31.8**

**Hardware Version**.....: **Ver A**

**Modulation** .....: **OFDM**

**Frequency**.....: **From 5180MHz-5240MHz, 5745MHz-5825MHz**

**Ratings**.....: **DC 24V from external circuit**

**Result**.....: **PASS**

TEST REPORT

Equipment under Test : Smart Projector

Model /Type : J92-5D5

Listed Models : J92-5D2,J92-5D3,J92-5D4,J92-5D6,J92-5D7,J92-5D8,J92-5D9,J92-5DA,J92-5DB,J92-5DC,J92-5DD,J92-5DE,J92-5DF,J92-5DG,J92-5DH,J92-5DI,J92-5DJ,J92-5DK,J92-5DM,J92-5DN,J92-5DL,J92-5DO,J92-5DP,J92-5DQ,J92-5DR,J92-5DS,J92-5DT,J92-5DU,J92-5DV,J92-5DW,J92-5DX,J92-5DY,J92-5DZ

Applicant : SHENZHEN HOLATEK CO., LTD.

Address : #12,Building 1,Chongwen Park, Nanshan Zhiyuan,3370 Liuxian Ave, Nanshan District, Shenzhen, China.

Manufacturer : SHENZHEN HOLATEK CO., LTD.

Address : #12,Building 1,Chongwen Park, Nanshan Zhiyuan,3370 Liuxian Ave, Nanshan District, Shenzhen, China.

|              |      |
|--------------|------|
| Test Result: | PASS |
|--------------|------|

The test report merely corresponds to the test sample.  
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Contents

|                                                               |            |
|---------------------------------------------------------------|------------|
| <b>1 TEST STANDARDS .....</b>                                 | <b>4</b>   |
| <b>2 SUMMARY .....</b>                                        | <b>5</b>   |
| 2.1 General Remarks .....                                     | 5          |
| 2.2 Product Description .....                                 | 5          |
| 2.3 Equipment Under Test .....                                | 6          |
| 2.4 Short description of the Equipment under Test (EUT) ..... | 6          |
| 2.5 EUT configuration .....                                   | 6          |
| 2.6 EUT operation mode .....                                  | 6          |
| 2.7 Block Diagram of Test Setup .....                         | 6          |
| 2.8 Related Submittal(s) / Grant (s) .....                    | 7          |
| 2.9 Modifications .....                                       | 7          |
| <b>3 TEST ENVIRONMENT .....</b>                               | <b>8</b>   |
| 3.1 Address of the test laboratory .....                      | 8          |
| 3.2 Test Facility .....                                       | 8          |
| 3.3 Environmental conditions .....                            | 8          |
| 3.4 Test Description .....                                    | 8          |
| 3.5 Statement of the measurement uncertainty .....            | 9          |
| 3.6 Equipments Used during the Test .....                     | 10         |
| <b>4 TEST CONDITIONS AND RESULTS .....</b>                    | <b>11</b>  |
| 4.1 AC Power Conducted Emission .....                         | 11         |
| 4.2 Radiated Emissions .....                                  | 14         |
| 4.3 Maximum Conducted Average Output Power .....              | 21         |
| 4.4 Power Spectral Density .....                              | 28         |
| 4.5 Emission Bandwidth (26dB Bandwidth) .....                 | 63         |
| 4.6 Minimum Emission Bandwidth (6dB Bandwidth) .....          | 79         |
| 4.7 Frequency Stability .....                                 | 95         |
| 4.8 Automatically Discontinue Transmission .....              | 98         |
| 4.9 Band edge for RF Conducted Emissions .....                | 99         |
| <b>5 TEST SETUP PHOTOS OF THE EUT .....</b>                   | <b>127</b> |
| <b>6 PHOTOS OF THE EUT .....</b>                              | <b>128</b> |

## **1 TEST STANDARDS**

The tests were performed according to following standards:

[FCC Rules Part 15.407](#): UNLICENSED NATIONAL INFORMATION INFRASTRUCTURE DEVICES.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 789033 D02](#): GUIDELINES FOR COMPLIANCE TESTING OF UNLICENSED NATIONAL INFORMATION INFRASTRUCTURE (U-NII) DEVICES PART 15, SUBPART E

## 2 SUMMARY

### 2.1 General Remarks

|                                |   |               |
|--------------------------------|---|---------------|
| Date of receipt of test sample | : | Jul. 28, 2024 |
| Testing commenced on           | : | Jul. 28, 2024 |
| Testing concluded on           | : | Aug. 07, 2024 |

### 2.2 Product Description

|                                                                                                                                                                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                    |              |               |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|--------------|---------------|
| Product Name:                                                                                                                                                                                                                                         | Smart Projector                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                    |              |               |
| Model/Type reference:                                                                                                                                                                                                                                 | J92-5D5                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                    |              |               |
| Listed Models:                                                                                                                                                                                                                                        | J92-5D2,J92-5D3,J92-5D4,J92-5D6,J92-5D7,J92-5D8,J92-5D9,J92-5DA,J92-5DB,J92-5DC,J92-5DD,J92-5DE,J92-5DF,J92-5DG,J92-5DH,J92-5DI,J92-5DJ,J92-5DK,J92-5DM,J92-5DN,J92-5DL,J92-5DO,J92-5DP,J92-5DQ,J92-5DR,J92-5DS,J92-5DT,J92-5DU,J92-5DV,J92-5DW,J92-5DX ,J92-5DY,J92-5DZ(The electrical circuit design, layout, components used and internal wiring are identical. Only the body color, pattern, sales customers, and sales regions are different) |                                    |              |               |
| Power supply:                                                                                                                                                                                                                                         | DC 24V from external circuit                                                                                                                                                                                                                                                                                                                                                                                                                       |                                    |              |               |
| Adapter information:                                                                                                                                                                                                                                  | M/N:NSA240EC-2401001<br>Input:AC 100-240V 50/60Hz 2.5A<br>Output:DC 24V/10.0A                                                                                                                                                                                                                                                                                                                                                                      |                                    |              |               |
| Sample ID:                                                                                                                                                                                                                                            | GRCTR240702037-1# (Engineer sample),<br>GRCTR240702037-2# (Normal sample)                                                                                                                                                                                                                                                                                                                                                                          |                                    |              |               |
| WIFI                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                    |              |               |
| Supported type:                                                                                                                                                                                                                                       | 20MHz system                                                                                                                                                                                                                                                                                                                                                                                                                                       | 40MHz system                       | 80MHz system | 160MHz system |
|                                                                                                                                                                                                                                                       | 802.11a<br>802.11n<br>802.11ac<br>802.11ax                                                                                                                                                                                                                                                                                                                                                                                                         | 802.11n<br>802.11ac<br>802.11ax    | N/A          | N/A           |
| Operation frequency:                                                                                                                                                                                                                                  | 5180MHz-5240MHz<br>5745MHz-5825MHz                                                                                                                                                                                                                                                                                                                                                                                                                 | 5190MHz-5230MHz<br>5755MHz-5795MHz | N/A          | N/A           |
| Modulation:                                                                                                                                                                                                                                           | OFDM                                                                                                                                                                                                                                                                                                                                                                                                                                               | OFDM                               | N/A          | N/A           |
| Channel number:                                                                                                                                                                                                                                       | 9                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 4                                  | N/A          | N/A           |
| Channel separation:                                                                                                                                                                                                                                   | 20MHz                                                                                                                                                                                                                                                                                                                                                                                                                                              | 40MHz                              | N/A          | N/A           |
| Antenna type:                                                                                                                                                                                                                                         | FPC antenna                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                    |              |               |
| Antenna gain*(Supplied by the customer):                                                                                                                                                                                                              | Ant 1:<br>3.3 dBi for 5180MHz-5240MHz<br>3.3 dBi for 5745MHz-5825MHz<br>Ant 2:<br>3.3 dBi for 5180MHz-5240MHz<br>3.2 dBi for 5745MHz-5825MHz                                                                                                                                                                                                                                                                                                       |                                    |              |               |
| Remark:*When the information provided by the customer was used to calculate test results, if the information provided by the customer is not accurate, shenzhen GUOREN Certification Technology Service Co., Ltd. does not assume any responsibility. |                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                    |              |               |

## 2.3 Equipment Under Test

### Power supply system utilised

|                      |   |                                                                   |                                   |
|----------------------|---|-------------------------------------------------------------------|-----------------------------------|
| Power supply voltage | : | <input type="radio"/> 230V / 50 Hz                                | <input type="radio"/> 120V / 60Hz |
|                      |   | <input type="radio"/> 12 V DC                                     | <input type="radio"/> 24 V DC     |
|                      |   | <input checked="" type="radio"/> Other (specified in blank below) |                                   |

DC 24V from external circuit

## 2.4 Short description of the Equipment under Test (EUT)

This is a Smart Projector.

For more details, refer to the user's manual of the EUT.

## 2.5 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

☐ - supplied by the manufacturer

☒ - supplied by the lab

|                         |                 |
|-------------------------|-----------------|
| <input type="radio"/> / | M/N: /          |
|                         | Manufacturer: / |

## 2.6 EUT operation mode


The Applicant provides communication tools software(SecureCRT) to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) for testing meet KDB558074 test requirement.

Operation Frequency List WIFI on 5G Band:

| Operating band               | 20MHz   |                 | 40MHz   |                 | 80MHz   |                 |
|------------------------------|---------|-----------------|---------|-----------------|---------|-----------------|
|                              | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| U-NII 1<br>(5150MHz-5250MHz) | 36      | 5180            | 38      | 5190            | 42      | 5210            |
|                              | 40      | 5200            |         |                 |         |                 |
|                              | 44      | 5220            | 46      | 5230            |         |                 |
|                              | 48      | 5240            |         |                 |         |                 |
| U-NII 3<br>(5725MHz-5850MHz) | 149     | 5745            | 151     | 5755            | 155     | 5775            |
|                              | 153     | 5765            |         |                 |         |                 |
|                              | 157     | 5785            | 159     | 5795            |         |                 |
|                              | 161     | 5805            |         |                 |         |                 |
|                              | 165     | 5825            | --      | --              | --      | --              |

Note: The line display in gray is those Channels/Frequencies select to test in this report for each operation mode.

## 2.7 Block Diagram of Test Setup



## **2.8 Related Submittal(s) / Grant (s)**

This submittal(s) (test report) is intended to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.

## **2.9 Modifications**

No modifications were implemented to meet testing criteria.

### 3 TEST ENVIRONMENT

#### 3.1 Address of the test laboratory

**Shenzhen GUOREN Certification Technology Service Co., Ltd.**

101#, Building K & Building T, The Second Industrial Zone, Jiazitang Community, Fenghuang Street, Guangming District, Shenzhen, China

#### 3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

**FCC-Registration No.: 920798    Designation Number: CN1304**

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

**A2LA-Lab Cert. No.: 6202.01**

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

**ISED#: 27264    CAB identifier: CN0115**

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed by Innovation, Science and Economic Development Canada to perform electromagnetic emission measurement.

**CNAS-Lab Code: L15631**

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories for the Competence of Testing and Calibration Laboratories.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

#### 3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

|                    |              |
|--------------------|--------------|
| Normal Temperature | 15-35 °C     |
| Relative Humidity  | 30-60 %      |
| Air Pressure       | 950-1050mbar |

#### 3.4 Test Description

| FCC Requirement    |                                            |                       |
|--------------------|--------------------------------------------|-----------------------|
| FCC Part 15.207    | AC Power Conducted Emission                | PASS                  |
| FCC Part 15.407(a) | Emission Bandwidth(26dBm Bandwidth)        | PASS <sup>Note1</sup> |
| FCC Part 15.407(e) | Minimum Emission Bandwidth(6dBm Bandwidth) | PASS <sup>Note2</sup> |
| FCC Part 15.407(a) | Maximum Conducted Output Power             | PASS                  |
| FCC Part 15.407(a) | Peak Power Spectral Density                | PASS                  |
| FCC Part 15.407(g) | Frequency Stability                        | PASS                  |



|                                  |                                        |            |
|----------------------------------|----------------------------------------|------------|
| FCC Part 15.407(b)               | Undesirable emission                   | PASS       |
| FCC Part 15.407(b)/15.205/15.209 | Radiated Emissions                     | PASS       |
| FCC Part 15.407(h)               | Dynamic Frequency Selection            | N/A Note 3 |
| FCC Part 15.203/15.247(b)        | Antenna Requirement                    | PASS       |
| FCC Part 15.407(c)               | Automatically Discontinue Transmission | PASS       |

Note 1: Apply to U-NII 1, U-NII 2A, and U-NII 2C band.

Note 2: Apply to U-NII 3 band only.

Note 3: This device not work in DFS band.

Note 4: N/A means “not applicable”.

#### Data Rate Used:

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

| Test Items                                                                                                                                                                                   | Mode                             | Data Rate |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|-----------|
| Maximum Conducted Output Power<br>Power Spectral Density<br>Emission Bandwidth(26dBm Bandwidth)<br>Minimum Emission Bandwidth(6dBm Bandwidth)<br>Undesirable emission<br>Frequency Stability | 11a/OFDM                         | 6 Mbps    |
|                                                                                                                                                                                              | 11n HT20,11ac VHT20,ax HE20/OFDM | 7.2 Mbps  |
|                                                                                                                                                                                              | 11n HT40,11ac VHT40,ax HE40/OFDM | 15.0Mbps  |
|                                                                                                                                                                                              | 11ac VHT80,ax HE80/OFDM          | 65.0Mbps  |

### 3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 “Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1” and TR-100028-02 “Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 “ and is documented in the Shenzhen GUOREN Certification Technology Service Co., Ltd.quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GUOREN Certification Technology Service Co., Ltd.:

| Test                   | Range       | Measurement Uncertainty | Notes |
|------------------------|-------------|-------------------------|-------|
| Radiated Emission      | 30~1000MHz  | 4.06 dB                 | (1)   |
| Radiated Emission      | 1~18GHz     | 5.14 dB                 | (1)   |
| Radiated Emission      | 18-40GHz    | 5.38 dB                 | (1)   |
| Conducted Disturbance  | 0.15~30MHz  | 2.14 dB                 | (1)   |
| Max output power       | 30MHz~18GHz | 0.54 dB                 | (1)   |
| Power spectral density | /           | 0.56 dB                 | (1)   |
| Spectrum bandwidth     | /           | 1.2%                    | (1)   |

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.


### 3.6 Equipments Used during the Test

| Test Equipment             | Manufacturer           | Model No.   | Equipment No. | Calibration Date | Calibration Due Date |
|----------------------------|------------------------|-------------|---------------|------------------|----------------------|
| LISN                       | R&S                    | ENV216      | GRCTEE009     | 2023/09/27       | 2024/09/26           |
| LISN                       | R&S                    | ENV216      | GRCTEE010     | 2023/09/27       | 2024/09/26           |
| EMI Test Receiver          | R&S                    | ESPI        | GRCTEE017     | 2023/09/28       | 2024/09/27           |
| EMI Test Receiver          | R&S                    | ESCI        | GRCTEE008     | 2023/09/27       | 2024/09/26           |
| Spectrum Analyzer          | Agilent                | N9020A      | GRCTEE002     | 2023/09/27       | 2024/09/26           |
| Spectrum Analyzer          | R&S                    | FSP         | GRCTEE003     | 2023/09/28       | 2024/09/27           |
| Vector Signal generator    | Agilent                | N5181A      | GRCTEE007     | 2023/09/27       | 2024/09/26           |
| Analog Signal Generator    | R&S                    | SML03       | GRCTEE006     | 2023/09/27       | 2024/09/26           |
| Climate Chamber            | QIYA                   | LCD-9530    | GRCTES016     | 2023/09/27       | 2024/09/26           |
| Ultra-Broadband Antenna    | Schwarzbeck            | VULB9163    | GRCTEE018     | 2023/09/28       | 2026/09/27           |
| Horn Antenna               | Schwarzbeck            | BBHA 9120D  | GRCTEE019     | 2023/09/28       | 2026/09/27           |
| Loop Antenna               | Zhinan                 | ZN30900C    | GRCTEE020     | 2023/10/15       | 2026/10/14           |
| Horn Antenna               | Beijing Hangwei Dayang | OBH100400   | GRCTEE049     | 2023/09/28       | 2026/09/27           |
| Amplifier                  | Schwarzbeck            | BBV 9745    | GRCTEE021     | 2023/09/27       | 2024/09/26           |
| Amplifier                  | Taiwan chengyi         | EMC051845B  | GRCTEE022     | 2023/09/28       | 2024/09/27           |
| Temperature/Humidity Meter | Huaguan                | HG-308      | GRCTES037     | 2023/09/27       | 2024/09/26           |
| Directional coupler        | NARDA                  | 4226-10     | GRCTEE004     | 2023/09/27       | 2024/09/26           |
| High-Pass Filter           | XingBo                 | XBLBQ-GTA18 | GRCTEE053     | 2023/09/27       | 2024/09/26           |
| High-Pass Filter           | XingBo                 | XBLBQ-GTA27 | GRCTEE054     | 2023/09/27       | 2024/09/26           |
| Automated filter bank      | Tonscend               | JS0806-F    | GRCTEE055     | 2023/09/27       | 2024/09/26           |
| Power Sensor               | Agilent                | U2021XA     | GRCTEE070     | 2023/09/27       | 2024/09/26           |
| EMI Test Software          | ROHDE & SCHWARZ        | ESK1-V1.71  | GRCTEE060     | N/A              | N/A                  |
| EMI Test Software          | Fera                   | EZ-EMC      | GRCTEE061     | N/A              | N/A                  |

## 4 TEST CONDITIONS AND RESULTS

### 4.1 AC Power Conducted Emission

#### TEST CONFIGURATION



#### TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

#### AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following:

| Frequency range (MHz) | Limit (dBuV) |           |
|-----------------------|--------------|-----------|
|                       | Quasi-peak   | Average   |
| 0.15-0.5              | 66 to 56*    | 56 to 46* |
| 0.5-5                 | 56           | 46        |
| 5-30                  | 60           | 50        |

\* Decreases with the logarithm of the frequency.

#### TEST RESULTS

Remark:


1. All modes of 802.11a/ 802.11ac VHT20/802.11ac VHT40/802.11ac VHT80/ 802.11ax HE20/ 802.11ax HE40/802.11ax HE80/ 802.11n HT20/ 802.11n HT40 were tested at Low, Middle, and High channel; only the worst result of 802.11n HT20 CH36 was reported as below:
2. Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:

Power supply:

DC 24V from Adapter AC  
120V/60Hz

Polarization

L

**MEASUREMENT RESULT: "GRCT24731010\_fin"**

7/31/2024 11:06AM

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.198000         | 56.70         | 9.5          | 64            | 7.0          | QP       | L1   | GND |
| 0.494000         | 37.20         | 9.7          | 56            | 18.9         | QP       | L1   | GND |
| 1.074000         | 23.60         | 10.0         | 56            | 32.4         | QP       | L1   | GND |
| 2.574000         | 21.00         | 10.0         | 56            | 35.0         | QP       | L1   | GND |
| 7.706000         | 21.10         | 10.0         | 60            | 38.9         | QP       | L1   | GND |
| 18.014000        | 20.60         | 10.1         | 60            | 39.4         | QP       | L1   | GND |

**MEASUREMENT RESULT: "GRCT24731010\_fin2"**

7/31/2024 11:06AM

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.290000         | 35.90         | 9.6          | 51            | 14.6         | AV       | L1   | GND |
| 0.494000         | 24.70         | 9.7          | 46            | 21.4         | AV       | L1   | GND |
| 0.862000         | 17.80         | 9.7          | 46            | 28.2         | AV       | L1   | GND |
| 2.234000         | 14.00         | 10.0         | 46            | 32.0         | AV       | L1   | GND |
| 9.978000         | 17.20         | 10.0         | 50            | 32.8         | AV       | L1   | GND |
| 24.578000        | 24.10         | 10.2         | 50            | 25.9         | AV       | L1   | GND |

Note:1).Level (dBμV)= Reading (dBμV)+ Transducer (dB)

2). Transducer (dB)=insertion loss of LISN (dB) + Cable loss (dB)


3). Margin(dB) = Limit (dBμV) - Level (dBμV)

Power supply:

DC 24V from Adapter AC  
120V/60Hz

Polarization

N



MEASUREMENT RESULT: "GRCT24731009\_fin"

7/31/2024 11:01AM

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.206000         | 58.30         | 9.6          | 63            | 5.1          | QP       | N    | GND |
| 0.438000         | 42.10         | 9.8          | 57            | 15.0         | QP       | N    | GND |
| 1.078000         | 31.70         | 10.0         | 56            | 24.3         | QP       | N    | GND |
| 2.478000         | 25.60         | 10.0         | 56            | 30.4         | QP       | N    | GND |
| 9.030000         | 21.30         | 10.0         | 60            | 38.7         | QP       | N    | GND |
| 21.214000        | 30.50         | 10.2         | 60            | 29.5         | QP       | N    | GND |

MEASUREMENT RESULT: "GRCT24731009\_fin2"

7/31/2024 11:01AM

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.170000         | 48.20         | 9.5          | 55            | 6.8          | AV       | N    | GND |
| 0.470000         | 28.00         | 9.7          | 47            | 18.5         | AV       | N    | GND |
| 1.382000         | 20.50         | 10.0         | 46            | 25.5         | AV       | N    | GND |
| 2.130000         | 18.40         | 10.0         | 46            | 27.6         | AV       | N    | GND |
| 10.390000        | 18.10         | 10.0         | 50            | 31.9         | AV       | N    | GND |
| 24.578000        | 24.30         | 10.2         | 50            | 25.7         | AV       | N    | GND |

- Note:1).Level (dBμV)= Reading (dBμV)+ Transducer (dB)  
2). Transducer (dB)=insertion loss of LISN (dB) + Cable loss (dB)  
3). Margin(dB) = Limit (dBμV) - Level (dBμV)

## 4.2 Radiated Emissions

### Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

### Undesirable emission limits

| Requirement  | Limit(EIRP)     | Limit (Field strength at 3m) <sup>Note1</sup> |
|--------------|-----------------|-----------------------------------------------|
| 15.407(b)(1) | PK:-27(dBm/MHz) | PK:68.2(dBμV/m)                               |
| 15.407(b)(2) |                 |                                               |
| 15.407(b)(3) |                 |                                               |
| 15.407(b)(4) |                 |                                               |

Note1: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$


- (5) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209
- (6) In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

### Radiated emission limits


| Frequency (MHz) | Distance (Meters) | Radiated (dBμV/m)                | Radiated (μV/m) |
|-----------------|-------------------|----------------------------------|-----------------|
| 0.009-0.49      | 3                 | 20log(2400/F(KHz))+40log(300/3)  | 2400/F(KHz)     |
| 0.49-1.705      | 3                 | 20log(24000/F(KHz))+ 40log(30/3) | 24000/F(KHz)    |
| 1.705-30        | 3                 | 20log(30)+ 40log(30/3)           | 30              |
| 30-88           | 3                 | 40.0                             | 100             |
| 88-216          | 3                 | 43.5                             | 150             |
| 216-960         | 3                 | 46.0                             | 200             |
| Above 960       | 3                 | 54.0                             | 500             |

**TEST CONFIGURATION**


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



**Test Procedure**

- Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
- Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
- And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- Repeat above procedures until all frequency measurements have been completed.
- Radiated emission test frequency band from 9KHz to 40GHz.
- The distance between test antenna and EUT as following table states:

| Test Frequency range | Test Antenna Type   | Test Distance |
|----------------------|---------------------|---------------|
| 9KHz-30MHz           | Active Loop Antenna | 3             |
| 30MHz-1GHz           | Bilog Antenna       | 3             |
| 1GHz-18GHz           | Horn Antenna        | 3             |
| 18GHz-25GHz          | Horn Antenna        | 1             |

- Setting test receiver/spectrum as following table states:

| Test Frequency range | Test Receiver/Spectrum Setting                                                                            | Detector |
|----------------------|-----------------------------------------------------------------------------------------------------------|----------|
| 9KHz-150KHz          | RBW=200Hz/VBW=3KHz, Sweep time=Auto                                                                       | QP       |
| 150KHz-30MHz         | RBW=9KHz/VBW=100KHz, Sweep time=Auto                                                                      | QP       |
| 30MHz-1GHz           | RBW=120KHz/VBW=1000KHz, Sweep time=Auto                                                                   | QP       |
| 1GHz-40GHz           | Peak Value: RBW=1MHz/VBW=3MHz,<br>Sweep time=Auto<br>Average Value: RBW=1MHz/VBW=10Hz,<br>Sweep time=Auto | Peak     |

**TEST RESULTS**


Remark:

- This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
- All 802.11a/ 802.11ac VHT20/802.11ac VHT40/802.11ac VHT80/ 802.11ax HE20/ 802.11ax HE40/ 802.11ax HE80/ 802.11n HT20/ 802.11n HT40 modes have been tested for below 1GHz test, only the worst case 802.11n HT20 low channel of U-NII 1 band was recorded.
- All 802.11a/ 802.11ac VHT20/802.11ac VHT40/802.11ac VHT80/ 802.11ax HE20/ 802.11ax HE40/ 802.11ax HE80/ 802.11n HT20/ 802.11n HT40 modes have been tested for above 1GHz test, only the worst case 802.11n HT20 was recorded.
- Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.



## For 30MHz-1GHz

Horizontal



Site LAB

Limit: FCC Part15 RE-Class B\_30-1000MHz

EUT: Smart Projector

M/N: J92-5D5

Mode: 802.11n (HT20) CH 36

Note: N/A

Polarization: *Horizontal*

Power: AC120V/60Hz

Distance: 3m

Temperature: 23(C)

Humidity: 51 %


| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Level (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Detector | Height (cm) | Azimuth (deg.) | P/F | Remark |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-------------|----------------|-----|--------|
| 1   | 51.1209         | 34.98          | -17.53        | 17.45          | 40.00          | -22.55      | peak     | 200         | 7              | P   |        |
| 2 ! | 83.8156         | 56.09          | -21.97        | 34.12          | 40.00          | -5.88       | peak     | 200         | 357            | P   |        |
| 3   | 156.4578        | 53.74          | -21.90        | 31.84          | 43.50          | -11.66      | peak     | 200         | 61             | P   |        |
| 4 * | 296.1836        | 57.39          | -17.08        | 40.31          | 46.00          | -5.69       | peak     | 100         | 66             | P   |        |
| 5   | 394.8545        | 45.91          | -15.79        | 30.12          | 46.00          | -15.88      | peak     | 100         | 316            | P   |        |

Note:1).Level (dBμV/m)= Reading (dBμV)+ Factor (dB/m)

2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin(dB) = Level (dBμV/m) - Limit (dBμV/m)

## Vertical



Site LAB

Polarization: *Vertical*

Temperature: 23(C)

Limit: FCC Part15 RE-Class B\_30-1000MHz

Power: AC120V/60Hz

Humidity: 51 %

EUT: Smart Projector

Distance: 3m

M/N: J92-5D5

Mode: 802.11n (HT20) CH 36

Note: N/A

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Azimuth (deg.) | P/F | Remark |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-------------|----------------|-----|--------|
| 1   | 43.2014         | 49.39          | -17.67        | 31.72          | 40.00          | -8.28       | peak     | 100         | 48             | P   |        |
| 2   | 55.2207         | 49.10          | -17.83        | 31.27          | 40.00          | -8.73       | peak     | 100         | 123            | P   |        |
| 3 * | 83.8155         | 58.44          | -21.97        | 36.47          | 40.00          | -3.53       | peak     | 100         | 96             | P   |        |
| 4   | 114.9167        | 55.73          | -19.75        | 35.98          | 43.50          | -7.52       | peak     | 100         | 325            | P   |        |
| 5   | 226.8935        | 50.30          | -18.62        | 31.68          | 46.00          | -14.32      | peak     | 100         | 78             | P   |        |
| 6   | 296.1836        | 50.75          | -17.08        | 33.67          | 46.00          | -12.33      | peak     | 100         | 111            | P   |        |

Note:1).Level (dBuV/m)= Reading (dBuV)+ Factor (dB/m)

2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin(dB) = Level (dBuV/m) - Limit (dBuV/m)

**For 1GHz to 40GHz**

### U-NII 1 & 802.11n HT20 Mode (above 1GHz)

[illegible][illegible]

**U-NII 3 & 802.11n HT20 Mode (above 1GHz)**

| Tested    | Frequency | Emission | Detector | ANT | Limit    | Margin | Raw    | Antenna | Cable  | Pre       | Correction |
|-----------|-----------|----------|----------|-----|----------|--------|--------|---------|--------|-----------|------------|
| Channel   | (MHz)     | Level    | Mode     | Pol | (dBuV/m) | (dB)   | Value  | Factor  | Factor | amplifier | Factor     |
|           |           | (dBuV/m) |          |     |          |        | (dBuV) | (dB/m)  | (dB)   | (dB)      | (dB/m)     |
|           | 5650.00   | 51.54    | PK       | H   | 68.30    | 16.76  | 69.9   | 30.54   | 5.74   | 54.64     | -18.36     |
|           | 5700.00   | 51.78    | PK       | H   | 105.30   | 53.52  | 70     | 30.61   | 5.83   | 54.66     | -18.22     |
| 149.00    | 5720.00   | 52.24    | PK       | H   | 110.90   | 58.66  | 70.11  | 30.82   | 6.02   | 54.71     | -17.87     |
|           | 5725.00   | 51.54    | PK       | H   | 122.30   | 70.76  | 69.39  | 30.83   | 6.05   | 54.73     | -17.85     |
| (5745MHz) | 11490.00  | 50.12    | PK       | H   | 68.20    | 18.08  | 54.87  | 39.23   | 10.83  | 54.81     | -4.75      |
|           | --        | --       | --       | --  | --       | --     | --     | --      | --     | --        | --         |
| 157.00    | 11570.00  | 51.09    | PK       | H   | 68.20    | 17.11  | 55.54  | 39.34   | 10.96  | 54.75     | -4.45      |
| (5785MHz) | --        | --       | --       | --  | --       | --     | --     | --      | --     | --        | --         |
|           | 5850.00   | 51.54    | PK       | H   | 122.30   | 70.76  | 69.26  | 30.85   | 6.08   | 54.65     | -17.72     |
| 165.00    | 5855.00   | 51.45    | PK       | H   | 110.90   | 59.45  | 69.16  | 30.87   | 6.10   | 54.68     | -17.71     |
|           | 5875.00   | 52.57    | PK       | H   | 105.30   | 52.73  | 70.26  | 30.90   | 6.13   | 54.72     | -17.69     |
|           | 5925.00   | 50.78    | PK       | H   | 68.30    | 17.52  | 68.32  | 30.94   | 6.15   | 54.63     | -17.54     |
| (5825MHz) | 11650.00  | 51.41    | PK       | H   | 68.20    | 16.79  | 55.12  | 39.42   | 11.15  | 54.28     | -3.71      |
|           | --        | --       | --       | --  | --       | --     | --     | --      | --     | --        | --         |

| Tested    | Frequency | Emission | Detector | ANT | Limit    | Margin | Raw    | Antenna | Cable  | Pre       | Correction |
|-----------|-----------|----------|----------|-----|----------|--------|--------|---------|--------|-----------|------------|
| Channel   | (MHz)     | Level    | Mode     | Pol | (dBuV/m) | (dB)   | Value  | Factor  | Factor | amplifier | Factor     |
|           |           | (dBuV/m) |          |     |          |        | (dBuV) | (dB/m)  | (dB)   | (dB)      | (dB/m)     |
|           | 5650.00   | 51.45    | PK       | V   | 68.30    | 16.85  | 69.81  | 30.54   | 5.74   | 54.64     | -18.36     |
|           | 5700.00   | 52.08    | PK       | V   | 105.30   | 53.22  | 70.30  | 30.61   | 5.83   | 54.66     | -18.22     |
| 149.00    | 5720.00   | 51.37    | PK       | V   | 110.90   | 59.53  | 69.24  | 30.82   | 6.02   | 54.71     | -17.87     |
|           | 5725.00   | 51.81    | PK       | V   | 122.30   | 70.49  | 69.66  | 30.83   | 6.05   | 54.73     | -17.85     |
| (5745MHz) | 11490.00  | 51.71    | PK       | V   | 68.20    | 16.49  | 56.46  | 39.23   | 10.83  | 54.81     | -4.75      |
|           | --        | --       | --       | --  | --       | --     | --     | --      | --     | --        | --         |
| 157.00    | 11570.00  | 51.25    | PK       | V   | 68.20    | 16.95  | 55.70  | 39.34   | 10.96  | 54.75     | -4.45      |
| (5785MHz) | --        | --       | --       | --  | --       | --     | --     | --      | --     | --        | --         |
|           | 5850.00   | 52.68    | PK       | V   | 122.30   | 69.62  | 70.40  | 30.85   | 6.08   | 54.65     | -17.72     |
| 165.00    | 5855.00   | 51.46    | PK       | V   | 110.90   | 59.44  | 69.17  | 30.87   | 6.10   | 54.68     | -17.71     |
|           | 5875.00   | 51.57    | PK       | V   | 105.30   | 53.73  | 69.26  | 30.90   | 6.13   | 54.72     | -17.69     |
|           | 5925.00   | 50.36    | PK       | V   | 68.20    | 17.84  | 67.90  | 30.94   | 6.15   | 54.63     | -17.54     |
| (5825MHz) | 11650.00  | 51.22    | PK       | V   | 68.20    | 16.98  | 54.93  | 39.42   | 11.15  | 54.28     | -3.71      |
|           | --        | --       | --       | --  | --       | --     | --     | --      | --     | --        | --         |

**REMARKS:**

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the other emission levels were very low against the limit.
5. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.
6. Worst case data at 6Mbps at IEEE 802.11a, MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11ac VHT20 ,IEEE 802.11ac VHT40,IEEE 802.11ac VHT80, IEEE 802.11ax HE20 ,IEEE 802.11ax HE40 and IEEE 802.11ax HE80.

### 4.3 Maximum Conducted Average Output Power

#### Limit

##### **For the band 5.15-5.25 GHz.**

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.


**For the 5.25-5.35 GHz and 5.47-5.725 GHz bands**, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz.

**For the band 5.725-5.85 GHz**, the maximum conducted output power over the frequency band of operation shall not exceed 1 W

#### Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

#### Test Configuration



**Test Results****Ant 1****U-NII 1**

| Type           | Channel | Output power (dBm) | Limit (dBm) | Result |
|----------------|---------|--------------------|-------------|--------|
| 802.11a        | 36      | 11.18              | 23.98       | Pass   |
|                | 40      | 10.83              |             |        |
|                | 48      | 11.80              |             |        |
| 802.11n HT20   | 36      | 10.75              | 23.98       | Pass   |
|                | 40      | 10.24              |             |        |
|                | 48      | 11.20              |             |        |
| 802.11n HT40   | 38      | 10.65              | 23.98       | Pass   |
|                | 46      | 11.23              |             |        |
| 802.11ac VHT20 | 36      | 10.79              | 23.98       | Pass   |
|                | 40      | 10.26              |             |        |
|                | 48      | 11.15              |             |        |
| 802.11ac VHT40 | 38      | 10.65              | 23.98       | Pass   |
|                | 46      | 11.19              |             |        |
| 802.11ac VHT80 | 42      | 9.48               | 23.98       | Pass   |
| 802.11ax HE20  | 36      | 11.42              | 23.98       | Pass   |
|                | 40      | 10.97              |             |        |
|                | 48      | 11.87              |             |        |
| 802.11ax HE40  | 38      | 10.82              | 23.98       | Pass   |
|                | 46      | 10.35              |             |        |
| 802.11ax HE80  | 42      | 8.77               | 23.98       | Pass   |

## U-NII 3

| Type           | Channel | Output power (dBm) | Limit (dBm) | Result |
|----------------|---------|--------------------|-------------|--------|
| 802.11a        | 149     | 11.21              | 30.00       | Pass   |
|                | 157     | 10.75              |             |        |
|                | 165     | 11.57              |             |        |
| 802.11n HT20   | 149     | 10.60              | 30.00       | Pass   |
|                | 157     | 10.13              |             |        |
|                | 165     | 10.95              |             |        |
| 802.11n HT40   | 151     | 10.36              | 30.00       | Pass   |
|                | 159     | 10.43              |             |        |
| 802.11ac VHT20 | 149     | 10.57              | 30.00       | Pass   |
|                | 157     | 10.04              |             |        |
|                | 165     | 10.93              |             |        |
| 802.11ac VHT40 | 151     | 10.35              | 30.00       | Pass   |
|                | 159     | 10.40              |             |        |
| 802.11ac VHT80 | 155     | 9.76               | 30.00       | Pass   |
| 802.11ax HE20  | 149     | 11.37              | 30.00       | Pass   |
|                | 157     | 10.86              |             |        |
|                | 165     | 11.71              |             |        |
| 802.11ax HE40  | 151     | 9.54               | 30.00       | Pass   |
|                | 159     | 9.65               |             |        |
| 802.11ax HE80  | 155     | 8.15               | 30.00       | Pass   |

**Ant 2****U-NII 1**

| Type           | Channel | Output power (dBm) | Limit (dBm) | Result |
|----------------|---------|--------------------|-------------|--------|
| 802.11a        | 36      | 11.67              | 23.98       | Pass   |
|                | 40      | 11.78              |             |        |
|                | 48      | 10.00              |             |        |
| 802.11n HT20   | 36      | 11.13              | 23.98       | Pass   |
|                | 40      | 11.20              |             |        |
|                | 48      | 10.34              |             |        |
| 802.11n HT40   | 38      | 11.02              | 23.98       | Pass   |
|                | 46      | 10.58              |             |        |
| 802.11ac VHT20 | 36      | 11.09              | 23.98       | Pass   |
|                | 40      | 11.22              |             |        |
|                | 48      | 10.34              |             |        |
| 802.11ac VHT40 | 38      | 11.95              | 23.98       | Pass   |
|                | 46      | 10.44              |             |        |
| 802.11ac VHT80 | 42      | 8.71               | 23.98       | Pass   |
| 802.11ax HE20  | 36      | 11.79              | 23.98       | Pass   |
|                | 40      | 12.07              |             |        |
|                | 48      | 11.15              |             |        |
| 802.11ax HE40  | 38      | 10.18              | 23.98       | Pass   |
|                | 46      | 10.69              |             |        |
| 802.11ax HE80  | 42      | 7.75               | 23.98       | Pass   |



## U-NII 3

| Type           | Channel | Output power (dBm) | Limit (dBm) | Result |
|----------------|---------|--------------------|-------------|--------|
| 802.11a        | 149     | 12.85              | 30.00       | Pass   |
|                | 157     | 12.31              |             |        |
|                | 165     | 12.25              |             |        |
| 802.11n HT20   | 149     | 11.18              | 30.00       | Pass   |
|                | 157     | 10.69              |             |        |
|                | 165     | 10.60              |             |        |
| 802.11n HT40   | 151     | 11.56              | 30.00       | Pass   |
|                | 159     | 11.22              |             |        |
| 802.11ac VHT20 | 149     | 11.17              | 30.00       | Pass   |
|                | 157     | 10.63              |             |        |
|                | 165     | 10.54              |             |        |
| 802.11ac VHT40 | 151     | 11.53              | 30.00       | Pass   |
|                | 159     | 11.10              |             |        |
| 802.11ac VHT80 | 155     | 9.31               | 30.00       | Pass   |
| 802.11ax HE20  | 149     | 12.87              | 30.00       | Pass   |
|                | 157     | 12.28              |             |        |
|                | 165     | 11.76              |             |        |
| 802.11ax HE40  | 151     | 10.59              | 30.00       | Pass   |
|                | 159     | 10.14              |             |        |
| 802.11ax HE80  | 155     | 8.37               | 30.00       | Pass   |

**MIMO****U-NII 1**

| Type           | Channel | Output power<br>Ant 1(dBm) | Output power<br>Ant 2(dBm) | Output power<br>MIMO(dBm) | Limit (dBm) | Result |
|----------------|---------|----------------------------|----------------------------|---------------------------|-------------|--------|
| 802.11n HT20   | 36      | 10.75                      | 11.13                      | 13.95                     | 23.98       | Pass   |
|                | 40      | 10.24                      | 11.20                      | 13.76                     |             |        |
|                | 48      | 11.20                      | 10.34                      | 13.80                     |             |        |
| 802.11n HT40   | 38      | 10.65                      | 11.02                      | 13.85                     | 23.98       | Pass   |
|                | 46      | 11.23                      | 10.58                      | 13.93                     |             |        |
| 802.11ac VHT20 | 36      | 10.79                      | 11.09                      | 13.95                     | 23.98       | Pass   |
|                | 40      | 10.26                      | 11.22                      | 13.78                     |             |        |
|                | 48      | 11.15                      | 10.34                      | 13.77                     |             |        |
| 802.11ac VHT40 | 38      | 10.65                      | 11.95                      | 14.36                     | 23.98       | Pass   |
|                | 46      | 11.19                      | 10.44                      | 13.84                     |             |        |
| 802.11ac VHT80 | 42      | 9.48                       | 8.71                       | 12.12                     | 23.98       | Pass   |
| 802.11ax HE20  | 36      | 11.42                      | 11.79                      | 14.62                     | 23.98       | Pass   |
|                | 40      | 10.97                      | 12.07                      | 14.57                     |             |        |
|                | 48      | 11.87                      | 11.15                      | 14.54                     |             |        |
| 802.11ax HE40  | 38      | 10.82                      | 10.18                      | 13.52                     | 23.98       | Pass   |
|                | 46      | 10.35                      | 10.69                      | 13.53                     |             |        |
| 802.11ax HE80  | 42      | 8.77                       | 7.75                       | 11.30                     | 23.98       | Pass   |

## U-NII 3

| Type           | Channel | Output power<br>Ant 1(dBm) | Output power<br>Ant 2(dBm) | Output power<br>MIMO(dBm) | Limit (dBm) | Result |
|----------------|---------|----------------------------|----------------------------|---------------------------|-------------|--------|
| 802.11n HT20   | 149     | 10.60                      | 11.18                      | 13.91                     | 30          | Pass   |
|                | 157     | 10.13                      | 10.69                      | 13.43                     |             |        |
|                | 165     | 10.95                      | 10.60                      | 13.79                     |             |        |
| 802.11n HT40   | 151     | 10.36                      | 11.56                      | 14.01                     | 30          | Pass   |
|                | 159     | 10.43                      | 11.22                      | 13.85                     |             |        |
| 802.11ac VHT20 | 149     | 10.57                      | 11.17                      | 13.89                     | 30          | Pass   |
|                | 157     | 10.04                      | 10.63                      | 13.36                     |             |        |
|                | 165     | 10.93                      | 10.54                      | 13.75                     |             |        |
| 802.11ac VHT40 | 151     | 10.35                      | 11.53                      | 13.99                     | 30          | Pass   |
|                | 159     | 10.40                      | 11.10                      | 13.77                     |             |        |
| 802.11ac VHT80 | 155     | 9.76                       | 9.31                       | 12.55                     | 30          | Pass   |
| 802.11ax HE20  | 149     | 11.37                      | 12.87                      | 15.19                     | 30          | Pass   |
|                | 157     | 10.86                      | 12.28                      | 14.64                     |             |        |
|                | 165     | 11.71                      | 11.76                      | 14.75                     |             |        |
| 802.11ax HE40  | 151     | 9.54                       | 10.59                      | 13.11                     | 30          | Pass   |
|                | 159     | 9.65                       | 10.14                      | 12.91                     |             |        |
| 802.11ax HE80  | 155     | 8.15                       | 8.37                       | 11.27                     | 30          | Pass   |

## 4.4 Power Spectral Density

### Limit

(1) For the band 5.15 - 5.25 GHz.

(i) For an outdoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band.<sup>note1</sup>

(ii) For an indoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band.<sup>note1</sup>

(iii) For fixed point-to-point access points operating in the band 5.15 - 5.25 GHz, transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi.

(iv) For mobile and portable client devices in the 5.15 - 5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 MHz band.<sup>note1</sup>

(2) For the 5.25 - 5.35 GHz and 5.47 - 5.725 GHz bands, the peak power spectral density shall not exceed 11 dBm in any 1 MHz band.<sup>note1</sup>

(3) For the band 5.725 - 5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500 kHz band.<sup>note1, note2</sup>

Note1: If transmitting antennas of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note2: Fixed point - to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information.

### Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW = 1MHz for U-NII 1, U-NII 2A, U-NII C band and 300KHz for U-NII 3 band.
3. Set the VBW  $\geq 3 \times$  RBW.
4. Set the span to encompass the entire EBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.

### Test Configuration



**Test Results****Ant 1**

| Type              | Bands   | Channel | Power Spectral Density<br>(dBm/MHz) | Limit<br>(dBm/MHz) | Result |
|-------------------|---------|---------|-------------------------------------|--------------------|--------|
| 802.11a           | U-NII 1 | 36      | 0.80                                | 11                 | Pass   |
|                   |         | 40      | 0.38                                |                    |        |
|                   |         | 48      | 1.84                                |                    |        |
| 802.11n<br>HT20   | U-NII 1 | 36      | 0.25                                |                    |        |
|                   |         | 40      | -0.38                               |                    |        |
|                   |         | 48      | 0.74                                |                    |        |
| 802.11n<br>HT40   | U-NII 1 | 38      | -1.97                               |                    |        |
|                   |         | 46      | -1.24                               |                    |        |
| 802.11ac<br>VHT20 | U-NII 1 | 36      | 0.31                                |                    |        |
|                   |         | 40      | -0.43                               |                    |        |
|                   |         | 48      | 0.88                                |                    |        |
| 802.11ac<br>VHT40 | U-NII 1 | 38      | -1.93                               |                    |        |
|                   |         | 46      | -1.30                               |                    |        |
| 802.11ac<br>VHT80 | U-NII 1 | 42      | -5.47                               |                    |        |
| 802.11ax<br>HE20  | U-NII 1 | 36      | 1.06                                |                    |        |
|                   |         | 40      | -0.08                               |                    |        |
|                   |         | 48      | 1.28                                |                    |        |
| 802.11ax<br>HE40  | U-NII 1 | 38      | -1.27                               |                    |        |
|                   |         | 46      | -1.23                               |                    |        |
| 802.11ax<br>HE80  | U-NII 1 | 42      | -5.05                               |                    |        |

| Type           | Bands   | Channel | Power Spectral Density (dBm/300KHz) | Power Spectral Density (dBm/500KHz) | Limit (dBm/500KHz) | Result |
|----------------|---------|---------|-------------------------------------|-------------------------------------|--------------------|--------|
| 802.11a        | U-NII 3 | 149     | -1.98                               | 0.238                               | 30                 | Pass   |
|                |         | 157     | -2.44                               | -0.222                              |                    |        |
|                |         | 165     | -1.61                               | 0.608                               |                    |        |
| 802.11n HT20   | U-NII 3 | 149     | -2.85                               | -0.632                              |                    |        |
|                |         | 157     | -2.91                               | -0.692                              |                    |        |
|                |         | 165     | -2.49                               | -0.272                              |                    |        |
| 802.11n HT40   | U-NII 3 | 151     | -5.57                               | -3.352                              |                    |        |
|                |         | 159     | -5.36                               | -3.142                              |                    |        |
| 802.11ac VHT20 | U-NII 3 | 149     | -2.69                               | -0.472                              |                    |        |
|                |         | 157     | -3.29                               | -1.072                              |                    |        |
|                |         | 165     | -2.40                               | -0.182                              |                    |        |
| 802.11ac VHT40 | U-NII 3 | 151     | -5.16                               | -2.942                              |                    |        |
|                |         | 159     | -4.92                               | -2.702                              |                    |        |
| 802.11ac VHT80 | U-NII 3 | 155     | -9.12                               | -6.902                              |                    |        |
| 802.11ax HE20  | U-NII 3 | 149     | -1.76                               | 0.458                               |                    |        |
|                |         | 157     | -2.96                               | -0.742                              |                    |        |
|                |         | 165     | -1.95                               | 0.268                               |                    |        |
| 802.11ax HE40  | U-NII 3 | 151     | -4.04                               | -1.822                              |                    |        |
|                |         | 159     | -3.73                               | -1.512                              |                    |        |
| 802.11ax HE80  | U-NII 3 | 155     | -7.19                               | -4.972                              |                    |        |

Remark:  $P.S.D(dBm/500KHz) = P.S.D(dBm/300KHz) + 10 \log(500 \text{ kHz}/300KHz)$ .

**Ant 2**

| Type              | Bands   | Channel | Power Spectral Density<br>(dBm/MHz) | Limit<br>(dBm/MHz) | Result |
|-------------------|---------|---------|-------------------------------------|--------------------|--------|
| 802.11a           | U-NII 1 | 36      | 1.40                                | 11                 | Pass   |
|                   |         | 40      | 1.42                                |                    |        |
|                   |         | 48      | -0.27                               |                    |        |
| 802.11n<br>HT20   | U-NII 1 | 36      | 0.54                                |                    |        |
|                   |         | 40      | 0.64                                |                    |        |
|                   |         | 48      | -1.12                               |                    |        |
| 802.11n<br>HT40   | U-NII 1 | 38      | -0.61                               |                    |        |
|                   |         | 46      | -2.12                               |                    |        |
| 802.11ac<br>VHT20 | U-NII 1 | 36      | 0.47                                |                    |        |
|                   |         | 40      | 0.62                                |                    |        |
|                   |         | 48      | -1.17                               |                    |        |
| 802.11ac<br>VHT40 | U-NII 1 | 38      | -0.57                               |                    |        |
|                   |         | 46      | -2.27                               |                    |        |
| 802.11ac<br>VHT80 | U-NII 1 | 42      | -4.88                               |                    |        |
| 802.11ax<br>HE20  | U-NII 1 | 36      | 0.78                                |                    |        |
|                   |         | 40      | 1.38                                |                    |        |
|                   |         | 48      | -0.65                               |                    |        |
| 802.11ax<br>HE40  | U-NII 1 | 38      | -1.31                               |                    |        |
|                   |         | 46      | -3.30                               |                    |        |
| 802.11ax<br>HE80  | U-NII 1 | 42      | -5.97                               |                    |        |

| Type           | Bands   | Channel | Power Spectral Density (dBm/300KHz) | Power Spectral Density (dBm/500KHz) | Limit (dBm/500KHz) | Result |
|----------------|---------|---------|-------------------------------------|-------------------------------------|--------------------|--------|
| 802.11a        | U-NII 3 | 149     | -0.38                               | 1.838                               | 30                 | Pass   |
|                |         | 157     | -0.89                               | 1.328                               |                    |        |
|                |         | 165     | -1.20                               | 1.018                               |                    |        |
| 802.11n HT20   | U-NII 3 | 149     | -2.12                               | 0.098                               |                    |        |
|                |         | 157     | -2.65                               | -0.432                              |                    |        |
|                |         | 165     | -2.84                               | -0.622                              |                    |        |
| 802.11n HT40   | U-NII 3 | 151     | -3.79                               | -1.572                              |                    |        |
|                |         | 159     | -4.40                               | -2.182                              |                    |        |
| 802.11ac VHT20 | U-NII 3 | 149     | -2.34                               | -0.122                              |                    |        |
|                |         | 157     | -2.71                               | -0.492                              |                    |        |
|                |         | 165     | -3.12                               | -0.902                              |                    |        |
| 802.11ac VHT40 | U-NII 3 | 151     | -4.08                               | -1.862                              |                    |        |
|                |         | 159     | -4.59                               | -2.372                              |                    |        |
| 802.11ac VHT80 | U-NII 3 | 155     | -8.27                               | -6.052                              |                    |        |
| 802.11ax HE20  | U-NII 3 | 149     | -0.77                               | 1.448                               |                    |        |
|                |         | 157     | -1.48                               | 0.738                               |                    |        |
|                |         | 165     | -1.65                               | 0.568                               |                    |        |
| 802.11ax HE40  | U-NII 3 | 151     | -2.95                               | -0.732                              |                    |        |
|                |         | 159     | -3.41                               | -1.192                              |                    |        |
| 802.11ax HE80  | U-NII 3 | 155     | -6.28                               | -4.062                              |                    |        |

Remark:  $P.S.D(dBm/500KHz) = P.S.D(dBm/300KHz) + 10 \log(500 \text{ kHz}/300KHz)$ .



**MIMO****U-NII 1**


| Type           | Channel | Power Spectral<br>Density<br>Ant 1<br>(dBm/MHz) | Power Spectral<br>Density<br>Ant 2<br>(dBm/MHz) | Power Spectral<br>Density<br>MIMO<br>(dBm/MHz) | Limit<br>(dBm/MHz) | Result |
|----------------|---------|-------------------------------------------------|-------------------------------------------------|------------------------------------------------|--------------------|--------|
| 802.11n HT20   | 36      | 0.25                                            | 0.54                                            | 3.41                                           | 11                 | Pass   |
|                | 40      | -0.38                                           | 0.64                                            | 3.17                                           |                    |        |
|                | 48      | 0.74                                            | -1.12                                           | 2.92                                           |                    |        |
| 802.11n HT40   | 38      | -1.97                                           | -0.61                                           | 1.77                                           |                    |        |
|                | 46      | -1.24                                           | -2.12                                           | 1.35                                           |                    |        |
| 802.11ac VHT20 | 36      | 0.31                                            | 0.47                                            | 3.40                                           |                    |        |
|                | 40      | -0.43                                           | 0.62                                            | 3.14                                           |                    |        |
|                | 48      | 0.88                                            | -1.17                                           | 2.99                                           |                    |        |
| 802.11ac VHT40 | 38      | -1.93                                           | -0.57                                           | 1.81                                           |                    |        |
|                | 46      | -1.30                                           | -2.27                                           | 1.25                                           |                    |        |
| 802.11ac VHT80 | 42      | -5.47                                           | -4.88                                           | -2.15                                          |                    |        |
| 802.11ax HE20  | 36      | 1.06                                            | 0.78                                            | 3.93                                           |                    |        |
|                | 40      | -0.08                                           | 1.38                                            | 3.72                                           |                    |        |
|                | 48      | 1.28                                            | -0.65                                           | 3.43                                           |                    |        |
| 802.11ax HE40  | 38      | -1.27                                           | -1.31                                           | 1.72                                           |                    |        |
|                | 46      | -1.23                                           | -3.30                                           | 0.87                                           |                    |        |
| 802.11ax HE80  | 42      | -5.05                                           | -5.97                                           | -2.48                                          |                    |        |

## U-NII 3


| Type           | Channel | Power Spectral Density Ant 1 (dBm/500KHz) | Power Spectral Density Ant 2 (dBm/500KHz) | Power Spectral Density MIMO (dBm/500KHz) | Limit (dBm/500KHz) | Result |
|----------------|---------|-------------------------------------------|-------------------------------------------|------------------------------------------|--------------------|--------|
| 802.11n HT20   | 149     | -0.632                                    | 0.098                                     | 2.76                                     | 30                 | Pass   |
|                | 157     | -0.692                                    | -0.432                                    | 2.45                                     |                    |        |
|                | 165     | -0.272                                    | -0.622                                    | 2.57                                     |                    |        |
| 802.11n HT40   | 151     | -3.352                                    | -1.572                                    | 0.64                                     |                    |        |
|                | 159     | -3.142                                    | -2.182                                    | 0.37                                     |                    |        |
| 802.11ac VHT20 | 149     | -0.472                                    | -0.122                                    | 2.72                                     |                    |        |
|                | 157     | -1.072                                    | -0.492                                    | 2.24                                     |                    |        |
|                | 165     | -0.182                                    | -0.902                                    | 2.48                                     |                    |        |
| 802.11ac VHT40 | 151     | -2.942                                    | -1.862                                    | 0.64                                     |                    |        |
|                | 159     | -2.702                                    | -2.372                                    | 0.48                                     |                    |        |
| 802.11ac VHT80 | 155     | -6.902                                    | -6.052                                    | -3.45                                    |                    |        |
| 802.11ax HE20  | 149     | 0.458                                     | 1.448                                     | 3.99                                     |                    |        |
|                | 157     | -0.742                                    | 0.738                                     | 3.07                                     |                    |        |
|                | 165     | 0.268                                     | 0.568                                     | 3.43                                     |                    |        |
| 802.11ax HE40  | 151     | -1.822                                    | -0.732                                    | 1.77                                     |                    |        |
|                | 159     | -1.512                                    | -1.192                                    | 1.66                                     |                    |        |
| 802.11ax HE80  | 155     | -4.972                                    | -4.062                                    | -1.48                                    |                    |        |

Test plot as follows


Ant 1




11A-Ant1-5180-PASS




11A-Ant1-5200-PASS




11A-Ant1-5240-PASS




11A-Ant1-5745-PASS



11A-Ant1-5785-PASS




11A-Ant1-5825-PASS



11N20SISO-Ant1-5180-PASS




11N20SISO-Ant1-5200-PASS



11N20SISO-Ant1-5240-PASS



11N20SISO-Ant1-5745-PASS




11N20SISO-Ant1-5785-PASS







11N20SISO-Ant1-5825-PASS




11N40SISO-Ant1-5190-PASS




11N40SISO-Ant1-5230-PASS



11N40SISO-Ant1-5755-PASS




11N40SISO-Ant1-5795-PASS




11AC20SISO-Ant1-5180-PASS






11AC20SISO-Ant1-5200-PASS



11AC20SISO-Ant1-5240-PASS




11AC20SISO-Ant1-5745-PASS




11AC20SISO-Ant1-5785-PASS




11AC20SISO-Ant1-5825-PASS




11AC40SISO-Ant1-5190-PASS



11AC40SISO-Ant1-5230-PASS




11AC40SISO-Ant1-5755-PASS




11AC40SISO-Ant1-5795-PASS







11AC80SISO-Ant1-5210-PASS




11AC80SISO-Ant1-5775-PASS




11AX20SISO-Ant1-5180-PASS




11AX20SISO-Ant1-5200-PASS




11AX20SISO-Ant1-5240-PASS




11AX20SISO-Ant1-5745-PASS



11AX20SISO-Ant1-5785-PASS




11AX20SISO-Ant1-5825-PASS




11AX40SISO-Ant1-5190-PASS






11AX40SISO-Ant1-5230-PASS



11AX40SISO-Ant1-5755-PASS



11AX40SISO-Ant1-5795-PASS



11AX80SISO-Ant1-5210-PASS



11AX80SISO-Ant1-5775-PASS