

FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID:SMCJMGO-G1

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: f is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

TEST RESULTS

BT:

1Mbps			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)
CH00	2402	1.48	30
CH39	2441	1.69	30
CH78	2480	1.52	30
2Mbps			
CH00	2402	0.72	20.96
CH39	2441	1.10	20.96
CH78	2480	0.93	20.96
3Mbps			
CH00	2402	0.67	20.96
CH39	2441	0.97	20.96
CH78	2480	0.88	20.96

BLE

Test Channel	Frequency (MHz)	Maximum Conducted Output Power(PK) (dBm)	LIMIT (dBm)
CH00	2402	-4.42	30
CH19	2440	-4.37	30
CH39	2480	-4.45	30

WIFI

TX 802.11b Mode				
Test Channel	Frequency (MHz)	Maximum Conducted Output Power(PK) (dBm)	Maximum Conducted Output Power(AV) (dBm)	LIMIT (dBm)
CH01	2412	15.53	12.71	30
CH06	2437	15.66	12.84	30
CH11	2462	15.64	12.82	30
TX 802.11g Mode				
CH01	2412	14.25	11.12	30
CH06	2437	14.27	11.14	30
CH11	2462	14.16	11.03	30
TX 802.11n-HT20 Mode				
CH01	2412	13.72	11.49	30
CH06	2437	13.71	11.48	30
CH11	2462	13.67	11.44	30
TX 802.11n-HT40 Mode				
CH03	2422	12.96	10.54	30
CH06	2437	12.89	10.47	30
CH09	2452	12.94	10.52	30

Mode	Range	Maximum peak output power (dBm)	Output power (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm ²)	Limit of Power Density (S) (mW/ cm ²)	Result
802.11b	11~13	13	19.95	1(1.26)	0.0050	1	Pass
802.11g	10~12	12	15.85	1(1.26)	0.0040	1	Pass
802.11n-HT20	10~12	12	15.85	1(1.26)	0.0040	1	Pass
802.11n-HT40	9~11	11	12.59	1(1.26)	0.0032	1	Pass
BT	0~2	2	1.58	1(1.26)	0.0004	1	Pass
BLE	-5~-3	-3	0.50	1(1.26)	0.0001	1	Pass

Frequency MHz	Range	Maximum peak output power (dBm)	Output power (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm ²)	Limit of Power Density (S) (mW/ cm ²)	Result
2412-2462	11~13	13	19.95	1(1.26)	0.0050	1	Pass