



A diagram of a network switch with several labeled ports:

- management**: connected to a terminal.
- console**: connected to a terminal.
- serial DCE**: connected to a serial cable.
- serial DTE**: connected to a serial cable.
- Ethernet**: connected to a network.
- RAM**: memory module.
- Flash**: storage module.
- CPU**: central processing unit.
- Power**: power supply.
- Fan**: cooling fan.
- Temperature sensor**: monitors temperature.
- Voltage sensor**: monitors voltage.
- Current sensor**: monitors current.
- Power button**: power control.
- Reset button**: reset control.
- Test button**: diagnostic control.
- Status LED**: indicator light.
- Activity LED**: activity indicator.
- Error LED**: error indicator.
- Link LED**: link status indicator.
- Speed LED**: speed indicator.
- Duplex LED**: duplex mode indicator.
- Collision LED**: collision indicator.
- Jabber LED**: jabber detection indicator.
- Port LED**: port status indicator.
- Port Activity LED**: port activity indicator.
- Port Error LED**: port error indicator.
- Port Link LED**: port link status indicator.
- Port Speed LED**: port speed indicator.
- Port Duplex LED**: port duplex mode indicator.
- Port Collision LED**: port collision indicator.
- Port Jabber LED**: port jabber detection indicator.

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54




55

56

57

58

59



- [illegible]

FCC Information and Copyright

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules.

These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. The device has been evaluated to meet general RF exposure requirement.

The device can be used in portable exposure condition without restriction.