



Valued Quality. Delivered.

TEST REPORT

Report Number: 14010362HKG-002

Application
for
Original Grant of 47 CFR Part 15 Certification
Single New of RSS-210 Issue 8 Equipment Certification

2.4GHz Audio Baby Monitor - Parent Unit

FCC ID: SMH32116P

IC: 4593A-32116P

Prepared and Checked by:

Approved by:

Signed On File

Jess Tang
Lead Engineer

Digitally signed by Nip
Ming Fung, Melvin
Location: Intertek
Testing Services Hong
Kong Ltd

Nip Ming Fung, Melvin
Assistant Manager
July 31, 2014

- Intertek's standard Terms and Conditions can be obtained at our website: <http://www.intertek.com/terms/>.
- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Hong Kong Ltd.

2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

INTERTEK TESTING SERVICES

GENERAL INFORMATION

Applicant Name:	CIRCUS WORLD DISPLAYS LTD.
Applicant Address:	4080 Montrose Rd, Niagara Falls, Ontario L2H 1J9, Canada.
FCC Specification Standard:	FCC Part 15, October 1, 2012 Edition
FCC ID:	SMH32116P
FCC Model(s):	32116P, AA3180P
IC Specification Standard:	RSS-210 Issue 8, December 2010 RSS-Gen Issue 3, December 2010
IC:	4593A-32116P
IC Model(s):	32116P
Type of EUT:	Transceiver
Description of EUT:	2.4GHz Audio Baby Monitor - Parent Unit
Serial Number:	N/A
Sample Receipt Date:	January 09, 2014
Date of Test:	June 26 - July 3, 2014
Report Date:	July 31, 2014
Environmental Conditions:	Temperature: +10 to 40°C Humidity: 10 to 90%

INTERTEK TESTING SERVICES

Table of Contents

1.0 Test Results Summary & Statement of Compliance	4
1.1 Summary of Test Results	4
1.2 Statement of Compliance	4
2.0 General Description	6
2.1 Product Description	6
2.2 Test Methodology	6
2.3 Test Facility	6
3.0 System Test Configuration	8
3.1 Justification	8
3.2 EUT Exercising Software	9
3.3 Details of EUT and Description of Accessories	10
3.4 Measurement Uncertainty	10
4.0 Test Results	12
4.1 Field Strength Calculation	12
4.2 Radiated Emissions	13
4.2.1 Radiated Emission Configuration Photograph	13
4.2.2 Radiated Emission Data	13
4.2.3 Transmitter Duty Cycle Calculation	18
4.3 Radiated Emission on the Bandedge	20
4.4 AC Power Line Conducted Emission	22
4.4.1 AC Power Line Conducted Emission Configuration Photograph	22
4.4.2 AC Power Line Conducted Emission Data	22
5.0 Equipment List	25

INTERTEK TESTING SERVICES

EXHIBIT 1 TEST RESULTS SUMMARY & STATEMENT OF COMPLIANCE

INTERTEK TESTING SERVICES

1.0 Test Results Summary & Statement of Compliance

1.1 Summary of Test Results

Test Items	FCC Part 15 Section	RSS-210/ RSS-Gen [#]	Results	Details see section
Antenna Requirement	15.203	7.1.2 [#]	Pass	2.1
Radiated Emission Radiated Emission on the Bandedge	15.249(a), 209, & 109 15.249(d)	A2.9(a) A2.9(b)	Pass Pass	4.2 4.3
Radiated Emission in Restricted Bands	15.205	2.2	Pass	4.2
AC Power Line Conducted Emission	15.207 & 15.107	7.2.4 [#]	Pass	4.4

Note: Pursuant to FCC Part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

1.2 Statement of Compliance

The equipment under test is found to be complying with the following standard:

FCC Part 15, October 1, 2012 Edition
RSS-210 Issue 8, December 2010
RSS-Gen Issue 3, December 2010

INTERTEK TESTING SERVICES

EXHIBIT 2 GENERAL DESCRIPTION

INTERTEK TESTING SERVICES

2.0 General Description

2.1 Product Description

The 32116P is a 2.4GHz Audio Baby Monitor - Parent Unit. It operates at frequency range of 2402.784MHz to 2479.680MHz. The Parent Unit is powered by a "Ni-MH" type rechargeable battery pack (2.4V, 600mAh) and/or an adaptor 100-240VAC to 5VDC 600mA.

The antenna used in parent unit is integral, and the test sample is a prototype.

For FCC, the Model(s): AA3180P is the same as the Model: 32116P in electrical designs including software & firmware, PCB layout and construction design/physical design/enclosure. The only differences between these models are model number, color of enclosure and trade name to be sold for marketing purpose.

The circuit description is saved with filename: descri.pdf.

2.2 Test Methodology

Both AC power line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009). Preliminary radiated scans and all radiated measurements were performed in radiated test sites. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

2.3 Test Facility

The radiated test site and conducted measurement facility used to collect the radiated data and conducted data are at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC and the Industry Canada.

INTERTEK TESTING SERVICES

EXHIBIT 3 SYSTEM TEST CONFIGURATION

INTERTEK TESTING SERVICES

3.0 System Test Configuration

3.1 Justification

For radiated emissions testing, the equipment under test (EUT) was setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables (if any) were manipulated to produce worst case emissions.

The Parent Unit was powered by a fully charged battery and/or an AC adaptor.

For the measurements, the EUT was attached to a plastic stand if necessary and placed on the wooden turntable. If the EUT attached to peripherals, they were connected and operational to simulate typical use.

The signal was maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization were varied during the search for maximum signal level. The antenna height was varied from 1 to 4 meters. Radiated emissions were taken at three meters unless the signal level was too low for measurement at that distance. If necessary, a pre-amplifier was used and/or the test was conducted at a closer distance.

For any intentional radiator powered by AC power line, measurements of the radiated signal level of the fundamental frequency component of the emission was performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.

For transmitter radiated measurement, the spectrum analyzer resolution bandwidth was 100 kHz for frequencies below 1000 MHz. The resolution bandwidth was 1 MHz for frequencies above 1000 MHz.

Radiated emission measurement for transmitter was performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

Emission that are directly caused by digital circuits in the transmit path and transmitter portion were measured, and the limit are according to FCC Part 15 Section 15.209. Digital circuitry used to control additional functions other than the operation of the transmitter are subject to FCC Part 15 Section 15.109 Limits.

INTERTEK TESTING SERVICES

3.1 Justification - Cont'd

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 4.2.3.

Determination of pulse desensitization was made according to *Hewlett Packard Application Note 150-2, Spectrum Analysis... Pulsed RF*. The effective period (Teff) was referred to Exhibit 4.2.3. With the resolution bandwidth 1MHz and spectrum analyzer IF bandwidth 3dB, the pulse desensitization factor was 0dB.

For AC line conducted emission test, the EUT along with its peripherals were placed on a 1.0m(W)x1.5m(L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN), which provided 50ohm coupling impedance for measuring instrument. The LISN housing, measuring instrument case, reference ground plane, and vertical ground plane were bounded together. The excess power cable between the EUT and the LISN was bundled.

All connecting cables of EUT and peripherals were manipulated to find the maximum emission.

All relevant operation modes have been tested, and the worst case data was included in this report.

3.2 EUT Exercising Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use.

INTERTEK TESTING SERVICES

3.3 Details of EUT and Description of Accessories

Details of EUT:

A battery (provided with the unit) was used to power the device. Their description are listed below.

- (1) A "Ni-MH" type rechargeable battery (2.4V, 600mAh, Brand: SANIK) (Supplied by Client)
- (2) An AC adaptor (100-240VAC 50/60Hz 150mA to 5.0VDC 600mA, Model: 5E-AD050060-U, Brand: Levana) (Supplied by Client)

Description of Peripherals:

There are no accessories necessary for compliance of this product.

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Uncertainty and Compliance - Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

INTERTEK TESTING SERVICES

EXHIBIT 4 TEST RESULTS

INTERTEK TESTING SERVICES

4.0 Test Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

4.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where FS = Field Strength in dB μ V/m
 RA = Receiver Amplitude (including preamplifier) in dB μ V
 CF = Cable Attenuation Factor in dB
 AF = Antenna Factor in dB
 AG = Amplifier Gain in dB
 PD = Pulse Desensitization in dB
 AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Example

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$AV = -10 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{ dB}\mu\text{V/m}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(32 \text{ dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$$

INTERTEK TESTING SERVICES

4.2 Radiated Emissions

4.2.1 Radiated Emission Configuration Photograph

Worst Case Radiated Emission
at

2402.784 MHz

The worst case radiated emission configuration photographs are attached in the Appendix and saved with filename: config photos.pdf

4.2.2 Radiated Emission Data

The data in tables 1-4 list the significant emission frequencies, the limit and the margin of compliance.

Judgement -

Passed by 3.5 dB margin

INTERTEK TESTING SERVICES

Mode: TX-Channel 02

Table 1

Radiated Emission Data

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	2402.784	114.1	33	29.4	42.1	68.4	94.0	-25.6
H	4805.568	64.6	33	34.9	42.1	24.4	54.0	-29.6
H	7208.352	50.7	33	37.9	42.1	13.5	54.0	-40.5
H	9611.136	56.1	33	40.4	42.1	21.4	54.0	-32.6
H	12013.920	43.1	33	40.5	42.1	8.5	54.0	-45.5
H	14416.704	43.2	33	40.0	42.1	8.1	54.0	-45.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	2402.784	114.1	33	29.4	110.5	114.0	-3.5
H	4805.568	64.6	33	34.9	66.5	74.0	-7.5
H	7208.352	50.7	33	37.9	55.6	74.0	-18.4
H	9611.136	56.1	33	40.4	63.5	74.0	-10.5
H	12013.920	43.1	33	40.5	50.6	74.0	-23.4
H	14416.704	43.2	33	40.0	50.2	74.0	-23.8

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.
 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 Section 2.2.

*

INTERTEK TESTING SERVICES

Mode: TX-Channel 46

Table 2

Radiated Emission Data

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	2440.800	112.6	33	29.4	42.1	66.9	94.0	-27.1
H	4881.600	64.3	33	34.9	42.1	24.1	54.0	-29.9
H	7322.400	50.2	33	37.9	42.1	13.0	54.0	-41.0
H	9763.200	55.7	33	40.4	42.1	21.0	54.0	-33.0
H	12204.000	43.6	33	40.5	42.1	9.0	54.0	-45.0
H	14644.800	45.2	33	38.4	42.1	8.5	54.0	-45.5

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	2440.800	112.6	33	29.4	109.0	114.0	-5.0
H	4881.600	64.3	33	34.9	66.2	74.0	-7.8
H	7322.400	50.2	33	37.9	55.1	74.0	-18.9
H	9763.200	55.7	33	40.4	63.1	74.0	-10.9
H	12204.000	43.6	33	40.5	51.1	74.0	-22.9
H	14644.800	45.2	33	38.4	50.6	74.0	-23.4

- NOTES: 1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna is used for the emission over 1000MHz.
5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 Section 2.2.

INTERTEK TESTING SERVICES

Mode: TX-Channel 91

Table 3

Radiated Emission Data

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	2479.680	111.8	33	29.4	42.1	66.1	94.0	-27.9
H	4959.360	63.5	33	34.9	42.1	23.3	54.0	-30.7
H	7439.040	49.9	33	37.9	42.1	12.7	54.0	-41.3
H	9918.720	55.1	33	40.4	42.1	20.4	54.0	-33.6
H	12398.400	43.8	33	40.5	42.1	9.2	54.0	-44.8
H	14878.080	45.2	33	38.4	42.1	8.5	54.0	-45.5

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	2479.680	111.8	33	29.4	108.2	114.0	-5.8
H	4959.360	63.5	33	34.9	65.4	74.0	-8.6
H	7439.040	49.9	33	37.9	54.8	74.0	-19.2
H	9918.720	55.1	33	40.4	62.5	74.0	-11.5
H	12398.400	43.8	33	40.5	51.3	74.0	-22.7
H	14878.080	45.2	33	38.4	50.6	74.0	-23.4

- NOTES: 1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna is used for the emission over 1000MHz.
5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 Section 2.2.

INTERTEK TESTING SERVICES

Mode: Sound Receiving and Charging

Table 4

Radiated Emission Data

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
V	55.300	38.8	16	11.0	33.8	40.0	-6.2
V	110.600	35.6	16	14.0	33.6	43.5	-9.9
H	165.900	33.9	16	17.0	34.9	43.5	-8.6
H	221.200	33.6	16	17.0	34.6	46.0	-11.4
H	276.500	28.2	16	22.0	34.2	46.0	-11.8
H	331.800	25.6	16	24.0	33.6	46.0	-12.4
H	442.400	23.4	16	26.0	33.4	46.0	-12.6

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205/RSS-210 Section 2.2.

INTERTEK TESTING SERVICES



4.2.3 Transmitter Duty Cycle Calculation

$$\begin{aligned}\text{Duty Cycle (DC)} &= \text{Maximum On time in } 100\text{ms}/100\text{ms} \\ &= 0.780\text{ms}/100\text{ms} \\ &= 0.0078\end{aligned}$$

$$\begin{aligned}\text{Average Factor (AF) in dB} &= 20 \log_{10} (0.0078) \\ &= -42.158 \text{ dB}\end{aligned}$$

INTERTEK TESTING SERVICES

Plot of transmitter ON time
Parent unit Traffic



INTERTEK TESTING SERVICES

4.3 Radiated Emission on the Bandedge

From the following plots, they show that the fundamental emissions are confined in the specified band (2400MHz and 2483.5MHz). In case of emissions up to two standard bandwidths away from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.4 (2009) for frequency being measured.


Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in FCC Part 15 Section 15.209, whichever is the lesser attenuation, which meet the requirement of FCC Part 15 Section 15.249(d) / RSS-210 A2.9(b).

The plots of radiated emission on the bandedge are saved as below.


INTERTEK TESTING SERVICES

Plots of radiated emission on the bandedge

Parent unit, Lowest channel



Parent unit, Highest channel



INTERTEK TESTING SERVICES

4.4 AC Power Line Conducted Emission

- ☐ Not applicable – EUT is only powered by battery for operation.
- ☒ EUT connects to AC power line. Emission Data is listed in following pages.
- ☐ Baby Unit connects to AC power line and has transmission. Parent Unit connects to AC power line but has no transmission. Emission Data of Baby Unit is listed in following pages.

4.4.1 AC Power Line Conducted Emission Configuration Photograph

Worst Case Line-Conducted Configuration

The worst case line conducted configuration photographs are saved with filename: config photos.pdf


4.4.2 AC Power Line Conducted Emission Data

The plot(s) and data in the following pages list the significant emission frequencies, the limit and the margin of compliance

Passed by more than 20 dB margin

INTERTEK TESTING SERVICES

Worst Case: Sound Receiving and Charging



INTERTEK TESTING SERVICES

EXHIBIT 5 EQUIPMENT LIST

INTERTEK TESTING SERVICES

5.0 Equipment List

1) Radiated Emissions Test

Equipment	EMI Test Receiver	Log Periodic Antenna	Biconical Antenna
Registration No.	EW-2251	EW-0446	EW-2512
Manufacturer	R&S	EMCO	EMCO
Model No.	ESCI	3146	3104C
Calibration Date	Nov. 20, 2013	Apr. 30, 2013	Jun. 25, 2013
Calibration Due Date	Nov. 20, 2014	Oct. 30, 2014	Dec. 25, 2014

Equipment	Spectrum Analyzer	Double Ridged Guide Antenna	Spectrum Analyzer
Registration No.	EW-2253	EW-1015	EW-2188
Manufacturer	R&S	EMCO	AGILENTTECH
Model No.	FSP40	3115	E4407B
Calibration Date	May. 8, 2014	Mar. 05, 2013	Apr. 16, 2014
Calibration Due Date	May. 8, 2015	Sep. 05, 2014	Apr. 16, 2015

Equipment	Broad-Band Horn Antenna
Registration No.	EW-1679
Manufacturer	SCHWARZBECK
Model No.	BBHA9170
Calibration Date	Jun. 5, 2014
Calibration Due Date	Jun. 5, 2015

2) Conducted Emissions Test

Equipment	EMI Test Receiver	LISN
Registration No.	EW-2500	EW-2501
Manufacturer	ROHDESCHWARZ	R&S
Model No.	ESCI	ENV-216
Calibration Date	Mar. 22, 2013	Dec. 25, 2013
Calibration Due Date	Aug. 28, 2014	Nov. 30, 2014

END OF TEST REPORT