

1.1. Test Result of RF Exposure Evaluation

- . Product: Wireless Mobile Router
- . Test Item: RF Exposure Evaluation Data
- . Test site: OATSI-SD
- . Test Mode: Normal Operation

1.1.1. Antenna Gain

The maximum Gain is 1.0 dBi.

1.1.2. EUT Operation condition

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

1.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

Modulation Standard: IEEE 802.11b

Test Date: Oct. 24, 2004 Temperature: 24°C Humidity: 63%

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Power Density (S) (mW/cm ²)
01	2412	13.77	0.0060
06	2437	13.22	0.0053
11	2462	13.73	0.0047

Modulation Standard: IEEE 802.11g

Test Date: Oct. 24, 2004 Temperature: 24°C Humidity: 63%

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Power Density (S) (mW/cm ²)
01	2412	13.09	0.0051
06	2437	12.73	0.0047
11	2462	12.19	0.0041

The MPE is calculated as $0.0060 \text{ mW} / \text{cm}^2 < \text{limit } 1 \text{ mW} / \text{cm}^2$. So, RF exposure limit warning or SAR test are not required.