



**FCC 47 CFR PART 15 SUBPART C
INDUSTRY CANADA RSS 210**

CERTIFICATION TEST REPORT

FOR

WINDOW SHADE CONTROLLER

MODEL NUMBER: 206B0000

**FCC ID: SO7-206B0000
IC: 11009A-206B0000**

REPORT NUMBER: 14U19271 REVISION A

ISSUE DATE: DECEMBER 17, 2014

Prepared for
PELLA CORP.
102 MAIN STREET PELLA, IOWA 50219

Prepared by

**UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**

Revision History



NVLAP LAB CODE 200065-0

Rev.	Issue Date	Revisions	Revised By
--	12/8/14	Initial Issue	P. ZHANG
A	12/17/14	Updated page 12 and below 30MHz data	P. ZHANG

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. CALIBRATION AND UNCERTAINTY	5
4.1. MEASURING INSTRUMENT CALIBRATION	5
4.2. SAMPLE CALCULATION	5
4.3. MEASUREMENT UNCERTAINTY	6
5. EQUIPMENT UNDER TEST	7
5.1. DESCRIPTION OF EUT	7
5.2. DESCRIPTION OF AVAILABLE ANTENNAS	7
5.3. SOFTWARE AND FIRMWARE	7
5.4. WORST-CASE CONFIGURATION AND MODE	7
5.5. MODIFICATIONS	7
5.1. DESCRIPTION OF TEST SETUP	8
6. TEST AND MEASUREMENT EQUIPMENT	10
7. ANTENNA PORT TEST RESULTS	11
7.1. 20 dB AND 99% BW	11
7.2. DUTY CYCLE	15
7.3. TRANSMISSION TIME	21
8. RADIATED EMISSION TEST RESULTS	22
8.1. TX RADIATED SPURIOUS EMISSION	22
9. SETUP PHOTOS	30

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: Pella Corp
EUT DESCRIPTION: WIRELESS SENSOR
MODEL: 206B0000
SERIAL NUMBER: 2004808(EUT), 2004809(EUT), 2004810(BATTERY)
DATE TESTED: NOVEMBER 26 - DECEMBER 4, 2014

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 15 SUBPART C	Pass
INDUSTRY CANADA RSS-210 Issue 8, Annex 1	Pass
INDUSTRY CANADA RSS-GEN Issue 4	Pass

UL Verification Services Inc tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.


Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Verification Services Inc By:

Tested By:



PENG ZHANG
PROJECT LEAD
UL Verification Services Inc.



R. ALEGRE
LAB TECHNICIAN
UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15, RSS-GEN Issue 4, and RSS-210 Issue 8.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
☐ Chamber A	☐ Chamber D
☒ Chamber B	☐ Chamber E
☒ Chamber C	☐ Chamber F

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://ts.nist.gov/standards/scopes/2000650.htm>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned}\text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m}\end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	± 3.52 dB
Radiated Disturbance, 30 to 5000 MHz	± 4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a Controller for window shades with wireless transceiver.

5.2. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a monopole antenna, with a maximum gain of -5 dBi.

5.3. SOFTWARE AND FIRMWARE

The typical factory firmware installed in the EUT during testing was ESW1054-01-A01.HEX

The firmware installed in the EUT to allow continuous transmit during testing was ESW1054-01-ConstantTX.HEX

5.4. WORST-CASE CONFIGURATION AND MODE

The EUT was investigated in each of its three orthogonal axes. All radiated testing was performed in the worse-case axis, which was found to be the "X-axis". See photos for details.

5.5. MODIFICATIONS

No modifications were made during testing.

5.1. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

NONE


I/O CABLES

NONE

TEST SETUP

The EUT is a stand-alone device, which operated on a button push.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	Asset	Cal Due
Antenna, Biconolog, 30MHz-1 GHz	Sunol Sciences	JB1	C01171	02/13/15
Antenna, Horn, 18GHz	EMCO	3115	C00783	10/25/15
Antenna, Horn, 25.5 GHz	ARA	MWH-1826/B	C00980	11/14/15
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00580	01/28/15
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01052	10/22/15
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01069	12/20/14
CBT Bluetooth Tester	R & S	CBT	None	07/12/15
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/14
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/14
LISN, 30 MHz	FCC	50/250-25-2	C00626	01/14/15
Reject Filter, 2.4GHz	Micro-Tronics	BRM50702	N02684	CNR
ESA-E Spectrum Analyzer, 9kHz-26.5 GHz	Agilent / HP	E4407B	C01098	04/04/15
Antenna, Loop, 30 MHz	EMCO	6502	C00593	02/20/15

7. ANTENNA PORT TEST RESULTS

7.1. 20 dB AND 99% BW

LIMITS

FCC §15.231 (c)

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

IC A1.1.3

For the purpose of Section A1.1, the 99% Bandwidth shall be no wider than 0.25% of the center frequency for devices operating between 70-900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency.

TEST PROCEDURE

ANSI C63.4

The transmitter output is connected to the spectrum analyzer.

20dB Bandwidth: The RBW is set to 100 KHz. The VBW is set to 300 KHz. The sweep time is coupled. Bandwidth is determined at the points 20 dB down from the modulated carrier.

99% Bandwidth: The RBW is set to 1% to 3% of the 99 % bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

RESULTS

No non-compliance noted:


20dB Bandwidth

Frequency (MHz)	20dB Bandwidth (kHz)	Limit (kHz)	Margin (kHz)
433.9	549	1084.75	-535.75


99% Bandwidth

Frequency (MHz)	99% Bandwidth (kHz)	Limit (kHz)	Margin (kHz)
433.9	800.86	1084.75	-283.89

20dB BANDWIDTH



99% BANDWIDTH



7.2. DUTY CYCLE

LIMITS

FCC §15.35 (c)

The measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value. The exact method of calculating the average field strength shall be submitted with any application for certification or shall be retained in the measurement data file for equipment subject to notification or verification.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer or radiated field strength. The RBW is set to 100 kHz and the VBW is set to 100 kHz. The sweep time is coupled and the span is set to 0 Hz. The number of pulses is measured and calculated in a 100 ms scan.

CALCULATION


Average Reading = Peak Reading (dBuV/m) + 20log (Duty Cycle), Where Duty Cycle is $(\# \text{ of long pulses} * \text{long pulse width}) + (\# \text{ of short pulses} * \text{short pulse width}) / 100$ or T

RESULTS


No non-compliance noted:

One Period (ms)	Long Pulse Width (ms)	# of Long Pulses	Short Width (ms)	# of Short Pulses	Duty Cycle	20*Log Duty Cycle (dB)
100	0.24	12	0.08	41	0.062	-24.21


ONE PERIOD




LONG PULSE WIDTH




NUMBER OF LONG PULSES



SHORT PULSE WIDTH



NUMBER OF SHORT PULSES



7.3. TRANSMISSION TIME

LIMITS

FCC §15.231 (a) (2)

IC A1.1.1 (b)


A transmitter activated automatically shall cease transmission within 5 seconds after activation.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer or radiated field strength. The RBW is set to 100 kHz and the VBW is set to 100 kHz. The sweep time is set to 10 seconds and the span is set to 0 Hz.

RESULTS

No non-compliance noted:



8. RADIATED EMISSION TEST RESULTS

8.1. TX RADIATED SPURIOUS EMISSION

LIMITS

FCC §15.231 (b)

IC A1.1.2

In addition to the provisions of § 15.205, the field strength of emissions from Intentional radiators operated under this section shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental Frequency (microvolts/meter)	Field Strength of Spurious Emissions (microvolts/meter)
40.66 - 40.70	2,250	225
70 - 130	1,250	125
130 - 174	1,250 to 3,7501	125 to 3751
174 - 260	3,750	375
260 - 470	3,750 to 12,5001	375 to 1,2501
Above 470	12,500	1,250

1 Linear interpolation

§15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	(²)
13.36 - 13.41	322 - 335.4		

1 Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.
2 Above 38.6

§15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 88	100 **	3
88 216	150 **	3
216 960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 72 MHz, 76 88 MHz, 174 216 MHz or 470 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.


For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

RESULTS

No non-compliance noted:

FUNDAMENTAL, HARMONICS AND TX SPURIOUS EMISSION (30 – 1000 MHz)



Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	AF T243 (dB/m)	Amp/Cbl (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	55.415	52.14	PK	7.2	-28.5	30.84	40	-9.16	0-360	101	V
2	64.0425	48.59	PK	7.7	-28.4	27.89	40	-12.11	0-360	101	V
3	94.0475	44.69	PK	8.5	-28	25.19	43.52	-18.33	0-360	101	V
4	186.145	39.79	PK	10.9	-27	23.69	43.52	-19.83	0-360	101	H
5	433.9	110.63	PK	16.6	-26	100.23	100.83	-0.6	0-360	200	H
6	867.9	69.56	PK	21.8	-23.3	68.06	80.83	-12.77	0-360	200	H

PK - Peak detector


Radiated Emissions

Frequency (MHz)	Meter Reading (dBuV)	Det	AF T243 (dB/m)	Amp/Cbl (dB)	DC factor	Corrected Reading (dBuV/m)	Pk/AV Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
433.92	111.88	PK	16.6	-26	-	100.23	100.83	-0.6	172	203	H
433.92	105.72	Av	16.6	-26	24.21	76.02	80.83	-4.81	172	203	H
867.857	64.2	Av	21.8	-23.3	24.21	45.38	60.83	-15.45	173	199	H
867.857	71.09	PK	21.8	-23.3	-	69.59	80.83	-11.24	173	199	H

PK - Peak detector

Av - average detection

HARMONICS AND TX SPURIOUS EMISSIONS ABOVE 1GHz



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl (dB)	Corrected Reading (dBuV/m)	Class B Avg Limit (dBuV/m)	Av(CISPR) Margin (dB)	Pk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.302	70.87	PK	28.9	-34.6	65.17	-	-	74	-8.83	0-360	200	H
2	1.736	80.37	PK	29.4	-33.5	76.27	-	-	80.83	-4.56	0-360	200	H
3	2.17	61.45	PK	31.3	-33.2	59.55	-	-	80.83	-21.28	0-360	102	H
4	2.604	51.31	PK	32.5	-32.7	51.11	-	-	80.83	-29.72	0-360	102	H
5	3.038	57.45	PK	32.8	-32.3	57.95	-	-	80.83	-22.88	0-360	200	H
6	3.472	55.5	PK	32.8	-32	56.3	-	-	80.83	-24.53	0-360	102	H
7	4.34	52.53	PK	33.7	-31.3	54.93	-	-	74	-19.07	0-360	200	H
8	4.774	56.4	PK	34.2	-30.9	59.7	-	-	74	-14.3	0-360	102	V

PK - Peak detector

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl (dB)	PK Corrected Reading (dBuV/m)	DC factor	AV Corrected reading (dBuV/m)	Class B Avg Limit (dBuV/m)	Av(CISPR)Margin (dB)	Class B Pk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1.736	80.37	PK	29.4	-33.5	76.27	24.21	52.06	54	-1.94	80.83	-4.56	67	202	H
2.169	61.45	PK	31.3	-33.2	59.55	24.21	35.34	54	-18.66	80.83	-21.28	67	103	H
2.603	51.31	PK	32.5	-32.7	51.11	24.21	26.9	54	-27.1	80.83	-29.72	67	202	H
3.037	57.45	PK	32.8	-32.3	57.95	24.21	33.74	54	-20.26	80.83	-22.88	67	202	H
3.472	55.5	PK	32.8	-32	56.3	24.21	32.09	54	-21.91	80.83	-24.53	67	103	H
4.339	52.53	PK	33.7	-31.3	54.93	24.21	30.72	54	-23.28	74	-19.07	67	199	H

PK - Peak detector

Avg - Video bandwidth < Resolution bandwidth

* Average Reading = Peak Reading (dBuV/m) + 20log (Duty Cycle), Where Duty Cycle is (# of long pulses * long pulse width) + (# of short pulses * short pulse width) / 100 or T

HARMONICS AND TX SPURIOUS EMISSIONS 9KHz to 30MHz

FCC Part 15, Subpart B & C 3 Meter Distance Measurement At Chamber

Company: PELLA
Project #: 14U19271
EUT configuration #: EUT ONLY Cont. TX.
Mode of operation: 9KHz-30MHz
Tester: R. Alegre
Date: 12/3/14

Frequency (MHz)	PK (dBuV)	QP (dBuV)	AV (dBuV)	AF dB/m	Distance (m)	Distance Correction (dB)	PK Corrected Reading (dBuV/m)	AV Corrected Reading (dBuV/m)	PK Limit (dBuV/m)	AV Limit (dBuV/m)	PK Margin (dB)	AV Margin (dB)	Notes
Loop Antenna Face On:													
0.02	68.35		51.27	13.8	3	-80.00	2.15	-14.93	61.58	41.58	-59.4	-56.5	
0.05	64.77		52.66	11.3	3	-80.00	-3.93	-16.04	53.62	33.62	-57.6	-49.7	
0.22	49.75		38.39	10.8	3	-80.00	-19.45	-30.81	40.76	20.76	-60.2	-51.6	
0.78	36.45	27.33		10.61	3	-40.00	-2.06		29.76		-31.8		
6.16	44.9	35.31		10.88	3	-40.00	6.19		29.54		-23.4		
24.26	31.36	23.89		9.333	3	-40.00	-6.78		29.54		-36.3		
Loop Antenna Face Off:													
0.02	66.23		48.8	13.8	3	-80.00	0.03	-17.40	61.58	41.58	-61.6	-59.0	
0.05	62.26		49.94	11.3	3	-80.00	-6.44	-18.76	53.62	33.62	-60.1	-52.4	
0.22	47.41		38.56	10.8	3	-80.00	-21.79	-30.64	40.76	20.76	-62.5	-51.4	
0.78	35.27	26.37		10.61	3	-40.00	-3.02		29.76		-32.8		
6.16	37.86	29.67		10.88	3	-40.00	0.55		29.54		-29.0		
24.26	28.44	21.28		9.333	3	-40.00	-9.39		29.54		-38.9		

* No more emissions were found up to 30MHz

Note: The emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 10000Mhz. Radiated emission limits in these three bands are based on measurements employing an average detector.

P.K. = Peak
Q.P. = Quasi Peak Readings
A.F. = Antenna factor

Below 150kHz => RBW=VBW=200 or 300Hz
Above 150kHz =>RBW=VBW=9 or 10kHz (Average => VBW=10Hz)

Rev. 060314